

ROADIAN HP



> English

1. V-Shaped Directional Center Pattern provides exceptional grip and style on any road surface
2. 5 Pitch Random Variation tread design provides smooth, quiet yet aggressive handling along with stylized appeal
3. Excellent hydro-design provided by the wide and deep traction grooves and blocks
4. Large Shoulder blocks contribute to firm handling and maximum cornering grip

> Spanish

1. Superficie de contacto direccional en forma de V- Mayor control de alto rendimiento para cualquier superficie de carretera
2. 5 Variaciones de sonidos al azar- Optimización del diseño seccional para reducir el ruido patrón
3. Canales direccionales profundos y anchos- Proporciona una alta eficiencia de drenaje y frenado
4. Grades flancos- Maximiza el agarre en curvas

> French

1. Pattern de Surface de contact Directionnelle en Type de V- Amélioration d'une adhésion en haute performance sur n'importe quelle surface de route
2. 5 Variations de Pitch arbitraires- Optimisation de Design en section pour diminuer les bruits de pattern
3. Rainure Directionnelle Profonde et Etendue- Approvisionnement d'un excellent drainage et d'arrêt
4. Blocage de Bord Large- Maximalisation d'adhésion du virage



Inch	Code	Size	Max. Load		Rim		Section Width		Overall Diameter		Tread Depth		SLR.	S/W	UTQG			E Mark	Mud + Snow	Note	Original Equipment	
			lbs	kgs	Measuring	Approved	mm	inch	mm	inch	mm	/32"			Wear	Trac.	Temp.					
24 inch	15354	305/35R 24 XL	112V	2469	1120	11.0	10.0 ~ 11.5	313	12.3	824	32.4	8.7	11/32	389	BS	460	A	A	E	M+S		
	15474	295/35R 24 XL	110V	2337	1060	10.5	10.0 ~ 11.5	301	11.9	816	32.1	8.7	11/32	386	BS	460	A	A	E	M+S		
22 inch	15457	295/30R 22 XL	103V	1929	875	10.5	10.0 ~ 11.0	301	11.9	737	29.0	8.7	11/32	349	BS	460	A	A	E	M+S		
	15464	255/30R 22 XL	95V	1521	690	9.0	8.5 ~ 9.5	260	10.2	713	28.1	8.7	11/32	340	BS	460	A	A	E	M+S		
	15472	285/35R 22 XL	106V	2094	950	10.0	9.5 ~ 11.0	290	11.4	759	29.9	8.7	11/32	358	BS	460	A	A	E	M+S		
	15456	265/35R 22 XL	102V	1874	850	9.5	9.0 ~ 10.5	271	10.7	745	29.3	8.7	11/32	353	BS	460	A	A	E	M+S		
	15460	305/40R 22 XL	114V	2601	1180	11.0	10.0 ~ 11.5	313	12.3	803	31.6	8.7	11/32	375	BS	460	A	A	E	M+S		
	15452	305/45R 22 XL	118V	2910	1320	10.0	9.5 ~ 11.5	303	11.9	833	32.8	8.7	11/32	387	BS	460	A	A	E	M+S		
	15466	285/45R 22 XL	114V	2601	1180	9.5	9.0 ~ 10.5	285	11.2	815	32.1	8.7	11/32	380	BS	460	A	A	E	M+S		
20 inch	15463	295/40R 20	106V	2094	950	10.5	10.0 ~ 11.5	301	11.9	744	29.3	8.7	11/32	347	BS	460	A	A	E	M+S		
	15470	275/40R 20 XL	106V	2094	950	9.5	9.0 ~ 11.0	278	10.9	728	28.7	8.7	11/32	340	BS	460	A	A	E	M+S		
	15459	295/45R 20 XL	114V	2601	1180	10.0	9.5 ~ 11.0	296	11.7	774	30.5	8.7	11/32	358	BS	460	A	A	E	M+S		
	15454	275/45R 20 XL	110V	2337	1060	9.0	8.5 ~ 10.5	273	10.7	756	29.8	8.7	11/32	351	BS	460	A	A	E	M+S		
	15468	265/45R 20 XL	108V	2205	1000	9.0	8.5 ~ 10.0	266	10.5	746	29.4	8.7	11/32	347	BS	460	A	A	E	M+S		
	15473	285/50R 20 XL	116V	2756	1250	9.0	8.0 ~ 10.0	297	11.7	794	31.3	8.7	11/32	366	BS	460	A	A	E	M+S		
	15469	265/50R 20 XL	111V	2403	1090	8.5	7.5 ~ 9.5	277	10.9	774	30.5	8.7	11/32	358	BS	460	A	A	E	M+S		
	15467	255/50R 20 XL	109V	2271	1030	8.0	7.0 ~ 9.0	265	10.4	764	30.1	8.7	11/32	354	BS	460	A	A	E	M+S		
15471	275/55R 20 XL	117V	2833	1285	8.5	7.5 ~ 9.5	284	11.2	810	31.9	8.7	11/32	372	BS	460	A	A	E	M+S			
19 inch	11009	285/45R 19 XL	111V	2403	1090	9.5	9.0 ~ 10.5	285	11.2	739	29.1	8.7	11/32	342	BS	460	A	A	E	M+S		
	11010	255/50R 19 XL	107V	2149	975	8.0	7.0 ~ 9.0	265	10.4	739	29.1	8.7	11/32	342	BS	460	A	A	E	M+S		
18 inch	15558	255/55R 18 XL	109V	2271	1030	8.0	7.0 ~ 9.0	265	10.4	737	29.0	8.7	11/32	338	BS	460	A	A	E	M+S		
	15455	285/60R 18	116V	2756	1250	8.5	8.0 ~ 10.0	292	11.5	799	31.5	8.7	11/32	362	BS	460	A	A	E	M+S		
	15608	265/60R 18	110H	2337	1060	8.0	7.5 ~ 9.5	272	10.7	775	30.5	8.7	11/32	353	BS	460	A	A	E	M+S		
17 inch	11577	275/55R 17	109V	2271	1030	8.5	7.5 ~ 9.5	284	11.2	734	28.9	8.7	11/32	334	BS	460	A	A	E	M+S		
	15453	275/60R 17	110V	2337	1060	8.0	7.5 ~ 9.5	279	11.0	762	30.0	8.7	11/32	345	BS	460	A	A	E	M+S		
	15451	265/60R 17	108V	2205	1000	8.0	7.5 ~ 9.5	272	10.7	750	29.5	8.7	11/32	341	BS	460	A	A	E	M+S		
	11006	255/60R 17	106V	2094	950	7.5	7.0 ~ 9.0	260	10.2	738	29.1	8.7	11/32	336	BS	460	A	A	E	M+S		
	11576	255/65R 17 XL	114H	2601	1180	7.5	7.0 ~ 9.0	260	10.2	764	30.1	8.7	11/32	346	BS	460	A	A	E	M+S		
15465	235/65R 17 XL	108V	2205	1000	7.0	6.5 ~ 8.5	240	9.4	738	29.1	8.7	11/32	336	BS	460	A	A	E	M+S			
16 inch	11004	235/60R 16	100V	1764	800	7.0	6.5 ~ 8.5	240	9.4	688	27.1	8.7	11/32	313	BS	460	A	A	E	M+S		
	11575	215/65R 16 XL	102H	1874	850	6.5	6.0 ~ 7.5	221	8.7	686	27.0	8.7	11/32	312	BS	460	A	A	E	M+S		

※ These data can be changed by the manufacturer without prior notice, and differently applied by regions.