




This is entertainment




**PRODUCT
UPDATE 2019**


Showtec Phantom 100 Spot



You can hear the crowds shouting your name behind the closed curtains. Your hand grasps the microphone more tightly, the adrenaline starts rushing through your veins and despite the heat, you get goose bumps. The giant LED screen behind you shows your name in sparkling colours, larger than life. The band already starts to play the intro to your concert and the line array speakers pump music into the stadium, raising the crowd's anticipation. You start to relax a little bit because you know what will happen next. The theatre spots are programmed to deliver the best show ever and all the lights in the trusses have been aligned to perfection. The light engineer gives the "Go"-sign, the music picks up, lights swing into position, the audience goes wild. You take a deep breath and then the curtains open.

This is entertainment!





**Moving Heads Polar**

Moving Heads Spots	6
Moving Heads Beams	8
Moving Heads Washers	10

Moving Heads Phantom

Moving Heads Spots	12
Moving Heads Washers	16

Light effects

Effect Lights	18
---------------	----

Battery lights

Battery Spots	22
---------------	----

Blinders

Blinders DMX	26
--------------	----

Deco lights

LED Shapes	31
------------	----

Light Bars

Light Bars Indoor	36
-------------------	----

Parcans

Parcan 64	37
-----------	----

Spots

Spots Outdoor	38
---------------	----

Theatre Lights

Profiles	39
Theatre Spots	42

Wall Washers

Washers Outdoor	44
-----------------	----

Light bulbs

LED E27 bulbs	48
---------------	----

Light controllers

LED Controllers	49
-----------------	----

Powerdistribution

240V Connectors	50
-----------------	----

Software controllers

Light controllers	51
DMX gear	52

FX Hardware

Foggers	54
Fazers	56
Confetti machines	57
CO2 Hardware	57
Hazers	58
Fog Liquids	58

Lightstands

Stand Accessories	60
-------------------	----

Textiles

Deco Textiles	60
LED Drapes	61
Pipe & Drape	62

Rigging

Rigging Accessories	63
---------------------	----

**Audio Mixers**

19 Inch Mixers	64
----------------	----

Speakers

Active Series	66
Installation Series	68

Cases

Light Cases LCA	76
-----------------	----

Connectors

XLR Chassis & Connectors	80
--------------------------	----

**LED Screens**

Pixel Screens	82
Installation Screens	84
LED Screen Rigging	85

AV Controllers

AV Gear	86
Signal Converters	87
Signal Converters & Splitters	88
Video Processors	92



Showtec Polar Moving Head Series

When the environment and the conditions are harsh Showtec Polar comes into play and thrives. Polar performs, all the time...



Don't let the weather get in the way of creating an awesome lightshow. Why let rain keep you from putting together an awesome outdoor presentation? Like they say "The show must go on" and with Showtec Polar you can. A range of rugged IP-65 rated moving heads, designed around sturdy housings with great optics, strong LED engines and a wide array of features and effects. The Showtec Polar family presents a Beam with a razor sharp 1.7° angled beam, a Wash with 8 separate controllable RGBW LED modules and a very versatile Hybrid fixture built around a powerful 300W LED engine. Fixtures engineered to deliver no matter what the conditions are. Just bring on the rain and Polar will bring the light.





FEATURES:

- IP65
- Spot, Beam & Wash
- Beam angle: 3-30°
- 5F Circular prism & linear prism

Polar 300 Hybrid

40102 IP-65 Moving Head


The Showtec Polar 300 Hybrid is designed around a 300W LED module and performs perfectly as a beam or spot effect due to the 3° to 30° zoom range. Incorporated in the unit are some exciting features like 8 rotating gobos and 12 static gobos with various effects. Put this in the mix with the double prism effect, from combining the 5f prism with the linear prism and you will have created an awesome effect. As IP65 unit very well equipped for outdoor purposes and versatile applications, controllable via DMX-512, RDM, Art-net and SACN.



Technical information:

Output	
Lux @ 10m:	22750 Lux (3°)
Lux @ 1m:	71250 Lux (30°)
Light Source:	300W module
Beam angle:	3-30°
Electrical:	
Input voltage:	100-240V AC / 50-60Hz
(auto ranging)	
Max. Power consumption:	400W
Control	
On Board:	Display
Control protocol:	DMX-512, Art-net, RDM, SACN
Control personality:	Basic/22ch, Standard/26CH, Extended/30ch
Optical system	
Dimmer:	0-100% (16bit)
Strobe:	0-25Hz
Focus:	Motorized linear focus
Prism:	1x 5F prism with bi-directional rotation, Speed adjustable 1x Linear prism with bi-directional rotation, Speed adjustable, can use superposition
Frost:	1 Frost filter, linear adjustment

Movement	
Pan:	540°
Tilt:	270°
Pan/Tilt resolution:	(8-16 bit)
Gobos & Colours:	
Rotating gobo:	8 Gobos + White, Gobo-flow effect, Gobo shake, Bi-directional rotation
Static gobo:	12 Gobos + White, Gobo-flow effect, Gobo shake
Colours:	CMY wheels, One colour wheel (8 dichroic filters + White, Rainbow-flow effect)
Physical	
Cooling:	Forced Convection
Colour:	Black
Casing:	Flame retardant plastic, Die-cast Aluminum
Data connections:	XLR 5P / RJ-45
Power connections:	Seetronic Input
Dimensions:	416 x 356 x 670 mm
Ambient Temperature:	-20°C ~ 45°C
IP Rated:	IP65
Weight:	34.6 kg
Certification & Safety:	
Certification:	CE, MET





FEATURES:

- IP65
- 100W Module
- Beam angle 1.7°
- 5F prism & linear prism

Polar 100 Beam

40100 IP-65 Moving Head

If you combine a razor-sharp 1.7° angled beam, extremely fast and precise X/Y movements and a strong 100W LED Module together with an IP65 rated housing, rotating gobos, dichroic filters and a speed adjustable prism, then you will have the perfect setting for the Showtec Polar 100 Beam moving head. A compact and light weight yet powerful moving head, capable of delivering 170000 lux@ 5m. Very well suited as showstopper for small to medium events and a perfect addition to larger setups to add just that little bit extra to the show.



Technical information:

Output Lux @ 5m: 170000 Lux
 Light Source: 100W module
 Angle: 1.7°

Electrical Input voltage: 100-240V AC / 50-60Hz (auto ranging)
 Max. Power consumption: 180W

Control On Board: Display
 Control protocol: DMX-512, Art-net, RDM
 Control personality: Basic/13ch, Standard/16CH, Extended/19ch

Optical system Dimmer: 0-100% (16bit)
 Strobe: 0-25Hz
 Focus: Motorized linear focus
 Prism: 1x 5F prism with bi-directional rotation, Speed adjustable
 1x Linear prism with bi-directional rotation, Speed adjustable

Movement Pan: 540°
 Tilt: 270°
 Pan/Tilt resolution: (8-16 bit)


Special: Pan/Tilt movement black out, user selectable pan/tilt ranges

Gobos & Colours: Colours: One colour wheel (9 dichroic-filters + White, Rainbow-flow effect)
 Rotating Gobo: 8 Gobos + White, Gobo-flow effect, Gobo shake, Bidirectional rotation

Physical Cooling: Natural Radiation
 Colour: Black
 Casing: Flame retardant plastic, Die-cast Aluminum

Data connections: XLR 5P / RJ-45
 Power connections: Seetronic In/Output
 Dimensions: 410 x 280 x 483 mm
 Ambient Temperature: -20°C ~ 45°C
 IP Rated: IP65
 Weight: 19.52 kg

Certification & Safety: CE, MET



8 Circular Prism

5 Linear Prism





FEATURES:

- IP65
- Multiple high power LED sources
- HSIC / RGBW / CMY mode
- Wide zoom range 4.5 - 35°

Polar 340 WashFX



40101 IP-65 Moving Head


The Showtec Polar Wash FX is an innovative and versatile IP65 Wash moving head. Equipped with 7x40W RGBW LED modules and one 60W RGBW LED module offering individual pixel control. Finishing touch and additional feature is a separate LED-ring which can create awesome effects. This gives you the freedom to design awesome visuals through DMX-512, RDM, Art-net or SACN. With a zoom-range of 4.5° to 35° and a choice of various colour mixing modes like HSIC, RGBW or CMY the Showtec Polar Wash FX delivers every time. Compact in size and light weight but it will make sure that its effect cannot be ignored. The Showtec Polar 340 Wash FX will fit perfectly into any rental fleet, is ideal for mobile applications or for outdoor use at festivals or amusement parks.

Technical information:

Output		Led group:	RGB colour light, can present the circular arrangement, flowing water, chasing, Single point control effect
Lux @ 1m:	300000lux (4.5°)	Movement	
Lux @ 1m:	15000lux (35°)	Pan:	540°
Light Source:	7x40W(RGBW) + 1x60W(RGBW)	Tilt:	270°
Beam Angle:	4.5 - 35°	Pan/Tilt resolution:	(8-16 bit)
Electrical		Special:	Pan/Tilt movement black out, user selectable pan/tilt ranges
Input voltage:	100-240V AC / 50-60Hz (auto ranging)	Physical	
Max. Power consumption:	350W	Cooling:	Forced convection
Control		Colour:	Black
On Board:	Display	Casing:	Die-cast Aluminum
Control protocol:	DMX-512, Art-net, RDM, SACN	Data connections:	XLR 5P / RJ-45
Control personality:	HSIC(13ch), CMY(15CH), Person1(22ch), Person2(29ch), Pixel(45CH)	Power connections:	Seetronic Input
Optical system		Dimensions:	416 x 356 x 488 mm
Dimmer:	0-100% (16bit)	Ambient Temperature:	-20°C ~ 45°C
Strobe:	0-25Hz	IP Rated:	IP65
Zoom range:	4.5 - 35°	Weight:	22.84 kg
Prism:	8F prism with bi-directional rotation, Speed adjustable	Certification and safety	
		Certification:	CE, MET







FEATURES:

- 7 Bi-Rotating gobo's & 8 colours
- Pro Power In- & Output
- Gobo shake, gobo rotate and 3-facet prism
- Quick Lock Brackets



Phantom 65 Spot

40071 White

The Showtec Phantom 65 Spot is a very compact multifunctional moving light, specially designed for use on small to mid-sized stages, for DJs and entertainers.

It is the ultimate successor to the Phantom Spot 50 and next to its stylish looks, it is just packed with great features.

Full 65W white LED light output, 1 glass + 6 metal gobos, with gobo-flow and shake, 8 dichroic-filters + white enabling split colours and rainbow-flow effects, a 3-facet prism and great new optics with adjustable manual focus are all on board. It is just hard to believe that this compact fixture can carry all these features!

Thanks to its size and weight of only 6kg, this moving head can be mounted in any position with just one clamp. Also, Pro Power and DMX in- and output allow for easy daisy-chaining of the Phantom 65 spot.

The Showtec Phantom series, a household name in the entertainment lighting industry, is a range of very reliable fixtures with low power consumption and high performance. Taking into account today's lighting demands, this series offers a range of modern fixtures such as Spot, Wash, Beam, Matrix FX, and Hybrid.

Razor sharp beams, colourful matrix effects or spectacular gobo imagery, a Showtec Phantom will, just as any true superhero, never disappoint you.

Technical information:

Output		Special:	Pan / Tilt movement blackout, User-selectable Pan & Tilt ranges, 540°/360°/180°, Reverse Pan / Tilt movement
Beam Angle:	16°		
Light Source:	1 x 65W White LED		
Lux @ 5m:	1870		
Electrical		Gobos & Colours	
Input voltage:	100~240VAC, 50/60Hz (auto ranging)	Gobo:	1 glass + 6 metal gobos
Power consumption:	180W max. at full output	Gobo functions:	Gobo-flow effect, Gobo shake
Control		Rotation:	Bi-directional
On-Board:	Full colour display	Colours:	8 dichroic-filters + white
Control Protocol:	DMX512, Auto, Sound, Manual, Master-Slave	Colour functions:	Split colours, Rainbow-flow effect
Control Personality:	Advanced 13ch /Basic 8ch	Physical	
Optical system		Colour:	White
Dimmer:	0-100%	Housing:	Metal & Flame-retardant plastic
Strobe:	0-20Hz	Data Connection:	XLR 3p in- & output
Focus:	Manual focus	Power connection:	Pro Power in- & output
Prism:	3-facet prism	Dimensions (WxDxH):	238 x 202 x 357 mm
Movement		Weight:	6Kg
Pan:	540°	Certification and Safety	
Tilt:	270°	Certification:	CE
Pan/Tilt resolution:	16 bit	Max. ambient Temp.:	40°C



FEATURES:

- Optional WDMX
- 7 colours + white
- 8-facet circular & 5- facet linear prism
- Motorized zoom and focus



Phantom 130 Spot

40073 White

The Showtec Phantom 130 LED Spot is a medium sized, but very powerful moving head, suitable for a variety of venues and applications.

This stylishly designed fixture contains a 130 watt white LED light-source, providing an extremely high light output. Fixed and rotating gobo wheels (7 gobos each), seven dichroic-filters + white, the colour wheel and circular and rotating prisms, are all on board. Together with the motorized focus and mechanical zoom, this makes a highly versatile moving head.

Like all Phantom fixtures, this spot can be controlled by DMX512 but is also capable of operating in stand-alone mode (Auto, Sound and Manual).

Compact, lightweight and versatile; the Phantom 130 LED Spot definitely is a sensible choice for your entertainment lighting needs.

The Showtec Phantom series, a household name in the entertainment lighting industry, is a range of very reliable fixtures with low power consumption and high performance. Taking into account today's lighting demands, this series offers a range of modern fixtures such as Spot, Wash, Beam, Matrix FX, and Hybrid.

Razor sharp beams, colourful matrix effects or spectacular gobo imagery, a Showtec Phantom will, just as any true superhero, never disappoint you.

Technical information:

Output
Lux @ 5m: 5200 (12°)
Beam Angle: 12° - 21°
Light Source: 130W White LED

Electrical
Input voltage: 100-240VAC, 50/60Hz (auto ranging)
Power consumption: 300W max.

Control
On-Board: Full colour display
Control Protocol: DMX512, Auto, Sound, Manual, Master-Slave
Control Personality: Advanced 16ch /Basic 12ch

Optical system
Dimmer: 0-100%
Strobe: 0-20Hz
Focus: Motorized
Zoom: Motorized
Prism: 6-facet circular & 5- facet linear prism rotating prism

Movement
Pan: 540°
Tilt: 270°
Pan/Tilt resolution: 16 bit


Special: Pan / Tilt movement
blackout, User-selectable
Pan & Tilt ranges,
540°/360°/180°, Reverse
Pan / Tilt movement

Gobos & Colours
Fixed Gobowheel: 7 gobos
Rotating Gobowheel: 7 gobos
Gobo functions: Gobo-flow effect, Gobo shake
Rotation: Bi-directional
Colourwheel: 7 dichroic-filters + white
Colour functions: Split colours, Rainbow-flow effect

Physical
Colour: White
Housing: Metal & Flame-retardant plastic

Data Connection: XLR 3p in- & output
Power connection: Pro Power in- & output
Dimensions (WxDxH): 321 x 211 x 462 mm
Weight: 13Kg

Certification and Safety
Certification: CE
Max. ambient Temp.: 40°C



Phantom 100 Spot

40077 Black


As addition to the successful Phantom Range, Showtec presents the Phantom 100. A compact, yet powerful moving head with all the features from its smaller brother the Phantom 65 and some additional features. For instance, the Showtec Phantom 100 packs a 100W white LED engine, is equipped with a 3-facet circular & 5-facet linear, rotating prism and with a manually controllable beam angle of 12°-17° you can create the beam you like.



FEATURES:

- 7 Bi-Rotating gobo's & 8 colours
- Pro Power In- & Output
- Dual rotating overlaying prisms
- Quick Lock Brackets

6 Circular Prism



5 Linear Prism



Technical information:

Output	Lux @ 5m: 5500 (12°)	Special:	Pan / Tilt movement blackout, User-selectable Pan & Tilt ranges, 540°/360°/180°, Reverse Pan / Tilt movement
Beam Angle:	12°-17° (manual)		
Light Source:	100W White LED		
Electrical		Gobos & Colours	7 gobos
Input voltage:	100-240VAC, 50/60Hz (auto ranging)	Rotating Gobowheel:	7 gobos
Power consumption:	240W max.	Gobo functions:	Gobo-flow effect, Gobo shake
Control		Rotation:	Bi-directional
On-Board:	Full colour display	Colourwheel:	8 dichroic-filters + white
Control Protocol:	DMX512, Auto, Sound, Manual, Master-Slave	Colour functions:	Split colours, Rainbow-flow effect
Control Personality:	Advanced 14ch / Basic 10ch	Physical	
Optical system		Colour:	Black
Dimmer:	0-100%	Housing:	Metal & Flame-retardant plastic
Strobe:	0-20Hz	Data Connection:	XLR 3p in- & output
Focus:	Motorized	Power connection:	Pro Power in- & output
Prism:	3-facet circular & 5-facet linear, rotating prism	Dimensions (WxDxH):	320 x 211 x 422 mm
Movement		Weight:	10Kg
Pan:	540°	Certification and Safety	
Tilt:	270°	Certification:	CE
Pan/Tilt resolution:	16 bit	Max. ambient Temp.:	40°C







FEATURES:

- 4 Section control
- Pro Power In- & Output
- Very fast movement
- Quick Lock Brackets



Phantom 180 Wash





40031 Black

The Showtec Phantom 180 Wash is an RGBW wash moving head with motorized zoom, 7°-50°. It is equipped with 12 powerful 15W RGBW LEDs, divided into 4 separate controllable sections. Dimmable from 0% to 100% and with strobe function onboard from 0 to 20Hz. Pan & tilt movements are precise and very quick and offer various programmable modes. The 6-facet circular & 5-facet linear and rotating prism offer various visual possibilities.



Technical information:

Output		
Lux @ 3m:	14200 (7°)	Movement
Beam Angle:	7°-50° (motorized)	Pan:
Light Source:	12 x 15W RGBW LED's	Tilt:
		Pan/Tilt resolution:
		Special:
Electrical		User-selectable Pan & Tilt ranges, 540°/360°/180°, Reverse Pan / Tilt movement
Input voltage:	100~240VAC, 50/60Hz (auto ranging)	Physical
Power consumption:	220W max.	Colour:
		Housing:
Control		Data Connection:
On-Board:	Full colour display	Power connection:
Control Protocol:	DMX512, Auto, Sound, Manual, Master-Slave	Dimensions (WxDxH):
Control Personality:	Advanced 29ch /Basic 14ch	Weight:
		Certification and Safety
Optical system		Certification:
Dimmer:	0-100%	Max. ambient Temp.:
Strobe:	0-20Hz	
Zoom:	Motorized	





Club Par Dizzy 3/8

42653 4-in-1 multi effect



The Showtec Club Par range has a new member. The Showtec Club Par Dizzy 3/8, a compact but fully packed 4-in-1 multi effect fixture. It produces an RGB wash effect, can generate a UV effect, packs various LED patterns and even presents an awesome strobe. All this comes from 27pcs 0.5W cool white LEDs, 3pcs 8W 4-in-1 RGB+UV LEDs and 18pcs 0.5W RGB LEDs. The various LEDs have been integrated into the fixture in sections. The big advantage of the Showtec Club Par 3/8 is that each section can be controlled and programmed separately. This little effect giant is not only controllable via the already included IR remote but has 5 different control modes and various built-in programs. Looking for a setup with more units is no issue at all. Power linking is possible up to 16 units and daisy-chaining the DMX channel via the 3P XLR connectors is also a breeze. Another advantage is the double adjustable bracket which can be used as a floorstand. The Showtec Club Par Dizzy 3/8 is fully equipped to get the party started and is ideal for deejays and small events.

Technical information:

Electrical		Beam Angle:	22°
Power input:	100-240V 50/60Hz	Physical	
Power linking:	Up to 16 Units	Dimensions:	264 x 214 x 76,9 mm
Power consumption:	65W	Weight:	1,1 Kg
LED Source	3 x 8W 4-in-1 RGB+UV LED's 27 x 0,5W Cool White SMD LED's 18 x 0,5W RGB SMD LED's	Housing:	Plastic
Output:	1118 lux @ 2m	Colour:	Black
Control		Data Connector:	3 pole XLR (In/Out)
Control mode:	Auto, Sound, Master/Slave, DMX 512	Power Connection:	IEC in- & output
DMX Channels:	3,9	Cooling:	Fan Cooled
Control Display:	4 Digits LED	Certification and Safety	
Optical system		Certification:	CE
Dimmer:	0-100%	Max. ambient Temp.:	40°C
Strobe:	0-20Hz		

FEATURES:

- RGB Wash
- UV Blacklight
- 10 Section Strobe Ring
- 6 Section RGB Patterns
- IR Remote included



DreamWave

43166 Effect light

If you are looking for a light effect which has the WOW-factor! and can blow you away with its effects and possibilities then your search is now officially over. Put 6 powerful 15W quad colour LED modules in a cool housing and the Showtec DreamWave is born. The Showtec DreamWave delivers dynamic, stunning fire projections or cool water visuals and anything in between, which makes it truly a versatile unit. But just as easily you can use it as moodlight by creating dreamlike sceneries through DMX. Use it stand-alone or as music controlled unit to give your event just that little bit extra, to give it that WOW-factor. Just plug it in and get the party started.

Technical information:

General:	
Power input	100-240V – 50/60Hz
Power consumption:	70W
Control:	DMX, Master/Slave, Sound Active
DMX Channels:	10, 34
Control display:	4 digits LED
Power connections:	IEC Input
Data connector:	3 pole XLR (in/out)
Dimensions:	246 x 185 x 246
Weight:	3,5kg
LED Beams:	
Colours:	RGBW
Power:	6x 15W
System:	4-in-1
Beam angle:	34 – 90 degrees

FEATURES:

- Colour & LED Control
- Stunning built-in light shows
- DMX Control
- Wide beam-angle



DreamMoon

43167 Effect light

The DreamMoon is a dynamic and highly decorative effect light. It can be used both as a background effect or beam effect. Due to the highly reflective and optical advanced mirror dish the DreamMoon produces crisp, vivid colours and beams at your gig. The DreamMoon has 1 glass pattern pre-mounted. A further 3 glass patterns are included and can be easily exchanged in order to customize your DreamMoon and create your desired effect.

Technical information:

General:
 Powerinput: 100-240V – 50/60Hz
 Power consumption: 68W
 Control: Auto, DMX, Master/Slave, Sound Active
 DMX Channels: 5, 9
 Control display: 4 digits LED
 Power connections: IEC Input
 Data connector: 3 pole XLR (in/out)
 Dimensions: 271 x 200 x 292mm
 Weight: 3,6kg

LED Beams:
 Colours: RGBW
 Power: 1x 60W
 System: 4-in-1



FEATURES:

- Wide Beam angle
- Excellent built-in light shows
- DMX Control
- Multipurpose effect







MULTI
EFFECT

1 x 60W
LED

RGBW


METAL
HOUSING





FEATURES:

- 100W White LED module
- 8 Colour wheel
- 7 (Rotating) Gobo wheel
- 3F Prism
- Motorized focus



Shark Scan One

45025 100W White LED

The Showtec Shark Series consists of compact but powerful effect fixtures. And the latest addition, the Showtec Shark Scan One is no exception to this rule. It is a stylish and compact Scanner with a high power 100W white LED source. It has the complete look and feel of a retro scanner but packs a lot of easy-to-use features. An 8 colour wheel, strobe function, 3F Prism and rotating gobo wheel combined with motorized focus can be used to create stunning effects. All functions are controllable by DMX but it is also possible to run stand-alone or sound-to-light programs, therefore the ideal scanner for small to medium events.




Technical information:

Output:	Light Source:	100W white LED module	Movement:	
Angle:	Angle:	18°	Pan:	160°
			Tilt:	50°
Electrical:	Input voltage:	100-240V AC / 50-60Hz (auto ranging)	Gobos & Colours:	
Max. Power consumption:		116W	Colours:	Colour wheel (8 colour + White, Rainbow-flow effect)
Control:	On Board:	0-LED Display	Gobo:	7 Gobos + Open, Rotation, Gobo-shake, Gobo-scroll
Control protocol:	Control protocol:	DMX, Auto, Sound, Master/Slave	Physical:	
Control personality:	Control personality:	8CH / 14CH	Cooling:	Forced convection
Optical system:	Dimmer:	0-100% (linear dimmer)	Colour:	Black
Strobe:	Strobe:	0-25Hz	Data connections:	In/Out (XLR 3P)
Focus:	Focus:	Motorized focus	Power connections:	ProPower In- & Output
Prism:	Prism:	1x 3F prism	Dimensions:	253 x 158 x 380 mm
			Ambient Temperature:	-5°C ~ 40°C
			IP Rated:	IP20
			Weight:	6.2Kg



FEATURES:

- 100W White LED module
- 8 Colour wheel
- 7 (Rotating) Gobo wheel
- 3F Prism
- Motorized focus



Technical information:

Output:		Movement:	
Light Source:	100W white LED module	Pan:	160°
Angle:	18°	Barrel Rotation:	360°
Electrical:		Gobos & Colours:	
Input voltage:	100-240V AC / 50-60Hz	Colours:	Colour wheel (8 colour + White, Rainbow-flow effect)
Max. Power consumption:	125W	Rotating Gobo:	7 Gobos + Open, Rotation, Gobo-shake, Gobo-flow scroll
Control:		Physical:	
On Board:	0-LED Display	Cooling:	Forced convection
Control protocol:	DMX, Auto, Sound, Master/Slave	Colour:	Black
Control personality:	8CH / 14CH	Data connections:	In/Out (XLR 3P)
Optical system:		Power connections:	In/Out (ProPower)
Dimmer:	0-100% (linear dimmer)	Dimensions:	253 x 158 x 430 mm
Strobe:	0-25Hz	Ambient Temperature:	-5°C ~ 40°C
Focus:	Motorized focus	IP Rated:	IP20
Prism:	1x 3F prism	Weight:	6.6kg

Shark Barrel 90
45026 100W White LED

The Showtec Shark Series presents a new member of the family: the Showtec Shark Barrel 90. Together with the Shark Scan One they truly deliver a "Blast from the past"-feeling due to the retro barrel-effect. But don't let its size fool you. A high power 100W white LED source delivers a great output and the various features onboard turn the Barrel 90 into a versatile fixture. The 8 colour wheel, strobe function, 3F Prism and rotating gobo wheel combined with motorized focus can be used to create stunning effects. Controlling the unit is possible through DMX but also as stand-alone or sound-to-light programs. For small to medium events and mobile applications very well equipped.





EventSpot 1600 Q4

44050 4x 12W RGBW, Black

44051 4x 12W RGBW, Brushed Aluminium

The Eventspot 1600 Q4 is an extremely compact and rugged event lighting fixture with lithium ion battery and original Wireless Solutions Sweden built-in. It is equipped with 4x 12W RGBW combined with dedicated high class optics ensuring a bright and well-defined 10° beam. Separate chargers or charger cases are available as options to fit your desired solution. The battery has a lifetime of up to 15hrs at RGBW. The projection angle of the fixture can be adjusted and optional beamshapers are available to create desired beam angles. With the IP-54 rating this LED battery light is the right choice for professional rental use. A very useful feature is the "Working time". With this feature you can specify the actual working timeframe of the unit from 1 to 15hrs max. The Eventspot will then automatically divide the current capacity of the battery to make sure that the unit will work the length of the specified time. This feature comes in very handy when there is no opportunity to charge the battery but operating it is still required.

Technical information:

Output:		Battery:	
Luminus flux:	1580	Type:	Lithium ion
Lux @2m:	15000	Voltage:	18,5
		Storage:	15.6 Ah
Light Source:		Battery life time:	Up to 15hrs RGBW
LED System:	4 x 12W RGBW LED	Charging Cycle:	6hrs
Drive Current:	650mA		
Refresh rate:	12KHz	Physical:	
		Dimensions:	180 x 180x 280 mm
Control:		Weight:	5 kg
Control Mode:	WDMX, DMX512, Stand-alone, Manual, Master/slave	Housing:	Aluminum and Iron
		Colour:	Black
DMX channels:	4,6,10	Data Connectors:	XLR 3pole
		Cooling:	Aluminum heat sink
Optical system:		Certification and Safety:	
Dimmer:	0-100%	Certification:	CE
Strobe:	0-15Hz	IP:	54
Beam Angle:	10°	Operation Temperature:	-10°C ~40°C



- FEATURES:**
- 4x 12W RGBW colourmixing
 - Long battery life (up to 15hrs RGBW)
 - IP-54 For outdoor use
 - Wireless DMX by Wireless Solutions Sweden
 - Capacity saving "Working time" feature

Charger for EventSpot 1600 Q4

44052

Desktop quick charger for Eventspot 1600. Easy wireless 'drop' connection for fast changing fixtures. With LED charging indicator and powerCON in- and output.

Technical information:

Input Voltage:	100-240V AC 50/60Hz
Max. Power:	75W
Output:	24V, 3A
Dimensions:	220 x 220 x 75 mm
Weight:	2 Kg



Beamshaper for EventSpot 1600 Q4

44053 40°

Dedicated Eventspot 1600 Q4 filter to change the output beam angle to 40°.

44054 15° x 60°

Dedicated Eventspot 1600 Q4 filter to change the output beam angle to 15°x60°

44055 20°

Dedicated Eventspot 1600 Q4 filter to change the output beam angle to 20°.



Charger Case for EventSpot 1600 Q4

D7300 Flightcase for 6 pcs

The Charger Case for the EventSpot 1600 Q4 holds up to 6 pieces of the EventSpot 1600 Q4. It has a built-in charger which makes it very easy to load your Eventspots without the need of taking them out of the flight case. Just plug the case by the Neutrik Powercon connector to the socket and all 6 EventSpots start loading. Built-in safety features for overheating ensures safety at all times.

Equipment not included.

Technical information:

Specifications Flightcase
 Dimensions: 653 x 576 x 500 mm
 Weight: 45,0 Kg (without spots)
 (power cable not included)

FEATURES:

- Roadproof design
- Built-in charger
- Powercon input for charger connection
- Including 4 Blue wheels, swivel plus brake
- Built-in safety-switch to prevent overheat during loading
- Holds up to 6 EventSpot 1600 Q4



EventSpot 1600 Q4 Set

44056 Charger case with 6pcs Black

44057 Charger case with 6pcs Brushed Aluminium

Technical information:

Specifications Flightcase
 Dimensions: 653 x 576 x 500 mm
 Weight: 75,0 Kg (incl spots)
 (power cable included)

Specifications Eventspot

Output:
 Luminous flux: 1580
 Lux @2m: 15000

Light Source:
 LED System: 4 x 12W RGBW LED
 Drive Current: 650mA
 Refresh rate: 12KHz

Control:
 Control Mode: WDMX, DMX512, Stand-alone, Manual, Master/slave
 DMX channels: 4,6,10

Optical system:
 Dimmer: 0-100%
 Strobe: 0-15Hz
 Beam Angle: 10°
 Battery Type: Lithium ion
 Voltage: 18,5
 Storage: 15.6 Ah
 Battery life time: Up to 15hrs RGBW
 Charging Cycle: 6hrs

Physical:
 Dimensions: 180 x 180x 280 mm
 Weight: 5 kg
 Housing: Aluminum and Iron
 Colour: Black
 Data Connectors: XLR 3pole
 Cooling: Aluminum heat sink

Certification and Safety:
 Certification: CE
 IP: 54
 Operation Temperature: -10°C ~40°C

FEATURES:

- Roadproof design
- Built-in charger
- 4x 12W RGBW colourmixing
- Long battery life (up to 15hrs RGBW)
- Built-in safety-switch to prevent overheat during loading





EventLITE 4/10 Q4

44060 incl. Wireless DMX, Black

The Showtec EventLITE 4/10 is a battery powered RGBW spot with wireless DMX in a sturdy aluminum housing.

Due to its built-in battery and Wireless DMX module (from Wireless Solutions) you do not need any cables. It is equipped with a built-in charger system and the battery will last at least 12 hours on a single colour when it is fully charged. The spot can be tilted 25° which is useful to uplight a wall. The EventLITE 4/10 is compact, easy in transportation and lightweight. It includes automated and sound activated programs, can be daisy –chained in master-slave mode (wired dmx), and can be customized manually, by optional IR-remote controller or (wireless) DMX.

Technical information:

Light Source:	4 x 10W RGBW LED	on a single colour	
LED System:		Charging Cycle:	10 hrs (LED Charging indicator)
Optical system:		Physical:	
Dimmer:	0-100%	Dimensions:	140 x 140 x 210 mm
Strobe:	0-15Hz	Weight:	3,5 Kg
Beam angle:	15°	Housing:	Metal
Electrical:		Security:	Kensington Lock eye
Input Voltage:	100~240 VAC...50/60Hz	Colour:	Black
Max. Power:	45W	Power Connectors:	IEC input
Operation mode:	OLED display	Data Connectors:	XLR 3p
Control feature:	WDMX, DMX512, Stand-alone, Manual, Master/slave	Cooling:	Aluminum heatsink
DMX channels:	4, 6, 9 Channels	Certification and Safety:	
Battery:		Certification:	CE
Type:	Lithium ion	IP Rating:	IP54 top/ IP20 bottom
Storage:	4,16 Ah	Max. ambient Temp.:	40°C
Runtime:	up to 6hrs RGBW / 12 hrs	Operation Temperature:	-10°C ~40°C



FEATURES:

- Long battery life (up to 6hrs RGBW)
- RGBW 4-in-1 LEDs
- Wireless DMX by Wireless Solutions Sweden
- Eco mode for extended battery life
- Controllable by optional IR-remote



Carrying Bag for 4 pcs EventLITE 4/10 Q4

44063

Technical information:

High quality soft carrying bag suitable for 4pcs EventLITE 4/10 Q4. The inside partition is removable and the bag has a side pocket for accessories.

IR Remote for EventLITE 4/10 Q4

44062



Chargercase for 6x EventLITE 4/10 Q4

44064 Compact flightcase

Dedicated chargercase for 6 units Showtec EventLITE 4/10 Q4

Equipment not included.

Technical information:

Case:
 Dimensions: 600 x 450 x 490 mm (LxBxH) including wheels
 Power consumption: 150W

FEATURES:

- Pre-wired for charging the fixtures inside the case
- Durable Compact Flightcase
- Stacking recesses on top
- Includes power cord for power supply at the case



EventLITE 4/10 Q4 Set

44061 Flightcase incl 6 pcs EventLITE

Technical information:

Light Source
 LED System: 4 x 10W RGBW LED

Optical system
 Dimmer: 0-100%
 Strobe: 0-15Hz
 Beam angle: 15°

Electrical
 Input Voltage: 100~240 VAC...50/60Hz
 Max. Power: 45W
 Operation mode: OLED display
 Control feature: WDMX, DMX512, Stand-alone, Manual, Master/slave
 DMX channels: 4, 6, 11 Channels

Battery:
 Type: Lithium ion
 Storage: 4,16 Ah
 Runtime: 5 hrs at full RGBW on / 12 hrs on a single colour
 Charging Cycle: 10 hrs (LED Charging indicator)

Physical
 Dimensions: 140 x 140 x 210 mm
 Weight: 3,5 Kg
 Housing: Metal
 Security: Kensington Lock eye
 Colour: Black
 Power Connectors: IEC input
 Data Connectors: XLR 3p
 Cooling: Aluminum heatsink

Certification and Safety
 Certification: CE
 IP Rating: IP20
 Max. ambient Temp.: 40°C
 Operation Temperature: -10°C ~40°C

Case
 Dimensions: 600 x 450 x 490 mm (LxBxH) including wheels
 Power consumption: 150W

FEATURES:

- Flightcase + 6x EventLITE + Ir Remote
- Pre-wired for charging the fixtures inside the case
- Stacking recesses on top
- Including power cord



Sunstrip LED**30752 With Tungsten Simulation**


The Showtec Sunstrip LED is the successor of the already popular Sunstrip Active. The Sunstrip LED has five DMX modes: 1, 2, 3, 10 and 20 channel. Next to DMX it can be controlled in Manual, Auto or Master / Slave Mode. The DMX 3 & 5 pole and Powercon in/output make the Sunstrip LED easy to daisy-chain in every setup. Through the Tungsten mode the Sunstrip LED works like conventional bulbs while there is still an option to operate them in Warm white, Cool white or a combination of both. The Sunstrip LED is equipped with two Wall/Floor brackets in order to put your Sunstrip in any desired position.

**Technical information:**

Power Input:	230V 50Hz
Power Consumption:	145W
Fuse:	2A
Light Source:	10 x 14W (Warm / Cool Prolight Opto)
Control:	DMX, Manual, Auto, Master/Slave
DMX Channels:	1,2,3,10, 20 Channel
Control Display:	OLED Display
Power Connector:	Powercon in- & output
Data Connector:	XLR In/Out (3 & 5 Pin)
Dimensions:	1000 x 140 x 77 mm
Weight:	7 Kg
Accessories:	Mounting / Floor brackets (included)

FEATURES:

- Tungsten, Warm, Cool Dimmer mode
- Low Power Consumption
- Pixel Invert function
- Including Mounting Brackets



LED Par 64 Aircraft DMX**30745** 4° Beam Angle


The LED Par 64 Aircraft brings an old school effect back to life with all advantaged of the new technologies. Due to the 4° lenses and powerful 18x 4W LEDs it creates a very narrow warm white beam just like the aircrafts we used to know. Because of LED and DMX technology there is no need for heavy dimmer racks and difficult cabling. Another advantage is that each aircraft can be programmed separately to create even more dynamic effects. It has a solid housing, a heavy duty double bracket and Powercon in- & output to fulfill all high demanding rental needs.

**Technical information:**



Control
On Board: LED Display
Options: DMX512, Auto, Manual

Electrical
Input Voltage: 100/240VAC, 50/60Hz
Power consumption: 85W @FO

Physical
Dimensions (LxWxH): 515 x 260 x 260 mm
Weight: 3,5 kg
IP Rating: IP-20
Housing: Metal
Connections: Powercon in/out + XLR 3 pole in/out

**FEATURES:**

- 18x 4W WW LEDs
- Powercon in- & output
- Double Bracket
- Shooting range 100m

**Razor Blade 10****30746** 4° Beam Angle

The Showtec Razor Blade 10, is a 2-in-1 LED matrix bar equipped with 10pcs 3W Warm White High Power LEDs(4° beam angle) and 60pcs RGB LEDs. Razor Blade 10 has a 11, 20, 47, 190 channel personality to serve the basic users as well as the advanced users that would like to have full pixel control. The 11 channel mode allows users to control all basic functions and also built-in programs, 20/47/190 channel mode allow users to gain full control of all pixels to create stunning effects.

The Razor Blade 10 can be controlled by DMX, Artnet, Klingnet, but can also be used as a stand-alone fixture with built-in programs. When using multiples units the built-in programs can be synchronized due to master/slave function.

Technical information:



Output
10x High Power LED: Warm White 3W (Cree) /
Beam angle: 4°
60x RGB LED: RGB 0.3W

Electrical
Input voltage: 110-240V / 50-60Hz (auto ranging)
Power consumption: 80W

Control
On Board: LCD Display
Mode: DMX, Artnet, Klingnet, Auto, Sound, Master/Slave

Control protocol: DMX-512, Artnet, Klingnet, RDM
Control personality: 11, 20, 47, 190 Channels

Physical
Housing: Black / Metal
Front cover: Black frost / Flame retardant plastic
Data connections: XLR 3p / XLR 5p / RJ-45
Power connections: PRO Power in- & output
Dimensions: 780 x 110 x 72 mm
Weight: 3.2 Kg

**FEATURES:**

- 10x 3W Warm White High power LEDs / 4° Beam Angle
- 60x 0.3W RGB LEDs
- DMX / Artnet / Klingnet / RDM
- Full Pixel control





Stage Blinder 1 LED

30784 80W Dual White LED module

The Showtec Stage Blinder 1 LED is an audience blinder with a single pod. The unit can be controlled by DMX and holds a 80 Watt Dual White COB. It's the ideal power saving solution for giving your stage the ultimate blinding experience.

Technical information:

Light Source	1 x 80W (2 x 40W) Dual-White (1800K/3060K) COB	Pod movement:	+/- 180° stepless
LED System:	2490K	Beam Angle:	65.5 degrees
Colour temperature:	2490K	Field Angle:	99.5 degrees
Output:	4190lm	Physical Dimensions:	250 x 170 x 80 mm
Refresh rate:	3,1 KHz	Weight:	2,0 Kg
Electrical Power Supply:	100~240VAC, 50/60Hz	Housing:	Metal / Plastic
Power Consumption:	85W @ FO	Colour:	Black
Control Control Mode:	Manual, DMX512	Power connectors:	Powercon connector In/Out
DMX channels:	1, 2 Channel Mode	DMX Connectors:	XLR 3 pole In/Out
Optical system Dimmer:	0-100%	Safety Operation temperature:	-5~45°
Strobe freq.:	0,6 – 18 Hz	Protection rate:	IP20

FEATURES:

- Very Punchy Single Blinder
- Tungsten Simulation
- Compact Design



Stage Blinder 4 LED

30783 4x 80W Dual White LED modules

The Showtec Stage Blinder 4 LED is an audience blinder with 4 single pods. Each Pod can be controlled separately by DMX and holds a 80 Watt Dual White COB. It's the ideal power saving solution for giving your stage the ultimate blinding experience.


Technical information:

Light Source	4 x 80W (2 x 40W) Dual-White (1800K/3060K) COB	Beam Angle:	65 degrees
LED System:	2490K	Field Angle:	99.5 degrees
Colour temperature:	2490K	Physical Dimensions:	380 x 370 x 335 mm (Included Bracket)
Output:	14000lm	Weight:	7,0 Kg
Refresh rate:	3,1 KHz	Housing:	Die cast
Electrical Power Supply:	100~240VAC, 50/60Hz	Colour:	Black
Power Consumption:	320W @ FO	Power connectors:	Powercon Connector In/Out
Control Control Mode:	Manual, Auto, DMX512	DMX Connectors:	XLR 3pole In/Out
DMX channels:	1, 2, 4, 5 Channel Mode	Safety Operation temperature:	-5~45°
Optical system Dimmer:	0-100%	Protection rate:	IP20
Strobe freq.:	0,3 – 8 Hz		
Pod movement:	+/- 20° stepless		

FEATURES:

- Very Punchy 4 way LED Blinder
- Tungsten Simulation
- Compact Design





The Showtec Dot E1 is the smallest fixture of the three with room for 1 E27 bulb. Due to its small size, it can be placed almost everywhere. The Showtec Star E6 accommodates 6 E27 sockets in a hexagon shape. The Edison Bar E6 is the retro bar of the Edison range. Installing them alongside a catwalk or scattering units in the background of the stage automatically adds a sophisticated feel to the event.

Showtec offers a wide range of E27 LED filament bulbs which combined with the Edison fixtures will get the feeling of nostalgia and design across perfectly and turn every event into something special. For more bulbs check out page 48.



Edison Dot E1

30747 DMX Dimmer E27

Technical information:

Power Input: 230V / 50Hz
 Power Consumption: 50W
 Fuse: T1A, 250V
 Light Source: E27 Ledbulbs (not included)
 Control: Built-in Programs, Sound Active, DMX
 DMX Channels: 1

Control Display: LCD
 Power Connector: Seetronic Power in- & output
 Data Connector: XLR In/Out (3 Pin)
 Dimensions: 185.3 x 161 x 166.5mm
 Weight: 1.7 Kg
 Accessories: Mounting bracket (included)

FEATURES:

- E27 Socket
- Lockable menu
- Power & DMX in- / output



Edison Star E6

30748 DMX Dimmer E27

Technical information:

Power Input: 230V / 50Hz
 Power Consumption: 130W
 Fuse: T2A, 250V
 Light Source: E27 Ledbulbs (not included)
 Control: Built-in Programs, Sound Active, DMX
 DMX Channels: 6

Control Display: LCD
 Power Connector: Seetronic Power in- & output
 Data Connector: XLR In/Out (3 Pin)
 Dimensions: 274.2 x 265.2 x 146.5mm
 Weight: 2.5 Kg
 Accessories: Mounting bracket (included)

FEATURES:

- E27 Socket
- Lockable menu
- Power & DMX in- / output



Edison Bar E6

30749 DMX Dimmer E27

Technical information:

Power Input: 230V / 50Hz
 Power Consumption: 130W
 Fuse: T2A, 250V
 Light Source: E27 Ledbulbs (not included)
 Control: Built-in Programs, Sound Active, DMX
 DMX Channels: 6

Control Display: LCD
 Power Connector: Seetronic Power in- & output
 Data Connector: XLR In/Out (3 Pin)
 Dimensions: 1044 x 160 x 130mm
 Weight: 5.1 Kg
 Accessories: Mounting brackets (included)

FEATURES:

- E27 Socket
- Lockable menu
- Power & DMX in- / output







Festoonlight Q4 Controller

41750 including 10m connection cable

Showtec's Festoon controller offers various control modes for the Festoon strings. Full pixel control for up to three Festoon strings. If you would like to add more strings to one setup, that is possible by adding the optional Festoon booster. With the booster you can extend your setup to a maximum of 6 strings on one controller. The Festoon controller is delivered including a 10mtr extension cable. Please note that the Festoon string and Festoon booster are available separately.

Technical information:

Operation:	DMX, Artnet, Built-in programs	Environment:	IP-20
DMX channels:	2, 4, 8, 20, Full Pixel control	Weight:	2,55Kg
Power Supply:	100-240VAC...50/60Hz	Included strings:	none
Power Consumption:	110W max @ FO	Included booster:	none
Mounting:	Quick lock bracket	Included extension cable:	1 piece 10m included (Use maximum 1 extension cable in the Festoonlight Q4 setup)
Controller box Size:	315 x 200 x 81,5mm	Max length:	90m
Operating temp:	-5° - +40°	Max strings:	3 pcs without booster / 6 pcs including booster
Cooling:	Convection		
Power Connections:	Pro Power in- & output		
Data Connection:	XLR 3 pole in- & output, Ethercon in- & output		

FEATURES:

- Full pixel control
- Easy to install
- Extend up to 6 strings per controller (including booster)
- Artnet and Dmx control
- Roadproof



Festoonlight Q4 String

41751 20 pixels, 15mtr.

The Showtec Festoon Q4 string has a length of 15mtr with 20 pixels. Each pixel can be controlled individually with the dedicated Festoon controller. On the standard controller you can connect a total of three Festoon strings as a series. Expanding this to a total of 6 strings per controller is possible by using the dedicated Festoon booster

Technical information:

Light source:	5050SMD RGB Led	Power Consumption:	35W per string
Beam angle:	360°	Use the eyelets on the bulbs for mounting the string. Do not use the cable for mounting.	
Refresh rate:	1,9 KHz	Please note: the strings (41751) are only compatible with Festoonlight Q4 Controller (41750)	
String Length:	15m		
Bulbs per string:	20 Pcs		
Bulb Size:	Ø 80mm		
Distance between bulbs:	75 cm		

FEATURES:

- Full pixel control
- Easy to install
- Extend up to 6 strings per controller (including booster)
- Artnet and Dmx control
- Roadproof

Festoonlight Q4 Booster

41752 For 4 to 6 Festoon strings

The Showtec Festoon booster needs to be used as soon as you would like to expand the number of Festoon strings on your controller. For each controller a maximum quantity of 3 Festoon strings can be connected together. Only if you need to expand this quantity to a maximum of 6 Festoon strings per controller the booster is required.

Technical information:

When you want to connect more than 3 strings to the Festoonlight Q4 Controller (41750) you need to connect this Booster.







Illumilift RGBW

41165 4m Hoist / 25cm LEDsphere

The Showtec Illumilift adds another dimension to your venue, literally. The Illumilift consists of a 4 meter winch system with a 25cm RGBW LED sphere. Through DMX512 in basic or advanced mode you can generate full saturated colours with the RGBW module inside the LED sphere. By adding white even soft tones are possible. It's high speed 16 bit lifting motor makes positioning via DMX control very accurate. Both Power and DMX In/Out make these units easy to daisy chain for bigger setups. The two DMX modes include a Safety channel avoiding unexpected movement. For a really awesome effect you can put various Illumilift sets into one setup. And combining it with the optional 35cm RGBW LED sphere gives ultimate freedom to your Lighting and Designs.


Important: please note that the Illumilift hoist is only meant to be used in combination with the 35cm or 25cm LED Sphere,

Technical information:

Dimensions:	36.5 x 33 x 13 cm	Total power consumption:	50W
Weight:	9kg (including 25cm Sphere)	LED control:	RGBW
Max Load on cable:	2Kg	Refresh Rate:	9.1 KHz
Lifting height:	4m	Control:	DMX512 / Manual
Lifting speed:	0 – 0.25 m/s	Connection:	3-pin XLR DMX In/out and ProPower In/out
Lifting Cable:	5x 0,5 mm ²	Mount:	2 brackets included
Power supply:	100 ~ 240VAC, 50/60 Hz	IP Rating:	IP22
Power on cable:	4 channels max 18V DC, max 0.3A per channel		

FEATURES:

- 16 bit position control
- Interchangeable led spheres
- Lifting speed control
- Operation safety channel




Illumilift RGBW LED Sphere

41167 25cm

Separate 25cm LEDsphere, especially for the Showtec Illumilift and Showtec Illumilift Turbo

Technical information:

Dimensions:	25cm (diameter)
Weight:	0.85kg
Total power consumption:	18W
LED control:	RGBW
IP Rating:	IP22



Illumilift RGBW Turbo**41166 6m High Speed Hoist / 35cm LEDsphere**

The Showtec Illumilift Turbo adds another dimension to your venue, literally. The Illumilift consists of a high speed 6 meter winch system with a 35cm RGBW LED sphere. Through DMX512 in basic or advanced mode you can generate full saturated colours with the RGBW module inside the LED sphere. By adding white even soft tones are possible. It's high speed 16 bit lifting motor makes positioning via DMX control very fast and accurate. Both Power and DMX In/Out make these units easy to daisy chain for bigger setups. The two DMX modes include a Safety channel avoiding unexpected movement. For a really awesome effect you can put various Illumilift sets into one setup. And combining it with the optional 25cm RGBW LED sphere gives ultimate freedom to your Lighting and Designs.


Important: please note that the Illumilift hoist is only meant to be used in combination with the 35cm or 25cm LED Sphere.

Technical information:

Dimensions:	46.5 x 37 x 19 cm	Total power consumption:	76W
Weight:	14 Kg (including 35cm Sphere)	LED control:	RGBW
Max Load on cable:	2Kg	Refresh Rate:	19.6 KHz
Max Lifting height:	6m	Control:	DMX512/ Manual
Lifting speed:	0 – 2,5 m/s Max	Connection:	3-pin XLR DMX In/out and ProPower In/out
Lifting Cable:	5x 0,5 mm ²	Mounting:	2 brackets included
Power supply:	100 – 240VAC, 50/60 Hz	IP Rating:	IP22
Power on cable:	4 channels max 18V DC, max 0.3A per channel		

FEATURES:



- 16 bit position control
- Interchangeable led spheres
- Lifting speed control
- Operation safety channel

**Illumilift RGBW LED Sphere****41168 35cm**

Separate 35cm LEDsphere, especially for the Showtec Illumilift and Showtec Illumilift Turbo

Technical information:

Dimensions:	35cm (diameter)
Weight:	1,36kg
Total power consumption:	18W
LED control:	RGBW
IP Rating:	IP22





Maniac FX 7




41307 Beam + Wash

Combining the best of both worlds might be the best description of the Showtec Maniac 7. The Showtec Maniac 7 is truly a two-for-one multi-effect. A wash-effect with 7x 7W High Power, pixel controlled RGB LED's with a 40° beam angle. This offers the possibility of creating your very own show with great colours and an equal spread. But it is also a beam effect with 7x 3W cold white LEDs which generate razor sharp 2° beams. Both effects together in one housing creates an awesome effect. Daisy-chaining units with the DMX-signal into one large presentation is no problem. Power linking up to 8 units at a time is just as easy by using the Power-PRO connector. For mobile party locations, dj's, pubs and events the ideal effect. Easy to install, equally easy to operate and adding something special to your event.



Technical information:

Electrical		Strobe:	0-20Hz
Power input:	100-240V 50/60z	Beam Angle:	40° Wash - 2° Beam
Power linking:	Up to 8 Units		
Power consumption:	180W	Physical	
		Dimensions:	1000 x 140 x 120 mm
LED Source		Weight:	4,5 Kg
	7 x 3W Cold White	Housing:	Aluminium
	7 x 7W High Power RGB	Colour:	Black
Control		Data Connector:	3 pole XLR (In/Out)
Control mode:	Auto, Sound, Master/Slave, DMX 512	Power Connection:	PowerPRO In/Out
DMX Channels:	3,4,6,10,12 and 15	Cooling:	Fan Cooled
Control Display:	4 Digits LED	Certification and Safety	
Optical system		Certification:	CE
Dimmer:	0-100%	Max. ambient Temp.:	40°C



FEATURES:

- Powerful Beam effects
- Pixel Control
- Built-in programs
- Power and Data daisy chain



LED Pinpoint Q4

42407 Black


The LED Pinpoint PRO RGBW is a powerful but compact LED Pinpoint which can easily compete with its traditional equivalents. The RGBW LEDs deliver a strong beam which is ideal to illuminate mirror balls or small surfaces

Technical information:

Output		Optical system	
Lumens:	141	Beam Angle:	4°
Lux @2m:	7010	Physical	
Max. Distance:	10m	Dimensions:	310x150x105 mm
Light Source		Weight:	1,3 Kg
LED System:	1x15W 4-in-1 RGBW Prolight Opto LED	Housing:	ABS Plastic
Drive Current:	1000 mA	Colour:	Black
Electrical		Fixture Connection:	Schuko/XLR (3-pin) DMX in/out Pigtaills Convection
Power Supply:	AC 100-240V 50/60 Hz	Cooling:	
Power Consumption:	22W @FO	Safety	
Control		Operation temperature:	-20~40°C
Program:	Built-in auto programs		
Control Mode:	DMX512		
DMX channels:	4,6,8		

FEATURES:

- Compact & lightweight
- 15W RGBW Prolight Opto LED
- Ideal to illuminate mirrorballs
- Plug & Play



Par 64 LED-100Z

42530 3200K, Black

42531 5600K, Black

The Par 64 LED100Z-3200K is a traditional parcan equipped with the latest technology in order to create traditional halogen effects with all the benefits from LED.

This Parcan is equipped with a bright 3200K Citizen LED which brings over 4400 Lumen. The manual zoom allows you to adjust the beam angle at 5 different positions starting from a tight 15° beam angle up to a nice flood of 35°. The fixture can be fully controlled by DMX and a filter frame is included for those who want to add diffusion filters or colour gels.

Technical information:

Output		Electrical	
Distance:	> 10m	Input voltage:	100-230V / 50-60Hz
LED Quantity:	1x 80W Citizen LED	Power consumption:	105 W
Output:	4400 Lumen (42530) 4330 Lumen (42531)	Power Factor:	> 0,8
Refreshrate:	3 KHz	Physical	
Dimmer:	0-100% (DMX)	Dimensions in mm:	444 (L) x 302 (W) x 405 (H)
Beam angle:	15°, 20°, 25°, 30°, 32° (Manual Zoom)	Weight:	3,7 kg
CRI:	>80	IP Rating:	IP-20
Colourtemperature:	3200K (42530) 5600K (42531)	Operating temperature:	-20°C/45°C
		Housing:	Aluminium
		Connections:	Schuko VDE Plug 3 pole XLR
Control		Cooling:	By fan
On board:	Display for easy setup	Filterframe:	Included
Options:	DMX512, Auto, Manual		
DMX Personality:	1, 2, 3 Channels		



FEATURES:

- Manual zoom
- Halogen dimming effect
- DMX Control
- Retro Look



Par 64 LED-120Z-Q4

42540 Black

The Par 64 LED120Q4 Zoom is a traditional parcan equipped with the latest technology in order to create traditional halogen effects with all the benefits from LED.

This Parcan is equipped with a bright 120W RGBA LED Module from ProLight Opto which brings over 17000 Lumen at full on. Due to its RGBA LED module this fixture can create a wide pallet of colours. Especially the addition of the amber colour will allow you to create nice warm colours and perfect skin tones.

The manual zoom allows you to adjust the beam angle at 6 different positions starting from a tight 12° beam angle up to a nice flood of 35°. The fixture can be fully controlled by DMX and a filter frame is included for those who want to add diffusion filters.

Technical information:

Output		Electrical	
Distance:	> 10m	Input voltage:	100-230V / 50-60Hz
LED Quantity:	1x 120W RGBA ProLight Opto	Power consumption:	142W
Output (@12,5°):	Red: 4180 Lumen @ 2m Green: 6850 Lumen @ 2m Blue: 342 Lumen @ 2m Amber: 7950 Lumen @ 2m Full on: 17180 Lumen @ 2m	Power Factor:	>0,8
Refreshrate:	3 KHz	Fuse:	T2A 250V
Dimmer:	0-100% (DMX)	Physical	
Beam angle:	12°, 15°, 20°, 25°, 30°, 35° (Manual Zoom)	Dimensions:	444 (L) x 302 (W) x 405 (H) mm
		Weight:	4,1 kg
Control		IP Rating:	IP-20
On board:	Display for easy setup	Operating temperature:	-20°C/45°C
Options:	DMX512, Auto, Manual	Housing:	Aluminium
DMX Personality:	4, 7, 11 Channels	Connections:	Schuko VDE Plug 3 pole XLR
		Cooling:	By fan
		Filterframe:	Included



FEATURES:

- Manual zoom
- RGBA Colourmixing
- DMX Control
- Retro Look





Spectral Revo 6

43640 IP-65

The evolution and ongoing development of the Spectral series resulted in the Spectral Revo 6. An IP-65 rated outdoor fixture with a newly designed single lens which creates a very good homogenous output. Strong, saturated colours from the 125W 6-colour RGBALC Osram LED source produce a full spectrum of light. As an additional advantage this means that colour mixing or producing whites is truly sublime. The Spectral Revo 6 is very well suited for outdoor events and should not be missed in the product-range of any rental company.

Technical information:

Output:		Optical System:	
Max. Flux:	3051lm	Dimmer:	0-100%
Peak Intensity:	28987cd	Strobe:	0-20Hz
		Optics:	17°
Light Source:		Physical:	
LED:	125W custom Osram RGBALC LED Array	Dimensions:	320 x 418 x 219 mm
Colour Range:	16.7 million additive colours with full saturation control	Weight:	8,5Kg
		Housing:	Die-casting aluminum
		Colour:	Black
Electrical:		PI rating:	IP-65
Input Voltage:	AC100V-240V, 50/60Hz	Fixture Connection:	XLR (5-pin) DMX in/out, Powercon True1 power in/out
Max. Power:	145W	Cooling:	Forced Convection
Control:		Operation Temperature:	-40°C ~45°C (operating) / -20°C ~45°C (startup)
On-board:	Display for Auto and Custom control		
Control Protocol:	DMX512		
Control Personality:	Basic, CLR, HSIC, SSP, Tour, TR16		



FEATURES:

- PC Lens Optics
- RGBALC Osram source
- Forced Convection cooling
- IP65 rated



Performer Profile Mini

33090 3200K

33091 5600K

With the Performer Profile Mini we bring you the perfect complement in function and form to our Performer Profile 600 in a tiny fixture that's just one-third the size of the Profile 600. Equipped with a 30W COB LED, Gobo holder and a four-blade shutter system, it has an extremely clear cutting edge, sharp gobo images and also can create a crystal bright projection effect. The optional available lenses 19°, 26° and 36° and zoom lens tube provide the suitable output for each location. Versatile from small to medium applications for bars, pubs, museums, restaurants, and other small scale installations where size matters.

Technical information:

Light source		Control	
LED quantity:	30 W COB	Dimmer:	Directly on triac, RDM
Lux@1m:	15000 (19° 33090)	Beam angle:	19°-36° Optional
Lux@1m:	16000 (19° 33091)		
Colour rendering:	>90Ra	Physical	
Colour temperature:	3200K (33090)	Dimensions:	345 x 130 x 231 mm
Colour temperature:	5600K (33091)	Weight:	1,3 kg
		Housing:	Die-cast aluminium
Electrical		Colour:	Black
Input voltage:	110~240VAC, 50/60Hz	Mount Features:	Portable/Track-mount
Max. Power:	25W	Cooling:	Forced - Air convection
Drive Current:	0,5A		



- FEATURES:**
- 30W LED Light source
 - Directly Triac Dimming
 - DMX / RDM
 - Colour temperature 3200K/5600K





Performer Profile IP 3200K

33110 IP-65 rated Profile spot


The Showtec Performer Profile IP 3200K is very well equipped for outdoor purposes. Theme parks, open air festivals or theatres form the perfect stage for the Performer Profile IP3200K. IP-65 rated, CRI> 90Ra, a variable beamangle of 15°-30° which is adjustable via the electronic zoom and focus system. The Performer Profile IP3200K has framing shutters built-in which can be controlled manually. For the overall control of the unit, this can be done manually, via RDM or DMX-512 protocol. A rotatable goboholder is also part of the package.

Technical information:

Lightsource		Beam Angle:	15°-30°
LED System:	1x 260W COB LED	Zoom:	electrical
Drive current:	1.5A	Focus:	electrical
CCT:	3200K	Physical:	
Refresh rate:	600Hz to 25kHz	Dimension:	648 x 344 x 273 mm
Output:	23600Lux @ 3m (15°)	Weight:	16Kg
Electrical		Housing:	Die Cast Aluminum
Input voltage:	100~240VAC, 50/60Hz	Colour:	Black, powder coated
Power consumption:	250W@FO	Power Connectors:	Dedicated IP connector
Control		Data Connectors:	XLR 3 & pole in- & output
On-board:	Dimmer	Cooling:	Silent Fan
Control Protocol:	Manual, DMX-512, RDM	IP Rating:	IP-65
DMX Personality:	Simple, Mode 16Bit	Ambient temp:	-20°C ~ +45°C
Optical system			
Dimmer:	0-100%		
Dim curve:	Dimm4 technology, 4 presets		
Dim resolution:	16bit		

FEATURES:

- CRI> 90Ra
- Motorized Focus
- Manual framing system
- 15°-30° Electronic zoom system



Performer Profile IP Q4

33111 IP-65 rated Profile spot

The Showtec Performer Profile IP Q4 is very well equipped for outdoor purposes. Theme parks, open air festivals or theatres form the perfect stage for this strong fixture. IP-65 rated, engineered around a 250W RGBW LED array, a variable beamangle of 15°-30° which is adjustable via the electronic zoom and focus system, 16-bit 0-100% dimming. The Performer Profile IP3200K has framing shutters built-in which can be controlled manually. For the overall control of the unit, this can be done manually, via RDM or DMX-512 protocol. A rotatable goboholder is also part of the package.

Technical information:

Lightsource		Dim resolution:	16bit
LED System:	1x 250W LED Array RGBW	Beam Angle:	15°-30°
Drive current:	1.2A	Zoom:	electrical
CCT:	2700-8000K	Focus:	electrical
Refresh rate:	600Hz to 25kHz	Physical:	
Output:	9975Lux @ 3m (15°)	Dimension:	648 x 344 x 273 mm
Electrical		Weight:	16Kg
Input voltage:	100~240VAC, 50/60Hz	Housing:	Die Cast Aluminum
Power consumption:	300W@FO	Colour:	Black, powder coated
Control		Power Connectors:	Dedicated IP connector
On-board:	Dimmer	Data Connectors:	XLR 3 & pole in- & output
Control Protocol:	Manual, DMX-512, RDM	Cooling:	Silent Fan
DMX Personality:	HSIC, Simple, Colour 8Bit, Colour 16Bit	IP Rating:	IP-65
Optical system		Ambient temp:	-20°C ~ +45°C
Dimmer:	0-100%		
Dim curve:	Dimm4 technology, 4 presets		

FEATURES:

- Motorized Focus
- 15°-30° Electronic zoom system
- Manual framing system
- Rotating Gobo holder





Performer Fresnel Mini

- 33053** 30W, 3100K, DDT
- 33054** 30W, 3100K, Dmx Control
- 33055** 30W, 3100K, Battery Powered

The Showtec Performer Fresnel Mini spotlights form a range of 3 pieces of mini fresnel spotlights which are extremely suitable for a wide range of applications. From accent lighting on decors and company parties to accent lighting in theatres or for TV recordings. Due to its compact design, it can be used anywhere. The manual zoom ensures that the bundle is adjustable in the right size and the supplied barndoor ensures the correct design of the bundle. There are 3 models: the DDT model can be dimmed with a traditional dimmer pack and is therefore ideal for installations where you want to switch to LED light sources without adjusting the infrastructure. The DMX variant (33054) can be controlled with any DMX desk and the battery version (33055) is the ideal solution for mobile solutions such as TV reports or interviews.

The Showtec Performer Fresnel Mini with super stylish design, extremely lightweight and compact, warm white 3200K, manual zoom 12°-34°. Fanless design and quiet performance, fully compatible with TRI-AC control, smooth dimming curve, it is a truly perfect tool for theatre, museum, gallery, hotel, and retail shops.

Technical information:

Lightsource:	1x 30W LED	Manual Zoom:	12°-35°
Source:	3100K	Physical:	
Colour Temperature:	3100K	Dimensions:	252 x 178 x 188 mm
Colour Rendering:	>92Ra	Weight:	2.0 Kg
Lux@1m:	16500 (12°)	Housing:	Extruded Aluminium
Lux@1m:	4500 (35°)	Colour:	Black
Electrical:		Fixture connection:	Power In
Input voltage:	210-240VAC, 50/60Hz	Barndoor:	Optional (33056)
Power consumption:	23W	Cooling:	Air convection
Control:		Certification and Safety:	
On-board:	non	Certification:	CE
Control protocol:	direct triac	IP Rating:	IP20
Optical System:		Operation Temperature:	0°C ~40°C
Dimmer:	5-100%		



FEATURES:


- Classic Compact Fresnel design
- High efficiency 30W LED source
- Fanless convection cooling
- Direct triac dimming technology (DDT)



Barndoor for Performer Fresnel Mini

33056

Optional dedicated barndoor for Performer Fresnel Mini DDT/DMX/Battery



Performer 1000 LED MKII

33035 Fresnel 5600K



The Performer 1000 LED MKII the successor of Performer 1000 LED. Redesigned optics and upgraded LED source has increased the output with almost 25%. It is an extremely bright and compact lighting fixture that is suitable for a wide range of professional applications. Fantastic dimming and smooth zoom range provide lighting designers with an incredibly useful lighting tool.

Technical information:

Light Source		Physical	
LED Qty.:	1x COB	Dimensions:	324 x 288 x 266 mm
Drive Current:	3A	Weight:	6 Kg
Refresh rate:	600Hz	Housing:	Extruded aluminium
		Colour:	Black
Electrical		Fixture Connection:	DMX in/out, power in/out
Input Voltage:	100~240 VAC	Cooling:	Forced air
Max. Power:	105W	Environment:	Dry
		Operation Temperature:	-20°C ~ 40°C
Control		Output	
On-board:	Dimmer	Max. Flux:	4000lm
Control Protocol:	DMX512	Peak Intensity:	112500cd
DMX Personality:	1,2,3 Ch	Colour Rendering:	>90Ra
Optical System Dimmer:	0-100%		
Manual Zoom:	10° - 60°		
Colour temperature:	5600K		

FEATURES:

- LED COB Lightsource
- Wide Manual Zoom Range
- DMX control
- Colourtemperature 5600K



Performer 2000 DDT MKII

33036 Fresnel 5600K



The Performer 2000 DDT MKII is a Fresnel wash which can be used on traditional dimming pack allowing you to upgrade your venue to LED fixtures without the need of changing your complete infrastructure. This MKII successor has redesigned optics and upgraded LED source which extremely increased the output. The Performer 2000 DDT has an adjustable motorized focus which is easily accessible by the rotary knob on the back of the fixture. Furthermore the Performer 2000 DDT MKII can also run a constant voltage and be controlled by DMX. It offers superb and smooth dimming and an even field of light. The Performer 2000 DDT MKII comes including a filter frame. A barndoor is available as option.

Technical information:

Lightsources		Physical	
Source:	1x 250W LED	Dimensions:	417 x 286 x 260 mm
Refresh rate:	600 Hz to 25 kHz	Weight:	6.6 Kg
Peak intensity:	10333cd	Housing:	Extruded Aluminium
		Colour:	Black
Electrical		Fixture connection:	Power In/Out
Input voltage:	100-240V AC	Cooling:	Forced - Air convection - Silent fan
Power consumption:	195W		
Control		Output	
On-board:	Dimmer 0-100%	Max. Flux:	6400 Lumen
Dim curve:	Dimm4 technology, 4 presets	Colour Rendering:	>90Ra
Dim resolution:	16bit	Colour Temperature:	5600K
Control protocol:	DMX512, Direct Triac		
DMX Personality:	1, 2, 5		
Optical System:			
Dimmer:	0-100%		
Motorized Zoom:	13 - 41 degrees		
Field angle:	25 - 76 degrees.		

FEATURES:

- LED Lightsource
- Wide Electric Zoom Range
- > CRI 90
- Colourtemperature 5600K





Helix S5000 Q4

43725 40 x 10W 10°

You are already familiar with our Helix 4000 units for quite some time now and you gave us some very valuable input with which we could upgrade this unit and produce the Helix S5000. With a rating of IP-65 and sturdy design this unit is well equipped to be used outdoors.

With 40 Prolight Opto RGBW 4-in-1 LEDs you will have absolutely no problem in colouring large areas. The 10° optic lenses generate a very strong beam and for more versatility you can always use one of the optional beam shapers: 20°, 40° or 15x60°. Besides these magnetic beam shapers, a barndoor or tophat are available as separate option as well.

The Helix S5000 is compatible with the Helix 4000 because they use the same colour presets and personalities. On top of this the Helix S5000 has Section control. Each unit has been equipped with WDMX by Wireless Solution Sweden and the 180° Flip-function gives you the opportunity to always place the unit in such a way that the cables and connectors are no longer visible. Rigging is also no issue because the unit comes complete with Quicklocks. We have even added a backlight touch display so you will be able to control your Helix S5000 under any circumstance where light is scarce. If you need to transport them, you can use our Premium line flightcase which will fit both models: Helix 4000 Q4 and Helix S5000.

Technical information:

Light Source	40 x Prolight Opto RGBW	Strobe:	0-20Hz
LED System:	4-in-1 10W LEDs	Beam Angle:	10° (optional 20°, 40°, 15x60°)
Output@2m:	54000lux	Tilt Angle:	0-180°
Refreshrate:	3, 4, 6, 12 Khz	Physical Dimensions:	532 x 320 x 122 mm
Electrical Power Supply:	AC 100-240V 50/60 Hz	Weight:	9,5 Kg
Power Consumption:	415W	Housing:	Die-cast aluminum
Control Control Mode:	Auto/ built-in programs, Master/slave, DMX / RDM	Colour:	Black
DMX channels:	4, 6, 8, 20, 24ch	Power Connectors:	Powercon True1
Optical system Dimmer:	0-100%	Data Connectors:	XLR-HD 5-pin
Dim Curves:	4	Cooling:	Forced-air
		Safety Operation temperature:	-10-40°C
		IP-Rating:	IP-65

FEATURES:

- 5 Sections control
- W-DMX by Wireless Solutions Sweden
- IP-65 rated
- 10° and optional available Beamshapers



Barndoor for Helix S5000 Q4

43726

Dedicated barndoor for Helix S5000 Q4. Connection via quicklock pins



Tophat for Helix S5000 Q4

43730

Dedicated tophat for Helix S5000 Q4. Connection via quicklock pins



Beamshaper for Helix S5000 Q4

43727 20°

43729 15°x60°

43728 40°

Dedicated Helix S5000 Q4 filter to change the output beam angle. Connection to the unit via Magtags (A very easy way to make a quick and precise connection (without the use of tools, clamps or screws)





FEATURES:

- Clever software provides up to 15 hours battery life
- W-DMX by Wireless Solutions Sweden
- IP-65 rated
- 10° and optional available Beamshapers

Helix M1000 Q4 Mobile

43740 RGBW Wash fixture

To further expand the Helix family, Showtec has created the versatile, lightweight and compact Helix M1000 Mobile. This versatile RGBW wash fixture operates fully wireless. The onboard Lithium Ion battery, combined with smart software will provide an extended operating time of up to 15 hours regardless of the choice of output colour or intensity. With the possibility to link to Wireless DMX or use the provided programs, there will be a solution for each application. To enhance the versatility, available accessories like the beamshapers, barndoor and tophat will tailor the item to the demand. With a rating of IP-65 and sturdy design this unit is well equipped to be used outdoors.

Technical information:

Light Source	8 x Prolight Opto RGBW 4-in-	Battery Type:	Lithium ion
LED System:		Voltage:	18,5V
1 10W LEDs		Storage:	13 Ah
Output@2m:	8000lux	Battery life time:	8h @ Full, 15h by software
Refreshrate:	12 KHz	Charging Cycle:	6hrs
Electrical Power Supply:	AC 100-240V 50/60 Hz	Physical Dimensions:	370 x 302 x 122 mm
Power Consumption:	75W	Weight:	7,5 Kg (incl battery)
Control Settings:	OLED Graphical display with 4 touch buttons	Housing:	Die-cast aluminum
Control Mode:	Auto/ built-in programs, Master/slave, DMX	Colour:	Black
DMX channels:	4, 6, 10ch	Power Connectors:	Powercon True1
Optical system Dimmer:	0-100%	Data Connectors:	XLR-HD 5-pin
Dim Curves:	4	Cooling:	Passive
Strobe:	0-20Hz	Safety Operation temperature:	0-40°C
Beam Angle:	10° (optional 20°, 40°, 15x60°)	IP-Rating:	IP-65
Tilt Angle:	0-180°		





Tophat for Helix M1000 Q4 Mobile

43741

Dedicated tophat for the Helix M1000 Q4. Connection via quicklock pins



Barndoor for Helix M1000 Q4 Mobile

43742

Dedicated barndoor for Helix M1000 Q4 Mobile. Connection via quicklock pins



Beamshaper for Helix M1000 Q4 Mobile

43745 20°

43746 40°

43747 15° x 60°

Dedicated beamshapers for the Showtec Helix M1000 Q4 Mobile. Connection to the unit via Magtags (A very easy way to make a quick and precise connection (without the use of tools, clamps or screws))



The antique look and warm glow of vintage reproduction **LED filament bulbs** are popular for restaurants, lobbies and hotels. Antique LEDs have experienced an incredible revival in recent decades. Better yet, LED lamps

have been developed to imitate this beautiful style by creating a LED "filament" that is similar to the classic filament of an filament bulb.

LED Filament Bulb BT180

83275 6W, dimmable

Technical information:

Type: BT180
 Socket: E27
 Voltage: 230V AC, 50Hz
 Power: 6W
 Temp: 2700K
 CRI: 80
 Powerfactor: 0,9
 Output: 360 Lumen
 Dimmable: Yes
 Dimensions: 180 x 360mm



LED Filament Candle Bulb B10

83265 Spiral Filament

Technical information:

Type: C35
 Socket: E14
 Voltage: 230V AC, 50Hz
 Power: 2W
 Temp: 2200K
 CRI: 90
 Powerfactor: 0,9
 Output: 140 Lumen
 Dimmable: Yes
 Dimensions: 35 x 100mm



LED Filament Bulb T9

83266 300mm, Crossed Filament

83267 225mm, Crossed Filament

83268 185mm, Crossed Filament

83269 300mm, Straight Filament

83270 225mm, Straight Filament

83271 185mm, Straight Filament

Technical information:

Type: T28 (T9)
 Socket: E27
 Voltage: 230V AC, 50Hz
 Power: 8W
 Temp: 2700K
 CRI: 80
 Powerfactor: 0,5
 Output: 800 Lumen
 Dimmable: Yes
 Dimensions: 28 x 300mm



LED Filament Bulb BT118

83276 6W, dimmable

Technical information:

Type: BT118
 Socket: E27
 Voltage: 230V AC, 50Hz
 Power: 6W
 Temp: 2700K
 CRI: 80
 Powerfactor: 0,9
 Output: 360 Lumen
 Dimmable: Yes
 Dimensions: 118 x 258mm



LED Filament Bulb PS52

83278 6W, dimmable

Technical information:

Type: PS160 (PS52)
 Socket: E27
 Voltage: 230V AC, 50Hz
 Power: 6W
 Temp: 2700K
 CRI: 80
 Powerfactor: 0,9
 Output: 360 Lumen
 Dimmable: Yes
 Dimensions: 160 x 300mm



LED Filament Bulb G200

83277 6W, dimmable

Technical information:

Type: G200
 Socket: E27
 Voltage: 230V AC, 50Hz
 Power: 6W
 Temp: 2700K
 CRI: 80
 Powerfactor: 0,9
 Output: 360 Lumen
 Dimmable: Yes
 Dimensions: 200 x 290mm



LED Filament Bulb BTT80

83280 6W, dimmable

Technical information:

Type: BTT80
 Socket: E27
 Voltage: 230V AC, 50Hz
 Power: 6W
 Temp: 2700K
 CRI: 80
 Powerfactor: 0,9
 Output: 360 Lumen
 Dimmable: Yes
 Dimensions: 60x340mm



LED Filament Bulb PS35

83279 6W, dimmable

Technical information:

Type: PS110 (PS35)
 Socket: E27
 Voltage: 230V AC, 50Hz
 Power: 6W
 Temp: 2700K
 CRI: 80
 Powerfactor: 0,9
 Output: 360 Lumen
 Dimmable: Yes
 Dimensions: 110 x 200mm



LED Filament Bulb R160

83281 6W, dimmable

Technical information:

Type: R160
 Socket: E27
 Voltage: 230V AC, 50Hz
 Power: 6W
 Temp: 2700K
 CRI: 80
 Powerfactor: 0,9
 Output: 360 Lumen
 Dimmable: Yes
 Dimensions: 160x245mm





ColorCue 1

50703 LED Controller

The ColorCue 1 offers one grand master fader with 6 colour rotary encoders, 12 memory buttons for colours/chases/user memories.

Technical information:

Power supply:	DC 12V- 500mA
Power consumption:	10 Watt
Power connector:	Adapter (included)
Fixed colours:	12 pcs
Fixed chases:	12 pcs
User colours:	12 pcs
User chases:	12 pcs with 99 steps
Fixtures:	1
DMX-512:	XLR 3 pole
Dimensions:	258 x 150 x 60 mm (LxWxH)
Weight:	0,9 Kg



FEATURES:

- Intelligent LED DMX controller
- Control RGBWA-UV fixtures up to 6 channels
- 24 Colours & 24 Chases

ColorCue 2

50704 LED Controller

The ColorCue 2 offers one grand master fader, 6 fixture intensity faders, 6 colour rotary encoders, 20 memory buttons for colours/chases/user memories.

Technical information:

Power supply:	DC 12V- 500mA
Power consumption:	15 Watt
Power connector:	Adapter (included)
Fixed colours:	20 pcs
Fixed chases:	20 pcs
User colours:	20 pcs
User chases:	20 pcs with 99 steps
Fixtures:	6
DMX-512:	XLR 3 pole
Dimensions:	385 x 175 x 60 mm (LxWxH)
Weight:	1,2 Kg



FEATURES:

- Intelligent LED DMX controller
- Control 6 pcs RGBWA-UV fixtures up to 6 channels
- 40 Colours & 40 Chases

PowerCon True1 power-out

NAC3MXWTOP locking male connector

Technical information:
 Title: NAC3MXWTOP
 Gender: male
 Contact resistance: $\leq 3 \text{ m}\Omega$ (inner)
 Number of electrical contacts: 2 + PE
 Rated current per contact: 16A max
 Rated maximum voltage: 250 V ac
 Cable Outside Diameter: 6 – 12 mm
 Wiresize: 1.0 – 2,5 mm²
 Temperature range: -30 °C to +80 °C



PowerCon True1 power-in

NAC3FXWTOP locking female connector

Technical information:
 Title: NAC3FXWTOP
 Gender: female
 Contact resistance: $\leq 3 \text{ m}\Omega$ (inner)
 Number of electrical contacts: 2 + PE
 Rated current per contact: 16A max
 Rated maximum voltage: 250 V ac
 Cable Outside Diameter: 6 – 12 mm
 Wiresize: 1.0 – 2,5 mm²
 Temperature range: -30 °C to +80 °C



PowerCon True1 inlet connector

NAC3MPXTOP locking 16A mains connector

Technical information:
 Title: NAC3MPXTOP
 Gender: male
 Contact resistance: $\leq 3 \text{ m}\Omega$ (inner)
 Number of electrical contacts: 2 + PE
 Rated current per contact: 16A max
 Rated maximum voltage: 250 V ac
 Wiresize: 2,5 mm²
 Temperature range: -30 °C to +80 °C
 Optional Accessories: Sealing Cover SCNAC-MPX



PowerCon True1 in/outlet connector

NAC3PXTOP locking 16A mains connector

Technical information:
 Title: NAC3PXTOP
 Gender: male/female
 Contact resistance: $\leq 3 \text{ m}\Omega$ (inner)
 Number of electrical contacts: 2 + PE
 Rated current per contact: 16A max
 Rated maximum voltage: 250 V ac
 Wiresize: 2,5 mm²
 Temperature range: -30 °C to +80 °C
 Optional Accessories: Sealing Cover SCNAC-PX



IEC C13 to Schuko Male

- 92020** 3 x 1,5mm² 1mtr
- 92021** 3 x 1,5mm² 3mtr
- 92022** 3 x 1,5mm² 5mtr
- 92023** 3 x 1,5mm² 10mtr

Technical information:
 Cable diameter: 3x1.5mm²
 Cable length: 1m/3m/5m/10m
 Cable type: H05VV-F
 Male plug: Straight schuko connector (CEE 7/7)
 Female Plug: IEC (C13)



IEC C13 to IEC C14

- 92030** 3 x 1,5mm² 1mtr
- 92031** 3 x 1,5mm² 3mtr
- 92032** 3 x 1,5mm² 5mtr
- 92033** 3 x 1,5mm² 10mtr

Technical information:
 Cable diameter: 3x1.5mm²
 Cable length: 1m/3m/5m/10m
 Cable type: H05VV-F
 Male plug: IEC (C14)
 Female Plug: IEC (C13)



IEC C13 to UK BS13 Plug

- 92040** 3 x 1,5mm² 1mtr
- 92041** 3 x 1,5mm² 3mtr

Technical information:
 Cable diameter: 3x1.5mm²
 Cable length: 1m/3m
 Cable type: H05VV-F
 Male plug: UK Plug (BS13)
 Female Plug: IEC (C13)



IEC C13 to Australia Plug

- 92050** 3 x 1,5mm² 1mtr
- 92051** 3 x 1,5mm² 3mtr

Technical information:
 Cable diameter: 3x1.5mm²
 Cable length: 1m/3m
 Cable type: H05VV-F
 Male plug: Australia Plug Type I (AS/NZS 3112:2011)
 Female Plug: IEC (C13)



QuickDMX D512S

50057 512 Channels



With the "D512S" interface it is possible to use Quick DMX software without any restriction for all 512 DMX channels. This interface can store one scene or chase for 512 DMX channels that will be played if connection with computer is lost.

Please note that Quick DMX D512S only works with Quick DMX software.

For general help you can also go to: <http://bit.ly/X4bDcv> a technical forum for Quick DMX. Tutorials can be found in this link: <http://bit.ly/1oHfq9m>

Technical information:

Stand Alone: Yes (one scene or chase)
 Operating System: Windows and Mac OSX
 External power supply: USB power adapter 5VDC (not included)
 DMX Connector: 3-pin
 Weight: 0.08 kg
 Size: 72 x 35 x 35mm

FEATURES:

- Metal road proof casing
- Power & Link indication LEDs at front panel
- Unlimited nr. of different fixtures
- Full 512 DMX channels
- MIDI triggerable by "learning" mode



QuickDMX D1024

50056 2x512 Channels, 40Hz refresh rate



With the "D1024" interface it is possible to use Quick DMX software without any restriction for all 1024 DMX channels. This interface can store one scene or chase for 1024 DMX channels that will be played if connection with computer is lost. Please note that Quick DMX D1024 only works with Quick DMX software.



For general help you can also go to: <http://bit.ly/X4bDcv> a technical forum for Quick DMX. Tutorials can be found in this link: <http://bit.ly/1oHfq9m>

Technical information:

Stand Alone: Yes (one scene or chase)
 Operating System: Windows and Mac OSX
 External power supply: USB power adapter 5VDC (not included)
 DMX Connectors: 3-pin
 Weight: 0.17kg
 Size: 84 x 75 x 40mm

FEATURES:

- Metal road proof casing
- Power & Link indication LEDs at front panel
- Unlimited nr. of different fixtures
- Full 1024 DMX channels
- MIDI triggerable by "learning" mode





Truss Booster RDM 1-6

50793 3-pole XLR

50794 5-pole XLR

The Truss Booster RDM is a compact and nifty solution for splitting and boosting your DMX or RDM signal. Mounting on truss or onto pipes is possible in various ways by using the bracket or by adding velcro straps to the 4 slots. A rubber protection-ring on either side of the rugged housing makes this booster ideal for road productions.

Technical information:

Input connectors: 3 Pole XLR M (50793)/5 Pole XLR M (50794)
 Output connectors: 6 x 3 Pole XLR F / 1 x 3 pole XLR F (Thru) (50793)
 Output connectors: 6 x 5 Pole XLR F / 1 x 5 pole XLR F (Thru) (50794)
 Power input: 100 ~ 240VAC, 50/60Hz
 Dimensions: 280 x 175 x 210 mm (LxWxH)
 Weight: 2 kg

FEATURES:

- Small Design for easy truss mounting
- DMX/RDM splitter for 6 outputs
- Powercon in /- Out
- Supports Remote Device Management (RDM) Protocol



NET-2/3 or NET-2/5 Pocket**50807** 2 Channel Artnet node, 3p XLR**50808** 2 Channel Artnet node, 5p XLR

The Showtec NET-2/3 Pocket and NET-2/5 Pocket nodes are cutting-edge network routing devices which convert ArtNET or sACN to DMX512 and back. The power input can be provided by POE which makes the 12V power supply superfluous.

A maximum of 1024 channels can be transported over a single CAT5. All settings can be done by the easy-to-use menu on the graphic display and buttons on the front.

Settings can also be arranged via the webbrowser possibility, which gives you (remote) access through your computer or laptop and your network. Default login account: Admin, password: Admin.

Technical information:

Configuration examples:

- ArtNet to 2x DMX output
- 2x DMX input to ArtNet
- Clone 1 DMX inputs to 1x DMX output and Artnet
- HTP/LTP Merge 2x ArtNet to DMX output
- HTP/LTP Merge DMX input and ArtNet to DMX output

DMX: 2x 3-pin or 2x 5-pin XLR
 Supported protocols: ArtNET, sACN, TCP/IPv4, DMX-512A
 Dimensions: 67 x 115 x 44 mm
 Power supply: 12VDC, 500mA POE
 Power consumption: 6W max.
 Operating temp: 0 to +40 °C
 Weight: 335gr

Connections:

Network: RJ45

FEATURES:

- Supports ArtNET and sACN protocol
- 1Gbps data speed
- 2 universes DMX input or output
- Web Setup Interface

**TR-512 Wallpanel****50824** RJ45

The TR-512 Wallpanel offers a ready-made solution to trigger your stored shows in the TR-512 DMX Recorder. Connect a normal RJ-45 cable between both, and you are good to go. By changing tech button settings in the TR-512, and changing a jumper on the backside, you can determine the playback reaction of your show when pressing the buttons. The subtle backlight in each key ensures users to clearly find the buttons even in the darkest environments.

Technical information:

Input connector: RJ-45
 Frontpanel: 85 x 85 x 7 mm
 Installation depth: 32 mm (without connector)

**19" 1U Socketstrip 7****91233** With breaker**91234** With Powercon input**Technical information:**

Power consumption: max 3680W
 Cable: 2m 3x1.5mm²
 Weight: 0.95 Kg
 IP rating: IP20
 Output: 7 x schuko
 Input: Fix cable schuko

**19" 1U Socketstrip****91235** 6 zones**Technical information:**

Power consumption: max 3680W
 Cable: 2m 3x1.5mm²
 Weight: 0.95 Kg
 IP rating: IP20
 Output: 6 x Schuko
 Input: Fix cable Schuko





WTF-F800

61130 800W Fogger

The Showtec WTF Series offers a range of Fog and Haze effect machines. The current range contains 2 foggers: the WTF-F800 and his big brother WTF-F1000. Both fog machines which can fill your venue with fog in no time. The WTF-FZ1500 produces a more subtle, almost haze-like smoke. The density of the smoke can be controlled through the built-in fan. The powerful WTF-J800 JET machine completes the WTF series. This machine can be used as a special FX on stage and the illumination of the LEDs give the vertical fog jet an extra dimension.

Technical information:

Power Supply:	220-240VAC, 50 / 60 Hz
Heater:	800W
Output:	2.500 cu.ft.
First heat up time:	4 minutes
Tank capacity:	0.8 liter
Fluid Consumption:	18ml / min (full output)
Include Remote:	YES
Remote Connection:	Fixed Cable
Cable Length Remote:	3 M
Power Input Connector:	Fixed Cable
Dimensions:	330 x 160 x 130 mm
Weight:	4 KG



FEATURES:

- Powerful Output
- Stylish design
- 800W Heater
- Remote control



WTF-F1000

61131 1000W DMX Fogger

The Showtec WTF Series offers a range of Fog and Haze effect machines. The current range contains 2 foggers: the WTF-F800 and his big brother WTF-F1000. Both fog machines which can fill your venue with fog in no time. The WTF-FZ1500 produces a more subtle, almost haze-like smoke. The density of the smoke can be controlled through the built-in fan. The powerful WTF-J800 JET machine completes the WTF series. This machine can be used as a special FX on stage and the illumination of the LEDs give the vertical fog jet an extra dimension.

Technical information:

Power Supply:	220-240VAC, 50 / 60 Hz
Heater:	1000W
Output:	10.000 cu.ft / min
First heat up time:	6 minutes
Tank capacity:	1.35 liter
Fluid Consumption:	72ml / min (full output)
Include Remote:	YES
Remote Connection:	fixed cable
Cable Length Remote:	3M
Power Input Connector:	fixed cable
Dimensions:	385 x 270 x 247 mm
Weight:	5.8 KG



FEATURES:

- Powerful Output
- Stylish design
- 1000W Heater
- Remote control

WTF-J800**61132 800W Fog-Jet LED**

The Showtec WTF Series offers a range of Fog and Haze effect machines. The current range contains 2 foggers: the WTF-F800 and his big brother WTF-F1000. Both fog machines which can fill your venue with fog in no time. The WTF-FZ1500 produces a more subtle, almost haze-like smoke. The density of the smoke can be controlled through the built-in fan. The powerful WTF-J800 JET machine completes the WTF series. This machine can be used as a special FX on stage and the illumination of the LEDs give the vertical fog jet an extra dimension.

Technical information:

Power Supply:	220-240VAC, 50 / 60 Hz
Heater:	800W
Light Source:	12 x 3W (4 Red, 4 Green, 4 Blue)
Output:	3 meters' height
First heat up time:	4.5 minutes
Tank capacity:	2.4 Liters
Fluid Consumption:	45ml / min
Include Remote:	YES, wireless remote W-2
Power Input Connector:	IEC
Dimensions:	385 x 270 x 247 mm
Weight:	6.3 KG

FEATURES:

- Powerful Output
- RGB LED Source
- 800W Heater
- DMX / Wireless Control

**M-7X****60770 1500W Pro CO2 Simulating RGBA Fogger**

The Antari M-7X is a professional upright fogger with a powerful output and RGBA LEDs to create a colorful CO2 effect. It can be used in horizontal and vertical, up and downwards position without problems. The mechanical design of M-7X is made for rentals because the fluid tank is kept in a separate compartment inside the machine. This ideal for transport, no need to take care of the position.

Technical information:

Input voltage:	240VAC, 50/60Hz
Power Consumption:	1550W
Initial Heat-Up Time:	5 min.
Fluid Consumption Rate:	150 ml / min
Tank Capacity:	2.4 litre
Control Options:	On-Board Control Panel, DMX, Remote
Remote:	W2 included
DMX Channels:	9
DMX Connections:	DMX 3+5 pin XLR
Power connection:	Neutrik PowerCon
Weight:	11,5 Kg
Dimensions (mm):	345 x 193 x 385

FEATURES:

- Horizontal, Vertical and downward operation
- Integrated RGBA LED system
- Closed fluid tank compartment
- Built-in colour chases





WTF-FZ1500

61133 1500W DMX Fazer

The Showtec WTF Series offers a range of Fog and Haze effect machines. The current range contains 2 foggers: the WTF-F800 and his big brother WTF-F1000. Both fog machines which can fill your venue with fog in no time. The WTF-FZ1500 produces a more subtle, almost haze-like smoke. The density of the smoke can be controlled through the built-in fan. The powerful WTF-J800 JET machine completes the WTF series. This machine can be used as a special FX on stage and the illumination of the LEDs give the vertical fog jet an extra dimension.

Technical information:

Power Supply:	220-240VAC, 50 / 60 Hz
Heater:	1450W
Output:	6.000 cu.ft. /min
First heat up time:	1.5 minutes
Tank capacity:	5 Liters
Fluid Consumption:	5.1 ml / min (full output)
Power Input Connector:	fixed cable
Dimensions:	427 x 295 x 237 mm
Weight:	15 KG

FEATURES:

- Controllable Output
- Stylish design
- 1450W Heater
- DMX control



FX Shot MKII

60906 Electric confetti shooter

Showtec's FX Shot MKII is an easy-to-use electric confetti shooter. They are designed to fire prefilled single use electric cannons, which are available in 50cm and 80cm. Confetti or streamers in various colours, even fluor UV and metallic colours are an option. The cannons contain a pressurized nitrogen cartridge which launches confetti up to 12 meters and streamers even 20 meters wide.

Attention:

The FX Shot will be activated by a 230V power source and can therefore be operated very easy by a 230V power switch like the Showtec DJ-Switch (50363). If you like to operate by DMX you can use a Showtec Relay Pack (50752) in combination with a Showtec DMX controller.

Technical information:

Size:	13 x 12 cm
Weight:	1.7 kg
Voltage:	230V
Power:	100W
Operation:	230V on/off or DMX by using a switch pack

FEATURES:

- Easy set-up and use
- Suited for 50cm and 80cm shooters
- Plug-and-play
- Powercon in/output





FX Blaster XL

61031 Electric confetti shooter

For big concerts, stadiums and festivals you need special FX equipment which perform in a big way. The Showtec FX Blaster is the designated tool for the job. With an awesome combined output of 25 mtr with CO2 and confetti, a capacity of 15kg of confetti per minute or even 20kg per 90 seconds, the FX Blaster is a magnificent eye-catcher which cannot be overlooked. Easy to handle, can be placed anywhere because no additional power is required to control it and with 4 different output angles you can direct the massive output where the action is.

Technical information:

Size (LxWxH): 66x38x135cm
 Weight : 56 Kg
 Power: CO2 gas (liquid)
 Control: Manual
 Consumption: Confetti
 Max. Distance: 25m
 Capacity: 10-15Kgs of confetti p/m
 Standard in flightcase, swivel wheels with brakes

Confetti and cryogenic effect
 4 Different output angles

Set includes:
 3/8 Manual Valve for FX Blaster
 CO2 high pressure hose 3/8 Male – Female, 3 meter
 CO2 bottle to hose connector



FX Ice Jet MKII

61002 CO2 Shooter

Showtec – also for great show effects! The Showtec FX Ice Jet MKII is a CO2 shooter which creates beautiful clouds of thick but quickly dissipating smoke in a true festival style. The FX Ice Jet only requires a CO2 bottle with dip-pipe to work and can be controlled remotely either by a relay pack or via a DMX switch.

Technical information:

Input Voltage: 230VAC, 50Hz
 Power consumption: 20W
 Control: 230V on/off switch, or by DMX relay pack
 Consumption: 0,5kg/s CO2 (use only CO2 bottle with dip pipe)
 Max distance: approx. 8m (depending on environmental temp and humidity)
 Dimensions: 130 x 80 x 130mm – Pipe: 205mm Base: 200 x 125mm
 Weight: 2,9Kg
 Input & output Thread: 3/8"
 Powercon in/output

General Safety Rules:

- It is very important to always read the manual before using these items.
- Always visually inspect every component carefully, and make sure they are in good condition and function properly before using them.
- Only use the CO2 Ice Jet if there are no people, animals or other objects in the direction of the output.
- Make sure children, unauthorised people or animals do not obtain access to the CO2 Jet
- Consult your gas supplier for full instructions with regarding to the CO2 bottle, and how to use.
- Only authorised persons may carry out working with the CO2 Jet





Mistique

60769 CO2 Hazer

The best special FX are the ones which are almost invisible but in the meantime create the perfect mood for your event. Presenting the Showtec Mistique CO2 Hazer. This hazer produces an extremely fine haze due to the combination of low pressurised CO2 and a high quality oil-based Mistique dedicated Hazer-liquid. The corresponding smoke particles of the Mistique are so fine that they don't cloud the stage, leave no residue on equipment or on stage, do not interfere with lighting plans and have a long-lasting effect. For TV-applications especially the Showtec Mistique CO2 Hazer embodies the perfect solution to many challenges. It produces a haze without disturbing any filming going on. The units are extremely silent because there is no pump to generate any kind of noise. The pressure of the CO2 is enough to create the desired effect on stage. Another advantage of the fine haze is its complete transparency. Only its effect is visible without adding any kind of unwanted colour to the stage. Showtec did call the hazer "Mistique" for a reason and seeing is believing.

Technical information:

Input Voltage: 220-240VAC, 50/60Hz
 Power Consumption: 1200W max
 Heating Time: under 8 minutes
 Maximum Output: 5000 cu.ft/min
 Output Direction: up, down, forward
 Output Regulation: 5-40psi
 Fan Speed: 0-100%
 Tank Capacity: 2.5 Liter
 Liquid Type: MHL-2 only
 Liquid Consumption: 120ml/hour (@40psi)
 Gas Type: CO2



FEATURES:

- Very even and thin haze ensures no visible cloudy effect on stage
- Customizable output direction gives extra flexibility
- Extreme silent operation due to CO2





CO2 3/8 Q-Lock Hose

61017 0,75m

High-pressure hose assembly, hose according to SAE 100R7 with inner jacket made of polyester, 2 braided inserts made of polyester fibre, outer jacket made of wear-resistant, UV and micro organism resistant polyurethane.
Length: 0.75mtr

Technical information:

Max pressure: 175 bar / 2537 psi
Safety ratio: 1:4
Inner shell material: Polyester
Outer shell material: Polyurethane
Internal diameter: 9,7mm
External diameter: 16,0mm
Min. Bend radius: 60mm
Input: male QLock
Output: female QLock
Length: 0,75m
Weight G/m: 155gr

These hoses meet/exceed standard SAEJ517 sec.
SAE100R7 - EN 855 - ISO 3949



CO2 Q-Lock Regulator

61019 1x Female Q-Lock

Pressure reducing valve with two manometers and quick connection Q-Lock

Technical information:

Max pressure: 10 bar / 145 psi
Input: 1x 21.8 thread
Output: 1x female Q-Lock
Material: Electrolytically galvanized steel & Chrome-plated brass
Weight: 840 Gr
Safety: ISO 7241-1 A



MHL-2 Mistique Hazer Liquid

60569 2 Liter

2 Liter of dedicated high quality oil-based Hazer liquid for the Mistique CO2 Hazer




Rotating truss holder for MAT-series

70883 Mammoth Stands

Steel rotating truss holder, specifically designed for the MAT-series stands from Mammoth. It can hold truss with a diameter up to 52mm and rotates in any direction, thus offering the freedom of place the truss any where

Technical information:
 Dimensions: 50 x 60 x 170 mm
 Slide diameter: 52x 52 mm
 Truss Holder diameter: 52 x 52 mm
 Weight: 0,83 Kg



Bannerclamp

75130 Black

75131 Silver

The bannerclamp can be used to easily fix banners to any truss or tube. Tube diameter 48-51mm.

Technical information:
 Tube diameter: 48 -51mm
 Material: Aluminium
 Colour: Black
 SWL: 50Kg.
 Weight: 0.33Kg
 Dimension: 75x125x55mm

FEATURES:

- Easily fix banners to any truss or tube



Deko-Molton, black, roll

89260 60m x 20cm

89261 60m x 40cm


89262 60m x 60cm

89263 60m x 80cm

89264 60m x 100cm

Deko-molton, very well suited to complement any stage setup where a skirt is needed, where a curtain is wanted during events to accentuate an area or simply cover up cable-work or it can be used as a temporary backdrop. The applications are endless and working with the deko-molton is easy. Each roll comes complete with three additional double sided tapes (length 20mtr). Available in 5 standard stage heights: 20cm , 40cm, 60cm, 80cm or 100cm. Length of each roll is 60mtr and the cloth is fire retardant according to DIN4102/B1 regulations.

Technical information:
 Width: 20cm/40cm/60cm/80cm/100cm
 Length: 60m
 Colour: Black
 Weight: 160 gram/m²
 Safety: Fire retardant according DIN4102/B1
 Packing: Including double sided tape (3 rolls of 20m)



Star Dream**40427** 144 White LEDs - incl. controller 6x3mtr**40428** 192 White LEDs - incl. controller 6x4mtr**40429** 128 RGB LEDs - incl. controller 6x3mtr**40430** 128 RGB LEDs - incl. controller 6x4mtr

The Showtec Star Dream is 6x3mtr and fully compatible with Wentex Pipe and drape. The backdrop curtain is equipped with velcro and eyelets. Divided into 8 groups are the white or RGB LEDs with their dedicated built-in controller. The Star Dream has several operation modes like Auto, Sound and Master/Slave. Controlling via DMX is also no issue (3 Pole XLR in- & out) . The Star Dream is made out of flame retardant molton in black.

Technical information:

Curtain
 Curtain material: Flame retardant molton
 Curtain size: 6x3m (40427, 40429)
 6x4m (40428, 40430)
 Light source: 144 pcs 5mm white LEDs (40427)
 192 pcs 5mm white LEDs (40428)
 128 pcs 5mm RGB LEDs (40429, 40430)
 Curtain colour: Black
 Curtain net weight: 12,5 kg

Controller
 Control: DMX, Auto, Sound, Master/Slave
 DMX channels: 5 channel or 12 channel mode
 DMX connector: 3 Pole XLR in- & out
 Power connector : Pro Power input
 Colour: Matt black
 Input voltage: 100-240V AC 50/60Hz
 Power consumption: 100W max.
 Dimensions: 180 x 150 x 50 mm (LxWxH)
 Weight: 1,2Kg

FEATURES:

- Certified Original Backdrop curtain with Velcro and eyelets
- White and RGB LEDs in 8 groups
- Built in controller





Voile CS Curtain

89460 300 x 300cm, Black

89461 300 x 300cm, White

89462 300 x 400cm, Black

89463 300 x 400cm, White

Voile is a semitransparent fabric which in combination with our popular Pipe & Drape system can create highly decorative effects.

The voile curtains are available in 2 sizes and 2 colours. Each curtain has Velcro on top in order to connect it directly to your Pipe & Drape. Moreover the Velcro is also equipped with contra-velcro strips which allows you to use one curtain as both pleated and unpleated drape.

Technical information:

Specifications:

Fabric:	Voile CS
Weight:	55 gr/m ²
Lead rope:	100 gram
Flame retardant:	B1 + M1 (EN 4102-B1)
Colour:	Black/White
Size:	300cm high, 300cm wide 400cm high, 300cm wide



Stabilizer Base with wheels



70030 Steel

Stabilizing steel base for truss featuring extendable legs and wheels for moving the truss easily. This new base will make all your jobs more comfortable. It is very versatile thanks to its adjustable legs, allowing the base to be placed everywhere, so you can put it against the wall just retracting one of its legs. All these characteristics make the accessory suitable for being used in many places. Additionally, it is made of steel and has four stabilizers which helps to level the base properly and in safety conditions in every surface (flat or uneven). It can be used with squared trusses of different sizes (10x10, 22x22, 29x29 and 40x40).

Technical information:

Dimensions folded:	590 x 590 x 170 mm
Dimensions folded out option 1:	740 x 740 x 170 mm
Dimensions folded out option 2:	900 x 900 x 170 mm
Weight:	14,5 Kg

Please note: no half spigots included!



The Moustache Single Tube Clamp

75120 Black

75121 Silver

The Moustache - Single Tube Clamp Black can be used to easily rig a single tube in the center of a truss, due to the innovative construction the clamp can be mounted without any tools. The Moustache clamp is suitable for the Pro30 Step/Pro30 Triangle/Pro30 Square Truss. Fix clamp – Black (productcode: 75123) available to fix the pipe to the truss.

Technical information:

Suitable for: Pro30 Step/Pro30 Triangle/Pro30 Square Truss
Tube diameter: 48 -51mm
Material: Metal
Colour: Black
SWL: 100Kg.
Weight: 1.27Kg
Dimension (closed): 250x170x17mm
Dimension (open): 332x220x17mm



Fixclamp



75123 Black

75122 Silver

The Fix Clamp can be used with the Moustache Clamp – Single Tube Clamp Black (ordercode 75120) to fix the single tube to truss.

Technical information:

Tube diameter: 48 -51mm
Spacing distance: 160mm (dimension = tube center to center)
Material: Aluminum
Colour: Black/Silver
SWL: 200Kg.
Weight: 0.93Kg
Dimension: 226x100x32mm



GIG-143 TAB

D2301 14 Channel digital mixer incl. dynamics & DSP


The GIG-143 TAB digital mixing console is the first 19" 3HE Rackmount digital mixing console in the GIG range from DAP-Audio. It is a compact digital mixing console that owns all the features of the bigger digital mixers available in the market. It has 8 XLR/TRS combo inputs and 3 TRS stereo inputs, all equipped with gate, compressor and a 4-band full parametric EQ on each input channel. The 2 analogue outputs feature a compressor and individual 31-band graphical EQ. Even though this compact digital mixer has a lot of features, DAP-Audio managed to design a user interface understandable for all users with or without any experience. To achieve this DAP-Audio added dedicated direct access buttons for all important features a sound engineer needs during his performance. This helps the user to go directly to the desired function without getting lost in complex menu structures. Direct control is essential in a live situation, therefore all the channels are equipped with an input fader and are always automatically patched to the main parameter of your selected functionality. This also gives the console an 'analogue' feel to the digital environment. The GIG-143 TAB features a bright OLED display, 4 dedicated AUX outputs plus a control room output, 1 built-in FX engine, 6 user definable DCA's and full internal 24-bit/48kHz sampling rate make this the most complete and interesting digital mixing console in its market segment.

Features:

- Bright OLED screen
- Easy to use software interface
- 8 direct access buttons for easy channel control
- Digital Gate/Compressor/4-band full parametric EQ on each input
- 31-band graphical EQ on main output
- 14 Analog inputs
- 4x AUX sends (pre/post switchable per channel)
- Separate control room output
- 24-bit FX engine
- Ultra-low noise discrete preamps with +48V Phantom Power
- High-definition ADC's (114dB dynamic range)
- 6x user definable DCA's
- Full 24-bit/48KHz sampling rate
- Separate volume controlled headphone outputs

Technical information:

Mono channels	
Mic Inputs:	XLR balanced
Line Input:	TRS balanced
Freq Response:	20Hz ~ 20kHz, +/- 1,5dB
Distortion (THD-N):	<0,01% @ 0dB, 22Hz ~22kHz
Max Input Level:	+20dBu
SNR:	< -108dB
Phantom Power:	+48V
Stereo Channels	
Line Input:	TRS balanced
Freq Response:	20Hz ~ 20kHz, +/- 1,5dB
Distortion (THD-N):	<0,01% @ 0dB, 22Hz ~22kHz
Max Input Level:	+20dBu
SNR:	< -108dB
EQ	
LowPass:	20Hz ~ 20kHz
Frequency Range:	20Hz ~ 20kHz
Gain:	0dBu +/- 18dB
Q-factor:	0,4 ~ 128
HighPass:	19,7Hz
Gate	
Threshold Range:	-75dB ~ 0dB
Attack Time:	0,5ms ~ 200ms
Release Time:	10ms ~ 1000ms
Ratio:	1:1 ~ 1:10 until gate
Compressor	
Threshold Range:	-30dB ~ +20dB
Attack Time:	10ms ~ 150ms
Release Time:	10ms ~ 1000ms
Ratio:	1:1 ~ 1:10 until limit
Gain:	0 ~ +24dB
Impedances	
Microphone input:	6,8K Ohm
Other Inputs:	27K Ohm
Other Outputs:	120 Ohm
Power Supply:	AC 100-240V 50Hz/60Hz
Power Consumption:	40W
Measurements:	483 (19") x 134 (3HE) x 321mm
Weight:	7,2Kg





FEATURES:

- Ultra-low noise discrete preamps with +48V Phantom Power
- High-definition ADC's (114dB dynamic range)
- Bright OLED Screen
- Digital Gate/Compressor/4-band full parametric EQ on each input
- Easy to use software interface



PURE

The DAP audio Pure Series produces the most Pure sound in its class. A bi-active lightweight speaker range consisting of a 12" full range, 15" full range speaker and a dedicated 18" active subwoofer. With these powerful cabinets you have the right tool for mobile and live sound, applicable for bands, DJs, presentations and more. The on board Class-D bi-amp amplification offers pure power and keeps these cabinets lightweight and easy to handle. Pure series are equipped with a sophisticated 24bit, 96Khz DSP Processor giving the user the opportunity to select presets for Live, Voice, DJ, Monitor applications and still being able to tune, store and recall your own sound settings. Tools like running hours, editable company name and delay settings, all lockable make the Pure Series ideal for rental as well. It offers two combined line microphone inputs with a link output which can be set to channel 1, channel 2 or a mix of both. The advanced protection system including thermal, overload protection and a custom compressor limiter will make sure that Pure keeps delivering on any event.



Pure-12A

D3721 12" Active Cabinet with DSP

If you are looking for a speaker that packs a punch, then the DAP Audio Pure-Series is just what you have been looking for. An active full range 12" speaker which can be tweaked perfectly via the 24-bit DSP-module, accessible through the integrated LCD display. 2 separate XLR-inputs offer the possibility of connecting two audio-sources. Very well suited for mobile applications, rental companies and also fixed installation. The cabinet is constructed out of birch plywood with a scratch resistant finish which can handle the rough live on the road.

Technical information:

System:	2-way active full range
AMP Power:	600 W Continuous, Bi-AMP(Class D 500 W LF, 100 W HF), 1200W Peak
Speaker:	12" Woofer and 1" Compression driver
Frequency Response (+/-6dB):	45 Hz - 20 kHz
MAX SPL @ 1m:	126dB
Crossover frequency:	1,7 KHz
Dispersion(-6dB):	75° Horizontal / 50° Vertical
Cooling:	forced cooling inside
Audio Connector:	XLR In- and output / 3,5mm mini-jack Aux in
External Controls:	Controllable DSP trough LCD interface
DSP Processor:	24 bit, 24bit/96kHz Audio conversion AD/DA
Electronic Protections:	Thermal / Convection-Fan / Overload / Digital Limiter / Compressor
Mains Connector:	ProPower Connector In & Out
Power Supply:	120/230VAC, 50Hz/60Hz
Power Consumption:	Max 600W
Enclosure Construction:	12mm Birch Plywood, Water Resistant coating, 1,5mm metal grill with foam
Mounting:	35mm pole mount
Dimensions (HxWxD):	550 x 365 x 356 mm
Net Weight:	23 Kg / 50,7 lbs



FEATURES:

- 600W RMS
- Active speaker system
- 24-bit DSP Processor with LCD-display
- 2ch Input mixer
- 35mm pole mount



Pure-15A**D3720 15" Active Cabinet with DSP**

The DAP Pure 15A is a bi-amped 15" + 1" lightweight cabinet with DSP. With a size of only 640 x 426 x 410 this is a very compact powerful and versatile 15" cabinet suitable for mobile and live applications. The cabinet is constructed out of birch plywood with a scratch resistant finish which can handle the rough live on the road.

Technical information:

System:	2-way active full range
AMP Power:	600 W Continuous, Bi-AMP(Class D 500 W LF, 100 W HF), 1200W Peak
Speaker:	15" Woofer and 1" Compression driver
Frequency Response (+/-6dB):	40 Hz - 20 kHz
MAX SPL @ 1m:	128dB
Crossover frequency:	1,7 KHz
Dispersion(-6dB):	75° Horizontal / 50° Vertical
Cooling:	forced cooling inside
Audio Connector:	XLR In- and output / 3,5mm mini-jack Aux in
External Controls:	Controllable DSP trough LCD interface
DSP Processor:	24 bit, 24bit/96kHz Audio conversion AD/DA
Electronic Protections:	Thermal / Convection-Fan / Overload / Digital Limiter / Compressor
Mains Connector:	ProPower Connector In & Out
Power Supply:	120/230VAC, 50Hz/60Hz
Power Consumption:	Max 600W
Enclosure Construction:	15mm Birch Plywood, Water Resistant coating, 1,5mm metal grill with foam
Mounting:	35mm pole mount
Dimensions (HxWxD):	640 x 426 x 410 mm
Net Weight:	29 Kg / 64 lbs

FEATURES:

- 600W RMS
- Active speaker system
- 24-bit DSP Processor with LCD-display
- 2ch Input mixer
- 35mm pole mount

**Pure-18AS****D3725 18" Active Subwoofer with DSP**

DAP Audio's Pure-Series offers an active 18" subwoofer with 1600W Class-D power which complements the 12" and 15" unit perfectly. Equipped with a 24-bit DSP-module accessible through a large LCD-display, you have the possibility to determine perfectly the sound you require for your venue. If you are looking for a way to add Pure bass to your party-place, then here's your answer.

Technical information:

System:	Active subwoofer
AMP Power:	800 W Continuous Class D, 1600W Peak
Speaker:	18" Heavy duty Woofer with 4" Voicecoil
Frequency Response (+/-6dB):	35 Hz - 150 Hz (High-pass dependant)
MAX SPL @ 1m:	129dB
Crossover frequency:	DSP programmable
Dispersion(-6dB):	360° Horizontal / 180° Vertical
Cooling:	forced cooling inside
Audio Connector:	XLR In- and output
External Controls:	Controllable DSP trough LCD interface
DSP Processor:	24 bit, 24bit/96kHz Audio conversion AD/DA
Electronic Protections:	Thermal / Convection-Fan / Overload / Digital Limiter / Compressor
Mains Connector:	ProPower Connector In & Out
Power Supply:	120/230VAC, 50Hz/60Hz
Power Consumption:	Max 600W
Enclosure Construction:	18mm Birch Plywood, Water Resistant coating, 1,5mm metal grill with foam
Mounting:	35mm/M12 pole mount
Dimensions (HxWxD):	650 x 520 x 600 mm
Net Weight:	33 Kg / 72,7 lbs

FEATURES:

- 800W RMS, 1600W Class-D
- Active speaker system
- 24-bit DSP Processor with LCD-display
- 2ch Input mixer
- M12/35mm pole mount





EVO 5A

D3688 Active speaker set, 25W Black

D3689 Active speaker set, 25W White

The DAP Audio EVO series loudspeaker range is designed for fixed audio installations and a wide range of applications. EVO series combines an elegant design with high fidelity audio in a wide variety of cabinet sizes. This range of 2-way cabinets is available as low impedance or with line transformer to serve both small and large installs. The included multi angled bracket offers a fast and easy installation and gives optimal orientation for both horizontal and vertical mounting. DAP audio Evo series are the perfect solution to fulfill installations in environments such as restaurants, retail stores, pubs, or even clubs thanks to their high performance components and extremely wide coverage. The EVO series are available as standard models in various wattages and as 100V-range.

Technical information:

Speaker system:	Active 2-way Full Range
Continues power:	2x25Watt
Connection:	Balanced / Unbalanced
Sensitivity W/m:	89dB
LF Driver:	5,25" Woofer
HF Driver:	1" Mylar Dome Tweeter
Dispersion:	110 x90° HxV
Frequency Response:	80Hz-20.000Hz (+/-3dB)
Mounting:	60° Multi angled bracket
Construction:	ABS
Grill material:	Steel
Dimensions:	252 x 163 x 163mm
Weight:	5,9 Kg
Approvals:	CE

FEATURES:

- Built-in amplifier
- Multi angled Brackets
- Fast and easy installation
- Balanced inputs



EVO 6A

D3690 Active speaker set, 35W Black

D3691 Active speaker set, 35W White

The DAP Audio EVO series loudspeaker range is designed for fixed audio installations and a wide range of applications. EVO series combines an elegant design with high fidelity audio in a wide variety of cabinet sizes. This range of 2-way cabinets is available as low impedance or with line transformer to serve both small and large installs. The included multi angled bracket offers a fast and easy installation and gives optimal orientation for both horizontal and vertical mounting. DAP audio Evo series are the perfect solution to fulfill installations in environments such as restaurants, retail stores, pubs, or even clubs thanks to their high performance components and extremely wide coverage. The EVO series are available as standard models in various wattages and as 100V-range.

Technical information:

Speaker system:	Active 2-way Full Range
Continues power:	2x35Watt
Connection:	Balanced / Unbalanced
Sensitivity W/m:	90dB
LF Driver:	6,5" Woofer
HF Driver:	1" Mylar Dome Tweeter
Dispersion:	110 x90° HxV
Frequency Response:	50Hz-20.000Hz (+/-3dB)
Mounting:	60° Multi angled bracket
Construction:	ABS
Grill material:	Steel
Dimensions:	302 x 196 x 193mm
Weight:	8,8 Kg
Approvals:	CE

FEATURES:

- Built-in amplifier
- Multi angled Brackets
- Fast and easy installation
- Balanced inputs



EVO 8A

D3692 Active speaker set, 80W Black

D3693 Active speaker set, 80W White

The DAP Audio EVO series loudspeaker range is designed for fixed audio installations and a wide range of applications. EVO series combines an elegant design with high fidelity audio in a wide variety of cabinet sizes. This range of 2-way cabinets is available as low impedance or with line transformer to serve both small and large installs. The included multi angled bracket offers a fast and easy installation and gives optimal orientation for both horizontal and vertical mounting. DAP audio Evo series are the perfect solution to fulfill installations in environments such as restaurants, retail stores, pubs, or even clubs thanks to their high performance components and extremely wide coverage. The EVO series are available as standard models in various wattages and as 100V-range.

Technical information:

Speaker system:	Active 2-way Full Range
Continues power:	2x80Watt
Connection:	Balanced / Unbalanced
Sensitivity W/m:	92dB
LF Driver:	8" Woofer
HF Driver:	1" Silk Dome Tweeter
Dispersion:	100 x90° HxV
Frequency Response:	40Hz-20.000Hz (+/-3dB)
Mounting:	60° Multi angled bracket
Construction:	ABS
Grill material:	Steel
Dimensions:	385 x 250 x 227mm
Weight:	13,5 Kg
Approvals:	CE



FEATURES:

- Built-in amplifier
- Multi angled Brackets
- Fast and easy installation
- Balanced inputs



Xi MKII Speaker-series

powered by
CELESTION



Presenting the Xi MKII series, a loudspeaker range for fixed audio installations, redesigned from the Xi- installation speakers with significant changes. Major change is the use of a Celestion HF Driver which enhances the sound performance of the unit extensively. The cabinet and grill have been redesigned as well to have a contemporary and elegant look.

Besides the looks and sound quality it also excels in installer-solutions with versatile installation possibilities: optional U-shape brackets, screw threads for use of flying eyes and to fit most common wall mount brackets. No inner adapter applied and a recessed speakon chassis completes the perfect design for an install cabinet. Finished with a scratch resistant paint and a MagTag metal grill, which can be detached without tools, fast and easily. The Xi-5MKII and Xi-6MKII are 16 Ohm to accommodate

1. Intro

The Xi-MKII series meets today's standards and is very well equipped for a wide variety of indoor applications such as restaurants, cafes, clubs, health centres, theme parks or hospitality areas. Anywhere where an outstanding sound quality and a compact high pressure level speaker are required.

2. Celestion inside

The entire Xi-MKII Series has been equipped with Celestion HF drivers which is a major improvement on the sound performance of each unit. Almost 100 years ago Celestion started to manufacture innovative and reliable loudspeakers. This quality and dedication to perfection was what we needed to complete the Xi-MKII Series. To optimize the magnetic, acoustic and electro mechanical design FEA, Finite Element Analysis, has been used. For the Xi-MKII Series we used the Celestion 1" exit light weight, low-profile ferrite magnet compression driver with 1" copper clad aluminium voice coil. Each driver is equipped with a single piece PETP film diaphragm and surround.

3. Multiple mounting options

Mounting the Xi-MKII series speakers is easy due to a couple of options. Model specific M8 screw threads for the use of flying eyes or M6 for an additional bracket. These threads can be found on two sides, giving you the possibility of installing the speaker either horizontally or vertically. A nifty

installations with larger quantities. Xi-8MKII and Xi-10MKII have rotatable horns which makes the use in both horizontal and vertical position possible. The high powered subwoofer has a ultra-compact design so it will fit in every location and with the optional slim line wall bracket it is possible to mount the subwoofer tight to a wall.

The Xi-MKII series meets today's standards and is applicable for a wide variety of indoor applications such as restaurants, cafes, clubs, health centers, theme parks, hospitality areas and anywhere where an outstanding sound quality and a compact high pressure level speaker are required. Xi MKII series cabinets are available in black and white.


feature is that you can position the logo on the grill based on the placement of the enclosure. An optional U-shaped bracket is available with which the speaker can be installed close to the wall. To make sure that the speakon connectors will not take up that space, the speakon chassis are recessed, the perfect design for an install cabinet. Third option for a fixed installation is the possibility of attaching a wall-bracket to the backside of the speaker. For every installation-challenge the right solution.

4. Detachable MagTag grill

The speakers have been equipped with MagTags, very small magnetic plates on the enclosure which keep the metal grill firmly and completely fitting in place. No tools needed, simply take the grill off manually. Ideal for maintenance and adjustment of the Xi-8MKII and Xi-10MKII rotatable horn.

5. Rotatable 90° x 60° horn

The Xi-8MKII and Xi-10MKII units have a rotatable 90°x60° horn. This makes it possible to place the enclosure vertically or horizontally, without compromising the sound quality. The DAP Logo on the detachable grill can be placed horizontally or vertically as well. This feature enables the ideal installation in any situation.



6. 16 ohm models

The Xi-5MKII and Xi-6MKII are 16 ohm models. This means that these two models are very well suited to use with larger quantities and only one amp. The ideal solution where compact cabinets and a good sound distribution is needed.

7. High pressure handling

All the Xi-MKII enclosures are equipped with a uniquely designed bass-reflex port. This makes sure that even at high power levels the mechanical movement of the cone stays under control. In combination with the optimized high-pass filter, the new Xi-MKII series of speakers can take a lot of power and reach high sound pressure levels. They can truly stand their ground and will not give in.

8. Compact subwoofer

The Xi-28B is a compact lightweight subwoofer designed to be combined with the Xi-series top cabinets. The subwoofer is equipped with 2 pcs 8" speakers and needs to be operated with an active crossover. Together with the optional Xi-28B bracket and the recessed Speakon chassis the subwoofer can be installed flat against the wall which makes it very suitable for situations where space is limited. Based on the position of the subwoofer, the logo on the metal grill can be rotated in the desired and matching position.

9. Available models

From the small compact Xi-5MKII and Xi-6MKII, ideal for larger areas and as background speakers, to the Xi-8MKII and Xi-10MKII with the rotatable horn, the Xi-MKII offers the right solution for any installation challenge. The complete Xi-MKII series is available in black and white and can be used as full range cabinets without the need of an additional bass cabinet. The Xi-82B can be added when extra low is needed.





Xi-5 MKII

D3444 5,25" / 1" Full range installation cabinet black

D3445 5,25" / 1" Full range installation cabinet white

The smallest member of the Xi-MKII family, with a 5.25" LF driver and a 1" Celestion HF driver. Recessed speaker connectors and multiple mounting options. This is a 16 ohm speaker which facilitates the use of multiple speakers. Please note that the corresponding hanging brackets are available as option; D3422HB for black and D3422WHB for white

Technical information:

Speaker system:	2-way
Continuous power:	125 Watt
Program power:	250 Watt
Peak power:	500 Watt
Impedance:	16 Ohm
Sensitivity W/m (Full Space):	93 dB
Peak SPL at 1 m (Theoretical):	120 dB
LF Driver:	5,25"
HF Driver:	1" Celestion
Dispersion (HxV):	90° x 60°
Freq. Response (-3 dB):	80 – 20.000 Hz
Freq. Range (-10 dB):	60 – 20.000 Hz
Recommended High Pass Filter:	75 Hz, BW-24
Mounting:	M6 screw-threads for optional brackets
Connectors:	Speakon in & thru
Construction:	Wood
Grill material:	Steel
Dimensions :	225 x 205 x 275 mm
Weight:	4.9 Kg
Approvals:	CE

FEATURES:

- 16 Ohm
- Celestion Driver
- Multiple mounting options
- Smooth frequency response
- Detachable MagTag metal grill



Xi-6 MKII

D3446 6,5" / 1" Full range installation cabinet black

D3447 6,5" / 1" Full range installation cabinet white

The 2nd enclosure from the Xi-MKII family, a 2-way speaker with a 6.5" LF driver and a 1" Celestion HF driver. Recessed speaker connectors and multiple mounting options. This is a 16 ohm speaker which facilitates the use of multiple speakers. Please note that the corresponding hanging brackets are available as option; D3423HB for black and D3423WHB for white



Technical information:

Speaker system:	2-way
Continuous power:	175 Watt
Program power:	300 Watt
Peak power:	700 Watt
Impedance:	16 Ohm
Sensitivity W/m (Full Space):	92 dB
Peak SPL at 1 m (Theoretical):	122 dB
LF Driver:	6,5"
HF Driver:	1" Celestion
Dispersion (HxV):	90° x 60°
Freq. Response (-3 dB):	80 – 20.000 Hz
Freq. Range (-10 dB):	60 – 20.000 Hz
Recommended High Pass Filter:	75 Hz, BW-24
Mounting:	M6 screw-threads for optional brackets
Connectors:	Speakon in & thru
Construction:	Wood
Grill material:	Steel
Dimensions:	250 x 226 x 333 mm
Weight:	6 Kg
Approvals:	CE

FEATURES:

- 16 Ohm
- Celestion Driver
- Multiple mounting options
- Smooth frequency response
- Detachable MagTag metal grill



Xi-8 MKII**D3448** 8" / 1,375" Full range installation cabinet black**D3449** 8" / 1,375" Full range installation cabinet white

The 2-way Xi-8MKII installation speaker offers an 8" LF driver and a 1.4" Celestion HF driver. Various mounting options which have been expanded by making the horn rotatable. With this option you have the choice of mounting the speaker vertically or horizontally. This makes the Xi-8MKII a very versatile model which suits almost every space. The corresponding hanging brackets are optional: D3424HB for black and D3424WHB for white

Technical information:

Speaker system:	2-way
Continuous power:	250 Watt
Program power:	500 Watt
Peak power:	1000 Watt
Impedance:	8 Ohm
Sensitivity W/m (Full Space):	95 dB
Peak SPL at 1 m (Theoretical):	125 dB
LF Driver:	8"
HF Driver:	1" Celestion
Dispersion (HxV):	90° x 60°
Freq. Response (-3 dB):	55 – 20.000 Hz
Freq. Range (-10 dB):	55 – 20.000 Hz
Recommended High Pass Filter:	55 Hz, BW-24
Mounting:	M6 screw-threads for optional brackets M8 screw-threads for flying eyes
Connectors:	Speakon in & thru
Construction:	Wood
Grill material:	Steel
Dimensions:	290 x 263 x 430 mm
Weight:	10,7 Kg
Approvals:	CE

**FEATURES:**

- Celestion high driver
- Rotatable 90° x 60° horn
- Multiple mounting options
- Smooth frequency response
- Detachable MagTag metal grill

**Xi-10 MKII****D3450** 10" / 1,375" Full range installation cabinet black**D3451** 10" / 1,375" Full range installation cabinet white

The 2-way Xi-10MKII installation speaker offers an 10" LF driver and a 1.4" Celestion HF driver. Various mounting options which have been expanded by making the horn rotatable. With this option you have the choice of mounting the speaker vertically or horizontally. This makes the Xi-8MKII a very versatile model which suits almost every space. The corresponding hanging brackets are optional: D3425HB for black and D3425WHB for white. The metal grill is detachable and very easy to handle due to the MagTag principle.

Technical information:

Speaker system:	2-way
Continuous power:	300 Watt
Program power:	600 Watt
Peak power:	1200 Watt
Impedance:	8 Ohm
Sensitivity W/m (Full Space):	96 dB
Peak SPL at 1 m (Theoretical):	127 dB
LF Driver:	10"
HF Driver:	1.4" Celestion
Dispersion (HxV):	90° x 60°
Freq. Response (-3 dB):	45 – 18.000 Hz
Freq. Range (-10 dB):	40 – 20.000 Hz
Recommended High Pass Filter:	40 Hz, BW-24
Mounting:	M6 screw-threads for optional brackets M8 screw-threads for flying eyes
Connectors:	Speakon in & thru
Construction:	Wood
Grill material:	Steel
Dimensions:	350 x 300 x 528 mm
Weight:	14 Kg
Approvals:	CE

**FEATURES:**

- Celestion high driver
- Rotatable 90° x 60° horn
- Multiple mounting options
- Smooth frequency response
- Detachable MagTag metal grill





Xi-28 MKII

D3452 Installation subwoofer black

D3453 Installation subwoofer white

The Xi-28B MKII is a compact lightweight subwoofer designed to combine with the Xi-series top cabinets. Together with the optional Xi-28B bracket it can be installed flat against the wall which makes it very suitable for situations where space is limited. For optimal performance it needs an high- and low pass processed amplification. The two 8" speakers and the sophisticated bass reflex horn housing offer a very powerful precise bass sound reproduction with high sound pressure levels.

Technical information:

Speaker system:	Dual bass reflex sub
Continuous power:	400 Watt
Program power:	800 Watt
Peak power:	1600 Watt
Impedance:	4 Ohm
Sensitivity W/m (Half Space):	100 dB
Peak SPL at 1 m (Theoretical):	132 dB
LF Driver:	2x 8"
Dispersion (HxV):	360° x 180°
Freq. Response (-3 dB):	45 – 4,000 Hz
Freq. Range (-10 dB):	40 – 4,500 Hz
Recommended High Pass Filter:	45 Hz, BW-24
Recommended Low Pass Filter:	110 Hz, LR-24
Mounting:	Floor / Optional bracket
Connectors:	Speakon in
Construction:	Wood
Grill material:	Steel
Dimensions(W x H x D):	520 x 240 x 540 mm
Weight:	17Kg
Approvals:	CE

FEATURES:

- Double 8" 4 Ohm compact sub
- Natural high pressure bass reproduction
- Extreme tight mountable
- Recessed speakon chassis

CS-850S

D6588 50W 8" Ceiling Subwoofer

Public address 100V 8" subwoofer producing a frequency range between 28 to 200Hz and a perfect addition to your current setup where lower frequencies are required. Please note to determine and measure precisely where to install the subwoofer. Mounting depth of the speaker is 180mm while the mounting hole should be 260mm

Tip: the housing is ABS and the colour is a neutral white which offers the possibility to paint the frame and the grille to match the interior. Please note to paint both the frame and the grille before installing them.




Technical information:

Power taps:	100V/70V/50W/30W/15W/5W
Impedance:	8Ω
Line Voltage:	100V
Speaker size LF:	8"
Frequency response:	28-200Hz
Sensitivity:	90dB
Material:	ABS
Colour:	White
IP rating:	IP-40
Mounting Hole:	Ø 260 mm
Dimensions (LxWxH):	260 x 175
Weight:	3 Kg

FEATURES:

- Built-in amplifier
- Multi angled Brackets
- Fast and easy installation
- Balanced inputs



PSS-110 MKIII**D2611 10" Portable Battery Powered Soundsystem**

The Dap Audio PSS-110 MKIII is the successor of the PSS-series with a complete new design in a lightweight ABS housing. The PSS-110 MKIII is a complete portable PA system powered by an internal battery. When it is used on mains power the battery will be charged automatically. The built-in charger has an overload protection circuit and a battery level indicator. The PSS-110MKIII is equipped with a USB player, a four channel audio mixer for microphone and line signals and a wireless microphone. The mixer has master volume, bass and treble control and a talk over function. To connect the PSS-110 MKIII with a second PA system it has a dedicated line output. It is an all-in-one concept that is very easy to use at events and places where you don't have access to a main power supply like:

- Fair events
- Theme parks
- Sport events
- Outdoor church services
- Street musicians
- Product presentations

Technical information:

Power Supply:	110V / 240VAC, 50/60Hz
Battery:	22.2V (Lithium battery)
System Type:	2-Way Active Vented Speaker
Transducer Low:	10" Woofer, 1.5" Voice coil
Transducer driver:	1" Ferrite Driver, 1" Voice coil
Horn Coverage:	90° H x 45° V
Frequency Response(-6dB):	65Hz-20KHz
Crossover Frequency:	5KHz
Max SPL:	117dB Max
AMP Power Output: RMS:	200W(AC)(LF-Class D 135W&HF-Class D 65W)
Equalizer Controls:	BASS: ±10dB (at 100Hz) TREBLE: ±10dB (at 10kHz)
External Controls:	Master Volume Controls : Mic & Line
AUX each Volume Controls:	Wireless Volume Controls; Voice Priority Switch;
Power Indicators:	Recharged Indicators; Battery Level indicators;
	RF Signal Indicators
Voice Priority:	MIC1 and Wireless
Signal to noise ratio:	Mic: >70dB
Line:	>75dB
Battery charge time:	Less than 5 hours
Battery use time:	More than 3 hours (Regular Play)
Wireless Frequency band:	615 - 637MHz
Built-in player:	MP3 – USB Player
Enclosure Construction:	Plastic cabinet, trapezoidal, metal grille, rubber foot, handle.
Mounting:	35,5mm standard pole-mount
Dimensions(HxWxD):	568 x 300 x 300mm
Net Weight:	12.8 Kg

**FEATURES:**

- Main power & battery operation
- Built-in battery charger with overload protection
- All in one concept: USB player, mixer and wireless mic
- Trolley model makes transportation easy



Case for Followspot 120W

D7059 Flightcase



Dedicated flightcase for the Showtec Followspot 120W including stand

Technical information:	
Dimensions:	890 x 528 x 439 mm (incl. wheels)
Wheels:	4x 100m swivel (4x brake)

Case for Chimp 100 + Touchscreen

D7264 Premium Line



A special all-in-one solution for combining the Infinity Chimp 100 and a touchscreen. Recommended screen size is 22 inch and maximum thickness is 70mm.

Equipment not included.

Technical information:	
Dimensions:	700 x 630 x 320mm
LCD compartment:	550 x 410 x 70mm (max)
Wheels:	yes
Touchscreen:	none
Weight:	46kg

Case for 2x Vintage Blaze '55

D7054 Flightcase



Dedicated sturdy flightcase for 2pcs Showtec Vintage Blaze '55

Technical information:	
Dimensions:	884 x 781 x 803 mm (incl. wheels)
Wheels:	4x 100m swivel (2x brake)

Case for 4x Pulse Pixel Bar 16

D7042 Value Line



Dedicated flightcase for 4pcs Showtec Pulse Pixelbar 16 Q4

Technical information:	
Dimensions:	988 x 472 x 312 mm
Wheels:	2 x Built-in wheels

Case for 8x Pulse Pixel Bar 16

D7053 Flightcase

Dedicated sturdy flightcase for 8pcs Showtec Pulse Pixel Bar 16 Q4

Technical information:

Dimensions: 1182 x 489 x 627 mm (incl. wheels)
Wheels: 4x 100m swivel (2x brake)



Case for 8x Candela Pix 50

D7057 Flightcase

Dedicated flightcase for 8pcs Showtec Candela Pix 50

Technical information:

Dimensions: 1107 x 560 x 480 mm (incl. wheels)
Wheels: 4x 100m swivel (2x brake)



Case for 8x Candela Pix 100

D7058 Flightcase

Dedicated flightcase for 8pcs Showtec Candela Pix 100, including compartment for cables and accessories

Technical information:

Dimensions: 1250 x 671 x 732 mm (incl. wheels)
Wheels: 4x 100m swivel (2x brake)



Charger Case for EventSpot 1600 Q4

D7300 Flightcase for 6 pcs

The Charger Case for the EventSpot 1600 Q4 holds up to 6 pieces of the EventSpot 1600 Q4. It has a built-in charger which makes it very easy to load your Eventspots without the need of taking them out of the flight case. Just plug the case by the Neutrik Powercon connector to the socket and all 6 EventSpots start loading. Built-in safety features for overheating ensures safety at all times.

Equipment not included.

Technical information:

Specifications Flightcase
Dimensions: 653 x 576 x 500 mm
Weight: 45,0 Kg (without spots)
(power cable not included)



Case for 2x Furion S201

D7265 Premium Line



High grade materials, Penn-Elcom hardware all around and a foam interior to match the shapes of 2 Infinity Furion S201 units perfectly. The Premium line flightcase is ideal for transportation and handling of the Furion units. Inside the flightcases you will also find the dedicated Infinity stage tool, a nifty tool to help you during rigging.

Equipment not included.

Technical information:	
Dimensions:	600 x 800 x 700mm
Weight:	41kg
Wheels:	4x 100mm swivel (2x brake)

Case for 2x Furion S401

D7266 Premium Line



The Premium line flightcases all excel in the materials used. 9mm high grade plywood, combined with Penn-Elcom hardware and CNC machined foam interiors to keep the Infinity Furion units safe during handling, rigging and transportation form the combination every rigger or rental company is looking for. Dedicated case for 2 units of Infinity Furion S401 and, as a small extra, including 1pcs of the Infinity Stage tool to make rigging life a bit easier.

Equipment not included

Technical information:	
Dimensions:	600 x 800 x 700mm
Weight:	40kg
Wheels:	4x 100mm swivel (2x brake)

Case for 2x Furion S601

D7267 Premium Line



High grade materials, Penn-Elcom hardware all around and a foam interior to match the shapes of 2 units of Infinity Furion S601, the Furion flagship, perfectly. The Premium line flightcase is ideal for transportation and handling of the Furion units. Inside the flightcases you will also find the dedicated Infinity stage tool, a nifty tool to help you during rigging. Equipped with 4x 100mm swivel wheels, 2 of which have brakes.

Equipment not included

Technical information:	
Dimensions:	600 x 800 x 700mm
Weight:	41kg
Wheels:	4x 100mm swivel (2x brake)

Case for 4x Stage Blinder 4

D7056 Flightcase



Dedicated flightcase for 4 pcs Showtec Stage Blinder 4 LED (item-code 30783)

Technical information:	
Dimensions:	822 x 592 x 658 mm (incl. wheels)
Wheels:	4x 100m swivel (4x brake)

Case for 4x Helix S5000 incl. accessories

D7269 Premium Line

Flightcase for 4pcs Helix S5000 with separate compartments for the corresponding optional accessories. Four mountingbrackets, four tophats, four barndoors, eight beamshapers and room for clamps, cables, quicklocks and safety cables. The perfect transportation method to make sure that your Helix units stay save and complete on the road.

Equipment not included.




Technical information:

Dimensions: 1200 x 700 x 898mm
 Weight: 41Kg
 Wheels: 4x 100mm swivel (2x brake)

Case for 8x DMT Premiere Series

D7293 Premium Line

Sturdy flightcases, specifically constructed for easy handling and stacking Premiere LED screens horizontally. The flightcase can house a total of 8 Premiere screens of 100x50cm. The preformed foam keeps the screens safe during transportation and handling. Four strong swivel wheels have all been fitted with brakes. Two additional drawers have been added as well to store cables, connectors or rigging accessories. Tip: for vertical stacking you can use the D7290 case. Equipment not included.



Technical information:

Dimensions: 1200 x 605 x 1160 mm (incl wheels)
 Wheels: 4x 100mm swivel (all brake)

Case for 6x E-series LED Screen 100x50

D7292 Premium Line

Dedicated flightcase for the DMT E-Series LED screens 100x50cm. The case can house up to 6 screens, has been fitted with high-impact foam and Penn-Elcom hardware all around.

Equipment not included



Technical information:

Dimensions: 1100 x 790 x 731 mm (incl wheels)
 Wheels: 4x 100mm swivel (2 brake)



XLR 3p. Connector Male TOP

NC3MXTOP Gold contacts, Stainless steel Housing



NEUTRIK
CONNECTING THE WORLD

XLR 3p. Connector Female TOP

NC3FXTOP Gold contacts, Stainless steel Housing



NEUTRIK
CONNECTING THE WORLD

XLR 5p. Connector Male TOP

NC5MXTOP Gold contacts, Stainless steel Housing



NEUTRIK
CONNECTING THE WORLD

XLR 5p. Connector Female TOP

NC5FXTOP Gold contacts, Stainless steel Housing



NEUTRIK
CONNECTING THE WORLD

XLR 3p. Chassis Male TOP

NC3MDXTOP Gold contacts, Black Housing



NEUTRIK
CONNECTING THE WORLD

XLR 3p. Chassis Female TOP

NC3FDXTOP Gold contacts, Black Housing



NEUTRIK
CONNECTING THE WORLD

XLR 5p. Chassis Male TOP

NC5MDXTOP Gold contacts, Black Housing



NEUTRIK
CONNECTING THE WORLD

XLR 5p. Chassis Female TOP

NC5FDXTOP Gold contacts, Black Housing



NEUTRIK
CONNECTING THE WORLD

IP65 Sealing cover for NC3MDX-TOP

SCMDXTOP Black



NEUTRIK
CONNECTING THE WORLD

IP65 Sealing cover for NC3FDX-TOP

SCFDXTOP Black



NEUTRIK
CONNECTING THE WORLD

Eco Cable Tie

D9578
12 x 200mm / 100 Pcs



Snap Fastener with Clip

D9579
5 Pcs




Velcro Cable Tie on Roll

89102
Black, 20mm x 4500mm





**Premiere Series PS5.9N****101721** 50x50 cm**Premiere Series PS4.6N****101726** 50x50 cm**Premiere Series PS3.9N****101731** 50x50 cm**Premiere Series PS2.9N****101736** 50x50 cm

FEATURES:

- Lightweight
- Novastar A5 Control system
- Hot-swappable LED Modules and control modules
- Neutrik Ethercon / Powercon
- Magnesium die-cast housing

ORDERCODE:	101736	101731	101726	101721
Pixel pitch	2,97	3,91	4,63	5,95
SMD Type	Nationstar 2020	Inteled SMD1818 Blackframe	Nationstar SMD2727 Blackframe	Nationstar SMD2727 Blackframe
Pixels	168 x 168 pixels	128 x 128 pixels	108 x 108 pixels	84 x 84 pixels
NITS	> 1200	> 5000	> 5000	> 5000
Receiver card	Novastar A5	Novastar A5	Novastar A5	Novastar A5
Viewing angle	110°/110°	110°/110°	110°/110°	110°/110°
Minimum viewing distance	2 mtr	4 mtr	4 mtr	5 mtr
Dimensions	500 x 500 x 65 mm	500 x 500 x 65 mm	500 x 500 x 65 mm	500 x 500 x 65 mm
Weight	9 Kg	8,5 Kg	8,5 Kg	8 Kg
Housing material	Magnesium die-cast	Magnesium die-cast	Magnesium die-cast	Magnesium die-cast
Curved angles	N/A	N/A	N/A	N/A
Maximum horizontal hang	16	16	16	16
Maximum vertical hang	15	15	15	15
Transparency	0%	0%	0%	0%
Power connection	Neutrik® Powercon True™	Neutrik® Powercon True™	Neutrik® Powercon True™	Neutrik® Powercon True™
Input voltage	100 to 240 VAC, 50/60 Hz (auto-ranging)	100 to 240 VAC, 50/60 Hz (auto-ranging)	100 to 240 VAC, 50/60 Hz (auto-ranging)	100 to 240 VAC, 50/60 Hz (auto-ranging)
Power consumption	Average 150 Watt, Maximum 300 Watt	Average 140 Watt, Maximum 300 Watt	Average 145 Watt, Maximum 300 Watt	Average 135 Watt, Maximum 300 Watt
Control protocol	Novastar	Novastar	Novastar	Novastar
Data connection	Neutrik® Ethercon™	Neutrik® Ethercon™	Neutrik® Ethercon™	Neutrik® Ethercon™
Indoor/outdoor	Indoor	Indoor / Outdoor	Indoor / Outdoor	Indoor / Outdoor
IP Rating	IP30	IP65 Front / IP54 Rear	IP65 Front / IP54 Rear	IP65 Front / IP54 Rear
Working temperature	(-)10°C - +45°C	(-)10°C - +45°C	(-)10°C - +45°C	(-)10°C - +45°C
Including	Data Link Cable, Power Link Cable	Data Link Cable, Power Link Cable	Data Link Cable, Power Link Cable	Data Link Cable, Power Link Cable

Premiere Series PS5.9N**101720** 50x100 cm**Premiere Series PS3.9N****101730** 50x100 cm**Premiere Series PS4.6N****101725** 50x100 cm**Premiere Series PS2.9N****101735** 50x100 cm**FEATURES:**

- Lightweight
- Novastar A5 Control system
- Hot-swappable LED Modules and control modules
- Neutrik Ethercon / Powercon
- Magnesium die-cast housing

ORDERCODE:	101735	101730	101725	101720
Pixel pitch	2,97	3,91	4,63	5,95
SMD Type	Nationstar SMD2020	Inteled SMD1818 Blackframe	Nationstar SMD2727 Blackframe	Nationstar SMD2727 Blackframe
Pixels	168 x 336 pixels	128 x 256 pixels	108 x 216 pixels	84 x 168 pixels
NITS	> 1200	> 5000	> 5000	> 5000
Receiver card	Novastar A5	Novastar A5	Novastar A5	Novastar A5
Viewing angle	110°/110°	110°/110°	110°/110°	110°/110°
Minimum viewing distance	3 mtr	4 mtr	4 mtr	5 mtr
Dimensions	500 x 1000 x 65 mm	500 x 1000 x 65 mm	500 x 1000 x 65 mm	500 x 1000 x 65 mm
Weight	14 Kg	13 Kg	13 Kg	13 Kg
Housing material	Magnesium die-cast	Magnesium die-cast	Magnesium die-cast	Magnesium die-cast
Curved angles	N/A	N/A	N/A	N/A
Maximum horizontal hang	16	16	16	16
Maximum vertical hang	10	10	10	10
Transparency	0%	0%	0%	0%
Power connection	Neutrik® Powercon True™	Neutrik® Powercon True™	Neutrik® Powercon True™	Neutrik® Powercon True™
Input voltage	100 to 240 VAC, 50/60 Hz (auto-ranging)	100 to 240 VAC, 50/60 Hz (auto-ranging)	100 to 240 VAC, 50/60 Hz (auto-ranging)	100 to 240 VAC, 50/60 Hz (auto-ranging)
Power consumption	Average 235 Watt, Maximum 300 Watt	Average 140 Watt, Maximum 300 Watt	Average 285 Watt, Maximum 300 Watt	Average 135 Watt, Maximum 300 Watt
Control protocol	Novastar	Novastar	Novastar	Novastar
Data connection	Neutrik® Ethercon™	Neutrik® Ethercon™	Neutrik® Ethercon™	Neutrik® Ethercon™
Indoor/outdoor	Indoor	Indoor / Outdoor	Indoor / Outdoor	Indoor / Outdoor
IP Rating	IP30	IP65 Front / IP54 Rear	IP65 Front / IP54 Rear	IP65 Front / IP54 Rear
Working temperature	(-)10°C - +45°C	(-)10°C - +45°C	(-)10°C - +45°C	(-)10°C - +45°C
Including	Data Link Cable, Power Link Cable	Data Link Cable, Power Link Cable	Data Link Cable, Power Link Cable	Data Link Cable, Power Link Cable



Install Series FI-10

101531 5000 Nits SMD Outdoor

Very well equipped for outdoor use are the various fixed installation screens DMT has to offer. The DMT Pixelscreen FI-10 with a 10mm pixel pitch is the ideal screen for stadiums, outdoor advertisement or signage solutions due to the IP-65 front-rating and IP-54 back-rating. The modular construction of the screen within a lightweight aluminium frame guarantees a seamless screen setup and provides convection cooling at the same time. The cabinets are designed with fast locks for quick and efficient assembly. The LED modules within the screens are hot swappable and serviceable from the front of the screen. Furthermore the screen is completely front serviceable therefore very well suited for any project or application. Equipped with a Novastar receiver-card guarantees a steady and reliable control system.

Technical information:

Pixel Pitch:	10mm
LED light source:	3in1 SMD 3535 black frame
Brightness Level:	5000 Nits
Transparency:	0%
Refresh rate:	>1000Hz (configurable)
Module Resolution:	32 x 24px
Cabinet Resolution:	64 x 72px
Viewing angle:	110° x 110° (HxV)
Control system:	Novastar
Input Voltage:	100~240VAC, 50/60Hz
Max Power Consumption:	650 W/m ²
Average Power Consumption:	215 W/m ²
IP Rating:	IP65 Front / IP54 Rear
Data connection:	Neutrik Ethercon
Power connection:	Neutrik powerCON TRUE1
Cooling:	Convection cooling
Mechanical connection:	Fastlock system
Maximum rigging height:	25 Cabinets
Module size:	320 x 240 mm - W x H
Cabinet size:	640 x 720 x 116 mm - W x H x D
Cabinet weight:	17.5 Kg
Operating Temperature:	-10°C ~ +45°C
Certification:	CE, EMC, LVD, FCC, ETL, RoHS

FEATURES:

- 10mm Outdoor LED screen
- IP65
- Permanent outdoor use
- Ideal for stadiums, outdoor advertisement, or signage solutions

Install Series FI-6

101541 5500 Nits SMD Outdoor

The DMT Pixelscreen FI-6 with a 6.67mm pixel pitch and a brightness level of 5500 Nits is the ideal screen for stadiums, outdoor advertisement or signage solutions due to the IP-65 front-rating and IP-54 back-rating. It is very well equipped for outdoor use and preferably as a fixed installed screen. The modular construction of the screen within a lightweight aluminium frame guarantees a seamless screen setup and provides convection cooling at the same time. The cabinets are designed with fast locks for quick and efficient assembly. The LED modules within the screens are hot swappable and serviceable from the front of the screen. Each screen is equipped with a Novastar receiver-card which guarantees a steady and reliable control system.

Technical information:

Pixel Pitch:	6.67mm
LED light source:	3in1 SMD 3535 black frame
Brightness Level:	5500 Nits
Transparency:	0%
Refresh rate:	>1000Hz (configurable)
Module Resolution:	48 x 36px
Cabinet Resolution:	96 x 108px
Viewing angle:	110° x 110° (HxV)
Control system:	Novastar
Input Voltage:	100~240VAC, 50/60Hz
Max Power Consumption:	650 W/m ²
Average Power Consumption:	215 W/m ²
IP Rating:	IP65 Front / IP54 Rear
Data connection:	Neutrik Ethercon
Power connection:	Neutrik powerCON TRUE1
Cooling:	Convection cooling
Mechanical connection:	Fastlock system
Maximum rigging height:	25 Cabinets
Module size:	320 x 240 mm - W x H
Cabinet size:	640 x 720 x 116 mm - W x H x D
Cabinet weight:	17.5 Kg
Operating Temperature:	-10°C ~ +45°C
Certification:	CE, EMC, LVD, FCC, ETL, RoHS

FEATURES:

- 6.67mm Outdoor LED screen
- IP65
- Permanent outdoor use
- Ideal for stadiums, outdoor advertisement, or signage solutions

Stacking Bracket

101743 Premiere Series

DMT has introduced the Stacking bracket for Premiere Series LED screens which can be used to mount any Premiere series cabinet to a stacking frame or Layher stage construction.

Easy locking system; the bracket can easily be locked / released just by turning the handle 90°, no further tools are required.

The stacking bracket can be used with all Premiere series cabinets.

Technical information:

Dimensions: 272 x 133 x 50mm. (W x L x H - Including clamp)
 Weight: 1.42Kg.
 Colour: Black
 Clamp: 50mm diameter

FEATURES:

- Easy assembly due to innovative locking mechanism
- Suitable for all Premiere series cabinets
- No tools required





DLD-84 8,4" LCD Display

101206 8,4" Display with DVI link

The DMT DLD-84 is a table mount monitor system. It can be used for VJ monitoring, surveillance systems and any other multimedia setup where monitoring is necessary. Optional 19 inch mountingbracket available for 2x DLD-84.

Technical information:

Resolution: 1280x720
 Power Voltage: AC 85-264V 50/60Hz
 Dimensions: 227x130x39
 Weight: 0,87Kg.
 1x Table Stand Included
 1x DVI to HDMI Adapter Included
 1x Power Supply



FEATURES:

- 8.4" LCD display
- DVI Input and Loop
- Optional 19 inch bracket available for 2x DLD-84 (ordercode:101207)



19" bracket for 2x DLD-84, 8.4" LCD display

101207

19" bracket for mounting 2x DLD-84, 8.4" LCD Display in 19" rack

Technical information:

19" bracket for mounting 2x DLD-84, 8.4" LCD display
 Dimensions(without handle): 37 x 483 x 128
 Dimensions (with handle): 67 x 483 x 128
 Colour: Black



Drum of 100m with 2 fiber Singlemode 9/125 cable**102050** Fiber optic cable

Optical Fiber cable Drum 100mtr. With 2 x fiber Single mode 9/125 cable, equipped with robust push-pull coupling mechanism connector

**Technical information:**

Drum of 100mtr. Fiber with 2 fiber singlemode 9/125 cable
 Operating temperature: -40°C up to +85°C
 Weight: 4.35Kg
 Dimension: 320 x 250 x 365
 Extension cable to daisychain fiber cable drum available (ordercode: 102052)
 Breakout socket QODC2-F to 2x LC simplex available (ordercode: 102053)

Break-out cable 2m, Q-ODC2-F to 2x LC simplex**102051** Fiber optic cable

Optical Fiber break-out cable Q-ODC2-F to 2x LC simplex

**Technical information:**

Break-out cable 2mtr. Q-ODC2-F to 2xLC connector
 Break out cable for optical fiber cable drum 100m(ordercode:102050)

Extension cable 1m with 2x Q-ODC2-F**102052** Fiber optic cable

Optical Fiber Extension cable 1m with 2x Q-ODC2-F

**Technical information:**

Extension cable with 2x Q-ODC2-F - 1mtr.
 Operating temperature: -40°C up to +85°C

Q-ODC2-F socket with D-flange**102053** Fiber optic cable

Q-ODC2-F breakout with D-flange to 2 x LC connector

**Technical information:**

Break-out 1x Q-ODC2-F to 2 x LC connector, mounted in D-flange
 Weight: 0.04Kg
 Dimension(square flange): 15x15x2
 Dimension(including connector): 15x15x40





Novastar CVT 320 Fiberconverter

101641

When you need to cover a large distance between your Novastar processor and LED screen the CVT 320 is the ideal solution for you. The Novastar CVT320 can be used either as transmitter or as receiver. Due to the LC interface it is very easy to connect it to any fiber source. To transfer signal from one sending-card output to the designated LED screen you always need two CVT320 units (TX transmitter and RX receiver). The fiber converter is plug and play and no further drivers are required.

Technical information:

Supply Voltage: AC 100-240V 50/60HZ.
 Power consumption: 16W.
 In/Output Interface: 1 Ethernet port
 Fiberport: LC interface
 Dimension: 149 x 132 x 38mm, W x H x D
 Weight: 0.7kg
 Operating temperature: -20°C ~ +60°C
 Operating humidity: 0% RH-95% RH

FEATURES:

- Fiber converter to cover large distances between processor and LED screens
- Transmission distance up to 15KM.
- Plug and play, no driver required



Novastar DIS-300 Splitter

101651 Signal Converter & Splitters

The Novastar DIS-300 is specialized for multi-screens and super large led screens. The card possesses two input ports and eight output ports, enabling that one split to eight and two split to four. Functions change automatically. Each RJ45 port can be independently adjusted, and supports read back parameters from cabinet.

Technical information:

Inputs: 2 x Ethernet Inputs
 Outputs: 8 x Ethernet Outputs
 Power supply: AC 100-240V ~50/60 Hz
 Power consumption: 3.40W
 Operating temperature: -20°C ~ +75°C
 Operating humidity: 0% ~ 95%
 Dimensions: 356 x 171 x 45mm

FEATURES:

- Two split modes: one input mode: Input A to 8x Output / or two input mode: A&B to 2x four outputs
- Each RJ45 port can be independently adjusted, and support read back parameters from cabinet



Nova M3 MFN300 Function Box

101611

The Nova M3 MFN300 Functionbox is a multifunction box with a variety of auxiliary functions in compact housing. It can be easily added to the screen setup at any desired position within the ethernet screen connection.

The MFN300 function box allows you to add a variety of functions such as: sensor inputs to connect Light or Temperature sensors to the screen setup but it also has eight on-board relay contacts, RS 232 connection, audio output.

Technical information:

Ethernet connection: 2x Gigabit ethernet port
 RS232: Sub-D 9pin Male
 Audio: 3.5mm
 Supply Voltage: AC-100-240V-50/60HZ
 Operating temperature: -20 ~ +75°
 Operating humidity: 0% RH-99% RH
 Colour: Black
 Dimensions: 186 x 206 x 49mm
 Weight: 1,12Kg.

FEATURES:

- 2 x Ethernet port connection for use at any position within the screen network
- 2 x External sensor inputs, to add Light / Temperature sensor
- Audio output
- RS 232 connection
- 8x relay power switch control





Novastar Lightsensor NS60

101612

The Novastar NS60 is a light sensor which can be used to monitor ambient brightness and achieve automatic brightness adjustment of LED displays. It can be connected directly to: MSD300/MCTRL300/MCTRL600 sending card or MFN300 multifunctioncard.

The light sensor can be used for indoor and outdoor applications, furthermore there's no external power supply required.

Technical information:

Cable length: 5mtr. can be extended up to 100mtr.
 Supply Voltage: DC 5V
 Brightness range: 0-65535 lux
 Operating temperature: -30°C ~ +70°C
 Operating humidity: 0% RH-99% RH
 Dimensions: 34x83.3mm

FEATURES:

- Automatic brightness adjustment / ambient brightness monitoring
- Waterproof IP65
- No external power supply required



Novastar Temperature sensor MTH 310

101613

The Novastar MTH310 is a waterproof temperature sensor to monitor ambient temperature. MTH310 can be connected to MFN300 multifunction card. Furthermore there's no external power supply required.

Technical information:

Cable length: 5mtr. (can be extended up to 100mtr.)
 Supply Voltage: DC 5V
 Temperature measuring range: -20°C ~ +75°C
 Operating temperature: -25°C ~ +85°C
 Operating humidity: 0% RH-99% RH
 Dimensions: 85x20mm

FEATURES:

- Waterproof IP65
- No external power supply required





MCTRL-300

101629 Sender Box

The Novastar MCTRL-300 is a compact basic sending card which makes setting up your Novastar equipped LED screen easy and simple. Encased in a sturdy housing the Novastar MCTRL-300 incorporates not only a DVI and audio input but also an on-board light sensor input. This can be used to connect a Novastar light sensor (101612) directly to the sending card for automatic brightness adjustment when ambient lighting changes. By adding the MCTRL-300 to your LED screen setup you will have the instant ability to play any content of your PC directly on the LED screen.

Technical information:

Input Resolution:	1280x1024, 1024x1200, 1600x848, 1920x712 or 2048x668 (width and height can be specially defined by customers)
Capacity:	1.3 million pixels
Supply Voltage:	AC 100-240V 50/60HZ.
Power consumption:	16W.
Control Method:	USB Interface
Video Interface:	DVI
Audio Interface:	3.5mm
Video Format:	RGB
Output Interface:	2 Ethernet ports
Bit Depth Of Video Resource:	8bit
Lightsensor interface:	1
Dimension:	204 x 160 x 48mm - W x H x D
Weight:	1kg
Operating temperature:	-20°C ~ +60°C
Operating humidity:	0% RH-95% RH

FEATURES:

- Cabinet config files saving and sending
- 2 x Ethernet output port
- DVI Video Input port
- Lightsensor interface port
- Audio Input

Novastar MSD-300

101610 Sender Box

The Novastar MSD-300 is a basic sending card which lets you operate your LED Screen which is equipped with the Novastar control system.


The MSD-300 can be plugged in any PC with a free PCI slot. With the MSD-300 setting up your LED screen becomes easy and simple. Furthermore the MSD-300 can play any content of your PC direct on the LED screen.

Technical information:

Input Resolution:	1280x1024, 1024x1200, 1600x848, 1920x712 or 2048x668 (width and height can be specially defined by customers)
Capacity:	1.3 million pixels
Supply Voltage:	5.0V (by standard PC connector)
Control Method:	USB Interface
Video Interface:	DVI
Audio Interface:	3.5mm
Video Format:	RGB
Output Interface:	2 Ethernet ports
Bit Depth Of Video Resource:	8bit
Lightsensor interface:	1
Dimension:	126.3 x 91.4 x 20mm

FEATURES:

- Cabinet config files saving and sending
- 2 x Ethernet output port
- DVI Video Input port
- Lightsensor interface port
- Audio Input





Novastar MCTRL-660 Pro

101621 Sender Box

FEATURES:

- Low latency of less than <1 frame
- Cabinet config files saving and sending
- Brightness, Colour and Test Pattern adjustable by knob
- Full HD Pixels capacity
- 8/10/12-bit Colour Depth
- 3G-SDI Input/loop
- 6 x Gigabit Ethernet output port
- 2 x 10G optical output port
- GENLOCK In / Loop

The MCTRL660 PRO is a professional low-latency controller. A single MCTRL660 PRO has a loading capacity of up to 1920x1200@60Hz.

The MCTRL660 PRO has many industry-leading advanced technologies. Various video inputs such as HDMI, DVI, 3G SDI and 6x Gigabit ethernet / 2x 10G optical outputs allow users to configure ultra-large screens with ultra-width or ultra-height.

Technical information:

Input Resolution:	1920x1200@60Hz., 1920x1080@60Hz., (width and height can be specially defined by customers)
Capacity:	2.3 million pixels.
Supply Voltage:	AC-100-240V-50/60HZ
Power Consumption:	20W
Control Method:	USB / Ethernet Interface
Video Input Interface:	HDMI/DVI/3G-SDI
Video Format:	RGB:4:4:4, YCbCr4:4:4, YCbCr4:2:2, YCbCr4:2:0
Output Interface:	6 x Gigabit ethernet port / 2 x 10G Optical port
Colour Depth:	8/10/12bit
Dimensions:	482.6 x 349.0 x 50.7mm
Weight:	4.6kg
Operating temperature:	-20°C ~ +60°C
Operating humidity:	0% RH-90% RH, non-condensing



FEATURES:

- 4K Capacity
- Free rotation
- Neutrik etherCON outputs
- Easy operation

Novastar Phobos R5 Processor

101650 Sender Box

The Novastar Phobos MCTRL R5 is an independent master with an epoch-making significance. The loading capacity of a single unit is up to 3840x1080@60Hz, which is able to meet the on-site requirements of oversized LED displays.

Working with the A8s or A10s receiving card, the MCTRL R5 supports free screen configuration on SmartLCT, presenting full rotation of the display screen at any angle, adding diversity to images, and bringing different visual experience to users

The design of MCTRL R5 is innovative, it allows to configure a display at any time without PC. Various video inputs such as HDMI, dual-link DVI, SDI etc. and outputs of 8-channel Neutrik Gigabit Ethernet ports as well as 2-channel optical fiber ports are supported.

Technical information:

Inputs:	6G SDI interface, HDMI 1.4, Dual-link DVI
Outputs:	8 channel Neutrik Gigabit Ethernet outputs, 2-channel optical fiber outputs
Control:	Ethernet, USB
Genlock:	Blackburst
Power supply:	AC 100-240V ~ 50/60 Hz
Power consumption:	25W
Operating temperature:	-20°C ~ +60°C
Operating humidity:	10% RH - 90% RH
Dimensions:	482.6 x 334.6 x 52mm
Weight:	4.3 Kg



D1 Videomixer with scaler

101281 Onboard LCD Touch Screen

D1 makes video scaling and mixing more accessible and intuitive than ever before. D1 is equipped with the latest technologies and innovations which makes it a fully integrated All-in-One video processor.

The integrated touch screen makes accessing the different functions an easy task. DMT implemented large illuminated buttons which are familiar from the LS125 MKII, onto the D1 to make switching sources more visible and accessible.

Audio features are also built right into D1 which makes outputting from embedded audio or external sources possible.

Much more than only a vision mixer, D1 includes both cross-conversion and pixel to pixel scaling for modern displays, making this a comprehensive video solution for meeting rooms, schools, houses of worship and rental video productions.



Technical information:

Input	4x	HDMI
Output Program (PGM)	1x	HDMI
Output Preview (PVW)	1x	HDMI

Input Resolutions DVI/HDMI:

SMPTÉ:	625@25/50 PAL 525@29.97/59.94 NTSC 1080p@50/59.94/60 1080i@50/59.94/60 720p@50/59.94/60
VESA :	800x600@60 1024x768@60 1280x768@60 1280x1024@60 1600x1200@60 1920x1080@60

Output Resolutions (Select from preset or user defined)

SMPTÉ:	480i 576i 625@25/50 PAL 525@29.97/59.94 NTSC 1080p@50/59.94/60 1080i@50/59.94/60 720p@50/59.94/60
VESA:	800x600@60 1024x768@60 1280x768@60 1280x1024@60 1600x1200@60 1920x1080@60

Genlock Y In:	Black Burst: 480i 576i 720p@50/59.94 1080i@50/59.94 1080p@50/59.94/60 1080psf@23.98/24
---------------	--

Grayscale Processing:	12bit
-----------------------	-------

Processing Engine:	10bit
--------------------	-------


Power Connection:	IEC (power cable included)
Power Voltage:	AC 85-264V 50/60Hz
Power Consumption:	65W
Temperature:	-25°C ~ +55°C
Humidity:	10 - 90% RH
Dimensions:	485mm x 280mm x 95mm
Weight:	5.5Kg.

Features

Layers :	2
DSK / Chromakey:	Yes (foreground layer)
Blend:	Yes (foreground layer)
Mask:	Yes (foreground layer)
Transition Effect:	Yes

FEATURES:

- Fully integrated mixer and scaler
- Dedicated Preview output
- Onboard LCD Touch Screen
- Integrated audio
- Transition effects
- PIP, OSD, DSK, BLEND, MASK, LOGO and STILL
- Sync to Genlock
- Individual Pixel-to-Pixel scaling per input



Legend

	256 DMX Channels		WDMX Control		CMY Colour Mixing		Beam		RGBALC 6-1 LED
	512 DMX Channels		RDM Control		CTB Correction		Spot		RGB-UV 4-1 LED
	Adapter Included		Matrix Patterns		CTO Correction		Wash		RGB LEDs
	Battery powered		Motorized Focus		Tungsten Simulation		Hybrid		RGBW LEDs
	Battery powered Display		LED Power		3100K		Beam Angle		RGBA LEDs
	Plug & Play		Discharge Power		3200K		Zoom		RGBWA LEDs
	Continuous Rotating		230V Direct Dimming		5600K		RGB 3-1 LED		
	Chip On Board Technology		Frost Filter		Back Light		RGBA 4-1 LED		
	Art Net Controlled		Multi Effect		Section Control		RGBW 4-1 LED		
	Klingnet Control		No Fan		ABS Housing		RGBWA 5-1 LED		
	Flicker Free Operation		Pixel Control		Metal Housing		RGBWA-UV 6-1 LED		
	Digital Motion Effect		IP Rating		Die Cast Housing		RGBWA_UV_L 7-1 LED		

Showtec Polar 100 Beam





HIGHLITE

Vestastraat 2, 6468 EX Kerkrade.

The Netherlands.

Phone: +31 - (0)45-5667701

E-mail: sales@highlite.com

Web: www.highlite.com