







# A4 BLACK & WHITE NETWORK PRINTER

### High Productivity

The DX-B450P/DX-B350P is capable of up to 43/34 ppm with a paper capacity\*1 that expands to 1800 sheets. These efficient network printers are perfect for all your office document needs.

dpi resolution 1200 guarantees page after page of high quality text and graphics, with the first page appearing in little more than 8 seconds.





# Environment Friendly

The DX-B450P/DX-B350P conform to the **Energy Star** programme, an international system identifying energy-efficient products.

The DX-B450P/DX-B350P also conform to standards set for the Nordic Swan and Blue Angel European environmental labels.

Additionally, in support of the ROHS directive, these network printers are fully compliant, which restricts the use of Hazardous Substances.

### Easy to use and Manage

Both machines come with a range of advanced print features that make them easy to use and manage. Handy tools such as Web Browser and Printer Status Monitor let you know what the printer is doing without having to leave your desk, and Automated Email Alerts notify you when the toner or paper levels are low.

In addition, the Duplex Module\*2, allows automatic two-sided printing, and busy teams will appreciate the Offset Catch Tray\*2, which keeps print jobs separate.


# Advanced Security

The DX-B450P and DX-B350P have robust security features, such as Port Control and IP Filtering which unauthorised network Additionally, you can prevent confidential documents from being left in the output tray by requiring the originator to personally enter a PIN at the printer before the job can start.



Web Browser





Easy -To-Use Print Drivers

<sup>\*1</sup> Based on 75 g/m<sup>2</sup> \*2 Optional



# FAST AFFORDABLE PRINTING

### KEY FEATURES

### Highly Productive

- Speedy output of max. 43/34 ppm printing
- Quick first print output time of 8.1/8.9 seconds (simplex)
- Extensive paper capacity\*2 of max. 1,800 sheets
- Standard 1 x 150 and 1 x 550 sheet paper drawers
- 500 sheet Offset Catch Tray\*1 for keeping print jobs separate
- Standard future-proofed network connectivity with IPv6
- Direct PDF Printing PS3 as standard
- Optional 40 GB Hard Drive

### Remote Administration

- Device Management tools include a web browser, e-mail alerts and Printer Status Monitor
- Modify configurations and update firmware using the Printer Maintenance Utility
- Intuitive Print Drivers help simplify operation and improve productivity
- \*1 Based on 75 g/m<sup>2</sup>
- \*2 Optional

## Superb Image Quality

• True 1,200 x 1,200 dpi ensures finely detailed reproduction

### Advanced Security

- IP Filtering restricts access to the printer
- Changing web port numbers and disabling protocols limits how stored data can be accessed
- Secure Erase<sup>\*1</sup> overwrites the Hard Drive with random data

### Reduce Costs and Save Energy

- Duplex Module\*1 for double sided printing will save on paper
- Energy Star, Nordic Swan and Blue Angel accreditations



### System Configuration

### 1. DX-B450P

A4 Mono Printer Base Unit

#### 2. DX-B350P

A4 Mono Printer Base Unit

#### 3. DX-CSX

550 Sheet Paper Drawer (for DX-B450P) A6 – A4; 550 sheets; 64 – 216 g/m<sup>2</sup>

#### 4. DX-CSX1

550 Sheet Paper Drawer (for DX-B350P) A6 – A4; 550 sheets; 64 – 216 g/m<sup>2</sup>

#### 5. DX-TEX1

Offset Catch Tray (for DX-B450P & DX-B350P)

500 sheet output capacity; 64 – 216 g/m<sup>2</sup>

#### 6. DX-DUX2

Duplex Module (for DX-B450P)
Double sided printing; 64 – 216 g/m<sup>2</sup>

#### 7. DX-DUX1

Duplex Module (for DX-B350P)

Double sided printing; 64 – 216 g/m<sup>2</sup>


#### MX-DXSM50

Printer Memory

#### MX-DXHD50

40 GB Hard Drive

**Compact Flash Memory** 



#### **SPECIFICATIONS**

#### General

Workgroup network printer Type Printing System Electro-photographic laser DX-B350P: Up to 34 ppm **Print Speed** DX-B450P: Up to 43 ppm CPU MIPS RM7035 - 533MHz

128 MB expandable to 640 MB, User Flash 12 MB Memory

First Print DX-B350P: Approx. 9 sec (A4) DX-B450P: Approx. 8 sec (A4) **Output Time** Warm-up time Maximum of 17 seconds from power on

**Print Resolution** 1200 dpi, 600 dpi DX-B350P: Approx. 21 Kg Weight DX-B450P: Approx. 21.5Kg Dimensions (W x D x H) 421.8 x 465.4 x 404.3 mm

#### Media

Standard: Up to 700 sheet capacity (2 Drawer) Paper Feed System

(1) 150-sheet multipurpose

System: drawer and (1) 550 sheet paper drawer Maximum: Up to 1,800 sheet capacity (4 Drawer)

**Paper Types** (2) additional 550 sheet paper drawers.

Paper drawers: 64-216 gsm

Paper types include: plain, transparency, pre-punched, letterhead, color, pre-printed, bond, labels, cardstock,

postcard and envelope

Max. A4 – Min. A6R (Custom - W: 76.2 mm - 215.9 mm and L: Paper Sizes

127.0 mm - 355.6 mm)

Paper that is smaller than W: 98.4 mm x L: 148.0 mm must

be placed in Tray 1.

Paper that is smaller than W: 88.9 mm x L: 139.7 mm cannot

be duplexed or output to the Offset Catch tray.

Duplex Optional

**Output Capacity** Standard: Up to 500 sheets (face down)

#### Connectivity

Interfaces Ethernet 10/100 Base-T, Hi-speed USB 2.0, IEEE 1284 parallel

(DB25), RS-232C Serial

PCL5e, PCL®6 80 HP® compatible (99 scalable, 1 fixed fonts), Languages & Fonts 8 barcodes. Adobe® PostScript® 3™ 136 standard Adobe

scalable fonts Adobe Direct PDF 1.3

**Print Drivers** Windows® 98, Windows NT® 4, Windows 2000, Windows XP,

Windows XP x64, Windows Server 2003, Windows Server x64, Windows Server 2008, Windows Server 2008 x64,

Windows Vista®, Windows Vista x64, MAC OSX® - including 10.2 through 10.5 (PPD

Operating Windows 98, Windows NT 4, Windows 2000, Windows XP, Windows XP x64, Windows Server 2003, Windows Server x64, system

Windows Server 2008, Windows Server 2008 x64, Windows Vista, Windows Vista x64, MAC OS-X - 10.2 through 10.5, Unix® and Linux® (Redhat 7.3, 8.0, 9.0; Sun Solaris 8, 9, 10; SUSE Linux

Professional 9.1, 9.2, 9.3; HP-UX 11i)

TCP/IPv4, UDP, BOOTP, DHCP, ARP, ICMP, DNS, WINS, HTTP, LPR, Protocols

HTTP, Apple EtherTalk, IPv6, ICMPv6, Bonjour, Netware V5, V6,

POP3, SMTP

**Network Security** IP/Mac address filtering, protocol filtering, port management Configuration Web-based management system with user/administrator

Method level login security

#### Operating Environment

**Operating Temperature** 5°C to 35°C

**Relative Humidity** 15% to 85% non-condensing DX-B350P: AC 230-240 VAC 4.9 AMPS Power DX-B450P: AC 230-240 VAC, 5.5 AMPS

**Power Consumption** DX-B350P: Maximum: 1,000 W Power Save Mode: Maximum 13W

DX-B450P: Maximum: 1,285 W Power Save Mode: Maximum 15W

DX-B350P: ENERGY STAR® qualified **Energy Savings** 

DX-B450P: ENERGY STAR qualified when used with the optional Compliance

DX-DUX2 duplex unit

#### Paper Drawer (Option)

Tray Capacity Up to 550 sheets **Power Source** Supplied from the main unit

Weight Approx. 2.12Kg

Dimensions 283.7 mm (W) x 394.6 mm (D) x 85.6 mm (H)

#### **Duplex Unit (Option)**

**Output Capacity** Up to 500 sheets **Output Delivery** Face down

**Power Source** Supplied from the main unit Offset Approx 25mm

Weight Approx 1.9 Kg

Dimensions DX-B350P: 351.7 mm (W) x 96.1 mm (D) x 218.5 mm (H) DX-B450P: 351.7 mm (W) x 146.2 mm (D) x 238 mm (H)

### Offset Catch Tray (Option)

**Output Capacity** Up to 500 sheets **Output Delivery** Face down

**Power Source** Supplied from the main unit

Offset Approx. (25mm) Weight Approx. 2.6 Ka

Dimensions 417.8 mm (W) x 312.5 mm (D) x 226 mm (H)

#### Accessories

DX-CSX1 550 sheet adjustable paper drawer (For DX-B350P) DX-CSX2 550 sheet adjustable paper drawer (For DX-B450P) DX-DUX1

Duplex unit (For DX-B350P) DX-DUX2 Duplex unit (For DX-B450P) DX-TFX1 Offset catch trav MX-DXHD50 40GB hard disk drive kit MX-DXSM50 512MB expansion memory

#### **Supplies**

DX-B35DTH High yield (18K) toner cartridge (For DX-B350P)

Declared yield value in accordance with ISO/IEC 19752 DX-B45DTH High yield (21K) toner cartridge (For DX-B450P)

Declared yield value in accordance with ISO/IEC 19752

- Design and specifications are subject to change without prior notice.
- Colour variations to products may occur due to printing.
  Some features require Optional items. Please consult with an authorised Sharp Reseller for details.
- All information and technical details are correct as at machine release date.
   Windows, Windows NT, Windows Server, and Windows Vista are registered trademarks of Microsoft Corporation in the United States and/or other countries. All other brand names and product names may be trademarks or registered trademarks of their respective owners.
- The Energy Star logo is a certification mark and may only be used to certify products that have been
  determined to meet the Energy Star programme requirements. Energy Star is a US registered mark. The Energy Star guidelines apply to products only in the US, Europe, Australia, New Zealand, and Japan.



Distributed by:

#### **SHARP CORPORATION OF AUSTRALIA PTY LTD**

ABN 40 003 039 405

1 Huntingwood Drive, Huntingwood NSW 2148 P.O. Box 6827, Blacktown, NSW 2148 Tel: (02) 9830 4600 Fax: (02) 9672 1208 www.sharp.net.au

#### SHARP CORPORATION OF NEW ZEALAND LTD

59 Hugo Johnston Drive P.O. Box 12244, Penrose, Auckland Tel: (09) 573 0111 Fax: (09) 573 0112 www.sharp.net.nz

