




**MOTOROLA**

TWO-WAY RADIOS

# GM340: The Popular Radio

The Popular Radio is the simple two-way radio solution for professionals who need to stay in contact. The GM340 can easily increase productivity by keeping users communicating, yet streamlines their radio use allowing them to concentrate on the job at hand. With the Popular Radio, communication couldn't be easier.



## Operator friendly controls and features include:

- **Signalling**  
*The radio software encompasses Private Line™ and 5-tone selective signalling.*
- **Voice Operated Transmit (VOX)**  
*Hands free operation when used with VOX accessory.*
- **Emergency Signalling**  
*Sends help signal to a pre-defined person or group of people. The help signal can contain a pre-recorded voice message enabling your whereabouts or status to be determined immediately by the receiving person.*
- **Lone Worker**  
*Added security and safety for individuals who work remotely from their team. The radio enters emergency mode if the user does not respond to the warning signal.*
- **Option Board Expandability\***  
*You can expand the existing capabilities by adding one of the following option boards:*
  - Encryption for message security.
  - SmarTrunk II for low cost trunking.
  - Voice Storage option board provides voice recorder features allowing you to store and retrieve messages.
- **External Alarm**  
*Activates the vehicle horn and/or lights on receipt of an incoming call, so you won't miss a call even when away from your vehicle.*
- **Public Address Mode**  
*This feature allows you to use your radio audio as a public address system simply by adding an external speaker and switch fitted and programmed by your dealer.*
- **Data Capable**  
*A modem can be fitted inside a special expansion head, or external to the radio.*

## Additional features include:

- Channel Scan
- X-Pand™ Voice Compression and Low Level Expansion
- Adjustable Power Levels
- Programmable Channel Spacing (12.5/20/25 kHz)
- Talkaround
- Call Forward

\*Please check with your dealer for availability on specific option boards.

As Dedicated As You Are

# Professional Radio

# GM340 Mobile Two-Way Radio Specifications

General		
Specification	VHF	UHF
Frequency Range:	136-174 MHz	403-470 MHz
Frequency Stability (-30°C to +60°C, 25°C Ref.)	±2.5 PPM	±2 PPM
Channel Capacity:	6	
Channel Spacing:	12.5/20/25 kHz	
Power Output:	1-25W	1-25W
Power Supply:	13.2Vdc (10.8 - 15.6 Vdc) negative vehicle ground	
Dimensions (L x W x H)	177mm x 176mm x 56mm (add 8mm for Volume Knob) (6.97" x 6.93" x 2.2" - add 0.3" for Volume Knob)	
Weight:	1400 g (3.15 lbs)	
Operating Temperature	-30 to 60°C	
Sealing	Passes rain testing to IP54	
Shock and Vibration	Meets MIL-STD 810-C,D&E and TIA/EIA 603	
Dust	Meets MIL-STD 810-C,D&E and TIA/EIA 603	
Humidity	Meets MIL-STD 810-C,D&E and TIA/EIA 603	

Transmitter	
Specification	VHF/UHF
Modulation Limiting:	±2.5 kHz @ 12.5 kHz ±4.0 kHz @ 20 kHz ±5.0 kHz @ 25 kHz
FM Hum and Noise:	-40 dB @ 12.5 kHz -45 dB @ 20/25 kHz
Conducted/Radiated Emissions:	-36 dBm < 1 GHz -30 dBm > 1 GHz
Adjacent Channel Power	-60 dB @ 12.5, -70 dB @ 20/25 kHz
Audio Response: (300 to 3000Hz)	+1, -3dB
Audio Distortion: @ 1000 Hz, 60% Rated Maximum Deviation:	3% Typical

Mobile Military Standards 810 C, D, & E						
Applicable MIL-STD	810C		810D		810E	
	Methods	Procedures	Methods	Procedures	Methods	Procedures
Low Pressure	500.1	1	500.2	2	500.3	2
High Temperature	501.1	1,2	501.2	1,2	501.3	1,2
Low Temperature	502.1	2	502.2	1,2	502.3	1,2
Temp. Shock	503.1	1	503.2	1	503.3	1
Solar Radiation	505.1	1	505.2	1	505.3	1
Rain	506.1	2	506.2	2	506.3	2
Humidity	507.1	2	507.2	2,3	507.3	3
Salt Fog	509.1	1	509.2	1	509.3	1
Dust	510.1	1	510.2	1	510.3	1
Vibration	514.2	8,10	514.3	1	514.4	1
Shock	516.2	1,2,5	516.3	1	516.4	1

Receiver		
Specification	VHF	UHF
Sensitivity (12dB SINAD): (ETS)	0.30µV (0.22 µV Typical)	
Intermodulation: (ETS)	>65 dB; >70 dB in Base Mode	
Adjacent Channel Selectivity: (ETS)	80dB @ 25 kHz 75dB @ 20 kHz 65dB @ 12.5 kHz	75 dB @ 25 kHz 70 dB @ 20 kHz 65 dB @ 12.5 kHz
Spurious Rejection: (ETS)	80 dB @ 20/25 kHz 75 dB @ 12.5 kHz	75 dB @ 20/25 kHz 70 dB @ 12.5 kHz
Rated Audio: (ETS)	3W Internal 7.5W & 13W External	
Audio Distortion @ Rated Audio:	3% Typical	
Hum and Noise:	-40 dB @ 12.5 kHz -45 dB @ 20/25 kHz	
Audio Response: (300 to 3000Hz)	+1, -3dB	
Conducted Spurious Emission per FCC Part 15:	-57 dBm <1 GHz -47 dBm >1 GHz	

\*Availability subject to individual country's law and regulations.

Specifications are subject to change without notice and are issued for guidance purposes only.

All specifications listed are typical. Radios meet applicable regulatory requirements.


Conforms to EC directive 89/336/EEC

Complies with ETS 300 113

Contact your local Authorised Motorola Dealer to find out more about how communicating with the Professional Radio series will benefit your organisation.

**RIEDEL**  
Funk- & Intercomtechnik  
Uellendahler Str. 353  
42109 Wuppertal

Hotline: +49 (0) 202 292-93 31  
motorola@riedel.net  
www.riedel.net



**RIEDEL**  
The Communications People

**UK Sales Office**

**Middle East and Africa Headquarters:**  
Motorola Ltd  
Jays Close, Viabes Industrial Estate  
Basingstoke, Hampshire RG22 4PD  
United Kingdom  
Tel (01256) 358211  
Fax (01256) 488080

**Central Europe Headquarters**

**Eastern Europe, Turkey and Central Asia Headquarters:**  
Motorola GmbH  
Heinrich Hertz Strasse 1  
65232 Taunusstein  
Germany  
Tel. +49 6128 700  
Fax +49 6128 951084



For exceptional performance, reliability and quality, Motorola Original accessories are the only options. For full details, please refer to the Professional Radio Series Accessories brochure.



Motorola, Professional Radios, As Dedicated As You Are and X-Pand are trademarks of Motorola Inc.  
© 2000 Motorola, Printed in the United Kingdom  
<http://www.mot.com>