

## **SCALEOVIEW L22W-8** 22 Inch LCD widescreen Display

Issue October 2007

Pages 2

An attractive price doesn't mean that you have to compromise on style or performance. The SCALEOVIEW L22W-8 widescreen display offers best performance for the home office and multimedia, such as photo editing and gaming. With its extremely slim and stylish design, the SCALEOVIEW L22W-8 fits perfectly into your home environment.

### Highlights

- 22-inch widescreen display for a perfect viewing experience at high resolution
- Best performance to an affordable price
- Very easy and comfortable to use
  - Plug & Play
  - Auto-adjust
  - Easy-to-use OSD menu

### Ergonomics

- Optimum flicker-free and distortion-free picture
- Excellent color purity
- Well balanced brightness uniformity
- Excellent high contrast (1000:1)
- Space saving design

### Technical highlights

- 22" (55.9 cm) LCD widescreen display
- Excellent contrast 1000:1
- Brightness 300 cd/m<sup>2</sup>
- Fast response time (typ.) 5 ms
- Internal power supply

### Reliability

- Low power consumption
- Power management according to EPA
- Guaranteed quality and stability



<b>Visible screen diagonal</b>	22 inch (55.9 cm)
<b>Resolutions</b>	
Pixels	1680 x 1050
Pixels*	1280 x 768
* expanded	
<b>Picture size</b>	473.76 x 296.1 mm
<b>Colors</b>	16.7 million
<b>Pixel Pitch</b>	0.282 mm
<b>Frequencies</b>	
Horizontal	31 - 83 kHz
Vertical	56 - 76 Hz
<b>Brightness (typical)</b>	300 cd/m <sup>2</sup>
<b>Contrast up to</b>	1000:1
<b>Viewing angle (cr&gt;=5)</b>	
Horizontal	170°
Vertical	170°
<b>Response time (typical)</b>	5 ms
<b>Plug and Play</b>	VESA DDC2B
<b>Setting options</b>	
Brightness (Back light control)	
Contrast, Volume control	
Picture position (horizontal and vertical), H-size, Phase,	
Color temperature and individual color setting	
Auto-adjust (direct access key)	
Activate factory settings	
Menu language	
<b>OSD Language</b>	
English, German, Spanish, French, Italian, Russian, Polish, Dutch	
<b>Base</b>	
Tilt angle	-5° / +20°
<b>Video input</b>	1x D-SUB, 1x DVI-D
<b>Audio input / output</b>	
Audio signal input	3.5 mm stereo phone jack
Audio output	1 W (L) + 1 W (R)

<b>Electrical values</b> (internal power supply)	
Rated voltage	100 - 230 V
Frequency	50 - 60 Hz
Power draw	
EPA 'On Mode'	29 W
Max.	< 55 W
Stand by	< 1 W
Protection class	1
<b>Temperatures/ dimensions/ weight</b>	
Ambient temperature (to IEC721):	
Working (recommended)	5°C to 35°C
Storage	-20°C to 60°C
Dimensions (H x W x D):	
(with stand)	415 x 515 x 206 mm
Weight (Monitor only)	5.4 kg
<b>Reliability</b>	
MTBF (demonstrated)	70,000 h
Lifetime of LCD backlight	50,000 h
(brightness > 50 % of original brightness)	
<b>Compliance with standards</b>	
Product safety	EN60950
Ergonomics	GS mark ISO13406-2 (Pixel fault class II)
Radiation immunity and RFI suppression	CE certification according to EC Directive 89/336/EEC (EN55022/B, EN55024 EN61000-3-2/-3); TCO'03
<b>Accessories</b>	
Power cable (1.5 m)*	1x wall socket (Euro-Schuko-Type CEE7)
Data cable (1.5 m)*	D-SUB (15-pin)
Audio cable (1.8 m)*	3.5 mm stereo phone jack
* detachable on display	
<b>Special features</b>	Standardized mounting interface according VESA FPMPI (100 mm) Kensington Lock
<b>Order code</b>	S26361-K1224-V203
<b>EAN</b>	433364 3101916

