

DATASHEET FUJITSU CELSIUS H700 proGREEN selection MOBILE WORKSTATION

WORKSTATION POWER ON-THE-GO

CELSIUS H700

The CELSIUS H700 delivers workstation power in a notebook form factor. Featuring a power-saving Intel[®] processor, NVIDIA[®] graphics and an EcoButton to help extend battery life, the CELSIUS H700 delivers uncompromising green performance without tethering you to the office. Secure and reliable, it is ideal for business environments such as CAD and digital content creation.

WORKSTATION PERFORMANCE

Higher productivity thanks to mobile workstation performance

■ Professional NVIDIA® Quadro® graphics, Intel® Core™ i7 processor with vPro™ technology

UNLIMITED CONNECTIVITY

Online anywhere, anytime.

Integrated WLAN, 3G/UMTS and Bluetooth[®]

ULTIMATE SECURITY

- Protect your data from non-authorized access
- Integrated SmartCard reader and fingerprint sensor

ADVANCED RELIABILITY

Protects your notebook against physical damage

Spill-resistant keyboard and hard disk drive ShockSensor

ISV CERTIFICATION

- Excellent performance and absolute stability in professional environments
- Comprehensive certification for workstation applications

NVIDIA









proGREEN

COMPONENTS

PROCESSOR	Intel [®] Core™ i7 processor 620M (2.66 GHz, 4 MB, 1066 MHz)
OPERTAING SYSTEM	Microsoft® Windows® 7 Professional 64-bit
Operating system optional preinstall	ed
MEMORY MODULES	4 GB (2 module(s) 2 GB) DDR3, 1066 MHz, PC3-8500, SO DIMM
HARD DISK DRIVE (INTERNAL)	500 GB, 7200 rpm, SATA, 2.5-inch S.M.A.R.T.
Hard disk notes	ShockSensor for HDD shock protection One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. Accessible capacity may vary, also depending on used software
WLAN	Intel® Centrino® 6200 802.11 a/b/g/n
WIRELESS TECHNOLOGIES	
Antennas	2 Dual band WLAN antennas, 2 UMTS antenna
WLAN notes	Import and usage according to country-specific regulations.
3G/UMTS	Sierra Wireless Gobi 2000 (downlink 7.2 Mbit/s, uplink 5.76 Mbit/s)
DISPLAY	39.6 cm (15.6-inch), LED backlight, (Full HD), anti-glare display, magnesium, 1920 x 1080 pixel
MODULAR BAY OPTION	DVD Super Multi
Base unit	CELSIUS H700
GENERAL SYSTEM INFORMATION	
Chipset	Intel® QM57
BIOS features	BIOS based on Phoenix SecureCore
GRAPHICS	
Max. resolution external display	DVI-D: 2560 x 1600 pixels (60Hz); HDMI: 1080p
Graphics brand name	NVIDIA® Quadro FX 880M
Graphics features	DualView
Dedicated video memory	1 GB (GDDR3 VRAM)
INTERFACES	
DC-in	1
Audio: line-out / headphone	1
Audio: line-in / microphone	1
Internal microphones	2 digital array microphones
USB 2.0 total	4
VGA	1
DisplayPort	1
Serial (RS-232)	1
Ethernet (RJ-45)	1
FireWire (IEEE1394)	1
Kensington Lock support	2
PC Card slot (Type I/II)	1
Memory card slots	1 (SD/MS/MSPro)
Express card slots	1
SmartCard slot	1
SIM card slot	1
eSATA	1 Aputiona LICD abarra functionality
Interface Module notes	Anytime USB charge functionality
WIRED COMMUNICATION	
Modem type	Optional: 56 K V.92 modem MDC1.5
LAN	10/100/1000 MBit/s Intel® 82577 LM

Audi stype On board Audi codec Ranke AL2669 Audi codec Ranke AL2669 Audi codec Ballt-In vehcam, 1.3 megapake, VGA camera Interfaces FOWER SUPPLY Ada do apper 19 V / 100 W (6.27 A) Rated rogtage range 50 - 60 Hz Ated frequency range 50 - 60 Hz Rated rogtage range 50 - 60 Hz Ated frequency range 50 - 60 Hz Rated rogtage range 50 - 60 Hz Rated rogtage range 50 - 60 Hz Rated rogtage range 50 - 60 Hz Rated frequency range 50 - 60 Hz Rated frequency range 50 - 60 Hz Rated frequency range 50 - 60 Hz Battery torional) Likn hatmy & 60 Hz Battery torional) Likn hatmy & 60 Hz Battery torional Upin 3 P Battery torional Upin 3 P Battery torional Upin 7 h Battery toriange Si 22 × 25 x 36 mm Dimensions (W x D x h) 372 × 25 5 x 36 mm Weight toriange Si - 35°C Operating anthient temperature 5 - 35°C Operating system compatibile Microsoft* Windows* XP Professional (XVD) Operating system compatibile Microsoft* Windows* XP Professional (XD)		
Audio codec Realtek ALC269 Audio features Storeo speakers, 2 internal microphones Genera Buil-In webcarn, 13 megapiest, VGA camera Interfaces	MULTIMEDIA	
Audio features Stereo speakers, 2 internal microphones Camera DitI-in webcarn, 1.3 megapixel, VGA camera Interfaces Notes SuPLY Ad adopter 19 V / 100 W (5.27 A) Adata voltage range 100 - 240 V (AC Input) Rated frequency range 50 - 60 hz Tak battery (optional) L-lon, 3300 MA, 14 Wh Battery features Dynamic charge supported (apid charge) Benchmark Mobile Mark 2005 Runtime 154 battery up to 7 h Battery features Dynamic charge supported (apid charge) Benchmark Mobile Mark 2005 Runtime 154 battery up to 7 h Battery features Battery life may vary dopending on product model, configuration, applications, power management settings and features Dimensions (W x D H) 372 x 255 x 38 mm Operating relative humidity 20 - 85 % (unning) Operating relative humidity 20 - 85 % (unning) Operating system compatible Microsoft* Windows* 7 Professional 64-bit Operating system policeal preinstalled Microsoft* Windows* 7 Professional 1 Vista Business Additional software (preinstalled) Acker Archat Reade Additional software (preinstalled) Acker Archat Reade Additional software (preinstalled) Acker Archat Reade Morcosoft* Windows* 7 Profes		
Camera Buill-In webcarn, 1.3 megapixel, VGA camera Interfaces POWER SUPPLY A dapter 19 V / 100 W [5.27 Å] Rated voltage range 100 - 240 V (AC input) Rated voltage range 0.0 - 040 V (AC input) Rated voltage range 0.0 - 040 V (AC input) Statefor Fequency range 0.0 - 040 V (AC input) Statefor Fequency range 0.0 - 040 V (AC input) Statefor Fequency range 0.0 - 040 V (AC input) Statefor Fequency range Do Tomaric charge supported (range) descenters Battery fortional) Diversion (M R ac 2005 Battery rotos Battery rotos DIMENSIONS / WEIGHT / ENVIRONMENTAL Diversion (M R ac 256 X 80 mm Weight notes Actual weight may vary depending on configuration Operating relative humidity 20 - 85 % (running) Operating system compatible Microsoft* Windows* 7P Professional (DVO) Microsoft* Microsoft* Windows* 7P Professional (DVO) Microsoft* Microsoft* W		
Interfaces POWER SUPPLY AD adapter POWER SUPPLY POWER SUPPLY POWER SUPPLY POWER POWE		
AC adapter 19 V/ 100 W (5.27 A) AC adapter 19 V/ 100 W (5.27 A) Rated voltage range 100 - 240 V (AC Input) Rated frequency range 50 - 60 Hz State frequency range 50 - 60 Hz State frequency range Dynamic charge supported (npid charge) Battery features Dynamic charge supported (npid charge) Benchmark Mobile Mark 2005 Runtime 1st battery up to 5 h Runtime 1st battery up to 7 h Battery notes Battery recharge time depends on usage. DIMENSIONS / WEIGHT / ENVIRONMENTAL Immensions (W x D k H) Operating antilent temperature 5 - 35°C Operating system optional preinstated Microsoft* Windows* 7 Professional 64-bit Operating system conpatibile Microsoft* Windows* 7 Professional 64-bit Operating system conpatibile Microsoft* Windows* 7 Professional 7000 Vindows Vindows* 7 Professional 64-bit Operating system conpatibile Offer and system conpatibile Microsoft* Windows* 7 Professional 7000 Windows Int Microsoft* Windows* 7 Professional 7000 Windows Int Microsoft* Windows* 7 Professional 7000 Operating system coptical		Built-III webcam, T.3 megapixei, VGA camera
AG adapter 19 V/ 100 W (5.27 A) Rated vidtage range 100 - 240 V (AC Input) Rated vidtage range 50 - 60 /z Ented frequency range 50 - 60 /z Statery (optional) L-Hon hattery B cell, 5.800 mAh, 84 Wh 2nd battery (optional) L-Hon, 3800 mAh, 41 Wh Bettery teatures Dynamic charge supported (rapid charge) Benchmark Mobile Mark 2005 Runtime 1st + 2nd battery up to 6 h Runtime 1st + 2nd battery up to 6 h Runtime 1st + 2nd battery up to 7 h Battery notes Battery life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery reatrage time depends on usage. DIMENSIONS / WEIGHT / ENVIRONMENTAL Dimensions (W X D X H) Operating anabient temperature 5 - 35°C Operating realizer bundidty 20 - 5 kg (unning) Operating system optional preinstalled Microsoft* Windows* 7P Professional A4-bit Operating system optional preinstalled Microsoft* Windows* 7P Professional (VD) Microsoft* Windows* 7P Professional / Vista Business Additional software (preinstalled) Adoto Actobat Reader Application Panel Diperating system notes Driver system Visita * An other system Visita * An other system Syste	Interfaces	
Rated voltage range 100 - 240 V (AC liquit) Rated frequency range 50 - 50 1/z Rated frequency range 50 - 50 1/z Sta battery (optional) Li-kon satury 8-cell, 5.800 mAh, 64 Wh 2nd battery (optional) Li-kon satury 8-cell, 5.800 mAh, 64 Wh Battery restures Dynamic charge supported (rapid charge) Benchmark Mobile MAX: 2005 Runtime 1st battery up to 6 h Runtime 1st - 2nd battery up to 7 h Battery notes Battery incharge supported (rapid charge) Dimensions (W x D x H) 372 x 255 x 36 mm Dimensions (W x D x H) 372 x 255 x 36 mm Veight notes Actual weight may vary depending on configuration, applications, power management settings and features Veight notes Actual weight may vary depending on configuration Operating relative humidity 20 - 85 % (unning) Operating relative humidity 20 - 85 % (unning) Operating system optional preinstalled Microsoft* Windows* XP Professional (VU0) Microsoft* Windows*	POWER SUPPLY	
Rated frequency range 60 - 60 Hz 1st batery Li-lon battery B-cell, 5.000 mAh, 84 Wh Zot battery (potional) Li-lon, 3000 mAh, 41 Wh Battery features Dynamic charge supported (rapid charge) Benchmark Mobile Mark 2006 Runtime 1st battery up to 7 h Battery notes Battery life may vary depending on product model, configuration, applications, power management settings and features DIMENSIONS / WEIGHT / ENVIRONMENT Total and	AC adapter	19 V / 100 W (5.27 A)
1st battery Li-lon battery 6ctional) Li-lon, 3800 mAh, 64 Wh 2nd battery (optional) Li-lon, 3800 mAh, 61 Wh Model Battery fortunal Dynamic charge supported (rapid charge) Benchmark Model Mark 2005 Runtime 1st attery up to 6 h Battery fortunal up to 7 h Battery notes Battery returne time depends on usage. DIMENSIONS / WEIGHT / ENVIRONMENTAL Dimensions (W x D x H) 372 x 255 x 36 mm 272 x 255 x 36 mm Operating ambient temperature 5 - 35° C Operating ambient temperature 5 - 35° C Operating relative humidity 20 - 85 % (furning) OPerating system compatible Microsoft* Windows* 7 Professional Operating system optional preinstalled Microsoft* Windows* XP Professional (VDD) Microsoft* Windows VXP Professional (VDD) Microsoft* Windows VXP Professional (VDD) Microsoft* Windows VXP Professional (VDD) Microsoft* Windows* XP Professional (VDD) Microsoft* Windows Visit* Businses Add	Rated voltage range	100 - 240 V (AC Input)
2nd battery (optional) Li lan, 3800 mAh, 41 Wh Battery features Oynamic charge supported (rapid charge) Benchmark Molie Mark 2005 Runtime 1st battery up to 6 h Runtime 1st battery up to 7 h Battery notes Calify and the supported (rapid charge) Battery notes Calify in any vary depending on product model, configuration, applications, power management settings and features DIMENSIONS / WEIGHT / ENVIRONMENTAL Dimensions (W X D x M) Dimensions (W X D x M) 372 x 255 x 36 mm Weight notes Actual weight may vary depending on configuration Operating ambient temperature 5 - 35° C Operating anbient temperature 5 - 35° C Operating system optional preinstalled Microsoft® Windows® 7 Professional 64-bit Operating system notes Driver support for Windows® 7 Professional (VD) Windows® XP Professional (VD) Windows® XP Professional / Vista Business Additional software (preinstalled) Adobe Acrobat Reader Application Panel Balger Marager ShockSensor Utility Prover Savity Utility Wreless Selector Utility Prover Savi	Rated frequency range	
Battery features Dynamic charge supported (rapid charge) Benchmark Mobile Mark 2005 Runtime 1st 4 2nd battery up to 6 h Battery Inters Battery recharge time depends on usage. DIMENSIONS / VEICHT / ENVIRONMENTAL 275 kg Dimensions (W x D x H) 372 x 255 x 36 mm Operating ambient temperature 5 - 35° C Operating relative humidity 20 - 85 % (running) Operating relative humidity 2 - 85 % (running) Operating relative humidity 2 - 85 % (running) Operating system optional preinstalled Microsoft [®] Windows [®] XP Professional (DUD) Microsoft [®] Windows [®] XP Pro	1st battery	
Benchmark Mobile Mark 2005 Runtime 1st battery up to 6 h Runtime 1st + 2nd battery up to 7 h Battery notes Battery iffe may vary depending on product model, configuration, applications, power management settings and features utilized. Battery refearge time depends on usage. DIMENSIONS / WEIGHT / ENVIRONMENTAL Dimensions (W x D x H) Dimensions (W x D x H) 372 x 255 x 36 mm Weight 2.75 kg Weight notes Actual weight may vary depending on configuration Operating mabient temperature 5 - 35° C Operating system optional preinstalled Microsoft* Windows* 7 Professional 64-bit Operating system optional preinstalled Microsoft* Windows* XP Professional (DVD) Microsoft* Windows* XP Professional (DVD) Microsoft* Windows* XP Professional (DVD) Microsoft* Windows* XP Professional / Vista Business ADDITIONAL SOFTWARE Adobe Acrobat Reader Application Panel Display Manager Additional software (preinstalled) Microsoft* Windows* 7 operating systems) Additional software (optional) Driver & Utility Virreises Stelector Utility Power Saving Utility Power Saving Utility Power Saving Utility Diver S & Utilities DVD (UUDVD) UMTS Somection manager (optional with UMTS) SmartCase Logen+ MANAGEABILITY DeskUpdate Driver management DeskView Worate (optional) Weike-on-LAW	2nd battery (optional)	
Runtime 1st battery up to 6 h Runtime 1st + 2nd battery up to 7 h Battery notes Battery life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery recharge time depends on usage. DIMENSIONS / WEIGHT / ENVIRONMENTAL Dimensions (W x D x H) 372 x 255 x 36 mm 372 x 255 x 36 mm Weight 2.75 kg Weight 2.75 kg Operating ambient temperature 5 - 35°C Operating relative humidity 20 - 85 % (unning). OPERATING SYSTEM Operating system optional preinstalled Microsoft® Windows® 7 Professional 64-bit Operating system optional preinstalled Microsoft® Windows® 7 Professional (D/D) Microsoft® Windows® XP Professional (D/D) Microsoft® Windows® XP Professional (D/D) Microsoft® Windows® XP Professional (Vista Business ADDITIONAL SOFTWARE Additional software (preinstalled) Additional software (preinstalled) Kacha Actual Reader Application Panel Display Manager StockSensor Ullity Virges Selector Ullity EasyGuide online user documentation Norton Internet Security (Ind. Firowal). Toshika Stack 4.x (not available for Windows® 7 operating systems) Additional software (optional) DeskUpdate Driver management DeskView Migrate (optional) Duriers & Lillities DVD (JUUDV) Weigles Selector Ullity EasyGuide online user documentation Noton Inter		
Runtime 1st + 2nd battery up to 7 h Battery notes Battery wary depending on product model, configuration, applications, power management settings and features Battery notes Battery rotes Dimensions (W x D x H) 372 x 255 x 36 mm Veight notes Actual weight may vary depending on configuration Operating ambient temperature 5 35°C Operating mibient temperature 5 35°C Operating system optional preinstalled Microsoft® Windows® 7 Professional 64-bit Operating system optional preinstalled Microsoft® Windows® XP Professional (DVD) Microsoft® Windows® XP Professional (DVD) Microsoft® Windows Vista® Business 32-bit Operating system notes Adobe Acrobat Reader Application Panel Display Manager Additional software (preinstalled) Adobe Acrobat Reader Application Panel Display Manager ShockSensor Ullity Wireless Selector Ullity Wireless Vertifies S (Windows® 7 operating systems) Additional software (optional) Were Active Coptional Diskly		
Battery notes Battery life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery trecharge time depends on usage. DIMENSIONS / WEIGHT / ENVIRONMENTAL Image: Control of		
utilized. Battery recharge time depends on usage. DIMENSIONS / WEIGHT / ENVIRONMENTAL Dimensions (W x D x H) 372 x 255 x 36 mm Weight 2.75 kg Weight notes Actual weight may vary depending on configuration Operating ambient temperature 5 - 35°C Operating relative humidity 20 - 85 % (running) OPERATING SYSTEM Unicrosoft® Windows® 7 Professional 64-bit Operating system optional preinstalled Microsoft® Windows® XP Professional (DVD) Microsoft® Windows® XP Professional (DVD) Microsoft® Windows® XP Professional (DVD) Microsoft® Windows® XP Professional (DVD) Microsoft® Windows® XP Professional (Vista Business ADDITIONAL SOFTWARE Adobe Acrobat Reader Application Panel Display Manager ShockSensor Utility Additional software (preinstalled) Adobe Acrobat Reader Application Panel Display Manager ShockSensor Utility Wireless Selector Utility Vireless Selector Utility EasySuide online user documentation Nero Essential S (furning software) Norton Internel Security (incl. Firewall) Toshiba Stack 4.x (not available for Windows® 7 operating systems) Additional software (optional) Divers & Utilities DVD (DUDVD) UMTS connection manager (optional with UMTS) SmartCase Logon+ Manageability features DeskUpdate Driver management DeskView Mortol (optional) Wake-on-LAN		
Dimensions (W x D x H) 372 x 255 x 36 mm Weight 2.75 kg Weight notes Actual weight may vary depending on configuration Operating ambient temperature 5 - 35 °C Operating relative humidity 20 - 85 % (running) OPERATING SYSTEM Operating system optional preinstalled Microsoft® Windows® 7 Professional 64-bit Operating system compatible Microsoft® Windows® XP Professional (DVD) Microsoft® Windows® XP Professional (DVD) Microsoft® Windows Vista® Business 32-bit Diver support for Microsoft® Windows® XP Professional / Vista Business ADDITIONAL SOFTWARE Adobe Acrobat Reader Adplication Panel Display Manager ShockSensor Utility Power Saving Utility Wireless Selector Utility Power Saving Utility Wireless Selector Utility Power Saving Utility Wireless Selector Utility Strat availabet for Windows® 7 operating systems) Additional software (optional) Drivers & Utilities DVD (DUDVD) UMTS connection manager (optional) Drivers & Utilities DVD (DUDVD) UMTS connection manager (optional) Microsoft available for Windows® 7 operating systems) Additional software (brities DVD (DUDVD) UMTS connection manager (optional) Drivers & Utilities DVD (DUDVD) UMTS connection manager (optional) WANAGEABILITY Desk	Battery notes	
Weight2.75 kgWeight notesActual weight may vary depending on configurationOperating ambient temperature5.35°COperating relative humidity20.85 % (running)OPERATING SYSTEMOperating system optional preinstalledMicrosoft® Windows® 7 Professional 64-bitOperating system compatibleMicrosoft® Windows® XP Professional (DVD) Microsoft® Windows® XP Professional (DVD) Microsoft® Windows® XP Professional (DVD) Microsoft® Windows® XP Professional / Vista BusinessOperating system notesDiver support for Microsoft® Windows® XP Professional (NDD) Microsoft® Windows® XP Professional (NDD) Nore Saving Utility Power	DIMENSIONS / WEIGHT / ENVIRONME	NTAL
Weight notes Actual weight may vary depending on configuration Operating ambient temperature 5 - 35°C Operating relative humidity 20 - 85 % (running) OPERATING SYSTEM Operating system optional preinstalled Microsoft® Windows® 7 Professional 64-bit Operating system compatible Microsoft® Windows® XP Professional (DVD) Microsoft® Windows® XP Professional (DVD) Microsoft® Windows® XP Professional / Vista Business Operating system notes Driver support for Microsoft® Windows® XP Professional / Vista Business ADDITIONAL SOFTWARE Adobe Acrobat Reader Additional software (preinstalled) Adobe Acrobat Reader Application Panel Display Manager StockSensor Utility Power Saving Utility Power Saving Utility Power Saving Utility Power Saving Utility Wirdess VP (Optional) Nero Essentials S (burning software) Norton Internet Security (incl. Firewall) Toshiba Stack 4.x (not available for Windows® 7 operating systems) Additional software (optional) MANAGEABLITY Desk/Update Driver management Desk/We Migrate (optional) Desk/We Migrate (optional) Wake-on-LAN Wake-on-LAN	Dimensions (W x D x H)	372 x 255 x 36 mm
Operating ambient temperature 5 - 35°C Operating relative humidity 20 - 85 % (running) OPERATING SYSTEM Operating system optional preinstalled Microsoft® Windows® 7 Professional 64-bit Operating system compatible Microsoft® Windows® XP Professional (DVD) Microsoft® Windows® XP Professional (DVD) Microsoft® Windows Vista® Business 32-bit Operating system notes Driver support for Microsoft® Windows® XP Professional / Vista Business Additional software (preinstalled) Adobe Acrobat Reader Application Panel Display Manager ShockSensor Utility Power Saving Utility Wireless Selector Utility EasyGuide online user documentation Nero Essentials S (burning software) Norton Internet Security (incl. Firewall) Toshiba Stack 4.x (not available for Windows® 7 operating systems) Additional software (optional) Drivers & Utilitis DVD (DUVD) WirS connection manager (optional) with UMTS) SmartCase Logon + MANAGEABILITY DeskUpdate Driver management Desk/Werk Migrate (optional) Wake-on-LAN	Weight	2.75 kg
Operating relative humidity 20 - 85 % (running) OPERATING SYSTEM Operating system optional preinstalled Operating system compatible Microsoft® Windows® XP Professional (DVD) Microsoft® Windows® XP Professional (DVD) Microsoft® Windows® XP Professional (DVD) Microsoft® Windows® XP Professional (DVD) Microsoft® Windows® XP Professional / Vista Business Operating system notes Driver support for Microsoft® Windows® XP Professional (VDD) Microsoft® Windows® XP Professional / Vista Business ADDITIONAL SOFTWARE Adobe Acrobat Reader Application Panel Display Manager ShockSensor Utility Power Saving Utility Wireless Selector Utility EasyGuide online user documentation Nero Essentials S (burning software) Norton Internet Security (incl. Firewall) Toshiba Stack 4.4 (not available for Windows® 7 operating systems) Additional software (optional) Drivers & Utilities DVD (DUDVD) UMTS connection manager (optional with UMTS) SmartCase Logon+ Manageability features Desk/Jpdate Driver management Desk/iew Control (optional) Wake-on-LAN	Weight notes	Actual weight may vary depending on configuration
OPERATING SYSTEM Operating system optional preinstalled Microsoft® Windows® 7 Professional 64-bit Operating system compatible Microsoft® Windows® XP Professional TwinLoad Microsoft® Windows® XP Professional (DVD) Microsoft® Windows Vista® Business 32-bit Operating system notes Driver support for Microsoft® Windows® XP Professional / Vista Business ADDITIONAL SOFTWARE Adobe Acrobat Reader Application Panel Display Manager ShockSensor Utility Power Saving Utility Wireless Selector Utility Power Saving Subide online user documentation Nero Essentials (S (burning software) Norton Internet Security (incl. Firewall) Toshiba Stack 4.x (not available for Windows® 7 operating systems) Additional software (optional) Drivers & Utilities DVD (DUDVD) UMTS connection manager (optional with UMTS) SmartCase Logon+ Manageability features DeskUpdate Driver management DeskView Migrate (optional) Wake-on-LAN	Operating ambient temperature	
Operating system optional preinstalled Microsoft® Windows® 7 Professional TwinLoad Microsoft® Windows® XP Professional (DVD) Microsoft® Windows® XP Professional (DVD) Microsoft® Windows® XP Professional / Vista Business Operating system notes Driver support for Microsoft® Windows® XP Professional / Vista Business Additional software (preinstalled) Adobe Acrobat Reader Application Panel Display Manager ShockSensor Utility Power Saving Utility Wireless Selector Utility Wireless Selector Utility Wireless Selector Utility Norton Internet Security (incl. Firewall) Toshiba Stack 4.x (not available for Windows® 7 operating systems) Additional software (optional) Drivers & Utilities DVD (DUDVD) UMTS connection manager (optional with UMTS) SmartCase Logon+ MANAGEABILITY DeskUpdate Driver management DeskView Wingrate (optional) DeskView Control (optional) Wake-on-LAN	Operating relative humidity	20 - 85 % (running)
Operating system compatible Microsoft® Windows® XP Professional TwinLoad Microsoft® Windows® XP Professional (DVD) Microsoft® Windows ® XP Professional / Vista Business Operating system notes Driver support for Microsoft® Windows® XP Professional / Vista Business Additional software (preinstalled) Adobe Acrobat Reader Application Panel Display Manager ShockSensor Utility Power Saving Utility Wireless Selector Utility EasyGuide online user documentation Norton Internet Security (incl. Firewall) Toshiba Stack 4.x (not available for Windows® 7 operating systems) Additional software (optional) Driver & Utilities DVD (DUDVD) UMTS connection manager (optional with UMTS) SmartCase Logon+ MANAGEABILITY DeskUpdate Driver management DeskView Control (optional) DeskView Control (optional) Wake-on-LAN	OPERATING SYSTEM	
TwinLoad Microsoft® Windows® XP Professional (DVD) Microsoft® Windows Vista® Business 32-bit Operating system notes Driver support for Microsoft® Windows® XP Professional / Vista Business Additional software (preinstalled) Adobe Acrobat Reader Application Panel Display Manager ShockSensor Utility Power Saving Utility Wireless Selector Utility Power Saving Utility Wireless Selector Utility Power Saving Utility Norton Internet Security (incl. Firewall) Toshiba Stack 4.x (not available for Windows® 7 operating systems) Additional software (optional) Drivers & Utilities DVD (DUDVD) UMTS connection manager (optional with UMTS) SmartCase Logon+ MANAGEABILITY DeskUpdate Driver management DeskView Migrate (optional) DeskView Control (optional) DeskView Control (optional)	Operating system optional preinstall	ed Microsoft® Windows® 7 Professional 64-bit
ADDITIONAL SOFTWARE Additional software (preinstalled) Adobe Acrobat Reader Application Panel Display Manager ShockSensor Utility Power Saving Utility Power Saving Utility Wireless Selector Utility Power Saving Utility EasyGuide online user documentation Nero Essentials S (burning software) Norton Internet Security (incl. Firewall) Toshiba Stack 4.x (not available for Windows® 7 operating systems) Additional software (optional) Drivers & Utilities DVD (DUDVD) UMTS connection manager (optional with UMTS) SmartCase Logon+ Manageability features DeskUpdate Driver management DeskView Control (optional) DeskView Control (optional) Wake-on-LAN Wake-on-LAN	Operating system compatible	TwinLoad Microsoft [®] Windows [®] XP Professional (DVD)
Additional software (preinstalled) Adobe Acrobat Reader Application Panel Display Manager ShockSensor Utility Power Saving Utility Power Saving Utility Wireless Selector Utility EasyGuide online user documentation Nero Essentials S (burning software) Norton Internet Security (incl. Firewall) Toshiba Stack 4.x (not available for Windows® 7 operating systems) Additional software (optional) Drivers & Utilities DVD (DUDVD) UMTS connection manager (optional with UMTS) SmartCase Logon+ Manageability features DeskUpdate Driver management DeskView Migrate (optional) DeskView Control (optional) Wake-on-LAN Wake-on-LAN	Operating system notes	Driver support for Microsoft® Windows® XP Professional / Vista Business
Application Panel Display Manager ShockSensor Utility Power Saving Utility Power Saving Utility Wireless Selector Utility EasyGuide online user documentation Nerro Essentials S (burning software) Norton Internet Security (incl. Firewall) Toshiba Stack 4.x (not available for Windows® 7 operating systems) Additional software (optional) Drivers & Utilities DVD (DUDVD) UMTS connection manager (optional with UMTS) SmartCase Logon+ Manageability features DeskUpdate Driver management DeskView Migrate (optional) DeskView Control (optional) Wake-on-LAN Wake-on-LAN	ADDITIONAL SOFTWARE	
Additional software (optional) Drivers & Utilities DVD (DUDVD) UMTS connection manager (optional with UMTS) SmartCase Logon+ MANAGEABILITY DeskUpdate Driver management DeskView Migrate (optional) DeskView Control (optional) Wake-on-LAN	Additional software (preinstalled)	Application Panel Display Manager ShockSensor Utility Power Saving Utility Wireless Selector Utility EasyGuide online user documentation Nero Essentials S (burning software) Norton Internet Security (incl. Firewall)
Manageability features DeskUpdate Driver management DeskView Migrate (optional) DeskView Control (optional) Wake-on-LAN Wake-on-LAN	Additional software (optional)	Drivers & Utilities DVD (DUDVD) UMTS connection manager (optional with UMTS)
DeskView Migrate (optional) DeskView Control (optional) Wake-on-LAN	MANAGEABILITY	
Manageability type DeskView 10.x client management including:	Manageability features	DeskView Migrate (optional) DeskView Control (optional)
	Manageability type	DeskView 10.x client management including:

MANAGEABILITY	
DeskView features	On/Offline remote client management Detailed system inventory management and reports BIOS Management Remote power management System notifications Security Remote Control DeskView Helpdesk Integration WoL (Wake on LAN)
Supported standards	WMI PXE BootP (made4you)
Manageability link	http://ts.fujitsu.com/solutions/it_infrastructure_solutions/manageability/featurefinder.html
SECURITY	
Physical security	Kensington Lock support
System security	Advanced Theft Protection Computrace® enabled BIOS Optional: Trusted platform module (TPM 1.2) Symantec Norton Internet Security (90 day test version)
User security	Integrated Fingerprint Sensor Separate SmartCard slot Hard disk password SystemLock BIOS SmartCard security User and supervisor BIOS password
COMPLIANCE	
Product	CELSIUS H700
Germany	GS
Europe	CE
USA/Canada	cCSAus FCC Class B (depending on wireless configuration)
Global	RoHS (EU & China) ENERGY STAR® 5.0 Medical EMC standard IEC60601-1-2 in combination with medical kit
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/default.aspx

PORTREPLICATOR INTERFACES (OPTIONAL)

	Port replicator/AC adapter/EU-cable kit
DC-in	1
Audio: line-in	1
Audio: line-out	1
USB 2.0 total	4
DisplayPort	1
VGA	1
DVI	1
Serial (RS-232) text	1
Ethernet (RJ-45)	1
Parallel	1
Kensington Lock support	2
eSATA	1

WARRANTY

Standard Warranty	3 years (depending on country)
Service level MAINTENANCE AND SUPPORT S	Collect & Return Service / Bring in (depending on county specific requirements) SERVICES - THE PERFECT EXTENSION
Recommended Service	5x9, Response Time: Next Business Day
Service Weblink	http://ts.fujitsu.com/Supportservice

FUJITSU PLATFORM SOLUTIONS

In addition to Fujitsu CELSIUS H700, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

MORE INFORMATION

Learn more about Fujitsu CELSIUS H700, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. http://ts.fujitsu.com/celsius

FUJITSU GREEN POLICY INNOVATION

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT.

Please find further information at http://www. fujitsu.com/global/about/environment/



COPYRIGHTS

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://ts.fujitsu.com/ terms_of_use.html

Copyright © Fujitsu Technology Solutions

DISCLAIMER

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

CONTACT

FUJITSU Technology Solutions Website: http://ts.fujitsu.com 2010-03-08 CE-EN