

Data Sheet Fujitsu Display P24W-6P IPS Displays

Superior display: 61 cm (24-inch) widescreen Cutting edge display technology and innovative Green solutions

Enjoy perfect picture quality, outstanding ergonomics and usability as well as comfortable energy saving solutions of this Fujitsu P Line widescreen display.

In Plane Switching (IPS) panel technology with an ultra wide viewing angle of 178°

Energy saving solution - with ECO button direct access to power saving operation mode

Auto Brightness Control (ABC) works via sensor and dims the brightness optimized to the brightness of the working environment

Optimized and relaxed position - with ergonomic stand featuring height adjust, swivel, tilt and 90° rotation

Highly flexible connectivity through different interfaces - 4x USB, DisplayPort, HDCP (via DVI-D), DVI and Analog

Representative design with space saving front frame and smart details like connector cover and discretely integrated speakers

Due to the DisplayView Manageability tools ready for remote inventory gathering and for remote execution of configuration tasks





reddot design award winner 2011























Technical details

Power save mode	0.5 W
Hard switch off	0.0 W
Power consumption (typical, w/o soun Soft switch off	0.7 W
etup	Input select, Language, DDC-CI, OSD-Timeout, Factory recall
nformation	Model name, S/N, Resolution/mode, Signal input
udio	Mute, Volume
oioi mage adjust	Clock, Phase, H-Position, V-Position, Expansion, Saturation, Sharpness
rightness / Contrast olor	9300K, 7500K, 6500K, Native, sRGB, Custom Color (R,G,B)
anguages	Spanish, Swedish, Turkish Brightness, Contrast, Black level, Auto Brightness, Auto level
ase-of-use menu	Arabic, Czech, Danish, Dutch, English, Finnish, French, German, Italian, Norwegian, Polish, Portuguese, Russian,
SB upstream	וענט א ו
	1 x USB
SB downstream	4 x USB 2.0
udio signai input udio sound output	2 x 1.5 W
udio signal input	3.5 mm stereo phone jack
GA/D-SUB	1 x D-SUB
VI	1 x DisplayPort 1 x DVI (HDCP)
onnectivity isplayPort	1 v DicplayDort
ertical Connectivity	50 - 76 Hz
lorizontal Vertical	30 - 82 kHz
requencies	20 02 141-
ixel Pitch	0.27 mm
icture size	518 x 324 mm
ideo modes	1080i/p, 720i/p, 576i/p, 480i/p
esolution (interpolated)	1680 x 1050 pixel, 1600 x 1200 pixel, 1400 x 900 pixel, 1280 x 800 pixel, 1280 x 768 pixel, 1024 x 768 pixel, 800 x 600 pixel, 640 x 480 pixel
esolution (native)	1920 x 1200 pixel (recommended)
iagonal Size	61 cm (24-inch)
spect ratio	16:10
ize and resolution	
rightness - typical	400 cd/m
ligh color gamut - typical	
olor performance	16.7 million colors (8-bit)
iewing angle (h/v) - typical	178°/178° CR10:1
esponse time gray to gray typical	5 ms
ontrast - advanced	20,000:1
Contrast - typical	1000:1
Picture performance	
Swivel angle	340°
ilt angle	-3° / +35°
otation to portrait	90° (AutoPivot)
Picture height over desk (min)	50 mm
leight adjust range	100 mm
rgonomic stand tand	4-in-1 Stand
	Display Function compatible gamma preset
	Disability Function and a still a second accept

Page 2 / 4

0 " " " EDA " "	/7.W
Operating with EPA settings	47 W
Operating maximum brightness	78 W
Electrical values	100 // 2/0 //
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Protection class	
Compliance	EN COORD OF THE REPORT OF THE PROPERTY OF THE
Europe	EN 60950, CE certification according to EC Directive 2004/108/EEC, RoHS, WEEE, IT-Eco-Declaration
Model	P24W-6
Germany	TÜV GS
Russia	GOST
USA/Canada	FCC Class B, cUL
Japan	VCCI
Saudi Arabia	SASO
Global	TCO'03, ISO9241-307 (Pixel fault class I)
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/
Quality and Reliability	
MTBF (demonstrated)	70000 h
Dimensions / Weight / Environmental	
Dimension without stand (W x D x H)	563 x 65 x 376 mm
Dimension with stand $(W \times D \times H)$	563 x 228 x 397 mm
Weight (packed)	11.4 kg
Weight (unpacked)	8.0 kg
Weight (Monitor only)	5.5 kg
Operating ambient temperature	5 - 35℃
Miscellaneous	
Miscellaneous	VESA DDC/ CI, Standardized mounting interface VESA FP MP MI 100 mm, Kensington lock prepared
Package content	
Display delivered accessories	DisplayPort data cable 1.8 m, DVI-D Data cable 1.8 m, D-SUB Data cable 1.8 m , Audio cable 1.8 m, USB-cable 1.8 m (USB-A to USB-B), Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m, Quickstart flyer, Utility CD, Warranty
	booklet, Safety booklet
Display delivered accessories notes	Data cables, USB cable and audio cable detachable on display
Order information	
Order Code	S26361-K1435-V140
EAN-No.	4051554358518
Warranty	
Standard Warranty	3 years
Service level	Collect & Return Service (depending on country)
Spare Parts availability	5 years
Service Weblink	http://ts.fujitsu.com/Supportservice

Page 3 / 4 http://ts.fujitsu.com/displays

More information

Fujitsu platform solutions

In addition to Fujitsu Display P24W-6P IPS, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu Display P24W-6P IPS, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

http://ts.fujitsu.com/displays

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT.

Please find further information at http://www.fujitsu.com/global/about/environment/



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see http://ts.fujitsu. com/terms_of_use.html Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

Contact

FUJITSU Technology Solutions Website: http://ts.fujitsu.com 2011-12-01 CE-EN All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://ts.fujitsu.com/terms_of_use.html Copyright © Fujitsu Technology Solutions