



NEC Value, Multipurpose and Short Throw Projectors provide a comprehensive range of models for Corporates or Education who require the highest standards of performance and ecological features but work to a price point. Models available include SVGA, XGA and WXGA, Conventional and Short Throw Models. Most models include exceptionally long lamp and filter life as well as innovative ecological features and similarly the majority of our models include a special warranty upgrade for Education. Power is also an option with the M420X boasting 4200 ANSI Lumen.

Empowered by Innovation **NEC**



COMPARISON CHART
Value, MultiPurpose and Short Throw
Projectors **November 2012**

GENERAL		IMAGE															
Part Code	Product Name	Display	Aspect Ratio	Native Resolution	Brightness [ANSI Lumens]	Brightness in Eco Mode (approx. %)	Contrast Ratio	Lamp	Lamp (Eco Mode)	Lamp Life [hrs.]	Lamp Life Eco Mode [hrs.]	Projection Factor	Projection Distance [m]	Projection Angle	Screen Size (Diagonal: min. / max.) [cm (inch)]	Zoom: M = Manual, D = Digital	Focus Adjustment: M = Manual, D = Digital
VALUE IDEAL FOR CLASSROOMS, (SMALL) MEETING ROOMS, CROSS-USE (PRIVATE/PROFESSIONAL), MOBILE / COOPERATIVE APPLICATIONS																	
60003377	L51W LED	DLP 1 x 1.15 cm (0.45") DDR DMD Chip	16:10	1280 x 800 (WXGA)	500	50%	4000:1	LED Light Source	N/A	N/A	N/A	1.4 : 1	0.52 - 3	13.8	43.2 / 254 (17 / 100)	D	M
60003177	V230X	DLP 1 x 1.4 cm (0.55") DDR DMD Chip	4:3	1024 x 768 (XGA)	2300	90%	2000:1	180W AC	160W AC	3500	5000	1.95 - 2.15 : 1	1.2 - 13	12.8 - 14.0	76 / 762 (30 / 300)	M	M
60003176	V260	DLP 1 x 1.4 cm (0.55") DDR DMD Chip	4:3	800 x 600 (SVGA)	2600	90%	2000:1	180W AC	160W AC	3500	5000	1.95 - 2.15 : 1	1.2 - 13	12.8 - 14.0	76 / 762 (30 / 300)	M	M
60003180	V260W	DLP 1 x 1.65 cm (0.65") DDR DMD Chip	16:10	1280 x 800 (WXGA)	3500	90%	2000:1	180W AC	160W AC	3500	5000	1.95 - 2.15 : 1	1.0 - 10.9	12.9 - 14.1	76 / 762 (30 / 300)	M	M
60003178	V260X	DLP 1 x 1.4 cm (0.55") DDR DMD Chip	4:3	1024 x 768 (XGA)	3500	90%	2000:1	180W AC	160W AC	3500	5000	1.95 - 2.15 : 1	1.2 - 13	12.8 - 14.0	76 / 762 (30 / 300)	M	M
60003181	V300W	DLP 1 x 1.65 cm (0.65") DDR DMD Chip	16:10	1280 x 800 (WXGA)	3000	75%	2000:1	225W AC	170W AC	3000	5000	1.95 - 2.15 : 1	1 - 10.9	12.9 - 14.1	76 / 762 (30 / 300)	M	M
60003179	V300X	DLP 1 x 1.4 cm (0.55") DDR DMD Chip	4:3	1024 x 768 (XGA)	3000	75%	2000:1	225W AC	170W AC	3000	5000	1.95 - 2.15 : 1	1.2 - 13.0	12.8 - 14.0	76 / 762 (30 / 300)	M	M
MULTI-PURPOSE PARTICULARLY SUITED FOR CLASSROOMS AND SMALL TO MEDIUM SIZED MEETING ROOMS																	
60002958	M230X	3 x 1.6 cm (0.63") p-Si LCD Panel	4:3	1024 x 768 (XGA)	2300	80%	2000:1	180W AC	145W AC	5000	6000	1.3 - 2.2 : 1	0.7 - 14.5	6.5 - 11.4	63.5 / 762 (25 / 300)	M	M
60003404	M271X	3 x 1.6 cm (0.63") p-Si LCD Panel with MLA	4:3	1024 x 768 (XGA)	2700	80%	3000:1	145W AC	110W AC	6000	10000	1.3 - 2.2 : 1	0.7 - 14.7	6.5 - 11.4	63.5 / 762 (25 / 300)	M	M
60003408	M271W	3 x 1.5 cm (0.59") p-Si LCD Panel with MLA	16:10	1280 x 800 (WXGA)	2700	80%	3000:1	145W AC	110W AC	6000	10000	1.3 - 2.2 : 1	0.7 - 14.7	6.5 - 11.4	63.5 / 762 (25 / 300)	M	M
60003405	M311X	3 x 1.6 cm (0.63") p-Si LCD Panel with MLA	4:3	1024 x 768 (XGA)	3100	80%	3000:1	145W AC	110W AC	6000	10000	1.3 - 2.2 : 1	0.7 - 14.7	6.5 - 11.4	63.5 / 762 (25 / 300)	M	M
60003407	M311W	3 x 1.5 cm (0.59") p-Si LCD Panel with MLA	16:10	1280 x 800 (WXGA)	3100	75%	3000:1	230W AC	175W AC	5000	8000	1.3 - 2.2 : 1	0.7 - 14.7	6.5 - 11.4	63.5 / 762 (25 / 300)	M	M
60003406	M361X	3 x 1.6 cm (0.63") p-Si LCD Panel with MLA	4:3	1024 x 768 (XGA)	3600	75%	3000:1	230W AC	175W AC	5000	8000	1.3 - 2.2 : 1	0.7 - 14.7	6.5 - 11.4	63.5 / 762 (25 / 300)	M	M
60003131	M420X	3 x 1.6 cm (0.63") p-Si LCD Panel with MLA	4:3	1024 x 768 (XGA)	4200	75%	2000:1	265W AC	195W AC	3000	3500	1.3 - 2.2 : 1	0.6 - 13.8	6.5 - 11.4	63.5 / 762 (25 / 300)	M	M
SHORT THROW IDEAL FOR CLASSROOMS AND SMALL TO MEDIUM SIZED MEETING ROOMS																	
60003072	M260WS	3 x 1.5 cm (0.59") p-Si LCD Panel with MLA	16:10	1280 x 800 (WXGA)	2600	75%	2000:1	230W AC	170W AC	4000	5000	0.47 : 1	0.6 - 1.1	37.3 - 38.6	142.2 / 264.2 (56 / 104)	D	M
60003074	M260XS	3 x 1.6 cm (0.63") p-Si LCD Panel with MLA	4:3	1024 x 768 (XGA)	2600	80%	2000:1	180W AC	145W AC	5000	6000	0.47 : 1	0.6 - 1.1	37.3 - 38.6	152.4 / 279.4 (60 / 110)	D	M
60003075	M300WS	3 x 1.5 cm (0.59") p-Si LCD Panel with MLA	16:10	1280 x 800 (WXGA)	3000	75%	2000:1	265W AC	195W AC	3000	3500	0.47 : 1	0.6 - 1.1	37.3 - 38.6	142.2 / 264.2 (56 / 104)	D	M
60003076	M300XS	3 x 1.6 cm (0.63") p-Si LCD Panel with MLA	4:3	1024 x 768 (XGA)	3000	75%	2000:1	230W AC	170W AC	4000	5000	0.47 : 1	0.6 - 1.1	37.3 - 38.6	152.4 / 279.4 (60 / 110)	D	M
60003077	M350XS	3 x 1.6 cm (0.63") p-Si LCD Panel with MLA	4:3	1024 x 768 (XGA)	3500	75%	2000:1	265W AC	195W AC	3000	3500	0.47 : 1	0.6 - 1.1	37.3 - 38.6	152.4 / 279.4 (60 / 110)	D	M



This document is © copyright 2012 NEC Display Solutions Europe GmbH. All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 24.10.2012

www.nec-display-solutions.com



GENERAL				CONNECTIVITY										ELECTRICAL				MECHANICAL		ERGONOMICS		WARRANTY			
Part Code	Product Name	RGB Input: Mini D-sub 15 pin	RGB Output: Mini D-sub 15 pin	Video Input: RCA	HDMI® (Deep Color, Lip sync)	S-Video Input: Mini DIN 4-pin	Audio Input: RCA Stereo	Audio Input: 3.5 mm Stereo Mini Jack	Audio Output: 3.5 mm Stereo Mini Jack	PC Control Input: F = Mini DIN 8 pin (Female), M = D-Sub 9 pin (RS-232) (Male)	USB Type A (USB 2.0)	USB Type B	LAN (RJ45)	SD Card	Power Consumption Normal Mode [W]	Power Consumption ECO Mode [W]	Power Consumption Network Standby Mode [W]	Power Consumption Power-Saving Mode [W]	Dimensions without lens and feet (W x H x D) [mm]	Weight [kg]	Speakers (mono) [W]	TCO	Projector: 3 years pan-European Premium Service	Lamp: 6 Months, max. 1000 Hrs	Education Warranty Available

VALUE IDEAL FOR CLASSROOMS, (SMALL) MEETING ROOMS, CROSS-USE (PRIVATE/PROFESSIONAL), MOBILE / COOPERATIVE APPLICATIONS

60003377	L51W LED	1	-	1	1	-	-	1	-	-	1	1	-	1	105	70	-	0.5	226 x 43 x 174	1.2	1 x 2	-	●	N/A	-
60003177	V230X	1	1	1	-	1	-	1	-	M	-	-	-	-	233	210	4	0.8	310 x 95 x 247	2.5	1 x 7	●	●	●	-
60003176	V260	1	1	1	-	1	-	1	-	M	-	-	-	-	233	210	4	0.8	310 x 95 x 247	2.5	1 x 7	-	●	●	-
60003180	V260W	2	1	1	1	1	-	2	1	M	-	-	1	-	233	210	4	0.8	310 x 95 x 247	2.5	1 x 7	-	●	●	●
60003178	V260X	2	1	1	1	1	-	2	1	M	-	-	1	-	233	210	4	0.8	310 x 95 x 247	2.5	1 x 7	●	●	●	●
60003181	V300W	2	1	1	1	1	-	2	1	M	-	-	1	-	268	210	4	0.8	310 x 95 x 247	2.5	1 x 7	-	●	●	●
60003179	V300X	2	1	1	1	1	-	2	1	M	-	-	1	-	268	210	4	0.8	310 x 95 x 247	2.5	1 x 7	●	●	●	●

MULTI-PURPOSE PARTICULARLY SUITED FOR CLASSROOMS AND SMALL TO MEDIUM SIZED MEETING ROOMS

60002958	M230X	2	1	1	1	1	1	2	1	M	2	1	1	-	239	193	8	0.4	339 x 99 x 257	2.9	1 x 10	●	●	●	●
60003404	M271X	2	1	1	1	1	2	2	1	M	2	1	1	-	193	172	8	0.4	339 x 99 x 257	2.99	1 x 10	-	●	●	●
60003408	M271W	2	1	1	1	1	2	2	1	M	2	1	1	-	193	172	8	0.4	339 x 99 x 257	2.99	1 x 10	-	●	●	●
60003405	M311X	2	1	1	1	1	2	2	1	M	2	1	1	-	193	172	8	0.4	339 x 99 x 257	2.99	1 x 10	-	●	●	●
60003407	M311W	2	1	1	1	1	2	2	1	M	2	1	1	-	236	211	8	0.4	339 x 99 x 257	2.99	1 x 10	●	●	●	●
60003406	M361X	2	1	1	1	1	2	2	1	M	2	1	1	-	236	211	8	0.4	339 x 99 x 257	2.99	1 x 10	-	●	●	●
60003131	M420X	2	1	1	1	1	2	2	1	M	2	1	1	-	343	264	8	0.4	398 x 115 x 282	3.6	1 x 10	-	●	●	●

SHORT THROW IDEAL FOR CLASSROOMS AND SMALL TO MEDIUM SIZED MEETING ROOMS

60003072	M260WS	2	1	1	1	-	2	2	1	M	2	1	1	-	302	236	8	0.4	398 x 140 x 309.5	4.0	1 x 10	●	●	●	●
60003074	M260XS	2	1	1	1	1	2	2	1	M	2	1	1	-	239	193	8	0.4	398 x 140 x 309.5	4.0	1 x 10	●	●	●	●
60003075	M300WS	2	1	1	1	1	2	2	1	M	2	1	1	-	343	264	8	0.4	398 x 140 x 309.5	4.0	1 x 10	●	●	●	●
60003076	M300XS	2	1	1	1	1	2	2	1	M	2	1	1	-	302	236	8	0.4	398 x 140 x 309.5	4.0	1 x 10	●	●	●	●
60003077	M350XS	2	1	1	1	1	2	2	1	M	2	1	1	-	343	264	8	0.4	398 x 140 x 309.5	4.0	1 x 10	●	●	●	●



NEC Ultrashort Throw Projectors provide a comprehensive range of models for Corporates or Education who require the highest standards of performance and ecological features but work to a price point. Models available include XGA and WXGA in both our popular U Series and our new professional quality UM Series. Most models include exceptionally long lamp and filter life as well as innovative ecological features and similarly the majority of our models include a special warranty upgrade for Education.

Empowered by Innovation



GENERAL		IMAGE															
Part Code	Product Name	Display	Aspect Ratio	Native Resolution	Brightness (ANSI Lumens)	Brightness in Eco Mode (approx. %)	Contrast Ratio	Lamp	Lamp (Eco Mode)	Lamp Life (hrs.)	Lamp Life Eco Mode (hrs.)	Projection Factor	Projection Distance [m]	Projection Angle	Screen Size (Diagonal: min. / max.) [cm (inch)]	Zoom: M = Manual, D = Digital	Focus Adjustment: M = Manual, D = Digital

ULTRA SHORT THROW IDEAL FOR MEETING ROOMS AND DIGITAL SIGNAGE APPLICATIONS, AS WELL AS FOR CLASSROOMS

60002965	U250X	DLP 1 x 1.4 cm (0.55") 2x LVDS DMD	4:3	1024 x 768 (XGA)	2500	82%	2000:1	230W AC	190W AC	2500	4000	0.377 : 1	0.132 – 0.319	55.3	160 / 216 (63 / 85)	D	M
60002966	U260W	DLP 1 x 1.65 cm (0.65") 2x LVDS DMD	16:10	1280 x 800 (WXGA)	2600	82%	2000:1	230W AC	190W AC	2500	4000	0.3 : 1	0.152 – 0.319	55.3	196 / 254 (77 / 100)	D	M
60002971	U300X	DLP 1 x 1.4 cm (0.55") 2x LVDS DMD	4:3	1024 x 768 (XGA)	3000	87%	2000:1	280W AC	245W AC	2500	3000	0.377 : 1	0.132 – 0.319	55.3	160 / 216 (63 / 85)	D	M
60003068	U310W	DLP 1 x 1.65 cm (0.65") 2x LVDS DMD	16:10	1280 x 800 (WXGA)	3100	87%	2000:1	280W AC	245W AC	2500	3000	0.3 : 1	0.152 – 0.319	55.3	196 / 254 (77 / 100)	D	M
60003391	UM280X	3 x 1.6 cm (0.63") p-Si LCD Panel with MLA	4:3	1024 x 768 (XGA)	2800	60%	3000:1	170W AC	140W AC	5000	8000	0.36 : 1	0.45 - 0.85	49.2	152.4 / 279.4 (60 / 100)	D	M
60003390	UM280W	3 x 1.5 cm (0.59") p-Si LCD Panel with MLA	16:10	1280 x 800 (WXGA)	2800	60%	3000:1	170W AC	140W AC	5000	8000	0.36 : 1	0.45 - 0.85	53.1	161.5 / 269.2 (63 / 100)	D	M
60003393	UM330X	3 x 1.6 cm (0.63") p-Si LCD Panel with MLA	4:3	1024 x 768 (XGA)	3300	60%	3000:1	195W AC	160W AC	3500	6000	0.36 : 1	0.45 - 0.85	49.2	152.4 / 279.4 (60 / 100)	D	M
60003392	UM330W	3 x 1.5 cm (0.59") p-Si LCD Panel with MLA	16:10	1280 x 800 (WXGA)	3300	60%	3000:1	195W AC	160W AC	3500	6000	0.36 : 1	0.45 - 0.85	53.1	160 / 269.2 (63 / 100)	D	M

COMPARISON CHART

Ultra Short Throw Projectors November 2012

COMPARISON CHART

Ultra Short Throw Projectors November 2012



This document is © copyright 2012 NEC Display Solutions Europe GmbH. All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 24.10.2012

www.nec-display-solutions.com

Empowered by Innovation **NEC**

GENERAL		CONNECTIVITY										ELECTRICAL				MECHANICAL		ERGONOMICS		WARRANTY						
Part Code	Product Name	RGB Input: Mini D-sub 15 pin	RGB Output: Mini D-sub 15 pin	Video Input: RCA	HDMI® (Deep Color, Lip sync)	S-Video Input: Mini DIN 4-pin	Audio Input: RCA Stereo	Audio Input: 3.5 mm Stereo Mini Jack	Audio Input: 3.5 mm Microphone Jack	Audio Output: 3.5 mm Stereo Mini Jack	PC Control Input: F = Mini DIN 8 pin (Female), M = D-Sub 9 pin (RS-232) (Male)	USB Type A (USB 2.0)	USB Type B	LAN (RJ45)	SD Card	Power Consumption Normal Mode [W]	Power Consumption ECO Mode [W]	Power Consumption Network Standby Mode [W]	Power Consumption Power-Saving Mode [W]	Dimensions without lens, and feet (W x H x D) [mm]	Weight [kg]	Speakers (mono) [W]	TCO	Projector: 3 years pan-European Premium Service	Lamp: 6 Months, max. 1000 Hrs	Education Warranty Available
ULTRA SHORT THROW IDEAL FOR MEETING ROOMS AND DIGITAL SIGNAGE APPLICATIONS, AS WELL AS FOR CLASSROOMS																										
60002965	U250X	2	1	1	1	1	1	2	1	1	M	-	-	1	-	300	244	3	0.5	427 x 200 x 406	6.5	1 x 10	●	●	●	●
60002966	U260W	2	1	1	1	1	1	2	1	1	M	-	-	1	-	300	245	3	0.5	427 x 200 x 406	6.5	1 x 10	●	●	●	●
60002971	U300X	1	1	1	1	1	1	2	1	1	M	-	-	1	-	360	315	3	0.5	427 x 200 x 406	6.5	1 x 10	●	●	●	●
60003068	U310W	2	1	1	1	1	1	2	1	1	M	-	-	1	-	360	315	3	0.5	427 x 200 x 406	6.5	1 x 10	●	●	●	●
60003391	UM280X	1	1	1	2	1	2	1	1	1	M	2	1	1	-	235	212	8	0.4	378 112 x 428	5.2	1 x 16	●	●	●	●
60003390	UM280W	1	1	1	2	1	2	1	1	1	M	2	1	1	-	235	212	8	0.4	378 112 x 428	5.2	1 x 16	●	●	●	●
60003393	UM330X	1	1	1	2	1	2	1	1	1	M	2	1	1	-	263	233	8	0.4	378 112 x 428	5.2	1 x 16	-	●	●	●
60003392	UM330W	1	1	1	2	1	2	1	1	1	M	2	1	1	-	263	233	8	0.4	378 112 x 428	5.2	1 x 16	-	●	●	●



A TRADITION OF PERFORMANCE

Following a tradition of producing Reference quality display products in the Digital Cinema and Large Format Display Sector, the new range of NEC Installation projectors provide the ultimate in performance with a model for all requirements from Corporate Conference Rooms to Professional Auditoriums, with brightness as high as 11,000 ANSI Lumen and WUXGA.

Empowered by Innovation



GENERAL		IMAGE												
Part Code	Product Name	Display	Aspect Ratio	Native Resolution	Brightness (ANSI Lumens)	Brightness in Eco Mode (approx. %)	Contrast Ratio (DB™ = with DynamicBlack™)	Lamp	Lamp (Eco Mode)	Lamp Life (hrs.)	Lamp Life Eco Mode (hrs.)	Lens (mm)	Lens: optional bayonet lenses (LM = with lens memory)	Projection Factor (std. option)
INSTALLATION NEC 4100 SERIES - IDEAL FOR EDUCATION, IT SECTOR AND CORPORATE NEC P SERIES - BEST SOLUTION FOR LARGER MEETING ROOMS AND UNIVERSITY LECTURE HALLS														
60002354	NP4100	1 x 1.78 cm (0.7") DMD Chip - DLP™ Technology	4:3	1024 x 768 (XGA)	6200	80%	2100:1 DB™	2 x 280 W AC	2 x 224W AC	2000	3000	optional	5	1.78 - 2.35 : 1 (NP08ZL)
60003086	P350W	3 x 1.5 cm (0.59") p-Si LCD Panel with MLA	16:10	1280 x 800 (WXGA)	3500	75%	2000:1	265 W UHP AC	195 W UHP AC	3000	3500	F= 1.7-2.0, f= 17.4-29.0	-	1.3 - 2.2 : 1
60003081	P420X	3 x 1.6 cm (0.63") p-Si LCD Panel with MLA	4:3	1024 x 768 (XGA)	4200	75%	2000:1	265 W UHP AC	195 W UHP AC	3000	3500	F= 1.7-2.0, f= 17.4-29.0	-	1.3 - 2.2 : 1
ADVANCED INSTALLATION IDEAL FOR CORPORATE, HIGH EDUCATION AND RENTAL														
60003082	PA500U	3 x 1.93 cm (0.76") p-Si inorganic LCD Panel with MLA	16:10	1920 x 1200 (WUXGA)	5000	80%	2000:1	330 W UHP AC	264 W UHP AC	3000	4000	optional	5	1.5-3.02:1 (NP13ZL)
60003083	PA500X	3 x 2 cm (0.79") p-Si inorganic LCD Panel with MLA	4:3	1024 x 768 (XGA)	5000	80%	2000:1	330 W UHP AC	264 W UHP AC	3000	4000	optional	5	1.5-3.02:1 (NP13ZL)
60003085	PA550W	3 x 1.9 cm (0.75") p-Si inorganic LCD Panel with MLA	16:10	1280 x 800 (WXGA)	5500	80%	2000:1	330 W UHP AC	264 W UHP AC	3000	4000	optional	5	1.5-3.02:1 (NP13ZL)
60003084	PA600X	3 x 2 cm (0.79") p-Si inorganic LCD Panel with MLA	4:3	1024 x 768 (XGA)	6000	80%	2000:1	330 W UHP AC	264 W UHP AC	3000	4000	optional	5	1.5-3.02:1 (NP13ZL)
EXTREME PERFORMANCE INSTALLATION IDEAL FOR RENTAL/STAGING, LARGE CORPORATE, HIGH EDUCATION, CONFERENCE ROOM, MUSEUM AND SIGNAGE														
60003183	PX700W	1.65 cm (0.65") DMD Chip - DLP™ Technology	16:10	1280 x 800 (WXGA)	7000	80%	2100:1 DB™	2 x 400 W AC	2 x 320W AC	2000	2500	optional	6 (5 with LM)	0.76:1 & 1.25-8.3:1
60003182	PX750U	1.7 cm (0.67") DMD Chip - DLP™ Technology	16:10	1920 x 1200 (WUXGA)	7500	80%	2100:1 DB™	2 x 400 W AC	2 x 320W AC	2000	2500	optional	6 (5 with LM)	0.76:1 & 1.25-8.3:1
60003184	PX800X	1.78 cm (0.7") DMD Chip - DLP™ Technology	4:3	1024 x 768 (XGA)	8000	80%	2100:1 DB™	2 x 400 W AC	2 x 320W AC	2000	2500	optional	6 (5 with LM)	0.76:1 & 1.25-8.3:1
HIGH PERFORMANCE INSTALLATION BEST SOLUTION FOR RENTAL / STAGING, HIGH EDUCATION AND DIGITAL SIGNAGE														
60003275	PH1000U	3 x 2.44 cm (0.96") 3-Chip - DLP™ Technology	16:10	1920 x 1200 (WUXGA)	11000	75%	2000:1	2 x 400 W AC	2 x 320W AC	2000	2500	optional	5 (4 with LM)	0.67:1&1:1& 1.39-6.96:1

COMPARISON CHART

Installation Projectors November 2012

This document is © copyright 2012 NEC Display Solutions Europe GmbH. All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 24.10.2012

Empowered by Innovation



www.nec-display-solutions.com

GENERAL		IMAGE					CONNECTIVITY										ELECTRICAL				MECHANICAL			ERGONOMICS		WARRANTY										
Part Code	Product Name	Projection Distance [m]	Screen Size (Diagonal: min. / max.) [cm]	Lens Adjustment: MAN = Manual, MOT = Motorised	Frequency Horizontal [kHz]	Frequency Vertical [Hz]	Computer Analog Input: 5 BNC	Computer Analog Input: Mini D-sub 15 pin	Computer Analog Output: Mini D-sub 15 pin	Computer Digital Input: DisplayPort	Computer Digital Input: HDMI® D = DVI-D (with HDCP)	Video Input: RCA	S-Video Input: Mini DIN 4-pin	Audio Input: RCA Stereo	Audio Input: 3.5 mm Stereo Mini Jack	Audio Input: HDMI Audio Support	Audio Input: DisplayPort Audio Support	Audio Output: 3.5 mm Stereo Mini Jack (variable)	PC Control Input: D-Sub 9 pin (RS-232)	Remote Control Input: 3.5 mm Stereo Mini Jack	USB Type A (USB 2.0)	USB Type B	LAN (RJ45, 10/100 base-T)	Power Consumption Normal Mode Single Lamp / Dual Lamp [W]	Power Consumption Eco-Mode Single Lamp / Dual Lamp [W]	Power Consumption Normal Stand-by Mode [W]	Power Consumption Network Stand-by Mode [W]	Power Consumption Power Saving Mode [W]	Dimensions without lens and feet (W x H x D) [mm]	Weight [kg]	Fan Noise Eco Mode Single Lamp / Dual Lamp [dB (A)]	Fan Noise Normal Mode Single Lamp / Dual Lamp [dB (A)]	Speakers [W]:	ErP	Projector: 3 years pan-European Premium Service	Lamp: 6 Months, max. 1000 Hrs

INSTALLATION NEC 4100 SERIES - IDEAL FOR EDUCATION, IT SECTOR AND CORPORATE | NEC P SERIES - BEST SOLUTION FOR LARGER MEETING ROOMS AND UNIVERSITY LECTURE HALLS

60002354	NP4100	1.42 – 24.35 (NP08ZL)	102 (40") / 1270 (500")	MOT	15–90	50 – 85	1	1	1	-	D	1	1	2	3	-	-	1	1	1	-	1	1	365 / 690	310 / 540	30	30	1	505 x 197 x 385	17.5	31 / 34	34 / 38	2x3W	-	●	●
60003086	P350W	0.7 – 14.6	64 (25") / 762 (300")	MAN	15–100 (RGB: 24)	50 – 120	-	2	1	-	1	1	1	2	1	-	1	1	-	2	1	1	343	264	9	9	0.4	398 x 282 x 115	3.9	30	36	1x10W	●	●	●	
60003081	P420X	0.6 – 13.8	64 (25") / 762 (300")	MAN	15–100 (RGB: 24)	50 – 120	-	2	1	-	1	1	1	2	1	-	1	1	-	2	1	1	343	264	9	9	0.4	398 x 282 x 115	3.9	30	36	1x10W	●	●	●	

ADVANCED INSTALLATION IDEAL FOR CORPORATE, HIGH EDUCATION AND RENTAL

60003082	PA500U	0.70 (NP11FL) - 76.4 (NP15ZL)	76 (30") / 1270 (500")	MAN	15–108 (RGB: 24–108)	48 – 120	1	2	1	1	1	1	1	3	1	1	1	1	1	2	-	1	455	369	18	6	0.2	499 x 144 x 359	7.8	32	38	1x10W	●	●	●
60003083	PA500X	0.50 (NP11FL) - 76.4 (NP15ZL)	76 (30") / 1270 (500")	MAN	15–108 (RGB: 24–108)	48 – 120	1	2	1	1	1	1	1	3	1	1	1	1	1	2	-	1	443	356	18	6	0.2	499 x 144 x 359	7.7	31	38	1x10W	●	●	●
60003085	PA550W	0.50 (NP11FL) - 76.4 (NP15ZL)	76 (30") / 1270 (500")	MAN	15–108 (RGB: 24–108)	48 – 120	1	2	1	1	1	1	1	3	1	1	1	1	1	2	-	1	443	356	18	6	0.2	499 x 144 x 359	7.7	31	38	1x10W	●	●	●
60003084	PA600X	0.50 (NP11FL) - 76.4 (NP15ZL)	76 (30") / 1270 (500")	MAN	15–108 (RGB: 24–108)	48 – 120	1	2	1	1	1	1	1	3	1	1	1	1	1	2	-	1	443	356	18	6	0.2	499 x 144 x 359	7.7	31	38	1x10W	●	●	●

EXTREME PERFORMANCE INSTALLATION IDEAL FOR RENTAL/STAGING, LARGE CORPORATE, HIGH EDUCATION, CONFERENCE ROOM, MUSEUM AND SIGNAGE

60003183	PX700W	0.8 (NP16FL) - 54 (NP21ZL)	127 (50") / 762 (300")	MOT	15–108 (RGB: 24)	48 – 120	1	2	1	1	1	1	1	-	-	-	-	-	1	1	2	-	1	494 / 931	405 / 753	27	18	0.4	504 x 192 x 516	19.7	39	43	-	●	●	●
60003182	PX750U	0.8 (NP16FL) - 54 (NP21ZL)	127 (50") / 762 (300")	MOT	15–108 (RGB: 24)	48 – 120	1	2	1	1	1	1	1	-	-	-	-	-	1	1	2	-	1	515 / 958	429 / 777	34	23	0.4	504 x 192 x 516	19.7	39	43	-	●	●	●
60003184	PX800X	0.8 (NP16FL) - 54 (NP21ZL)	127 (50") / 762 (300")	MOT	15–108 (RGB: 24)	48 – 120	1	2	1	1	1	1	1	-	-	-	-	-	1	1	2	-	1	489 / 927	404 / 752	28	18	0.4	504 x 192 x 516	19.7	39	43	-	●	●	●

HIGH PERFORMANCE INSTALLATION BEST SOLUTION FOR RENTAL / STAGING, HIGH EDUCATION AND DIGITAL SIGNAGE

60003275	PH1000U	1.1 (NP25FL) - 74 (NP29ZL)	203 (80") / 1270 (500")	MOT	15–108 (RGB: 24)	48 – 120	1	2	1	1	1	1	1	-	-	-	-	-	1	1	2	-	1	580 / 1050	490 / 840	90	60	0.5	578 x 235 x 558	40	41 / 43	41 / 45	-	●	●	●
----------	---------	----------------------------	-------------------------	-----	------------------	----------	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	------------	-----------	----	----	-----	-----------------	----	---------	---------	---	---	---	---