# TM-T88V-i

### DATASHEET





Epson's main strength is its compact, energy saving and high precision technologies that it has acquired and developed over the years. The same applies to Epson's TM series of thermal receipt printers where Epson has refined its original printer mechanisms and technologies to create products that are distinct from those of competitors such as Star, Bixolon, Citizen and SII. As part of its efforts to maintain its market leadership, Epson has also developed its original ESC/Pos command language for receipt printers.

As a result of these efforts, Epson receipt printers have become a global standard. Sold throughout the world, the company's miniprinters have been highly evaluated by customers with sales now surpassing 300 million units.

The latest innovation in Epson's long line of receipt printers are its series of smart receipt printers. Built on the firm foundations Epson has established over the years they have been created to meet the needs of the age.

TM-T88V-i

The Epson TM-T88V-i provides users with a straightforward and elegant printing solution, with no need for drivers. Ideal for use with tablet PCs or mobile phones, the TM-T88V-i is simple to use and maintain, with the ability to print from any device running an HTML 5 compatible web browser. In addition, the TM-T88V-i has greyscale printing for the addition of logos and images to receipts.

## **KEY FEATURES**

- Print via browsers Print directly from HTML 5 browsers
- No drivers needed No drivers to install or update
- XML compatible Responds to web application commands
  ESC/POS function
- Recognises functions sent as XML
- Greyscale printing Add logos and images to materials



## PRODUCT SPECIFICATIONS

Print method	Thermal line printing	- \
INTERFACES		_
Interfaces	Ethernet interface (100 Base-TX / 10 Base-T), USB 2.0 Type A (4x), USB 2.0 Micro-AB, SD	G
	memory card, blank	_
GENERAL		7
Product dimensions	145 x 195 x 148 mm (Width x Depth x Height)	(
Product weight	16 kg	
Color	Epson Dark Gray / Epson Cool White	•
Sound Pressure	Operation: 55 dB (A)	
Installation	horizontally	
Humidity	Operation 10% - 90%, Storage 10% - 90%	
Temperature	Operation 5° C - 45° C, Storage -10° C - 50° C	
FONTS & STYLES		
Print Speed	300 mm/sec	
Printing Font	ANK	
Character size	0.99 mm (W) x 2.4 mm (H) / 1.41 mm (W) x 3.39 mm (H)	
Character set	95 Alphanumeric, 18 set International, 128 x 43 Graphic	
Dot density	180 dpi x 180 dpi	
DATA BUFFER		
Data Buffer	4 kB or 45 Bytes	
STANDARDS COMPLIANCE		
EMC Standards	CE marking	
Safety standards	τϋν	
OTHER FEATURES		
Cutter	Partial Cut	
Factory options	Autocutter, Near-end sensor	
Sensors	Unit open sensor, Paper End Sensor, Paper Near End Sensor	

TM-T88V-i

#### WHAT'S IN THE BOX

AC Adaptor

#### OPTIONAL ACCESSORIES

• Epson OT-WL01 (732): Wireless LAN set for Epson TM-i C32C890732

For more information please contact:

Telephone: 01952 607111 (UK)+ 01 436 7742 (Republic of Ireland) E-mail: enquiries@epson.co.uk Chat: etalk.epson-europe.com Fax: 0871 222 6740 + Local call rate. Web: www.epson.co.uk www.epson.ie

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.

