



2019 Model Year Standard Specification



Principal Dimensions

Length overall (incl. pulpit)

fixed platform:

49'2" (15.0m)

Length overall (excl. pulpit)

fixed platform: 48'6" (14.8m)

Length overall (incl. pulpit)

submersible platform: 51'4" (15.64m)

Length overall (excl. pulpit)

submersible platform: 50'8" (15.44m)

Transport height:

15'10" (4.83m)

Dry weight (approx.):

12.79 imp. tons / 14.33 US tons

(13,000kg)

Beam (incl. gunwale):

14'2" (4.32m)

Berths:

4 - 7

Draught:

3'10" (1.17m) unloaded

Height above waterline

(incl. arch & nav. light mast):

15'1" (4.6m)

Fuel capacity:

288 gallons / 346 US gallons

(1,309 litres)

Water capacity (incl. calorifier):

106 gallons / 127 US gallons

(482 litres)

Engines

& Performance

2 x Volvo Penta IPS600 D6-435, diesel

(435mhp each):

32 knots

Type approval:

В

2 x Volvo Penta IPS700 D8-550, diesel

(550mhp each):

34 knots

Max. persons capacity:

16



Deck Plans

Main Deck



Lower Deck 2 Cabin



Lower Deck 3 Cabin





Deck

Targa 48 OPEN

Anchor chain locker
Anchor winch controls
Anchor winch (electric)
Calibrated anchor chain
Dinghy garage
Ensign & staff

Fender set
Full set of IMCO navigation lights
Hot & cold water transom shower
Moulded non-slip deck surface
Recessed self-draining area on
foredeck for coachroof sun cushions

Riding light Rubbing strake

Self-stowing Delta® anchor Stainless steel bow fairleads Stainless steel bow, spring & stern

cleats

Stainless steel handrails Stainless steel pulpit

Stainless steel stemhead roller
Stainless steel transom wing cleats
Swim ladder to bathing platform
Teak-laid bathing platform (with
option of submersible platform)
Toughened glass curved windscreen
Transom gate from cockpit to integral

bathing platform Twin horns Water filler

Windscreen washers Windscreen wipers

Helm Position

12V socket

Bilge pump switches with integral operating warning lights & audible

alarms

Twin helm seat

Controls for engine bay fire extinguisher system
Drinks holders

Electronic single-lever throttle & gear controls for port & starboard engines

Folding foot plinth Fuel gauges

Full engine instrumentation including; tachometers, oil pressure gauges, temperature gauges, audible alarms &

engine hour meters

Garmin GMi 20 digital multi-function instrument system with colour display

Garmin VHF marine radio
Helm position indicator
High-speed magnetic compass

IPS joystick

Remote anchor winch controls
Searchlight with remote control at

helm

Waterproof switches for navigation & riding lights, windscreen wipers & engine bay extractor fan

Electrical Systems

All 240V, 24V & 12V circuits (where applicable) protected by circuit breakers with main electrical load control panel

Electrical sockets

Heavy duty circuit breakers Isolating switches to all batteries



Targa 48 OPEN

12 Volt 240 Volt

Batteries – 2 x heavy duty batteries for Polarity check & earth leakage

domestic services protection system

1 x heavy duty battery for exclusive Power points throughout the boat fed port engine starting from shore power or generator

1 x heavy duty battery for exclusive Regulated battery charger

starboard engine starting Shore power supply Emergency battery coupling system

permits starboard engine to start port engine if domestic batteries accidently

discharged

12V heavy duty weatherproof socket Cockpit

Bathing platform lights Manual bilge pumps

Boat hook Mooring warps

Moulded non-slip deck surface Central dining area with table Stainless steel handrails Companion seating to helm Step for side deck access **Drinks holders**

Stowage lockers under companion Engine bay access hatch

Life raft stowage

seat Fender stowage

Warp lockers Glove locker

Waterproof speaker's x 2

Choice of interior finishes from the Amalfi, Capri, Hamptons or St Tropez Interior Décor interior styling ranges selected by the Fairline Yachts Design Studio

Antifouling protection to hull Integrally moulded engine bearers **Hullform & Construction**

Deep 'V' hull Polyurethane foam cores throughout deck for strength & thermal insulation Design, layout & detailing by the Fairline Yachts Design Studio Resin infused hull & internal liner

Transverse & longitudinal Full length moulded spray deflectors

strengthening stringers throughout Hard top with electric sliding canvas hull roof

Hull colour - White

Access to day head 22" LCD television Saloon

Aerial & connections for television Lockers (overhead) Cocktail table converts to dining table Radio & iPod dock with 2 speakers

Companionway timber steps with Sliding door to cockpit with integral handrail blind system

First aid kit

Hull window Stowage locker under dinette seating

LED ceiling lights Underfloor stowage locker



Targa 48 OPEN

Hand basin with hot & cold water

Mirror

Opening porthole

Stowage locker

Control panel for 12V/240V domestic Integrated waste bin Galley electrical circuits Lacquered cupboard doors Crockery stowage LED ceiling lights Extractor fan Lockers (overhead) Fire extinguisher Sink with hot & cold mixer tap Foundations® work surface with Tall fridge/freezer with automatic covers 12V/240V change-over Hob, oven & grill Work surface lights **Hull window** Access to en suite LED ceiling lights **Master Cabin** Bedside tables Opening portholes Chest of drawers **Reading lights** Full length double bed Vanity unit Full length mirror Wardrobe Full standing-height shower with Automatic shower tray pump-out Master En Suite integral shower tray & adaptable system shower head Electric silent-flush freshwater toilet Hand basin with hot & cold water Extractor fan Solid surface vanity unit locker & basin Mirror with hot & cold pressurised water Opening porthole Full set of bathroom fittings Stowage locker Access to shower/WC compartment LED ceiling lights **Forward Cabin** Bedside tables Lockers (overhead) Double bed converting to V-berth Low level drawers Full length mirror Opening portholes Hatch to foredeck Reading lights Headboard shelf unit Trinket locker Wardrobe Full length mirror Opening porthole Third Cabin Full length twin bunk beds Reading lights Optional, in lieu of saloon Wardrobe LED ceiling lights Automatic shower tray pump-out Full standing-height shower with **Guest En Suite** integral shower tray & adaptable system shower head Electric silent-flush freshwater toilet

Extractor fan

water

Foundations® vanity unit locker & basin with hot & cold pressurised

Full set of bathroom fittings



Targa 48 OPEN

Engines & Sterngear

Automatic bilge pumps for engine bay with a manual 'on' override

Automatic engine bay fire extinguisher High capacity emergency manual bilge

system

Electric engine bay fans
Electric trim tabs with cathodic

protection

Engine bay lights

Engine room soundproofing

pump system with changeover valves
Sea cocks on all inlets/outlets below

waterline

Fuel System

Changeover valve system to permit each engine to draw fuel from & return fuel to either tank

Emergency fuel shut-off valves High capacity water separators & fuel

filters

Individual fillers & vents to port &

starboard Twin fuel tanks

Freshwater System

Automatic, pressurised supply

Calorifier hot water system

Water tank

USA Specifications
In addition to or in lieu of
those listed above

Voltage - 2 x 110V (220V) 60Hz

Whilst every effort is made to keep all sales literature up to date, it should not be regarded as an infallible statement of current specifications & does not constitute an offer for the sale of any particular boat. We continually seek to improve the specification & design of our boats, so alterations & upgrades to specifications take place continually.

Appointed dealers are not agents of Fairline Yachts Ltd & are not authorised to commit Fairline Yachts Ltd by any express of implied undertaking or representation.

Performance Figures: Power quoted in our literature for diesel inboard engines is crankshaft output.

Performance Estimates: Performance estimates are given in good faith, but are in no way guaranteed for any particular model. Dirt on the bottom of the boat, damage to the propellers, engine tuning, external water & air temperatures & the weight of crew, fuel & water carried can all adversely affect performance. For those & other reasons we can give no performance guarantees