Powerfully portable

It's a fact of life on the road: at some point, you need to recharge your notebook. The HP Slim Power Adapter is big on features that can help you do more when you're on the go—and its small size and light weight so it won't weigh you down.



Genuine HP Power Adapter

Tested on HP notebooks by HP engineers, the HP Slim Power Adapter features Smart-pin technology, so you can count on compatibility with any Smart-pin notebook from HP or Compaq and optimal power consumption. With built-in surge protection, this AC adapter looks out for your PC. Only HP Genuine Adapters can be guaranteed to be fully compatible with HP notebooks.

Recharge more than your notebook

The HP Slim Power Adapter offers flexibility for a variety of situations. Need a little more space? Stretch an extra three feet by attaching the included AC cord. Removable cables easily wrap around the less-than-1" thin pack for easy transport. And with the integrated USB port, you can enjoy two-for-one charging—your notebook plus your phone, MP3 player, or other device—from one outlet.

Features & Benefits

- Included USB port allows you to charge two devices with only one power outlet
- $\bullet\,$ Thin profile is less than 1" thick
- · Easy cable management of wires while on the go
- Built in surge protection for your peace of mind

Compatibility

· Compatible with any Smart Pin enabled or 90W barrel pin notebook

What's in the Box?

- AC Adapter
- AC Cord
- Smart-Pin DC Cable and Non-Smart DC cable

Warranty and Support

- One-year, worldwide parts-and-labor limited warranty
- 24x7 HP technical phone support during warranty period

Technical Specifications

- Input 100 to 240 VAC
- · Input Efficiency 87% min at 115 VAC
- Input frequency range 47 to 63 Hz
- Input AC current 1.6 A at 90 VAC, 0.85 A at 180 VAC
- Output Output power 90W
- DC output 19.5V
- 5 0V
- Hold-up time 5 msec at 115 VAC input
- Output current limit <11A, Over voltage protection- 29V max automatic shutdown
- Connector 3 pin/grounded, mates with interchangeable cords
- Environmental Design Operating temperature 32° to 104° F (0° to 40° C)
- Non-operating (storage) temperature -4° to 149° F (-20° to 65° C)
- Altitude 0 to 10,000 ft (0 to 3,048 m)
- Humidity 20% to 80%
- Storage Humidity 10% to 90%
- EMI and Safety Certifications CE Mark- full compliance with LVD and EMC directives
- Worldwide safety standards- IEC950, EN60950, UL1950, Class2, SELV
- Agency approvals- C-UL-US, NORDICS, DENAN, EN55022 Class B, CISPR22 Class B, NOM-1 NYCE; MTBF- over 200,000 hours at 25°C ambient condition.

Additional Information

Questions about the HP 90W Slim Adapter? Look us up online at www.hp.com

- HP Part Number: BT798AA#ABA
- UPC Code: 885631694015
- Tariff: 8504409520
- ITF 14 Master Carton: 10885631519148
- Country of Origin: China
- Master Carton Quantity: 8
 Master Carton Dimensions:
- 13.00" x 11.80" x 10.80"
- Master Carton Weight: 9.98 lbs
- Packaged Product Dimensions: 8.64" x 6.10" x 2.60"
- Unpackaged Product Dimensions:
- 5.43" x 2.28" x 0.67"
- Packaged Product Weight: 1.24 lbs
- Unpackaged Product Weight: 0.49 lbs
- Pallet Information:
 - -Dimensions:
 - 47.24"(L) x 39.37"(W) x 48.03"(H)
- -Layers: 4
- -Products per layer: 96
- -Total products per pallet: 384

VISIT WWW.HP.COM FOR MORE DETAILS!

[©]2010 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing shall be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. **09 10 r1 tg** Actual product may vary from image shown on datasheet.

