

Q8731A ^{B+} ^{13x 19"} _{A3+} ^{330x483mm} 380_{g/m²} (25 sheets)

HP Artist Matte Canvas

Easily frame your fine art prints when you use stretchable cotton-polyester blend canvas. The unique size makes it ideal for photography and enlargements. This subtle, textured finish canvas features a special ink-receptive coating for brilliant, water-resistant images.

Fade Resistant!	More than 200 years of light and thermal fade with the HP Photosmart Pro B9180 Photo Printer using HP 38 Pigment Inks ¹ Based on preliminary light-fade under glass and storage permanence (thermal degradation) testing by Wilhelm Imaging Research. For details, see www.hp.com/go/printpermanence. In Europe, Middle East and Africa, visit www.hp.com/eur/faderesistance.
Acid Free!	Ensure long-lasting reproductions, using canvas constructed with acid-free substrates and neutral coatings.
Water Resistant!	Special ink-receptive coating that protects the surface from cracking. Artwork and photographs are water resistant when printed using HP Vivera pigment inks.
Immediate Dry Time!	Ink dries immediately after printing. Allow 24 hours for the ink to cure before mounting or framing.
Lamination Suitable!	Can be laminated with commercially available pressure-sensitive laminate films. Product must be overcoated with a protective spray or liquid laminate.



©2006 Hewlett-Packard Development Company, L.P. The information contained in this document is subject to change without notice.

HP Artist Matte Canvas Technical Specification Sheet

MSRP	\$99.99 / €79.40	
Product # / Availability	Q8731A / Worldwide	
Country of Origin	United States	
Shelf Life	1 years, unopened in original package stored at 72 °F (+/- 5°)	
Optimized Compatibility	Optimized for the HP Photosmart Pro B9180, HP DesignJet Z2100 and Z3100 Photo Printer series	
Based Material	Polyester / cotton blend	

Thickness/caliper	18 mil/ 457 microns	ISO 534 Test Method
Weight/grammage	380 g/m²	ISO 536 Test Method
Finish	Matte	ASTM D-523 Test Method
CIE Whiteness	107	CIE Ganz 82 Test Method
ISO Brightness	91	n/a
Opacity	n/a	TAPPI T-425 Test Method
Operating temperature for optimum performance	15-25 °C ; (59-80 °F)	n/a
Operating humidity for optimum performance	40-60%	n/a
Other	Designed for indoor use. Mounting: Attach to rigid board or frame using staples or tacks. Not recommended: glue or pressure sensitive adhesive.	

For best results store media in a sealed bag.

