Description

"B+S" Automatic Digital Saccharimeter, ADS420, Two Single Wavelength, Conforms to ICUMSA Single (ISS) Sugar Scale, Included PC Software, Robust Touch Sensitive LCD Screen, -225~+225°Z 전자동 디지털 당편광계, 당 순도 측정, 편이한 조작, 온도 보상, 흡광도 표시



Automatic Digital Saccharimeter, ADS420 Single Sugar Scale from -225~+225° Z, Flow Package

- Origin: Made in England (영국)
- Single Sugar Scale (ISS) from -225 to +225 °Z
- LED Light Source & Interference Filter requires no Maintenance.
- A Single Temperature Sensor Provides the Measurement for Sugar Compensation
- Quartz Compensation Facilitates Accurate Verification and Calibration using a Quartz Control Plate
- * Simple Operation with four graphically presented Push Buttons
- * Can Measure Dark Samples of Up to 3 O.D.
- * High Accuracy to ±0.03°Z
- * Bright LED Display and Low Maintenance
- * Sugar Industry: Sugar Cane Juice, Sugar Beet Juice, Processed Sugar, Purity System

Standard Package: Included One 200mm Tube, Standard Lid, Sodium Wavelength Using a Glass Centre

Fill tube.

Flow Package: Included One Water Jacketed Funnel Flow Cell. Slot Lid. Sodium Wavelength Using a Funnel Flow Tube for Repetitive Sampling sucj as in a Busy Tare House.

Specifications

ISS (°Z)	Range	-225 ~ + 225
	Resolution	0.01
	Reproducibility	0.02
	Accuracy	±0.03
Light Source		LED/Interference Filter (589.3nm)
Beam Diameter		4 mm
Maximum Tube Length		220 mm
Reading Time		20 seconds
Temperature		5 ~ 40℃
Temperature Compensation		None, Sugar, Quartz to 20 ℃
Optical Density Range		0.0 ~ 3.0 O.D.
Interfaces		1×RS232 (Print or csv Format)
Net Weight		10.5 kg
Dimensions		
Power Supply		90~250V, 50/60Hz

주문 (Ordering)

-		
BS.37.20	Digital Saccharimeter, ADS420, Standard Package, Sodium Wavelength	18,556,830
	Including Saccarimeter, 200mm Centre Filling Glass Sample tube	
	Standard Lid, Instruction Manual, CO ROM and Certificate of Conformity	
BS.37.22	Digital Saccharimeter, ADS420, Flow Package, Sodium Wavelength(589mm)	19,885,800
	Landard's an October 1990 Control of the Australia Control of Cont	

Including Saccarimeter, 200mm Water jacketed Funnel Flow Cell Slotted Lid, Instruction Manual, CO ROM and Certificate of Conformity

Optional Accessories

BS.34.20	Quartz Control Plate 34 ° A / 100 ° Z
BS.34.21	5 ° A / 15 ° Z
BS.34.241	Temperature Sensor Saddle for QCP

[※] Optional Polarimeter Tubes Details : See Page 838 Optional Accessories



Ea.

Ea.

Price. ₩

Price, ₩ 2.959.030 2,959,030 143,090

Wisd 2 는 (주)대한과학이

독자적으로 개발 및 생산하여 세계 55여개 국으로 수출하고 있는 생명공학, 환경, 화학 전문 실험장비의 세계화 브랜드 입니다.



The World of DAIHAN®