

Datamax-O'Neil® E-Class III



STANDARD FEATURES

- 203 DPI (8 dots/mm) print resolution
- Drop in media loading
- USB, RS-232, or Parallel
- Gap label, black mark plain or fanfold label
- Label length detection
- Direct Thermal and Thermal Transfer Models
- Rugged construction – double wall and concentric hinges
- Media viewing window
- Field installable options

SPECIFICATIONS

Print Speed:

Basic – 4 inches per second
Advanced - 5 Inches per second (IPS)
(127 mm/s)

Print Length Range:

0.375 in - 99 in (9.5 to 2514 mm)

Print Width:

4.25 in maximum

Media Types:

Label Roll OD – Max 5.0 in
Core – 1 in
Fan-fold, die-cut or continuous labels, perforated or continuous tag/ticket stock
Width: 0.75 to 4.4 in
Thickness – 0.0025 to 0.01 in
Sensing: Basic -Fixed position
Advanced –Positional adjustable sensors capable of gap between labels, black bar on back, and notch or hole sensing

Printer language:

DPL, PL-Z or PL-E emulation

Ribbon:

Coated side in or coated side out (CSI/CSO)
Width range 1.0-4.3 in (25–109 mm)
Core: 0.5-1.0 in (13–25 mm)

Resident Fonts:

10 alphanumeric fonts from 0.08 to 0.25IN including OCR-A, OCR-B, CG Triumvirate smooth font from AGFA

Bar Codes:

Linear -Code 3 of 9, Code 93, Code 128), UCC/EAN-128, UPC E, EAN 8/13, Interleaved 2 or 5, Codabar, Post Net, HIBC, UPC 2 and 5 Addendums, Plessey, and Telepen

2-D Symbolologies:

MaxiCode, PDF417, Datamatrix, QR Code, USD-8, Aztec, TLC 39, Micro PDF417

Dimensions:

8.01 x 7.36 x 11.1 in (203.5 x 187 x 282 mm)

Memory:

64MB Flash/16 MB DRAM

Interfaces:

Baud rate – up to 38,400 BPS
Standard: USB and RS-232 (DB-9)
Advanced Model Mini-Parallel Centronics also

Power:

Auto Switching 100/240 VAC, 50/60 Hz, US Power Cord

Environment:

Operation: 40°F to 95°F (4°C to 35°C)

Operating Temperature:

40°F to 95°F (4°C to 35°C)

Weight:

5.2lbs (2.4kg)

Warranty:

One-year limited warranty

Datamax-O'Neil® E-Class III

PART NUMBER/PRICE

PART #	DESCRIPTION	WEIGHT	PRICE
Basic Model			
121119	Printer, E-4204B Direct Thermal, Tear Bar 110/240VAC printer	6 lbs	\$495.00
Advanced Mode			
121120	Printer, E-4205A, Direct Thermal, 110/240 V printer	6 lbs	595.00
121122	Printer, E-4205A, Direct Thermal, Peel and Present 110/240 V printer	6 lbs	630.00
121121	Printer, E-4205A, Thermal Transfer, Peel and Present, 110/240 V printer	6 lbs	730.00

OPTIONS/ACCESSORIES

PART #	DESCRIPTION	PRICE
126769	Peel and Present option for basic model	\$55.00
64794	RS-232 9pin serial cable	55.00
79074	USB cable	20.00
41276	6ft Serial cable, DB9 to blunt end	55.00
97370	LabelView™ Pro bar code software	499.00
38941	Cleaning pens for open printhead printers 12 per box	57.00
68517	External Rewinder/Unrewinder DMXREW1, 110 V	495.00
112517	Printhead, 203 dpi	125.00
41276	6ft serial cable, DB to blunt end	55.00
38941	Cleaning pens for open print head printers, 12 per box	57.00
Label Stock/Ribbon		
40332	Direct thermal, 2.25 W x 2 in L, 5 in diameter with perf., 1445 per roll	14.25
53251	Direct thermal, 4.0 W x 3 in L, 5 in diameter with perf., 930 per roll	23.35
40331	Direct thermal, 4.0 W x 4.0 in L, 5 in diameter with perf., 745 per roll	23.35
37345	Direct thermal, 4.0 W x 6.0 in L, 5 in diameter with perf., 450 per roll	20.00
53261	Thermal transfer, 4.0 W x 3.0 in L, 5 in diameter with perf., 930 per roll	18.05
35477	Ribbon, 3.5 in x 360 ft, general purpose	7.62
35478	Ribbon, 4.33 in x 360 ft, general purpos	9.85

DATAMAX-O'NEIL