Fujitsu recommends Windows[®] 7.

Data Sheet Fujitsu CELSIUS H700 Mobile Workstation

Workstation power on-the-go

The CELSIUS H700 delivers workstation power in a notebook form factor. Featuring the latest Intel® processors and powerful NVIDIA® Quadro® graphics, the CELSIUS H700 delivers uncompromising performance without tethering you to the office. Secure and reliable, it is ideal for business environments such as CAD and digital content creation.

Workstation performance

Higher productivity thanks to mobile workstation performance

Professional NVIDIA[®] Quadro[®] graphics, Intel[®] Core[™] i5 & i7 processors with vPro[™] technology

Unlimited connectivity

Online anywhere, anytime.

Optional integrated WLAN, 3G/UMTS and Bluetooth®

Ultimate security

Protect your data from non-authorized access

Integrated SmartCard reader and fingerprint sensor

Advanced Reliability

Protects your notebook against physical damage

Spill-resistant keyboard and hard disk drive ShockSensor

ISV certification

Excellent performance and absolute stability in professional environments

Comprehensive certification for workstation applications







FUJITSU

Components

Processor	Intel® Core™ i7-840QM processor (1.86 GHz, 8 MB)	
	Intel® Core™ i7-740QM processor (1.73 GHz, 6 MB)	
	Intel® Core™ i7-820QM processor (1.73 GHz, 8 MB)	
	Intel® Core™ i7-720QM processor (1.6 GHz, 6 MB)	
Operating system		
Operating system	Genuine Windows® 7 Professional 64-bit	
Operating system compatible	Genuine Windows® 7 Professional 32-bit	
,	Genuine Windows® XP Professional	
Operating system notes	Driver support for Microsoft [®] Windows [®] XP Professional / 7 Professional	
Memory modules	2 GB (1 module(s) 2 GB) DDR3, 1333 MHz, PC3-10600, SO DIMM	
Base unit memory	CELSIUS H700	
Supported capacity RAM (min.)	2 GB	
Supported capacity RAM (max.)	8 GB	
Memory slots total	2	
Memory slot type	DIMM (DDR3)	
Hard disk drives (internal)	SSD SATA, 256 GB, 2.5-inch, S.M.A.R.T.	
	SATA, 7200 rpm, 320 GB, 2.5-inch, S.M.A.R.T.	
Hard disk notes	ShockSensor for HDD shock protection	
naid uisk notes	One Gigabyte equals one billion bytes, when referring to hard disk drive capacity.	
	Accessible capacity may vary, also depending on used software.	
Wireless technologies		
Antennas	2 Dual band WLAN antennas, 2 UMTS antennas	
WLAN notes	Import and usage according to country-specific regulations.	
	2nd hard disk drive	
	Blu-ray Disc™ Triple Writer, SATA	
Base unit		
	CELSIUS H700	
General system information		
Chipset	Intel® QM57	
Chipset BIOS features Graphics	Intel® QM57 BIOS based on Phoenix SecureCore	
Chipset BIOS features Graphics Max. resolution external display	Intel® QM57 BIOS based on Phoenix SecureCore 2560 x 1600 pixel via DisplayPort and Dual Link DVI	
Chipset BIOS features Graphics Max. resolution external display Graphics brand name	Intel® QM57 BIOS based on Phoenix SecureCore 2560 x 1600 pixel via DisplayPort and Dual Link DVI NVIDIA® Quadro® FX 880M	
Chipset BIOS features Graphics Max. resolution external display Graphics brand name Graphics features	Intel® QM57 BIOS based on Phoenix SecureCore 2560 x 1600 pixel via DisplayPort and Dual Link DVI NVIDIA® Quadro® FX 880M DualView	
Chipset BIOS features Graphics Max. resolution external display Graphics brand name	Intel® QM57 BIOS based on Phoenix SecureCore 2560 x 1600 pixel via DisplayPort and Dual Link DVI NVIDIA® Quadro® FX 880M	
Chipset BIOS features Graphics Max. resolution external display Graphics brand name Graphics features	Intel® QM57 BIOS based on Phoenix SecureCore 2560 x 1600 pixel via DisplayPort and Dual Link DVI NVIDIA® Quadro® FX 880M DualView	
Chipset BIOS features Graphics Max. resolution external display Graphics brand name Graphics features Dedicated video memory	Intel® QM57 BIOS based on Phoenix SecureCore 2560 x 1600 pixel via DisplayPort and Dual Link DVI NVIDIA® Quadro® FX 880M DualView	
Chipset BIOS features Graphics Max. resolution external display Graphics brand name Graphics features Dedicated video memory Interfaces DC-in Audio: line-out / headphone	Intel® QM57 BIOS based on Phoenix SecureCore 2560 x 1600 pixel via DisplayPort and Dual Link DVI NVIDIA® Quadro® FX 880M DualView 1 GB (GDDR3 VRAM)	
Chipset BIOS features Graphics Max. resolution external display Graphics brand name Graphics features Dedicated video memory Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone	Intel® QM57 BIOS based on Phoenix SecureCore 2560 x 1600 pixel via DisplayPort and Dual Link DVI NVIDIA® Quadro® FX 880M DualView 1 GB (GDDR3 VRAM) 1 1 1	
Chipset BIOS features Graphics Max. resolution external display Graphics brand name Graphics features Dedicated video memory Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones	Intel® QM57 BIOS based on Phoenix SecureCore 2560 x 1600 pixel via DisplayPort and Dual Link DVI NVIDIA® Quadro® FX 880M DualView 1 GB (GDDR3 VRAM) 1 1	
Chipset BIOS features Graphics Max. resolution external display Graphics brand name Graphics features Dedicated video memory Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones USB 2.0 total	Intel® QM57 BIOS based on Phoenix SecureCore 2560 x 1600 pixel via DisplayPort and Dual Link DVI NVIDIA® Quadro® FX 880M DualView 1 GB (GDDR3 VRAM) 1 1 1	
Chipset BIOS features Graphics Max. resolution external display Graphics brand name Graphics features Dedicated video memory Interfaces DC-in Audio: line-out / headphone Audio: line-out / headphone Internal microphones USB 2.0 total VGA	Intel® QM57 BIOS based on Phoenix SecureCore 2560 x 1600 pixel via DisplayPort and Dual Link DVI NVIDIA® Quadro® FX 880M DualView 1 GB (GDDR3 VRAM) 1 1 2 1 2 digital array microphones	
Chipset BIOS features Graphics Max. resolution external display Graphics brand name Graphics features Dedicated video memory Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones USB 2.0 total	Intel® QM57 BIOS based on Phoenix SecureCore 2560 x 1600 pixel via DisplayPort and Dual Link DVI NVIDIA® Quadro® FX 880M DualView 1 GB (GDDR3 VRAM) 1 1 2 digital array microphones 4	
Chipset BIOS features Graphics Max. resolution external display Graphics brand name Graphics features Dedicated video memory Interfaces DC-in Audio: line-out / headphone Audio: line-out / headphone Internal microphones USB 2.0 total VGA	Intel® QM57 BIOS based on Phoenix SecureCore 2560 x 1600 pixel via DisplayPort and Dual Link DVI NVIDIA® Quadro® FX 880M DualView 1 GB (GDDR3 VRAM) 1 1 2 digital array microphones 4 1	

Interfaces		
FireWire (IEEE1394)	1	
Kensington Lock support	2	
PC Card slot (Type I/II)	1	
Memory card slots	1 (SD/MS/MSPro)	
Express card slots	1	
SmartCard slot	1	
SIM card slot	1	
eSATA	1	
Interface Module notes	Anytime USB charge functionality	
Wired communication		
LAN	10/100/1000 MBit/s Intel® 82577 LM	
Spill-resistant keyboard		
Number of keyboard keys: 86, Keyboard	pitch: 19 mm, Keyboard stroke: 2.7 mm	
TouchStick (optional)		
Touchpad with two mouse buttons and s	scroll via fingerprint sensor	
Second set of mouse buttons EcoButton		
LockWorkstation button		
MobilityCenter button		
Fingerprint sensor		
Multimedia		
Audio type	On board	
Audio type Audio codec	Realtek ALC269	
Audio type Audio codec Audio features	Realtek ALC269 Stereo speakers, 2x internal microphones	
Audio type Audio codec Audio features Camera	Realtek ALC269	
Audio type Audio codec Audio features Camera Power supply	Realtek ALC269 Stereo speakers, 2x internal microphones Optional: Built-in webcam, 1.3 megapixel, VGA camera	
Audio type Audio codec Audio features Camera Power supply AC adapter	Realtek ALC269 Stereo speakers, 2x internal microphones Optional: Built-in webcam, 1.3 megapixel, VGA camera 19 V / 100 W (5.27 A)	
Audio type Audio codec Audio features Camera Power supply AC adapter Rated voltage range	Realtek ALC269 Stereo speakers, 2x internal microphones Optional: Built-in webcam, 1.3 megapixel, VGA camera 19 V / 100 W (5.27 A) 100 V - 240 V (AC Input)	
Audio typeAudio codecAudio featuresCameraPower supplyAC adapterRated voltage rangeRated frequency range	Realtek ALC269 Stereo speakers, 2x internal microphones Optional: Built-in webcam, 1.3 megapixel, VGA camera 19 V / 100 W (5.27 A) 100 V - 240 V (AC Input) 50 Hz - 60 Hz	
Audio typeAudio codecAudio featuresCameraPower supplyAC adapterRated voltage rangeRated frequency range1st battery	Realtek ALC269Stereo speakers, 2x internal microphonesOptional: Built-in webcam, 1.3 megapixel, VGA camera19 V / 100 W (5.27 A)100 V - 240 V (AC Input)50 Hz - 60 HzLi-Ion battery 8-cell, 5.800 mAh, 84 Wh	
Audio typeAudio codecAudio featuresCameraPower supplyAC adapterRated voltage rangeRated frequency range1st battery2nd battery (optional)	Realtek ALC269Stereo speakers, 2x internal microphonesOptional: Built-in webcam, 1.3 megapixel, VGA camera19 V / 100 W (5.27 A)100 V - 240 V (AC Input)50 Hz - 60 HzLi-Ion battery 8-cell, 5.800 mAh, 84 WhLi-Ion, 3800 mAh, 41 Wh	
Audio typeAudio codecAudio featuresCameraPower supplyAC adapterRated voltage rangeRated frequency range1st battery2nd battery (optional)Battery features	Realtek ALC269Stereo speakers, 2x internal microphonesOptional: Built-in webcam, 1.3 megapixel, VGA camera19 V / 100 W (5.27 A)100 V - 240 V (AC Input)50 Hz - 60 HzLi-Ion battery 8-cell, 5.800 mAh, 84 WhLi-Ion, 3800 mAh, 41 WhDynamic charge supported (rapid charge)	
Audio typeAudio codecAudio featuresCameraPower supplyAC adapterRated voltage rangeRated frequency range1st battery2nd battery (optional)Battery featuresBenchmark	Realtek ALC269Stereo speakers, 2x internal microphonesOptional: Built-in webcam, 1.3 megapixel, VGA camera19 V / 100 W (5.27 A)100 V - 240 V (AC Input)50 Hz - 60 HzLi-Ion battery 8-cell, 5.800 mAh, 84 WhLi-Ion, 3800 mAh, 41 WhDynamic charge supported (rapid charge)Mobile Mark 2005	
Audio typeAudio codecAudio featuresCameraPower supplyAC adapterRated voltage rangeRated frequency range1st battery2nd battery (optional)Battery featuresBenchmarkRuntime 1st battery	Realtek ALC269Stereo speakers, 2x internal microphonesOptional: Built-in webcam, 1.3 megapixel, VGA camera19 V / 100 W (5.27 A)100 V - 240 V (AC Input)50 Hz - 60 HzLi-Ion battery 8-cell, 5.800 mAh, 84 WhLi-Ion, 3800 mAh, 41 WhDynamic charge supported (rapid charge)Mobile Mark 2005up to 5 h	
Audio typeAudio codecAudio featuresCameraPower supplyAC adapterRated voltage rangeRated frequency range1st battery2nd battery (optional)Battery featuresBenchmarkRuntime 1st batteryRuntime 1st + 2nd battery	Realtek ALC269Stereo speakers, 2x internal microphonesOptional: Built-in webcam, 1.3 megapixel, VGA camera19 V / 100 W (5.27 A)100 V - 240 V (AC Input)50 Hz - 60 HzLi-Ion battery 8-cell, 5.800 mAh, 84 WhLi-Ion, 3800 mAh, 41 WhDynamic charge supported (rapid charge)Mobile Mark 2005up to 5 hup to 9 h	
Audio typeAudio codecAudio featuresCameraPower supplyAC adapterRated voltage rangeRated frequency range1st battery2nd battery (optional)Battery featuresBenchmarkRuntime 1st battery	Realtek ALC269 Stereo speakers, 2x internal microphones Optional: Built-in webcam, 1.3 megapixel, VGA camera 19 V / 100 W (5.27 A) 100 V - 240 V (AC Input) 50 Hz - 60 Hz Li-Ion battery 8-cell, 5.800 mAh, 84 Wh Li-Ion, 3800 mAh, 41 Wh Dynamic charge supported (rapid charge) Mobile Mark 2005 up to 5 h up to 9 h Battery life may vary depending on product model, configuration, applications, power management settings and	
Audio type Audio codec Audio features Camera Power supply AC adapter Rated voltage range Rated frequency range 1st battery 2nd battery (optional) Battery features Benchmark Runtime 1st battery Runtime 1st + 2nd battery Battery notes	Realtek ALC269Stereo speakers, 2x internal microphonesOptional: Built-in webcam, 1.3 megapixel, VGA camera19 V / 100 W (5.27 A)100 V - 240 V (AC Input)50 Hz - 60 HzLi-Ion battery 8-cell, 5.800 mAh, 84 WhLi-Ion, 3800 mAh, 41 WhDynamic charge supported (rapid charge)Mobile Mark 2005up to 5 hup to 9 h	
Audio type Audio codec Audio features Camera Power supply AC adapter Rated voltage range Rated frequency range 1st battery 2nd battery (optional) Battery features Benchmark Runtime 1st battery Runtime 1st battery Battery notes Dimensions / Weight / Environmental	Realtek ALC269 Stereo speakers, 2x internal microphones Optional: Built-in webcam, 1.3 megapixel, VGA camera 19 V / 100 W (5.27 A) 100 V - 240 V (AC Input) 50 Hz - 60 Hz Li-lon battery 8-cell, 5.800 mAh, 84 Wh Li-lon, 3800 mAh, 41 Wh Dynamic charge supported (rapid charge) Mobile Mark 2005 up to 5 h up to 9 h Battery life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery recharge time depends on usage.	
Audio typeAudio codecAudio featuresCameraPower supplyAC adapterRated voltage rangeRated frequency range1st battery2nd battery (optional)Battery featuresBenchmarkRuntime 1st batteryRuntime 1st + 2nd batteryBattery notesDimensions / Weight / EnvironmentalDimensions (W x D x H)	Realtek ALC269 Stereo speakers, 2x internal microphones Optional: Built-in webcam, 1.3 megapixel, VGA camera 19 V / 100 W (5.27 A) 100 V - 240 V (AC Input) 50 Hz - 60 Hz Li-lon battery 8-cell, 5.800 mAh, 84 Wh Li-lon, 3800 mAh, 41 Wh Dynamic charge supported (rapid charge) Mobile Mark 2005 up to 5 h up to 9 h Battery life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery recharge time depends on usage. 372 x 255 x 36 mm	
Audio type Audio codec Audio features Camera Power supply AC adapter Rated voltage range Rated voltage range Rated frequency range 1st battery 2nd battery (optional) Battery features Benchmark Runtime 1st battery Runtime 1st battery Runtime 1st + 2nd battery Battery notes Dimensions / Weight / Environmental Dimensions (W x D x H) Weight	Realtek ALC269 Stereo speakers, 2x internal microphones Optional: Built-in webcam, 1.3 megapixel, VGA camera 19 V / 100 W (5.27 A) 100 V - 240 V (AC Input) 50 Hz - 60 Hz Li-lon battery 8-cell, 5.800 mAh, 84 Wh Li-lon, 3800 mAh, 41 Wh Dynamic charge supported (rapid charge) Mobile Mark 2005 up to 5 h up to 9 h Battery life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery recharge time depends on usage. 372 x 255 x 36 mm 2.75 kg	
Audio typeAudio codecAudio featuresCameraPower supplyAC adapterRated voltage rangeRated frequency range1st battery2nd battery (optional)Battery featuresBenchmarkRuntime 1st batteryRuntime 1st + 2nd batteryBattery notesDimensions / Weight / EnvironmentalDimensions (W x D x H)WeightWeight notes	Realtek ALC269 Stereo speakers, 2x internal microphones Optional: Built-in webcam, 1.3 megapixel, VGA camera 19 V / 100 W (5.27 A) 100 V - 240 V (AC Input) 50 Hz - 60 Hz Li-lon battery 8-cell, 5.800 mAh, 84 Wh Li-lon, 3800 mAh, 41 Wh Dynamic charge supported (rapid charge) Mobile Mark 2005 up to 5 h up to 9 h Battery life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery recharge time depends on usage. 372 x 255 x 36 mm 2.75 kg Actual weight may vary depending on configuration	
Audio type Audio codec Audio features Camera Power supply AC adapter Rated voltage range Rated voltage range Rated frequency range 1st battery 2nd battery (optional) Battery features Benchmark Runtime 1st battery Runtime 1st battery Runtime 1st + 2nd battery Battery notes Dimensions / Weight / Environmental Dimensions (W x D x H) Weight	Realtek ALC269 Stereo speakers, 2x internal microphones Optional: Built-in webcam, 1.3 megapixel, VGA camera 19 V / 100 W (5.27 A) 100 V - 240 V (AC Input) 50 Hz - 60 Hz Li-lon battery 8-cell, 5.800 mAh, 84 Wh Li-lon, 3800 mAh, 41 Wh Dynamic charge supported (rapid charge) Mobile Mark 2005 up to 5 h up to 9 h Battery life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery recharge time depends on usage. 372 x 255 x 36 mm 2.75 kg	

Additional Software	
Additional software (preinstalled)	Adobe Acrobat Reader
	Application Panel
	Display Manager
	EasyGuide online user documentation
	, Nero Essentials S (burning software)
	Norton Internet Security (incl. Firewall)
	Power Saving Utility
	ShockSensor Utility
	SmartCase Logon+
	Toshiba Bluetooth Stack (only with Windows Vista® or Windows® XP operating systems)
	Wireless Selector Utility
Additional software (optional)	Drivers & Utilities DVD (DUDVD)
	UMTS connection manager (optional with UMTS)
Manageability	
Manageability technology	DeskUpdate Driver management
	iAMT Intel [®] Active Manageability Technology v6.0 (not activated, not set up)
	Intel [®] vPro™ technology
Manageability software	DeskView 10.x client management including:
DeskView components	On/Offline remote client management
	Detailed system inventory management and reports
	BIOS Management
	Remote power management
	System notifications
	Security Remote Control
	DeskView Helpdesk Integration
Supported standards	WMI
	PXE
	BootP (made4you)
Manageability link	WoL (Wake on LAN) http://ts.fujitsu.com/solutions/it_infrastructure_solutions/manageability/featurefinder.html
	וונף.אנצ.וטונגט.נטוואסוטנוטואר_ווווסגנוטננטואאוזמומעפטווונאופגטפווועאפגטופוווטפו.וונווו
Security	
System protection	Kensington Lock support
Audit proof protection	Advanced Theft Protection
	Computrace® enabled BIOS
	Optional: Trusted platform module (TPM 1.2) Norton Internet Security (incl. Firewall) 90 days version
Access protection	Integrated Fingerprint Sensor
Access protection	Separate SmartCard slot
	Hard disk password
	SystemLock BIOS SmartCard security
	User and supervisor BIOS password
Compliance	
Product	CELSIUS H700
Germany	GS
•	CE
Europe	
USA/Canada	cCSAus FCC Class B (depending on wireless configuration)
Global	RoHS (EU & China)
	Medical EMC standard IEC60601-1-2 in combination with medical kit
	ENERGY STAR® 5.0 (depending on configuration)
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/
Warranty	
Standard Warranty	3 years (depending on country)

Warranty	
Service level	Collect & Return Service / Bring-in Service (depending on country specific requirements)
Maintenance and Support Services -	the perfect extension
Recommended Service	5x9, Response Time: Next Business Day
Service Weblink	http://ts.fujitsu.com/Supportservice

Recommended Accessories

ComboSaver	Protect your notebook-and the personal information you have stored-from theft. Lock it with this easy-to-use, keyless 4-wheel combination lock from Kensington, the leader in notebook security	Order Code: S26361-F1650-L500
Privacy filter	Privacy filters help block the screen view from anyone viewing the computer from a side view. 3M's unique microlouver privacy technology allows persons directly in front of the computer to see on-screen data clearly. 3M offers the broadest line of computer filters available.	Order Code: S26391-F6097-L317
Prestige City Trolley 17	Aluminum trolley handle with optimized wheels for smooth rolling, a separate front case for power supply and cables and a heightened compartment to accommodate e.g. clothes for a overnight stay. For Tablet PC and Notebooks up to 43 cm / 17-inch. City Trolley is designed only for transportation of laptops, clothes and sanitary belongings in the city environment (up to 10 kg).	Order Code: S26391-F1191-L130
Presenter IV Air	Do you often give presentations? Would you like to communicate pro actively with your audience during your presentations? Step up to the plate and make use of your freedom of movement with the Presenter IV Air Whether you're leafing through informative material, adjusting audio files or using the laser pointer to indicate special features, you have everything reliably under control with this presenter. Thanks to the 2D air mouse function you can even do away with the cable mouse and navigate through your files with ease	Order Code: S26381-K440-L100
HS S2000NC Headset	The HS S2000NC Headset offers more than current headsets. Besides superb sound quality, the headset provides an impressive feature: a button to switch off noise and disburden your ears of unwanted noise level.	Order Code: S26391-F7139-L3

Prestige City Trolley 17



Aluminum trolley handle with optimized wheels for smooth rolling, a separate front case for power supply and cables and a heightened compartment to accommodate e.g. clothes for a overnight stay. For Tablet PC and Notebooks up to 43 cm / 17-inch. City Trolley is designed only for transportation of laptops, clothes and sanitary belongings in the city environment (up to 10 kg).

Order Code: S26391-F1191-L130

More information

Fujitsu platform solutions

In addition to Fujitsu CELSIUS H700, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu CELSIUS H700, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

http://ts.fujitsu.com/celsius

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT.

Please find further information at http://www. fujitsu.com/global/about/environment/



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see http://ts.fujitsu. com/terms_of_use.html

Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

Contact

FUJITSU Technology Solutions Website: http://ts.fujitsu.com 2011-09-30 CE-EN All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see http://ts.fujitsu.com/terms_of_use.html Copyright © Fujitsu Technology Solutions