



## 7-PORT USB 2.0 HUB

Connect more USB devices  
to your PC or Mac

Transfer data at  
up to 480Mbps<sup>1</sup>

Works with both USB 2.0  
and 1.1<sup>2</sup> devices



The D-Link® 7-Port USB 2.0 Hub (DUB-H7) provides seven additional USB 2.0 ports to your PC or Mac, allowing you to connect USB devices such as digital cameras, external hard drives, flash drives, and printers. Providing data rates of up to 480Mbps<sup>1</sup>, this 7-port hub is the ideal solution for transferring data between your computer and external USB storage devices.

### **SIMPLE PLUG-AND-PLAY**

Designed to provide quick and easy access, the DUB-H7 is equipped with seven type "A" downstream ports for connecting USB peripherals or other USB hubs. The DUB-H7 does not require any software or complicated installation process. It is a Plug-and-Play device that provides seamless connectivity to both PCs and Macs. You can simply connect the DUB-H7 to your computer and start connecting your USB devices.

### **BACKWARD COMPATIBLE WITH USB 1.1<sup>2</sup>**


The DUB-H7 is backward compatible with USB 1.1<sup>2</sup> devices, ensuring connectivity between your computer and legacy USB devices. Diagnostic LEDs located on the front of the device provide power state and port status.

The D-Link 7-Port USB 2.0 Hub (DUB-H7) is an excellent choice for adding more USB ports to your computer for connecting your existing peripherals as well as adding the latest USB cameras and external storage devices.

### WHAT THIS PRODUCT DOES

The D-Link® 7-Port USB 2.0 Hub (DUB-H7) provides seven additional USB 2.0 ports to your PC or Mac, allowing you to connect USB devices such as digital cameras, external hard drives, flash drives, and printers.

### YOUR NETWORK SETUP



### TECHNICAL SPECIFICATIONS

#### STANDARDS

- + USB 2.0 / 1.1<sup>2</sup>
- + OHCI (Open Host Controller Interface)
- + EHCI (Enhanced Host Controller Interface)

#### PORTS

- + One Upstream USB Type "B" Receptacle
- + Seven Downstream USB Type "A" Receptacle

#### CONNECTIVITY

Up to 127 Devices by Cascading Multiple Hubs

#### WIRING TOPOLOGY

Tiered Star

#### DIAGNOSTIC LEDs

- + Self-powered (Red on self-power)
- + Port Status (Green, per port)

#### TEMPERATURE

- + Operating: -4° to 158°F
- + Storage: -40° to 158° F

#### HUMIDITY

- + Operating: 25% ~ 95% Non-condensing
- + Non-operating: 25% ~ 95% ± 2 - 3% Non-condensing

#### COMPLIANCE

CE, FCC Class B

#### DIMENSIONS

- + Item (WxDxH): 2.44" x 4.03" x 1.09"
- + Packaging (WxDxH): 6.75" x 3.25" x 11.25"

#### WEIGHT

- + Item: 0.19 lbs.
- + Packaging: 0.9 lbs.

#### WARRANTY

1-Year Limited<sup>3</sup>

<sup>1</sup> For comparison purposes only. Maximum transfer rate based on USB 2.0 specifications. Actual data throughput will vary.

<sup>2</sup> Using a USB 1.1 port will affect device performance.

<sup>3</sup> 1-Year Limited Warranty available only in the USA and Canada.

<sup>4</sup> Computers must adhere to Microsoft's recommended system requirements. Please contact Microsoft for details.

<sup>5</sup> Computers must adhere to Apple's recommended system requirements. Please contact Apple for details.

©2004-2007 D-Link Corporation/D-Link Systems, Inc. All rights reserved. D-Link and the D-Link logo are trademarks or registered trademarks of D-Link Corporation or its subsidiaries in the United States and/or other countries. Windows Vista is either a registered trademark or trademark of Microsoft Corporation in the United States and/or other countries. Windows is a registered trademark of Microsoft Corporation in the United States and/or other countries. Other trademarks or registered trademarks are the property of their respective owners.

#### MINIMUM SYSTEM REQUIREMENTS

Computer with:

- + Windows Vista<sup>4</sup>, Windows® XP SP2, or Windows® 2000 SP4
- + Mac OS® X 10.4<sup>5</sup> or Higher
- + USB 1.1<sup>2</sup> Port

#### PACKAGE CONTENTS

- + 7-Port USB 2.0 Hub
- + AC Adapter
- + USB 2.0 Cable
- + Quick Installation Guide