

THE PROFESSIONAL DESKTOP PRINTER WITH DUPLEX FUNCTIONALITY.

This high performance printer prides itself with its compact design and double-sided printing as standard, making it ideal for individuals or small teams requiring professional documents in seconds.

- 22 pages per minute with 1,200 dpi quality
- Easy connection with USB and parallel interface
- Powerful controller with 32 MB RAM as standard
- 6 emulations (incl. PS 3, PCL 6) and PRESCRIBE IIe
- Long-life technology, lowest cost per page in its class

Excellent in its class:
50-sheet multi-purpose tray and optional paper cassette for paper handling of up to 550 sheets.



Network connectivity lets everyone join in. Choose directly as standard or later as an option.



FS-1030D

MONOCHROME A4 DESKTOP PRINTER

Ecosys® The ECOSYS technology is based on extremely durable components. The drum, developer and fuser of the FS-1030D are designed to last for 100,000 pages. As toner is the only consumable required, ECOSYS printers operate with the lowest cost per page in their class, and they are particularly environmentally friendly. Thanks to their modular system and flexible paper options all ECOSYS printers can be configured to meet your exact requirements.

GENERAL

Technology: Kyocera ECOSYS, Laser
Engine speed: Up to 22 pages per minute A4 simplex
Up to 11 pages per minute A4 duplex (5.5 sheets)
Resolution: 1,200 dpi quality (1,800 x 600)
Time to first page: 10 seconds or less
Warm-up time: 15 seconds or less from power on
Duty cycle: Max. 20,000 pages per month,
average 2,800 pages per month
Power source: AC 220 ~ 240 V, 50/60 Hz
Power consumption: Printing: 370 W, Stand-by: 8.4 W,
Power-Saving (ECOpower): 4.3 W
Noise (ISO 7779): Printing: 53 dB(A), Stand-by: 28 dB(A),
Power-Saving (ECOpower): Immeasurably low
Dimensions (W x D x H): Main unit: 378 x 375 x 235 mm
Weight: Main unit incl. toner: Approx. 10.5 kg
Certifications: TÜV/GS, CE, PTS
This product is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by Kyocera under normal environmental conditions.

Input capacity: 250-sheet universal paper cassette, 60-105 g/m², A4, A5, B5, Letter, Legal, Custom (148 x 210 mm to 216 x 356 mm)
50-sheet multi-purpose tray, 60-163 g/m², A4, A5, B5, Letter, Custom (70 x 148 mm to 216 x 356 mm)
Max. input capacity with optional paper feeder PF-17:
550 sheets
Duplex as standard
Output capacity: 250 sheets face-down

CONTROLLER

Processor: PowerPC 405 / 266 MHz
Memory: Standard 32 MB + ECOmemory, max. 288 MB in 1 SDRAM DIMM slot
Emulations: PCL6/PCL5e incl. PJL, KPDL 3 (PostScript 3 compatible) with automatic emulation sensing (AES), Line Printer, IBM Proprinter X24E, Epson LQ-850, Diablo 630
Controller language: PRESCRIBE IIe
Fonts: 80 outline fonts accessible in all emulations, 1 bitmap font, 45 types of one-dimensional barcodes plus two-dimensional barcode PDF-417, Downloadable fonts: Kyocera, PCL + TrueType format, Type 1 + 3 format
Print features: Automatic duplex unit enables booklet printing

System platform:

The FS-1030D offers USB and parallel connectivity as standard and delivers optional network connectivity and problem-free system administration. Kyocera's single platform technology means that the same driver can be used for every Kyocera PCL/PostScript print device on the network: from single-user desktop printers to high-end multifunctional systems. Only Kyocera offers this effortless combination of IT sophistication and high-performance paper handling expertise.

PRESCRIBE IIe:

With the Kyocera page design and control language PRESCRIBE IIe, even complex graphics, logos and forms (even multipart forms) can be created independently of the system and saved and updated in the printer. Consequently, integration into print files no longer applies. They are only accessed as required and therefore relieve the load on the network.

KM-NET for Client/KM-NET Viewer:

The settings of all printers on the network can be checked visually and amended from any Windows PC. KM-NET for Client for easy setup and check of the printer status via parallel, USB or optional network connection. KM-Net Viewer is an advanced printer management software tool using the standardized protocol SNMP.

INTERFACES

Standard interface: High speed bi-directional parallel (IEEE 1284), USB 2.0 (Full Speed), KUIO-LV option interface slot
Multiple interface connection (MIC): Allows simultaneous data transfer via up to three interfaces, with each interface having its own virtual printer.

OPTIONS

Paper handling
PF-17 Paper feeder: 250 sheets, 60-105 g/m², A4, A5, B5, Letter, Legal, Custom (148 x 210 mm to 216 x 356 mm)
CB-100 Cabinet: Wooden cabinet with storage capacity, including castors (wheels)

Memory
Printer memory: 1 SDRAM DIMM slot (16, 32, 64, 128 or 256 MB)
CompactFlash® memory card type 1: 1 slot (for up to 2 GB), forms, fonts, logos, macro storage

Optional interface

IB-21E Network card: 10Base-T/100Base-TX
SB-50 Network card: 10Base-FL, FibreLink
SB-60 Network card: TokenRing STP/UTP
SB-70 Network card: Wireless LAN – IEEE 802.11b
SB-110FX Network card: 10Base-T/100Base-TX/100Base-FX, FibreOptic
SB-140 Network card: 10Base-2/10Base-T/100Base-TX
SB-80 Parallel interface: 2nd parallel interface – IEEE 1284
IB-11 Serial interface: RS-232C serial interface (max. 115.2 kbps)

External network interface

IB-100 Ethernet print server: 10Base-T/100Base-TX

CONSUMABLES

TK-120 Toner-kit: Microfine toner for 7,200 pages with 5% coverage (ISO/IEC 19752)*, 10,000 pages according to Dr. Grauert letter (ISO 10561A)

* Capacity of starter toner is 3,600 pages with 5% coverage (ISO/IEC 19752)

WARRANTY

2-year warranty as standard. Kyocera guarantees the drum and developer for 3 years or 100,000 pages (whichever occurs sooner), provided each printer is used and cleaned in accordance with the service instructions.

KYOLIFE KYOLife 3-year on-site warranty for printer and options.

MODEL CONFIGURATIONS

FS-1030DN: incl. integrated IB-21E Network card



Select your options to suit your needs:



PF-17 Paper feeder

CB-100 Cabinet

Product depicted includes optional extras

Your Kyocera Business Partner:

Kyocera Mita Europe B.V., Hoeksteen 40, 2132 MS Hoofddorp, The Netherlands, Tel +31 (0) 20 65 40 000, Fax +31 (0) 20 65 31 256, www.kyoceramita-europe.com, info@kyoceramita-europe.com

Kyocera Mita Corporation, 2-28, 1-Chome, Tamatsukuri, Chuo-Ku, Osaka 540-8585, Japan, www.kyoceramita.com
Kyocera does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.