

SCALEOVIEW L19-8 19 Inch LCD Display Preliminary

Issue August 2007

Pages 2

An attractive price doesn't mean that you have to compromise on style or performance. The SCALEOVIEW L19-8 display offers best performance for the home office and multimedia, such as photo editing and gaming. With its extremely slim and stylish design, the SCALEOVIEW L19-8 fits perfectly into your home environment.

Highlights

- 19-inch display for a perfect viewing experience
- Best performance to an affordable price
- Stylish black design with a silver front
- Very easy and comfortable to use
 - Plug & Play
 - Auto-adjust
 - Easy-to-use OSD menu

Ergonomics

- Optimum flicker-free and distortion-free picture
- Excellent colour purity
- Well balanced brightness uniformity
- Excellent high contrast (1000:1)
- Space saving design

Technical highlights

- 19" (48.0cm) LCD display
- Excellent contrast 1000:1
- Brightness 300 cd/m²
- Fast response time (typ.) 5 ms
- Internal power supply

Reliability

- Low power consumption
- Power management according to EPA
- Guaranteed quality and stability



Visible screen diagonal	19 inch (48.0 cm)
Resolutions	
Pixels	1280 x 1024
Pixels*	1280 x 768
* expanded	800 x 600
Picture size	372.3 x 301 mm
Colours	16.2 million
Pixel Pitch	0.294 mm
Frequencies	
Horizontal	30 - 81 kHz
Vertical	55 - 76 Hz
Brightness	300 cd/m ²
Contrast	1000:1
Viewing angle (cr <=5)	
Horizontal	170°
Vertical	170°
Response time (typical)	5 ms
Plug and Play	VESA DDC2B
Setting options	
Brightness (Back light control)	
Contrast, Volume control	
Picture position (horizontal and vertical), H-size, Phase,	
Color temperature and individual color setting	
Auto-adjust (direct access key)	
Activate factory settings	
Menu language	
OSD Language	
English, German, Spanish, French, Italian, Russian,	
Swedish, Dutch	
Base	
Tilt angle	-5° +20°
Audio characteristics	
Audio signal input	3.5mm stereo phone jack
Audio output	1 W (L) + 1 W (R)

Electrical values (internal power supply)	
Rated voltage	100 - 240 V
Frequency	50 - 60 Hz
Power draw	
Max.	<50 W
Stand by	< 1 W
Protection class	1
Temperatures/ dimensions/ weight	
Ambient temperature (to IEC721):	
Working (recommended)	5°C to 35°C
Storage	-20°C to 60°C
Dimensions (H x W x D):	
(with stand)	367 x 426 x 66 mm
Weight (Monitor only)	4.9 kg
Reliability	
MTBF (demonstrated)	70,000 h
Lifetime of LCD backlight	50,000 h
(brightness > 50 % of original brightness)	
Compliance with standards	
Product safety	EN60950
Ergonomics	GS mark ISO13406-2 (Pixel fault class II)
Radiation immunity and RFI suppression	CE certification according to EC Directive 89/336/EEC (EN55022/B, EN55024 EN61000-3-2/-3); TCO'99
Video input	1 x D-SUB, 1 x DVI
Accessories	
Power cable (1.5 m)*	For wall socket (Euro-Schuko-Type CEE7)
Data cable (1.5 m)*	D-SUB (15-pin)
Audio cable (1.8 m)*	3.5mm stereo phone jack
* detachable on display	
Special features	Standardized mounting interface according VESA FPMPI (100 mm) Kensington Lock
Order code	S26361-K1222-V203 EAN: 433364 3101299

