

Fujitsu PRIMERGY Servers Portfolio

Dynamic Infrastructures
for workgroup, datacenter
and cloud computing





FUJITSU






shaping tomorrow with you

Higher IT efficiency and reduced total cost of ownership

Fujitsu PRIMERGY Micro and Tower Servers





Model	PRIMERGY MX130 S2 	PRIMERGY TX100 S3p 	PRIMERGY TX120 S3p 	PRIMERGY TX140 S1p 
Characteristics	Micro server for macro results	Enter the world of PRIMERGY TX servers	For small environments with high demands	The expandable SME allrounder
Type	Mono socket micro server (horizontal/vertical operation possible)	Mono socket tower server	Mono socket tower server	Mono socket tower server
Height units	-	-	-	5 U when used in a rack
Processor	AMD Athlon™ II, AMD Sempron™, AMD Opteron™ 3200	Intel® Xeon® processor E3 v2 family, Intel® Core™ i3, Intel® Pentium®	Intel® Xeon® processor E3 v2 family, Intel® Core™ i3, Intel® Pentium®	Intel® Xeon® processor E3 v2 family, Intel® Core™ i3, Intel® Pentium®
Memory capacity	2 GB - 16 GB, 4 DIMM (DDR3)	2 GB - 32 GB, 4 DIMM (DDR3)	2 GB - 32 GB, 4 DIMM (DDR3)	2 GB - 32 GB, 4 DIMM (DDR3)
Storage configuration	4x 3.5-inch or 6x 2.5-inch optional	4 x 3.5-inch	4 x 2.5-inch or 2 x 3.5-inch	4x 3.5-inch or 8x 2.5-inch optional
Storage drives hot-plug	HDD SATA 3.5-inch 250 GB - 3 TB (non hot-plug)	HDD SATA 3.5-inch 250 GB - 3 TB (non hot-plug)	HDD SATA 3.5-inch 250 GB - 3 TB HDD SATA 2.5-inch 160 GB - 1 TB HDD SAS 2.5-inch 73 GB - 900 GB SSD SATA 2.5-inch 32 GB - 400 GB	HDD SATA 3.5-inch 250 GB - 3 TB HDD SATA 2.5-inch 160 GB - 1 TB HDD SAS 2.5-inch 73 GB - 900 GB SSD SATA 2.5-inch 32 GB - 400 GB
iRMC	no	no	yes (advanced pack opt.)	yes (advanced pack opt.)
RAID 0, 1 5, 6	✓ -	✓ optional	✓ optional	✓ optional
Active power (max.)	159 W	209 W	147 W	216 W
I/O slots	1x PCIe 2.0 x4, 1x PCIe 2.0 x16, 1x PCIe x1, 1x PCI	1 x PCIe 2.0 x1, 1 x PCIe 2.0 x4, 2x PCIe 2.0/3.0 x8	1 x PCIe 2.0 x1, 1 x PCIe 2.0 x4, 1 x PCIe 2.0/3.0 x16, 1 x PCI	1 x PCIe 2.0 x1, 1 x PCIe 2.0 x4, 1 x PCIe 2.0/3.0 x16, 1 x PCI




Model	PRIMERGY TX150 S8 	PRIMERGY TX200 S7 	PRIMERGY TX300 S7 
Characteristics	The one-processor tower server - maximized!	Well-balanced price- performance	No compromise tower server
Type	Mono socket tower server	Dual socket tower server	Dual socket tower server
Height units	4 U when used in a rack	4 U when used in a rack	4 U when used in a rack
Processor	Intel® Xeon® processor E5-2400 product family Intel® Xeon® processor E5-1400 product family	Intel® Xeon® processor E5-2400 product family	Intel® Xeon® processor E5-2600 product family
Memory capacity	2 GB - 96 GB, 6 DIMM (DDR3)	2 GB - 192 GB, 12 DIMM (DDR3)	2 GB - 768 GB, 24 DIMM (DDR3)
Storage configuration	8 x 3.5-inch or 16 x 2.5-inch	8 x 3.5-inch or 16 x 2.5-inch	4 x 3.5-inch (12 optional) or 8 x 2.5-inch (24 optional)
Storage drives hot-plug	HDD SATA 3.5-inch 250 GB - 3 TB HDD SATA 2.5-inch 160 GB - 1 TB HDD SAS 3.5-inch 300 GB - 600 GB HDD SAS 2.5-inch 73 GB - 900 GB SSD SAS / SATA 2.5-inch 100 GB - 400 GB	HDD SATA 3.5-inch 250 GB - 3 TB HDD SATA 2.5-inch 160 GB - 1 TB HDD SAS 3.5-inch 300 GB - 600 GB HDD SAS 2.5-inch 73 GB - 900 GB SSD SAS / SATA 2.5-inch 100 GB - 400 GB	HDD SATA 3.5-inch 250 GB - 3 TB HDD SATA 2.5-inch 250 GB - 1 TB HDD SAS 3.5-inch 300 GB - 600 GB HDD SAS 2.5-inch 73 GB - 900 GB SSD SAS / SATA 2.5-inch 100 GB - 400 GB
iRMC	yes (advanced pack opt.)	yes (advanced pack opt.)	yes (advanced pack opt.)
RAID 0, 1 5, 6	✓ optional	✓ optional	✓ optional
Active power (max.)	278 W	432 W	1070 W
I/O slots	2 x PCIe 3.0 x4 (mech. x8), 1 x PCIe 3.0 x16, 1 x PCIe 2.0 x1 (mech. x16), 1 x PCIe 2.0 x4 (mech. x8), 1 x PCI	2 x PCIe 3.0 x4 (mech. x8), 2 x PCIe 3.0 x16, 1 x PCIe 2.0 x4 (mech. x8), 1 x PCI	1 x PCIe 2.0 x4, 2x PCIe 3.0 x4, 5 x PCIe 3.0 x8, 2 x PCIe 3.0 x16

Higher IT efficiency and reduced total cost of ownership

Fujitsu PRIMERGY Rack Servers



Model	PRIMERGY RX100 S7p 	PRIMERGY RX200 S7 	PRIMERGY RX300 S7 	PRIMERGY RX350 S7 
Characteristics	Small in size and low in cost – rich in optional features	Maximum productivity in a 1U housing	The versatile 2U powerhouse	Maximum expandability in a 2 way server
Type	Mono socket rack server	Dual socket rack server	Dual socket rack server	Dual socket rack server
Height units	1 U	1 U	2 U	4 U
Processor	Intel® Pentium®, Intel® Xeon® processor E3 v2 family, Intel® Core™ i3	Intel® Xeon® processor E5-2600 product family	Intel® Xeon® processor E5-2600 product family	Intel® Xeon® processor E5-2600 product family
Memory capacity	2 GB - 32 GB, 4 DIMM (DDR3)	2 GB - 768 GB, 24 DIMM (DDR3)	2 GB - 768 GB, 24 DIMM (DDR3)	2 GB - 768 GB
Storage configuration	2 x 3.5-inch or 4 x 2.5-inch	4 x 2.5-inch or 8 x 2.5-inch	6 x 3.5-inch or 16 x 2.5-inch	12 x 3.5-inch or 24 x 2.5-inch
Storage drives hot-plug	HDD SATA 3.5-inch 250 GB - 3 TB HDD SATA 2.5-inch 250 GB - 1 TB HDD SAS 3.5-inch 300 GB - 600 GB HDD SAS 2.5-inch 73 GB - 900 GB	HDD SATA 2.5-inch 250 GB - 1 TB HDD SAS 2.5-inch 73 GB - 900 GB SSD SAS 2.5-inch 100 GB - 400 GB PCIe SSD 320 GB - 640 GB	HDD SATA 2.5-inch 250 GB - 1 TB HDD SATA 3.5-inch 250 GB - 3 TB HDD SAS 2.5-inch 73 GB - 900 GB HDD SAS 3.5-inch 300 GB - 600 GB SSD SAS 2.5-inch 100 GB - 400 GB	HDD SATA 2.5-inch 250 GB - 1 TB HDD SATA 3.5-inch 250 GB - 3 TB HDD SAS 2.5-inch 73 GB - 900 GB HDD SAS 3.5-inch 300 GB - 600 GB SSD SAS 2.5-inch 100 GB - 400 GB
iRMC	yes (advanced pack opt.)	yes (advanced pack opt.)	yes (advanced pack opt.)	yes (advanced pack opt.)
RAID 0, 1 5, 6	✓ optional	✓ optional	✓ optional	✓ optional
Active power (max.)	193 W	627 W	800 W	1070 W
I/O slots	1 x PCIe 2.0 x1, 1 x PCIe 2.0 x4, 1 x PCIe 2.0/3.0 x16	3 x PCIe 3.0 x8, 1 x PCIe 3.0 x16	5 x PCIe 3.0 x8, 2 x PCIe 3.0 x16	1x PCIe 2.0 x4, 2 x PCIe 3.0 x4, 5 x PCIe 3.0 x8, 2 x PCIe 3.0 x16

Model	PRIMERGY RX500 S7 	PRIMERGY RX600 S6 	PRIMERGY RX900 S2 
Characteristics	Economic scaling to four socket performance	Scalability and balanced composition ensure your growth	It starts where 4 socket servers end up!
Type	Quad socket rack server	Quad socket rack server	Eight socket rack server
Height units	4 U	4 U	8 U
Processor	Intel® Xeon® processor E5-4600	Intel® Xeon® processor E7-2800 / Intel® Xeon® processor E7-4800 / Intel® Xeon® processor E7-8800 product families	Intel® Xeon® processor E7-8800 product family
Memory capacity	8 GB - 1536 GB, 48 DIMM (DDR3)	8 GB - 2048 GB, 64 DIMM (DDR3)	8 GB - 4096 GB, 128 DIMM (DDR3)
Storage drives hot-plug	8 x 2.5-inch	8 x 2.5-inch	8 x 2.5-inch
Storage drives hot-plug	HDD SAS 2.5-inch 73 GB - 900 GB SSD SATA 2.5-inch 100 GB - 400 GB SSD SAS 2.5-inch 100 GB - 400 GB	HDD SAS 2.5-inch 73 GB - 900 GB SSD SAS 2.5-inch 100 GB - 400 GB PCIe SSD 320 GB - 640 GB	HDD SAS 2.5-inch 73 GB - 900 GB SSD SAS 2.5-inch 100 GB - 400 GB PCIe SSD 320 GB - 640 GB
iRMC	yes (advanced pack opt.)	yes (advanced pack opt.)	yes (advanced pack opt.)
RAID 0, 1 5, 6	✓ optional	✓ optional	optional optional
Active power (max.)	1400 W	1790 W	2800 W
I/O slots	9 x PCIe 3.0 x8 FH 2 x PCIe 3.0 x16 FH	3 x PCIe 2.0 x4, 4 x PCIe 2.0 x8 (2x hot-plug), 1 x PCIe 2.0 x16, 2 x PCIe x4	2 x PCIe 2.0 x4, 14 x PCIe 2.0 x8 (4 x hot-plug)

Driving your success with unbeatable performance and efficiency

Fujitsu PRIMERGY Blade Servers



Model	PRIMERGY BX920 S3	PRIMERGY BX924 S3	PRIMERGY SX910 S1	PRIMERGY SX940 S1	PRIMERGY SX960 S1	PRIMERGY SX980 S1
Characteristics	Universal dual socket Server Blade with advanced computing and I/O performance in a small form factor	High-end Server Blade with maximum scalability	Easy and fast data backup	For easy and cost effective server consolidation	Direct attached and, in combination with NetApp Data ONTAP-v, shared storage solution (VSX910)	Centralized storage capacity via SAS Connection Blade
Type	Dual socket Server Blade	Dual socket Server Blade	Storage Blade Tape	Storage Blade Disk	Storage Blade Disk	Storage Blade Disk
Max. number per BX900	18	18	6	6	2	6
Max. number per BX400	8	8	4	4	2	3
Processor	Intel® Xeon® processor E5-2400 product family	Intel® Xeon® processor E5-2600 product family	-	-	-	-
Memory capacity	4 GB – 384 GB, 12 DIMM (DDR3)	4 GB – 768 GB, 24 DIMM (DDR3)	-	-	-	-
Storage drives hot-plug / Tape drives	max. 2 x 2.5-inch <ul style="list-style-type: none"> HDD SAS 73 GB – 900 GB HDD SATA 250 GB – 1 TB SSD SAS 100 GB – 400 GB SSD SATA 100 GB – 400 GB 	max. 2 x 2.5-inch (non hot-plug) <ul style="list-style-type: none"> HDD SATA 320 GB – 500 GB (1x), SSD SATA 100 GB – 400 GB (2x), SSD SAS 100 GB – 400 GB (2x) 	max. 1 x SAS <ul style="list-style-type: none"> LTO3HH Ultrium, 400 GB, 60 MB/s, 3Gb/s LTO4HH Ultrium, 800 GB, 120 MB/s, 6Gb/s LTO5HH Ultrium, 1500 GB, 140 MB/s, 6Gb/s 	max. 4 x 2.5-inch <ul style="list-style-type: none"> HDD SAS 73 GB – 900 GB HDD SATA 160 GB – 1 TB SSD SATA 100 GB – 400 GB 	max. 10 x 2.5-inch <ul style="list-style-type: none"> HDD SAS 73 GB – 900 GB HDD SATA 160 GB – 1 TB SSD SATA 100 GB – 400 GB 	max. 10x 2.5-inch <ul style="list-style-type: none"> HDD SAS 73 GB – 900 GB SSD SAS 100 GB – 400 GB
iRMC	yes (iRMC S3 advanced pack incl.)	yes (iRMC S3 advanced pack incl.)	-	-	-	-
RAID 0, 1 5, 6	✓ -	✓ -	-	✓ ✓	✓ ✓	✓ ✓
Ethernet controller onboard	2 x 10 Gbit CNA via midplane to Ethernet Connection Blade	2 x 10 Gbit CNA via midplane to Ethernet Connection Blade	-	-	-	-
Mezzanine cards	2 x PCIe 3.0 x8 (Quad 1Gbit Eth, Dual 10Gbit Eth, Dual 8Gbit FC, Dual 40Gbit IB, Dual 56Gbit IB, SAS HBA/RAID 6Gbit, Dual 10Gbit CNA)	2 x PCIe 3.0 x8 (Quad 1Gbit Eth, Dual 10Gbit Eth, Dual 8Gbit FC, Dual 40Gbit IB, Dual 56 Gbit IB, SAS HBA/RAID 6Gbit, Dual 10Gbit CNA)	-	-	-	-

Model	PRIMERGY BX400 S1	PRIMERGY BX900 S2
Characteristics	Blade Made Easy. Tailor-made performance for midmarket companies	The enhanced dynamic cube
System unit type	6 U chassis for 19-inch rack or floorstand version	10 U chassis for 19-inch rack
Dimensions (WxDxH)	445 x 785 x 267 mm	445 x 778 x 438 mm
Front bays	8 x for server or storage blades	18 x for server or storage blades
Midplane	High speed midplane with 3 fabrics	High speed midplane with 4 redundant fabrics
Rear bays	4 x for Connection Blades 4 x for PSU-Fan modules	8 x for Connection Blades (2 connection blades per fabric) 6 x for PSU modules
Management Blades	1 x hot-plug Management Blade as standard, redundant Management Blade as option	1 x hot-plug Management Blade as standard, redundant Management Blade as option
Fan configuration	Up to 3 hot-plug, redundant fan units (2 fan modules per unit)	Up to 6 hot-plug, redundant fan modules (3 as minimum)
Power supply configuration	Up to 4 x hot-plug power supply modules (1 x as standard)	Up to 6 x hot-plug power supply modules, 3 x as minimum (4th to 6th power supply modules necessary for redundancy, depending on system configuration)
Connection Blade type	<p><u>Ethernet</u> 1 Gb 18/6 switch 1 Gb 36/12 switch 1 Gb 36/8+2 switch</p> <p><u>DCB (Ethernet, FCoE, iSCSI)</u> 10 Gb 18/8 switch 10 Gb 18/6+6 Fabric switch (Brocade) 10 Gb 16/8 Fabric Extender (Cisco) 10 Gb 18/18 Pass Thru</p> <p><u>Fibre Channel (FC)</u> 8 Gb 26-port switch (Brocade) 8 Gb 18/18 Pass Thru</p> <p><u>SAS</u> 6 Gb 18/6 SAS switch</p> <p><u>InfiniBand (IB)</u> 40 Gb 18/18 IB switch (Mellanox) 56 Gb 18/18 IB switch (Mellanox)</p>	

PRIMERGY scale-out servers

Fujitsu PRIMERGY CX server family



Model	PRIMERGY CX400 S1
Characteristics	Rack optimized enclosure for double dense server nodes providing high efficiency and best serviceability for HPC and various datacenter (cloud) scenarios.
System unit type	2 U chassis for 19-inch rack
Weight	up to 38 kg plus 2.5 kg for rack rails
Front bays	Storage drives: 12 x 3.5-inch or 24 x 2.5-inch (HDD, SSD)
Rear bays	2/4 x for 2U/1U half wide server nodes CX2x0 2 x for PSU
Fan configuration	4 non hot-plug fans
Max. input of single power supply	1400 W
Power supply configuration	up to 2 x hot-plug power supply modules (1 x as standard)
Operation panel - Operation buttons	On/Off switch / ID button
Warranty	
Standard Warranty	3 years
Service Level	On-site Service
Standard Warranty note	(depending on country)
Maintenance and Support Services - the perfect extension	
Recommended Service	7 x 24, Onsite Response Time: 4h - For locations outside of EMEA please contact your local Fujitsu partner.
Number of nodes	4 x CX250 S1 2 x CX270 S1



Model	PRIMERGY CX250 S1	PRIMERGY CX270 S1
Characteristics	Multi Node Server for PRIMERGY CX400	HPC optimized Multi Node Server for PRIMERGY CX400
Type	Dual socket node	Dual socket node
Chipset	Intel® C600 (Intel® Patsburg A)	Intel® C600 (Intel® Patsburg A)
Processor(s)	Intel® Xeon® processor E5-2600 product family	Intel® Xeon® processor E5-2600 product family
Memory	16 GB – 512 GB	16 GB – 512 GB
Memory protection	Advanced ECC, SDDC (only for registered DIMMs)	Advanced ECC, SDDC (only for registered DIMMs)
Drive bays	6 x 2.5-inch or 3 x 3.5-inch	6 x 2.5-inch or 6 x 3.5-inch
Storage drives hot-plug	<ul style="list-style-type: none"> ■HDD SATA 2.5-inch 250 GB – 500 GB ■HDD SATA 3.5-inch 250 GB – 3 TB ■HDD SAS 2.5-inch 146 GB – 1 TB ■SSD SATA 2.5-inch 100 GB – 400 GB ■SSD SAS 2.5-inch 100 GB – 400 GB 	<ul style="list-style-type: none"> ■HDD SATA 2.5-inch 250 GB – 1 TB ■HDD SATA 3.5-inch 250 GB – 3 TB ■HDD SAS 2.5-inch 146 GB – 900 GB ■SSD SATA 2.5-inch 100 GB – 400 GB ■SSD SAS 2.5-inch 100 GB – 400 GB
I/O slots	2 x PCIe 3.0 x16	2 x PCIe 3.0 x8 1 x PCIe 3.0 x16 for GPGPU
Onboard or integrated controller		
LAN	2 x 10/100/1000 Mbit/s Ethernet (TCP/IP acceleration)	2 x 10/100/1000 Mbit/s Ethernet (TCP/IP acceleration)
Remote Management Controller	Baseboard management controller (BMC), IPMI 2.0 compatible	Baseboard management controller (BMC), IPMI 2.0 compatible optional 1x GPGPU NVIDIA Tesla M2075 / M2090 computing processor
Operating system and Virtualization Software		
Certified or supported operating systems and virtualization software	Windows Server 2008 / 2012 Windows HPC Server Windows Web Server Microsoft Hyper-V-Server SUSE Linux Enterprise Server Red Hat Enterprise Linux VMware ESXi	Windows Server 2008 / 2012 Windows HPC Server Windows Web Server Microsoft Hyper-V-Server SUSE Linux Enterprise Server Red Hat Enterprise Linux VMware ESXi




Model	PRIMERGY CX1000 S1
Characteristics	Cloud server infrastructure platform for Scale-Out data centers Scale Big - Spend Small
System unit type	Cloud server rack infrastructure
Fan configuration	Cooling unit with two centralized redundant fans produces low pressure plenum in a chimney area at rear side
Cooling	The innovative shared cooling architecture "Cool-Central™" provides new economics for scale-out data centers by significant reduction of energy consumption coupled with dramatic savings in data center space
Height unit rack	43 U
Dimension notes	Rack 38 U + 5 U cooling unit; Rack and cooling unit 250 kg; CX1000 incl. 38 x CX122 + 5x IP switch and all cabling max weight 470 kg
Number of nodes	38
Weight (packed)	500 kg
Weight notes	Actual weight may vary depending on configuration
Dimensions (WxDxH)	700 x 850 x 2083 mm
Active power (min.)	6300 W
Active power (max.)	14000 W
Power supply configuration note	Each CX122 server tray has its own PSU with 350W max.



Model	PRIMERGY CX122 S1
Characteristics	Cloud Server node for PRIMERGY CX1000
Type	Dual socket cloud node
Height units	1 U
Processor(s)	Intel®Xeon® processor 5500/5600 series
Memory capacity	12 – 144 GB 18 DIMM (DDR3)
Drive bays	2 x 2.5-inch
Storage drives	HDD SATA 2.5-inch 160 GB – 1 TB (non hot-plug)
iRMC	yes (advanced pack opt.)
Active power (max.)	350 W (per system unit)
Ethernet controller	2 x Gbit/s Ethernet onboard 1 x dedicated service LAN port
I/O slots	1 x PCIe x16

Integrated Server Lifecycle Management

Fujitsu PRIMERGY ServerView Suite



Deploy Fast, easy, reliable	Control Centralized, easy, efficient	Dynamize Simple, sophisticated, efficient	Maintain In any state, at any place	Integrate Seamless, manage uniformly
Server Setup Installation ✓ SV Installation Manager ✓ SV Scripting Toolkit	Server Monitoring ✓ SV Operations Manager ✓ SV System Monitor ✓ SV Event Management	Private Cloud Infrastructure ♦ SV Resource Orchestrator Cloud Edition (ROR CE)	Remote Management ♦/ ✓ SV Remote - iRMC S2 / iRMC S3 - Management Blades	Uniformed Management ♦/ ✓ SV Integration ♦ Fujitsu ManageNow® solutions ✓ Microsoft SMS & SCCM ✓ Microsoft MOM & SCOM ✓ Microsoft SCE ✓ Nagios ✓ Icinga ✓ HP Network Node Manager ✓ HP Operations Manager ✓ HP Systems Insight Manager ✓ IBM Tivoli TEC ✓ IBM Tivoli NetView ✓ CA Unicenter ✓ CA Spectrum ♦ BMC Patrol
Mass Deployment ♦ SV Deployment Manager ✓ Integration Pack for Altiris Deployment Server	Performance Management ✓ SV Performance Manager ✓ SV Threshold Manager	Consolidated Server Infrastructures ♦ SV Resource Coordinator Virtual Edition (ROR VE)	Update Management ✓ SV Update Manager / Express ✓ SV Download Manager ✓ SV Repository Manager	✓ Microsoft SCE ✓ Nagios ✓ Icinga ✓ HP Network Node Manager ✓ HP Operations Manager ✓ HP Systems Insight Manager ✓ IBM Tivoli TEC ✓ IBM Tivoli NetView ✓ CA Unicenter ✓ CA Spectrum ♦ BMC Patrol
	Power Management ✓ SV Power Monitor ✓ SV Power Consumption Manager	I/O Management ♦ SV Virtual-I/O Manager (VIOM)	Investigation ✓ SV Asset Management - Inventory Manager - Archive Manager ✓ SV PrimeCollect	✓ HP Operations Manager ✓ HP Systems Insight Manager ✓ IBM Tivoli TEC ✓ IBM Tivoli NetView ✓ CA Unicenter ✓ CA Spectrum ♦ BMC Patrol
	Storage Management ✓ SV RAID Manager ✓ SV Storage Manager		Inspection ✓ SV Online Diagnostics ♦ SV Customer Self Service - Local Service Panel - Local Service Display	

✓ = standard / free of charge, ♦ = optional



More Information on PRIMERGY ServerView Suite:
<http://www.fujitsu.com/fts/serverview>

Windows Server 2012

Fujitsu PRIMERGY servers and Microsoft® Windows Server®

	OEM	RORX	MX130 S2	TX100 S3p	TX120 S3p	TX140 S1p	TX150 S8	TX200 S7	TX300 S7	RX100 S7	RX200 S7	RX300 S7	RX330 S7	RX300 S7	RX600 S6	RX900 S2	BX920 S3	BX924 S3	CC250 S1	CC270 S1	CC122 S1	
Windows Server 2008 R2 SP1 Foundation	✓	✓	✓	✓	✓	✓	✓			✓												
Windows Server 2008 R2 SP1 Standard	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		✓	✓	✓	✓	✓	✓
Windows Server 2008 R2 SP1 Enterprise	✓	✓		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Windows Server 2008 R2 SP1 Datacenter	✓	✓		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Windows Server 2012 Foundation	✓	✓	✓	✓	✓	✓	✓															
Windows Server 2012 Standard	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Windows Server 2012 Datacenter	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Windows Small Business Server 2011 Standard	✓	✓		✓	✓	✓	✓	✓	✓	✓	✓	✓					✓	✓				
Windows Small Business Server 2011 Premium Add-on	✓	✓		✓	✓	✓	✓	✓	✓	✓	✓	✓					✓	✓				
Windows Small Business Server 2011 Essentials	✓	✓	✓	✓	✓	✓	✓															

Published by:
 Fujitsu Limited

Issue: September 2012
 Order number: 10431-3-0912-EN

Website: <http://www.fujitsu.com/fts/primergy>
 Copyright © Fujitsu Technology Solutions GmbH



All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/fts/about/fts/environment-care