

KM-6030

A3 MONOCHROME MULTIFUNCTIONAL

▶ print ▶ copy ▶ scan ▶ fax

SHIFT INTO A HIGHER GEAR WITH A VERSATILE DOCUMENT MANAGER.

Designed to support high-speed document workflow in any high-volume environment, this multifunctional reproduction system gives large departments complete control over both electronic and paper documents.

- 60 pages per minute in A4, 31 pages per minute in A3
- Time to first copy: 3.6 seconds
- Duplex document processor for up to 200 sheets
- 4,100 sheets input as standard, upgradeable to 8,100 sheets
- Long-life components

Product depicted includes optional extras

Innovative and productivity-enhancing design: double-sided document scanning in one path.



Professional document finishing solutions: automatic folding, centre binding, saddle stitching and hole punching.



 **KYOCERA**

KM-6030

A3 MONOCHROME MULTIFUNCTIONAL

The KM-6030 incorporates extremely durable components that guarantee efficient and reliable operation. The system is designed to meet the demanding requirements of busy office environments. The KM-6030 provides effective productivity and maximises uptime whilst ensuring a minimum impact on the environment.

System platform:

The KM-6030 offers USB and parallel connectivity as standard and delivers optional network connectivity and problem-free system administration. Kyocera's single platform technology means that the same driver can be used for every Kyocera PCL/PostScript print device on the network: from single-user desktop printers to high-end multifunctional systems. Only Kyocera offers this effortless combination of IT sophistication and high-performance paper handling expertise.

PRESCRIBE IIe:

With the Kyocera page design and control language PRESCRIBE IIe, even complex graphics, logos and forms (even multipart forms) can be created independently of the system and saved and updated in the printer. Consequently, integration into print files no longer applies. They are only accessed as required and therefore relieve the load on the network.

KM-NET for Client/KM-NET Viewer:

The settings of all devices on the network can be checked visually and amended from any Windows® PC. KM-NET for Client enables easy setup and monitoring of the printer status via parallel, USB or network connection. KM-NET Viewer is an advanced printer management software tool using the standardised protocol SNMP.

GENERAL

Technology: Kyocera Laser, Mono component
Engine speed: Max. 60/31 pages per minute A4/A3
Resolution: 1,200 dpi quality (1,800 x 600) (copy/print)
600 x 600 dpi, 256 greyscaled (scan)
Time to first copy: 3.6 seconds or less
Warm-up time: 30 seconds or less
Power source: AC 220 ~ 240 V, 50/60 Hz
Power consumption: Printing: 1,371 W, Stand-by: 395 W, Power-Saving (ECOpower): 236 W
Noise (ISO 7779): Printing: 75 dB(A), Stand-by: 58 dB(A), Power-Saving (ECOpower): Immeasurably low
Dimensions (W x D x H): 680 x 783 x 1,190 mm
Weight: Main unit: Approx. 188 kg
Certifications: TÜV/GS, CE
This product is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by Kyocera under normal environmental conditions.

Input capacity: 2 x 1,500-sheet high-capacity paper feeder, 60-160g/m², A4, 2 x 500-sheet universal paper feeder, 60-160g/m², A3-A5R, Folio
100-sheet multi-purpose tray, 45-200g/m², A3-A6R, Folio
Max. input capacity with options: 8,100 sheets
Duplex as standard
Output capacity: 250 sheets

COPY FUNCTIONS

Max. original size: A3
Continuous copying: 1-9,999
Memory capacity: Standard 128MB and 40GB HDD
Zoom range: 25-400% in 1% steps
Present magnification ratios: 22R / 9E
Digital features: Energy save mode, interrupt copy, scan once copy many, EcoPrint mode, electronic sort, rotate sort, rotate copy, N-up copy, split copy, cover mode, page numbering, image overlay, margin shift, border erase, positive/negative, mirror, proof mode, duplex, booklet copy, program (8), department code (1,000), job building, job reservation, image centring, repeat copy, form registration, shared data box, synergy print box

PRINT FUNCTIONS (OPTIONAL)

Processor: PowerPC 750FX / 600MHz
Memory: Standard 64MB + ECOMemory, max. 576MB (2 additional DIMM slots for 32, 64, 128, 256MB), 1 CompactFlash card slot
Emulations: PCL6/PCL5e incl. PJI, KPDL 3 (PostScript 3 compatible) with automatic emulation sensing (AES), KC-GL (HP-7550A), PDF direct printing, Line Printer, IBM Proprietary X24E, Epson LQ-850, Diablo 630
Controller language: PRESCRIBE IIe
Fonts: 80 outline fonts (PCL6), 136 PostScript KPDL 3 fonts, 1 bitmap font, 45 types of one-dimensional barcodes plus two-dimensional barcode (PDF-417)
Downloadable fonts: Kyocera, PCL + TrueType format, Type 1 + 3 format
Features: eMPS – for quick copy, proof and hold, private print, job storage and job management functionality with hard disk

INTERFACES

Standard interface: High-speed bi-directional parallel (IEEE 1284), USB 2.0 (Hi-Speed), Fast Ethernet 10-Base-T/100Base-TX, 2 KUIO-LV option interface slots
Multiple interface connection (MIC): Allows simultaneous data transfer via up to four interfaces, with each interface having its own virtual printer.

SCAN FUNCTIONS (OPTIONAL)

Functionality: Scan-to-PC, scan-to-email, scan-to-FTP, network TWAIN
Scan speed: 80 originals per minute (600 dpi/A4)
Scan resolution: 600, 400, 300, 200 dpi
Max. scan size: A3
Original recognition: Text, photo, text + photo OCR
Interface: 10Base-T/100Base-TX
Network protocol: TCP/IP
File types: TIFF, PDF
Compression format: G4 (MMR)
Bundle software: DB-Assistant, Scanner file utility, Address Book, Address editor, TWAIN source
Applicable PC: IBM AT/PC compatible, MAC
Applicable OS: Windows 95, 98, ME, NT4.0, 2000, XP, MAC/OS9, MAC/OSX

OPTIONS

Printing system (V), Scan system (G)

Paper handling
PF-650 High-capacity paper feeder: 4,000 sheets, 60-160g/m², A4
PF-660 High-capacity paper feeder: 4,000 sheets, 60-220g/m², A4-A3
DF-650 Document finisher: 3,000-sheet main tray, 200-sheets sub tray, 45-200g/m², staple 50-sheet, 4 modes incl. booklet stapling
MT-1(A) Multi-tray: 5-bins, 150/100 sheets (A4/A3) each bin (optional DF-650)
BF-1(A) Booklet folder: 16 sheets, 60-200g/m² for cover sheet (optional for DF-650)
PH-4C/PH-4D Punch hole unit: 2/4-hole/swedish type (optional for DF-650)

Memory for printing system (V)

DIMM memory: 2 slots for 32, 64, 128, 256MB (max. 576MB)
CompactFlash® card: 1 slot (8, 16, 32, 64MB), forms, fonts, logos, macro storage, PCL Barcode Flash
HD-10 Hard disk: 20GB, storage of data, forms, fonts and eMPS

Security

Data security kit (B)

Optional interface

SB-70 Network card: Wireless LAN – IEEE 802.11b
SB-110FX Network card: 10Base-T/100Base-TX/100Base-FX, FibreOptic
SB-110 Network card: 10Base-T/100Base-TX
IB-11 Serial interface: RS-232C serial interface (max. 115.2 kbps)
IB-23 Network card: 10Base-T/100Base-TX

CONSUMABLES

TK-655 Toner-kit: Microfine toner for 47,000 pages with 6% coverage



Your Kyocera Business Partner:

KYOCERA MITA Europe B.V., Hoeksteen 40, 2132 MS Hoofddorp, The Netherlands, Tel +31 (0) 20 65 40 000, Fax +31 (0) 20 65 31 256, www.kyoceramita-europe.com, info@kyoceramita-europe.com
KYOCERA MITA Corporation, 2-28, 1-Chome, Tamatsukuri, Chuo-Ku, Osaka 540-8585, Japan, www.kyoceramita.com

Kyocera does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

