

Cinterion/Siemens TC35i Terminal Modem GSM con conness. seriale



Cinterion TC35i (ex Siemens TC35i) è un terminale modem GSM con connessione seriale RS-232 e supporto voce, dati/fax ed SMS.

Scheda tecnica



SIEMENS

General features

- Dual-Band GSM 900/1800 MHz
[Please check here available bands in your country](#) (before product purchase)
- Compliant to GSM phase 2/2+
- Output power:
 - Class 4 (2 W) for EGSM900
 - Class 1 (1 W) for GSM1800
- Control via AT commands
- SIM Application Toolkit
- Supply voltage range: 8 ... 30 V
- Temperature range
 - Normal Operation: -20°C to +70°C
 - Restricted Operation: -25°C to +75°C
 - Switch off: +80°C
 - Storage: -40°C to +85°C
- Dimensions: 65 x 74 x 33 mm
- Weight: 130 g

Specification for CSD data transmission

- Up to 14.4 kbit/s
- V.110
- Non-transparent mode
- USSD support

Specification for SMS

- Point-to-point MO and MT
- SMS cell broadcast
- Text and PDU mode

Specification for fax

- Group 3, class 1, 2

Specification for voice

- Triple-rate codec for HR, FR and EFR
- Basic hands-free operation
- Echo cancellation
- Noise reduction

Special features

- 7E1-character framing

Interfaces

- Antenna connector FME (male)
- Plug-in power supply
- Handset audio interface
- Mini-SIM card reader
- V.24/V.28 interface on the 9-terminal sub-D socket
- Operating status LED

Approvals

- R&TTE, GCF, e-mark, CE
- Local approvals and network operator certifications
- ROHS & WEEE compliant

Web: <http://www.smsco.it>

The following networks operate in this country/area: ITALY

Telecom Italia SpA (TIM)	GSM 900/1800	Live
Telecom Italia SpA (TIM)	3G 2100	Live
Telecom Italia SpA (Telecom Italia)(INTERNATIONAL WATERS)	GSM 900/1800	Live

<http://maps.mobileworldlive.com/network.php?cid=21&cname=Italy>