

# Data Sheet

## Fujitsu FUTRO S700

### Thin Client

#### The Affordable Thin Client

---

The individually configurable Fujitsu FUTRO S700 thin client is ideal for secure server-based computing and desktop virtualization. Silent and easy to use, it also offers straightforward integration and manageability. User convenience is supported through a small footprint, dual monitoring and unique connectivity options. Exceptional quality guarantees a long lifecycle. Combined with low energy consumption, this minimizes your TCO.

#### Green technology

Your company's contribution to environmental protection

- A modern, environmentally conscious product concept - from development to recycling

#### Relaxed working

Quiet system for a pleasant working environment

- Flash memory and passive cooling concept

#### Energy efficiency

Saves energy and reduces CO2 emissions

- Integrated system concept with high-level power-saving components

#### Manageability


Easy administration while reducing total cost of ownership

- Outstanding manageability solution

#### Backpack solution

Less space needed

- The FUTRO S700 can be mounted behind the screen



# Technical details Components

<b>Memory modules</b>	1 GB (1 module(s) 1 GB) DDR3, 1066 MHz, PC3-8500, SO DIMM
	2 GB (1 module(s) 2 GB) DDR3, 1066 MHz, PC3-8500, SO DIMM
<b>Graphics</b>	DP to DVI-D (single link) Adapter Cable
<b>Hard disk drives (internal)</b>	mSATA, 1 GB Flash drive
	mSATA, 2 GB Flash drive
	mSATA, 4 GB Flash drive
	mSATA, 8 GB Flash drive
<b>Interface add on cards/components (optional)</b>	WLAN module
	Internal speaker
	2nd LAN/Power-over-Ethernet module
<b>Base unit</b>	FUTRO S700
<b>Operating system and software (Linux)</b>	
<b>Operating system</b>	eLux® RL - Embedded Linux
<b>Functions</b>	eLux® RL V3.8.0 or newer
	Adobe Flash Player 11 for Linux, V11.2.202.236-2 or newer
	Eterm 97801 terminal emulation, V3.1-1 or newer
	Mozilla Firefox Browser, V3.6.19.1-1 or newer
	RDP client, V1.7.1.2-4 or newer
	ICA client, V12.1.0-9 or newer
	VMware® View Client, V5.0.1.1-2 or newer (optional) (including support for PCoIP)
RDPConnect, V3.0-1 or newer	
Updates and optional software packages are available at <a href="http://www.mylux.com">www.mylux.com</a>	
<b>Options available via customizing</b>	Wireless LAN support Remote administration VPN support Firewall support
<b>Manageability</b>	Scout Enterprise, Flash memory management, Embedded operating system update and system monitoring, Managing devices by location, group or user, Individual operating system composition with ELIAS (only with eLux® RL)
<b>VPN (Linux)</b>	VPN client (optional)
<b>Operating system and software (Windows)</b>	
<b>Operating system</b>	Windows® Embedded Standard 7 (WS7E)
	Windows® Embedded Standard 7 (WS7E multimedia)

**Operating system and software (Windows)**

<b>Functions</b>	WS7E: Citrix® Receiver V 2.1.45663.0_12202010 or newer WS7E: Citrix® Online Plugin Full V 12.1.0.30_10282010 or newer WS7E: VMware® View Client V 4.6.0-366101 or newer (including support for PCoIP) WS7E: RDP-Client Protocol V 7.1 with RemoteFX or newer WS7E: Internet Explorer 8 WS7E: Acrobat Reader V 9.3 or newer WS7E: .NET Framework 2.0 or newer WS7E: Scout Agent for Windows® Embedded Standard 7 (optional) WS7E multimedia: Citrix® Receiver Enterprise V 3.3 or newer WS7E multimedia: VMware® View Client V 5.2.0-848202 or newer (including support for PCoIP) WS7E multimedia: RDP-Client Protocol V 7.1 with RemoteFX or newer WS7E multimedia: Internet Explorer 9 WS7E multimedia: Acrobat Reader X or newer WS7E multimedia: .NET Framework 4.0 or newer WS7E multimedia: Scout Agent for Windows® Embedded Standard 7 WS7E multimedia: WEDM Microsoft Windows Embedded Device Manager
<b>Manageability</b>	Scout Enterprise
<b>VPN (Windows)</b>	VPN through CUZ available

**Mainboard**

<b>Mainboard type</b>	D3003-B
<b>Formfactor</b>	miniITX
<b>Processor</b>	AMD G-Series G-T44R (1.2 GHz, )
<b>Chipset</b>	AMD A55E Controller Hub
<b>Processor quantity maximum</b>	1
<b>Memory slots</b>	1 SO DIMM (DDR3, 1066 MHz)
<b>Supported capacity RAM (max.)</b>	2 GB
<b>LAN</b>	Built-in 10/100/1000 MBit/s
<b>BIOS features</b>	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)
<b>Audio type</b>	On board
<b>Audio codec</b>	Realtek ALC262
<b>Audio features</b>	AC'97 codec

**Interfaces**

<b>Audio: line-in</b>	1
<b>Audio: line-out</b>	1
<b>Front audio: headphone</b>	1
<b>Front audio: line-in / microphone</b>	1
<b>USB 2.0 total</b>	8
<b>USB front</b>	2
<b>USB rear</b>	4
<b>USB internal</b>	2
<b>DisplayPort</b>	1 DP
<b>DVI</b>	1 DVI-I (integrated VGA can be used with DVI-VGA adapter)
<b>Serial (RS-232)</b>	1 external
<b>Mouse / Keyboard (PS/2)</b>	2
<b>Ethernet (RJ-45)</b>	1
<b>Kensington Lock support</b>	1

**Graphics**

<b>Graphics brand name</b>	AMD Radeon™ HD 6250
<b>Graphics color depth</b>	32 bit colors
<b>Shared video memory</b>	up to 256 MB
<b>TFT resolution (VGA)</b>	up to 1920 x 1200 pixel

**Graphics**

TFT resolution (DVI)	up to 1920 x 1200 pixel
TFT resolution (DisplayPort)	up to 2560 x 1600 pixel
Graphics features	DirectX 11 Shader Model 5 Open CL™ 1.1 (depending on CPU) OpenGL 4.1
Graphics notes	Graphics resolution depending on operating system and management solution.

**Network**

Network	TCP/IP with DNS and DHCP Point-to-Point protocol Supported Citrix Load Balancing over ICA DHCP support for automatic firmware upgrades and unit configuration Multiple master browser support on ICA
---------	--

**Electrical values**

Rated voltage range	100 V - 240 V (AC Input)
Rated frequency range	50 Hz - 60 Hz
Operating voltage range	100 V - 240 V (AC Input)
Operating line frequency range	50 Hz - 60 Hz

**Power consumption for standard configuration with Windows Embedded Standard**

Power consumption: Maximum (S0, running appl.)	19.9 W
Power consumption: Idle (S0, running OS, Idle mode)	9.1 W
Power consumption: Minimum (ACPI status S5, soft off, WOL enabled)	0.58 W

**Dimensions / Weight / Environmental**

Dimension with stand (W x D x H)	97 x 191 x 266 mm
Operating position	Vertical / horizontal
Weight	1,2 kg
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 35 °C
Operating relative humidity	5 - 85 % (relative humidity)

**Compliance**

Product	FUTRO S700
Model	TCS-D3003B
Germany	GS
Europe	CE certification according to EC Directive 2004/108/EEC CB
USA/Canada	CSA FCC Class B (depending on wireless configuration) CAN/CSA ICES-003 Class B
Global	ENERGY STAR® 5.0 RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) EPEAT® Silver (dedicated regions)
Japan	VCCI
India	WPC
Russia	GOST
Compliance notes	Energy Star compliance may vary depending on actual configuration
Compliance link	<a href="http://globalsp.ts.fujitsu.com/sites/certificates/default.aspx">http://globalsp.ts.fujitsu.com/sites/certificates/default.aspx</a>

<b>Security</b>	
Audit proof protection	Write protection for the Flash module
<b>Warranty</b>	
Standard Warranty	2 years (depending on country)
Service level	Bring-in Service (for countries within region FTS CEMEA&I, for all other countries depending on local regulations, minimum: 2 years material warranty)
Warranty Terms & Conditions	<a href="http://support.ts.fujitsu.com/warranty">http://support.ts.fujitsu.com/warranty</a>
<b>Maintenance and Support Services - the perfect extension</b>	
Recommended Service	9x5, Response Time: Next Business Day
Spare Parts availability	5 years after end of product life
Service Weblink	<a href="http://www.fujitsu.com/fts/services/support">http://www.fujitsu.com/fts/services/support</a>

## Recommended Accessories

Midspan Micro Semi PD-9501G		Midspan Micro Semi PD-9501G is a single port Power over Ethernet solution, specially designed to power IEEE 802.11n and other high power Ethernet end Terminals with 60W. It is fully backward compatible and easy to implement in your existing Ethernet infrastructure.	Order Code: S26361-F1744-L10
Midspan Micro Semi PD-9512G		Midspan Micro Semi PD-9512G is a Power over Ethernet solution with 12 ports, -72W per port, specially designed to power network devices like cameras, access control systems, Thin Clients and other Ethernet end terminals. It is fully backward compatible and supports IPv4 and IPv6.	Order Code: S26361-F1744-L20
Longshine Switch		The 16-Port 10/100/1000 Mbps Gigabit Longshine switch provides you a real Gigabit connection. Users are able to transfer large files with high bandwidth requirements faster while administrators experience a real efficiency improvement. The fanless Longshine switch is energy efficient, easy to install and fully compliant with all kinds of network protocols.	Order Code: S26391-F6055-L416
Mounting Kit Solution FUTRO S		The Fujitsu Mounting Kit Solution for FUTRO S gives you two options for mounting your thin client behind a display and hiding the system cables out of the way. The solid metal mounting bracket lets you mount directly to a VESA compatible display or via the included subadapter plate with Velcro™ strap for non-VESA displays.	Order Code: S26361-F2601-L530
Display B22W-6 LED		The B22W-6 LED offers best ergonomics and usability for intensive office use with a 4-in-1 stand.	Order Code: S26361-K1375-V140

**Display B24W-6 LED**



The Fujitsu Display B24W-6 LED combines the best ergonomic and energy saving solutions for intensive office use. The flexible stand with height adjust assures an individual and healthy posture for long-time working sessions. With its impressive screen size it allows working on different documents in parallel or standard CAD applications.

Order Code:  
S26361-K1427-V140

**Mouse MC200**



The Fujitsu Mouse MC200 provides SMB and enterprise the right combination of quality features and cost savings. It is appropriate for either right or left handed users and features two mouse buttons plus a scroll wheel that acts as a third button. It connects with a familiar plug and play USB interface for trouble free installation.

Order Code:  
S26381-K463-L100

**Keyboard KB900**



The KB900 is a very flat keyboard with extra low keys and spill-resistant protection. The elegant design and top-quality construction makes the KB900 the ideal input device for any PC or Notebook user. If you accidentally spill some water or coffee onto the keyboard, this special construction helps the liquid to flow away.

S26381-K560-L4\*\* (\*\*:  
Country specific variation)

**Wireless Keyboard Set LX900**



The Wireless Keyboard LX900 is a top of the line desktop solution for lifestyle orientated customers, who want only the best for their desk. This superb keyboard set with offers ambitious users more functions, security and better features than a conventional interface device. It even includes 2.4 GHz technology and 128 AES encryption for security.

S26381-K564-L4\*\* (\*\*:  
Country specific variation)

# More information

## Fujitsu OPTIMIZATION Services

In addition to Fujitsu FUTRO S700, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

### Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

### Computing Products

[www.fujitsu.com/global/services/computing/](http://www.fujitsu.com/global/services/computing/)

### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

## More information

Learn more about Fujitsu FUTRO S700, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. [www.fujitsu.com/fts/FUTRO](http://www.fujitsu.com/fts/FUTRO)

## Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment/>



## Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see [www.fujitsu.com/terms](http://www.fujitsu.com/terms)

Copyright © Fujitsu Technology Solutions

## Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

## Contact

FUJITSU Technology Solutions  
Website: [www.fujitsu.com/fts](http://www.fujitsu.com/fts)  
2013-02-27 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see [www.fujitsu.com/terms](http://www.fujitsu.com/terms)  
Copyright © Fujitsu Technology Solutions