

### MicW Audio

a division of BSWA Technology Ltd.

Add: Unit 1003, North Ring Center No.18 Yumin Road,  
Xicheng District, Beijing 100029, China

Phone: +86-10-5128 5118

Fax: +86-10-8225 1626

Email: sales@micwaudio.com

Web: www.micwaudio.com

### European office

Fred van Eijk

Tel: +31 6 538 00 254

Add: Esdoorn 22B 6226TA Maastricht, The Netherlands

Email: fred@micwaudio.com

### U.S. Office

MicW USA

Add: P.O.Box 2289 Renton, WA 98056, U.S.A

Phone: 425-998-3936

Fax: 425-526-5817

Email: qunyanm@micwaudio.com

Pictures for reference only, subject to our available products.

# Professional Microphones

For Studio, Broadcast and Live applications.



**MicW** | professional  
microphones

## Introduction

At MicW/BSWA, we are committed to the research, design and manufacture of high-quality microphones for measurement, studio, and broadcast use. Passionate about pure sound, captured or amplified, we always demand the highest levels of craftsmanship and employ dedicated audio engineers, test engineers and highly skilled craftsmen to produce the best possible products for an increasingly demanding market. All our microphones undergo rigorous testing in a range of studio and other recording sessions that replicate actual customer applications.

Only the best quality materials, such as nickel and titanium, are used in our microphone ranges. These include the nickel diaphragm N-Series and the titanium large diaphragm T-Series. Both of these ranges have impressive specifications that result in clear, pure sound. Our innovative design approach, combined with the use of high-grade materials, aims to bring you a new and exciting recording experience.

As well as researching new approaches, we constantly strive for innovation. 2011 saw the release of our i-Series external professional microphones for iPhone, iPad, iPod Touch and other mobile devices, with the i436 Class 2 mic in particular garnering an overwhelming amount of interest. For more information on this series, we invite you to read our new i-Series brochure, or visit <http://www.micwaudio.com>.

We are proud that our products can contribute to the optimization and refinement of your recordings, live performances, and broadcasts. Our goals for 2013/14 include enhancing our product ranges and delivering increasingly high levels of service. We also hope to meet you at one of this year's pro audio exhibitions where we will be pleased to demonstrate our products and discuss your particular requirements.


WU QUINLI, PhD, CEO



T-Series  
unique LDC titanium capsule.



N-Series  
recording microphone for high-end  
recording and broadcasting.



L-Series  
professional Lavalier microphones for  
TV, ENG, video production and stage  
applications.



H-Series  
headworn microphones.



E-Series  
for interviews, ENG, podcasts and film/  
video production.



M-Series  
measurement microphones complying  
with the IEC 61094 and IEC61672 Sound  
Level Meter standards.



i-Series  
Professional Microphones are designed especially  
for iOS devices like the iPad, iPhone and iPod Touch,  
but can also be used in other mobile devices.



# T-Series

MicW's T-Series offers new and innovative microphone technology. The T551 cardioid LCD model boasts a 1.5" / 38 mm titanium diaphragm and an elegant body design. Offering remarkable flexibility, the microphone's extremely wide range, low-distortion performance and temperature/humidity resistance makes it suitable for a wide range of applications.

## The T-Series

### General Description

The capsule is the most important element of any microphone. However in this series, it's the absolute highlight! Made from pure titanium, the T-Series 38mm capsule is manufactured under clean room conditions using a special secret process.

### Why Titanium?

For a capsule of this size, the material must meet several very specific requirements:

- Light weight
- Robust construction
- Optimum vibration characteristics

This particular combination can only be found with pure titanium.

The capsule housing is made from solid copper, providing the necessary weight to effectively suppress resonances.

Following manufacture, each capsule spends 24 hours in a climate chamber being artificially "aged". This helps prevent the sound changes that can often occur through standard ageing.

| Preferred       | Recommended      |
|-----------------|------------------|
| Acoustic guitar | Solo vocals      |
| Backing vocals  | Grand piano      |
| Bongos          | Upright piano    |
| Congas          | Cello            |
| Cymbals         | Clarinet         |
| Horn            | Tom-tom          |
| Hi-hat          | Violin           |
| Harmonica       | Guitar amplifier |
| Flute           | Bass amplifier   |
| Trumpet         | Woodwind         |
| Trombone        | Marimba          |
| Sax             |                  |

### Microphone Placement:

There is a common view in the recording industry that sound from a properly miked high-quality instrument, played by a skilled musician, can be sent directly to a DAW / recording device with little or no modification necessary.

The T-Series capsule housing contains an integral pop filter.



## T551 Cardioid LCD

MicW's T-Series offers new and innovative microphone technology. The T551 cardioid LCD model boasts a 1.5" / 38 mm titanium diaphragm and an elegant body design. Offering remarkable flexibility, the microphone's extremely wide range, low-distortion performance and temperature/humidity resistance makes it suitable for a wide range of applications.

### Applications



### Specifications

| Microphone T551           |                         |
|---------------------------|-------------------------|
| Type                      | Pre-polarized condenser |
| Capsule diameter          | 38mm (1.5")             |
| Polar pattern             | Cardioid                |
| Sensitivity ( $\pm 3$ dB) | 40mV/Pa;                |
| Frequency response        | 20Hz~20kHz              |
| Power supply              | 48V phantom power       |
| Max. SPL (<1% THD)        | 135 dB                  |
| Equ. noise level          | <16 dBA                 |
| Output impedance          | <200 Ohm                |
| Length                    | 163mm                   |
| Weight                    | 340g                    |
| Connector                 | 3-pin XLR               |



# N-Series

MicW's N-Series microphones contain nickel diaphragm capsules derived from parent company BSWA's leading-edge technology. Products range from 1" to 1/4" microphones. Together with the compact CN 201, the N-Series provides a comprehensive range of omnidirectional and cardioid models.

## N-Series

With their nickel diaphragm capsules and high-quality preamplifiers, N-Series microphones deliver an extremely natural, transparent sound with very high fidelity. A 5µm-thick nickel membrane, mounted in a stainless steel housing, is optimized and manually stretched to enable the best transmission. An elaborate process, it is nevertheless the only way to achieve such an extraordinary sound quality. N-Series microphones are also remarkable for their very low noise floor and impressive SPLs (up to 140dB max), along with an unparalleled frequency response of 20Hz - 40kHz. This enables the microphones to deliver pure sound with no added color. Due to their discreet size, the CN Series microphones are ideal for close miking of instruments during live performances and TV production work.

| Preferred       | Recommended      |
|-----------------|------------------|
| Acoustic guitar | Ensemble / choir |
| Acoustic bass   | Solo vocals      |
| Double bass     | Grand piano      |
| Backing vocals  | Upright piano    |
| Bongos          | Cello            |
| Congas          | Clarinet         |
| Cymbals         | Tom-tom          |
| Horn            | Violin           |
| Hi-hat          | Guitar amplifier |
| Harmonica       | Bass amplifier   |
| Flute           | Woodwind         |
| Trumpet         | Marimba          |
| Trombone        | Kick drum        |
| Sax / brass     | Mallets          |
| Bassoon         |                  |



What's in the N-Series box: N-Series microphones are supplied in a hard plastic case with professional shock mount, windscreen and frequency test report included.

## N101 Large Diaphragm

The N101 is an omnidirectional microphone with 1" capsule and totally transparent preamplifier. The capsule design includes stainless steel housing and a 5µm-thick nickel diaphragm. The diaphragm tension is carefully adjusted during manufacture to ensure a frequency response of 20Hz - 20kHz. The N101 offers a totally transparent audio path with an exceptionally low noise floor and an SPL handling capability of 135dB. The N101 Pair is a state-of-the-art stereo kit featuring two matched N101 microphones. Each pair has a guaranteed sensitivity match to within 0.5 dB and a phase match to within 5°.

### Applications



### Specifications

| Microphone N101    |                         |
|--------------------|-------------------------|
| Type               | Pre-polarized condenser |
| Capsule diameter   | 23.8mm (1")             |
| Polar pattern      | Omnidirectional         |
| Sensitivity (±2dB) | 50mV/Pa;                |
| Frequency response | 20Hz~20kHz              |
| Power supply       | 48V phantom power       |
| Max. SPL (<1% THD) | 135 dB                  |
| Equ. noise level   | <18 dBA                 |
| Output impedance   | <200 Ohm                |
| Length             | 157mm                   |
| Weight             | 165g                    |
| Connector          | 3-pin XLR               |



## N151 Cardioid Large Diaphragm

The N151 is a cardioid microphone with pressure gradient capsule. The capsule uses similar construction materials to the N101, with a nickel diaphragm and stainless steel housing. It is carefully handcrafted to provide optimal neutrality, accuracy and extremely low distortion. The first-order cardioid pick-up pattern gives superb separation between sound sources while spot miking in every kind of live music situation.

### Applications



### Specifications

| Microphone N151    |                         |
|--------------------|-------------------------|
| Type               | Pre-polarized condenser |
| Capsule diameter   | 23.8mm (1")             |
| Polar pattern      | Cardioid                |
| Sensitivity (±2dB) | 32mV/Pa;                |
| Frequency response | 20Hz~20kHz              |
| Power supply       | 48V phantom power       |
| Max. SPL (<1% THD) | 137 dB                  |
| Equ. noise level   | <19 dBA                 |
| Output impedance   | <200 Ohm                |
| Length             | 157mm                   |
| Weight             | 165g                    |
| Connector          | 3-pin XLR               |



## N201 Standard Omni

The N201 is an omnidirectional microphone with 1/2" capsule and totally transparent preamplifier. It is suitable for the most critical recording applications that require extreme performance and environmental stability. The microphone has a flat frequency response from 20Hz - 20kHz, with a low noise floor of 18dB(A). Acoustic accessories are also available for the N201 including directional modifiers and protection grids. These modify the acoustic behavior of the microphone in terms of directional pattern and high frequency response.

The N201 Pair is a state-of-the-art stereo kit featuring two matched N201 microphones. Each pair has a guaranteed sensitivity match to within 0.5 dB and a phase match to within 5°.

### Applications



### Specifications

| Microphone N201    |                         |
|--------------------|-------------------------|
| Type               | Pre-polarized condenser |
| Capsule diameter   | 12.7mm ( 1/2")          |
| Polar pattern      | Omni                    |
| Sensitivity (±2dB) | 40mV/Pa;                |
| Frequency response | 20Hz~20kHz              |
| Power supply       | 48V phantom power       |
| Max. SPL (<1% THD) | 135 dB                  |
| Equ. noise level   | <18 dBA                 |
| Output impedance   | <75 Ohm                 |
| Length             | 155mm                   |
| Weight             | 120g                    |
| Connector          | 3-pin XLR               |




## N241 Reference

The N241 is a reference microphone with 1/2" all-metal capsule. Carefully engineered to give long-term reliability and accuracy, it has a linear frequency response of up to 40kHz achieved through superior acoustic and mechanical design.

The N241 can handle extreme sound levels up to 140dB. Drums, percussion, brass and other powerful sound sources can be close miked with total accuracy for a clean, undistorted, dynamic sound. Designed according to IEC 61094 standard dimensions, the N241 can be calibrated using the BSWA CA 114 Sound Level Calibrator.

### Applications



### Specifications

| Microphone N241    |                         |
|--------------------|-------------------------|
| Type               | Pre-polarized condenser |
| Capsule diameter   | 12.7mm ( 1/2")          |
| Polar pattern      | Omni                    |
| Sensitivity (±2dB) | 26mV/Pa;                |
| Frequency response | 20Hz~40kHz              |
| Power supply       | 48V phantom power       |
| Max. SPL (<1% THD) | 140 dB                  |
| Equ. noise level   | <22 dBA                 |
| Output impedance   | <75Ohm                  |
| Length             | 150mm                   |
| Weight             | 120g                    |
| Connector          | 3-pin XLR               |





The CN Series is - due to its small footprint - very suitable for TV and Video live productions.

## CN201 Compact Microphone

The omnidirectional CN201 compact microphone has a similar 1/2" capsule to the N201. However, its small footprint makes it ideal for direct instrument miking in orchestral environments, as well as for use on drums, overheads, string sections etc.

### Applications




### Specifications

| Microphone CN201   |                         |
|--------------------|-------------------------|
| Type               | Pre-polarized condenser |
| Capsule diameter   | 12.7mm ( 1/2")          |
| Polar pattern      | Omni                    |
| Sensitivity (±2dB) | 40mV/Pa;                |
| Frequency response | 20Hz~20kHz              |
| Power supply       | 48V phantom power       |
| Max. SPL (<1% THD) | 135dB                   |
| Equ. noise level   | <18 dBA                 |
| Output impedance   | <200 Ohm                |
| Cable length       | 3m                      |
| Mic Length         | 22mm                    |
| Weight             | 34g                     |
| Connector          | 3-pin XLR               |







## L-Series

With their extremely small size and superior EMI protection, MicW's new L-Series professional lavalier microphones deliver maximum performance in situations where microphone invisibility is important. Omni and cardioid pick-up patterns produce a warm clear sound that makes L-Series microphones perfect partners for a range of applications including broadcast, ENG, conferences and stage work.

## L-Series

### Lavalier Microphones

The omnidirectional L825 and cardioid L855 lavalier microphones are highly recommended for on air productions and forum discussions. They are also durable enough for ENG use. Their discreet dimensions make them well suited to television and video production.

### L825 Omnidirectional

#### Applications



#### Specifications

| Microphone L825           |              |
|---------------------------|--------------|
| Type                      | Condenser    |
| Capsule diameter          | 4.0mm        |
| Principle of operation    | Pressure     |
| Polar pattern             | Omni         |
| Sensitivity ( $\pm 3$ dB) | 5.6mV/Pa     |
| Frequency response        | 20Hz~20kHz   |
| Max. SPL (<0.1% THD)      | 126dB        |
| Equ. noise level          | 31dB(A)      |
| Power                     | 0.8-5V DC    |
| Operating temperature     | -17°C ~+60°C |
| Cable length              | 1.6m         |
| Weight                    | 1g           |
| Connector                 | Microdot*    |



# MicW's L-Series

The L-Series has been designed with a Microdot connector, MicW also provides several breakout adapters (see photo below) for a wide range of wireless systems or XLR input applications.

**\* Connector options**


- LC131AK Microdot to TA3F for connection to an AKG transmitter.
- LC241SH Microdot to TA4F for connection to a SHURE transmitter.
- LC031SE Microdot to mini jack with thread for connection to a Sennheiser transmitter.



- LC032SE Microdot to Lemo, for connection to a Sennheiser transmitter.
- LC441MW Microdot to mobile device for connection to iPhone, iPad and other smart devices.



## The L825 Kit contains the following items:



# H-Series

The H-Series includes MicW's new professional head-worn microphone. With its micro-miniature capsule and well designed single-ear mount, it delivers a clear and articulate sound regardless of the position of the capsule relative to the sound source.

# H-Series

## Headworn Microphones

The headworn omnidirectional H825 is designed for applications such as spoken word, singing, keyboard/vocal performance and other voice applications that require a headworn microphone with superior noise rejection and a smooth, natural-sounding frequency response.

The omnidirectional H825 has an extremely small capsule diameter (only 4mm) and is fitted with a very thin but robust cable, which is durable enough for ENG use.



### Applications



### Specifications

| Microphone H825        |              |
|------------------------|--------------|
| Type                   | Condenser    |
| Capsule diameter       | 4.0mm        |
| Principle of operation | Pressure     |
| Polar Pattern          | Omni         |
| Sensitivity(±3dB)      | 5.6mV/Pa     |
| Frequency response     | 20Hz~20kHz   |
| Max. SPL(<0.1% THD)    | 126dB        |
| Equ. noise level       | 31dB(A)      |
| Power                  | 0.8-5V DC    |
| Operating temperature  | -17°C ~+60°C |
| Cable length           | 1.6m         |
| Connector              | Microdot*    |

With optional adapters, the microphone can be used with virtually any manufacturer's wireless beltpack system.

#### \* Connector options

- LC131AK Microdot to TA3F for connection to an AKG transmitter.
- LC241SH Microdot to TA4F for connection to a SHURE transmitter.
- LC031SE Microdot to mini jack with thread for connection to a Sennheiser transmitter.



- LC032SE Microdot to Lemo, for connection to a Sennheiser transmitter.

- LC441MW Microdot to mobile device for connection to iPhone, iPad and other smart devices.



### The H825 Kit contains the following items:

- 1 Connector of choice
  - Microdot to Sennheiser Minijack (LC031SE) or
  - Microdot to AKG (LC131AK) or
  - Microdot to Shure (LC241SH) or
  - Microdot to Sennh 3-pin Lemo (LC032SE) or
  - Microdot to iPhone 3.5mm Jack (LC441MW)



# E-Series

MicW's E-Series is the perfect microphone range for start-up recordists, recording musicians and sound hobbyists. E-Series microphones offer both great sound and amazing value for money.

## E-Series

"E" stands for Entry Level. This microphone range is derived from the N-Series, but uses a less expensive capsule. Nevertheless, the polymer gold-layered diaphragm captures every detail in the sound field. Offering amazing value for money, E-Series microphones are ideal for start-up sound engineers, recording musicians and hobbyists.



| Preferred           | Recommended      |
|---------------------|------------------|
| Acoustic guitar     | Ensemble / choir |
| Acoustic bass       | Solo vocals      |
| Backing vocals      | Grand piano      |
| Bongos              | Upright piano    |
| Congas              | Cello            |
| Cymbals             | Clarinet         |
| Horn                | Tom-tom          |
| Hi-hat              | Violin           |
| Harmonica           | Guitar amplifier |
| Flute               | Bass amplifier   |
| Trumpet             | Woodwind         |
| Trombone            | Marimba          |
| Sax / brass         | Kick drum        |
| Outdoor bird sounds | Mallets          |
| Overdubs            |                  |

## E216 Omnidirectional

The E216 is an omnidirectional microphone with 1/2" capsule. It offers extraordinary performance at a low cost. The microphone's polymer diaphragm (covered with a thin gold layer) and its copper housing yield a flat frequency response up to 20kHz, with excellent dynamic range and low self noise. The E216 is ideal for miking delicate instruments and for spot miking during live performances and TV/broadcast productions.

### Applications



### Specifications

| Microphone E216    |                         |
|--------------------|-------------------------|
| Type               | Pre-polarized condenser |
| Capsule diameter   | 12.7mm (1/2")           |
| Polar pattern      | Omnidirectional         |
| Sensitivity (±2dB) | 30mV/Pa;                |
| Frequency response | 20Hz~20kHz              |
| Power supply       | 48V phantom power       |
| Max. SPL (<1% THD) | 135dB                   |
| Equ. noise level   | <28 dBA                 |
| Output impedance   | <75 Ohm                 |
| Length             | 155mm                   |
| Weight             | 120g                    |
| Connector          | 3-pin XLR               |



## E150 Series Modular Microphone

### New Technology - Natural Sound.

With the E150 Series, MicW once again breaks new ground. For the first time, a micro-perforated stainless steel panel is used as a front grille - an incredible 2,300 holes with a diameter of just 0.25mm!

The resulting effect on the sound is significant. Popping and sibilance are greatly reduced without any negative impact on the overall quality.

This technology is very common in aerospace and industrial audio measurement. It enables every nuance (detail) of the signal to be transmitted unaltered\*. Recordings sound extremely natural and "rounded", with high resolution and transient response.



\* Micro-Perforated Technology

### Applications



### Specifications

| Microphone E150                 |                            |               |                 |
|---------------------------------|----------------------------|---------------|-----------------|
| Capsule                         | E151                       | E152          | E153            |
| Polar pattern                   | Cardioid                   | Hypercardioid | Omnidirectional |
| Capsule diameter                | 20 mm                      |               |                 |
| Sensitivity (±3dB)              | -42 dB re. 1v/Pa           |               |                 |
| Frequency response              | 20 Hz ~ 20kHz              |               |                 |
| Power supply                    | 48V phantom power          |               |                 |
| Total harmonic distortion (THD) | < 1% up to 135 dB SPL peak |               |                 |
| Thermal noise                   | < 17 dBA                   |               |                 |
| Output impedance                | < 100 Ohm                  |               |                 |
| Length                          | 155mm                      |               |                 |
| Weight                          | 185g                       |               |                 |
| Connector                       | 3-pin XLR                  |               |                 |

\* The polar pattern and frequency response graphs are available on the MicWaudio.com website.



## MicW's E-Series

The E150 modular microphone offers a choice of omni, cardioid and super-cardioid condenser capsules. The following packages cater for a range of recording applications and are highly recommended for students and start-up engineers:

**E150 Set:** microphone preamplifier; cardioid capsule; hyper cardioid capsule; omni capsule; windscreen; shock mount; box; user manual

**E150 Stereo Set:** 2 x microphone preamplifier; 2 x cardioid capsule; 2 x super cardioid capsule; 2 x omni capsule; 2 x windscreen; 2 times shock mount; user manual




**E151 cardioid:** microphone preamplifier; cardioid capsule; windscreen; shock mount

**E152 super cardioid:** microphone preamplifier; super cardioid capsule; windscreen; shock mount



**E153 omni:** microphone preamplifier; omni capsule; windscreen; shock mount



## M-Series

MicW's M-Series professional measurement microphones comply with IEC 61094 and IEC 61672 sound level meter standards

## M-Series

### Measurement Microphones

What makes a good measurement microphone for audio applications? In addition to frequency response, sensitivity, omnidirectional polar pattern and dynamic range, the IEC 61094 specification for measurement microphones lists two further requirements:



- Calibration: The microphone should be capable of being calibrated by one of the following methods:

- Calibration methods specified in IEC 61094-2 or IEC 61094-3.
- Comparison with a standard calibrated laboratory microphone.
- Calibration using a sound calibrator as specified in IEC 60942.

The majority of measurement microphones currently on the market lack calibration capability due to structural or dimensional limitations.

- Environmental Sensitivity Stability: The standards also specify that microphone sensitivity changes due to temperature, humidity and static pressure should be within  $\pm 0.03$  dB/C,  $\pm 0.001$  dB/% and  $\pm 0.03$  dB/kPa. Most currently available measurement microphones do not meet these criteria, or are not tested under specific environmental conditions.

MicW/BSWA has 14 years of experience in manufacturing measurement microphones for industrial use. The M-Series measurement microphones for audio applications reflect that experience.



## M416 Measurement Microphone

The M416 is a calibrated measurement microphone with a detachable 1/4" capsule. It complies with the IEC 61672 Class 2 sound level meter standard and is suitable for measuring sound pressure in simple sound fields such as home recording studios and high-end hi-fi rooms.

### Applications



### Specifications

| Microphone M416   |                         |
|---|-------------------------|
| Type  | Pre-polarized condenser |
| Capsule diameter  | 7mm (1/4")              |
| Polar pattern   | Omni                    |
| Sensitivity ( $\pm 2$ dB)                                 | 30mV/Pa;                |
| Frequency response  | 20Hz~20kHz              |
| Power supply  | 48V phantom power       |
| Max. SPL(<1% THD)   | 130 dB                  |
| Equ. noise level  | <30 dBA                 |
| Output impedance  | <600 Ohm                |
| Maximum sensitivity change due to Temperature -10 to 50°C | +/-1.0 dB               |
| Humidity up to 98%RH                                      |                         |
| Pressure: 65 to 115 kPa                                   |                         |
| Length  | 144mm                   |
| Weight  | 110g                    |
| Connector   | 3-pin XLR               |



## M215 Measurement Microphone

The M215 is a calibrated measurement microphone with a detachable 1/2" capsule. It complies with the IEC 61094 and IEC 61672 Class 1 sound level meter standards that are widely used during technical reference measurement in professional audio environments such as theaters, recording studios, control room design and stage acoustics.

### Applications



### Specifications

| Microphone M215                 |                         |
|---------------------------------|-------------------------|
| Type                            | Pre-polarized condenser |
| Capsule diameter                | 12.7mm (1/2")           |
| Polar pattern                   | Omn                     |
| Sensitivity ( $\pm 2$ dB)       | 40mV/Pa;                |
| Frequency response              | 20Hz~31.5kHz            |
| Power supply                    | 48V phantom power       |
| Max. SPL (<1% THD)              | 135 dB                  |
| Equ. noise level                | <18 dBA                 |
| Output impedance                | <75 Ohm                 |
| Temperature coefficient (dB/°C) | 0.009                   |
| Humidity coefficient (dB/%RH)   | 0.001                   |
| Pressure coefficient (dB/kPa)   | 0.008                   |
| Length                          | 155mm                   |
| Weight                          | 120g                    |
| Connector                       | 3-pin XLR               |



## i-Series

The i-Series microphones are innovatively designed for use with iPhones, smartphones, DSLR and GoPro cameras. They offer outstanding performance in a range of audio measurements, recording, broadcasting and sport events applications. The iGoMic, a new member of the i-Series, is the latest innovative microphone from MicW.





# MicW's i-Series

## iGoMic™ Stereo Microphone

The iGoMic comprises an X-Y stereo-matched pair of microphone capsules specially designed for GoPro cameras. Using a matched pair with capsules configured at 90° X-Y coincident, the iGoMic provides a wide stereo image with natural depth and is ideal for recording music, sports events and ambient sound. It is small, lightweight and rugged. It also can be used with DSLR and video cameras.

### Applications



### Specifications

| iGoMic Stereo Microphone |                             |
|--------------------------|-----------------------------|
| Type                     | Electret Condenser          |
| Capsules                 | Matched pair cardioid       |
| Principle of Operation   | Two capsules in XY stereo   |
| Polar Pattern            | XY coincident               |
| Sensitivity(±3dB)        | -42 dB                      |
| Frequency Response       | 20Hz – 20 KHz               |
| Maximum SPL              | 115dB                       |
| S/N ratio                | >55dB                       |
| Impedance                | <2.2Kohm                    |
| Power supply             | Plug and Play               |
| Operating Temperature    | -20°C - +50 °C              |
| Diameters                | 20mm (Max); 14 mm (Min)     |
| Length                   | 51 mm                       |
| Weight                   | 16g                         |
| Connector                | 3.5 mm Stereo mini (female) |
| Output Channels          | Stereo Left and Right       |



## Accessories



PP190  
Shock mount for N-Series



PP290  
Shock mount for E-Series



PP390  
Mic holder for M-Series



PP590  
Shock mount for T-Series



PP591  
Shock mount for T-Series



WS015  
Windscreen for E150 Series



WS018  
Windscreen for L-Series, H-Series



WS022  
Windscreen for iGoMic



WS034  
Windscreen for M-Series



WS051  
Windscreen for 1" mic (50mm diameter)



WS052  
Windscreen for 1/2" mic (50mm diameter)



WS054  
Windscreen for 1/4" mic (50mm diameter)



**WS092**  
Windscreen for 1/2" mic  
(90mm diameter)



**WS094**  
Windscreen for 1/4" mic  
(90mm diameter)



**AM032**  
Acoustic equalizer  
(30mm diameter)



**AM042**  
Acoustic equalizer  
(40mm diameter)



**LC032SE**  
Microdot to Lemo,  
for connection to a  
Sennheiser transmitter



**LC241SH**  
Microdot to TA4F for  
connection to a SHURE  
transmitter



**LC131AK**  
Microdot to TA3F for  
connection to an AKG  
transmitter



**LC441MW**  
Microdot to mobile  
device for connection to  
iPhone, iPad and other  
smart devices



**AM052**  
Acoustic equalizer  
(50mm diameter)



**GD012**  
Grid for N201 and N241



**GD031**  
Grid for N101 and N151



**GD041**  
Grid for N101 and N151



**PI50**  
Microdot to XLR adaptor  
– provides 48V phantom  
power



**ATO11**  
Storage tube for M-Series



**PP011**  
Mic holder



**PB025**  
Plastic box for L-Series



**GD051**  
Grid for N101 and N151



**CA114**  
Sound level calibrator



**CLO11**  
Collar clip for CN



**CLO12**  
Collar clip



**PB030**  
Plastic box for CN201 and  
M-Series



**PB035**  
Plastic box for H-Series  
and iGoMic



**PB040**  
Plastic box for E150 Series



**PB050**  
Plastic box



**CL020**  
Rubber ring spare part  
for PP011



**CLO28**  
Crocodile clip



**TP011**  
Windscreen for L-Series



**LC031SE**  
Microdot to mini  
jack with thread  
for connection to a  
Sennheiser transmitter



**PB060**  
Plastic box



**CB031U**  
mini USB (30cm)



**CB030M (30cm)**  
3.5mm stereo cable (male  
mini jack)

## Company profile

Renowned for its pure clean sound, quality craftsmanship and elegant styling, MicW prides itself in designing and manufacturing high-quality, high performance microphones for a wide range of audio measurement and recording applications. MicW microphones and accessories are a perfect choice when only the best will do for vocal, instrumental, broadcast, film and video recording.

MicW's product ranges include the E-Series entry-level microphones, i-Series microphones for iOS and other portable devices, L-Series lavalier microphones, M-Series test measurement microphones, N-Series nickel diaphragm high performance microphones, H-Series headworn microphones, and the T-Series titanium diaphragm large diameter microphone.

## Features

- Flat frequency response for pure sound without unwanted coloring
- Titanium, nickel, stainless steel and polymer composite capsule diaphragm designs for the best possible microphone frequency response
- Excellent high humidity performance
- Fast transient response, wide dynamic range, low noise floor with models that easy handle up to 160 dB SPL
- Quality assurance through ISO 9001 certification



## Heritage

MicW is a division of BSWA Technology Ltd., a measurement microphone company. BSWA was founded in 1998 as a joint venture between the Chinese Academy of Sciences and five sound engineers looking to market high-quality affordable measurement microphones. Today, BSWA microphones are widely used in aerospace, automotive and environmental noise measurement. The experience and expertise gained from designing and manufacturing measurement microphones has enabled BSWA to create MicW, a microphone brand primarily aimed at the pro audio and music oriented markets.

Unique methods are used in the production of MicW's microphone capsules (the heart of any microphone), resulting in enhanced performance, increased reliability, greater sound definition and transparency. MicW capsule diaphragms are made from titanium, nickel, stainless steel and polymer composites, ensuring that the best material is always used for a specific design. Carefully selected quartz insulating material is also used in the microphone construction to guard against high temperatures and humidity. Each capsule is individually calibrated using the free field method in accordance with IEC 61049 measurement microphone standards, and "aged" in an environmental chamber for long-term stability.

## Quality Assurance

As a leader in the field of microphone technology, MicW invests heavily in product research and development. The company's main design campus and manufacturing facilities are located in Beijing, China and include anechoic chambers, clean rooms, environmental rooms and production areas.

MicW is committed to total quality management and is ISO 9001 certified, ensuring that every product meets stringent performance standards.



RoHS

