

Printer Specifications

Physical Specifications

Width: 666 mm (26.22 in.)

Depth: 626 mm (24.65 in.)

Height: 460 mm (18.11 in.)

Weight: 68 kg (149 lbs.)

Environmental Specifications

Temperature

- Storage: -20 degrees to 60 degrees C / -4 degrees to 140 degrees F
- Operating: 10 degrees to 32 degrees C / 50 degrees to 90 degrees F
- Optimum print quality environmental conditions: 17 degrees to 26 degrees C / 62 degrees to 80 degrees F

Relative Humidity

- Storage: 10% to 95%
- Operating: 10% to 85%
- Optimum print quality environmental conditions: 35% to 70%

Electrical Specifications

Available in two models:

- 110-127 VAC, 50/60 Hz
- 220-240 VAC, 50/60 Hz

ENERGY STAR® qualified printer

Performance Specifications

Resolution

- 600 x 600 dpi
- 600 x 2400 dpi

Print Speed

- Up to 37 ppm (pages per minute) black
- Up to 30 ppm color

Controller Specifications

500 MHz processor

Memory

- 128 Mbytes PC133 DRAM Standard on the Phaser® 7300B Color Printer
- 192 Mbytes PC133 DRAM Standard on the Phaser® 7300N Color Printer
- 256 Mbytes PC133 DRAM Standard on the Phaser® 7300DT Color Printer
- 384 Mbytes PC133 DRAM Standard on the Phaser® 7300DX Color Printer
- Upgradable to a maximum of 512 Mbytes

Page Description Languages (PDL)

- PCL5c
- Adobe PostScript 3
- PDF

Resident Fonts

- 136 PostScript Type 1
- 115 Central European PostScript Type 1
- 46 PCL fonts

Interfaces

- IEEE 1284 parallel
- Ethernet 10BaseT and 100BaseTx
- USB