



Urethane Synthetic Turf Adhesive

IBOLA[®] R-201

Fast-setting and economical 2 part urethane adhesive for installation of synthetic turf



- no VOC or solvents
- achieves LEED points
- installs in light rain and blazing heat
- no hazardous material
- no shipping restrictions
- lifetime warranty



Urethane Synthetic Turf Adhesive IBOLA® R-201

Durable, flexible adhesive for the installation of synthetic turf provides ideal playing conditions

The new generation of synthetic turf for sports fields can match the properties of natural grass, and even exceeds natural grass with regard to playing properties, maintenance costs and wear. But, sports-related and technical specifications are determined not only by the type of synthetic turf but even more so by professional installation using the proper adhesive products. A synthetic turf must not only meet the requirements of the specific sports with their extreme wear characteristics, but also has to withstand constantly changing ambient conditions such as rain and moisture, frost and snow. Consequently, an adhesive is required that has been specifically formulated to meet these extreme conditions.

7:0, Touch Down IBOLA R-201

IBOLA R-201 meets all requirements for a professional, durable installation of synthetic turf. With IBOLA R-201 adhesive, we help customers fulfill the installation guidelines for UEFA and FIFA certification.



IBOLA also offers seaming tape C-145, available in widths of 12" and 20" and lengths of either 330' or 980'.



Installation Benefits of IBOLA R-201

- ▶ Lifetime Warranty
- ▶ Installs in high humidity
- ▶ Installs on moist sub floors
- ▶ Even installs in light rain
- ▶ Installs between 32° - 100°F
- ▶ Adheres after 2 hours
- ▶ Excellent ridge formation
- ▶ Very high spread rate
- ▶ Easy to spread

Environmental Features of IBOLA R-201

- ▶ no VOC or solvents
- ▶ achieves LEED points
- ▶ no hazardous material
- ▶ no shipping restrictions
- ▶ suitable on heated sub floors



Sub floors/substrates	▶ Suitable on prepared sub floors
Open time	▶ approx. 45 min. at 70 °F
Potlife	▶ approx. 30 min. at 70 °F
Color	▶ Green
Spread Rate	▶ 6" wide: approx. 100 LF / gal. (approx. 50 SF / gal.)
Package size	▶ 2 gal. Part A + 1½ qrt. Part B



Observe Technical Data Sheet

For further information, please contact

STAUF USA, LLC.
6055 Primacy Parkway
Suite 428
Memphis, TN 38119
Toll-Free 866-GLUE USA
Phone 901-820-0007
Fax 901-820-0101
www.ibolausa.com
info@ibolausa.com

