

### **D-Link ANT24-0801**

### 8.5dBi Pico Cell Patch Antenna



- 8.5dBi Signal Gain
- 2.4GHz Frequency Range
- Swivel Mount for Directional Orientation
- Weatherproof and Corrosion Resistant

### Indoor/Outdoor 8.5 dBiPico Cell Patch Antenna

The D-Link ANT24-0801 is a Pico Cell Patch Antenna for wireless data transmission in indoor or outdoor environments. The ANT24-0801 provides 8.5dBi signal strength operating on 2.4~2.5 GHz ISM band (Industrial, Scientific and Medical). This provides wider range of wireless coverage to reduce the cost of running standard cable lines.

The ANT24-0801 is a convenient way to extended wireless coverage to an existing 802.11b wireless LAN network. The ANT24-0801 can be used with the DWL-900AP+ wireless access point, DI-614+ wireless router, DI-714P+ wireless router,

DWL-900AP wireless access point, DI-714 wireless router and the DI-713P wireless router Rev C1 or later wireless broadband router. The ANT24-0801 is weatherproof and made of corrosionresistant material to withstand harsh outdoor conditions.

The D-Link ANT24-0801 includes a swivel mount that allows pivotal adjustment for precise positioning for the most concentrated signal strength. The D-Link ANT24-0801 includes a Lightning Surge Protector and 3 meters of Extension cable.

## The D-Link ANT24-0801 Includes

Antenna

Manual

Conversion Cable

Mounting Kit

### 8.5dBi Pico Cell Patch Antenna

# Technical Specifications

#### **Electrical Specifications**

Frequency Range 2300 MHz -2500 MHz

Gain 8.5dBi

**VSWR** 1.5: 1 Max

**Polarization** Linear, vertical

**HPBW** 

horizontal: 70°vertical: 65°

Front to Back Ratio

15 dB

**Power Handling** 

50W (cw)

Impedance

50 Ohms

Connector

N-female

**Cable Length** 

3 Meters

**Environmental & Mechanical Characteristics** 

**Survival Wind Speed** 

200 km/hr

**T**emperature

-40°C to 80°C

Humidity

100% @ 25°C

**Lightning Protection** 

DC ground

**Radome Color** 

Gray-white

**Radome Material** 

ABS, UV resistant

**Housing Material** 

AL6063

Weight

0.3 kgw

Dimensions

120 x 120 x 43mm

Warranty

1 Year





