



Think big, with small. Epson's portable printer TM-P20 delivers mobility with efficiency in its compact size and rugged design, capable of fast print speeds of up to 100mm/s and a drop rating of 1.98m. Featuring a best-in-class operational battery life, fast Near Field Communication (NFC) pairing and a versatile compatibility with multiple smart devices, it is ideally suited for on-the-go printing - from retail to hospitality across various business applications. Reliable and easy to use, the TM-P20 is vital in elevating your business' productivity.













High Performance, Small Footprint

Discover a lightweight of 221g along with ultra-compact features and multiple connectivity options.

Industry-leading Battery Life

Ensure uninterrupted service to customers with up to 16 hours operational battery life for Wi-Fi models and 26 hours for Bluetooth models.

Easy Setting and Configuration

Comes complete with ESC/POS®, OPOS, JavaPOS and Windows® drivers which allow instant compatibility with existing POS solutions.



MODEL NUMBER	TM-P20
Print Technology	
Printing Method	Thermal line printing
Print Font	
Font	Font A: 12 x 24 32cpl; Font B: 9 x 24 42cpl (Default); Font C: 9 x 17 42cpl; Font D: 10 x 24 38cpl;
	Font E: 8 x 16 48cpl
Character Size (W x H)	Font A: 1.5 x 3.0mm; Font B: 1.12 x 3.0mm; Font C: 1.12 x 2.1mm; Font D: 1.25 x 3.0mm;
	Font E: 1.0 x 2.0mm
Character Set	95 Alphanumeric, 18 International, 128 x 43 Graphic
	Bar code: UPC-A, UPC-E, JAN8/EAN8, JAN13/EAN13, ITF (Interleaved 2 of 5), Codabar (NW-7),
	Code 39, Code 93, Code 128, GS1-128 (UCC/EAN-128), GS1 DataBar Omnidirectional, GS1 DataBar
	Truncated, GS1 DataBar Limited, GS1 DataBar Expanded, 2D symbol, PDF417, Datamatrix, QR Code,
	Maxi Code, Composite Aztec
nterface	802.11b/g/n (2.4GHz) and 802.11a/n (5GHz) or Bluetooth 3.0 (EDR supported)
ata Buffer	4,000 bytes
rint Speed Max.	100 mm/sec (Receipt Version)
Oot / Line	384 dots
ot / Inch	203 dpi
aper	
Dimensions (mm)	Roll paper: 57.5 ± 0.5 (W) × Dia. 40.4
ower	Custom Lithium-Ion Battery Pack, AC Adapter (Option)
Power Saving	Auto Power-off Function, Wi-Fi Power-saving Function
Charging	AC Adapter (3 hours to Full Charge)
attery Life*	Wi-Fi: 9 hours Wi-Fi (Energy saving mode): 16 hours Bluetooth: 26 hours
perating Temperature	10 to 50° C (14 to 122° F) Bluetooth Model, 0 to 50° C (32 to 122° F) Wi-Fi Model
lumidity	10 – 90% RH
Prop Rating	Test Rating of 6.5 feet
Reliability	
Printer Mechanism Life	10 million lines
TIBF	10 million lines 120,000 hours
MCBF	
Colour	16,000,000 lines
	Epson Black (EBCK)
Overall Dimensions (W x D x H) Mass (Approx.)	79.0 x 119.8 x 43.6mm (Belt clip included)
	Wi-Fi Model: Approximately 221 g (0.49 lb)
	Bluetooth Model: Approximately 212 g {0.47 lb}
Nuki nun	(Battery included; Belt Clip and Roll Paper Excluded, and Single Charger not included) Single Printer Charges (Vandle (OT 2000), Pottors Papels (OT 2000), Pottors Papels (OT 2000)
Options	Single Printer Charger/Cradle (OT-SC20), Battery Pack (OT-BY20), Padded Case (OT-PC20),
standard Accessories ROM	Battery Spacer (OT-BS20)
Ciandalu Accessories NOIVI	Roll Paper x 1 Roll (For Checking the Initial Movement of the Printer), CD-ROM (Drivers, Utility software,
Same and Indones attack	Manuals), Setup guide, Battery, Printer Charger, Belt Clip
General Information	Mala 1000 Are decided and Miladaure (Occopital and IMITA MIDA MIDAO December 117
Supported Operating Systems	Mobile iOS, Android and Windows, (Security Level WEP, WPA, WPA2-Personal/Enterprise)
MOM	64 MB
IV Area	User NV 1 KB, NV Graphics 384 KB
audible Alert	Programmable Buzzer
Sensors	Paper End, Cover Open, BM Sensor
ED Indicators	Battery Charge Level, Power Status, Error Condition
Software	TM-P20 Utility, EpsonNet Config, EpsonNet Simple Viewer, TM-P20 Remote Configuration Tool,
	TM Bluetooth Connector, Built-in Configuration Page
asy Setting	Easy Connection for Bluetooth - NFC, Easy Connection for Wi-Fi - NFC, Easy Connection for Bluetooth -
	Barcode, Easy Connection for Wi-Fi – Barcode, Easy Wi-Fi Setting – AdHOC Mode

Dimensions & Weight

Weight: Approx. 221 g (0.49 lb)



egend

i dots per 25.4 mm (dots per inch)

cpl characters per line

*P20 battery life can vary significantly depending on usage.

© 2015 Epson India Pvt. Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibitiot. EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation. All other products names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Information correct at time of printing Printed February 2015

EPSON INDIA PVT. LTD.

12th Floor, The Millenia, Tower A, No.1, Murphy Road, Ulsoor, Bangalore - 560 008. Tel: 080-30515000 Fax: 080-30515005

Regional Offices:

Ahmedabad - 2640 7176/77, Chennai - 3967 7500, Cochin - 4012 315, Coimbatore - 98942 19200, Indore - 4701 830, Kolkata - 6500 9370/77, Mumbai - 3079 8200, New Delhi - 3312 0300/01, Pune - 3028 6000/05, Secunderabad - 6463 9640/41





Dealer's Stamp

