

SNT-EX154

A fully featured four channel blade type video surveillance encoder, utilising state of the art image transmission and enhancement technology



Overview

Four Channel Blade Type Video Surveillance Encoder

Designed for use in applications requiring up to four analogue channels, the SNT-EX104 is a powerful, fully featured video encoder delivering a range of unique features.

The SNT-EX154 delivers a unique blade type four channel camera encoding concept delivering highly flexible system expansion possibilities with a range of rack mounting accessories. The SNT-EX154 adds significant value and performance to existing medium to large scale analogue systems where a highly scalable encoding solution is required.

Converting up to four traditional analogue video signals per blade into multiple digital video streams for transmission via IP-based networks, the SNT-EX154 offers unrivalled network flexibility.

Sony's unique XDNR (Excellent Dynamic Noise Reduction), VE (Visibility Enhancer) technology and DEPA Advanced (Distributed Enhanced Processing Architecture) combine with RS-485 and Coaxitron telemetry support to deliver superior image quality, a powerful video and audio analytics capability and advanced telemetry support to existing analogue systems.

The combination of powerful features and the enhancements offered to existing systems makes the Sony SNT-EX154 encoder the obvious choice when migrating from existing analogue camera systems, to a powerful, flexible and scalable IP based monitoring solution.

ONVIF (Open Network Video Interface Forum) compliance for easy interoperability with IP monitoring products from a variety of manufacturers.

- **The ultimate in scalable analogue to digital migration solutions from Sony**

Sony's SNT-EX154 encoders and rack mounting accessories connect with existing analogue cameras to deliver flexible IP integration solutions. Crisp and clear CCTV images are available with Sony's advanced image processing technology. The SNT-EX154 offers a highly scalable systems solution with enhanced levels of security, even in the most challenging lighting conditions.

- **Highly flexible network capability**

Enjoy exceptional operational flexibility using the ideal compression format for differing image and network types (JPEG for high quality still images).

- **Optimum image quality when using traditional analogue cameras**

By using Sony's SNT-EX range of encoders users can benefit from unrivalled image quality. State of the art image enhancing technology, that only Sony can offer, delivers clearer, brighter and higher quality images.

- **Simple to install, easy to maintain**

Intelligent IP and MAC support stores MAC address information to significantly reduce servicing and time and costs.

- **ONVIF compliance offers the optimum in system flexibility**

Compliance with ONVIF (Open Network Video Interface Forum) ensures interoperability and maximum flexibility between a wide range of manufacturers' network video products.

Features

- **Enhanced performance and image quality in all conditions combines with D1 resolution support in a highly scalable encoding solution**

Sony's unique XDNR (Excellent Dynamic Noise Reduction) and VE (Visibility Enhancer) and DFI (Dynamic Frame Integration) Technology come as standard features within the SNT-EX series of encoders. This unique image enhancing technology delivers superior noise free images in the most challenging conditions. By utilizing Sony's SNT-EX series with XDNR, VE and DFI technology high quality D1 resolution support, analogue camera's can now deliver superior imaging performance.

- **Triple codec operation**

The SNT-EX series supports three compression formats: JPEG, the best choice of high-quality still images.

- **Clear low-light images**

XDNR (Excellent Dynamic Noise Reduction) technology virtually eliminates image blur in low-light conditions, enabling users to clearly capture images that have not been easy to portray in the past. It also overcomes the problems associated with many competitor camera models. What's more, when both XDNR and Visibility Enhancer are turned on, the cameras can achieve four times the sensitivity compared to when they are off. This technology is ideal for any outdoor surveillance monitoring, such as in a car park at night.

- **Improved performance in challenging lighting conditions**

VE (Visibility Enhancer) technology improves performance in challenging lighting conditions, for example high-contrast environments, such as casinos and highways, that had previously been difficult to monitor. The Visibility Enhancer's advanced system suppresses extreme whites and boosts dark areas in a scene simultaneously and dynamically, to produce clearer images on the screen.

- **Improved performance from dynamic scenes**

DFI (Dynamic Frame Integration) technology produces superior images from scenes containing both still and moving objects. DFI technology detects moving objects and reduces motion blur, simultaneously detecting stationary objects and reducing jagged edges. DFI delivers an optimized image with superior clarity and can be added to any analogue system by utilizing Sony's SNT-EX series.

- **Powerful Intelligent Video Analytics**

Sony's SNT-EX Series encoder's include a complete IP surveillance solution based on its Distributed Enhanced Processing Architecture (DEPA™) platform. Intelligent video analytics automatically identify critical events for a high-level of security and to provide streamlined workflows. Unlike conventional monitoring solutions, the DEPA solution provides added intelligence to assist the surveillance operator in taking quick action. Users can precisely refine parameters for use in conjunction with the Intelligent Motion Detection and Intelligent Object Detection functions. By utilizing the SNT-EX series encoders, analogue cameras can now deliver the significant benefits offered by DEPA Advanced analytics.

- **Highly scalable systems solution**

The Sony SNT-EX154 encoders are complimented by a range of blade mounting accessories. Comprising of 1U and 3U rack options the encoding system can be expanded by adding SNT-EX154 blades to accommodate up to 16 or 48 analogue channels respectively.

- **Tamper Alarm**

When an attempt is made to tamper with the camera, such as spray-painting the lens, the SNT-EX Series detects this and triggers an alarm. This event can also be used to activate the camera relays, or even to start the Voice Alert function.

- **Advanced Audio Detection**

Unlike conventional audio detection where an alarm is triggered based on a preset audio level, the SNT-EX Series triggers its alarms based on ambient sound conditions as the threshold. The camera stores and updates ambient audio levels and frequencies, and when the threshold level based on this data, is surpassed, an alarm is triggered.

- **Voice Alert**

The encoder can store up to three pre-recorded audio alert messages which may be played via an active speaker upon manual or automatic initiation.

- **Versatile telemetry interface**

The SNT-EX series offers support for control of 3rd party telemetry cameras. Maximum flexibility of control is offered via RS-422, RS-485 and Coaxitron interfaces.

- **Flexible streaming support**

Video can be stored on optional USB memory media and then streamed using RTP/RTCP or RTSP protocols. This function is available with s/w version 1.1 or later.

- **Flexible recording and storage solutions**

External storage is also possible using USB flash memory. Continuous, pre and post event video may stored in compressed format for later retrieval.

- **Support for IPv6**

The SNT-EX Series supports Internet Protocol Version 6 (IPv6).

- **ONVIF Compliant**

The ONVIF (Open Network Video Interface Forum) defines a common protocol for the exchange of information between network video devices including automatic device discovery, video streaming and intelligence metadata. Allows interoperability between network video devices. By utilizing Sony SNT-EX encoders, analogue systems can fully benefit from full ONVIF interoperability.

Technical Specifications

Camera Features	
● Tone Correction	VE (VE)
● Noise Reduction	XDNR

Video Server Features	
● Coaxitron Control	Yes

Video	
● Resolution	720 x 576, 720 x 470, 640 x 480, 384 x 288, 320 x 240
● Compression Format	H.264, MPEG-4, JPEG
● Maximum Frame Rate	30 fps
● Multi Streaming Capability	Dual streaming
● Number of Clients	10

Intelligent Video/Audio Analytics	
● Intelligent Motion Detection	Yes
● Advanced Audio Detection	Yes

Audio	
● Compression Format	G.711, G.726

Network	
● Protocols	IPv4, IPv6, TCP, UDP, ARP, ICMP, IGMP, HTTP, HTTPS, FTP (client/server), SMTP, DHCP, DNS, NTP, RTP/RTCP, RTSP, SNMP (MIB-2)
● Number of IP Address/Mac ADDRESS	4
● Wireless Network	No
● Authentication	IEEE 802.1x

Interface	
● Analog Video Input	x4
● Composite Buffered Through Out	No
● Microphone Input	Mini jack (monaural), MIC IN/LINE IN: over 2.2 kΩ, DC 2.45 V plug-in power
● Audio Interface (IN/OUT)	IN: x1 OUT: x1
● Line Output	Mini jack (monaural), Max output level: 1.5 Vp-p
● Network Port	10BASE-T/100BASE-TX (RJ-45)
● Alarm Input (Sensor Input)	x4
● Alarm Output	x4
● Serial Interface	RS-485
● USB Slots	x4

General	
● Power Requirements	From Rack Station
● Power Consumption	12 W max.
● Operating Temperature	0°C to +45°C +32°F to 113°F
● Storage Temperature	-20°C to +60°C -4°F to +140°F
● Dimensions (W x H x D)*1	78 x 34 x 382 mm 3 1/8 x 1 3/8 x 15 1/8 inches
● Mass	Approx. 0.4 kg Approx. 14 oz

Notes	
● *1	The values for dimensions are approximate.

Compatible Products

Encoders



SNT-RS3U

Video Network Station rack mount for the SNT-EP154 and SNT-EX154