

Optoma Projector Range (EN)

Touchboards

205 Westwood Ave, Long Branch, NJ 07740
Phone: 866-94 BOARDS (26273) / (732)-222-1511
Fax: (732)-222-7088 | E-mail: sales@touchboards.com



UltraMobileLED

Ultra mobile



ML750e



ML1500e



X304M



W304M

	ML750e	ML1500e	X304M	W304M
Resolution	WXGA 1280 x 800	WXGA 1280 x 800	XGA 1024 x 768	WXGA 1280 x 800
Brightness ¹ (Bright mode)	700 LED Brightness*	1500 LED Brightness*	3000 ANSI Lumens	3100 ANSI Lumens
Contrast	15,000:1	20,000:1	10,000:1	10,000:1
Noise Level (Eco mode)	30dB	30dB	33dB	33dB
Weight (kg)	0.38	1.4	1.4	1.4
Lamp Life ² (hrs)	20,000 (LED Life) Bright	20,000 hours LED Life Bright	4000/5000 Eco/Bright	4000/5000 Eco/Bright
Dimensions (WxDxHmm)	105 x 106 x 39	270 x 170 x 42	220 x 178 x 71	220 x 178 x 71
Image Size	0.43 - 2.54m (17" - 100") Diagonal 16:10	0.43 - 2.54m (17" - 100") Diagonal 16:10	0.68m - 5.26m 33.58" - 259.25") Diagonal 4:3	0.68 - 6.54m (31.65" - 303.44") Diagonal 16:10
Throw Ratio	1.5:1	1.4:1	1.9 - 2.2:1	1.53 - 1.76:1
Zoom Type	-	-	1.15x Manual Zoom	1.15x Manual
Keystone Correction	±40° Vertical	±40° Vertical (Auto)	± 30° Vertical	± 30° Vertical
Connections	HDMI + MHL v1.0, Universal I/O - VGA / Audio Out 3.5mm, microSD-slot, USB-A reader/wireless	HDMI, VGA (YPbPr/RGB), Composite, Audio In 3.5mm, Audio Out 3.5mm, SD card slot, 2 x USB-A reader/wireless, micro USB	HDMI (1.4a 3D support), VGA (Wireless/YPbPr/RGB), Composite, Audio In 3.5mm, Audio Out 3.5mm, USB remote mouse	HDMI (1.4a 3D support), VGA (Wireless/YPbPr/RGB), Composite, Audio In 3.5mm, Audio Out 3.5mm, USB remote mouse
Optional Wireless	Yes	Yes	Yes	Yes
Speaker (Watts)	1	6W stereo (2x3W) SRS WOW HD Audio	1	1
Bag	Yes	Yes	Yes	Yes
Features	Native office viewer, media player, 1.5GB memory, LED light source, optional wireless presenting	Native office viewer, media player, LED light source, optional wireless presenting		

Mobile



DS340



S310



S311



S313

	DS340	S310	S311	S313
Resolution	SVGA 800 x 600	SVGA 800 x 600	SVGA 800 x 600	SVGA 800 x 600
Brightness ¹ (Bright mode)	2800 ANSI Lumens	3000 ANSI Lumens	3200 ANSI Lumens	3000 ANSI Lumens
Contrast	18,000:1	20,000:1	20,000:1	20,000:1
Noise Level (Eco mode)	28dB	28dB	28dB	26dB
Weight (kg)	2	2	2	2.5
Lamp Life ² (hrs)	5000 Bright	7000/6500/6000/5000 Eco+/Dynamic/Eco/Bright	7000/6500/6000/5000 Eco+/Dynamic/Eco/Bright	4500 Bright
Dimensions (WxDxHmm)	287 x 193 x 113	287 x 193 x 113	287 x 193 x 113	316 x 224 x 124
Image Size	0.69 - 7.62m (27.24" - 300.04") Diagonal 4:3	0.69 - 7.62m (27.24" - 300.04") Diagonal 4:3	0.69 - 7.62m (27.24" - 300.04") Diagonal 4:3	0.69 - 7.62m (27.24" - 300.04") Diagonal 4:3
Throw Ratio	1.97 - 2.17:1	1.97 - 2.17:1	1.97 - 2.17:1	1.97 - 2.17:1
Zoom Type	1.1x Manual	1.1x Manual	1.1x Manual	1.1x Manual
Keystone Correction	± 40° Vertical	± 40° Vertical	± 40° Vertical	± 40° Vertical
Connections	VGA (YPbPr/RGB), Composite, RS232, USB remote mouse/service	VGA (YPbPr/RGB), Composite, RS232, USB remote mouse	2x HDMI (1.4a 3D support), RS232, USB remote mouse/service, USB-A Power	HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), S-Video, Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RS232, USB remote mouse/service, USB-A Power
Optional Wireless	Yes	Yes	Yes	Yes
Speaker (Watts)			2	2
Bag	No	Yes	Yes	Yes
Features				

Mobile



DS346



S316



DX325



X300

	DS346	S316	DX325	X300
Resolution	SVGA 800 x 600	SVGA 800 x 600	XGA 1024 x 768	XGA 1024 x 768
Brightness ¹ (Bright mode)	3000 ANSI Lumens	3200 ANSI Lumens	2600 ANSI Lumens	2800 ANSI Lumens
Contrast	18,000:1	20,000:1	15,000:1	18,000:1
Noise Level (Eco mode)	29dB	29dB	28dB	28dB
Weight (kg)	2.35	2.35	2.2	2.2
Lamp Life ² (hrs)	6500/6000/5000 Dynamic/Eco/Bright	5000 Bright	6500/6000/5000 Eco+/Dynamic/Bright	6500/6000/5000 Eco+/Dynamic/Bright
Dimensions (WxDxHmm)	314.6 x 223.6 x 101.7	315 x 224 x 102	286 x 192 x 84	286 x 192 x 84
Image Size			0.70 - 7.70m (27.49" - 303.12") Diagonal 4:3	0.70 - 7.70m (27.49" - 303.12") Diagonal 4:3
Throw Ratio	1.95 - 2.15:1	1.95 - 2.15:1	1.95 - 2.15:1	1.95 - 2.15:1
Zoom Type	1.1x Manual	1.1x Manual	1.1x Manual	1.1x Manual
Keystone Correction	± 40° Vertical	± 40° Vertical	± 40° Vertical	± 40° Vertical
Connections	HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), S-Video, Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RS232, USB Service	HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB/Wireless), S-Video, Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RS232, USB service	VGA (YPbPr/RGB), S-Video, Composite, Audio In 3.5mm, Audio Out, RS232	VGA (YPbPr/RGB), S-Video, Composite, Audio In 3.5mm, VGA Out, RS232
Optional Wireless	Yes	Yes	Yes	Yes
Speaker (Watts)	2	2	2	2
Bag	Yes	Yes	Yes	Yes
Features	Eco+, Up to 10,000 hours lamp life - Education Cycle		Eco+	Eco+

Mobile



	X313	DX345	DX346	X315
Resolution	XGA 1024 x 768	XGA 1024 x 768	XGA 1024 x 768	XGA 1024 x 768
Brightness ¹ (Bright mode)	3000 ANSI Lumens	3000 ANSI Lumens	3000 ANSI Lumens	3200 ANSI Lumens
Contrast	20,000:1	18,000:1	18,000:1	20,000:1
Noise Level (Eco mode)	26dB	29dB	29dB	29dB
Weight (kg)	2.5	2.35	2.35	2.35
Lamp Life ² (hrs)	7000/6500/6000/4500 Eco+/Dynamic/Eco/Bright	5000 Bright	5000 Bright	5000 Bright
Dimensions (WxDxHmm)	316 x 224 x 124	315 x 224 x 102	315 x 224 x 102	315 x 224 x 102
Image Size	0.69 - 7.62m (27.24" - 300.04") Diagonal 4:3			
Throw Ratio	1.97 - 2.17:1	1.95 - 2.15:1	1.95 - 2.15:1	1.95 - 2.15:1
Zoom Type	1.1x Manual	1.1x Manual	1.1x Manual	1.1x Manual
Keystone Correction	± 40° Vertical	± 40° Vertical	± 40° Vertical	± 40° Vertical
Connections	HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), S-Video, Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RS232, USB remote mouse/service, USB-A Power	2 x VGA (YPbPr/RGB/Wireless), S-Video, Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RS232, USB service	HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB/Wireless), S-Video, Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RS232, USB service	2 x VGA (YPbPr/RGB/Wireless), S-Video, Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RS232, USB service
Optional Wireless	Yes	Yes	Yes	Yes
Speaker (Watts)	2	2	2	2
Bag	Yes	Yes	Yes	Yes
Features				

Mobile



	X316	W300	W311	W316
Resolution	XGA 1024 x 768	WXGA 1280 x 800	WXGA 1280 x 800	WXGA 1280 x 800
Brightness ¹ (Bright mode)	3200 ANSI Lumens	3000 ANSI Lumens	3200 ANSI Lumens	3400 ANSI Lumens
Contrast	20,000:1	18,000:1	20,000:1	20,000:1
Noise Level (Eco mode)	29dB	29dB	28dB	29dB
Weight (kg)	2.35	2.35	2	2.35
Lamp Life ² (hrs)	5000 Bright	5000 Bright	7000/6500/6000/5000 Eco+/Dynamic/Eco/Bright	5000 Bright
Dimensions (WxDxHmm)	315 x 224 x 102	315 x 224 x 102	287 x 193 x 113	315 x 224 x 102
Image Size			0.77 - 9.63m (30.44" - 379") Diagonal 16:10	
Throw Ratio	1.95 - 2.15:1	1.55 - 1.7:1	1.47 - 1.83:1	1.55 - 1.7:1
Zoom Type	1.1x Manual	1.1x Manual	1.2x Manual	1.1x Manual
Keystone Correction	± 40° Vertical	± 40° Vertical	± 40° Vertical	± 40° Vertical
Connections	HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), S-Video, Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RS232, USB service	HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), S-Video, Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RS232, USB service	2x HDMI (1.4a 3D support), Audio Out 3.5mm, RS232, USB remote mouse/service, USB-A Power	HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), S-Video, Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RS232, USB service
Optional Wireless	Yes	Yes	Yes	Yes
Speaker (Watts)	2	2	2	2
Bag	Yes	Yes	Yes	Yes
Features				

Mobile



	W313	W312	X312	W310
Resolution	WXGA 1280 x 800	WXGA 1280 x 800	XGA 1024 x 768	WXGA 1280 x 800
Brightness ¹ (Bright mode)	3200 ANSI Lumens	3200 ANSI Lumens	3200 ANSI Lumens	3000 ANSI Lumens
Contrast	20,000:1	20,000:1	20,000:1	20,000:1
Noise Level (Eco mode)	26dB	29dB	29dB	29dB
Weight (kg)	2.5	2.35	2.35	2.35
Lamp Life ² (hrs)	7000/6500/6000/4500 Eco+/Dynamic/Eco/Bright	5000 Bright	5000 Bright	5000 Bright
Dimensions (WxDxHmm)	316 x 224 x 124	315 x 224 x 102	315 x 224 x 102	315 x 224 x 102
Image Size	0.77 - 9.63m (30.44" - 379") Diagonal 16:10		0.70 - 7.62m (22.9" - 300") Diagonal 4:3	
Throw Ratio	1.47 - 1.83:1	1.55 - 1.7:1	1.95 - 2.15:1	1.55 - 1.7:1
Zoom Type	1.2x Manual	1.1x Manual	1.1x Manual	1.1x Manual
Keystone Correction	± 40° Vertical	± 40° Vertical	± 40° Vertical	± 40° Vertical
Connections	HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), S-Video, Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RS232, USB remote mouse/service, USB-A Power	HDMI (1.4a 3D support), VGA (YPbPr/RGB), S-Video, Composite, Audio In 3.5mm, Audio Out 3.5mm, RS232, USB service	HDMI (1.4a 3D support), VGA (YPbPr/RGB), S-Video, Composite, Audio In 3.5mm, Audio Out 3.5mm, RS232, USB service	HDMI (1.4a 3D support), VGA (YPbPr/RGB), S-Video, Composite, Audio In 3.5mm, Audio Out 3.5mm, RS232, USB service
Optional Wireless	Yes	Yes	Yes	Yes
Speaker (Watts)	2	2	2	2
Bag	Yes	Yes	Yes	Yes
Features				

Mobile

Desktop/Install



DX342



FX5200



EX631



EX632

Resolution	XGA 1024 x 768	XGA 1024 x 768	XGA 1024 x 768	XGA 1024 x 768
Brightness ¹ (Bright mode)	3000 ANSI Lumens	3300 ANSI Lumens	3500 ANSI Lumens	3500 ANSI Lumens
Contrast	18,000:1	8000:1	10,000:1	3000:1
Noise Level (Eco mode)	29dB	29dB	29dB	25dB
Weight (kg)	2.35	2.2	2.2	2.8
Lamp Life ² (hrs)	5000 Bright	3500 Bright	6000/5000/3500 Eco+/Eco/Bright	6000 Bright
Dimensions (WxDxHmm)	315 x 224 x 102	280 x 230 x 77	280 x 230 x 77	318 x 224 x 102
Image Size	0.70 - 7.62m (22.9" - 300") Diagonal 4:3	0.69 - 6.35m (27.21" to 249.81") Diagonal 4:3	0.69 - 6.35m (27.21" to 249.81") Diagonal 4:3	0.78 - 9.38m (30.79" - 369.43") Diagonal 4:3
Throw Ratio	1.95 - 2.15:1	1.97 - 2.17:1	1.97 - 2.17:1	1.6 - 1.9:1
Zoom Type	1.1x Manual	1.1x Manual	1.1x Manual	1.2x Manual
Keystone Correction	± 40° Vertical	± 40° Vertical	± 40° Vertical	± 20° Vertical
Connections	HDMI (1.4a 3D support), VGA (YPbPr/RGB), S-Video, Composite, Audio In 3.5mm, Audio Out 3.5mm, RS232, USB service	HDMI, 2 x VGA (RGB/YPbPr/Wireless), S-Video, Composite, Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RJ45, RS232, USB remote mouse/service	HDMI, 2 x VGA (RGB/YPbPr/Wireless), S-Video, Composite, Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RJ45, RS232, USB remote mouse/service	HDMI, 2 x VGA (RGB/YPbPr), S-Video, Composite, Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RJ45, RS232
Optional Wireless	Yes	Yes	Yes	No
Speaker (Watts)	2	10	10	10
Bag	Yes	Yes	Yes	No
Features				

Desktop/Install



EX400



W350



X401



W351

Resolution	XGA 1024 x 768	WXGA 1280 x 800	XGA 1024 x 768	WXGA 1280 x 800
Brightness ¹ (Bright mode)	3700 ANSI Lumens	3600 ANSI Lumens	4000 ANSI Lumens	3800 ANSI Lumens
Contrast	15,000:1	18,000:1	15,000:1	20,000:1
Noise Level (Eco mode)	29dB	29dB	29dB	29dB
Weight (kg)	2.04	2.57	3.23	2.57
Lamp Life ² (hrs)	6000/3500 Eco/Bright	4000 Bright	7000/4000/3000 Eco+/Eco/Bright	4000 Bright
Dimensions (WxDxHmm)	288 x 220 x 86	315 x 224 x 102	324 x 234 x 97	315 x 224 x 102
Image Size	0.78 - 9.38m (30.79" - 369.43") Diagonal 4:3		0.78 - 9.38m (30.79" - 369.43") Diagonal 4:3	
Throw Ratio	1.6 - 1.92:1	1.55 - 1.7:1	1.6 - 1.92:1	1.55 - 1.7:1
Zoom Type	1.2x Manual	1.1x Manual	1.2x Manual	1.1x Manual
Keystone Correction	± 40° Vertical	± 40° Vertical	± 40° Vertical	± 40° Vertical
Connections	HDMI, 2 x VGA (RGB/YPbPr), Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RJ45, RS232, USB remote mouse/service, USB-A reader/wireless, USB display, Mic In	HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), S-Video, Composite, 2 x Audio In 3.5mm, Mic in (shared with Audio in 2), Audio Out 3.5mm, VGA Out, RS232, USB mouse/service, RJ45	HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB/Wireless), Composite, 3 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RJ45, RS232, USB remote mouse/service, 12V trigger, 3D-Sync	HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), S-Video, Composite, 2 x Audio In 3.5mm, Mic in (shared with Audio in 2), Audio Out 3.5mm, VGA Out, RS232, USB mouse/service, RJ45
Optional Wireless	Yes	Yes	Yes	Yes
Speaker (Watts)	10	10	16	10
Bag	Yes	Yes	Yes	Yes
Features				

Desktop/Install



X600



EW631



EW400



W402

Resolution	XGA 1024 x 768	WXGA 1280 x 800	WXGA 1280 x 800	WXGA 1280 x 800
Brightness ¹ (Bright mode)	6000 ANSI Lumens	3500 ANSI Lumens	4000 ANSI Lumens	4500 ANSI Lumens
Contrast	10,000:1	10,000:1	15,000:1	20,000:1
Noise Level (Eco mode)	28dB	29dB	29dB	31dB
Weight (kg)	3.6	2.2	2.04	2.57
Lamp Life ² (hrs)	2500 Bright	6000/5000/3500 Eco+/Eco/Bright	6000/3500 Eco/Bright	3000 Bright
Dimensions (WxDxHmm)	326 x 254 x 104	280 x 230 x 77	288 x 220 x 86	315 x 224 x 102
Image Size	0.71 - 8.34m (28.01" - 328.38") Diagonal 4:3	0.78 - 8.02m (30.78" to 315.83") Diagonal 16:10	0.92 - 9.21m (36.18" - 362.71") Diagonal 16:10	
Throw Ratio	1.8 - 2.1:1	1.47 - 1.81:1	1.28 - 1.54:1	1.28 - 1.536:1
Zoom Type	1.15x Manual	1.2x Manual	1.2x Manual	1.2x Manual
Keystone Correction	± 30° Vertical	± 40° Vertical	± 40° Vertical	± 40° Vertical
Connections	2 x HDMI, DisplayPort, 2 x VGA (RGB/YPbPr), S-Video, Composite, 2 x Audio In (RCA/3.5mm), Audio Out 3.5mm 3.5mm, VGA Out, RJ45, RS232, USB service, 12V trigger, 3D-Sync	HDMI, 2 x VGA (RGB/YPbPr/Wireless), S-Video, Composite, Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RJ45, RS232, USB remote mouse/service	HDMI, 2 x VGA (RGB/YPbPr), Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RJ45, RS232, USB remote mouse/service, USB-A reader/wireless, USB display, Mic In	HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), S-Video, Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RS232, USB mouse/service, RJ45
Optional Wireless	Yes	Yes	Yes	Yes
Speaker (Watts)	3	10	10	10
Bag	Yes	Yes	Yes	Yes
Features		Eco+, Crestron RoomView®		

Desktop/Install

Short throw



W401

X402

W415

ZX212ST

Resolution	WXGA 1280 x 800	XGA 1024 x 768	WXGA 1280 x 800	XGA 1024 x 768
Brightness ¹ (Bright mode)	4500 ANSI Lumens	4200 ANSI Lumens	4500 ANSI Lumens	2300 ANSI Lumens
Contrast	15,000:1	20,000:1	15,000:1	100,000:1
Noise Level (Eco mode)	29dB	31dB	32dB	28dB
Weight (kg)	3.23	2.57	3.4	4.5
Lamp Life ² (hrs)	7000/4000/3000 Eco+/Eco/Bright	3000 Bright	7000/4000/3000 Eco+/Eco/Bright	20,000 (LED+ Life) Bright
Dimensions (WxDxHmm)	324 x 234 x 97	315 x 224 x 102	286 x 266 x 124	321 x 240 x 95
Image Size	0.92 - 9.19m (36.3" - 362") Diagonal 16:10		0.76 - 7.62m (30" - 300") Diagonal 16:10	0.99 - 4.89m (39.3" - 196.5") Diagonal 4:3
Throw Ratio	1.28 - 1.54:1	1.6 - 1.92:1	1.46 - 2.2:1, Offset: 112%~127%	0.626:1
Zoom Type	1.2x Manual	1.2x Manual	1.5x Manual	Fixed
Keystone Correction	± 40° Vertical	± 40° Vertical	± 40° Vertical	± 40° Vertical
Connections	HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB/Wireless), Composite, 3 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RJ45, RS232, USB remote mouse/service, 12V trigger, 3D-Sync	HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), S-Video, Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RS232, USB mouse/service, RJ45	HDMI, DisplayPort, 2x VGA (RGB/YPbPr), S-Video, Composite, 2 x Audio In (RCA/3.5mm), Audio Out 3.5mm, VGA Out, RJ45, RS232, USB service, 12V trigger	HDMI, VGA (RGB/YPbPr/SCART), S-Video, Composite, Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RJ45, RS232, USB remote mouse, USB-A reader/wireless, USB display, SD card slot
Optional Wireless	Yes	Yes	Yes	Yes
Speaker (Watts)	16	10	10	10
Bag	Yes	Yes	Yes	No
Features				

Short throw



ZW212ST

X305ST

X306ST

W305ST

Resolution	WXGA 1280 x 800	XGA 1024 x 768	XGA 1024 x 768	WXGA 1280 x 800
Brightness ¹ (Bright mode)	2500 ANSI Lumens	3000 ANSI Lumens	3200 ANSI Lumens	3200 ANSI Lumens
Contrast	100,000:1	18,000:1	18,000:1	18,000:1
Noise Level (Eco mode)	28dB	29dB	30dB	29dB
Weight (kg)	4.5	2.55	2.8	2.55
Lamp Life ² (hrs)	20,000 (LED+ Life) Bright	6000/4500 Eco/Bright	6000/5000/3500 Eco+/Eco/Bright	6000/4500 Eco/Bright
Dimensions (WxDxHmm)	321 x 240 x 95	288 x 220 x 86	288 x 220 x 86	288 x 220 x 86
Image Size	1.13 - 5.66m (44.6" - 222.8") Diagonal 16:10	1.00 - 5.0m (39.34" - 196.71") Diagonal 4:3	1.00 - 5.0m (39.34" - 196.71") Diagonal 4:3	1.13 - 5.67m (44.64" - 223.21") Diagonal 16:10
Throw Ratio	0.52:1	0.626:1	0.626:1	0.52:1
Zoom Type	Fixed	Fixed	Fixed	Fixed
Keystone Correction	± 40° Vertical	± 40° Vertical	± 40° Vertical	± 40° Vertical
Connections	HDMI, VGA (RGB/YPbPr/SCART), S-Video, Composite, Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RJ45, RS232, USB remote mouse, USB-A reader/wireless, USB display, SD card slot	HDMI (1.4a 3D support), 2 x VGA (RGB/YPbPr/Wireless), S-Video, Composite, Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RS232, USB remote mouse/service	HDMI (1.4a 3D support), 2 x VGA (RGB/YPbPr/Wireless), Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RJ45, RS232, USB remote mouse/service, Mic In	HDMI (1.4a 3D support), 2 x VGA (RGB/YPbPr/Wireless), S-Video, Composite, Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RS232, USB remote mouse/service
Optional Wireless	Yes	Yes	Yes	Yes
Speaker (Watts)	10	2	10	2
Bag	No	No	No	No
Features				

Short throw

Ultra Short throw



EH200ST

W316ST

X307USTi

W307UST

Resolution	1080p 1920 x 1080	WXGA 1280 x 800	XGA 1024 x 768	WXGA 1280 x 800
Brightness ¹ (Bright mode)	3000 ANSI Lumens	3600 ANSI Lumens	3300 ANSI Lumens	3500 ANSI Lumens
Contrast	20,000:1	20,000:1	15,000:1	15,000:1
Noise Level (Eco mode)	26dB	29dB	30dB	30dB
Weight (kg)	2.65	2.76	7.5	7.5
Lamp Life ² (hrs)	6500/6000/5000 Dynamic/Eco/Bright	4000 Bright	4000/3000 Eco/Bright	4000/3000 Eco/Bright
Dimensions (WxDxHmm)	315 x 224 x 114	315 x 224 x 102	357 x 367 x 231 (inc feet)	357 x 367 x 231 (inc feet)
Image Size	1.15 - 7.67m (45.3" - 300") Diagonal 16:9		1.53 - 2.56m (60.09" - 100.71") Diagonal 4:3	1.53 - 2.54m (60.09" - 100.02") Diagonal 16:10
Throw Ratio	0.49:1	0.524:1	0.43:1	0.35:1
Zoom Type	Fixed	Fixed	Fixed	Fixed
Keystone Correction	± 40° Vertical	± 40° Vertical	± 15° Vertical	± 15° Vertical
Connections	2 x HDMI (1.4a 3D support) + MHL v1.2, Audio Out 3.5mm, 12V trigger, 3D-Sync, USB service	HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), S-Video, Composite, 2 x Audio In 3.5mm, Mic in (shared with Audio in 2), Audio Out 3.5mm, VGA Out, RS232, USB mouse/service, RJ45	HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), S-Video, Composite, 4 x Audio In (RCA/3.5mm), Audio Out 3.5mm, VGA Out, RJ45, RS232, USB (interactive), 12V trigger, Mic In	HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), S-Video, Composite, 4 x Audio In (RCA/3.5mm), Audio Out 3.5mm, VGA Out, RJ45, RS232, USB (interactive), 12V trigger, Mic In
Optional Wireless	Yes	Yes	Yes	Yes
Speaker (Watts)	10	10	10	10
Bag	Yes	No	No	No
Features				

Ultra Short throw

High Resolution



X307UST



W307USTi



DH1009



DH1011

Resolution	XGA 1024 x 768	WXGA 1280 x 800	1080p 1920 x 1080	1080p 1920 x 1080
Brightness ¹ (Bright mode)	3300 ANSI Lumens	3500 ANSI Lumens	3200 ANSI Lumens	3500 ANSI Lumens
Contrast	15,000:1	15,000:1	20,000:1	13,000:1
Noise Level (Eco mode)	30dB	30dB	26dB	26dB
Weight (kg)	7.5	7.5	2.45	3.1
Lamp Life ² (hrs)	4000/3000 Eco/Bright	4000/3000 Eco/Bright	6500/6000/5000 Dynamic/Eco/Bright	6000/3500 Eco/Bright
Dimensions (WxDxHmm)	357 x 367 x 231 (inc feet)	357 x 367 x 231 (inc feet)	315 x 224 x 114	324 x 234 x 97
Image Size	1.53 – 2.56m (60.09" – 100.71") Diagonal 4:3	1.53 – 2.54m (60.09" – 100.02") Diagonal 16:10	1.06 - 7.67m (41.8" - 300") Diagonal 16:9	0.77 - 9.19m (30.15" - 361.75") Diagonal 16:9
Throw Ratio	0.43:1	0.35:1	1.48 - 1.62:1	1.5 - 1.8:1
Zoom Type	Fixed	Fixed	1.1x Manual	1.2x Manual
Keystone Correction	± 15° Vertical	± 15° Vertical	± 40° Vertical	± 40° Vertical
Connections	HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), S-Video, Composite, 4 x Audio In (RCA/3.5mm), Audio Out 3.5mm, VGA Out, RJ45, RS232, USB (interactivity), 12V trigger, Mic In	HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), S-Video, Composite, 4 x Audio In (RCA/3.5mm), Audio Out 3.5mm, VGA Out, RJ45, RS232, USB (interactive), 12V trigger, Mic In	2 x HDMI (1.4a 3D support) + MHL v 1.2, Audio Out 3.5mm, 12V trigger, 3D-Sync, USB service	2 x HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RS232, USB remote mouse/service, 3D-Sync
Optional Wireless	Yes	Yes	Yes	Yes
Speaker (Watts)	10	10	10	16
Bag	No	No	No	Yes
Features				

High Resolution



DH1017



EH300



EH415



EH500

Resolution	1080p 1920 x 1080	1080p 1920 x 1080	1080p 1920 x 1080	1080p 1920 x 1080
Brightness ¹ (Bright mode)	4200 ANSI Lumens	3800 ANSI Lumens	4200 ANSI Lumens	4700 ANSI Lumens
Contrast	10,000:1	15,000:1	12,000:1	10,000:1
Noise Level (Eco mode)	28dB	26dB	32dB	28dB
Weight (kg)	3.6	3.1	3.4	3.6
Lamp Life ² (hrs)	2500 Bright	6000/3500 Eco/Bright	7000/4000/3000 Eco+/Eco/Bright	2500 Bright
Dimensions (WxDxHmm)	326 x 254 x 104	324 x 234 x 97	286 x 266 x 124 (inc. feet)	326 x 254 x 104
Image Size	0.72 – 8.67m (28.41" – 341.28") Diagonal 16:9	0.77 - 9.19m (30.15" - 361.75") Diagonal 16:9	0.76 – 7.62m (30" - 300") Diagonal 16:9	0.72 – 8.67m (28.41" – 341.28") Diagonal 16:9
Throw Ratio	1.59 - 1.91:1	1.5 - 1.8:1	1.39 - 2.09:1, Offset: 115%~130%	1.59 - 1.91:1
Zoom Type	1.2x Manual	1.2x Manual	1.5x Manual	1.2x Manual
Keystone Correction	± 30° Vertical	± 40° Vertical	± 40° Vertical	± 30° Vertical
Connections	2 x HDMI, DisplayPort, 2 x VGA (RGB/YPbPr), S-Video, Composite, 2 x Audio In (RCA/3.5mm), Audio Out 3.5mm, VGA Out, RJ45, RS232, USB(Remote Mouse), +12v Trigger, 3D-Sync	2 x HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RS232, USB remote mouse/service, 3D-Sync	HDMI, DisplayPort, 2x VGA (RGB/YPbPr), S-Video, Composite, 2 x Audio In (RCA/3.5mm), Audio Out 3.5mm, VGA Out, RJ45, RS232, 12V trigger, USB service	2 x HDMI, DisplayPort, 2 x VGA (RGB/YPbPr), S-Video, Composite, 2 x Audio In (RCA/3.5mm), Audio Out 3.5mm, VGA Out, RJ45, RS232, USB(Remote Mouse), +12v Trigger, 3D-Sync
Optional Wireless	Yes	Yes	Yes	Yes
Speaker (Watts)	3	16	10	3
Bag	Yes	Yes	Yes	Yes
Features	Easy Lamp Replacement, Crestron RoomView®, PJ-Link			Easy Lamp Replacement, Crestron RoomView®, PJ-Link

High Resolution

Home



EH501



DH1008



H181X



H100

Resolution	1080p 1920 x 1080	1080p 1920 x 1080	WXGA 1280 x 800	WXGA 1280 x 800
Brightness ¹ (Bright mode)	5000 ANSI Lumens	2800 ANSI Lumens	3200 ANSI Lumens	3200 ANSI Lumens
Contrast	15,000:1	20,000:1	23,000:1	20,000:1
Noise Level (Eco mode)	27dB	26dB	28dB	26dB
Weight (kg)	4.5	2.45	2	2.21
Lamp Life ² (hrs)	4000/3000/2500 Eco+/Dynamic/Bright	6500/6000/5000 Dynamic/Eco/Bright	7000/6500/6000/5000 Eco+/Dynamic/Eco/Bright	6500/6000/4500 Eco+/Dynamic/Bright
Dimensions (WxDxHmm)	386 x 280 x 162	315 x 224 x 114	287 x 163 x 113	316 x 224 x 124
Image Size	0.76 – 7.62m (30" - 300") Diagonal 16:9	1.06 - 7.67m (41.8" - 300") Diagonal 16:9	0.77 – 9.63m (30.44" - 379") Diagonal 16:10	0.77m – 9.63m (30.44" - 379") Diagonal 16:10
Throw Ratio	1.37 - 2.05:1, Offset: 115%~135%	1.48 - 1.62:1	1.47 - 1.83:1	1.47 - 1.83:1
Zoom Type	1.5x Manual	1.1x Manual	1.2x Manual	1.2x Manual
Keystone Correction	± 40° Vertical	± 40° Vertical	± 40° Vertical	± 40° Vertical
Connections	HDMI, DVI-D, 2x VGA (RGB/YPbPr), S-Video, Composite, 3 x Audio In (RCA/3.5mm), Mic 3.5mm, Audio Out 3.5mm, VGA Out, RJ45, RS232, 2x USB-B (Remote Mouse/Display), 2x USB-A (Reader / WiFi), +12v Trigger	2 x HDMI (1.4a 3D support) + MHL v 1.2, Audio Out 3.5mm, 12V trigger, 3D-Sync, USB service	2x HDMI (1.4a 3D support), Audio Out 3.5mm, RS232, USB remote mouse/service, USB-A Power	HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), S-Video, Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RS232, USB (Remote Mouse)
Optional Wireless	Yes	Yes	Yes	No
Speaker (Watts)	30	10	2	2
Bag	No	No	No	No
Features	V-Lens Shift, PC-Free / LAN presentation, Crestron RoomView®, PJ-Link			Eco+

Home



H111



GT760



GT1070X



GT1080

	H111	GT760	GT1070X	GT1080
Resolution	WXGA 1280 x 800	WXGA 1280 x 800	1080p 1920 x 1080	1080p 1920 x 1080
Brightness ¹ (Bright mode)	3200 ANSI Lumens	3400 ANSI Lumens	2600 ANSI Lumens	2800 ANSI Lumens
Contrast	25,000:1	20,000:1	23,000:1	25,000:1
Noise Level (Eco mode)	26dB	29dB	26dB	26dB
Weight (kg)	2.5	2.55	2.65	2.65
Lamp Life ² (hrs)	7000/6500/6000/4500 Eco+/Dynamic/Eco/Bright	6000/4500 Eco/Bright	6500/6000/5000 Dynamic/Eco/Bright	6500/6000/5000 Dynamic/Eco/Bright
Dimensions (WxDxHmm)	316 x 224 x 124	288 x 220 x 86	315 x 224 x 114	315 x 224 x 114
Image Size	0.77 - 9.63m (30.44" - 379") Diagonal 16:10	1.13 - 5.67m (44.64" - 223.21") Diagonal 16:10	1.15 - 7.67m (45.3" - 300") Diagonal 16:9	1.15 - 7.67m (45.3" - 300") Diagonal 16:9
Throw Ratio	1.47 - 1.83:1	0.52:1	0.49:1	0.49:1
Zoom Type	1.2x Manual	Fixed	Fixed	Fixed
Keystone Correction	± 40° Vertical	± 40° Vertical	± 40° Vertical	± 40° Vertical
Connections	HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), S-Video, Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RS232, USB remote mouse/service, USB-A Power	HDMI (1.4a 3D support), 2 x VGA (RGB/YPbPr/Wireless), S-Video, Composite, Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RS232, USB (Remote Mouse)	2 x HDMI (1.4a 3D support) + MHL v1.2, Audio Out 3.5mm, 12V trigger, 3D-Sync, USB service	2 x HDMI (1.4a 3D support) + MHL v1.2, Audio Out 3.5mm, 12V trigger, 3D-Sync, USB service
Optional Wireless	Yes	No	Yes	Yes
Speaker (Watts)	2	2	10	10
Bag	No	Yes	Yes	Yes
Features		Gaming even in the smallest of rooms		

Home



HD141X



HD26



HD151X



HD36

	HD141X	HD26	HD151X	HD36
Resolution	1080p 1920 x 1080	1080p 1920 x 1080	1080p 1920 x 1080	1080p 1920 x 1080
Brightness ¹ (Bright mode)	3000 ANSI Lumens	3200 ANSI Lumens	2800 ANSI Lumens	3000 ANSI Lumens
Contrast	23,000:1	25,000:1	28,000:1	30,000:1
Noise Level (Eco mode)	26dB	26dB	27dB	27dB
Weight (kg)	2.45	2.45	4.5	4.5
Lamp Life ² (hrs)	6500/6000/5000 Dynamic/Eco/Bright	6500/6000/5000 Dynamic/Eco/Bright	2500 Bright	2500 Bright
Dimensions (WxDxHmm)	315 x 224 x 114	315 x 224 x 114	386 x 280 x 162	386 x 280 x 162
Image Size	1.06 - 7.67m (41.8" - 300") Diagonal 16:9	1.06 - 7.67m (41.8" - 300") Diagonal 16:9	0.76 - 7.67m (30" - 300") Diagonal 16:9	0.76 - 7.67m (30" - 300") Diagonal 16:9
Throw Ratio	1.48 - 1.62:1	1.48 - 1.62:1	1.37 - 2.05:1	1.37 - 2.05:1
Zoom Type	1.1x Manual	1.1x Manual	1.5x Manual	1.5x Manual
Keystone Correction	± 40° Vertical	± 40° Vertical	± 40° Vertical	± 40° Vertical
Connections	2 x HDMI (1.4a 3D support) + MHL v1.2, Audio Out 3.5mm, 12V trigger, 3D-Sync, USB service	2 x HDMI (1.4a 3D support) + MHL, Audio Out 3.5mm, 12V trigger, 3D-Sync, USB service	HDMI (1.4a 3D support), DVI-D, 2x VGA (RGB/YPbPr), S-Video, Composite, 3 x Audio In (RCA/3.5mm), Mic In, Audio Out 3.5mm, VGA Out, RS232, 2x USB remote mouse/service, USB-A Power, +12V trigger, 3D-sync	HDMI (1.4a 3D support), DVI-D, 2x VGA (RGB/YPbPr), S-Video, Composite, 3 x Audio In (RCA/3.5mm), Mic In, Audio Out 3.5mm, VGA Out, RS232, 2x USB remote mouse/service, USB-A Power, 12V trigger, 3D-sync
Optional Wireless	Yes	Yes	Yes	Yes
Speaker (Watts)	10	10	30	30
Bag	No	No	No	No
Features				

Home



HD161X



HD50



HD90



HD91

	HD161X	HD50	HD90	HD91
Resolution	1080p 1920 x 1080	1080p 1920 x 1080	1080p 1920 x 1080	1080p 1920 x 1080
Brightness ¹ (Bright mode)	2000 ANSI Lumens	2200 ANSI Lumens	1200 ANSI Lumens	1000 ANSI Lumens
Contrast	40,000:1	50,000:1	500,000:1	500,000:1
Noise Level (Eco mode)	29dB	29dB	23dB	23dB
Weight (kg)	3.8	3.8	6.5	7
Lamp Life ² (hrs)	3000 Bright	3000 Bright	20,000 (LED Life) Bright	20,000 (LED Life) Bright
Dimensions (WxDxHmm)	286 x 266 x 124	286 x 266 x 124	345 x 443 x 161.5mm (inc. feet)	345 x 443 x 161.5mm (inc. feet)
Image Size	0.76 - 7.67m (30" - 300") Diagonal 16:9	0.76 - 7.67m (30" - 300") Diagonal 16:9	0.76 - 7.67m (30" - 300") Diagonal 16:9	0.76 - 7.67m (30" - 300") Diagonal 16:9
Throw Ratio	1.39 - 2.09:1	1.39 - 2.09:1	1.22 - 1.52:1	1.5 - 2.89:1
Zoom Type	1.5x Manual	1.5x Manual	1.9x Manual	1.9x Manual
Keystone Correction	±30° Vertical	±30° Vertical	±30° Vertical	±30° Vertical
Connections	2 x HDMI (1.4a 3D support), VGA (RGB/YPbPr), Component, Composite, 3D-Sync, 12V trigger, RS232, USB-A Power, USB service	2 x HDMI (1.4a 3D support), VGA (RGB/YPbPr), Component, Composite, 3D-Sync, 12V trigger, RS232, USB-A Power, USB service	2 x HDMI (1.4a 3D support), VGA (RGB/YPbPr), Component, Composite, 3D-Sync, 2 x 12V trigger, RS232, USB-A Power, USB service	2 x HDMI (1.4a 3D support), VGA (RGB/YPbPr), Component, Composite, 3D-Sync, 2 x 12V trigger, RS232, USB-A Power, USB service
Optional Wireless	Yes	No	No	No
Speaker (Watts)	-	-	-	-
Bag	No	No	No	No
Features				

ProScene



EH500



W505



EH503



EH505

Resolution	1080p 1920 x 1080	WXGA 1280 x 800	1080p 1920 x 1080	WUXGA 1920 x 1200
Brightness ¹ (Bright mode)	4700 ANSI Lumens	5200 ANSI Lumens	5200 ANSI Lumens	5000 ANSI Lumens
Contrast	10,000:1	2000:1	2000:1	2000:1
Noise Level (Eco mode)	28dB	37dB	37dB	37dB
Weight (kg)	3.6	8.6 (without lens)	8.6 (without lens)	8.6 (without lens)
Lamp Life ² (hrs)	2500 Bright	1500 Bright	1500 Bright	1500 Bright
Dimensions (WxDxHmm)	326 x 254 x 104	431 x 341 x 183	431 x 341 x 183	431 x 341 x 183
Image Size	0.72 – 8.67m (28.41" - 341.28") Diagonal 16:9	Dependent upon lens	Dependent upon lens	Dependent upon lens
Throw Ratio	1.59 - 1.91:1	0.81 ~ 5.25 "Lens dependent"	0.77 ~ 5.0 "Lens dependent"	0.77 ~ 5.0 "Lens dependent"
Zoom Type	1.2x Manual	Dependent upon lens	Dependent upon lens	Dependent upon lens
Keystone Correction	± 30° Vertical	± 40° Vertical	± 40° Vertical	± 40° Vertical
Connections	2 x HDMI, Display Port, 2 x VGA (RGB/YpBPr), S-Video, Composite, 2 x Audio In (RCA/3.5mm), Audio Out 3.5mm 3.5mm, VGA Out, RJ45, RS232, USB (Remote Mouse), +12v Trigger, 3D-Sync	HDMI (1.4a 3D support), DVI-D, Display Port, 5BNC, Component Video, 2 x VGA (RGB/YpBPr), S-Video, Composite, 5 x Audio In (RCA/3.5mm), Audio Out 3.5mm, VGA Out, RJ45, RS232, USB (Remote Mouse), +12v Trigger, Wired Remote, 3D-Sync	HDMI (1.4a 3D support), DVI-D, Display Port, 5BNC, Component Video, 2 x VGA (RGB/YpBPr), S-Video, Composite, 5 x Audio In (RCA/3.5mm), Audio Out 3.5mm, VGA Out, RJ45, RS232, USB (Remote Mouse), +12v Trigger, Wired Remote, 3D-Sync	HDMI (1.4a 3D support), DVI-D, Display Port, 5BNC, Component Video, 2 x VGA (RGB/YpBPr), S-Video, Composite, 5 x Audio In (RCA/3.5mm), Audio Out 3.5mm, VGA Out, RJ45, RS232, USB (Remote Mouse), +12v Trigger, Wired Remote, 3D-Sync
Optional Wireless	Yes	Yes	Yes	Yes
Speaker (Watts)	3	3	3	3
Bag	Yes	No	No	No
Features	Easy Lamp Replacement, Crestron RoomView®, PJ-Link	"5 x Optional Lens [Short/STD/Long], Full Lens Shift, Crestron RoomView®, PJ-Link	"5 x Optional Lens [Short/STD/Long], Full Lens Shift, Crestron RoomView®, PJ-Link	"5 x Optional Lens [Short/STD/Long], Full Lens Shift, Crestron RoomView®, PJ-Link, Available in Black and White

ProScene



X605



W501



X501



EH501

Resolution	XGA 1024 x 768	WXGA 1280 x 800	XGA 1024 x 768	1080p 1920 x 1080
Brightness ¹ (Bright mode)	6000 ANSI Lumens	5000 ANSI Lumens	4500 ANSI Lumens	5000 ANSI Lumens
Contrast	2000:1	15,000:1	15,000:1	15,000:1
Noise Level (Eco mode)	37dB	27dB	27dB	27dB
Weight (kg)	8.6 (without lens)	4.5	4.5	4.5
Lamp Life ² (hrs)	3500 Bright	4000/3000/2500 Eco+/Dynamic/Bright	4000/3000/2500 Eco+/Dynamic/Bright	4000/3000/2500 Eco+/Dynamic/Bright
Dimensions (WxDxHmm)	431 x 341 x 183	386 x 280 x 162	386 x 280 x 162	386 x 280 x 162
Image Size	Dependent upon lens	0.76 – 7.62m (30" - 300") Diagonal 16:10	0.76 – 7.62m (30" - 300") Diagonal 4:3	0.76 – 7.62m (30" - 300") Diagonal 16:9
Throw Ratio	0.8 ~ 5.18 "Lens dependent"	1.45 - 2.17:1, Offset: 112%~132%	1.39 - 2.26:1, Offset: 115%	1.37 - 2.05:1, Offset: 115%~135%
Zoom Type	Dependent upon lens	1.5x Manual	1.6x Manual	1.5x Manual
Keystone Correction	± 30° Vertical	± 40° Vertical	± 40° Vertical	± 40° Vertical
Connections	HDMI (1.4a 3D support), DVI-D, Display Port, 5BNC, Component Video, 2 x VGA (RGB/YpBPr), S-Video, Composite, 5 x Audio In (RCA/3.5mm), Audio Out 3.5mm, VGA Out, RJ45, RS232, USB (Remote Mouse), +12v Trigger, Wired Remote, 3D-Sync	HDMI, DVI-D, 2x VGA (RGB/YpBPr), S-Video, Composite, 3 x Audio In (RCA/3.5mm), Mic 3.5mm, Audio Out 3.5mm, VGA Out, RJ45, RS232, 2x USB-B (Remote Mouse/Display), 2x USB-A (Reader / WiFi), +12v Trigger	HDMI, DVI-D, 2x VGA (RGB/YpBPr), S-Video, Composite, 3 x Audio In (RCA/3.5mm), Mic 3.5mm, Audio Out 3.5mm, VGA Out, RJ45, RS232, 2x USB-B (Remote Mouse/Display), 2x USB-A (Reader / WiFi), +12v Trigger	HDMI, DVI-D, 2x VGA (RGB/YpBPr), S-Video, Composite, 3 x Audio In (RCA/3.5mm), Mic 3.5mm, Audio Out 3.5mm, VGA Out, RJ45, RS232, 2x USB-B (Remote Mouse/Display), 2x USB-A (Reader / WiFi), +12v Trigger
Optional Wireless	Yes	Yes	Yes	Yes
Speaker (Watts)	3	30	30	30
Bag	No	No	No	No
Features	"5 x Optional Lens [Short/STD/Long], Full Lens Shift, Crestron RoomView®, PJ-Link	V.Lens Shift, PC-Free / LAN presentation, Crestron RoomView®, PJ-Link	V.Lens Shift, PC-Free / LAN presentation, Crestron RoomView®, PJ-Link	V.Lens Shift, PC-Free / LAN presentation, Crestron RoomView®, PJ-Link

ProScene



EH7700



12000L Simple Stacking



15000L Advanced Stacking



Geo Module BE-BWM01--

Resolution	WUXGA 1920 x 1200	WXGA 1280 x 800	WUXGA 1920 x 1200	1080p 1920 x 1080
Brightness ¹ (Bright mode)	7500 Centre Lumens using Bright colour wheel (Dual Lamp) / 7000 ANSI Lumens	12000 centre lumens using "Bright" mode settings	15000 centre lumens using "Bright" mode settings	
Contrast	5000:1	2000:1	2500:1	
Noise Level (Eco mode)	39dB			
Weight (kg)	24Kg (without lens)			
Lamp Life ² (hrs)	2500 Bright	3500 Bright	2500/2000 Bright	
Dimensions (WxDxHmm)	439 x 549 x 235			
Image Size	Dependent upon lens	Dependent upon lens	Dependent upon lens	
Throw Ratio	0.77 ~ 6.98 "Lens dependent"			
Zoom Type	Motorised	Dependent upon lens	Dependent upon lens	
Keystone Correction	Horizontal +20° / Vertical ±20°			
Connections	2 x HDMI, 5BNC, Component Video, 2 x VGA (YPbPr/RGB), S-Video, Composite, VGA Out, RJ45, RS232, +12v Tigger, Wired remote	HDMI, DVI-D, 5BNC, Component Video, 2 x VGA (YPbPr/RGB), S-Video, Composite, 3 x Audio In (RCA/Jack), Audio Out 3.5mm, VGA Out, RJ45, RS232, USB (Display), 2 x +12v Trigger, Wired remote, 3D Sync	HDMI, DVI-D, VGA Out, HDMI Out, RJ45	
Optional Wireless	No	Yes	No	No
Speaker (Watts)	-			
Bag	No	No	No	No
Features	5 x Optional Lens, Motorised Full Lens Shift, Mechanical Shutter, Crestron RoomView®, PJ-Link, Available in any colour, 360° Operation	3 x Optional Lens, Motorised Full Lens Shift, Crestron RoomView®, PJ-Link, Available in white, 360° Operation	5 x Optional Lens, Motorised Full Lens Shift, Crestron RoomView®, PJ-Link, Available in white, 360° Operation	

ProScene



HQView 320--

HQView 325--

HQView 520--

HQView 530--

Resolution	1080p 1920 x 1080	1080p 1920 x 1080	1080p 1920 x 1080	1080p 1920 x 1080
Brightness ¹ (Bright mode)	0 lumens		0 lumens	
Contrast				
Noise Level (Eco mode)				
Weight (kg)	1kg		1kg	
Lamp Life ² (hrs)				
Dimensions (WxDxHmm)				
Image Size				
Throw Ratio				
Zoom Type				
Keystone Correction				
Connections				
Optional Wireless		No		No
Speaker (Watts)				
Bag		No		No
Features				

ProScene



GB-200--

Resolution	1080p 1920 x 1080
Brightness ¹ (Bright mode)	
Contrast	
Noise Level (Eco mode)	
Weight (kg)	
Lamp Life ² (hrs)	
Dimensions (WxDxHmm)	
Image Size	
Throw Ratio	
Zoom Type	
Keystone Correction	
Connections	
Optional Wireless	No
Speaker (Watts)	
Bag	No
Features	



Optoma Europe Limited

42 Caxton Way, Watford Business Park,
Watford, Hertfordshire. WD18 8QZ
Tel: +44 (0) 1923 691800
Fax: +44 (0) 1923 691888

www.optoma.com



Copyright © 2014, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners.

Crestron®, the Crestron and RoomView® logo are registered trademarks of Crestron Electronics, Inc.

SRS® is a trademark of SRS Labs, Inc. WOW technology is incorporated under license from SRS Labs, Inc.

DLP®, BrilliantColor™ and the DLP logo are registered trademarks of Texas Instruments.

MHL, Mobile High-Definition Link and the MHL logo are trademarks or registered trademarks of the MHL, LLC.

¹Brightness will vary depending on the selected projector mode, environmental conditions and usage. As is common with all lamp based projectors, brightness will decrease over the lamp lifetime.

Regards. *The quoted LED brightness rating is based on the perceived equivalent ANSI lumen brightness when compared to a standard lamp projector. The LED brightness rating takes into account the Helmholtz-Kohrausch (HK) effect on the perceived brightness of colours. ²Typical lamp life achieved through testing. Will vary according to operational use and environment conditions. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated.

Touchboards

205 Westwood Ave, Long Branch, NJ 07740
Phone: 866-94 BOARDS (26273) / (732)-222-1511
Fax: (732)-222-7088 | E-mail: sales@touchboards.com