

# NEC V260

ORDER CODE: 60003176

NEC V260 Value Projector

**Get the Ultimate 3D Experience with a 3D ready DLP®Projector from NEC.** DLP®-Link™ technology allows 3D images to be projected with the aid of a single projector and active glasses without special screens, filters or emitters. The impression of 3D is created by the interaction with the active LCD shutter glasses. The easy to set up alternative to traditional 3D stereo projection.

An ideal solution for classrooms, (small) meeting rooms, cross-use (private/professional), mobile / cooperative applications.



## DELIVERING GENUINE BENEFITS

**3D ready** - future-proof DLP®-Link™ technology with 120Hz.

**Higher Efficiency, Lower Power Consumption** - full ErP compliance.

**Carbon Savings Meter** - to encourage the use of EcoMode.

**Long Lamp Life** - up to 5000 hrs.

**Green EcoMode Button** - on remote.

**Control and Monitoring** - via RS-232.

**Virtual Remote** - for direct PC control.



## OUTSTANDING PERFORMANCE

- **3D Ready** DLP®-link™ technology with 120Hz
- **Excellent and Brilliant Colours** - due to VIDi technology
- **Contrast** 2000:1
- **Quick Start** - Direct Power Off
- **7W Speaker**
- **Carbon Meter** - indicating the reduced amount of CO<sub>2</sub> emissions by the use of ECO mode



### SPECIAL CHARACTERISTICS

6-segment Colour Wheel; Auto Power Start; BrilliantColor™ and VIDi technology; Carbon Savings Meter; Funkce 3D ready; Long Life Lamp; Manual vertical Keystone Correction (V= ±40°); Off-Timer; Plug&Play; Quick-Start-/Direct-Power-Off Function; Virtual Remote for direct PC control



**Energy Efficiency:** Intelligent Power Management

**Ecological Materials:** 100% recyclable packaging;  
Downloadable manuals

**Ecological Standards:** ErP compliant

Technical Specification NEC V260	
<b>IMAGE</b>	
Displej	1 x 1,4 cm (0,55") DDR DMD Chip (Aspect Ratio 4:3)
Nativní rozlišení	800 x 600 (SVGA)
Jas <sup>1</sup>	2600 ANSI Lumen
Kontrastní poměr <sup>1</sup>	2000:1
Lampa	180 W DC
Životnost lampy [hod.]	3500 (5000 Eco Mode)
Projekční faktor	1,95 – 2,15 : 1
Projekční vzdálenost [m]	1,2 – 13
Screen Size (diagonal) [cm]	Minimum: 76; Maximum: 762
Zoom	Manual
Focus Adjustment	Manual
Podporované rozlišení	1024 x 768; 832 x 624; 800 x 600; 1280 x 720; 1280 x 960; 1280 x 1024; 1400 x 1050; 1600 x 1200; 1920 x 1080; 640 x 480
Frekvence	Horizontál: 15 – 100 kHz; Vertikal: 50 – 120 Hz
<b>CONNECTIVITY</b>	
ComputerAnalog	Vstup: 1 x Mini D-sub 15-pin, compatible to component (YPbPr); Výstup: 1 x Mini D-sub 15 pin
Video	Vstup: 1 x RCA
S-Video	Vstup: 1 x Mini DIN 4-pin
Audio	Vstup: 1 x 3.5 mm Stereo Mini Jack
PC Control	Vstup: 1 x D-Sub 9 pin (RS-232) (male)
Video signály	PAL; PAL60; NTSC; SECAM; NTSC 4.43; PAL-N; PAL-M
<b>REMOTE CONTROL</b>	
Dálkové ovládání	Source Select; Freeze-function; Keystone Correction; Auto Adjust; Aspect Ratio; Automatic Picture Adjustment; Magnify-function; Help-function; Lamp Mode Control; Picture Adjust; Audio Control; Picture Mute; Picture Mode; Nastavení ID
<b>ELECTRICAL</b>	
Napájení	100-240 V AC; 50 - 60 Hz
Spotřeba energie [W]	233 max.; 210 Eco Mode; 0,5 Stand-by Mode
<b>MECHANICAL</b>	
Rozměry (W x H x D) [mm]	310 x 95 x 247 (without lens and feet)
Hmotnost [kg]	2,5
Hlučnost ventilátoru [dB (A)]	31 / 34 (Eco / Normal)
<b>OPTIONAL ACCESSORIES</b>	
Volitelné příslušenství	Lamp (NP13LP); Universal Ceiling Mounts (NP01/02/03/04/05UCM); DLP-Link 3D Glasses (NP01GL); 3D Starter Kit (NP01SK3D)
<b>ERGONOMICS</b>	
Bezpečnost a ergonomie	CE; TÜV GS; ErP; RoHS
Speakers [W]	1 x 7 (mono)
<b>WARRANTY</b>	
Projektory	3 years pan-European service
Lamp	6 months, max. 1000 hrs
<b>SHIPPING CONTENT</b>	
Obsah balení	Projector; IR Remote Control (RD-443E); Mini D-SUB Signal Cable (1,8 m); Power Cord; Users Manual on CD-ROM; Quick Setup Guide; Lens Cap

<sup>1</sup>Compliance with ISO21118-2005