













Section 7 Voice Products

Plantronics	7.1–7.7
Voice over IP.	7.8–7.11
Analog Telephones	7.12–7.22
Digital Centrex Telephones	7.23–7.24
Wireless Telephones	7.25–7.29
Audioconferencing Telephones	7.30–7.32
Multimedia Videoconferencing	. 7.33–7.34
Key System	7.35
Cordless Telephones	7.36–7.37
ADA/TTY Telephones	7.38–7.39
Emergency/Door Telephones	7.40—7.49
Industrial Telephones	7.50—7.52
Valcom Paging	7.53–7.72
Bogen Paging	. 7.73–7.92
Talanhana Accassarias	7 03_7 00

Plantronics

Savi Wireless Professional Headset System

PLANTRONICS



FEATURES

- Integrates your PC and desk phone providing hands-free communications for conference calls, PC calls, Web conferencing and online presentations
- Voice-dedicated DECT 6.0 technology provides audio quality and the lowest probability of interference with other wireless devices
- Premium PC audio with improved call clarity and lifelike fidelity with wideband PC audio, that allows you to clearly hear your conversations every time
- Add an Electronic Hookswitch (EHS) cable or a HL10 handset lifter for remote call answer/end

Anixter No.	Vendor No.	Description
391297	SAVI W0100	Savi Office W0100, convertible
		headset (79956-01)
404601	SAVI W0101	Savi Office W0101, convertible headset,
		MOC optimized (82203-01)
391298	SAVI W0200	Savi Office W0200, over-the-ear
		headset (79957-01)
404602	SAVI W0201	Savi Office W0201, over-the-ear headset,
		MOC optimized (82204-01)
416696	SAVI W0300	Savi Office W0300, over-the-head headset,
		monaural (81794-01)
416698	SAVI W0350	Savi Office W0350, over-the-head headset,
		binaural (81802-01)

ACCESSORIES		
Anixter No.	Vendor No.	Description
403873	65116-02	Online indicator (works with HL10 only)
404119	HL10 SAVI	Savi Office HL10 handset lifter, straight plug (60961-35)
390532	APS-10	APS-10, Electronic Hookswitch, Siemens (37818-01)
390533	APA-20	APA-20, Electronic Hookswitch, Alcatel (37819-01)
390535	APC-40	APC-40, Electronic Hookswitch, Cisco (38350-01)
390536	APP-50	APP-50, Electronic Hookswitch, Polycom (38439-01)
421171	APV-62	APV-62, Electronic Hookswitch, Avaya (38734-01)

CS70N Wireless Professional Headset System

PLANTRONICS



FEATURES

- Talk hands-free, use a keyboard and mouse, lead a Webinar, reach for a file
- Voice-dedicated DECT 6.0 technology provides audio quality and lowest probability of interference
- Freedom of mobility with wireless range of up to 300 ft. from base
- Lightweight and stylish design for all-day comfort, making extended wearing effortless
- Features a noise-canceling microphone for crystal-clear conversations
- Remote call/answering capability
- Optimized for performance with IP desk phones
- Add an HL10 Handset Lifter for remote call answer/end

Anixter No.	Vendor No.	Description
346618	CS70N	CS70N wireless headset system (70450-06)
346619	CS70N/HL10	CS70N wireless headset system with
		HL10 handset lifter (70460-06)

ACCESSORIES

Anixter No.	Vendor No.	Description
403873	65116-02	Online indicator (works with HL10 only)
245211	HL10	HL10 handset lifter (60961-32)

CS55 Wireless Professional Headset System

PLANTRONICS



FEATURES

- Ideal for professionals in open environments that require mobility and superior sound quality
- Voice-dedicated DECT 6.0 technology, provides audio quality and lowest probability of interference
- Up to 10 hours of continuous talk time; full recharge in less than three hours
- Freedom of mobility with wireless range of up to 300 ft. from base
- Noise-canceling microphone for clear conversations

Continued on next page >>



Plantronics

(continued) CS55 Wireless Professional Headset System

- Convertible headset design for wearing over-the-head, over-the-ear or behind the head
- Add an HL10 Handset Lifter for remote call answer/end

Anixter No. Vendor No. Description

315841 CS55 CS55 wireless headset system (69700-06)
315947 CS55/HL10 CS55 wireless headset system with
HL10 handset lifter (69702-06)

ACCESSORIES

Anixter No. Vendor No. Description

403873 65116-02 Online indicator (works with HL10 only) **245211** HL10 HL10 handset lifter (60961-32)

SupraPlus Wireless Professional Headset System

PLANTRONICS



FEATURES

- Ideal for professionals who spend long hours on the phone and who want the stability of a monaural or binaural over-the-head headset
- Voice-dedicated DECT 6.0 technology provides audio quality and the lowest probability of interference with other wireless devices
- Up to 10 hours of continuous talk time
- Freedom of mobility with wireless range of up to 300 ft. from base
- Crystal-clear transmission with noise-canceling microphone for filtering out background sound
- Available in either monaural or binaural models with noise-canceling microphone
- Add an HL10 Handset Lifter for remote call answer/end

	mamadoc Emedi idi i	omoto can anomon, ona
Anixter No.	Vendor No.	Description
326275	CS351N	Monaural with noise-canceling microphone (70510-06)
326276	CS351N/HL10	Monaural with noise-canceling microphone with handset lifter (70530-06)
326288	CS361N	Binaural with noise-canceling microphone (70520-06)
326289	CS361N/HL10	Binaural with noise-canceling microphone with handset lifter (70540-06)

ACCESSORIES

Anixter No. Vendor No. Description

 403873
 65116-02
 Online indicator (works with HL10 only)

 245211
 HL10
 HL10 handset lifter (60961-32)

Savi 430 Wireless Headset System

PLANTRONICS



FEATURES

- Top quality wireless audio for the PC
- Superior DECT 6.0 technology
- Up to six hours of continuous talk time
- Freedom of mobility with wireless range of up to 300 ft. from base
- Advanced wideband audio using CAT-iq technology
- Plug-and-play installation
- Conference in up to three additional headsets
- Designed for all-day comfort

Anixter No. Vendor No. Description

 420289
 SAVI W430
 Savi W430, wireless USB headset (82396-01)

 420291
 SAVI W430-M
 Savi W430-M, wireless USB headset, MOC optimized (82397-01)

Voyager PRO Wireless Headset System

PLANTRONICS



- Unify and manage PC and mobile phone calls from one headset
- WindSmart technology, includes stainless steel mic screens, acoustic fabrics and electronic filters, aggressively blocks intrusive wind noise
- Advanced dual-mic AudiolQ2 technology cancels noise while retaining the unique sound of your voice
- Wideband for PC audio telephony

Anixter No.	Vendor No	Description
	VOYAGER PRO	Voyager PRO Bluetooth wireless
		headset (79800-01)
406591	SAVI WG200/B	Voyager PRO UC WG200/B,
		Bluetooth (38667-01)
406592	SAVI WG201/B	Voyager PRO UC WG201/B, Bluetooth,
		MOC optimized (38659-01)



Plantronics

Blackwire 200 Series USB Corded Headset

PLANTRONICS



FEATURES

- Remarkable audio quality, yet economically designed for enterprise Web deployment
- Wideband for best PC audio telephony
- Noise-canceling microphone filters out background noise
- Digital signal processing (DSP) provides more natural voice sound
- SoundGuard technology protects against instantaneous sound spikes
- Simple plug-and-play USB connection

Anixter No.	Vendor No.	Description
416522	BLACKWIRE C210	Monaural with noise-canceling microphone (80298-03)
416944	BLACKWIRE C220	Binaural with noise-canceling microphone (80299-03)
416523	BLACKWIRE C210-M	Monaural with noise-canceling microphone MOC optimized (80298-02)
416945	BLACKWIRE C220-M	Binaural with noise-canceling microphone, MOC optimized (80299-02)

Blackwire 420 Series USB Corded Headset

PLANTRONICS



FEATURES

- Engineered for Unified Communications
- Durable, portable design
- Folds flat and tucks into laptop bag
- Wideband for best PC audio telephony

- Noise-canceling microphone filters out background noise
- Full-range high fidelity stereo sound
- Simple plug-and-play USB connectivity

Anixter No. Vendor No. Description

416524 BLACKWIRE C420 Binaural with noise-canceling

microphone (82632-01)

416552 BLACKWIRE C420-M Binaural with noise-canceling microphone,

MOC optimized (82633-01)

Blackwire 600 Series USB Corded Headset

PLANTRONICS



FEATURES

- Premium audio and comfort optimized for PC communications
- · Engineered for all-day comfort
- Wideband for best PC audio telephony
- Noise-canceling microphone filters out background noise
- QuickAdjust boom for ideal microphone placement
- SoundGuard technology protects against instantaneous sound spikes
- · Audio optimized for voice and multimedia use

Anixter No.	Vendor No.	Description
416514	BLACKWIRE C610	Monaural with noise-canceling microphone (81964-41)
416515	BLACKWIRE C620	Binaural with noise-canceling microphone (81965-41)
416519	BLACKWIRE C610-M	Monaural with noise-canceling microphone, MOC optimized (81272-41)
416520	BLACKWIRE C620-M	Binaural with noise-canceling microphone,

MOC optimized (79930-41)



Plantronics

CT14 Telephone Headset System

PLANTRONICS



FEATURES

- Superior call clarity: DECT 6.0 technology offers up to a 300 ft. range and won't interfere with wireless networks or home appliances
- Talk up a storm: Up to 10 hours battery life/talk time; up to eight days standby
- Hands-free convenience: Ultra-compact "take with you" dial pad features an integrated belt/clothing clip
- Convertible wearing style: Noise-canceling headset can be worn over-the-head or over-the-ear
- Popular phone features: Caller ID/Call Waiting and one-touch voicemail access
- Flexibility and call control: Mute, volume and redial functions
- Robust phonebook: Stores 70 names/numbers and 30 Caller ID memory

Anixter No. Vendor No.

ndor No. Description

382371 CT14

Wireless headset system, convertible (80057-01)

Calisto P210-M USB Handset

PLANTRONICS



FEATURES

- USB handset brings the functionality of a phone to PC communications
- Standard phone features include dial pad, call answer/end, volume and mute
- Optimized for Microsoft Office Communicator 2007
- Traditional 12-key dial pad
- Familiar telephone design and functionality
- Simple USB plug-and-play connection

Anixter No. Vendor No. Description

416693 CALISTO P210-M USB handset, MOC optimized (57700.002)

Calisto P420-M USB Speakerphone

PLANTRONICS



FEATURES

- Transform any PC into a wideband audio speakerphone
- Compact and portable for in-office or on-the-road conferencing; protective carrying case included
- Simple, plug-and-play USB connection
- No additional AC power required

Anixter No. Vendor No. Description

416694 CALISTO P420 **416695** CALISTO P420USB speakerphone (82136-02)

CALISTO P420-M USB speakerphone,

MOC optimized (81402-02)

EncorePro Corded Professional Headset

PLANTRONICS



FEATURES

- Unprecedented comfort and clarity meets sleek design
- Nylon composite materials for featherweight comfort
- Reinforced, lightweight headband for strength and durability
- Sliding boom ensures precise microphone positioning
- Superior noise-canceling microphone
- Wideband audio ensures clear conversations

Anixter No. Vendor No. Description

380264 HW291N EncorePro monaural top with noise-canceling

microphone (78712-01)

381197 HW301N EncorePro binaural top with noise-canceling

microphone (78714-01)



Plantronics

DuoPro Corded Professional Headset

PLANTRONICS



FEATURES

- Very versatile headset, with best-in-class sound quality and ergonomic innovations for unsurpassed comfort
- Unique antitwist boom ensures perfect microphone placement
- Voice-optimized speaker sound
- Available with either Voice Tube or noise-canceling microphone

Anixter No. Vendor No. 241993 H171

Description

DuoPro convertible headset top (61121-01) DuoPro convertible headset top with noise-canceling microphone (61122-01)

TriStar Corded Professional Headset

H171N

PLANTRONICS

241994



FEATURES

- Designed for phone-intensive office professionals with unique fit requirements
- Exceptionally lightweight, over-the-ear style with three-point design for stability and comfort
- Four user-selectable earbuds for the perfect custom fit, even for eyeglass wearers
- Quick Disconnect lets you walk away from your phone while still wearing your headset
- 10 ft. coil cord and adjustable clothing clip
- Available with either noise-canceling or Voice Tube microphone

Anixter No. Vendor No. 168233 H81

Description

TriStar headset top (29408-01)

168232 H81N TriStar headset top with noise-canceling

microphone (40203-01)

Mirage Corded Professional Headset

PLANTRONICS



FEATURES

- Sculpted shape fits perfectly behind either ear and eliminates the need for
- External receiver rotates to rest lightly against ear
- Lightweight design that weighs less than an ounce
- Features quick disconnect
- Available with either Voice Tube or noise-canceling microphone

Anixter No. Vendor No.

Description

136994 H41 141126 H41N Mirage headset top (26089-11) Mirage headset top with noise-canceling

microphone (26851-02)

SupraPlus Corded Professional Headset

PLANTRONICS



FEATURES

- The highest level of performance for wideband VoIP communications
- Wideband audio for more natural sound with wideband telephones
- The standard in performance, reliability and all-day wearing comfort for contact center professionals
- Enhanced receive-side audio quality; intelligent flexible boom and stylish design provide greater headset flexibility
- Compatible with Plantronics amplifiers and USB-to-headset adapters
- Available in monaural or binaural models with either Voice Tube or noise-canceling microphone

SUPRAPLUS WIDEBAND

Anixter No.	Vendor No.	Description
391301	HW251	SupraPlus monaural (64336-31)
391302	HW261	SupraPlus binaural (64337-31)
343422	HW251N	SupraPlus monaural with noise-canceling microphone (64338-31)
343423	HW261N	SupraPlus binaural with noise-canceling microphone (64339-31)
391651	HW251N/DA-M	SupraPlus monaural with noise-canceling microphone, MOC optimized (81360-01)
391052	HW261N/DA-M	SupraPlus binaural with noise-canceling microphone, MOC optimized (80762-31)



Plantronics

Vista M22 Audio Processor

PLANTRONICS



FEATURES

- Connects Plantronics headsets to most single- or multi-line telephones
- Improves voice quality and maintains sound at a comfortable level
- Brings superior sound quality and acoustic protection to your telephone with Clearline audio technology
- Provides compatibility with those telephones that do not allow the direct connection of headsets

Anixter No. Vendor No.

338831 M22 Universal modular adapter (43596-40)

Description

141070 26503-01 AC power converter

VistaPlus AP15 Audio Processor

PLANTRONICS



FEATURES

- DSP-based audio processor promotes superior call clarity and accuracy
- AudioIQ keeps incoming calls at a consistent and comfortable listening level; along with echo cancellation that ensures superior transmit sound
- Compensates for background noise by automatically adjusting to changing noise levels
- Multiband compression improves intelligibility by connecting for signal loss anywhere in the bandwidth
- Engineered for compatibility with both single- and multi-line phones
- Ergonomically designed volume, headset/handset and mute controls

Anixter No. Vendor No. Description

391300 VISTAPLUS AP15 DSP-based audio processor (79960-01)

P10 Plug-Prong Adapter

PLANTRONICS



FEATURES

- Brings headset convenience to operator consoles, PBXs and most carbon ACDs
- Volume and automatic gain controls let you adjust incoming calls to a comfortable listening level
- Quick disconnect lets you walk away from your phone while still wearing your headset
- 10 ft. coil cord
- Works with any Plantronics H-Series headset

Anixter No. Vendor No. Description

 136999
 P10
 Plug-prong adapter (29362-01)

 137000
 P10H
 Plug-prong adapter with high gain (29362-02)

DA Series Audio Processors

PLANTRONICS



- · USB to headset adapter
- · Works with any Plantronics professional headset
- VoIP quality enhanced by echo suppression feature*
- Audio volume stays consistent with equalizing Call Clarity*
- Easy call control with inline volume and mute on DA60
- Loud transmissions suppressed by built-in sound guard*
- Effortless installation via USB plug-and-play
- * DA60 and DA55 models only

	,	
Anixter No.	Vendor No.	Description
275858	DA60	Superior audio quality and
		control (63725-01)
315519	DA55	Digitally enhanced audio quality (63725-03)
362678	DA45	Exceptional audio performance (77559-31)
321729	DA40	Affordable, enterprise-class quality (71800-41)



Plantronics

HL10 Handset Lifter

PLANTRONICS



FEATURES

- Automatically lifts handset from and returns it to the cradle
- Enables remote call or one-touch call answer/end with your Plantronics headset
- Remote ring detection
- Works with all Plantronics professional wireless headset systems
- Compatible with most standard desktop phones

Compatible i	men moot otamaara (acontrop bilonion
Anixter No.	Vendor No.	Description
245211	HL10	HL10 handset lifter (60961-32)
412294	SAVI HL10	Savi HL10 handset lifter, straight plug (60961-35)
240655	61578-01	Replacement mounting tape

Electronic Hookswitch (EHS) Cable

PLANTRONICS



FFATURES

- Use an EHS cable instead of a HL10 handset lifter to seamlessly connect a desktop handset to a Savi office headset system, CS family and the Voyager 510S headset
- Answer and end calls from up to 300 feet away
- Freedom to move about the office and multi-task
- · Connects with one simple step

FOR SAVI SERIES

TOTA GATT GETTLES		
Anixter No.	Vendor No.	Description
390532	APS-10	APS-10, Electronic Hookswitch,
		Siemens (37818-01)
390533	APA-20	APA-20, Electronic Hookswitch,
		Alcatel (37819-01)
390535	APC-40	APC-40, Electronic Hookswitch,
		Cisco (38350-01)

Anixter No.	Vendor No.	Description
390536	APP-50	APP-50, Electronic Hookswitch,
421171	APV-62	Polycom (38439-01) APV-62, Electronic Hookswitch, Avaya (38734-01)
FOR CS WIRE	LESS SERIES	
Anixter No.	Vendor No.	Description
372645	APC-4	APC-4, Electronics Hookswitch, Cisco (37978-01)
374838	APP-5	APP-5, Electronics Hookswitch, Polycom (38438-01)

Headset Accessories

PLANTRONICS

183538

042572

273144

10757-00

A10-16-S1 U.S.

40705-01

Anixter No. Vendor No.

		minaconomi, con a cirp, can cacinonic
183533	40704-01	Supra value pack includes: voice tube, cord clip, ear cushions
HEADSET ACC	CESSORIES	
Anixter No.	Vendor No.	Description
097725	15729-05	Encore/Supra standard foam ear cushions
097724	19025-01	Encore/Supra leatherette ear cushions
171941	29960-01	Tristar/Encore replacement voice tube
175169	29955-01	Tristar small ear softip
175167	29955-02	Tristar large ear softip
175166	29955-03	Tristar Bell tip, small with cushions
175162	29955-04	Tristar Bell tip, large with cushions
136647	24316-01	Universal windscreen for NC headsets
152704	06439-20	Supra/Starset clothing clip
183540	17590-03	Supra 3/4 replacement headband, black
097731	17593-01	Supra/Starset/Mirage replacement voice tube
137149	25640-01	Starset single versatip earpiece
031524	06448-00	Starset eartip kit, includes all sizes
183543	29814-01	Freehand circular ear cushions, six
177995	40265-03	SP-06/CT-460 foam ear cushions, black
139054	27708-01	Quick disconnect inline mute switch for P10 and P10H bottoms
183539	40974-01	Standard M10 to telephone cable, male to male modular plug
141070	26503-01	AC power converter
126265	18709-01	Modular to 2-prong adapter
166827	26716-01	Standard coil cable, quick disconnect to male modular plug
149049	27019-03	Supervisor inline in. Y adapter cable

Background noise suppressor

Cable, adapter (66268-02)

Description

Supra noise-canceling value pack includes: windscreen, cord clip, ear cushions

Voice over IP

SoundPoint IP 450 Telephone

POLYCOM



The SoundPoint IP 450 desktop phone is designed to bring advanced telephony features and applications to office workers handling a moderate volume of calls.

FFATURES

- Application: small office, home office or cubicle
- Up to three lines with up to two concurrent calls per line
- Revolutionary voice quality with Polycom HD Voice
- High-resolution backlit LCD with support of multiple languages and Asian characters
- Built-in XHTML microbrowser for third-party applications
- Fully enabled to run the Polycom Productivity Suite

Anixter No. Vendor No. Description

384096 2200-12450-001 Three-line SIP with Polycom HD Voice, black

SoundPoint IP 550 Telephone

POLYCOM



The SoundPoint IP 550 is a cutting-edge SIP phone that delivers calls of unprecedented richness and clarity and supports a range of cutting edge features.

FEATURES

- Application: manager or professional office
- Up to four lines with up to two concurrent calls per line
- Revolutionary voice quality with Polycom HD Voice technology
- Cutting-edge SIP features
- Backlit, easy-to-read LCD with support of Asian characters
- Interoperability with leading SIP-based IP PBX and Softswitch platforms

Anixter No. Vendor No. Description

348964 2200-12550-001 Four-line SIP with Polycom HD Voice, black

SoundPoint IP 650 Telephone

POLYCOM



The SoundPoint IP 650 is designed to appeal to both executive users who require advanced features and applications as well as attendants who need multiple line support.

FEATURES

- Applications: executive office or attendants
- Up to six lines (standalone mode) or 34 lines (expansion module)
- Revolutionary voice quality with Polycom HD Voice technology
- Cutting-edge SIP features and applications
- Expandable to support three Polycom SoundPoint IP expansion modules
- Interoperable with leading SIP-based IP PBX and Softswitch platforms
- USB port for future applications

Anixter No. Vendor No. Description

342841 2200-12651-001 Six-line SIP with Polycom HD Voice, black

9480i CT and 9480i CT IP Screenphones

AASTRA TELECOM



The 9480i is a multiline IP-based screenphone for the desktop. It is a flexible solution that is designed to integrate with IP Centrex as well as a wide variety of IP-based telephony systems. The 9480i offers an extended feature set, advanced security and interoperability through a new internal design that supports Aastra R2.x software - the same software that supports the Aastra 67xi series of IP telephones. The 9480i CT includes a cordless telephone for mobility workers.

- 9480i and 9480i CT base:
 - Eight-line backlit display, up to nine-call appearance lines
 - Extensive storage capacity for personal directory, callers log and redial list
 - Tightly integrates with a wide variety of IP telephony systems
 - Full-duplex speakerphone with excellent voice clarity, XML browser support
 - Firmware upgrades can be downloaded and installed in the field
 - Dual 10/100 Mbps switched Ethernet ports
 - Headset-compatible



Voice over IP

- Four navigational kevs
- Programmable keys and predefined keys for common call functions
- 9480i CT cordless handset:
- 2.4 GHz frequency hopped spread spectrum technology
- Five-line backlit display
- Coverage of up to 300,000 square feet
- Two softkeys for tight integration to base unit features
- Programmable function key supports up to 14 functions
- AC wall adapter for charging stand

Anixter No. Vendor No. Description 374834 94801 Charcoal

374835 94801 CT Charcoal, cordless handset

9143i IP Telephone

AASTRA TELECOM



The 9143i is an advanced, fully featured multiline IP telephone that takes full advantage of VoIP technology by offering a flexible, interoperable solution at an affordable price. The 9143i offers an extended feature set, advanced security and interoperability through a new internal design that supports the more powerful Aastra R2.x software - the same software that supports the Aastra 67xi Series of IP telephones.

FEATURES

- Three-line backlit display
- Enhanced call management, large storage for personal directory, callers log and regial list
- Tightly integrates with a wide variety of IP telephony systems
- High-performance speakerphone
- Firmware can be upgraded in the field
- Built in 10/100 Mbps Ethernet ports
- Headset-compatible
- Extensible Markup Language (XML) support
- Multiple SIP proxy support
- Seven programmable keys with LEDs

Anixter No. Vendor No. Description

374781 9143I Fully featured multiline SIP, charcoal,

extended feature set

67xi Series VoIP Telephones

AASTRA TELECOM

FEATURES

- XML browser Improved productivity and convergence via access to custom XML applications and information
- Enhanced call management Large storage for personal directory, callers log and redial list. Multiple navigational keys and configurable speed dial key with LFD indicators
- Tight integration Fully interoperable with leading IP-PBX platforms for easy deployment
- Multiple line/call appearance lights Support up to nine simultaneous calls and juggle multiple calls easily with a single press of a button (available on most models)
- Shared call appearances Shared calls allow you to place a call on hold at one set and pick it up at another set (available on most models)
- Remarkable audio Quality full-duplex speakerphone with excellent voice clarity/delivery and headset support options. Mulitcast group paging support. Intercom with auto-answer
- Scalability Expand the total number of programmable keys via 36-keys paper expansion module or 60-keys LCD expansion module; scalable up to 180 keys via three modules (available with most models)
- Firmware upgrades can be downloaded and installed in the field
- Less wiring Built-in dual 10/100 Mbps switched Ethernet ports let you share a connection with your computer; inline power support eliminates the need for a power adapter (available with most models)

6730I VOIP TELEPHONES



The 6730i is an entry level VoIP telephone with a slimmer design and up to six call appearance lines. The 6731i has the features of the 6730i, but with the additional features of PoE capable and two Ethernet ports.

Anixter No.	Vendor No.	Description
396409	67301	Charcoal, AC wall adapter included
396413	6731I-01	Charcoal, PoE powered, AC wall adapter not included
423735	6731I-02	Charcoal, PoE powered, AC wall adapter included

67391 VOIP TELEPHONE

The 6739i is a feature-rich IP telephone that offers a large 5.7 in. full color LCD screen. It has built-in dual Gigabit Ethernet support, is Bluetooth headset compatible, and supports PoE. An optional power adapter is sold separately. It also supports the M670i and M675i expansion modules.

Anixter No. Vendor No. Description

406207 6739I Executive-level featured multiline SIP

Continued on next page >>



Voice over IP

(continued) 67xi Series VoIP Telephones

6753I VOIP TELEPHONE



The 6753i is a featured, expandable VoIP telephone. With up to nine call appearance lines, it also supports up to three M670i expansion modules.

Anixter No. Vendor No.

Description

353968 6753I Featu

Featured multiline SIP, charcoal

6755I VOIP TELEPHONE



The 6755i is an advanced featured, expandable VoIP telephone that has a larger display screen. It also supports up to three M670i or M675i expansion modules.

Anixter No. Vendor No.

Description

353981 6755I

Advanced featured multiline SIP, charcoal

6757I AND 6757I CT VOIP TELEPHONES



The 6757i and 6757i CT are fully featured, expandable VoIP telephones. They offer the largest display screen in the 67xi line. They also support up to three M670i or M675i expansion modules. The CT model includes a cordless handset and charger base, with 2.4 GHz frequency Hopped Spread Spectrum. The cordless handset integrates with base phone features, offering: a five-line backlit display, vibration alerter, LED indicators and headset connector.

Anixter No. Vendor No.

Description

353988 6757I **353994** 6757ICT

Fully featured multiline SIP, charcoal Fully featured multiline SIP with cordless

handset, charcoal

67xi Series Expansion Modules

AASTRA TELECOM



The 67xi Series expansion modules are designed to increase the power and flexibility of the 67xi series SIP telephones. Up to three modules can be used with a 6753i, 6755i, 6757i or 6757i CT telephone to create a powerful, feature-rich console option. Modules share power and signaling with the phone, eliminating the need for additional wiring. Designed for receptionists, administrative assistants, call center agents, power users and executives who need to monitor and manage a large volume of calls on a regular basis. The 67xi Series expansion modules provide an intelligent choice for all enterprise IP environments.

FEATURES

- Choices two different models to give user choices of budget versus convenience
- Flexible and feature-rich supports speed-dial, call appearance lines, shared call and bridged line appearances, and busy lamp field (maximum of 50 BLF per phone)
- Ease of deployment power and signaling are shared with the phone, thereby avoiding any additional wiring expenses; configuration is also simplified via Web or configuration file from the phone
- Ease of use whether paper- or LCD-based, associated LED for each key provides quick status indication of the managed calls

Anixter No. Vendor No. Description

354042 M670l Expansion module, paper based 354048 M675l Expansion module, LCD based

MBU 400 Gateway

AASTRA TELECOM

This mobility solution includes one MBU 400 gateway base unit and one 420D handset. It is also expandable to support up to eight 420D handsets with eight unique SIP registrations. Combining this with one FXO port produces a fully integrated SIP and analog service for small businesses.

Anixter No. Vendor No.

423738 MBU 400 MBU 400 office mobility solution, one base unit and one 420D handset

423739 420D DECT MBU 400 handset with 1.5 in. backlit LCD display



3Com Voice Technology

3COM



3Com IP Telephony and Convergence applications are the cornerstone of secure converged networks. 3Com IP Telephony solutions, comprising NBX and VCX platforms, scale from five to 50,000 users. 3Com offers a wide range of IP phones, usable with NBX as well as with VCX. For smooth migration from legacy TDM PBX networks, 3Com offers a comprehensive suite of analog and digital VoIP gateways. The convergence application suite, comprising unified messaging, conferencing, presence and contact center, increases user productivity and strengthens customer interactions. As one of the leaders in secure converged networks, 3Com offers a complete IP Telephony and convergence applications portfolio.

Contact your local sales representative to configure a system that's right for you.

Cisco Unified IP Phone 7900 Series

CISCO SYSTEMS



Take full advantage of converged voice and data networks while retaining the convenience and user-friendliness you expect from a business phone. Cisco Unified IP phones can help improve productivity by meeting the needs of users throughout the organization. Advanced media endpoints enhances the end-user experience.

FFATIIRES

- IP phones with color liquid crystal display (LCD), including dynamic soft keys for call features and functions
- Support for information services, including XML capabilities to extend IP phone systems
- Capability to customize XML-based services to let users access a variety of information, such as stock quotes, employee directories and Web content
- On-campus mobility using voice over wireless LAN with the Cisco Unified wireless IP phone 7921G and Cisco Unified wireless 7925G to extend advanced unified communications capabilities for mobile workers

Contact your local sales representatives to learn more about this series of products.



2500 Desk Telephone

CORTELCO



FEATURES

- Fully modular
- 9 ft. handset cord
- Double-gong ringer
- Ringer volume control
- Hearing aid-compatible
- Five-year limited warranty
- Nationwide support system
- ADA volume control compliant
- Value-line versions contain a "D" at the end of their part numbers

Anixter No.	Vendor No.	Description
215813	250000VBA20M	Black
216140	250009VBA20M	lvory
215613	250013VBA20M	Beige
216142	250045VBA20M	Brown
215120	250047VBA20M	Red
214988	250044VBA20M	Ash
216236	250044VBA20F	Ash with flash
216150	250000VBA27M	Black with message waiting
214989	250044VBA27FC	Ash with flash and message waiting
397432	250000VBA20MD	Black, Value-line
397433	250044VBA20MD	Ash, Value-line
397434	250000VBA57MD	Black with message waiting, Value-line
352892	250044VBA57MD	Ash with message waiting, Value-line

2554 Wall Telephone

CORTELCO



- Fully modular
- 9 ft. handset cord
- Single-gong ringer
- Ringer volume control
- Hearing aid-compatible
- Five-year limited warranty
- Nationwide support system
- ADA volume control compliant
- Value-line versions contain a "D" at the end of their part numbers

Anixter No.	Vendor No.	Description
215614	255400VBA20M	Black
216144	255409VBA20M	lvory
216146	255413VBA20M	Beige
216143	255415VBA20M	White
215611	255444VBA20M	Ash
216145	255445VBA20M	Brown
215988	255447VBA20M	Red
216312	255444VBA20F	Ash with flash
216149	255444VBA27M	Ash with message waiting
216314	255444VBA27F	Ash with flash and message waiting
397436	255400VBA20MD	Black, Value-line
397437	255444VBA20MD	Ash, Value-line
397439	255400VBA27MD	Black with message waiting, Value-line
352893	255444VBA27MD	Ash with message waiting, Value-line



2500 Standard Series Telephone

SCITEC INC



FEATURES

- Heavy metal base
- Volume control handset (ADA/HAC-compliant)
- HI/LO ringer control
- Data port
- Optional message waiting light

2554 STANDARD WALL TELEPHONE

 Anixter No.
 Vendor No.
 Description

 397366
 2554W
 Black

 397367
 2554E
 Red

2510D STANDARD DESK TELEPHONE

With all the features listed above and a double-gong bell ringer.

 Anixter No.
 Vendor No.
 Description

 343017
 2510D
 Black

 397357
 2510E
 Red

Trendline

CORTELCO

FEATURES

- Tone/pulse dial
- · Pause, flash, redial
- · Receiver volume control
- Electronic ringer with on/off switch
- Hearing aid-compatible
- Desk/wall-mountable

6150 TRENDLINE TELEPHONE



With all the features listed above, plus: mute, three one-touch memory, 10 two-touch memory, visual ring indicator and one-year warranty

 Anixter No.
 Vendor No.
 Description

 266005
 615000V0E21M
 Black

 266004
 615021V0E21M
 Frost

8150 TRENDLINE TELEPHONE



With all the features of the 6150 plus: lighted keypad, fully modular, mute, reset button and two-year warranty. Note: 8150 does not have memory

 Anixter No.
 Vendor No.
 Description

 175105
 815044V0E21F
 Ash

 273433
 815000V0E21F
 Black

Healthcare Disposable Phone

CORTELCO



FEATURES

- Flash
- Mute
- Redial
- Tone/pulse
- On/off button
- Volume control
- Ringer-high/low/off

Optional bed-rail mount available

Anixter No. Vendor No.

250795 915044V0E21F Healthcare disposable telephone

Description

250796 915044BEDMNT Bed-rail mount

Single-use Disposable Patient Room Telephone

SCITEC INC



FEATURES

- One-piece design
- Reduces cross-contamination risks, cleaning and repair costs
- Increase telecom revenues by sending phone home with patient or family
- · Lighted dial pad
- On/Off lighted talk key
- · Flash, hold, redial keys
- Electronic ringer (ADA/HAC-compliant)
- HI/LO ringer control
- Message waiting light

Anixter No. Vendor No. Description 247557 H2001 White

Dignity 2420 Big Button Speakerphone

CORTELCO



FEATURES

- Incoming voice volume adjustment (18 dB to 40 dB)
- Incoming voice tone adjustment (frequencies)
- Incoming ringer volume adjustment (Off/Lo/High 95 dB)
- Incoming ringer tone adjustment (Hi or Lo)
- Caller ID/call waiting ID
- Large LCD display with backlight
- Three one-touch emergency buttons
- Speakerphone and on-hook predial
- Large dial buttons
- Tone/pulse dialing
- Flash/mute/redial/hold
- · Flashing visual ring indicator
- · Hearing aid-compatible
- One-year warranty

Anixter No. Vendor No. Description 332123 242021TP221F Frost

ez Touch Telephone

CORTELCO



FEATURES

- 10-number memory
- Ringer control
- Desk/wall-mountable
- Receiver volume control
- One-touch PHOTOmemory
- Large dial buttons
- Braille raised characters
- Tone/pulse switch
- Redial button
- Flashing visual ring indicator
- Hearing aid-compatible
- One-year warranty

Anixter No. Vendor No. Description 250794 240085V0E21F Sandstone

Colleague Basic Telephone

CORTELCO



FEATURES

- Last-number redial
- Flash (100-300-600 mS) switchable
- Message-waiting lamp (90 V)
- Handset volume control, ADA compliant
- Hook delay (positive line disconnect)
- Data jack
- Hearing aid-compatible
- Hold with LED indicator (flip-flop type)
- Desk/wall-mountable
- · Five-year warranty

 Anixter No.
 Vendor No.
 Description

 246493
 220100VBA27F
 Black

 246491
 220121VBA27F
 Frost



Colleague Speakerphone

CORTFI CO



FEATURES

- · Last-number redial
- Flash (100-300-600 mS) switchable
- Message-waiting lamp (90 V)
- Handset volume control. ADA compliant
- Hook delay (positive line disconnect)
- Data jack
- · Hearing aid-compatible
- Hold with LED indicator (flip-flop type)
- Desk/wall-mountable
- 10 one-touch programming memory
- Mute with LED indicator (flip-flop type)
- Hands-free speakerphone with LED indicator
- Headset control switch
- Line-in-use status with LED indicator (two-line version only)
- Conference (two-line version only)
- Five-year warranty

Anixter No.	Vendor No.	Description
246498	220300VBA27S	Single-line, black
246497	220321VBA27S	Single-line, frost
246500	220500VBA27S	Two-line, black
246499	220521VBA27S	Two-line, frost

Enhanced Colleague Series Telephone

CORTELCO



FEATURES

- Wide angle, three-line, ratchet-type backlit LCD display
- Voice-message indication
- Headset jacks (2.5 mm and RJ type)
- FSK and stutter dial capability
- Caller ID with call waiting

- Icons: new call, repeat call, forward call, toll call, message waiting
- 10 direct memories
- Redial/flash/mute
- Electronic hold
- Speakerphone
- Desk/wall-mountable
- Tone/pulse switchable
- Ring indicator
- Data port
- Conference (two-line only)
- Five-year warranty

 Anixter No.
 Vendor No.
 Description

 250009
 221000TP227E
 Single-line, black

 250010
 221021TP227E
 Single-line, frost

 250011
 222000TP227E
 Two-line, black

 250012
 222021TP227E
 Two-line, frost

Enhanced Colleague Line Powered CID Call Waiting

CORTELCO



FEATURES

- Line powered
- Improved Super-Twist LCD screen-improved viewing/reduced glare
- Ratchet-type LCD display-allows user to select viewing angle
- 90 V message waiting lamp
- 24 V M-W lamp
- Headset jacks (2.5 mm and RJ type)
- FSK capability
- Call waiting Caller ID2
- Extra large three-line LCD panel
- ADA compliant
- 60-message memory
- Voicemail button up to 24 digits
- 11 direct-dial memory + 10 keypad memory
- · Redial, flash, mute and hold
- Single-line speakerphone
- Desk/wall-mountable
- Ring indicator
- Data port
- Two-year warranty

 Anixter No.
 Vendor No.
 Description

 284038
 221100TP227E
 Black

 284040
 221121TP227E
 Frost

For basic line-powered model 8780, see Part No. 346287.



Analog Telephones

7 Series Caller ID Telephone

CORTELCO



FEATURES

- Caller ID with call waiting
- 99 CID memory
- Mute/hold/flash
- Redials last 10 numbers
- DTMF dialing
- 2.5 mm headset jack
- Speakerphone
- Conference (two-line only)
- Voicemail indication
- On-hook predial
- Directory name match
- 10 direct memories
- Wide-angle LCD
- Desk or wall-mountable
- Five-year warranty

Anixter No.	Vendor No.
349479	270000TP227S
353782	272000TP227S
364802	274000TP227
372519	275000TP227S
396941	2742CA000PA
396943	2743FM000PA

Description
Single-line, black
Two-line, black
Four-line, black
Four-line, extended features, black
Cordless phone adapter

Adapter for music on hold and

extension paging

Medallion Caller ID Telephone

CORTELCO



FEATURES

- Caller ID with call waiting
- 100 Caller ID memory
- · Contrast, mute, hold and flash

- Enhanced redial
- DTMF dialing
- 2.5 mm headset jack
- Speakerphone
- Conference (two-line only)
- Tone/pulse switch
- Selectable ringer cadences
- On-hook predial
- Directory name match
- 10 direct dial memories
- Three-line-wide angle, super-twist display
- Trilingual English, Spanish and French
- Five-year warranty

Anixter No. Vendor No. Description
336105 320041TP227E Single-line, charcoal
346170 322041TP227E Two-line, charcoal

Patriot Business Phones

CORTELCO



FEATURES

- Volume control (ADA compliant)
- Tone/pulse switch
- Two-year limited warranty
- Hold with LED indication
- Hearing aid-compatible
- Positive line disconnect
- Ringer volume control
- Flash (300 or 600 mS)
- Desk/wall-mountable
- Visual ring indicatorLast-number redial
- Directory card
- Fully modular
- Matte finish
- Data port
- Pause

PATRIOT BASIC

With all the features listed above

 Anixter No.
 Vendor No.
 Description

 250798
 219000V0E27F
 Black

 227929
 219075V0E27F
 Pearl gray



PATRIOT MEMORY

With all the features listed above, plus: $20\ \text{memory}$ locations, release, storable flash and pause

 Anixter No.
 Vendor No.
 Description

 250799
 219100V0E27S
 Black

 242671
 219175V0E27S
 Pearl gray

PATRIOT HANDSFREE

With all the features listed above, plus: speakerphone and headset compatibility

 Anixter No.
 Vendor No.
 Description

 179201
 219300V0E27S
 Black

 179203
 219375V0E27S
 Pearl gray

8004 Telephone

AASTRA TELECOM



FEATURES

- · Voltage message-waiting indicator
- Flash, mute, redial keys
- Hi/med/low ringer positions
- · Adjustable receiver volume
- · Phone line-powered

Anixter No. Vendor No. Description
210821 8004 PLATINUM Platinum
210820 8004 CHARCOAL Charcoal

8009 Telephone

AASTRA TELECOM



FEATURES

- Six programmable memory keys (up to 16 digits)
- Redial kev
- Parallel line jack for extension, fax or modem
- Line-release and -hold keys
- Link key

- Voltage message-waiting indicator
- Phone line-powered

 Anixter No.
 Vendor No.
 Description

 148741
 8009 BLACK
 Black

 166435
 8009 ASH
 Ash

9110, 9116 and 9120 Series Telephone

AASTRA TELECOM



FEATURES

- Call display with visual call waiting
- Speakerphone with mute
- Three-line adjustable display
- 80-name and -number callers list
- 20-number scroll-style directory
- 15 autodial positions
- Last-number redial
- Desk or wall-mount
- 9110 series is the value-based entry level version
- 9116LP offers PBX line or DC powered
- 9120 series offers the same features but in a two-line version

Anixter No.	Vendor No.	Description
286847	9110 CHARCOAL	Charcoal, seven programmable keys
264434	9116 CHARCOAL	Charcoal, 15 programmable keys
264435	9116 PLATINUM	Platinum, 15 programmable keys
353911	9116LP CHARCOAL	Charcoal, 15 programmable
		keys, line-powered
274897	9120 CHARCOAL	Charcoal, 14 programmable keys,

two-line version



9316CW Telephone

AASTRA TELECOM



FEATURES

- Call display and call waiting display
- Visual message waiting indicator
- Speakerphone with mute
- 50-names and -numbers directory and call log
- Three-line tilt backlit display
- Eight programmable memory keys
- Redial of the last five numbers called
- Secure numbers

 Anixter No.
 Vendor No.
 Description

 191723
 9316CW BLACK
 Black

 255231
 9316CW ASH
 Ash

 189632
 9316CW LT GREY
 Light grey

9417CW Telephone

AASTRA TELECOM



FEATURES

- Two lines with conference call
- Caller ID and call waiting display
- Visual message-waiting indicator
- Speakerphone with mute
- Six programmable memory keys
- 10-number redial
- 100-names and -numbers call log and directory
- Three-line backlit display of Caller ID on call waiting calls
- Fax switch

 Anixter No.
 Vendor No.
 Description

 191500
 9417CW BLACK
 Black

 423480
 9417CW ASH
 Ash

SP100 Single-line Basic Telephone

TELEMATRIX



FEATURES

- Single-line analog telephone
- Ideal for installation behind a POTS, PABX or Centrex telephone line
- Phone line-powered
- Large message-waiting lamp
- Flash kev
- · Last-number redial feature
- Electronic hold key with LED indicator (with remote release)
- Data port on the phone base
- Push-on/push-off handset volume boost
- Disconnect key
- Five-year warranty

 Anixter No.
 Vendor No.
 Description

 261231
 191001
 Black

 261227
 19100
 Ash

SP300 Single-line Feature Telephone

TELEMATRIX



FEATURES

- Single-line analog telephone with 11 feature keys
- Compatible for installation behind a POTS, PABX or Centrex telephone line
- Ideal for use as a call center telephone
- Large TouchLite message-waiting indicator/one-touch retrieval key
- Eight-step volume bar for controlling handset/headset/ring volume
- Four audible ringing cadence options
- Universal message-waiting for neon, LED, FSK and SDT detect applications
- Headset enabled-built-in amplifier supports modular and 2.5 mm connections, soft switching between headset and handset operations
- Flash key, mute key, pause key, electronic hold key, release key, disconnect key
- Last-number redial feature
- Data port on the phone base
- Five-year warranty

 Anixter No.
 Vendor No.
 Description

 261235
 193001
 Black

 261236
 19300
 Ash



SP400 Single-line Speakerphone

TELEMATRIX



FEATURES

- Single-line analog speaker telephone with 11 feature keys
- Also includes all standard features found on the SP300

 Anixter No.
 Vendor No.
 Description

 261238
 194001
 Black

 261237
 19400
 Ash

SP550 Single-line CID Speakerphone

TELEMATRIX



FEATURES

- Single-line analog display speaker telephone with Caller ID
- Large backlit LCD display with adjustable contrast control
- Caller ID feature: Type II compatible, displays date, time, name and number of caller - 100 records
- PhoneBook feature for storing frequently dialed telephone names and numbers -100 records
- Administrative programming level for secure configuring of the telephone
- TouchLite message-waiting indicator/one-touch retrieval key
- Universal message-waiting for neon, LED, FSK and SDT detect applications; soft switching between headset, speakerphone and handset operations
- On-hook dialing features for "pre-dial" or "hot-keypad" with edit option
- 11 programmable feature keys with interchangeable keycaps for customized labeling
- Also includes all standard features found on the SP300

 Anixter No.
 Vendor No.
 Description

 261242
 195501
 Black

 261241
 19550
 Ash

LP550 Phone Line-powered CID Speakerphone

TFI FMATRIX



FEATURES

- Single-line analog display speaker telephone with Caller ID
- Phone line-powered CID no AC adapter required
- Compatible for installation behind a POTS or PABX
- Large LCD display with adjustable contrast control
- Caller ID feature: Type II compatible, displays date, time, name and number of caller - 100 records
- TouchLite message-waiting indicator/one-touch retrieval key
- 11 programmable feature keys with interchangeable keycaps for customized labeling
- Also includes all standard features found on the SP300

 Anixter No.
 Vendor No.
 Description

 261240
 195551
 Black

 261239
 19555
 Ash

SP750 Two-line CID Speakerphone

TELEMATRIX



FEATURES

- Two-line analog display speaker telephone with Caller ID
- Large LCD display with adjustable contrast control
- Caller ID feature: Type II compatible, displays date, time, name and number of caller - 100 records
- PhoneBook feature for storing frequently dialed telephone names and numbers -100 records
- Administrative programming level for secure configuring of the telephone
- Line status indicators for line-in-use, on-hold and ringing
- Conference feature
- TouchLite message-waiting indicator/one-touch retrieval key
- On-hook dialing features for "pre-dial" or "hot-keypad" with edit option
- 11 programmable feature keys with interchangeable keycaps for customized labeling
- 1+ toll restriction feature
- Also includes all standard features found on the SP300

 Anixter No.
 Vendor No.
 Description

 261245
 297501
 Black

 261243
 29750
 Ash



Analog Telephones

STC-7003 Business Series Telephones

SCITEC INC



FEATURES

- Single-line
- Phone line-powered
- Type I/II Caller ID
- Speakerphone
- Nine programmable speed dial keys
- Neon/LED/Centrex (FSK)
- Visual message indication
- HI/LO/Off ringer control (ADA/HAC-compliant)
- Electronic ringer

Anixter No. Vendor No. Description

256242 STC-7003-B-VT Single-line caller ID speakerphone,

line-powered, black

256243 STC-7003-G-VT Single-line caller ID speakerphone,

line-powered, grey

STC-7002 Business Series Telephones

SCITEC INC



FEATURES

- Single-line
- Phone line-powered
- Speakerphone
- 10 programmable speed dial keys
- Neon/LED message light
- HI/LO/Off ringer control (ADA/HAC-compliant)
- Electronic ringer

Anixter No. Vendor No. Description

264200 STC-7002-B Single-line speakerphone, line-powered, black STC-7002-G Single-line speakerphone, line-powered, grey

STC-7001 Business Series Telephones

SCITEC INC



FEATURES

- Single-line
- Phone line-powered
- Feature phone
- 10 programmable speed dial keys
- Neon/LED message light
- HI/LO/Off ringer control (ADA/HAC-compliant)
- · Electronic ringer

Anixter No. Vendor No. Description

313605 STC-7001 Single-line telephone, line-powered, black

AT&T Telephone Model 983

VTECH COMMUNICATIONS INC



FEATURES

- Two-line capability
- Speakerphone
- No AC power needed
- Three-party conferencing
- 24-number memory
- Receiver/speakerphone/headset volume control
- Headset-compatible (2.5 mm jack)
- Distinctive ring tones
- Data port
- Hold/mute/flash/redial
- Line status indicators
- Desk/wall-mountable
- · Hearing aid-compatible

Anixter No. Vendor No. Description 372396 983 Charcoal



AT&T Telephone Model 993

VTECH COMMUNICATIONS INC



FEATURES

- Two-line capability
- Speakerphone
- · Caller ID/call waiting
- 99-name/number Caller ID log
- 100-name/number directory
- Receiver/speakerphone/headset volume control
- Three-party conferencing
- Headset-compatible
- Hold/mute/flash/redial/pause
- Data port
- Receiver/speakerphone/headset
- Line status indicators
- Distinctive ring tones

Anixter No. Vendor No. Description 368272 993 Charcoal

AT&T Four-line Telephone Model 1040

VTECH COMMUNICATIONS INC



FEATURES

- Up to four-line capability
- Speakerphone
- Three-party conferencing
- 32-number speed dial and 16 intercom number locations
- Expandable up to 16 stations
- Intercom/paging/call transfer
- · Hold/mute/flash/redial
- Two data ports

- Receiver/speakerphone/headset volume control
- Headset-compatible (2.5 mm jack)
- Do not disturb
- LCD display

Anixter No. Vendor No. Description 399175 1040 Charcoal

AT&T Four-line Telephone Model 1070

VTECH COMMUNICATIONS INC



FEATURES

- Up to four-line capability
- DECT 6.0 technology
- Speakerphone
- Three-party conferencing
- 32-number speed dial and 16 intercom number locations
- 200-name/number phonebook directory
- Expandable up to 16 stations
- Intercom/paging/call transfer
- Hold/mute/flash/redial
- Two data ports
- Visual message waiting indicator
- Call waiting and caller ID
- Speakerphone in base
- Headset-compatible (2.5 mm jack)
- Do not disturb
- LCD display

Anixter No. Vendor No. Description 399176 1070 Charcoal



AT&T Four-line Telephone Model 1080

VTECH COMMUNICATIONS INC



FEATURES

- · Up to four-line capability
- Speakerphone
- Fully integrated digital answering system
- Programmable auto attendant
- Three-party conferencing
- 32-number speed dial and 16 intercom number locations
- 200-name/number phonebook directory
- Expandable up to 16 stations
- Intercom/paging/call transfer
- Hold/mute/flash
- Two data ports
- Speakerphone in base
- Headset-compatible (2.5 mm jack)
- Do not disturb
- LCD display

Anixter No. Vendor No. Description 399177 1080 Charcoal

Integrated Telephone with Caller ID

PANASONIC



FEATURES

- 50-station caller ID memory and dialer
- 50-station phonebook and dialer
- Call waiting
- Phone company voice mail compatible (FSK compatible)
- Chain dial
- Programmable call restriction
- 3-step ringer volume control
- Switchable tone/pulse setting

 Anixter No.
 Vendor No.
 Description

 425229
 KX-TSC11B
 Black

 425230
 KX-TSC11W
 White

6221 Analog Telephone

AVAYA-VOICE PRODUCTS



FEATURES

- Positive disconnect
- Handset and ringer volume control
- Tone dialing
- PBX message waiting
- Redial
- Flash
- Data jack (RJ11)
- System hold (DEFINITY systems only)
- Repertory dialing (10 buttons with up to 24 digits or elements each)
- Personalized ringing
- Speakerphone

 Anixter No.
 Vendor No.
 Description

 214762
 700287758
 Charcoal

 284242
 700287717
 White

For more information on other Avaya telephony products contact your local sales office.

Integrated Telephone

PANASONIC



FEATURES

- · Hands-free speakerphone
- One-touch/speed dialer (20 stations)
- Ringer indicator
- Electronic volume controls for speakerphone (eight-step), handset and headset (four-step)
- · Headset-compatible
- Dial lock
- Three-step ringer control
- Data port
- Hold/flash/mute/redial/pause
- Wall-mountable

Anixter No.Vendor No.Description262594KX-TS105BSingle-line, black245337KX-TS105WSingle-line, white245335KX-TS108WSingle-line with display, white

245335KX-TS108WSingle-line with display, white245336KX-TS208WTwo-line with display, white



Digital Centrex Telephones

M5008 Meridian Digital Centrex Phone

AASTRA TELECOM



FEATURES

- Compatible with Nortel DMS 100 central office
- Loop-powered
- Eight-system programmable keys
- · Hold-and-release keys

Anixter No. Vendor No. Description
243842 M5008 BLACK Black, loop-powered
255232 M5008 ASH Ash, loop-powered

M5208 Meridian Digital Centrex Phone

AASTRA TELECOM



FEATURES

- · Compatible with Nortel DMS 100 central office
- 24 x 2 LCD display
- Loop-powered
- Visual ringing indication
- Eight-system programmable memory keys

Anixter No. Vendor No. Description
186280 M5208 BLACK Black, loop-powered
186274 M5208 ASH Ash, loop-powered

M5216 Meridian Digital Centrex Phone

AASTRA TELECOM



FEATURES

- Compatible with Nortel DMS 100 central office
- 24 x 2 LCD display
- Headset compatible
- Supports M522 expansion module
- Keys for feature access or directory numbers

Anixter No. Vendor No. Description

186286M5216 BLACKBlack, headset support186282M5216 ASHAsh, headset support

M5316 Meridian Digital Centrex Phone

AASTRA TELECOM



FEATURES

- Compatible with Nortel DMS 100 central office
- Hands-free operation
- 24 x 2 LCD display
- Time-and-date display with call timer
- 13 keys for feature access or directory numbers
- Calling-name-and-number display
- Supports M522 expansion module

Anixter No. Vendor No. Description
186289 M5316 BLACK Black, speakerphone
186287 M5316 ASH Ash, speakerphone



Digital Centrex Telephones

DC550 Digital Centrex Speakerphone

TELEMATRIX



FEATURES

- Digital Centrex display speakerphone with multiline functionality
- For installation with Nortel Networks MDC Digital Centrex Services
- Large backlit 2 x 24 LCD display
- · TouchLite message-waiting indicator
- Predial and last-number-redial features
- 11 advanced feature/line keys
- 16-step volume bar for controlling speaker/handset/headset/ringing volume
- Headset feature with: modular and 2.5 mm headset connectivity ports, built-in amplifier, separate headset ON/OFF line activation key (with LED indicator), soft switching between headset, speakerphone and handset operations
- Mute key, pause key, electronic hold key, release key

Anixter No.	Vendor No.	Description
268209	095501	Black
268206	09550	Ash

DC640 Digital Centrex Console

TELEMATRIX



- Digital Centrex display console telephone with multiline functionality
- For installation with Nortel Networks MDC Digital Centrex Services
- Large backlit 2 x 24 LCD display
- TouchLite message-waiting indicator
- Predial and last-number-redial features
- Quality speakerphone
- 40 advanced feature/line keys
- 16-step volume bar for controlling speaker/handset/headset/ringing volume
- Headset feature with: modular and 2.5 mm headset connectivity ports, built-in amplifier, separate headset ON/OFF line activation key (with LED indicator), soft switching between headset, speakerphone and handset operations
- Mute key, pause key, electronic hold key, release key

Anixter No.	Vendor No.	Description
284633	096401	Black
284644	09640	Ash



Wireless Telephones

SpectraLink 8000 Systems

SPECTRAL INK



The SpectraLink 8000 System offers mobile voice over a converged voice and data network, which reduces costs and simplifies management while significantly improving employee mobility, responsiveness and productivity. The SpectraLink 8000 System provides the richest functionality while integrating with the broadest range of enterprise applications and networks.

- Compatible with industry-standard 802.11a/b/g networks
- End-to-end IP telephony solution
- Digital interfaces for most popular legacy PBX telephone systems

2.0		a. 100ao) . 27. totophono o) otomo
Anixter No.	Vendor No.	Description
329203	TGA216	Telephony gateway, 16-port analog interface, power supply not included
329209	TGX216	Telephony gateway, 16-port Mitel SX interface, power supply not included
329207	TGN216	Telephony gateway, 16-port Nortel Meridian interface, power supply not included
329205	TGD216	Telephony gateway, 16-port universal digital interface, power supply not included
329195	SVP101	Voice Priority Server (SVP) required on a pure IP PBX solution, 100 user max., power supply not included
329196	SVP011	Voice Priority Server (SVP) required on a pure IP PBX solution, 10 user max., power supply not included
329197	SVP021	Voice Priority Server (SVP) required on a pure IP PBX solution, 20 user max., power supply not included
266123	TPS100A	Power supply for TGX2XX, MOG7XX and SVPXXX
329214	NCC101	SpectraLink configuration cradle for e340/h340/i640/8002 wireless telephones
329226	MKR151	Rack-mount kit

SpectraLink 8000 Series Wireless Telephones

SPECTRALINK



The SpectraLink 8000 Series Wireless Telephones support a broad range of enterprise applications, as these compact handsets offer a rich set of features and accessories.

FEATURES

- 802.11a/b/g standard-compatible
- · Provides all the features of a wired telephone set
- Simple to operate without extensive training
- Durable enough to withstand the rigors of daily use
- Supports digital, native IP and SIP interfaces to most major telephony platforms
- Superior voice quality on converged wireless networks using SpectraLink Voice Priority (SVP), Wi-Fi Standard QoS, or Cisco CCXv4
- Support for industry standard security protocols including WEP (40 bit and 128 bit) and 802.11i with Pre-Shared Key (PSK), WPA2 mode using EAP-FAST or PEAP, and Cisco Client Key Management (CCKM) or Opportunistic Key Caching (OKC)
- Audible and vibrating ringers, backlit display and keypad, built-in speakerphone, Push-to-Talk
- Text messaging support via Open Application Interface (OAI)
- Software configuration tool for simple configuration and management

SPECTRALINK 8000 SERIES WIRELESS TELEPHONES

Anixter No. 343711	Vendor No. WTB150	Description SpectraLink 8020 wireless telephone,
343712	WTE150	SRP and SIP SpectraLink 8030 wireless telephone, SRP and SIP

SPECTRALINK 8000 SERIES WIRELESS TELEPHONE ACCESSORIES

OI LOTTO ILITA	OOOO OLINILO MINLL	LOO ILLLI HONE MODEOGOMILO
Anixter No.	Vendor No.	Description
332384	BPL100	Standard capacity battery pack, four hours talk time, 80 hours standby time
332386	BPL200	Extended capacity battery pack, six hours talk time, 120 hours standby time
332388	BPL300	Ultra-extended capacity battery pack, eight hours talk time, 160 hours standby time
332481	DCD100	Dual charging stand, power supply not included
332482	DCS100	Single charging stand, power supply not included
332483	GCQ100	Quad charging stand, power supply not included

Continued on next page >>



Wireless Telephones

(continued)	SpectraLink 800	O Series Wireless Telephones
Anixter No.	Vendor No.	Description
242661	QPS100A	Power supply for single, dual, and quick chargers and configuration cradle - North America, Taiwan
266111	QPS200A	Power supply for quad chargers GCx100
348656	WT0150	Swivel clip for 6020/8020 series handsets
353907	WT0250	Swivel clip for 8030 handset
332493	WT0310	Swivel carrying case for 6020/8020 series, black with keypad cover
353909	WT0310	Swivel carrying case for 8030, black with keypad cover

SpectraLink h340 Wireless Telephone

Anixter No. Vendor No.

329215

329217

329222

SPECTRALINK

PT0501

PT0521

PT0651



Description

Clothing clip for SpectraLink

Swivel clip for SpectraLink

leather with keypad cover

e340/h340/8002 wireless telephones

e340/h340/8002 wireless telephones

Swivel carrying case for SpectraLink

e340/h340/8002 wireless telephones, black

The SpectraLink h340 Wireless Telephone is uniquely designed to meet the challenging needs of the healthcare workplace. With more durable plastics, backlit keypad, liquid damage warranty and multiple charging options, this handset is especially suited for 24-hour-shift-based environments.

FEATURES

- 802.11b radio
- Small lightweight form factor
- NiMH battery packs supporting four hours talk time and eighty hours standby time
- Rugged ABS plastics for increased durability
- Backlit display for 24-hour operation
- Standard one-year wear-and-tear plus liquid damage warranty coverage
- Single, dual, and quad charging options

Anistor No Vandar No

SPECTRALINK H340 WIRELESS TELEPHONES

AIIIXLEI NU.	venuon no.	nezcuhunu
329179	PTN141	SpectraLink h340 wireless IP phone for Mitel IP
329180	PTN151	SpectraLink h340 wireless IP phone, works with SpectraLink telephony gateway, SRP and open IP

SPECTRALINK H340 WIRELESS TELEPHONE ACCESSORIES

310012	Vendor No. BPN100	Description Battery pack for SpectraLink h340
329187	DCN201	Dual charging stand for SpectraLink h340 wireless telephone, power supply not included
329190	GCN101	Quad charger for SpectraLink h340 wireless telephone battery packs, power supply not included
329217	PT0521	Swivel clip for SpectraLink e340/h340/8002 wireless telephones

SpectraLink e340 Wireless Telephone

SPECTRALINK



The SpectraLink e340 Wireless Telephone was designed specifically for busy office environments. This compact handset offers features and accessories that address the needs of a variety of businesses.

FEATURES

- 802.11b radio
- Small lightweight form factor
- NiMH battery packs supporting four hours talk time and 80 hours standby time
- Single and dual charging options

SPECTRALINK E340 WIRELESS TELEPHONES

Anixter No. Vendor No.	Description
329175 PTE101	SpectraLink e340 wireless IP phone for legacy PBX
329176 PTE111	SpectraLink e340 wireless IP phone for Cisco call manager, enhanced model
329177 PTE141	SpectraLink e340 wireless IP phone for Mitel IP
329178 PTE151	SpectraLink e340 wireless IP phone, works with SpectraLink telephony gateway, SRP, SIP and Open IP

SPECTRALINK E340 WIRELESS TELEPHONE ACCESSORIES

OF COTTACION ESTO WINDLESO TELLI HONE ACCESSINIES		
Anixter No.	Vendor No.	Description
267122	BPE100	Nickel metal hybrid (NiMH) battery pack
329184	DCE101	Desktop charger for SpectraLink e340/8002 wireless telephones
329186	DCE201	Dual charging stand for SpectraLink e340, power supply not included



Wireless Telephones

Anixter No. Vendor No.

329222 PT0651 Swivel carrying case for SpectraLink

e340/h340/8002 wireless telephones, black

leather with keypad cover

329215 PT0501 Clothing clip for SpectraLink e340/h340/8002 wireless telephones

SpectraLink i640 Wireless Telephone

SPECTRALINK



The SpectraLink i640 Wireless Telephone was designed to meet the most demanding environmental requirements, and includes a larger earpiece and noise suppression for loud environments as well as Polycom's exclusive push-to-talk functionality. The handset is small enough to be highly mobile, yet rugged enough for heavy usage. (Part number varies based on PBX interface.)

FEATURES

- 802.11b radio
- · Sturdy industrial form factor
- PTT functionality
- Enlarged earpiece for operation in noisy environments
- NiMH battery packs supporting four hours talk time and 80 hours standby time
- Rugged ABS plastics for increased durability
- Standard one-year wear-and-tear warranty coverage
- Single, dual and quad charging options

SPECTRALINK 1640 WIRELESS TELEPHONES

Anixter No.	vendor No.	Description
329181	PTX111	SpectraLink i640 wireless IP phone for Cisco Call Manager
329182	PTX141	SpectraLink i640 wireless IP phone, Mitel IF
329183	PTX151	SpectraLink i640 wireless IP phone for
		SpectraLink telephony gateway, SRP and
		Open IP

SPECTRALINK 1640 WIRELESS TELEPHONE ACCESSORIES

Anixter No	Vendor No.	Description
267123	BPX100	Nickel metal hybrid (NiMH) battery pack
329185	DCX101	Desktop charger, power supply not included
329188	DCX201	Dual charging stand for SpectraLink i640, power supply not included
329189	GCX101	Quad charger for SpectraLink i640 battery packs, power supply not included
329216	PT0511	Clothing clip for SpectraLink i640 wireless telephones
329218	PT0601	Carrying case, black

SpectraLink 8002 Wireless Telephone

SPECTRALINK



The SpectraLink 8002 wireless telephone is a cost-effective, business-grade mobile telephony solution for small- to medium-sized businesses. Using the Wi-Fi Alliance's WMM QoS standard, the SpectraLink 8002 wireless telephone interoperates with most consumer-grade and SMB access point infrastructure devices, alleviating the need to install and maintain additional hardware while still providing enterprise-level security and quality voice communications. In keeping with the needs of the market segment, the SpectraLink 8002 is packaged in complete, ready-to-install bundles that include a single or dual charger, battery pack and a power supply.

FEATURE:

- 802.11b radio
- SIP integrations with multiple telephony platforms
- WMM QoS standards-compatible
- Small lightweight form factor
- NiMH battery packs supporting three hours talk time and 50 hours standby time
- Rugged ABS plastics for increased durability
- Single and dual charging options

SPECTRALINK 8002 WIRELESS TELEPHONE BUNDLES

Anixter No.	Vendor No.	Description
374636	2200-37010-020	SpectraLink 8002 single charger bundle
374660	2200-37020-020	SpectraLink 8002 dual charger bundle

SPECTRALINK 8002 WIRELESS TELEPHONE ACCESSORIES

SECTIVALINA	OUUZ WINELESS IEL	ELUNINE HODESSONIES
Anixter No.	Vendor No.	Description
374661	2200-37202-001	SpectraLink 8002 wireless telephone
		dual charger
329184	DCE101	Desktop charger for SpectraLink
		e340/8002 wireless telephones
329214	NCC101	SpectraLink configuration cradle for
		e340/h340/i640/8002 wireless telephones
329215	PT0501	Clothing clip for SpectraLink
		e340/h340/8002 wireless telephones
329217	PT0521	Swivel clip for SpectraLink
		e340/h340/8002 wireless telephones
329222	PT0651	Swivel carrying case for SpectraLink
		e340/h340/8002 wireless telephones, black
		leather with keypad cover
329224	PT0661	Swivel carrying case for SpectraLink
		e340/h340/8002 wireless telephone, black
		leather with keypad cover



Wireless Telephones

SpectraLink 6000 System

SPECTRALINK



The SpectraLink 6000 System is a dedicated wireless voice system, providing the highest level of reliability and security with minimal administration and maintenance. The SpectraLink 6000 System is the preferred choice of more enterprises in the U.S. than any other wireless system available.

FFATIIRE:

- Proven handset design for use in all business environments
- Scalable architecture for up to 3,200 users
- Interfaces to leading telephony platforms
- Superior radio performance
- Integration with market-leading applications

SPECTRALINK 6100 INFRASTRUCTURE

The SpectraLink 6100 MCU is conveniently sized to support 16 wireless telephone users and four base stations. Four SpectraLink 6100 MCUs can be connected together by an Inter-Processor Communication (IPC) cable to support as many as 64 users and 16 base stations

04 users and	TO DASE STATIONS	
Anixter No.	Vendor No.	Description
276278	SCA508	SpectraLink 6100 M3 MCU 8-port
		analog interface
276279	SCA516	SpectraLink 6100 M3 MCU 16-port
		analog interface
276282	SCD508	SpectraLink 6100 M3 MCU 8-port universal
		digital interface
276283	SCD516	SpectraLink 6100 M3 MCU 16-port universal
		digital interface
276285	SCF516	SpectraLink 6100 M3 MCU 16-port 4-wire
		universal digital interface
276286	SCN516	SpectraLink 6100 M3 MCU 16-port Nortel
		Meridian 1 and universal digital interface
276290	SCX516	SpectraLink 6100 M3 MCU 16-port Mitel
		SX-Series digital interface
329226	MKR151	Rack-mount kit
251158	RCC410	Standard base station for SpectraLink
		6100 systems
251160	RC0410	Outdoor enclosure base station for
		SpectraLink 6100 systems

SPECTRALINK 6300 INFRASTRUCTURE

The SpectraLink 6300 MCU is the processing center for large-scale deployments. It consists of at least one primary shelf and up to 19 expansion shelves and can support up to 3,200 users. The primary shelf contains the system controller card that manages call processing for the wireless network. Telephone line and base station connections are made to an interface module. Each module supports 16 wireless telephones and six base stations, for up to 180 wireless telephones and 60 base stations per shelf. Multiple sites can be networked using T1 circuits between up to 18 remote shelves and the main site

Anixter No.	Vendor No.	Description
276291	CPA316	SpectraLink 6300 analog interface module
276293	CPD316	SpectraLink 6300 universal digital interface module
276295	CPM316	SpectraLink 6300 Mitel digital interface module
276296	CPN316	SpectraLink 6300 Nortel Meridian 1 and universal digital interface module
276268	CRC301	T1 remote module
276269	CSC300	SpectraLink 6300 expansion shelf controller
276270	CSC301	SpectraLink 6300 single-shelf
		system controller
276273	CS0300	SpectraLink 6300 expansion shelf controller, OAI enabled
276274	CS0301	SpectraLink 6300 single-shelf system controller, OAI enabled
276298	MCS300	SpectraLink 6300 shelf
332372	MKA320	SpectraLink 6300 administration kit with modem
198685	RCC400	Standard base station for all systems
285793	RCH400	High-density base station for SpectraLink 6300 systems, deployed exclusively with other RCH400s
251156	RC0400	Outdoor enclosure base station for all systems



Wireless Telephones

SpectraLink 6020 Wireless Telephones

SPECTRALINK



The SpectraLink 6020 wireless telephones are designed specifically for use within the enterprise. They are extremely durable, and unlike consumer-grade cellular phone designs, have no moving parts, no external antennas and no complex configuration menus. The handsets have a rugged design with a large earpiece to provide comfort and seal out background noise.

- Provides all the features of a wired telephone set
- Simple to operate without extensive training
- Durable enough to withstand the rigors of daily use
- Superior voice quality comparable to a wired telephone

Anixter No.	Vendor No.	Description
328963	LTB100	Wireless telephone with vibrating ringer and backlit display/keypad
332384	BPL100	Standard capacity battery pack, four hours talk time, 80 hours standby time
332386	BPL200	Extended capacity battery pack, six hours talk time, 120 hours standby time
332388	BPL300	Ultra-extended capacity battery pack, eight hours talk time, 160 hours standby time
332482	DCS100	Single charging stand, power supply not included
332481	DCD100	Dual charging stand, power supply not included
332483	GCQ100	Quad charging stand, power supply not included
332484	WT0102	Coiled lanyard with clothing clip for 6000/8000 series handsets
348656	WT0150	Swivel clip for 6020/8020 series handsets
332493	WT0310	Swivel carrying case for 6020/8020 series, black with keypad cover
332494	WT0320	Rugged holster, black



Audioconferencing Telephones

VoiceStation 300 and 500

POLYCOM



Designed as a clear alternative to half-duplex handset speakerphones, both the VoiceStation 300 and 500 deliver professional-quality conferencing to offices and other smaller meeting areas. Note: The VoiceStation 500 connects to Bluetooth-enabled mobile phones and computers.

FFATIIRE

- Full-duplex performance-simultaneous two-way communication so everyone can hear and be heard clearly
- Three microphones/one speaker (not expandable)
- Combination iconic/alpha-numeric keypad mute, flash, hold, redial, data port (on power supply)
- Wall-mountable
- Warranty: 12 months

 Anixter No.
 Vendor No.
 Description

 332199
 2200-17910-001
 VoiceStation 300

 332202
 2200-17900-001
 VoiceStation 500

SoundStation2

POLYCOM



Ideal for small- to medium-sized conference rooms, the SoundStation2's distinctive, award-winning design is familiar throughout the world. The SoundStation Conference Phone makes natural, full-duplex (two-way) conversations easy without clipping or distortion. Simple to install and use, extension microphones expand range for medium- to larger-sized rooms.

FEATURES

- Echo cancellation and suppression adapt automatically to changing rooms and telephone lines
- Mute buttons/dual-color LED status lights
- Integrated keypad eliminates the need for a separate phone
- Powerful speaker

- Three quality cardioid microphones
- Full-duplex operation makes conversation natural and clear

Anixter No. Vendor No. Description

310485 2200-15100-001 Nonexpandable, no display

301451 2200-16000-001 Nonexpandable **303629** 2200-16200-001 Expandable

303802 2200-16155-001 Extension microphone kit

SoundStation2W

POLYCOM



The SoundStation2W is a conference phone without cords that gives you the freedom to conference anywhere team collaboration is important, even in rooms where there are no phone lines. With superior voice quality, proven DECT 6.0 wireless technology, added security of voice encryption, up to 24 hours of talk time, and the ability to dial through a cell phone, the SoundStation2W is raising the standard for everyday conferencing. With reliable 150 ft. wireless roaming from the base station, wireless frequency hopping to avoid interference, and a long-lasting lithium-ion battery, the SoundStation2W truly meets today's needs for excellent voice quality and usage flexibility.

FEATURES

- DECT 6.0 (1.9 GHz) wireless technology with 150 ft. range, 64-bit voice encryption
- Talk from up to 10 ft. away from the mic and be heard
- Noise reduction minimizes noise from projector and PC fans
- Expansion mics can be added (EX model only) and software upgradeable
- Works just like a regular conference phone

Anixter No. Vendor No. Description

397427 2200-07800-160 Expandable, DECT 6.0 (1.9 GHz) technology

397429 2200-07880-160 Nonexpandable,

DECT 6.0 (1.9 GHz) technology

285487 2200-07840-001 Extension microphones



Audioconferencing Telephones

SoundStation VTX 1000

POLYCOM



The Polycom SoundStation VTX 1000 is an advanced analog conference phone with Acoustic Clarity Technology delivering outstanding voice quality. It's the world's first conference phone that automatically adapts to each meeting environment, providing high-fidelity voice clarity for all participants.

- Acoustic Clarity Technology allows simultaneous natural conversation
- Unparalleled room coverage speak naturally from 2 ft. to 20 ft. and be heard clearly on the far end
- Revolutionary voice quality the world's first analog phone to deliver wideband voice over ordinary telephone lines
- Built-in investment protection the world's first conference phone that allows you to download new software remotely through an ordinary telephone line to add new features and applications
- Maximum configuration flexibility has independent input and output, bass/treble controls and internal mic and speaker control for multiple uses and applications including external speakers

Anixter No.	Vendor No.	Description
285383	2200-07300-001	VTX 1000 only
266331	2200-07142-001	VTX 1000 with extended mics and subwoofer
285385	2215-07155-001	Extension microphones
412699	2200-32400-001	Wireless expansion microphones, two
285388	2200-07242-001	Subwoofer with amplifier kit

SoundStation IP 6000 SIP

POLYCOM



The SoundStation IP 6000 SIP is a next-generation IP conference phone designed for small- to mid-sized rooms and provides 12-foot mic pickup for remarkable room coverage. The SoundStation IP 6000 is interoperable with leading SIP-based IP PBX and SoftSwitch platforms.

FEATURES

- Polycom HD Voice for high-fidelity calls at up to 14 kHz conference calls that sound as natural as being there
- Polycom's patented Acoustic Clarity Technology delivers a conference phone experience with no compromises
- Robust interoperability allows for compatibility with a broad array of SIP call platforms
- Add optional expansion microphones for greater pickup range

Anixter No.	Vendor No.	Description
368993	2200-15600-001	SoundStation IP 6000
374871	2200-15660-001	SoundStation IP 6000 with AC power kit
285385	2215-07155-001	Extension microphones
412699	2200-32400-001	Wireless expansion microphones, two

SoundStation IP 7000

POLYCOM



The SoundStation IP 7000 is a breakthrough conference phone that delivers outstanding performance and a robust feature set for SIP-based VoIP platforms. It is the most advanced conference phone ever developed, and is ideal for executive offices, conference rooms and board rooms.

FEATURES

- Polycom HD voice for high-fidelity calls at up to 22 kHz conference calls that sound as natural as being there
- Polycom's patented Acoustic Clarity Technology delivers a conference phone experience with no compromises
- Robust interoperability allows for compatibility with a broad array of SIP call platforms
- Add optional expansion microphones for greater pickup range
- Connect two units together for expanded mic pickup and volume for larger rooms

Anixter No.	Vendor No.	Description
371775	2200-40000-001	SoundStation IP 7000
371664	2230-40300-001	SoundStation IP 7000 with AC power kit
376713	2200-40040-001	Extension microphones



Audioconferencing Telephones

Conference Telephone

CORTELCO




FEATURES

- Mute with LED
- Full duplex
- On/off with LED
- Flash
- Tone/pulse dialing

- Ringer high/low/offExternal microphone (optional)
- One-year warranty

Anixter No. Vendor No. Description CP4400041PAK Charcoal





Multimedia Videoconferencing

 Automatically focuses on the current speaker while tracking the conversation flow

· Easy to deploy and use

Anixter No. Vendor No. Description

396520 2200-31200-100 CX5000 Unified Conference Station

HDX 7000 Series

POLYCOM



The HDX 7000 series provides flexible, affordable HD videoconferencing for high-quality communication throughout mainstream workplace environments. Ideal for education, medical, enterprise and on-demand collaboration applications.

FEATURES

- Advanced HD video technology, offers smooth, natural motion and sharp clear images for outstanding video in 720p or 1080p
- Polycom StereoSurround technology, using 22 kHz audio, delivers crisp, natural voice clarity even when multiple parties are speaking
- Make quality video calls across your network or over the public Internet with Polycom's Lost Packet Recovery (Polycom LPR) technology
- Share HD content such as presentations, graphics and rich-media content with other HD and non-HD systems
- Supports up to 2M line rate and up to 4M line rate with the Multipoint software option
- Supports up to two microphones for greater audio coverage
- Optional four-way embedded multipoint bridge for greater flexibility and participation
- · One-year warranty included
- A minimum of a one-year service agreement is required

Anixter No.	Vendor No.	Description
421366	7200-23130-001	HDX 7000-720, video resolution: 720p
423916	7200-23140-001	HDX 7000-1080, video resolution: 1080p
384778	5150-23912-001	HDX MPPlus Multingint software ontion

VVX 1500

POLYCOM



The first business media phone that combines advanced telephone, one-touch video and integrated business applications into a seamless, lifelike experience.

FEATURES

- Six-line, feature-rich phone with Polycom HD Voice technology
- Make simple and fast (one-touch) calls. Easy access to voice, video and applications with a single touch
- Deliver a business-grade experience with one personalized device
- Access business information at-a-glance
- Increase remote collaboration, build relationships and view body language
- Enable innovative third-party applications through a highly customizable Polycom XML API
- Achieve faster decisions making with the ability to integrate communications into business processes

Anixter No. Vendor No. Description

390511 2200-18061-025

Polycom WX 1500 six-line business media phone with video capability and HD voice

CX5000

POLYCOM



Easily add group video collaboration to Microsoft Office Live Meeting 2007 and Microsoft Office Communications Server 2007

- Delivers a unique, engaging 360-degree group video experience
- Brings video, voice, and content together into one seamless interactive session
- Immediately enhance team collaboration which helps you realize a fast ROI
- Enables faster and more effective decision making, improved interaction and lower costs



Multimedia Videoconferencing

HDX 8000 Series

POLYCOM



For organizations migrating to high-definition video and audio communications, Polycom HDX 8000 series systems provide a flexible and robust solution ideally suited for conference rooms, classrooms and meeting places worldwide.

- Advanced HD video technology offers smooth, natural motion and sharp, clear images for outstanding video in 720p or 1080p
- Polycom StereoSurround technology, Lost Packet Recovery and HD content sharing included
- Supports up to 4M line rate and up to 6M line rate with the Multipoint option
- Supports up to three microphones for larger room environments
- Supports one analog phone line connection of one audio-only participant
- Optional four-way embedded multipoint bridge for greater flexibility and participation
- One-year warranty included
- A minimum of a one-year service agreement is required

Anixter No.	Vendor No.	Description
421809	7200-23150-001	HDX 8000-720, video resolution: 720p
423957	7200-23160-001	HDX 8000-1080, video resolution: 1080p
384778	5150-23912-001	HDX MPPlus Multipoint software option



Key System

LG-Nortel ipLDK-60

LG-NORTEL CO LTD

The LG-Nortel ipLDK-60 combines innovative, flexible architecture with the latest in Voice over IP (VoIP) technology and advanced applications to offer a new type of communications platform for small- and medium-sized businesses.

Designed to support both analog and digital lines, the ipLDK-60 is ideal for businesses that have a mix of technologies; or are planning to transition from analog to digital phones. The system is designed to change with business requirement changes, both in capacity and features.

FEATURES

- Initial capacity: three main cabinet (three analog CO trunks, eight hybrid extensions)
- Cost effective
- Voicemail
- Auto Attendant
- Interactive voice response (IVR)
- IP connectivity
- Conferencing capabilities
- Caller ID
- Short Message Service (SMS) through fixed line
- Optional features enabled through a simple keycode: TAPI inteface, EzPhone, Phontage, IP networking, ezAttendant

IPLDK-60 PRECONFIGURED BUNDLES



Anixter No. Vendor No. 389904 L60-PKG1

389906 L60-PKG2

Description

3x8 main cabinet (three analog CO trunks, eight hybrid extensions) 6x16 main cabinet (six analog CO trunks,

16 hybrid extensions)

PHONE TERMINALS



Anixter No. Vendor No. Description
389914 LDP-6212D BB Digital terminal, 12 programmable keys, dark blue
389917 LDP-6230D BB Digital terminal, 30 programmable keys, dark blue
389919 LDP-6248DSS BB Expansion module, 48 programmable keys, dark blue

Contact your local sales representative to configure a system that is right for you.

Cordless Telephones

AT&T 5.8 GHz Corded/Cordless Answering System Telephone

VTFCH COMMUNICATIONS INC



FEATURES

- 5.8 GHz DSSFH technology
- Fully integrated digital answering system with 25 minutes recording time
- One additional handset and charger included
- Two-line capability
- · Corded base and cordless handset
- Expandable up to eight handsets
- Speakerphone on handset and base
- Two-way page and intercom
- Mute, flash, redial, hold, call transfer, data port
- Headset-compatible
- Caller ID/call waiting capability
- 50 name/number phonebook directory

Anixter No. Vendor No. Description

332560 TL76108 Corded/cordless answering system telephone

398257 TL76008 Cordless expansion handset

'

Long-range Industrial Cordless Phone System

FNGFNIUS

Longest-range cordless phone and two-way radio system for mobility behind a PBX, key system or PSTN lines. Single handset can access land-line, cellular, satellite or VoIP ports.

FEATURES

- Schools set up workgroups up to 32 lines and 90 users to cover indoor and outdoor campuses for improved safety. Two-way radios can be taken off-site for field trips
- Government and public safety talk via two-way radio off-site or during power failures. Rugged housing protects handset from most drops
- Industrial communicate via phone or two-way radio up to 250,000 sq. ft. in a warehouse or manufacturing plant
- Administrative and IT professionals get your calls up to 12 floors in buildings behind a PBX or key system
- Agriculture/public works cover up to 3,000 open acres with phone or two-way radio. Use the external antenna to get the signal above obstacles

For more information contact your local sales office.

Long-range Industrial Cordless Phone and Two-way Radio System

ENGENIUS

FEATURES

- Nine programmable PBX function soft keys
- Built-in two-way radio intercom and broadcast
- Two-way radio is independent of the base so it won't tie up a phone line
- Private, digital, full-duplex two-way radio intercom function, so you can talk and listen at the same time
- Broadcast feature allows handset users to send a half-duplex voice message to "all" handsets, to a "group" (up to nine different groups) or to a "single" handset
- Selectable, vibrate-to-loud ringer for all types of environments
- Expandable up to four lines (one line per base on single-line unit) and 36 handsets (nine handsets per base on single-line unit) and 90 handsets on a single base or eight base units on the four-line multi-base unit
- Call manager lets you control incoming calls
- Each base installs to a single CO line or analog port off a PBX or key system
- Digital spread spectrum with frequency hopping at 100 times per second
- Caller ID with call waiting, directory, transfer, flash, redial and mute
- Three-hour Li-lon battery travel charger
- Desktop handset charger with spare battery slot
- Battery hot-swap capability

Anixter No. Vendor No.

- Auto-power management to save battery life
- 2.5 mm direct headset connection (no adapter needed!)
- Optional long-range external antenna for indoor/outdoor use

DURAFON PRO (4-PORT/4-LINE/MULTIPLE BASE)



Expandable up to eight base units (32 ports) and up to 90 handsets. Supports broadcast through the base unit and DuraWalkie handsets. DuraWalkie is a two-way radio handset only. Speakerphone on both the DuraWalkie and Pro handsets. Optional external antenna to get above machinery, racking or to extend outdoor coverage

Description

minimedi moi	1011401 1101	2000: Iptioi:
332347	DURAFON PRO	Base, handset, battery and charger kit
332348	DURAFON PRO-HC	Additional handset, battery and charger kit
332349	DURAFON PRO-PIA	Base with four handsets, eight batteries,
		four DuraPouches and accessories
332350	DURAFONPROPIB20L	Base with four handsets, eight batteries,
		four DuraPouches, UL-AK20L
		and accessories
341184	DURAFONPROPIB10L	Base with four handsets, eight batteries,
		four DuraPouches, UL-AK10L
		and accessories
332351	DURAWALKIE	Handset, battery and charger kit



Cordless Telephones

DURAFON 1X (1-PORT/1-LINE)



Expandable up to four lines (one line per base) and 36 handsets (nine handsets per base, up to four bases). Optional external antenna to get above machinery, racking or to extend outdoor coverage

Anixter No.	Vendor No.	Description
309555	DURAFON 1X	Base, handset, battery and charger kit
309614	DURAFON 1X-HC	Additional handset, battery and charger kit
309615	DURAFON 1X-BU	Base unit only

DURAFON ACCESSORIES

Available accessories for EnGenius systems

		,
Anixter No.	Vendor No.	Description
309622	DURAPOUCH-EX	DuraPouch with 2 in. utility belt clip
273225	SN-ULTRA-DAN	Nortel/Meridian digital adapter
		single-port unit
309618	DURAFON-BC	Belt clip
309620	DURAFON-BA	Li-lon battery pack
309881	DURAFON-HSA1	Handset antenna - optimal performance
309879	DURAFON-HSA2	Handset antenna - low profile



ADA/TTY Telephones

TTYs (Telecommunications Text Telephones)

WEITBRECHT COMMUNICATIONS

Ultratec TTYs make business and personal communication for the deaf and hard-of-hearing clear and effective by providing a quick and easy link from anywhere in the world to wherever there is a compatible unit. All TTYs operate on standard household current as well as with rechargeable batteries.

For more information contact your local sales office.

Ultratec Supercom 4400

WEITBRECHT COMMUNICATIONS



The most elite nonprinting TTY available with 32 KB memory and other advanced calling features.

FEATURES

- 32 KB memory
- · Memos you can name for easy recall and sending
- Keyboard and memory dialing
- Call progress (display shows whether line is ringing or busy in direct connect)
- ullet Tone-and-pulse dial (including ullet, #, and hook flash)
- Auto ID
- Auto-answer (direct connect)
- · Remote message retrieval
- Busy/redial/wait for response/three-way calling
- Turbo code
- TTY voice announcer
- User-programmable relay voice announcer
- 20-character vacuum fluorescent display
- Rechargeable batteries
- Printer port
- Optional ASCII code

Anixter No. Vendor No. Description 150511 SUPERCOM 4400 White

Ultratec Miniprint 425

WEITBRECHT COMMUNICATIONS



A simple yet sophisticated printing unit with direct connect and some advanced calling features, but no memory.

FEATURES

- Built-in 24-character printer with three selectable print sizes
- Tone/pulse-dial
- Keyboard dialing
- Auto-answer with programmed message ("You have reached an answering machine, please leave a message.")
- Built-in ringer flash
- Auto ID
- Turbo code
- Advanced calling features (wait for response, three-way calling, change to other TTY)

Anixter No. Vendor No. Description 166342 MINIPRINT 425 White

Ultratec Superprint 4425

WEITBRECHT COMMUNICATIONS



The most advanced printing TTY with 32 KB memory and other advanced calling features.

- Built-in 24-character printer with three selectable print sizes
- 32 KB memory
- Memos you can name for easy recall and sending
- Keyboard and memory dialing
- Call progress (display shows whether line is ringing or busy in direct connect)
- Tone-and-pulse dial (including *, # and hook flash)
- Auto ID
- Auto-answer (direct connect)
- Remote message retrieval
- Auto busy/redial/wait for response/three-way calling



ADA/TTY Telephones

- Turbo code
- Time and date
- TTY voice announcer
- User-programmable relay voice announcer
- 20-character vacuum fluorescent display
- Rechargeable batteries
- Optional ASCII code
- Optional large visual display port (includes ASCII)

Anixter No. Vendor No. Description 166340 SUPERPRINT 4425 White

Ultratec Uniphone

WEITBRECHT COMMUNICATIONS



The Uniphone is a telephone for users who are deaf or hard-of-hearing. It is a combination TTY (text telephone) and standard telephone with volume control. This TTY can be used for making voice carry over (VCO) calls. Using this application, you can speak directly to other people and read their typed responses on the display. VCO calls can be made directly through the toll-free relay service or directly between Uniphone users for privacy.

FEATURES

- · Amplified handset to increase volume up to 20 dB
- Adjustable ringer volume
- Hearing aid-compatible handset
- Turbo code for real-time conversations
- Auto ID to automatically alert emergency services (and everyone you call) that you are calling by a TTY
- 48-character LCD display (two lines)
- Timer for call duration
- Built-in ring flasher
- · Color: white

Anixter No. Vendor No. Description

166341 UNIPHONE 1140 With light and auto answer

153078 UNIPHONE 1000 No light



S.M.A.R.T. Self Monitoring and Reporting Technology

GAI-TRONICS



Interfacing to a central computer equipped with GAI-Tronics Telephone Management Application (TMA) monitoring software, the phones perform advanced self-testing to ensure the health and functionality of the emergency communications system.

FEATURES

- Polls up to eight GAI-Tronics S.M.A.R.T. phones simultaneously
- Monitors for stuck buttons, line conditions (current levels), microprocessor self-test and call-in-progress interrupted
- GAI-Tronics S.M.A.R.T. phones will automatically report status to maintenance PC
- Offers visual indicators (GUI) for health status of each phone
- Provides inactive phone reports
- Call-usage reports (provides time, date and length of call)
- · Provides exception reports
- Provides maintenance call reports
- Secured access to TMA via key attached to the PC's USB port
- System uses existing telephone line
- Telephone fault database
- Remote maintenance monitoring
- Offers remote telephone configuration
- Windows-based software application
- Cost-effective telephone maintenance
- System remains fully functional while being monitored
- S.M.A.R.T. GAI-Tronics model numbers: 293-003, 293AL-003, 294AL-003, 297-003, 298-003
- TMA (Telephone Management Application) software sold separately, Model no. 12509-024

For ordering information, contact your local sales representative.

Wall-mount Emergency Telephone

GAI-TRONICS



- One-button call for help
- Auto-dials up to 24 digits
- Bright Safety Yellow housing (Model 293-001) Valox
- Bright Safety Yellow housing (Model 293AL-001) die-cast aluminum
- Finish (Model 293AL-001) polyurethane finish for enhanced durability
- Front panel design maximizes usability, simplifies maintenance
- Large "Palm" activation button standard on all phones
- Standard phone line-powered
- No external power or battery required
- Remote programming
- Password protected
- Auto-answer
- Silent monitoring
- · Auxiliary output activates peripheral equipment
- ADA compliance features standard on all models: features include Braille Help tag and "Call Received" LED
- Tamper-resistant hardware
- Custom colors and silk-screening available
- Model 293-003 and 293AL-003 features S.M.A.R.T. Self Monitoring and Reporting Technology
- Automatic LED light activation; red LED light flashes upon activation, steady when audio is detected (S.M.A.R.T. phones only)
- Extreme operating temperature range (-40°C to +60°C)
- NEMA 3R rated
- FCC registered, UL 60950 Listed and IC certified
- Model 233-001 tamper-resistant screwdriver is required for installation (sold separately)

Anixter No.	Vendor No.	Description
203346	293-001	Emergency telephone
203347	293AL-001	Emergency telephone with aluminum housing
255271	293-003	Emergency telephone with S.M.A.R.T.
258675	293AL-003	Emergency telephone with aluminum housing and S.M.A.R.T.



Wall-mount Emergency Telephone with Keypad

GAI-TRONICS



FEATURES

- One-button call for help
- Auto-dials up to 24 digits
- Bright Safety Yellow Housing, cast aluminum
- Call button with sealed metallic Braille keypad ideal for access control or similar local calls
- Front panel design maximizes usability, simplifies maintenance
- Large "Palm" activation button standard on all phones
- · Standard phone line-powered
- No external power or battery required
- Remote programming
- Password protected
- Auto-answer
- Silent monitoring
- · Auxiliary output activates peripheral equipment
- ADA compliance features standard on all models: features include Braille Help tag and "Call Received" LED
- Tamper-resistant screwdriver hardware
- Custom colors and silk-screening available
- Model 294AL-003 features S.M.A.R.T. Self Monitoring and Reporting Technology
- Automatic LED light activation; red LED light flashes upon activation, steady when audio is detected (S.M.A.R.T. phones only)
- Extreme operating temperature range (-40°C to +60°C)
- NEMA 3R rated
- FCC registered, UL 60950 Listed and IC certified
- The Model 233 tamper-resistant screwdriver is required for installation (sold separately)

Anixter No. Vendor No.

203348 294AL-001 Wall-mount emergency telephone **294AL-003** Wall-mount emergency telephone

with S.M.A.R.T.

Description

Flush-mount Emergency Telephone

GAI-TRONICS



FEATURES

- One-button call for help
- Auto-dials up to 24 digits
- 14 gauge brushed stainless steel finish
- Front panel design maximizes use ability, simplifies maintenance and allows customization
- Large "Palm" activation button standard on all phones
- Standard phone line-powered
- No external power or battery required
- Remote programming
- Password protected
- Auto-answer
- Silent monitoring
- Auxiliary output activates peripheral equipment
- ADA compliance features standard on all models: features include Braille Help tag and "Call Received" LED
- Tamper-resistant hardware
- Custom colors and silk-screening available
- Model 297-003 features S.M.A.R.T. Self-Monitoring and Reporting Technology
- Automatic LED light activation; red LED light flashes upon activation, steady when audio is detected (S.M.A.R.T. phones only)
- Extreme operating temperature range (-40°C to +60°C)
- NEMA 3R rated
- FCC registered, UL 60950 Listed and IC certified
- Model 233-001 tamper-resistant screwdriver is required for installation (sold separately)

Anixter No. Vendor No. Description

203349 297-001 Flush-mount emergency telephone **258670** 297-003 Flush-mount emergency telephone

with S.M.A.R.T.



Flush-mount Emergency Telephone with Keypad

GAI-TRONICS



FEATURES

- One-button call for help
- Auto-dials up to 24 digits
- 14 gauge brushed stainless steel finish
- Call button with sealed metal Braille keypad ideal for building access or local calls
- Front panel design maximizes usability, simplifies maintenance
- Large "Palm" activation button standard on all phones
- Standard phone line-powered
- No external power or battery required
- Remote programming
- Password protected
- Auto-answer
- Silent monitoring
- · Auxiliary output activates peripheral equipment
- ADA compliance features standard on all models: features include Braille Help tag and "Call Received" LED
- Tamper-resistant hardware
- Custom colors and silk-screening available
- Model 298-003 features S.M.A.R.T. Self Monitoring and Reporting Technology
- Automatic LED light activation; red LED light flashes upon activation, steady when audio is detected (S.M.A.R.T. phones only)
- Extreme operating temperature range (-40°C to +60°C)
- NEMA 3R rated
- FCC registered, UL 60950 Listed and IC certified
- The Model 233 tamper-resistant screwdriver is required for installation (sold separately)

Anixter No. Vendor No. Description

203350 298-001 Flush-mount emergency telephone

with keypad

258671 298-003 Flush-mount emergency telephone with

keypad and S.M.A.R.T.

VoIP Flush-mount Emergency Telephone

GAI-TRONICS



GAI-Tronics' hands-free VoIP flush-mount telephone is designed to provide direct point-to-point communications between personnel throughout a facility over existing Internet protocol LAN. The VoIP telephone features real-time alarm reporting that enables system supervisors to monitor the phone's activity and address caller's needs or maintenance issues immediately.

FEATURES

- No additional interface required
- Web page configuration
- Real-time alarm reporting via e-mail
- Power over Ethernet or alternative 48 V DC supply
- SIP compatible
- RJ45 LAN or WAN direct connection
- Automatic call divert (rollover), via memory list
- Four inputs and two outputs per phone
- ADA compliance features: Braille "HELP" label and "Call Received" LED indicator
- One-button call for help
- 14 gauge brushed stainless steel finish
- Remote programming
- Password protected
- Auto-answer
- Silent monitoring
- Auxiliary output activates peripheral equipment
- Tamper-resistant hardware
- NEMA 3R rated
- Compliance to Standards FCC CRF 47 Part 15
- Model 233-001 tamper-resistant screwdriver is required for installation (sold separately)

Anixter No. Vendor No. Description

368217 297-700 Flush-mount VoIP emergency telephone

VolP Flush-mount Emergency Telephone with Keypad

GAI-TRONICS



FEATURES

- No additional interface required
- Web page configuration
- Real-time alarm reporting via e-mail
- Power over Ethernet or alternative 48 V DC supply
- SIP compatible
- RJ45 LAN or WAN direct connection
- Automatic call divert (rollover), via memory list
- Four inputs and two outputs per phone
- ADA compliance features: Braille "HELP" label and "Call Received" LED indicator
- One-button call for help
- 14 gauge brushed stainless steel finish
- Call button with sealed metal Braille keypad ideal for building access or local calls
- Remote programming
- Password protected
- Auto-answer
- Silent monitoring
- · Auxiliary output activates peripheral equipment
- Tamper-resistant hardware
- NEMA 3R rated
- Compliance to Standards FCC CRF 47 Part 15
- Model 233-001 tamper-resistant screwdriver is required for installation (sold separately)

Anixter No. Vendor No. Description

368235 298-700 Flush-mount VoIP emergency telephone

VolP Wall-mount Emergency Telephone

GAI-TRONICS



GAI-Tronics' hands-free VoIP wall-mount telephone is designed to provide direct point-to-point communications between personnel throughout a facility over existing Internet protocol LANs. The VoIP telephone features real-time alarm reporting that enables system supervisors to monitor the phones' activity and address caller's needs or maintenance issues immediately.

FEATURES

- No additional interface required
- · Web page configuration
- Real-time alarm reporting via e-mail
- Power over Ethernet or alternative 48 V DC supply
- SIP compatible
- RJ45 LAN or WAN direct connection
- Automatic call divert (rollover), via memory list
- Four inputs and two outputs per phone
- ADA compliance features: Braille "HELP" label and "Call Received" LED indicator
- One-button call for help
- Bright Safety Yellow Housing (Model 293-700) Valox
- Bright Safety Yellow Housing (Model 293AL-700) cast aluminum
- Remote programming
- Password protected
- Auto-answer
- Silent monitoring
- Auxiliary output activates peripheral equipment
- Tamper-resistant hardware
- NEMA 3R rated
- Compliance to Standards FCC CRF 47 Part 15
- Model 233-001 tamper-resistant screwdriver is required for installation (sold separately)

Anixter No. Vendor No. Description

368226293-700Wall-mount VoIP emergency telephone368229293AL-700Wall-mount VoIP emergency telephone with

aluminum housing



VolP Wall-mount Emergency Telephone with Keypad

GAI-TRONICS



FEATURES

- No additional interface required
- Web page configuration
- Real-time alarm reporting via e-mail
- Power over Ethernet or alternative 48 V DC supply
- SIP compatible
- RJ45 LAN or WAN direct connection
- Automatic call divert (rollover), via memory list
- Four inputs and two outputs per phone
- ADA compliance features: Braille "HELP" label and "Call Received" LED indicator
- One-button call for help
- Bright Safety Yellow Housing, cast aluminum
- Call button with sealed metal Braille keypad ideal for building access or local calls
- Remote programming
- Password protected
- Auto-answer
- Silent monitoring
- Auxiliary output activates peripheral equipment
- Tamper-resistant hardware
- NEMA 3R rated
- Compliance to Standards FCC CRF 47 Part 15
- Model 233-001 tamper-resistant screwdriver is required for installation (sold separately)

Anixter No. Vendor No. Description

368266 294AL-700 VoIP wall-mount emergency telephone

with keypad

Emergency Phone Surface-mount Enclosures



FEATURES

- Accommodates GAI-Tronics' flush-mount emergency phones in surface-mount applications
- Non-corrosive aluminum construction
- Polyurethane finish for enhanced durability
- Offered in OSHA Yellow (236YL), Safety Red (236RD) or Standard Black (236BK)
- Telephone handset "Icon" label on side panels clearly indicates function to potential users
- Raised mounting bosses on rear for irregular surfaces
- USOC RJ11 connection terminal
- · Can be pole-mounted using GAI-Tronics' Model 231-001 kit
- Custom colors and labeling available

Anixter No. Vendor No. Description 236-001YL 246955 Yellow 236-001RD Safety Red 258676 236-001BK Standard Black 258677

Emergency Stanchion

GAI-TRONICS



FEATURES

- Architectural bronze color is aesthetically pleasing in all settings
- "Emergency" graphic on sides for high visibility
- Accommodates GAI-Tronics' flush-mount emergency phones
- Front panel light illuminates the telephone for night time use
- Durable powder-coated finish
- ADA-compliant
- Accommodates 530 Series beacon (sold separately)
- 3/16 in. thick cold rolled steel construction
- Height, 9.5 ft.
- · Weight, 200 lb.
- Only UL 1598 Listed stanchion for outdoor installations on the market
- Solar, cellular, RF configurations available

Anixter No. Vendor No. Description 246953 234 **Emergency stanchion**



- Houses GAI-Tronics' 290 series flush panel telephones (sold separately)
- Uses GAI-Tronics 530 series strobe (sold separately)
- Broadcast audio access via 600 ohm audio pair input
- Addressable via DTMF (telephone or RF application)
- · Remote volume control via DTMF
- Programmable output control for strobe or device activation during alarm
- Backup battery included (2.8 Ah) for one hour backup at full output
- PC programmable
- ADA-compliant
- UL 1598 Listed for Outdoor Installation
- Note RF (UHF and VHF) input also available. Contact us for details

Anixter No. Vendor No. Description 393982 234SBA4T

Stanchion broadcast assembly.

600 ohm, 4-speaker

FEATURES

GAI-TRONICS

- Bright Safety Yellow color; easily spotted in crisis situation
- "Emergency" graphic on sides for visibility

Emergency Wall-mount Stanchion

- Accommodates GAI-Tronics' flush-mount emergency phones
- Wall-mounted design requires minimal space: easily handicapped-accessible
- Durable aluminum construction with powder-coated finish
- Front panel light illuminates the telephone for night time use
- ADA-compliant
- Accommodates 530 Series beacon (sold separately)
- Easy installation via detachable back-plate
- Only UL 1598 Listed stanchion for outdoor installations on the market
- Custom colors and graphics available

Anixter No. Vendor No. Description

246954 234WM-202 Emergency wall-mount stanchion

Emergency Stanchion Broadcast Assembly

GAI-TRONICS



GAI-Tronics' Stanchion Broadcast Assembly provides high-quality, extremely intelligible voice and tone public address. Each assembly is addressable via DTMF signaling and is capable of being programmed for up to eight (8) addresses, allowing easy zoning of the public address system. An integral part of GAI-Tronics' campus public address system, the 234SBA is extremely versatile in that it can be accessed from GAI-Tronics' model ACC2500 Audio Control Center, an existing telephone network, radio system, or all three. The broadcast functionality operates completely separate from the two-way device installed in the stanchion. The rugged, submersible speakers will take anything Mother Nature can throw at them.

FEATURES

- Architectural bronze powder epoxy finish with white emergency graphics
- 360° coverage at 110 dB SPL at 1 meter (4-speaker installation)
- 114 in. H with strobe lens, 3/16 gauge cold rolled steel
- Light housing (120 V AC) assembly

Emergency Stanchion Broadcast Module

GAI-TRONICS



GAI-Tronics' Stanchion Broadcast Module (SBM) installs on top of a Model 234 Stanchion to provide an easy and cost-effective public address upgrade of existing equipment. Each assembly is addressable via DTMF signaling and is capable of being programmed for up to eight (8) addresses, allowing easy zoning of the public address system. An integral part of GAI-Tronics' campus public address system, the SBM is extremely versatile in that it can be accessed from GAI-Tronics' model ACC2500 Access Control Center, an existing telephone network, radio system, or all three. The broadcast functionality operates completely separate from the two-way device installed in the stanchion. The rugged, submersible speakers will take anything Mother Nature can throw at them.

- Architectural bronze powder epoxy finish
- 360° coverage at 110 dB SPL at 1 meter (4-speaker installation)
- 18 in. H. 3/16 gauge cold rolled steel
- Broadcast audio access via 600 ohm audio pair input
- Addressable via DTMF (telephone or RF application)
- Remote volume control via DTMF
- Programmable output control for strobe or device activation during alarm
- Backup battery included (2.8 Ah) for one hour backup at full output
- PC programmable
- Customer uses existing strobe and lens assembly for additional savings
- Note RF (UHF and VHF) input also available. Contact us for details

Anixter No. Vendor No. 393983

234SBMS4T

Description Stanchion broadcast module.

600 ohm, 4-speaker



Emergency/Door Telephones

Emergency Beacons

GAI-TRONICS



GAI-Tronics' "Blue Light" LED strobe constant-on, blue "glow" easily identifies the nearest emergency phone location, even in bright sunlight. The LED technology greatly reduces maintenance costs (no bulbs to replace) and the low power consumption provides energy savings.

FEATURES

- High visibility, even in daylight
- Provides an integral blue LED tower with constant-on and flashing operations when telephone is activated
- 100,000 LED life (approx. 10 years)
- Secondary contact output for activation of external auxiliary equipment
- Low operating temperature
- Weatherproof design, rated NEMA 3R (upright installation only)
- Die-cast aluminum base
- UL Listed

 Anixter No.
 Vendor No.
 Description

 355895
 530-001
 Blue, 120 V AC unit

 258679
 531A
 Blue, 24 V DC unit

Wireless Addressable Amplified Speaker

GAI-TRONICS



GAI-Tronics' Addressable Amplified Speakers are suitable for any permanent or temporary public address paging application. With its built-in amplifier circuit, rated 8 watts at 12 V DC, there is no need for a separate power amplifier, increasing system reliability by removing the single point of failure and creating a distributed amplified system. The addressable amplified speaker performs a self adjustment of its output volume based on the surrounding ambient noise level.

FEATURES

- Built-in 8 watt amplifier for public address applications
- Radio control (UHF/VHF) and 600-ohm (telephone line) input models
- Addressable (individual, zoned, all-page) via DTMF
- Addressable output control

- Remote DTMF volume control, 80-116 dB SPL
- 12 V DC input power
- Low battery alert
- External long-life battery option
- Solar panel power option
- Battery backup option
- · Surface or pole mounting
- Rainproof rating

 Anixter No.
 Vendor No.
 Description

 319906
 13353
 600-ohm input

 319907
 13363
 VHF, 154 - 174 MHz

 319908
 13373
 UHF, 450 - 470 MHz

ADA-compliant Emergency Phones

VIKING ELECTRONICS



The 1600A Series ADA-compliant emergency phones are designed to provide quick and reliable hands-free communications for any standard analog telephone line or analog phone system station port. All 1600A Series phones meet ADA requirements for elevator/emergency telephones, and can be programmed from any touch-tone phone. The phones can dial up to five programmable emergency numbers, as well as two central station numbers. In addition, the E-1600-20A features a second "Info" button that will dial up to three nonemergency numbers. The 1600A Series phones can be programmed to automatically deliver a digital announcement to identify the location of the emergency call. Alternatively, a DTMF touch-tone code may also be delivered. A "Call Connected" LED can be initiated manually or automatically. All programming parameters, including phone numbers and location numbers, are stored in nonvolatile memory. All units are phone line-powered, requiring no batteries or external power, and are compatible with common central station monitoring equipment. For outdoor or harsh environments, select 1600A Series phones are available with Enhanced Weather Protection (EWP). EWP products feature rubber gaskets and boots, hand-soldered silicon-sealed connections, gel-filled butt connectors, as well as urethane potted circuit boards with weather-sealed, field-adjustable trim pots and DIP switches for easy on-site programming.

- Meets ADA requirements for emergency phones
- Can automatically light the "Call Connected" LED for the hearing impaired
- Transmits a unique location I.D. code or voice announcement
- Grade 2 Braille label for the visually impaired
- Nonvolatile digital voice announcer with 16 seconds of voice memory
- Advanced call progress detection
- Hands-free operation
- Phone line-powered
- Nonvolatile memory (no batteries required)
- Touch-tone or pulse dialing
- Dials up to five emergency numbers



- E-1600-20A can dial up to three nonemergency "Info" numbers
- Cycles through backup emergency and nonemergency numbers on busy or no-answer
- Optional Enhanced Weather Protection (EWP)
- Hangs up on CPC, silence, busy signal, dial tone, time-out or touch-tone command
- Programmable to auto-answer on incoming calls
- Remotely programmable
- Extended temperature range (-15°F to 130°F)
- Seven different chassis or board only is available
- Available in a 42 in. tall tower phone model E-1600A-BLT-EWP or E-1600A-BLT2EWP
- Central station monitoring capability (dials two numbers)
- · Separate central station voice speed-dial number
- Optional PB-100 polling system available
- Ontional BLK-3-FWP strobe light kit available

Optional BLK	-3-EWP strobe light	kit available
Anixter No.	Vendor No.	Description
177498	E-1600A	ADA-compliant emergency phone, red
243942	E-1600-20A	ADA-compliant emergency phone with
		info button
243944	E-1600-20A-EWP	ADA-compliant emergency phone with info
		button and Enhanced Weather Protection
254828	E-1600-02A	ADA-compliant emergency phone,
		stainless steel
274177	E-1600A-EWP	ADA-compliant emergency phone with
		Enhanced Weather Protection, red
274179	E-1600-03B	ADA-compliant emergency phone,
		stainless steel
274181	E-1600-03B-EWP	ADA-compliant emergency phone, stainless
	- 1000 151	steel with Enhanced Weather Protection
274182	E-1600-45A	ADA-compliant emergency phone, yellow
274183	E-1600-45A-EWP	ADA-compliant emergency phone with
074104	F 1000 F04	Enhanced Weather Protection, yellow
274184	E-1600-50A	ADA-compliant emergency phone, for retrofit
274185	E-1600-50A-EWP	ADA-compliant emergency phone with
074100	F 1000 FFA	Enhanced Weather Protection, for retrofit
274186	E-1600-55A	ADA-compliant emergency phone, for build-in applications
274187	E-1600-55A-EWP	ADA-compliant emergency phone for build-in
2/4/0/	E-1000-33A-EWF	applications with Enhanced
		Weather Protection
274188	K-1600-EHFA	ADA-compliant emergency phone for
214100	N 1000 LIIIN	elevator, red
366777	E-1600-30A	ADA-compliant emergency phone,
	_ 1000 00	stainless steel
366778	E-1600-30A-EWP	ADA-compliant emergency phone, stainless
		steel with Enhanced Weather Protection
366779	E-1600-60A	ADA-compliant emergency phone, blue
366780	E-1600-60A-EWP	ADA-compliant emergency phone, blue with
		Enhanced Weather Protection

Hands-free Doorboxes

VIKING ELECTRONICS









The W-1000 (flush-mount), W-2000A (surface-mount) and W-3000 (flush-mount) and W-3005 (flush-mount with camera) doorboxes are designed to be installed on the unused telephone line input of nearly any phone system. One or two doorboxes can also share an existing residential phone line when used in combination with a C-1000B doorbox controller.

For outdoor or harsh environments, the W-1000, W-2000A and W-3000 and W-3005 are available with Enhanced Weather Protection (EWP). The W-1000-EWP, W-2000A-EWP, W-3000-EWP and W-3005-EWP feature rubber gaskets and boots, closed cell foam gasketing, hand-soldered silicon-sealed connections, anticorrosive gel-filled butt connectors, as well as urethane-encapsulated circuit boards with internally sealed, field-adjustable trim POTS and DIP switches.

- High-output speaker amplifier with volume adjustment POT
- Microphone volume adjustment POT
- 24 V talk battery
- 20 Hz ring generator (3.0 REN ring load maximum)
- Selectable number of rings
- Extended operating temperature range 15°F to 130°F
- Compact 45° terminal strip for easy wiring
- Optional Enhanced Weather Protection (EWP)
- W-3005 features a built-in high-resolution color video camera with wide viewing angle, tilt/swivel adjustments and wide operating temperature range

Anixter No.	Vendor No.	Description
185421	W-1000	Flush-mount, aluminum, black
122257	W-2000A	Surface-mount, plastic, light gray
219508	W-3000	Flush-mount, stainless steel
274171	W-1000-EWP	Flush-mount, aluminum, black with Enhanced Weather Protection
274172	W-2000A-EWP	Surface-mount plastic, light gray with Enhanced Weather Protection
274173	W-3000-EWP	Flush-mount, stainless steel with Enhanced Weather Protection
366782	W-3005	Flush-mount, stainless steel with video camera
366783	W-3005-EWP	Flush-mount, stainless steel with video camera and Enhanced Weather Protection



Emergency/Door Telephones

Hands-free Phone with Keypad

VIKING ELECTRONICS





The K-1700-3 provides a tough and attractive hands-free phone for apartment and residential door entry or applications requiring a vandal-resistant speakerphone. When the "Call" button is pressed, the K-1700-3 returns a dial tone. The keypad may then be used to dial any number. If no touch-tone is entered within eight seconds, CPC is detected, a busy signal is detected, or the programmable maximum call time has elapsed, the K-1700-3 will automatically disconnect. Model K-1705-3 has all of the same features as the K-1700-3 and also includes a color video camera. The K-1700 and K-1705 series entry phones are available in two attractive finishes: "brushed stainless steel" and "oil rubbed bronze." For outdoor or harsh environments, the K-1700-3 and K-1705-3 are both available with Enhanced Weather Protection (EWP). EWP products feature rubber gaskets and boots, closed cell foam gasketing, hand-soldered silicon-sealed connections, anticorrosive gel-filled butt connectors, as well as urethane-encapsulated circuit boards with internally sealed, field-adjustable trim POTS and DIP switches.

FEATURES

- Vandal-resistant features: 14 gauge, louvered, stainless steel faceplate with stainless steel speaker/mic screen, heavy-duty metal keypad and call button
- Available in two standard faceplate finishes: brushed stainless steel or oil rubbed bronze
- Model K-1705-3 features a built-in high-resolution color video camera with wide viewing, tilt/swivel adjustments and wide operating temperature range
- Optional Enhanced Weather Protection (EWP)
- Yellow "in use" LED
- · Volume adjustments for microphone and speaker
- Advanced call progress detection: disconnects on busy signal, return to dial tone, CPC reorder tone, maximum call time out and selectable silence time out
- Selectable auto-answer feature
- Selectable push-button disconnect
- Zinc-plated steel rough-in box with two 3/4 in. conduit knockouts
- Optional VE-6x7 surface-mount box available
- Selectable maximum call time
- Selectable momentary or continuous touch-tone output
- Selectable VOX switching speed
- Model K-1705-3 has an integral high-resolution color video camera with wide viewing angle

Anixter No.	Vendor No.	Description
244059	K-1700-3	Hands-free phone with keypad
274176	K-1700-3-EWP	Hands-free phone with keypad and Enhanced

Weather Protection
353559 K-1705-3 Video entry phone with keypad

Anixter No.	Vendor No.	Description
353563	K-1705-3-EWP	Video entry phone with keypad and Enhanced Weather Protection
393146	K-1700-3-BN	Hands-free phone with keypad, oil rubbed bronze
393147	K-1700-3-BN-EWP	Hands-free phone with keypad, oil rubbed bronze and Enhanced Weather Protection
393149	K-1705-3-BN	Video entry phone with keypad, oil rubbed bronze
393151	K-1705-3-BN-EWP	Video entry phone with keypad, oil rubbed bronze and Enhanced Weather Protection

Hands-free Speakerphone with Dialer

VIKING ELECTRONICS





The E-30 hands-free phone is designed to provide quick and reliable hands-free communications and can be connected directly to a C.O. line or analog PABX/KSU station. The E-30 features nonvolatile memory, a built-in five-number dialer, and intelligent call progress detection for automatic hang-up when the call is completed. Model E-35 has all of the same features as the E-30, and also includes a color video camera

The E-30-EWP shares all of the features of the E-30 in addition to Enhanced Weather Protection (EWP) for installation in harsh environments. EWP products feature rubber gaskets and boots, hand-soldered silicon-sealed connections, gel-filled butt connectors, as well as urethane potted circuit boards with weather sealed, field-adjustable trim pots and DIP switches for easy on-site programming.

- · Hands-free operation
- Phone line-powered
- Vandal-resistant stainless steel faceplate with heavy-duty metal call button
- Model E-35 features a built-in high-resolution color video camera with wide viewing, tilt/swivel adjustments and wide operating temperature range
- Nonvolatile memory (no batteries required)
- Touch-tone or pulse dialing
- Programmable to dial up to five numbers on busy or ring no answer
- Red off-hook LED indicator
- Hangs up on CPC, silence, busy signal, return to dial tone, time out or a touch-tone command
- Programmable to auto-answer on incoming calls



•	Remotely	programmable
---	----------	--------------

- Extended temperature range (-15°F to 130°F)
- Flush-mountable using included plastic rough-in box
- Shown in optional VE-5x5 surface-mount backbox

Anixter No.	Vendor No.	Description
209574	E-30	Hands-free phone with auto dialer
254830	E-30-EWP	Hands-free phone with auto dialer and
		Enhanced Weather Protection
353570	E-35	Video entry phone with auto dialer
353574	E-35-EWP	Video entry phone with auto dialer and
		Enhanced Weather Protection

Compact Video Entry Phones

VIKING ELECTRONICS



The E-50 Series video entry phones are compact, weather- and vandal-resistant speakerphones designed to provide two-way, hands-free audio communication and color composite video of who is at your door or gate. The E-50's compact size allows it to be mounted in a standard single-gang electrical box. The E-50 is available in five different attractive finishes to match your door hardware, light fixtures, etc. Replacement E-50 faceplates (PNL50) can be purchased separately and are available in all five standard finishes. The E-50's blue LED continually provides light for locating the push button in dark locations, dims to indicate off hook and flashes during incoming ring. The E-50 entry phones can share a single phone line with house or small business telephones when used with a Viking Model C-200 or C-250 or C-2000B entry phone controller. The E-50 entry phones can also be connected to an unused analog station port (programmed for ringdown) on a phone system or connected directly to a telephone line when used with a Viking Model K-1900-5 or K-1900-30 auto dialer. The E-50 features a built-in high-resolution color video camera, microphone and speaker volume controls, selectable auto answer for monitoring and intelligent call progress detection for automatic hang-up when the call is completed. For extreme outdoor environments or corrosive atmospheres, the E-50 Series is available with Enhanced Weather Protection (EWP).

Anixter No.	Vendor No.	Description
353541	E-50-SS	Stainless steel video entry phone
353551	E-50-SS-EWP	Stainless steel video entry phone with Enhanced Weather Protection
373609	E-50-BN	Oil rubbed bronze video entry phone
373610	E-50-BN-EWP	Oil rubbed bronze video entry phone with Enhanced Weather Protection
373611	E-50-BK	Satin black video entry phone





Industrial Telephones

Auto-dial Telephones

GAI-TRONICS



GAI-Tronics' industrial telephones are designed for those applications where standard telephones are not environmentally suitable. The auto-dial telephones are programmed to automatically dial when the handset is taken off hook. The phones have a detachable programming keypad, preventing unauthorized tampering of the pre-programmed phone number.

FEATURES

- Anti-corrosive housing
- Non-moveable hookswitch
- Hearing aid compatible (HAC)
- · Volume control handset
- Noise-canceling microphone
- Industrial strength Hytrel handset cord resists up to 250 lb. of pull strength
- Auto dials up to 31 digits
- Extreme operating temperature range (-40°C to +60°C)
- NEMA 3R rated
- FCC registered, UL 60950 Listed and IC certified Anixter No. Vendor No. Description

141122 257-001 Auto-dial telephone

Indoor/Outdoor Industrial Telephones

GAI-TRONICS



GAI-Tronics' indoor and outdoor industrial telephones are designed for applications where standard telephones are not environmentally suitable. The telephones include standard items such as a proximity detecting hookswitch with no moving parts and a sealed keypad to keep out dust, dirt and moisture. Typical applications include public areas, plant entrances, college campuses, airports, commercial locations, parking garages and amusement parks.

FEATURES

- · Anti-corrosive enclosure
- Non-moveable hookswitch
- Sealed metallic Braille keypad

- Hearing aid compatible (HAC)
- · Volume control handset
- Noise-canceling microphone
- Industrial strength Hytrel handset cord resists up to 250 lb. of pull strength
- Extreme operating temperature range (-40°C to +60°C)
- NEMA 3R rated
- FCC registered, UL 60950 Listed and IC certified

Anixter No. Vendor No.

141123 246-001 Indoor version
142507 256-001 Outdoor version

128694 256-001SK Outdoor version with spring kit

Hazardous Area Telephones

GAI-TRONICS





GAl-Tronics' Hazardous Area Telephones utilize an "intrinsically-safe" design; this configuration limits the power to the telephone to a low enough level that a hazardous condition cannot occur. These telephones are significantly less expensive, more feature-rich and easier to maintain than the old explosion proof design utilized by other manufacturers.

FEATURES

- Replaces explosionproof telephones without replacing system cable in most applications
- Weather-resistant, anticorrosive design
- "Shrill-type" penetrating ringer
- Noise-canceling microphone
- Low sidetone for noisy environments
- Switchable power supply 110 V AC/220 V AC
- Industrial strength Hytrel handset cord resists up to 250 lb. of pull strength
- Sealed metallic Braille keypad
- Hearing aid compatible (HAC)
- Extreme operating temperature range (-40°C to +60°C)
- NEMA rated 3R
- FCC registered, C(UL) / UL listed

Anixter No. Vendor No. Description
326772 261-001 Indoor version
326771 271-001 Outdoor version



Industrial Telephones

Clean Telephones

GAI-TRONICS



The GAl-Tronics Clean Phone unit's hands-free operations are ideal for clean rooms and other sterile environments. The advanced software makes this phone sophisticated enough to handle complex operations while maintaining ease of use. Visual graphics are printed on the reverse side of the overlay to prevent particulate shedding and ensuring longevity. The Clean Phone is ideal for semiconductor facilities, pharmaceutical plants and hospitals. The Model 40411-004 power supply (sold separately) is required for installation.

FEATURES

- · Completely smooth front panel with sealed overlay keeps phone particulate-free
- Easy to clean and resistant to chemical wash down
- Two auto-dial numbers for quick communication at the touch of a button
- Auto-answer option allows clean room or operating room personnel to answer calls without leaving their stations
- "Flash" button allows phone to use all features of a PBX system
- Oversized buttons allow easy operation for gloved hands
- Button functions are clearly indicated for ease of use
- Requires Model 40411-004 power supply (sold separately)

 Anixter No.
 Vendor No.
 Description

 141121
 295F
 Flush-mount version

 141120
 295W
 Wall-mount version

 354676
 40411-004
 Power supply

Tough Phone

GAI-TRONICS



The "Tough Phone" was developed for public and industrial areas requiring a virtually indestructible telephone. Each "Tough Phone" is housed in a 1/4 in. thick, sand-cast aluminum enclosure, coated with an exterior polyurethane finish. Standard equipment includes a spring return door, 15 in. lanyard armored cord resistant up to 800 lb. of pull strength, chrome-plated keypad and proximity hookswitch. The Model 233-001 tamper-resistant screwdriver is required for installation.

FEATURES

- Super-rugged cast aluminum enclosure is anti-corrosive
- Weather-resistant and vandalproof design
- Non-moveable chrome-plated hookswitch
- Lanyard embedded armored handset cord resists up to 800 lb. of pull strength
- Sealed metallic Braille keypad (226-001)
- Sealed handset
- Hearing aid compatible (HAC)
- Volume control handset
- Noise-canceling microphone
- Autodial (227-001) automatically dials up to 31 digits when handset is taken off-hook
- Tamper-resistant hardware
- NEMA 3R rated
- Extreme operating temperature range (-40°C to +60°C)
- FCC registered UL 60950 Listed and IC certified

 Anixter No.
 Vendor No.
 Description

 128692
 226-001
 Standard

 128691
 227-001
 Autodial

Industrial Telephone

GAI-TRONICS



GAl-Tronics' Industrial Telephones perform in environments too tough for standard telephones. Standard equipment includes a 29 in. lanyard armored cord resistant up to 800 lb. of pull strength, chrome-plated keypad and proximity hookswitch. The 270 Series design enhances the flexibility to flush-mount into the wall or surface-mount (using 236 Series wall enclosure). The Model 233-001 tamper-resistant screwdriver (sold separately) is required for installation.

FEATURES

- 14 gauge brushed stainless steel
- Weather-resistant and vandalproof design
- Non-moveable chrome-plated hookswitch
- 29 in. lanyard embedded armored handset cord resists up to 800 lb. of pull strength
- Sealed metallic keypad (276-001)
- Sealed handset
- Hearing aid compatible (HAC)
- Volume control handset
- Noise-canceling microphone
- Auto-dial (277-001) automatically dials up to 31 digits when handset is taken off-hook
- Tamper-resistant hardware
- Extreme operating temperature range (-40°C to +60°C)
- NEMA 3R rated
- FCC registered, UL 60950 Listed and IC certified

Anixter No. Vendor No. Description
246956 276-001 Industrial telephone



Industrial Telephones

Industrial Telephone Enclosures

GAI-TRONICS



FEATURES

- Glass-reinforced polyester enclosure
- Equipped with a No. 630 mounting plate to accommodate a standard wall telephone
- Weather-resistant design
- Suited for harsh outdoor use

Anixter No.	Vendor No.
094987	255-001
127649	255-001LD
161781	255-001SK

Description

Enclosure with 630A mounting plate Enclosure with keylock door Enclosure with spring-loaded door

Hot-line Phones

VIKING ELECTRONICS



The K-1900 Series of hot-line phones are programmable to dial a 1- to 32-digit telephone number each time the phone's handset is lifted. The products may be programmed to touch-tone or pulse-dial and will not dial on incoming calls. The K-1900 Series phones are available in a desk or wall chassis, as well as in a vandal-resistant stainless steel panel phone configuration. For outdoor or harsh environments, the K-1900-7 is available with (EWP) Enhanced Weather Protection.

FFATURES

- Phone line-powered
- Hearing aid-compatible amplified handsets
- Rotary handset volume control
- 1- to 32-digit programmable speed-dial number
- Touch-tone and 10/20 pps pulse dialing
- Nonvolatile memory (no batteries required)
- Restricts fraudulent calls from hand-held dialers
- K-1900D/W-2 available in red or ash
- Operates on a C.O. line or analog PABX/KSU extensions
- Ring detection (will not dial on incoming calls)
- Programmable security code to enter programming mode
- Touch-tone programmable

rough come p	0	
Anixter No.	Vendor No.	Description
172921	K-1900D-2	Hot-line phone, red, desk version
274189	K-1900D-2 ASH	Hot-line phone, ash, desk version
168883	K-1900W-2	Hot-line phone, red, wall version
274191	K-1900W-2 ASH	Hot-line phone, ash, wall-mount
244531	K-1900-7	Hot-line phone, stainless steel vandal-resistant
339087	K-1900-7-EWP	Hot-line phone, stainless steel vandal-resistant with Enhanced Weather Protection



Valcom System Design Service - Fast, Easy and Free!!!

VALCOM INC

Valcom's world-class system design assistance is available at 1-800-825-2661. For detailed product information, visit www.valcom.com.

Valcom MultiPath Systems

VALCOM INC

Valcom MultiPath systems offer high-quality internal communications and a multitude of features that are easily configured to suit the most advanced requirements. MultiPath systems include user-friendly administration software that allows end-users to easily manage their voice communications system daily, weekly, monthly or annually over their LAN/WAN network. Valcom MultiPath systems satisfy the sophisticated communications needs of large businesses such as airports, hospitals, industrial facilities, medical facilities, confinement centers, warehouses and schools.

ONE-WAY PAGING SYSTEMS WITH POWER *

*Expansion of systems may require additional power supplies.

#Power supply(ies) are included for headend equipment, additional power supplies required for amplified speakers

Anixter No.	Vendor No.	Description
320130	V-PW24	24 zones, expandable to
		72 zones, wall-mount
320131	V-PW48	48 zones, expandable to
		72 zones, wall-mount
320132	V-PR24	24 zones, expandable to
		192 zones, rack-mount
320133	V-PR48	48 zones, expandable to
		192 zones, rack-mount
320134	V-PR72	72 zones, expandable to
		192 zones, rack-mount
320135	V-PR96	96 zones, expandable to
		192 zones, rack-mount

TALK-BACK SYSTEMS WITH POWER *

*Expansion of systems may require additional power supplies.

#Power supply(ies) are included for headend equipment, additional power supplies required for amplified speakers

	pa opoaitoro	
Anixter No.	Vendor No.	Description
320136	V-TW24	24 zones, expandable to
000107	V TW/40	72 zones, wall-mount
320137	V-TW48	48 zones, expandable to
		72 zones, wall-mount
320138	V-TR24	24 zones, expandable to
		192 zones, rack-mount
320139	V-TR48	48 zones, expandable to
		192 zones, rack-mount
320141	V-TR72	72 zones, expandable to
		192 zones, rack-mount
320142	V-TR96	96 zones, expandable to
020172	¥ 11.50	192 zones, rack-mount
		TOL LUIDO, IAUN-IIIUUIIL

ACCESSORIES			
Anixter No.	Vendor No.	Description	
320150	V-CPU4	System CPU card with two V-SLC cards (four links)	
320151	V-TCM	24 point talk-back intercom expansion card	
320152	V-STX	24 point one-way paging expansion card	
320153	V-SLC	SLIC card - telephone interface two circuits	
320154	V-URI	Universal relay interface	
320155	V-SER	Serial card	
320156	V-DSP	Large display package	
320157	V-CLK	Clock control interface package	
339725	V-DCPI	Digital Clock Protocol Interface	
424837	V-CLK2924	Time event scheduling and master clock	
		control correction kit for V-2924A	
320158	V-PDP	Program distribution panel	
320159	V-C6124P	Power supply 6 amp positive 24 V DC	
320160	V-LPT	One-way paging adapter	
320161	V-2972PK	Push button call switch 6 pack	
320162	V-RDP	Rack-mount control panel with	
		AM/FM cassette	
339729	VP-9202	6 A/4 A switching power supply shelf (2U)	
TALK-BACK SI	PEAKER		
Anixter No.	Vendor No.	Description	
320166	V-C806PK	8 in. talk-back ceiling speaker with taps,	
320167	V-WTGY	six per pack 8 in. talk-back wall speaker with taps,	
320107	v-widi	gray/black grille, paintable	
320168	V-CTL	Talk-back 2 ft. X 2 ft. lay-in ceiling speaker	
		with backbox, with taps	
320169	VC-1090-W	Talk-back FlexHorn, white	
320178	VC-1090-GY	Talk-back FlexHorn, gray	
320170	VC-1090-BGE	Talk-back FlexHorn, beige	
424838	V-WGFLEX-2E	Wire cages used with FlexHorns	
MISCELLANEO	OUS PARTS		
Anixter No.	Vendor No.	Description	
320171	VC40R-4	4-position backplane cable	
320172	VC40R-8T	8-position backplane cable	
320173	VC40R-9T	9-position backplane cable	
320174	VC40R-16T	16-position backplane cable	
320177	VCMDM	Modem kit	

Most Valcom MultiPath systems can utilize Category 3/5/5e/6 telecom/datacom infrastructure - resulting in cost-saving installations and expansions, flexibility and reliability.



Voice Products

2 ft. x 2 ft. Lay-in Ceiling Speaker

VALCOM INC



FEATURES

- Easy installation
- No cutting tiles
- Quality speakers for voice and music
- Front-accessible volume control
- White acrylic baked enamel finish
- Integral backbox meets ASTM E84 flame and smoke test

Anixter No.	Vendor No.	Description
421225	V-9022A-2	2 ft. x 2 ft. lay-in ceiling speaker - one way
		(package two per box)
224262	V-9028	2 ft. x 2 ft. lay-in ceiling speaker - dual input
213702	V-9062	2 ft. x 2 ft. lay-in ceiling speaker - talk-back
210375	V-9022	2 ft. x 2 ft. lay-in ceiling speaker - one way
316967	V-TBAR	Optional trim bar

Desktop/Wall Speakers

VALCOM INC



FEATURES

- Convenient and easily accessible
- Self-standing or wall-mount on flat surface
- Use for off-hook voice announcement with hands-free reply

Anixter No.	Vendor No.	Description
148222	V-763-BK	One-way desktop/wall speaker with volume control, BK (black)
148221	V-762-BK	Talk-back desktop/wall speaker with volume control, BK (black)
217324	V-764-BK	Push-button desktop/wall speaker with volume control BK (black)

Add W (white) or GY (gray) at the end of part number instead of BK for different colors.

High-fidelity Signature Series Speakers

VALCOM INC



FEATURES

- Provides exceptional music and voice quality
- Built-in volume controls on each speaker
- High-fidelity audio output
- Built-in amplifiers

MONITOR SPEAKER

Anixter No.	Vendor No.	Description
204634	V-1440-BK	Black
217319	V-1440-BR	Brown
217320	V-1440-GY	Gray
233516	V-1440-W	White

IN-WALL SPEAKER

Anixter No.	Vendor No.	Description
204639	V-1450	White

CEILING SPEAKER

Anixter No. Vendor No. **Description** 194304 V-1420 White

LAY-IN CEILING SPEAKER

Anixter No. Vendor No. Description 316873 V-1422 White

Pendant Speaker

VALCOM INC



FEATURES

· High-efficiency speaker



- Ideal for music and sound rebroadcast
- Simply hang from 6 ft. chain, included

Anixter No.	Vendor No.	Description
246642	V-1015B-BK	One-way, black
316903	V-1015B-GY	One-way, gray
246644	V-1015B-W	One-way, white
316901	V-1019B-BK	Talk-back, black
316900	V-1019B-GY	Talk-back, gray
316899	V-1019B-W	Talk-back, white

SlimLine Wall Speaker

VALCOM INC



FEATURES

• Contemporary grill snaps on/off for easy access to the built-in volume control

(packaged two per box)

- Exceptional sound quality
- Easy installation
- Hangs on a single screw

O	0	
Anixter No.	Vendor No.	Description
183656	V-1042-BK	One-way, black
183659	V-1042-W	One-way, white
243130	V-1042-GY	One-way, gray
183665	V-1046-BK	Talk-back, black
183668	V-1046-W	Talk-back, white
251043	V-1046-GY	Talk-back, gray
424841	V-WGWALL-2	Wire cages used with wall speakers

Surface-mount Vandal-resistant One-way Ceiling Speaker

VALCOM INC



FEATURES

- Ideal for concrete ceilings and harsh areas
- Smooth tapered exterior prohibits grasping onto surface
- Steel security screen prevents objects from penetrating speaker
- Tamper-resistant screws
- Water-resistant speaker with built-in amplifier
- Sturdy steel housing
- Easy surface mounting or mount to standard 4 in. box

Anixter No. Vendor No. Description

237415 V-9010-W One-way ceiling speaker, white

Track-style Speaker

VALCOM INC



- Easy-mounting bracket attaches to the wall or exposed beams
- High-efficiency speaker
- Ideal for music and sound rebroadcast
- Available in white, black, gray

Anixter No.	Vendor No.	Description
246641	V-1013B-W	1 W, one-way, white
316908	V-1013B-BK	1 W, one-way, black
316907	V-1013B-GY	1 W, one-way, gray
316904	V-1014B-W	5 W, one-way, white
316906	V-1014B-BK	5 W, one-way, black
316905	V-1014B-GY	5 W, one-way, gray



Valcom Paging

Traditional Ceiling Speakers

VALCOM INC



FEATURES

- White epoxy finish
- Excellent sound quality for both voice and background music
- Built-in amplifier

Anixter No.	Vendor No.	Description
129244	V-1010C	4 in., one-way, flush-mount ceiling speaker with grill
121885	V-1020C	8 in., one-way, flush-mount ceiling speaker with grill
121849	V-1220	8 in., one-way, dual-input, flush-mount ceiling speaker with grill
121872	V-1060A	8 in., talk-back, flush-mount ceiling speaker with grill

P-TEC Speakers

VALCOM INC



FEATURES

- Patented push/lock mounting, no holes to cut
- Lightweight and easy to mount and move
- 70 V model is adjustable from 0.25 to 4 W
- Provides an external volume control

Anixter No. Vendor No. Description

171619 V-5330100 Voice coil (rated 0.25 W) 151072

V-5330200 70 V (adjustable from 0.25 to 4 W)

Recessed Round Ceiling Speakers

VALCOM INC



FEATURES

- Fits most suspended or standard ceilings
- Flush-mountable
- · White enamel finish
- Support bridge and all mounting hardware included

Anixter No. Vendor No. **Description**

151067 V-5330115 Voice coil (rated at 0.25 W)

V-5330215 70 V (adjustable from 0.125 to 2.5 W) 151075

Recessed Round Ceiling Speaker Backbox

VALCOM INC



The backbox is intended to cover the back of the speaker.

Anixter No. Vendor No. 151089 V-5335030-5 Description Speaker, round



Square Indoor and Outdoor Warehouse Speakers

VALCOM INC



FEATURES

- Suitable for mounting to beams and trusses
- Complete integrated backbox
- Adjustable 1/4 to four watts
- Water resistant (outdoor only)
- White metal housing

Anixter No. Vendor No. Description
175192 V-5330235 Square, indoor
304818 V-5330240 Square, outdoor

15 W and 30 W Horn Loudspeakers

VALCOM INC



FEATURES

- Can be mounted on a pole, column or flat surface
- Has a wide 110° audio-dispersion angle
- Capable of volume fine-tuning if used with a 70 V attenuator
- Use with the PagePac Plus AmpliCenter or PagePac 20

 Anixter No.
 Vendor No.
 Description

 151079
 V-5331200
 15 W horn

 151080
 V-5331205
 30 W horn

40 W Explosionproof Horn Loudspeaker

VALCOM INC



FEATURES

- UL and CSA Listed for installation in areas where explosive, flammable and/or corrosive substances are present
- Can be mounted on a pole, column or flat surface
- Has a wide 120° audio-dispersion angle
- Can be adjusted from 2.5 to 40 W
- Capable of volume fine-tuning if used with a 70 V attenuator
- Recommended for use with the PagePac Plus AmpliCenter or PagePac 20
- Usage ideal for medium- to high-noise areas

Anixter No. Vendor No.

171643 V-5331215A Explosionproof speaker

FlexHorn - Waterproof

VALCOM INC



The compact design is perfect for areas with low ceilings and low to moderate noise. Recess or surface-mountable. Includes an adjustable bracket for mounting on a horizontal or vertical plane. One-way or talk-back.

Anixter No.	Vendor No.	Description
316966	V-1080-BG	Beige, one-way
204625	V-1080-GY	Gray, one-way
204624	V-1080-W	White, one-way
316876	V-1090-BG	Beige, talk-back
243129	V-1090-GY	Gray, talk-back
243128	V-1090-W	White, talk-back
424844	V-WGFLEX-2	Wire cages used with FlexHorns

Valcom Paging

Paging Horns

VALCOM INC



FEATURES

- Weather-resistant
- Indoor/outdoor use
- · Exceptional natural sound
- Available in beige or gray
- Stainless steel hardware
- Omni-lock mounting system

INDUSTRIAL HORNS

Anixter No.	Vendor No.	Description
121878	V-1030C-BG	5 W one-way, beige
183653	V-1030C-GY	5 W one-way, gray
121876	V-1036C-BG	15 W one-way, beige
183655	V-1036C-GY	15 W one-way, gray
121873	V-1048C	Talk-back, beige
316890	V-1048C-GY	Talk-back, gray
424846	V-WGHORN-2	Wire cages used with paging horns (packaged two per hox)

MARINE HORN - WHITE HORN

Equipped with 0-ring seals, stainless steel hardware, resists deteriorating effects of salt, sun and humidity, non-yellowing white color.

Anixter No.	Vendor No.	Description
183652	V-1030M	5 W one-way
243131	V-1048M	Talk-back

SPECIAL PURPOSE HORNS

Anixter No.	Vendor No.	Description
121874	V-1038	30 W one-way
129246	V-1050C	5 W bi-directional

Digital Feedback Eliminator

VALCOM INC



The digital feedback eliminator records and saves the message, then rebroadcasts it over the speaker system, eliminating the need to move speakers or telephones for a quick and easy solution.

FEATURES

- Only one unit is needed to eliminate feedback to all zones
- Can be used on a single-zone page adapter
- Automatically adjusts the output level to a consistent volume
- Records a page while playing a recorded page
- · High-fidelity
- Solid-state design
- LED indicators for play, record, busy and power
- Dipswitch programmable features
- Two audio outputs

Anixter No.	Vendor No.	Description
255252	V-9964	Feedback eliminator

Door-answering Device

VALCOM INC



Provides talk-back communication between an entryway or doorway and a telephone system or dedicated single telephone set. Also, unlock the door remotely (electronic strike plate not included), just by dialing a code on the telephone (except V-2900).

- Transmit and receive volume controls
- Door-unlock activation
- Programmable security codes
- Indication of unauthorized entry
- Background music input with volume control
- Built-in ring generator with on/off switch
- Compatible with all Valcom talk-back and one-way speakers



- Programmable options include:
- Door-unlock codes
- Number of ringing cycles before door request is terminated
- Program access code
- Time (in seconds) the activated door lock remains unlocked
- Distinctive ring patterns
- Requires additional power (VP-624B or larger power supply)

Anixter No. Vendor No. Descrip

121841	V-2901A	One-zone door answering device
121842	V-2900	One-zone basic door answering device
204630	V-2904	Enhanced four-zone door answering device

FM Tuner

VALCOM INC



FEATURES

- Built-in speaker prevents the need for tuning over the speaker system
- Two separate outputs and volume controls for music on hold, background music
- Treble and bass controls
- · Dipole antenna included
- An "I" connector for use with an external coaxial antenna

Anixter No. Vendor No. Description 168941 V-2952 FM tuner

Messager USB Digital Messaging System

VALCOM INC



Valcom's Messager USB is a state-of-the-art digital audio playback device designed to provide a continuous-play audio source for message-on-hold, background music, or any other audio application where high-quality audio playback is required. Messages are stored on industry-standard USB flash drives from 16 MB up to 4 GB. The Messager USB is capable of MP3 file playback from 8 kbps all the way up to full CD-quality audio playback of 128 kbps.

FEATURES

- Plays MP3 files from USB flash drive
- Up to 4 GB flash drives supported

- No drivers or special software needed
- Playback quality up to 128 kbps
- Continuous playback
- Built-in monitor speaker
- · LED status indicator

Anixter No. Vendor No. Description

333605 V-9988 Messager USB Digital Messaging System

Multi-tone Generator

VALCOM INC



Adds tones over the paging system for evacuation, night ring, doorbells and other tone notifications needed

FEATURES

- Chime, slow whoop, warble, pulsed up to 16 available tones
- Tones activated by individual dry-contact closure up to eight at a time
- Automatically interrupts page or music during tone interval
- Provides standard immediate evacuation signals

Anixter No. Vendor No. Description
129251 V-9927A Multi-tone generator

Page Control Interfaces with Built-in Power, 2000 Series

VALCOM INC



FEATURES

- Provides one to six zones of hands-free talk-back and/or one-way paging
- Interfaces with telephone system via a loop-start/ground-start C.O. line position
- Page override input
- Programmable features per zone: background music, tones and talk-back
- Multiple units can be interconnected for a common All-Call
- Supports two talk-back speakers per talk-back zone
- Volume controls for background music, tones, All-Call and transmit/receive
- May be accessed from a dedicated single-line telephone set
- Standard 66 blocks used for connections
- One-way All-Call

Continued on next page >>



Valcom Paging

(continued) Page Control Interfaces with Built-in Power, 2000 Series

- DTMF-operated auxiliary contacts available for controlling electric door locks
- Background music input
- Dial tone, ringback tone, optional alert/repeated alert tone
- Battery backup input
- Built-in power
- Built-in tone generator (single/warble) with volume control
- UL/CSA/CE Certified

ONE-ZONE BASIC

Background music input automatically mutes in zone being paged. Provides access to the paging system

Anixter No. Vendor No. Description

240687 V-2000A One-zone, one-way page control, with power

ONE-ZONE ENHANCED

Background music input automatically mutes zone being paged. Phantom Zone - optional background music through all or selected speakers. Page override for special or priority announcements. Built-in tone generator for night ring, time clock tone and doorbell.

Anixter No. Vendor No. Description

190580 V-2001A One-zone, one-way page control, with power

and tone generator

THREE ZONES

Three zones and All-Call background music input automatically mutes in zone being paged. Built-in tone generator for night ring, time clock tone and door bell battery backup input. Field upgradable to talk-back with V-9953

Anixter No. Vendor No. Description

123263 V-2003A Three-zone, one-way page control, with power

and tone generator

SIX 70NFS

Includes features of V-2003A (six zones, three group calls and All-Call), override input, and is field upgradable to talk-back with V-9956

Anixter No. Vendor No. Description

129242 V-2006A Six-zone, one-way page control, with power

and tone generator

Doorplate Speakers

VALCOM INC





FEATURES

- Weather-resistant talk-back speaker
- Call button with call in Braille
- Fits standard 4 in. double-gang box

Anixter No. Vendor No. Description

174772 V-1072A-ST Doorplate speaker, flush mount,

stainless steel

316877 V-1072B-ST Doorplate speaker, flush with LED.

stainless steel

Anixter No.	Vendor No.	Description
233504	V-1072A-BRASS	Doorplate speaker, flush mount, brass
316878	V-1072B-BRASS	Doorplate speaker, flush with LED, brass
204643	V-1074	Surface-mount doorplate speaker with call button
183675	V-1073	Vandalproof doorplate speaker
424849	V9910-BK	Doorbox weather guard, black
424850	V9910- YEL	Doorbox weather guard, yellow

Talk-back Intercom System - Expandable

VALCOM INC



An innovative, new, expandable talk-back intercom system designed specifically for providing sophisticated communications solutions for schools, assisted-living facilities, auto dealerships, medical clinics and warehouses.

FEATURES

- Expandable up to 96 stations with expansion units
- · Hands-free talk-back
- Compatible with PBX, key systems or standalone telephone sets
- Caller identification
- One-way group call and All-Call
- Talk-back "meet me" and "follow me" capabilities
- Background music input
- Emergency override
- Door-unlock capabilities
- Time clock/emergency tones
- Accessed by loop-start trunk port or dedicated single-line set
- Built-in one-way and hands-free amplifiers with volume controls
- SMDR printer port
- · Riot mode

Anixter No. Vendor No. Description

254315 V-2924A 24-station talk-back intercom system
254316 V-2925A Expansion unit - 24-station increments

OPTION CARD - ENHANCEMENTS AVAILABLE FOR V-2924A SYSTEM

Enhanced Caller ID, user-defined page groups, flexible architectural numbering plan, PC-compatible programming port with Windows 95/98- or NT-based programming tool, system clock, secondary serial port

Anixter No. Vendor No. Description

194309 V-2926 Option card - remote programming 268917 V-2928 Option card - time event scheduler



In-wall Mixers

VALCOM INC



Valcom's In-Wall Mixer is a complete sound system that blends with today's modern décor. Each mixer provides two auxiliary inputs and one balanced microphone input. Auxiliary inputs can be used for music or program sources, PC audio or wireless microphones and easily mounts in a 4-gang electrical box with decorative white faceplate. An additional audio input (building page) easily adapts the in-room speakers to the building's existing paging system. An override feature allows building announcements priority over individual room activities.

FEATURES

- Contemporary styling to match today's offices, conference rooms and restaurant environments
- A master volume control is provided for final level adjustments
- An eight segment LED meter provides instant visual indication of audio signal levels
- The building page input overrides all other sources (voice operated, switch enabled)
- Full frequency range output for speakers and modified output for horn loads
- Built-in compressor (option switch controlled) evens out loud and quiet inputs
- Operates on 24 V DC requiring one Valcom power unit

Anixter No. Vendor No. Description
340076 V-9985-W In-wall mixer
340078 V-9984-W Remote input module
340080 V-9983-W In-wall main control module

Ambient-level Controller

VALCOM INC



The ambient-level controller uses its internal microprocessor via microphone input to sense ambient noise and optimizes the paging level to its surroundings.

FEATURES

- Ideal for areas where noise levels frequently change
- Permits automatic, manual or remote control of sound system levels
- Microphone may be placed up to 5,000 ft. from the unit

Anixter No. Vendor No. Description

215782 V-5335621 Ambient-level controller

PagePac Call Stacker

VALCOM INC



Eliminates busy signals on heavily used systems and prevents acoustic feedback.

FFATIIRF:

- Eliminates feedback by opening loop between paging device and speakers
- Enables the system to accept up to five simultaneous pages, store them and play them back in sequence
- Emergency messages can interrupt playback sequence
- Interrupted message will play in full once the emergency message has completed. (Note: must be used with PagePac Plus System.)
- Provides prompts in English, Spanish or both languages
- Access via analog station ports or central office lines

Anixter No. Vendor No. Description
215770 V-5325150 PagePac Call Stacker

Desktop Speakers

VALCOM INC



These desktop speakers are small, lightweight and designed to communicate within relatively small areas.

FEATURES

- · PagePac by Valcom Inc.
- Excellent private office intercom
- Covers 250 sa ft.
- Can be wall mounted
- Use for voice announce on busy with your phone system
- May be used for one-way or talk-back
- Privacy switch (70 V only)

Anixter No. Vendor No. Description
151074 V-5330210 70 V desktop speaker



Valcom Paging

PagePort PreAmp/Expander

VALCOM INC



FEATURES

- A master volume control for an entire system or groups of remote speakers
- Virtually unlimited expansion
- Pre-amplifies low-level audio to remote sites
- Isolates paging port from speaker lines

Anixter No. Vendor No.

Description

121867 V-1094A

Master volume control

70 V Expander

VALCOM INC



Provides unlimited expansion of 25/70/100 V systems without straining existing amplifier.

FEATURES

- Easily connects to the amplifier output or anywhere on the 70 V line
- Provides a master volume control for added speakers

Anixter No. Vendor No. Description 194306 V-1095 70 V expander

70 V Attenuators

VALCOM INC



This attenuator allows volume adjustment of 70 V speakers and horns. Accommodates up to 35 W of speaker load.

Anixter No. Vendor No. Description
151091 V-5335005A 70 V attenuator

Voice Coil Attenuator (3 W)

VALCOM INC



Controls the volume of voice coil speakers and horns.

FEATURES

• PagePac by Valcom Inc.

Anixter No. Vendor No. 272272 V-5335010A

Description

Voice coil attenuator 3 W



Voice Coil Door Speaker

VALCOM INC



Description

Know who is at your door with these talk-back DoorPhone speakers.

FEATURES

- Push-button on the DoorPhone with a speaker for signaling
- Stainless steel faceplate and tamperproof screws
- Weather-resistant enclosure for indoor or outdoor use
- Can be mounted to any surface or flush-mounted

Anixter No. Vendor No.

151068 V-5330120 Voice coil door speaker **230924** V-5330230 70 V door speaker

Universal DoorPhone Controller

VALCOM INC



Allows the user to remotely control locking and unlocking of premise doors.

FEATURES

- Provides voice communication between your telephone system and the DoorPhone speaker
- Controls remote door unlocking (with optional customer-supplied and customer-installed electromechanical door lock)
- Interfaces the DoorPhone speaker with an extra alert
- Volume control for speaker and talk-back
- May be used with central office lines or station ports and has ability to dial up to 16-digit telephone numbers

Anixter No. Vendor No. Description

216828 V-5324001 Universal DoorPhone controller

PagePac Station DoorPhone

VALCOM INC



Allows the user to control access and communicate with people at a premise door.

FEATURES

- Designed specifically for PARTNER Plus System
- Provides visible feedback to your visitor via a green LED that confirms the DoorPhone is activated
- Rings different extensions
- Requires no external power to operate
- Weather-resistant, tamperproof, ideal for indoor/outdoor use

Anixter No. Vendor No. Description

316866 V-5324004 PagePac Station DoorPhone

PagePac 6

VALCOM INC



Page your personnel with the PagePac 6.

FEATURES

- Provides a 6 W, compact, single-zone, one-way paging system, with an amplifier that provides 3.4 V of output
- Best suited for small businesses with quiet-to-moderate sound levels
- Useful in small- to medium-sized offices (up to 9,000 sq ft.) and warehouse or manufacturing applications up to 12,000 sq ft.
- Background music input available
- Provides page port/aux port access
- Power supply included
- Recommended for up to 18 voice coil speakers or six 1 W voice coil horns

Anixter No. Vendor No. Description 230909 V-5323006 PagePac 6



Valcom Paging

PagePac 6 Plus

VALCOM INC



Like PagePac 6, PagePac 6 Plus features a highly affordable, compact, 6 W paging amplifier and is intended for use in small- to medium-sized office and warehouse environments. PagePac 6 Plus is a versatile system that offers a full three zones of paging, plus the highly desirable talk-back capability (two-way, hands-free communication via system speakers).

FEATURES

- Provides a highly affordable, compact, three-zone paging system plus group and All-Call, with a 6 W paging amplifier
- Useful in small- to medium-sized offices (up to 9,000 sq ft.) and warehouse or manufacturing applications (up to 12,000 sq ft.)
- Supports up to two separate analog station paging lines and includes this port saver feature as standard
- Provides talk-back capability and programmable background music
- Provides three built-in, 2 W, voice coil amplifiers (one per zone)
- Recommended for up to 18 voice coil speakers (six per zone), or up to two 1 W voice coil horns per zone

Anixter No. Vendor No. Description
171646 V-5323008 6 W paging amplifier

PagePac Plus D-Series AmpliCenters

VALCOM INC



The PagePac Plus D-series AmpliCenter is the core of the PagePac Plus paging system. It can function as a standalone, single-zone paging system, or when coupled with a PagePac Controller, it can drive larger, more sophisticated, multizone systems. The PagePac Plus AmpliCenter is optimally designed for convenient, direct access and simplicity of operation using your own telephone system. The system automatically modifies voice level for maximum clarity and consistent, pleasant paging.

FFATURES

- Standalone or PagePac Plus Controller access
- Provides digital technology and remote amplifier output
- Provides overload protection and automatic reset

- Provides automatic voice-level adjustment for all pages
- · Background/foreground music volume adjustment
- LED displays to indicate power on/off status and aid in system troubleshooting
- Remote amplifier output
- Wall, rack or cabinet mounting

 Anixter No.
 Vendor No.
 Description

 304817
 V-5328040
 40 W output

 316865
 V-5328100A
 100 W output

PagePac Plus Controller

VALCOM INC



The PagePac Plus Controller is the cornerstone of the PagePac Plus Paging System. It provides for the first eight zones (designated work areas) of paging required and also serves as the primary interface (hub) for all telephone system connections. Together with the PagePac AmpliCenter, the PagePac Plus Controller facilitates paging capabilities for businesses and multi-site plants of any size. It also accommodates off-premises paging zones. The PagePac Plus Controller coordinates building security by controlling outside doors and entrances to individual work areas. It also includes a built-in bell and alert tones.

FEATURES

- Hands-free talk-back via system speakers
- System access passwords to restrict unauthorized usage (optional)
- Zone-specific, direct-dial/direct-page function with standard two-digit codes and user-assignable three- and four-digit codes
- Ability to interface with visual message centers
- System overload protection
- PC or DTMF telephone programmability
- Compatibility with all PBX, Key and Centrex telephone systems
- Provides "paging override" for priority announcements
- Seven alert tones programmable
- Up to eight programmable zones and zone groups
- Expandable to 56 zones of one-way or talk-back paging

Anixter No. Vendor No. Description 151102 V-5323100 Controller

171642 V-5323105 PagePac programming software



PagePac Plus Zone Expansion Unit

VALCOM INC

PagePac Plus

The PagePac Plus Zone Expansion Unit enables a paging system to significantly expand its messaging capabilities. The PagePac Plus Zone Expansion Unit connects to the PagePac Plus Controller and provides 16 additional paging zones. Up to three expansion units can be attached to a single controller for a maximum of 56 paging zones per system. All zones can be optioned for hands-free talk-back with a 70 V output or may be utilized as input/output contact closures.

Anixter No. Vendor No. Description
151096 V-5335100 Expansion unit

PagePal Interface

VALCOM INC



The PagePal Interface connects any other paging system to your telephone system. This unit features attendant override, allowing direct access from the attendant console or desktop microphone.

FEATURES

- Provides access to your paging system via an analog station, loop- or ground-start trunk and dry-loop (telephone system page port)
- Provides attendant override which allows direct access from the attendant or desktop microphone or page port with contact closure
- Includes tones for night bell, call or page confirmation, alerts, page busy and pre-announcement
- Provides a music input
- Not recommended for talk-back

Anixter No. Vendor No. Description
151105 V-5335700 PagePal Interface

PagePac Plus Controller PC Software

VALCOM INC

Provides easy programming from a computer instead of a telephone.

FEATURES

- PagePac by Valcom Inc.
- Requires less than 640 K RAM, uses a 3.5-inch floppy
- Operates in character mode
- Supports monochrome and color monitors or LCDs
- Has ability to retain configuration indefinitely
- PC connects to an RS-232 on the controller with a null modem cable
- Operates on generic, DOS-based, IBM PC or compatible system

Anixter No. Vendor No.

171642 V-5323105 PagePac programming software

Description

Universal Bi-directional Speakers

VALCOM INC



Universal bi-directional speakers are capable of unidirectional or bi-directional signal dispersion thanks to special, innovative cabinet mounts. These speakers come in either voice coil or 70 V models and are normally used when recessed ceiling mounts are either not desirable or not possible. Each speaker comes housed in a handsome black cabinet with a black cloth grille.

Anixter No. Vendor No. Description

230915 V-5330105 Voice coil (rated at 0.25 W)

215775 V-5330205 70 V (adjustable from 0.125 to 2.5 W)

Remote Amplifier Adapter

VALCOM INC



Expands the PagePac 6 and PagePac 6 Plus by allowing the addition of other amplifiers, both on-site and off-premises.

FEATURES

- Reduces potential noise problems
- Avoids downstream amp overdrive by ensuring that the input voltage and impedance match the downstream amplifier

Anixter No. Vendor No. Description

274735 V-5335305 Remote amplifier adapter



Valcom Paging

Digital Sound-level Meter

VALCOM INC



FEATURES

- Professional instrumentation
- Compact, newly designed shape
- High performance
- Easy max./min. function
- 32- to 130-dB/3 range
- Resolution, 0.1 dB
- IEC 651 type II
- 9 V battery included

Anixter No. Vendor No. 233552

V-9992

Description

Digital sound-level meter

Station-level Paging Adapter

VALCOM INC



FEATURES

- Full-featured paging with C.O. or Centrex lines
- Can combine with Valcom multizone or talk-back page control interfaces
- Requires 24 V DC/200 mA, filtered power supply

Anixter No. Vendor No. Description

121785 V-9940 Station-level paging adapter

Speaker-mounting Hardware for 8 in. Ceiling Speakers

VALCOM INC



FEATURES

• Bridges and backboxes for use with 8 in. ceiling speakers

	ion
185051 V-9914M Bridge, m	etal
189069 V-9915M-5 Backbox,	meta

183676 V-9916M Bridge/backbox combination, metal

Power Supplies

VALCOM INC



SWITCHING - FILTERED

Anixter No. Vendor No. Description VP-1124D 1 A, wall mount, 24 V DC 233554 VP-2124D 2 A, wall mount, 24 V DC 218598 VP-4124 4 A, wall mount, 24 V DC (48 V DC/2 A) 183678

183679 VP-6124 6 A, wall mount, 24 V DC

LINEAR - FILTERED

Anixter No. Vendor No. 122135

0.6 A, receptacle mount, 24 V DC VP-624B

Description

Description

SPECIAL PURPOSE

Anixter No. Vendor No.

122138 VP-324 250 mA, unfiltered, receptacle mount,

24 V DC

2 A, filtered, wall mount, 48 V DC 213680 VP-2048C

BATTERY BACKUP

Anixter No. Vendor No. Description 129250 VPB-260 2 A, 24 V DC



Analog Clocks - Wired and Wireless

VALCOM INC



FEATURES

- Valcom's quartz analog clocks are available in 12 in. or 16 in. round metal case with shatter-proof polycarbonate crystal
- Offers proven time-keeping accuracy and reliability

WIRED ANALOG CLOCKS

Anixter No.	Vendor No.	Description
339752	V-A2416	16 in. round, black, surface-mount, 24 V DC
339753	V-A11016	16 in. round, black, surface-mount, 110 V AC
339754	V-A2412	12 in. round, black, surface-mount, 24 V DC
339755	V-A11012	12 in. round, black, surface-mount, 110 V AC

OPTIONAL DRIVER

Anixter No. Vendor No. Description

6 amp 2 wire clock driver 339757 V-VCU

WIRELESS ANALOG CLOCKS AND REPEATER

Anixter No.	Vendor No.	Description
339758	V-AW2416	16 in. round, black, surface-mount, 24 V DC
339759	V-AW11016	16 in. round, black, surface-mount, 110 V AC
339760	V-AW16A	16 in. round, black, surface-mount, battery operated
339761	V-AW2412	12 in. round, black, surface-mount, 24 V DC
339762	V-AW12LP	12 in. round, black, surface-mount, 110 V AC
339763	V-AW12	12 in. round, black, surface-mount, battery operated
424852	V-AW12A-MD	12 in. round, black, surface-mount, military dial

SURFACE-MOUNT RINGS AND BRACKETS

Anixter No.	Vendor No.	Description
339764	V-SMR12	Surface-mount ring for 12 in. clock
339765	V-BDM12-4	Double-mount bracket for 12 in. clock
339766	V-UMB	Universal mounting bracket
339767	V-SMR16	16 surface-mount ring for 16 in. clock
339768	V-BDM16-4	16-4 double-mount bracket for 16 in. clock

CLOCK/SPEAKER BAFFLES

Anixter No.	Vendor No.	Description
339769	V-CSB12S	12 in. analog clock/8 in. speaker baffle
339770	V-CSBFB	Surface-mount backbox for V-CSB25 and/or V-CSB12S
339772	V-CSBRB	Recessed-mount backbox for V-CSB25 and/or V-CSB12S
WIRE GUARDS	S	
Anixter No.	Vendor No.	Description
339773	V-WGA12	12 in. wire guard

16 in. wire guard

Digital Clocks - Wired and Wireless

V-WGA16

VALCOM INC

339774



FEATURES

- Available with 2.5 in. or 4.0 in. easy-to-read four digit display
- Each has a specially molded anti-glare bezel which gives the digital clock a smooth, clean look
- All digital clocks are available in either 24 V DC or 110 V AC

WIRED DIGITAL CLOCKS

	Vendor No.	Description
339775	V-D2425	2.5 in. 24 V DC digital
339776	V-D11025A	2.5 in. 110 V AC/24 V DC digital
339777	V-D2440	4.0 in. 24 V DC digital
339778	V-D11040A	4 in. 110 V AC/24 V DC digital
339757	V-VCU	6 amp 2 wire clock driver
WIRELESS DIGITAL CLOCKS		

WIRELESS DIG	GITAL CLOCKS		
Anixter No.	Vendor No.	Description	
339780	V-DW2425	2.5 in. 24 V DC digital	
339781	V-DW11025	2.5 in. 110 V AC/24 V DC digital	
339782	V-DW2440	4 in. 24 V DC digital	
339783	V-DW11040	4 in. 110 V AC/24 V DC digital	
HOUSING	HOUSING		
Anixter No.	Vendor No.	Description	
339784	V-SM25	Surface- (wall-) mount housing for 2.5 in. digital clock	
339785	V-FM25	Flush-mount housing for 2.5 in. digital clock	
339786	V-SM40	Surface- (wall-) mount housing for 4 in. digital clock	
339787	V-FM40	Flush-mount housing for 4 in. digital clock	

Continued on next page >>



Valcom Paging

(continued) Digital Clocks - Wired and Wireless

CLOCK/SPEAKER BAFFLES			
	Anixter No.	Vendor No.	Description
	339788	V-CSB25	2.5 in. digital clock/8 in. speaker baffle
	339770	V-CSBFB	Surface-mount backbox for V-CSB25 and/or V-CSB12S
	339772	V-CSBRB	Recessed-mount backbox for V-CSB25 and/or V-CSB12S
	339791	V-CDT	Chronograph timer control box
	339792	V-WGD4	4 in. wire guard for use with the 2.5 in. and 4 in. digital clock

12 in. analog clock/8 in. speaker baffle

MOUNTING BRACKETS

339769

Anixter No.	vendor No.	Description
339793	V-DM25-4	Double-mount bracket for 2.5 in. digital clock
339794	V-DM40-4	Double-mount bracket for 4 in. digital clock

MASTER CLOCKS AND REPEATER

V-CSB12S

Anixter No.	Vendor No.	Description
339795	V-WMCA	Series master clock transceiver for use with
		wireless clocks

339796 V-GPSA Receiver for use with wireless clocks 339797 V-WMCRA Wireless master clock repeater for use with

wireless clocks

IP Paging Products - Managed

VALCOM INC



FEATURES

- Available in 1-, 2- and 4-channel models
- No server required
- Easy Windows-based setup
- Web-based configuration/setup
- One to 11 digit dial plans
- AUX audio input
- Can use DHCP servers to acquire IP addresses
- Contact closure available for audio indication and door unlocking
- Note: VIP-811, VIP-812 and VIP-814 also provide ringing indication contact

Anixter No.	Vendor No.	Description
316812	VIP-801	Networked page zone extender
316811	VIP-802	Dual networked page zone extender
316810	VIP-804	Quad networked page zone extender
316809	VIP-811	Enhanced networked station port
316808	VIP-812	Dual enhanced networked station port
316807	VIP-814	Quad networked station port

IP Paging Products - Networked Trunk Port

VALCOM INC

FEATURES

- Allows most loop start terminal devices to be connected to a managed IP-based LAN/WAN
- RJ45 for network connection
- Network activity LEDs
- Front panel activity LED
- 2.5 mm jack for DC
- 802.3af compliant

Anixter No.	Vendor No.	Description
316806	VIP-821	Enhanced networked trunk port
316805	VIP-822	Dual enhanced network trunk port
316804	VIP-824	Quad enhanced network trunk port

SIP Wall Speakers

VALCOM INC



- Sleek, modern design
- Excellent voice and music quality
- Gray with black grille
- Paintable housing
- Easy installation
- Built-in volume settings

	O	
Anixter No.	Vendor No.	Description
316815	VIP-410	IP wall speaker; one-way
370703	VIP-411-DS	IP surface-mount wall speaker, one-way, with digital clock
370705	VIP-412-DF	IP flush-mount wall speaker, one-way, with digital clock
424896	VIP-418	IP one-way square faceplate 8 in. speaker, white
424854	VIP-419-D	IP speaker faceplate speaker unit with digital clock, white
424855	VIP-429-D	IP talk-back speaker faceplate unit with digital clock, white
316813	VIP-430	IP wall speaker assembly; talk-back, gray with black grille
424859	VIP-432-DF	InformaCast IP wall speaker assembly; one-way, gray with black grille
424860	VIP-410-IC	InformaCast IP wall speaker assembly; one-way, gray with black grille



Anixter No. 424861	Vendor No. VIP-411-DS-IC	Description InformaCast IP surface-mount wall speaker, one-way, with digital clock, gray with
424862	VIP-412-DF-IC	black grille InformaCast IP flush-mount wall speaker, one-way, with digital clock, gray with black grille
424863	VIP-419-D-IC	InformaCast IP speaker faceplate speaker unit with digital clock, white
424864	VIP-429-D-IC	InformaCast IP talk-back speaker faceplate unit with digital clock, white
424865	VIP-430-IC	InformaCast IP wall speaker assembly; talk-back, gray with black grille
424878	VIP-432-DF-IC	InformaCast IP wall speaker assembly; talk-back, gray with black grille
424879	VB-R19	Recessed mount backbox for use with VIP-412-DF, VIP-412-DF-IC, VIP-432-DF, F/VIP-432-DF-IC
424903	VIP-428-IC	InformaCast IP talk-back square faceplate 8 in. speaker, white
424904	VB-S11	Surface-mount backbox for use with VIP-418, VIP-418-IC, VIP-428, VIP-428-IC
424897	VIP-428	IP talk-back square face-plate 8 in. speaker, white
424902	VIP-418-IC	InformaCast IP one-way square faceplate 8 in. speaker, white
424905	VB-R12	Recessed-mount backbox for use with VIP-418, VIP-418-IC, VIP-428, VIP-428-IC
424906	VB-A13	Angled-mount backbox for use with VIP-418, VIP-418-IC, VIP-428, VIP-428-IC
424880	VB-R22	Recessed-mount backbox for use with VIP-419-D, VIP-419-D-IC, VIP-429-D, VIP-429-D-IC
424881	VB-R22	Surface-mount backbox for use with VIP-419-D, VIP-419-D-IC, VIP-429-D, VIP-429-D-IC
424883	VB-A24	Angled-mount backbox for use with VIP-419-D, VIP-419-D-IC, VIP-429-D, VIP-429-D-IC

IP 2 ft. x 2 ft. Lay-in Ceiling Speakers

VALCOM INC



FEATURES

- Replaces a 2 ft. x 2 ft. tile
- Easy to install

- No cutting tiles, no broken tiles, no mess
- Excellent music and voice quality
- Built-in volume settings
- Durable white acrylic baked enamel finish
- Integral backbox meets or exceeds ASTM E84 flame and smoke test with three hour burn rating (UL 181)
- Power 802.3AF only

	,	
Anixter No.	Vendor No.	Description
424893	VIP-401	IP 1 ft. x 2 ft. lay-in ceiling speaker, one-way
316816	VIP-402	IP 2 ft. x 2 ft. lay-in ceiling speaker, one-way
424894	VIP-421	IP 1 ft. x 2 ft. lay-in ceiling speaker, talk-back
316814	VIP-422	IP 2 ft. x 2 ft. lay-in ceiling speaker, talk-back
424897	VIP-428	IP talk-back square faceplate 8 in. speaker, white
424898	VIP-401-IC	InformaCast IP 1 ft. x 2 ft. lay-in ceiling speaker, one-way
424899	VIP-402-IC	InformaCast IP 2 ft. x 2 ft. lay-in ceiling speaker, one-way
424900	VIP-421-IC	InformaCast IP 1 ft. x 2 ft. lay-in ceiling speaker, talk-back
424901	VIP422-IC	InformaCast IP 1 ft. x 2 ft. lay-in ceiling speaker, talk-back
424902	VIP-418-IC	InformaCast IP one-way square faceplate 8 in. speaker, white
424903	VIP-428-IC	InformaCast IP talk-back square faceplate 8 in. speaker, white
424905	VB-R12	Recessed-mount backbox for use with VIP-418, VIP-418-IC, VIP-428, VIP-428-IC
424906	VB-A13	Angled-mount backbox for use with VIP-418, VIP-418-IC, VIP-428, VIP-428-IC

Page Pro IP

VALCOM INC



FEATURES

- Enables voice access to one to four zones of one-way analog paging plus eight zones of IP paging
- · Designed for use with virtually all SIP-based telephone systems
- Live or recorded messages
- Easily connects loudspeaker system to existing computer networks
- Support IP and analog amplified speakers
- Web interface for control and setup
- Support legacy paging systems

Anixter No. Vendor No. Description

370447 VIP-201 SIP-based paging gateway - one analog SIP-based paging gateway - four analog SIP-based paging gateway - four analog



SIP Ceiling Speakers

VALCOM INC



IP 8 in., one-way, ceiling speaker

Anixter No.	Vendor No.	Description
370706	VIP-120	IP 8 in. ceiling speaker, one-way
424907	VIP-160	IP 8 in. ceiling speaker, talk-back
424908	VIP-120-IC	InformaCast IP 8 in. ceiling speaker, one-way
424910	VIP-160-IC	InformaCast IP 8 in. ceiling speaker, talk-back

SIP Paging Horn with Long-line Extender

VALCOM INC



FEATURES

- Weather-resistant
- Indoor/outdoor use
- Exceptional natural sound
- Available in beige (-BG), gray (-GY) or marine white (-M)
- Stainless steel hardware
- Omni-lock mounting system

Anixter No.	Vendor No.	Description	
365673	VIP-130L-BG	5W, one-way with long-line extender, beige	
424911	VIP-130L-GY	5W, one-way with long-line extender, gray	
424912	VIP-148L-BG	5W talk-back with long-line extender, beige	
424913	VIP-148L-GY	5W talk-back with long-line extender, gray	
424915	VIP-130-BG-IC	InformaCast 5W, one-way with long-line extender, beige	
424916	VIP-130L-GY-IC	InformaCast 5W, one-way with long-line extender, gray	
424917	VIP-148L-BG-IC	InformaCast 5W talkback with long-line extender, beige	
424918	VIP-148L-GY-IC	InformaCast 5W talkback with long-line extender, gray	
424846	V-WGHORN-2	Wire cages used with paging horns (packaged two per box)	

SIP FlexHorn

VALCOM INC



The compact design is perfect for areas with low ceilings and low to moderate noise. Recess or surface-mountable. Includes an adjustable bracket for mounting on a horizontal or vertical plane. One-way.

orizontal or vertical plane. Une-way.					
	Anixter No.	Vendor No.	Description		
	370713	VIP-480L-BG	SIP FlexHorn with long-line extender beige		
	370710	VIP-480L-GY	IP FlexHorn with long-line extender, gray		
	424920	VIP-480L-W	IP FlexHorn with long-line extender, white		
	424925	VIP-480L-BG-IC	InformaCast SIP FlexHorn with long-line extender, beige		
	424926	VIP-480L-BG-IC	InformaCast IP FlexHorn with long-line extender, gray		
	424927	VIP-480L-W-IC	InformaCast IP FlexHorn with long-line extender, white		
	370715	VIP-9805	Optional vandal-resistant enclosure		
	424921	VIP-483	IP FlexHorn with stainless steel grille, vandal-resistant, without backbox		
	424928	VIP-483-IC	InformaCast IP FlexHorn with stainless steel grille, vandal-resistant, without backbox		
	424923	VIP-581	IP FlexHorn interior angled surface-mount-unit, white		
	424929	VIP-580-IC	InformaCast IP FlexHorn interior surface-mount-unit, white		
	424924	VIP-581	IP FlexHorn interior square faceplate, white		
	424930	VIP-581-IC	InformaCast IP FlexHorn interior angled surface-mount-unit, white		
	424931	VIP-9880-IC	InformaCast IP FlexHorn interior square faceplate, white		
	424932	VB-R16	Recessed mount backbox for use with VIP-483, VIP-483-IC		
	424933	VB-R17-D	Recessed mount backbox for use with VIP-9880, for use with VIP-9880-IC		
	424844	V-WGFLEX-2	Wire cages used with FlexHorns		



Valcom Paging

SIP Intercom/Doorplate Speakers

VALCOM INC



The hands-free talkback intercom with long-line extender and dial code operated relay are the perfect solution to implementing door phone or similar functions in with modern IP telephone systems.

FEATURES

- Flush-mount
- Call button and LED
- Relay contact for door unlock

Anixter No.	Vendor No.	Description
370718	VIP-172L-BRASS	IP intercom - with long-line extender - brass
424935	VIP-172L-SS	IP intercom - with long-line extender,
		stainless steel
395837	VIP-172L-VRSS	IP intercom - vandal-resistant 11 AWG steel
424849	V9910-BK	Doorbox weather guard, black
424850	V9910- YEL	Doorbox weather guard, yellow

Networked Relay and Input Module

VALCOM INC



FEATURES

- Repeat contact closures
- Eight contact closure inputs (an input may control a single relay or a group of relays)
- Eight relay output supervision (a relay may be set to follow another relay)
- Power up relay state (active or inactive)
- Three input priority levels

Anixter No.	Vendor No.	Description

370721 VIP-848 Networked relay and input module

Local Power Option for 800 Series

VALCOM INC



FEATURES

- Receptacle-mount
- Unfiltered

Anixter No. Vendor No. Description
326238 VIP-324 .25 amp power supply

Networking Systems/Video Products/Video Security Systems

VALCOM INC



IP PoE analog and digital clocks.

- Easy to install via RJ45 connection
- Power over Ethernet (IEEE 802.3af)
- No master clock required set automatically by NTP (Network Time Protocol)
- 10/100BASE-T Ethernet compatible
- DHCP or static IP addressable
- · Industrial grade metal housing

maaocriai Sic	ado motar nodomo	
Anixter No.	Vendor No.	Description
393610	VIP-A12	IP PoE 12 in. analog clock
424939	VIP-A12DS	IP PoE 12 in. double-sided analog clock
393613	VIP-A16	IP PoE 16 in. analog clock
424940	VIP-A16DS	IP PoE 16 in. double-sided analog clock
393614	VIP-D425	IP PoE 2.5 in. four digit, digital clock
424941	VIP-D425DS	IP PoE 2.5 in. four digit, double-sided,
		digital clock
393615	VIP-D625	IP PoE 2.5 in. six digit, digital clock
424944	VIP-D625DS	IP PoE 2.5 in. six digit, double-sided
		digital clock
424942	VIP-D440	IP PoE 4.0 in. four digit, digital clock
424943	VIP-D440DS	IP PoE 4.0 in. four digit, double-sided,
		digital clock
395715	VIP-D640	IP PoE 4.0 in. six digit, digital clock
424946	VIP-D640DS	IP PoE 4.0 in. six digit, double-sided,
		digital clock



Valcom Paging

IP Talk-back Call Station

VALCOM INC



Allows communication to Valcom FXS units (VIP-811, -812, -814) and SIP-based telephone systems via a managed IP-based LAN/WAN.

Anixter No. Vendor No. 424938 VIP-9890-CB

DescriptionIP talk-back call station, vandal-resistant, yellow



7.72

Free Application Design Service

BOGFN

Bogen offers a free application design service to assist with the design of paging systems for any and every project encountered. It's fast, comprehensive and free. (Call 1-800-999-2809 (option 2) for more information or to send in a project.)

- Speaker-placement design
- Complete bill of materials
- Scope of work
- Detailed assumptions
- · Red-lined blueprints (blueprints must be supplied; AutoCAD blueprints accepted)

NEAR A-Series Speakers

BOGEN



NEAR A-Series speakers set the standard for smooth, accurate sound, attractive appearance and rugged construction. Designed to perform beautifully under the toughest conditions, the A-Series combines outstanding aesthetic design with NEAR speaker technology for unsurpassed audio quality and weatherproof durability. Available in black, green or white.

- Magnetic liquid suspension
- Cast-aluminum basket
- Sealed magnet
- Advanced rubber compound
- Metal diaphragm technology

•		
Anixter No.	Vendor No.	Description
236797	A2TBLK	6 in. black, 4, 8, 16 W taps, 70 V
243946	A6TBLK	6 in. black, 8, 16, 32 W taps, 70 V
243947	A8TBLK	8 in. black, 16, 32, 64 W taps, 70 V
270128	A2BLK	6 in. black, 100 W, 8 ohms
270133	A6BLK	6 in. black, 150 W, 8 ohms
270138	A8BLK	8 in. black, 175 W, 8 ohms
270132	A2TGRN	6 in. green, 4, 8, 16 W taps, 70 V
270137	A6TGRN	6 in. green, 8, 16, 32 W taps, 70 V
270142	A8TGRN	8 in. green, 16, 32, 64 W taps, 70 V
270131	A2GRN	6 in. green, 100 W, 8 ohms
270136	A6GRN	6 in. green, 150 W, 8 ohms
270141	A8GRN	8 in. green, 175 W, 8 ohms
270130	A2TWHT	6 in. white, 4, 8, 16 W taps, 70 V
270135	A6TWHT	6 in. white, 8, 16, 32 W taps, 70 V

Anixter No.	Vendor No.	Description
270140	A8TWHT	8 in. white, 16, 32, 64 W taps, 70 V
270129	A2WHT	6 in. white, 100 W, 8 ohms
270134	A6WHT	6 in. white, 150 W, 8 ohms
270139	A8WHT	8 in. white, 175 W, 8 ohms
273236	ASTB4	A-Series terminal block electrical cover
394141	AMT-15	Pro audio speaker cabinet
394137	AMT-12	Pro audio speaker
421322	A12	High output, long-throw loudspeaker

NEAR Orbit Speakers

BOGEN



The Orbit Ceiling Speaker (OCS1) is the ideal choice for various types of ceiling environments. The Orbit Pendant Speaker (OPS1) is the ideal choice for high ceiling and open-space environments. Both feature NEAR's MLS and MDT technologies, which improve sound quality and increase operating reliability. The low-distortion speaker design, featuring NEAR's spiderless driver and one-piece metal-allov cone structure. delivers superb articulation and the highest intelligibility for both music and speech. The OCS1 can be easily installed on hard-surfaced ceilings or in suspended ceilings and new construction (with the optional TBCR bracket). The OPS1 comes in black or white.

- Magnetic liquid suspension
- Stable, high-definition metal-alloy cone
- Sealed magnet
- Advanced rubber compound
- Metal diaphragm technology
- · Wide-dispersion coaxial driver for broad, even coverage

Anixter No.	Vendor No.	Description
265143	0CS1	6 1/2 in. MDT metal-alloy cone, 70 V/100 V $$
265147	OPS1B	6 1/2 in. MDT metal-alloy cone,
		70 V/100 V, black
265148	OPS1W	6 1/2 in. MDT metal-alloy cone,
		70 V/100 V, white
268547	CK-10	10 ft. long cable kit, silver
301186	CK10B	10 ft. long cable kit, black
301187	CK10W	10 ft. long cable kit, white
265155	TBCR	Tile bridge and c-ring support ring



Bogen Paging

Metal Box Speakers

BOGFN



The MB8TSQ and MB8TSL speakers feature an all-steel surface-mounted enclosure with an 8 in. cone loudspeaker and multi-tap 4-watt 70V/25V transformer. The MB8TSQ is suitable for ceiling or wall mounting. The MB8TSL is designed primarily for wall mounting and its face is angled downward by 12.5 degrees.

FFATIIRE

- Rugged all-steel surface-mounted enclosure
- Full range 8 in. cone speaker for excellent intelligibility
- Compatible with 25 V or 70 V amplifier system
- Multiple taps at 4, 2, 1, 1/2, 1/4, 1/8 watts
- 4-watt maximum output power
- Mounting hardware included

Anixter No. Vendor No.

320127 MB8TSQ **320128** MB8TSL

Description

8 in. cone surface-mounted speaker 8 in. cone surface-mounted speaker with

angled front face

Drop-in Ceiling Speaker

BOGEN



The Bogen Drop-in Ceiling Speaker is a full-range speaker that allows for fast and simple installation. No accessories or other hardware required for mounting. Just make one simple cut to the ceiling tile and drop the ceiling speaker in place.

FEATURES

- Easy installation
- One-piece assembly
- 70 V multi-tap pot (25 V)

Anixter No. Vendor No.

273174 CSD1X2

287226

CSD2X2

Description

Drop-in ceiling speaker, 1 ft. x 2 ft.,

integrated support rail

Drop-in ceiling speaker, 2 ft. x 2 ft., includes

support bar

Ceiling Speakers

BOGEN



The Bogen CS1EZ is a preassembled ceiling speaker comprised of an 8 in. cone speaker and steel ceiling grille painted with white enamel. The CS1EZ includes a volume control knob and rear-mounted screw terminal board for easier electrical connections.

FEATURES

- 1 W single-tap design
- Screw terminal connections for fast installation
- Designed for 70 V amplifier output
- 8 in. cone speaker for excellent audio quality

Anixter No. Vendor No. Description

241350 CS1EZ 1 W, volume control, easy design (not

quick install)

394172 C-SUB Ceiling subwoofer

Easy Install Ceiling Speakers

BOGEN



The Easy Install Speakers (SM1EZ and SM4T) drastically cut system installation time because each speaker can be completely installed, mounted in the ceiling, secured and connected in less than a minute.

The speakers can be installed in any drop ceiling with ceiling tiles quickly, easily and trouble-free and carry voice messages with clarity where dependable communication is required.

FEATURES

- Installs in seconds
- No tool installation
- Contemporary, low-profile design

No cleanup

Anixter No. Vendor No. Description 234464 SM1EZ 9.5 in. speak

34464 SM1EZ 9.5 in. speaker with single tap, 1 W,

easy install

241348 SM4T 9.5 in. speaker with multiple taps, 4 W,

easy install

249355 SMTB Tile bridge



High-fidelity Ceiling Speaker

BOGFN



The Bogen HFCS1 ceiling loudspeaker delivers superior sound and clear intelligibility in a variety of ceiling environments. The system can be easily installed in hard-surfaced ceilings, suspended ceilings and new construction. The HFCS1 offers several levels of power output via a front-mounted rotary switch. The low-distortion speaker design, coupled with dual front exit ports, delivers high intelligibility and exceptional low-frequency response for both music and speech reinforcement.

FFATURES

- · Wide-dispersion coaxial driver for broad, even coverage
- Good off-axis response with smooth contouring
- Computer-matched venting system for full bass output
- Large back can for deep bass response
- Power taps (in watts) 32, 16, 8, 4, 2 and 1
- Compounded rubber surround for lasting performance

Anixter No.	Vendor No.	Description
268554	HFCS1	6 1/2 in. PolyCone, 70 V/100 V
268547	CK-10	10 ft. long cable kit, silver
301186	CK10B	10 ft. long cable kit, black
301187	CK10W	10 ft. long cable kit, white
265155	TBCR	Tile bridge and c-ring support ring

Amplified Drop-in Ceiling Speaker

BOGEN

Bogen's ACD2X2 2 ft. x 2 ft. Amplified Drop-in Ceiling Speaker is a full-range speaker that allows for fast and simple installation. No accessories or other hardware required for mounting.

FEATURES

- Quick and easy to install; wire and drop in place
- 2 ft. x 2 ft. design fits in 2 ft. x 2 ft. and 2 ft. x 4 ft. ceiling grids
- Finely perforated grille over entire front of speaker panel
- 8 in. main cone speaker
- Self-contained 1 W amplifier
- · Front-mounted volume control
- Support rail for 2 ft. x 4 ft. ceilings included

Anixter No. Vendor No. Description

304673 ACD2X2 Amplified drop-in ceiling speaker, 2 ft. x 2 ft.

Amplified Loudspeakers

BOGEN



An 8 in. cone speaker with compact IC amplifier and volume control, $1\,\mathrm{W}$ output; operates on 24 V DC.

Anixter No. 301250	Vendor No. ASWG1DK	Description AS1 with ceiling grille, white, detachable
301230	AUMUIDIN	knob, 50 mA
106153	ASWG1	AS1 with ceiling grille, white, fixed knob, 50 mA

Foreground Speakers

BOGEN



The Bogen FG Series of foreground speakers are designed to complement sophisticated music systems. Their wide bandwidth provides the performance demanded by customers while their quality construction provides the reliability installers can count on. The FG Series is available in a variety of physical size and performance models to meet the needs of a wide range of distributed music applications.

- Three models
- Smooth, wide-frequency response for music or voice
- Compact, rugged plastic enclosures
- Individually sweep-tone tested to ensure reliability
- Mounting brackets included
- Black swivel mount available for FG20 and FG30 (not included)

Anixter No.	Vendor No.	Description
287439	FG15B	15 W foreground speaker, black finish
247849	FG15W	15 W foreground speaker, white finish
287458	FG20S	Splashproof 20 W foreground speaker, black
287456	FG30	30 W foreground speaker, black
301252	FGSM	Swivel mount for FG Series, black
301254	FGSMW	Swivel mount for FG Series, white



Bogen Paging

Vandal-resistant Speakers

BOGEN



The Bogen VRS1 and VRS2 are vandal-resistant speakers designed for hands-free two-way communications.

FEATURES

- Heavy-duty vandal-resistant and weather-resistant construction
- 8 ohms or 25 V (1/2 W) operation
- Call-in switch on VRS1 can be wired for "momentary" or "latching" operation
- One-way security hardware included

Anixter No.	Vendor No.	Description
241362	VRS1	Vandal-resistant speaker, transformer,
		H. S 21 . L

call-in switch

241363 VRS2 Vandal-resistant speaker with transformer

Speakers - 8 in. Transformer - 25/70 V

BOGEN

Bogen's 8 in. cone speakers are available preassembled onto a steel ceiling grille painted with white enamel. Options for these assemblies are recessed volume control, volume control with knobs and rear-mounted screw terminal strip for power taps.

FEATURES

- 8 in. cone speaker for excellent audio quality
- Six different power taps
- Preassembled for faster installation
- White enamel over steel grille

Anixter No.	Vendor No.	Description
241356	\$810	10-oz magnet
241354	\$86	6-oz magnet
241358	T72510	Speaker-matching transformers: 10, 5, 2 1/2, 1 1/4, 5/8 W taps
241357	T725	Speaker-matching transformers: 4, 2, 1, 1/2, 1/4 1/8 W tans

Mounting Hardware for Ceiling Speakers

BOGEN



Bogen offers a variety of accessories to assist in mounting various ceiling speakers.

Anixter No.	Vendor No.	Description
117800	TB8	Tile bridge
123495	RE84	Ceiling speaker enclosure
241357	T725	Speaker-matching transformers: 4, 2, 1, 1/2, 1/4, 1/8 W taps
241358	T72510	Speaker-matching transformers: 10, 5, 2 1/2, 1 1/4, 5/8 W taps
247850	MR8	Mounting ring

Ceiling Grilles for 8 in. Speakers

BOGEN



Bogen provides a wide selection of attractive ceiling grilles in white enamel or aluminum finishes. Each grille is shipped with the hardware needed to mount a speaker to the grille.

FEATURES

Accommodates 8 in. speaker

· · · · · · · · · · · · · · · · · · ·		
Anixter No.	Vendor No.	Description
241369	CG8A	Round aluminum grille, contoured
241370	CG8AW	Round aluminum grille, white
		finish, contoured
241371	PG8A	Round aluminum grille
241372	PG8W	Round steel grille, white finish
241373	SG8W	Round steel grille, with hidden studs



S86 Loudspeaker Assemblies

BOGFN

Bogen's metal ceiling grilles are sturdy, handsome and economical. They accommodate an 8 in. speaker. Supplied with complete hardware.

Anixter No. Vendor No. Description

101728 S86T725PG8W S86T725 on PG8W grille

103535 S86T725PG8WVK S86T725PG8W with knob volume control

WB8 Wall Baffle

BOGEN



Bogen's wall baffle is ruggedly constructed of 3/8 in. particle board with reinforced corners. It is finished in simulated walnut and will house any of Bogen's 8 in. speakers. A sloping front panel provides enhanced downward dispersion. Hardware for mounting a speaker to the baffle included.

FEATURES

- Ruggedly constructed
- · Accommodates 8 in. speaker

Anixter No. Vendor No.

241374 WB8

Description

Wall baffle, walnut finish

Wall Baffle

BOGEN



Model WBS8 wall baffle is ruggedly constructed of 3/8 in. particle board, attractively covered in simulated walnut vinyl, with black grille cloth. Assemblies include cone speaker, transformer and baffle; ready to install.

Anixter No. Vendor No. 107331 WBS8T725

Description S86T725 in WB8 baffle

103571 WBS8T725V WBS8T725 with volume control

Sound Columns

BOGEN



The Bogen SCW20 and SCW35 models are heavy-duty sound columns designed for sound reinforcement in churches, theaters, auditoriums and similar installations where it is necessary to cover a large area with a minimum of speakers.

FEATURES

- Precisely controlled sound projection
- · Directional characteristics reduce feedback
- Uniform sound level throughout area covered
- Clarity and intelligibility of speech reproduction
- Lower power requirements than conventional speakers
- Fast and simple installation

 Anixter No.
 Vendor No.
 Description

 241367
 SCW20
 20 W sound column

 241368
 SCW35
 35 W sound column

Paging Horns

BOGEN



The Bogen horn loudspeakers are compact, high-intelligibility, re-entrant-type loudspeakers, designed for one-way or two-way sound and communications systems.

FFATIIRES

- High intelligibility and efficiency
- Weatherproof and metal construction
- 25/70 V or 8-ohms operation

Anixter No.	Vendor No.	Description
107322	BDT30A	30 W horn, bi-directional
241364	SP58A	7.5 W paging speaker
107324	SPT5A	7.5 W paging speaker
241365	SP158A	15 W horn, 8 ohms
103534	SPT15A	15 W horn with transformer
107323	SPT30A	30 W horn with transformer
241366	SP308A	30 W horn, 8 ohms
320129	KFLDS30T	30 W horn, wide dispersion



Bogen Paging

Amplified Horns

BOGEN



Amplified horns are appropriate for noisy or outdoor locations. Equipped with mounting bracket. Operates on 24 V DC.

Anixter No.	Vendor No.	Description
103570	AH5A	5 W
107318	AH15A	15 W

24 V DC, 450 mA power supply **PRSASAC** 103538 241332 PRS624DA 24 V DC, 4 A power supply

Digital Switching Amplified Horns

BOGEN



The SAH5 and SAH15 horn loudspeakers employ digital switching amplifier technology resulting in unprecedented low DC current draw and heat dissipation. This means fewer power supplies, longer cable runs and the capacity to work at higher ambient temperatures than conventional analog amplified horn speakers.

FEATURES

- 5 W. 15 W and 30 W models
- High-efficiency digital switching amplifier technology
- Low DC current draw and heat dissipation
- Unique flare shape provides controlled sound dispersion
- Operates with continuous background music and at high ambient temperatures
- Rotatable horn for vertical or horizontal dispersion
- Cast-aluminum swivel mount

Anixter No.	Vendor No.	Description
304671	SAH5	High-efficiency, digital switching, amplified horn, 5 W
304672	SAH15	High-efficiency, digital switching, amplified horn, 15 W
339076	SAH30	High-efficiency, digital switching, amplified horn, 30 W

Easy Design Horn Loudspeakers

BOGEN



The Bogen Easy Design line of horn loudspeakers is made of weatherproof all-metal construction, thereby making them ideal for both indoor and outdoor use in industrial plants, warehouses, schools, construction sites and recreational areas. All models come with swivel- and tilt-mounting bases for greater flexibility in setting the angle projection.

FEATURES

- 7 W, 15 W and 30 W models
- Single-tap design
- Designed for 70 V amplifier outputs
- Weatherproof design

Anixter No.	Vendor No.	Description
241351	HS7EZ	7 W horn loudspeaker
241352	HS15EZ	15 W horn loudspeaker
241353	HS30EZ	30 W horn loudspeaker

General Purpose Amplifiers

BOGEN



This Bogen amplifier is a rugged, compact unit designed to meet the requirements of continuous low-power audio applications.

- Ideal for music on hold/line amplifier
- Compact
- UL Listed

Anixter No.	Vendor No.	Description
235690	GA6A	6 W amp
235689	GA2	1.5 W amp



Power Vector Amplifiers

BOGFN



Bogen's Power Vector modular input amplifier series offers a wide range of power to choose from, with five models ranging from 35 W to 250 W. The amplifiers are designed to work with both high- (70/25 V) and low-impedance (4/8 ohm) speaker systems. Each model includes eight module bays for input modules and allows up to four levels of priority between modules. Two module bays are also capable of accepting signal processing output modules.

FFATURES

- 35 W, 60 W, 100 W, 150 W and 250 W models
- Modular input amplifiers
- Accepts eight plug-in modules (advanced input and signal-processing output modules)
- 8 ohms, 25 V and 70 V outputs
- Separate volume control for each input channel plus master volume control, bass and treble
- 11-segment LED output level meter
- Output limiter control

Anixter No.	Vendor No.	Description
268513	V250	250 W amp
268514	V150	150 W amp
268515	V100	100 W amp
268516	V60	60 W amp
268518	V35	35 W amp
268519	RPK87	Rack-mount kit
268520	RVCP	Remote volume control panel
268521	PVSC	Power vector security cover

Wall-mount Power Vector Amplifiers

BOGEN



Bogen's Wall-mount Power Vector modular input amplifier series offers a wide range of power to choose from, with three models ranging from 100 W to 250 W. The

amplifiers are designed to work with both high- (70/25 V) and low-impedance (4/8 ohm) speaker systems. Each model includes eight module bays for input modules and allows up to four levels of priority between modules. Two module bays are also capable of accepting signal processing output modules.

FEATURES

- 100 W, 150 W and 250 W models
- Modular input amplifiers
- 8 ohms, 25 V and 70 V outputs
- Accepts eight plug-in modules (advanced input and signal-processing output modules)
- Inconspicuous permanent wall-mounting (in-wall or surface-mount)
- Separate volume control for each input channel plus master volume control, bass and treble
- 11-segment LED output level meter
- Output limiter control

Anixter No.	Vendor No.	Description
268505	WV100	100 W amp
268506	WV150	150 W amp
268507	WV250	250 W amp
235703	BBS	Backbox for surface mounting
235702	BBF	Backbox for flush mounting
235704	WMAD	Door for wall-mount power vector amps

Power Amplifiers

BOGEN



Bogen solid-state power amplifiers have been designed to fulfill the power amplification requirements of professional and commercial sound systems. Total harmonic distortion is less than 2 percent at rated output from 50 Hz to 15 kHz (MT250D and BPA60 models) or from 20 Hz to 20 kHz (HTA models).

- Distortion less than 2 percent THD
- Transient protection diodes
- Frequency response -2 dB from 20 Hz to 20 kHz
- Multiple output voltage/impedances available
- UL Listed

Anixter No.	Vendor No.	Description
235688	MT250D	250 W amp
235687	HTA250A	250 W amp
235686	HTA125A	125 W amp
235685	BPA60	60 W amp
273237	RPK53	Rack panel kit for BPA60



Bogen Paging

M-Class Amplifiers

BOGFN



The Bogen M-Class amplifier delivers on what professional sound installers need most: flexibility, power and reliability. Power: up to 600 W per channel stereo or 1,200 W of 70 V mono power. Reliability: massive power toroid and heat sinks, heavy 14-gauge chassis, back-slope AC voltage stabilization, clip limiters, DC voltage over-current, and thermal protection circuits. Three operating modes: stereo, 70 V mono, dual mono.

FEATURES

- Three operating modes: stereo, 70 V mono, dual mono
- Three mono power levels: 600 W, 900 W or 1,200 W for 70 V speaker systems

kit

• Three stereo power levels: 300 W, 450 W or 600 W

Anixter No.	Vendor No.	Description
235630	M600	600 W amp
235629	M450	450 W amp
235627	M300	300 W amp
268508	RPK86	Rear rack-mount

Gold Seal Series Amplifiers

BOGEN



The Gold Seal Series amplifiers are designed to meet the rigorous requirements of today's sophisticated sound systems. They combine unique and useable features with ultra-high reliability and professional performance. The amplifiers are available in 35 W, 60 W, 100 W, 150 W and 250 W models, each with exactly the same features to provide power and performance no matter how large or small the application.

FEATURES

- Dual-function, 10-band graphic equalizer
- Four dedicated microphone inputs
- 4 ohms direct aux input
- 8 ohm, 25 V, 25 V CT, and 70 V transformer coupled outputs
- Two rack spaces

Anixter No.	Vendor No.	Description
235635	GS35	35 W amp
235667	GS60	60 W amp
235668	GS100	100 W amp



Black Max Amplifiers

GSTRC

235672

BOGEN



Security cover for GS amps

Bogen's Black Max amplifiers are designed to provide maximum performance in constant voltage speaker systems. Dual 70 V transformerless outputs deliver exceptionally clean audio to speaker systems requiring two channels of audio up to 600 W per channel. Built-in power sequencing for multiple Black Max amplifiers combats current in-rush problems of large audio systems.

FEATURES

- Dual 70 V amplifier channels
- 300 W, 450 W or 600 W per channel for 70 V speaker systems
- Built-in power sequencing of other Black Max amplifiers

Anixter No.	Vendor No.	Description
268538	X600	600 W amp
268539	X450	450 W amp
268541	X300	300 W amp
268508	RPK86	Rear rack-mount kit

Talk-back Amplifier

BOGEN



The TBA15 is a unique amplifier that permits loudspeakers to be used as microphones to provide hands-free, two-way conversations through the paging system. In the idle state, the TBA15 uses the attached speakers as microphones and feeds this signal out to a telephone line. When the TBA15 senses a paging signal on the telephone line, it will switch on its 15 W amplifier and use the speakers conventionally.

- Hands-free two-way conversations through the paging system
- 15 W of speaker power
- Works on 25 V and 70 V speaker systems



· Wall- or 19 in. rack-mount

• Talk-back and page volume controls

Anixter No. Vendor No. Description
235725 TBA15 Talk-back amp, 15 watt

Classic Series Mixer Amplifiers

BOGEN



The Classic Series amps are mixer amplifiers intended for a variety of application sizes.

FEATURES

- 10 W, 20 W, 35 W, 60 W and 100 W models
- Balanced low-impedance microphone inputs; high-impedance auxiliary input
- Microphone precedence over aux 2 input with customer-supplied switch
- Selector switch permits 2 mic/1 aux or 1 mic/2 aux operation
- Provision to drive tape recorder, booster amplifier, 500/600 W telephone line
- UL and CSA Listed

Anixter No.	Vendor No.	Description
235673	C10	10 W amp
235674	C20	20 W amp
235678	C10M0H	10 W amp/1 W MOH
235679	C20M0H	20 W amp/1 W MOH
078310	C35	35 W amp
198438	C60	60 W amp
068202	C100	100 W amp
273232	RPK35B	Rack panel kit for C10 (MOH) and C20 (MOH)
198437	RPK50	Rack panel kit for C35, C60 and C100
273233	WMK1	In-wall mounting kit for C10 (MOH) and C20 (MOH)

Mixer/Pre-amplifier

BOGEN



FEATURES

- Active mixer
- Supplies mic-level and high-level outputs
- Separate volume controls for each input channel plus master controls
- Ideal for multiple-microphone public address applications
- Multiple units may be interconnected for more mic inputs

Anixter No.	Vendor No.	Description
235734	CAM2	Mixer/pre-amplifier, five inputs
235733	CAM8PR0	Two-channel, mic-mixer, with
		compressor/limiter, eight inputs
235732	CAM8	Two-channel, mic-mixer, eight inputs

ProMatrix Digitally Matrixed

BOGEN



The ProMatrix Digital Matrixed amplifier is the first of its kind to incorporate three independent amplifier channels with a unique digital interface, providing the ideal solution for restaurant, lounge/bar hotel, factory or similar facilities where multiple program and paging inputs need to be distributed to separate areas and automatically switched.

- Three independent amplifier channels rated 20, 60 and 100 W
- Two Lo-Z balanced mic inputs and four aux inputs
- Provision for telephone paging
- Flexible priority assignments for each input on each amplifier channel
- Automatic switching of inputs based on input activity
- Password-protected programming mode
- Wireless remote control

Anixter No.	Vendor No.	Description
235633	PM3000	Three-channel digital control pre-amp
235631	PM3180	Digital matrixed amplifier
235634	RMPWMK3	Remote mounting panel kit for front panel
273239	RPK79	Rack-mounting kit



Bogen Paging

Professional Boundary and Overhead Hanging Microphones

BOGFN



The SCU250 is a boundary microphone. This electret condenser model features a heavy copper case with a matte black finish; mounting keyways for hanging or for attachment to the mounting surface; a cardioid pickup pattern; an extra-wide frequency response of 20 Hz to 18 kHz; a maximum SPL limit of > 130 dB; a 26 ft. cable terminated by a detachable XLR connector with internal pre-amp and phantom power supply unit adapter; a 250-ohm impedance; and a sensitivity of -68 dB V at 74 dB SPL

The WCU250 is an overhead electret condenser microphone perfect for picking up large groups such as choirs and orchestras. The WCU250 has a frequency response of 50 Hz to 18 kHz; a maximum SPL limit of > 130 dB; a high-tensile cable with mini-XLR output plug and mini-XLR to XLR adapter; and a matte black finish.

Anixter No.	Vendor No.	Description
241423	SCU250	Boundary, condenser, unidirectional
268522	WCU250	Overhead hanging choir,
		condenser, unidirectional

Desktop Microphones

BOGEN



High-quality compact desktop microphone for sound reinforcement applications. Cuts through noisy backgrounds of live-miking situations and large gatherings.

FEATURES

- Desktop microphone
- Push-to-talk
- Lock

Anixter No.	Vendor No.	Description
235767	MBS1000A	Omnidirectional, push-talk/lock
235766	DDU250	Unidirectional, push-talk/lock

Gooseneck Microphones

BOGEN



The GCU250, GDU150 and MGN19 are gooseneck models. The GCU250 is an electret condenser microphone featuring a slim, semirigid, adjustable, 18 in. gooseneck body length with an integral XLR mounting base; a cardioid pickup pattern; a wide frequency response range of 50 Hz to 18 kHz; a maximum SPL limit of >130 dB; a 250-ohm impedance; and a sensitivity of -68 dB V at 74 dB SPL. The GDU150 is a dynamic microphone featuring a 16 in. long flexible gooseneck body with an integral XLR mounting base; a cardioid pickup pattern; a push-on/push-off talk switch; a 500-ohm impedance; and a sensitivity of -75 dB V at 74 dB SPL. The MGN19 is extremely reliable and durable. It features 7 ft. of four-conductor, two-shielded, permanently attached, synthetic jacketed cable, and a DPDT push-to-talk button-operated sealed microswitch mounted on the microphone housing.

Anixter No.	Vendor No.	Description
268524	GCU250	18 in., semi-rigid, condenser, unidirectional
268525	GDU150	16 in., flexible, dynamic, unidirectional
268526	MGN19	19 in., flexible, dynamic, omnidirectional

Microphone Accessories

BOGEN



Bogen offers a variety of microphone accessories to support their wide range of microphones.

Anixter No.	Vendor No.	Description
273240	MAC	Cable, 25 ft., female XLR to stripped and
		tinned wires
273241	XLR25	Cable, 25 ft., male XLR to female XLR
273243	MFM	Flange mount (GCU250, GDU150)
273244	MSM	Shock mount (GCU250, GDU150)
273246	MC27	Handheld clip (HD0100, HDU150, HDU250)
273247	SF4	Floor stand, 34 in. to 62 in.
273268	SB6	Floor boom stand, 34 in. to 62 in.
273255	DS3	Desk stand, 3 in. chrome finish tube
273269	WSGCU250	Windscreen for GCU250



Hand-held Microphones

BOGFN



These professional microphones are specially designed, high-output microphones that deliver high performance, reliability and accurate pickup for both vocal and instrumental sound. They are an excellent choice for professional recordings, live performances and other critical sound reinforcement applications.

FEATURES

- Light weight
- Ruggedly constructed

Anixter No.	Vendor No.	Description
235761	HDU250	Neo magnet dynamic, unidirectional
235763	HDU150	Dynamic, unidirectional
235764	HD0100	Dynamic, omnidirectional
390991	UDMS16HH	Wireless mic system, hand held
394175	UDMS16BP	Wireless mic system, body pack

Modular Lectern Array

BOGEN



Bogen lecterns are self-powered, self-contained systems utilizing high-end speaker array concepts to provide superior horizontal dispersion in a modular design for maximum flexibility. The MLA40 is a free-standing lectern that can also be configured for tabletop use. The MLA40T is a tabletop version of the lectern. Both are ideal for use in schools, churches, hotels and rental situations.

FFATURES

- Two models: MLA40 free-standing lectern with six 8 in. speakers and MLA40T tabletop lectern with two 8 in. speakers
- Built-in amplifier 40 W rms

- Switched and unswitched external speaker jacks for quick connection and disconnection of external speakers
- Switched jack automatically disables built-in speakers
- Two mic (Lo-Z) and one aux (Hi-Z) inputs, each with independent volume controls
- Automatic level control for enhanced intelligibility (defeatable)
- Intelligibility-enhancing speech filter (defeatable)
- Shock-mounted, high-quality, cardioid condenser 15 1/4 in. gooseneck microphone included
- Independent phantom power for condenser microphone on each mic input
- Recessed brass reading lamp with separate on/off switch or controlled by main power switch

Anixter No. Vendor No. Description

304648 MLA40 Modular lectern array, tabletop and

podium sections

304649 MLA40T Modular lectern array, tabletop section only

Attenuators

BOGEN





The AT series of attenuators allows the output level of a group of loudspeakers to be set from a wall-mounted volume control, without affecting overall amplifier volume settings. These rugged attenuators have 10 levels of sound control plus an off setting.

FFATIIRES

- Adjusts loudspeaker output levels on 25 V and 70 V systems
- Two models control up to 10 or 35 W speaker systems
- Ten attenuation steps and an off setting
- Mounts in standard electrical box
- Simple connections

Anixter No. Vendor No. Description

241327 AT35A 35 W (double-gang size) **178764** AT10A 10 W (single-gang size)



Bogen Paging

Advanced Input Modules

BOGEN



For Bogen M-Class and Power Vector amps.

Anixter No.	Vendor No.	Description
235731	TEL1S	Telephone input, loop/ground start
235730	SAX1R	Stereo aux input, dual RCA
235729	MIC1X	Mic input module, transformer isolated, XLR
235728	MAX1R	Mono aux input, RCA
235727	BRG1R	Bridging module, RCA
259880	BAL2S	Hi-Z stereo-balanced input module
259881	MIC1S	Mic input module, balanced, transformer isolated, screw terminals
259882	MIC2S	Mic input module, electronically balanced, transformer-isolated, screw terminals
259883	MIC2X	Mic input module, balanced, transformer-isolated, XLR
259884	TBL1S	Transformer, balanced line input
259885	TNG1S	Tone generator

Advanced Signal-processing Output Modules

BOGEN



Output modules for Bogen Power Vector and Wall-mount Power Vector amps.

par moaaroo n	2000	. rooter and man mount of
Anixter No.	Vendor No.	Description
268534	ANS1R	Ambient noise sensor
268535	CMP1R	Compressor limiter
268536	PEQ1R	Parametric equalizer

Transformer

BOGEN



The Bogen RIO1S is a multifunctional module with a priority-controlled relay contact, transformer-balanced input, transformer-balanced output and an RJ11 output for direct connection to the override input of a zone paging system.

Anixter No.	Vendor No.	Description
301258	RI01S	Relay/input/output
		transformer-balanced module

FM Tuner

BOGEN



The Bogen FMR Model is an economical FM radio/receiver especially designed to provide background music over a paging system or supply music-on-hold to a telephone system. The unit has 1 W and line-level outputs to facilitate connection to a variety of paging/telephone systems including an amplified speaker.

FEATURES

- Economical background music/music-on-hold source
- Choice of 1 W output for music-on-hold or line output for background music
- Automatic frequency control (AFC) prevents signal drift
- Uses 12 V DC or 24 V DC power supply (not included)
- Wall-mount design

Anixter No. Vendor No. Description

235757 FMR FM background music/music-on-hold tuner



AM/FM 35-watt Receiver

BOGFN



The RM350D is a unique self-contained paging system with an AM/FM tuner, providing 35 W of paging power. A low-impedance, balanced microphone input is provided for microphone paging announcements or telephone paging when used with an accessory transformer (WMT1A).

A music-only output can feed announcement-free background music to other equipment or to a telephone music-on-hold input.

FEATURES

- 35 W amplifier for 4- to 8-ohms, 25 V or 70 V speaker systems
- Built-in AM/FM tuner
- 18 FM and 12 AM station presets
- Single-button control for All-Call

Anixter No. Vendor No. Description

408495 DRZ35 Four-zone music and paging system

Analog Door Phone

BOGEN



Bogen's Door Phone provides convenient remote, hands-free, two-way communication between two locations. Durable, weather-resistant, stainless steel construction protects against vandals and varying weather conditions.

FEATURES

- Phone line-powered
- Two-way, hands-free communication
- Adjustable speaker and microphone volume
- Adjustable call-timer duration

Anixter No. Vendor No. Description 273301 ADP1 Door phone

Interphones

BOGEN



The TP Series of interphones are an ideal way of providing simple telecommunications between different areas in a facility. Simple to install and operate, these phones provide system-wide paging as well as telephonic communications.

FEATURES

- Six- or twelve-station capacity
- Telephonic communications between stations
- Built-in all-station paging

Anixter No. Vendor No. Description

273299TP6APSix-station-capacity interphone273300TP12APTwelve-station-capacity interphone

Teleconference Phone

BOGEN



The VHUB Teleconference Phone is a full-duplex, simultaneous, two-way communication conference phone that provides clean, clear sound for all of your teleconferencing needs. With three microphones, an easy-to-read recessed LCD display, 10-number speed dial, special calling functions and a simple three-step setup process, the VHUB Teleconference Phone is everything you could ask for in a conference phone and more.

FEATURES

- · Full-duplex operation
- DSP-based echo cancellation
- High-quality speaker
- LCD display screen
- Three omnidirectional microphones

Anixter No. Vendor N880. Description
256440 VHUB Teleconference phone



Bogen Paging

Intercom Systems

BOGEN



Bogen's CM Series of intercoms are ideal for interoffice communications. They provide a separate, direct communications link to other individuals in an organization. Systems can be configured as all-master systems, which allow access to any station in the system, or as master/remote systems, in which remote stations can be restricted to communicating only with specific stations.

FEATURES

- Six- or eleven-station capacity
- All-master system or any combination of masters and remotes
- Selective electronic tone calling
- Masters can call any station in system

Anixter No.	Vendor No.	Description
241336	CM206M	Six-button master
241337	CM211M	Eleven-button master
241338	CM200X	Remote station with call and privacy
241340	RF12A	12 V DC, 1 A

Intercoms

BOGEN



The PI35A and SI35A High-Powered Desktop Control Centers are dual-channel intercom and program distribution systems for applications with numerous locations, requiring maximum intelligibility of voice announcements and other sources.

FEATURES

- Communicate with 25 to 75 rooms or remote locations
- Distribute program material from microphones, tape player/tuner, or other background music sources, tone signals and emergency announcements to all or select locations
- · Five inputs

Anixter No.	Vendor No.	Description
273291	PI35A	$25\mbox{-room}$ maximum intercom and program
		distribution system
273296	SI35A	75-room maximum intercom and program
		distribution system

ANS-501 Paging Electronics

BOGEN



The ANS-501 automatically adjusts the paging levels in response to changes in the ambient noise of an area. Small sensor microphones monitor the ambient noise levels in an area served by a single amplifier. Paging signal output levels will be increased as ambient noise rises and decreased as noise levels drop. The ANS-501 control unit will adjust (boost or reduce) the input signal levels to the amplifier to ensure that the paging announcements will be heard at an audible, clear and comfortable level over the current ambient noise.

FEATURES

- Automatically adjusts paging level as ambient noise rises and falls
- Supports up to four small sensor microphones
- Sensor microphones can be located up to 2.000 ft, from control
- Only two wires needed for connection of sensor microphones
- Easily connects in at pre-amp out-power amp in process loop
- Shapes frequency response during high noise levels for best intelligibility

Anixter No. Vendor No. Description

235742 ANS501 Ambient noise sensor with power supply and

one microphone

235743 ANS500M Additional microphone for ANS500

VAR-1 Paging Electronics

BOGEN



The VAR-1 is a relay device that monitors audio activity over a wide range of input voltages and operates two sets of C-Form relay contacts in response to detected activity. The VAR-1 can be used to detect voltages as low as signals directly from a microphone or as high as signals from 70 V speaker systems. A low-level output of the detected audio, transformer-isolated from the input, is also made available for use with other equipment. Also can be used as a balanced low-impedance mic pre-amp.

FEATURES

- Two sets of C-Form (both N.O. and N.C.) relay contacts respond to audio activity
- Four levels of input signals: microphone, 600-ohms line, 25 V and 70 V speaker systems
- Built-in balanced, low-noise, high-gain microphone pre-amp Anixter No. Vendor No. Description

235749 VAR1 Voice activated relay (requires PRS40C P.S.)



DFT-120 Paging Electronics

BOGFN



The DFT-120 eliminates the acoustical feedback loop created by the telephone handset and the paging speaker, while providing high-capacity, high-quality recording and playback of audio pages.

FEATURES

- High sampling rate for excellent playback quality
- Ability to record a message while another is played
- Wall-mountable

Anixter No. Vendor No.

Description

235744 DFT120

Digital paging feedback terminal

TAMB Paging Electronics

BOGEN



The TAMB interfaces a telephone system with a paging system, allowing announcements to be made through any telephone. Any of these types of analog ports can be connected using the TAMB: loop-start trunk, ground-start trunk and station port (90 V ring-up). This wide range of port compatibility makes the TAMB indispensable for any telephone paging application because it eliminates the possibility of mismatching paging interfaces and port types.

FEATURES

- Loop-start, ground-start and station port (90 V ring-up) compatibility
- 600-ohms output
- Built-in confirmation tone indicating access to paging system (defeatable)
- Built-in pre-announce tone produced over paging system before announcement (defeatable)
- · Adjustable tone volume

Anixter No. Vendor No.

Description

103572 TAMB

Telephone access module

TG-4C Paging Electronics

BOGEN



The TG-4C is designed to produce four different types of tones for use as alarm or announcement signals in paging systems. An audio signal can be routed through the TG-4C to allow easy installation in paging systems. During generation of the tones, the routed audio will be suppressed.

FEATURES

- Four types of tones: steady, pulsed alarm, slow whoop and chime
- Tones triggered by external contact closure (momentary or long duration)
- Choice of continuous generation of tones or two-burst operation (except for steady tone)
- 600-ohms output

Anixter No. Vendor No.

Description

178761 TG4C

Telephone generator (requires PRS40C P.S.)

ZPM3 Zone Paging

BOGEN



The ZPM3 allows for economical one- or two-way paging (with TBA 15 Talk-Back Amplifier) to be directed into any of up to three different paging areas. Zones can be grouped together so that more than one zone is paged at the same time. All areas can also be paged at once. Zone selection can be made using DTMF tones or pulse dialing.

FEATURES

- Three-zone paging plus All-Call
- Three easily programmable zone groups (one to three zones in each)
- 100 W total power handling capability
- Background music input

Anixter No. Vendor No.

Description

178742 ZPM3

Independent three-zone paging module



Bogen Paging

PCM-2000 Zone Paging Systems

BOGEN



The PCM-2000 allows you to design a system that is specifically tailored to the requirements of the facility owner. The basic system supports up to three paging zones and consists of only three modules: central processor, telephone interface and zone module plus a power supply. Two additional zone modules can be added to the basic system to increase capacity to nine zones. When more than nine zones are required, a central processor module and up to three zone modules can be assembled as a satellite system. Ten additional nine-zone satellite systems can be installed to bring total zone capacity to 99 zones. When hands-free talk-back is desired, a single talk-back module can also be added to the system.

All interface programming uses common dip switches. Zone group programming, selection of signaling functions and all other parameters are easily set up by simply dialing in with a touch-tone phone. The system can support simultaneous high- and low-power paging, background music assigned per zone, local background music sourcing, and emergency zone group with choice of built-in tones or outside tone source.

Anixter No.	Vendor No.	Description
163464	PCMCPU	Central processor module
176038	PCMTIM	Telephone interface module
163466	PCMZPM	Zone module
176056	PCMTBM	Talk-back module
235739	PCMPS2	Power supply (one required per PCMCPU)

UTI1 Zone Paging Systems

BOGEN



The UT11 Universal Telephone Interface provides single-zone paging for one-way applications such as self-amplified speaker systems. It is compatible with all standard analog port types and includes two audio outputs with level controls, each of which can provide audio for 150 Bogen self-amplified speakers. A 24 V DC at 1 A internal supply is available to power external equipment.

FEATURES

- Emergency and general All-Call paging
- Interface with any telephone port type
- Background music input with variable muting options

- 24 V DC 1 A power supply included
- Output limiter ensures consistent page volume
- Override, triggered tones, night ring and aux relay contact
- 150-speaker T/R drive capacity per output

Anixter No. Vendor No. Description

304654 UTI1 Single-zone universal telephone interface 304655 RPKUTI1 Rack-mount and security cover kit

UTI312 Zone Paging Systems

BOGEN



The UTI312 Zone Paging Controller provides multizone paging for one-way applications such as self-amplified speaker systems, with each output capable of providing audio for up to 150 Bogen self-amplified speakers. The UTI312 is compatible with all standard analog port types. Each UTI312 comes with a pre-installed ZX3 module for three zones of paging and is expandable up to 12 zones. The UTI312 offers up to 24 programmable paging zone groups as well as All-Call, auto select, override, night ring, two tone triggers and code-calling zone groups. The UTI312 also offers flexible dialing.

FEATURES

- Expandable from three to twelve zones with ZX3 (one to three zone) modules
- Up to 24 paging zone groups
- Interface with any telephone port type
- Two background music inputs with variable muting options, assigned by zone
- 24 V DC 1 A power supply included
- Override, triggered tones, night ring, code calling and aux relay contact
- 150-speaker T/R drive capacity per output

Anixter No. Vendor No. Description

304656 UTI312 Multizone universal telephone interface 304657 ZX3 Three-zone expansion module for UTI312

VoIP Paging

BOGEN



Businesses can be set up for simultaneous company-wide overhead paging to multiple locations within a facility or across a campus without running new lines, or even to remote locations thousands of miles away. Bogen's zone paging controllers, the TAMB, and amplifiers integrate seamlessly with VoIP gateways to provide overhead voice paging over IP networks.



FEATURES

- Utilizes existing Ethernet network
- Simultaneous overhead voice paging to multiple locations within a facility, nearby or branch office buildings, or to remote locations using the Internet or Intranet
- Single- or multizone paging at any or all locations
- Efficiently communicate company-wide emergency alerts or general announcements, saving both time and money while improving communication
- Connects directly to phones or PBX; compatible with virtually any telephone port type
- Configurable from a Web browser or Microsoft Windows

Anixter No.	Vendor No.	Description
304650	MVP130BG	1-port VoIP gateway
304651	MVP210BG	2-port VoIP gateway
304652	MVP410BG	4-port VoIP gateway
304653	MVP810BG	8-port VoIP gateway

NR-100 Night Ringer

BOGEN



Model NR-100 connects to an amplifier via an auxiliary input and provides an electronic ring signal throughout the sound system when activated by telephone system night bell circuitry. Eliminates the need for separate night bells to alert security or other personnel of incoming calls. Operates from either 90 V ring signal or contact closure. Automatically mutes background music.

FEATURES

- Responds to 90 V ring signals or external system
- Produces dual-frequency electronic ringer tone
- Easily connects to any paging system
- Automatically mutes background music while ringing

Anixter No. Vendor No. Description
107320 NR100 Night ringer

ProHold Music-on-Hold

BOGEN



Bogen's ProHold products are music-on-hold announcers that turn a caller's on-hold waiting time into productive information and selling time. This system assures simple, reliable and high-quality playback of messages/music.

FEATURES

- Provides music and messages to callers placed on hold
- Clear digital audio quality
- Digital program transmission accuracy
- 600-ohms transformer-balanced output and 1 W into 8-ohms output
- Single-track control allows separate downloading of music and message so either can be changed at any time without affecting the other part of the program
- Audio files for download are standard WAV format, compatible with most studio editing and production software
- Store separate programs to run day/night, weekend or holiday/normal

Anixter No.	Vendor No.	Description
184955	PR04	Four-minute capacity
235751	PR08	Eight-minute capacity
184958	PR012	Twelve-minute capacity
235753	PR016	Sixteen-minute capacity

TPU Series Telephone Paging Amplifiers

BOGEN



Specifically designed for telephone paging, the TPU Series of amplifiers offers a choice of rated power output from 15 to 250 W. Input terminals are provided for a 600-ohms balanced telephone line and a background music source, as well as a balanced low-impedance microphone in the TPU-250, TPU-100B, TPU-60B and TPU-35B. Bridging jacks which double your outputs are also provided. The built-in night ringer sounds a tone through the paging system speakers when triggered by an external contact closure. Voice-activated circuitry automatically mutes or fades music when paging, eliminating mechanical and background noise. The TPU amplifiers also feature the Aphex Aural Exciter circuit for increased presence and intelligibility, greater perceived loudness (with no increase in power) and reduced listener fatigue. The compact units mount easily on a wall and only a screwdriver is needed for all connections and adjustments. UL and CSA Listed.

Anixter No.	Vendor No.	Description
106151	TPU15A	15 W
106149	TPU35B	35 W
106150	TPU60B	60 W
103745	TPU100B	100 W
235724	TPU250	250 W



Bogen Paging

Volume Controls

BOGFN



The BUFEX is a continuously variable speaker attenuator that can remotely control the volume of a network of speakers. The BUFEX also provides output buffering for up to 150 self-amplified speaker inputs and allows speaker system expansion from existing 100 V, 70 V or 25 V central amplifier systems. The BUFEX includes a bypass function that can override the volume control knob setting (even if set low or off) when activated by a contact closure or open collector output. A PCB-mounted bypass trim control adjusts the volume when in bypass mode with a maximum of 12 dB of attenuation. This allows emergency announcements to be heard through all speakers in a system. The BUFEX fits into a single-gang electrical box.

FEATURES

- Volume control for a network of speakers
- Buffer drives up to 150 speakers
- Bypass feature allows emergency announcements to be heard even when local speaker volume is set low or off
- Expand 100/70/25 V systems
- Ten position settings plus off

BUFEX

Anixter No. Vendor No.

304669

Description

Attenuator, buffer, and speaker expander for amplified speakers

Volume Controls

BOGEN

The SLC is a continuously variable volume control that can remotely control the volume of up to 150 self-amplified speakers. The SLC fits into a single-gang electrical box.

FEATURES

- Volume control for network of speakers
- Easy to install, wire with audio feed to speakers
- Ten position settings plus off
- Secure terminal strip connections

Anixter No. Vendor No. Description

304670 SLC Passive volume control for amplified speakers

Loop Start Interface/Power Supply

BOGFN



The PRSLSI serves as both a loop start interface and as a 24 V DC power supply.

FEATURES

- 24 V DC, 450 mA power supply
- Loop start interface for small paging systems
- Integral flanges for wall-mount; rubber feet for shelf-mount
- Six-terminal barrier strip
- UL and CSA Listed

Anixter No. Vendor No.

or No. Description

304658 PRSLSI

Loop-start interface, 24 V DC, 450 mA

power supply

Power Supplies

BOGEN



These power supplies are designed to supply the low-voltage DC requirements for Bogen products. Corded or outlet-mounted, 120 V AC primary supply input.

FFATIIRE

- Specially designed for use with Bogen equipment
- Wide range of voltages and current outputs

 Anixter No.
 Vendor No.
 Description

 241334
 PRS48
 48 V DC, 100 mA power supply

 241335
 PRS40C
 12 V DC, 300 mA power supply

 241340
 PE12A
 12 V DC, 1A

241340 RF12A 12 V DC, 1 A **273238** RF24A 24 V DC, 1 A



Wall-mount Power Supplies

BOGEN



Bogen's switching power supplies provide large current capacities in compact packages. They include easy and secure wall mounting with holsters or flange mounting.

FEATURES

- 24 V DC, power supply
- Loop start interface for small paging systems
- · Integral flanges for wall mount; rubber feet for shelf mount
- Six-terminal barrier strip
- UL and CSA Listed

Anixter No.	Vendor No.	Description
304674	SPS2454	24 V DC at 5.4 A
304676	SPS2425	24 V DC at 2.5 A
304677	SPS2410	24 V DC at 1 A
304678	SPS2406	24 V DC at 600 mA
304679	PRS2403	24 V DC at 300 mA, non-switching

Flange-mounted Re-entrant Type Horn

BOGEN



FEATURES

- 15 watts max. @ 70 V or 25 V
- Weatherproof design for indoor or outdoor use
- Vandal resistant, for applications in hostile environments
- All metal construction with black enamel finish
- Select flush- (BBFM6) or surface- (BBSM6) mount enclosure for installation (each sold separately)

Anixter No	. Vendor No.	Description
369379	FMH15T	Flange-mounted re-entrant type horn
369380	BBFM6	Flush-mount enclosure, black
369381	BBSM6	Suface-mount enclosure, white
369382	FMHAR8	Mounting adapter ring for FMH15
369383	SGHD8	Heavy-duty grille for FMH15, use with FMHAR8

High-fidelity Ceiling Speaker, Low Profile

BOGFN



FEATURES

- 6 3/4 in. mounting depth for installations into a variety of ceiling environments including suspended and hard surface ceilings
- Low-profile housing allows greater range of installation depths
- Computer-matched venting system for full bass output
- Wide dispersion coaxial driver provides broad, even coverage
- For 16 ohm, 70 V and 100 V systems
- Off-white finish

Anixter No.	Vendor No.	Description
265155	TBCR	Tile bridge and c-ring support ring
268547	CK-10	10 ft. long cable kit, silver
367042	HFCS1LP	High-fidelity ceiling speaker, low profile

High-fidelity, Small-footprint Ceiling Speaker

BOGEN



FEATURES

- Wide-dispersion coaxial driver for broad, even coverage; superb off-axis response
- Visually appealing, only 7 3/16 in. in diameter
- 4 in. cone speaker with tweeter
- Installs in wide range of ceiling types
- For 16 ohm and 70 V systems
- Selectable power taps via front-mounted control (under grille); 16, 8, 4, 2, 1 watts at 70 V

Anixter No.	Vendor No.	Description
268547	CK-10	10 ft. long cable kit, silver
369385	HFSF1	High-fidelity ceiling speaker, low profile
369386	TBSF	Tile bridge support
421328	CSUB	High-fidelity ceiling subwoofer



Bogen Paging

Drop-in Ceiling Speaker with Volume Control

BOGEN

FEATURES

- Recessed volume control accessible from front of grille
- · Easy assembly saves installation time, effort, and cost
- 1 ft. x 2 ft. perforated grille over entire front; off-white finish
- 8 in. cone speaker with 10 oz magnet and tweeter, and 25/70 V transformer
- Five power taps (4 W, 2 W, 1 W, 1/2 W and 1/4 W); selectable by rotary switch
- Complies with NFPA National Code 160b and UL 2043

Anixter No. Vendor No.

Description

369388 CSD1X2 Ceiling speaker, drop-in 1 ft. x 2 er. with

volume control

Drop-in Ceiling Speaker with No Back

BOGEN



FEATURES

- Exposed driver
- · Easy assembly saves installation time, effort and cost
- 1 ft. x 2 ft. perforated grille over entire front; off-white finish
- 8 in. cone speaker with 6 oz magnet and tweeter, and 25/70 V transformer
- Six power taps (4 W, 2 W, 1 W, 1/2 W, 1/4 W and 1/8 W); selectable by stripped and tinned leads

Anixter No. Vendor No.

Description

369389 CSD1X2NB Ceiling speaker, drop-in 1 ft. x 2 ft, no back

speaker enclosure

Drop-in Ceiling Speaker, No Back with Volume Control

BOGEN

FEATURES

- Exposed driver
- Recessed volume control accessible from front of grille
- · Easy assembly saves installation time, effort and cost
- 1 ft. x 2 ft. perforated grille over entire front; off-white finish
- 8 in. cone speaker with 6 oz magnet and tweeter, and 25/70 V transformer
- Six power taps (4 W, 2 W, 1 W, 1/2 W, 1/4 W and 1/8 W); selectable by stripped and tinned leads

Anixter No. Vendor No.

Description

369391 CSD1X2NBVR Ceiling speaker, drop-in, 1 ft. x 2 ft. no back speaker enclosure, with volume control

Drop-in Ceiling Speaker with Volume Control

BOGEN

FEATURES

- Recessed volume control accessible from front of grille
- Easy assembly saves installation time, effort and cost
- Tile support rail for 2 ft. x 4 ft. ceilings included
- 2 ft. x 2 ft. perforated grille over entire front; off-white finish
- 8 in. cone speaker with 10 oz magnet and tweeter, and 25/70 V transformer
- Five power taps (4 W, 2 W, 1 W, 1/2 W and 1/4 W); selectable by rotary switch
- Complies with NFPA National Code 160b and UL 2043

Anixter No. Vendor No. 368434 CSD2X2VR

Description

Ceiling speaker, drop-in, 2 ft. x 2 ft., with

volume control



Telephone Accessories

AT&T 1738 Answering System

VTECH COMMUNICATIONS INC



FEATURES

- Advanced digital sound quality
- Time/day stamp
- Message Guard memory for power failures
- Call screening/intercept
- Remote access with toll saver
- 40-minute record time
- Message counter
- Number announce

Anixter No. Vendor No. Description 359286 1739 White mist

Handset Cords

LYNN ELECTRONICS



These are fully modular, 4-conductor handset cords.

6-FOOT CORDS

Anixter No.	Vendor No.	Description
066637	L-H4DU-06-LA	Ash
060676	H4C-M-M-6-BE	Beige
038424	H4C-M-M-6-BK	Black
095529	H4C-M-M-6-IV	lvory
082081	H4C-M-M-6-WH	White

9-FOOT CORDS

Anixter No.	Vendor No.	Description
097184	H4C-M-M-9-ASH	Ash
061851	H4C-M-M-9-BE	Beige
072680	H4C-M-M-9-BK	Black
061850	H4C-M-M-9-IV	lvorv

12-FOOT CORDS

Anixter No.	Vendor No.	Description
066641	H4C-M-M-12-ASH	Ash
079868	H4C-M-M-12-BE	Beige
066864	H4C-M-M-12-BK	Black
066644	H4C-M-M-12-IV	lvory
062030	H4C-M-M-12-WH	White

15-FOOT CORDS

Anixter No.	Vendor No.	Description
057673	H4C-M-M-15-ASH	Ash
041771	H4C-M-M-15-BE	Beige
072681	H4C-M-M-15-BK	Black
043602	H4C-M-M-15-IV	lvorv

25-FOOT CORDS

Anixter No.	Vendor No.	Description
067059	H4C-M-M-25-ASH	Ash
060664	H4C-M-M-25-BE	Beige
096913	H4C-M-M-25-BK	Black
060663	H4C-M-M-25-IV	lvory
043264	H4C-M-M-25-WH	White
166867	H4C-M-M-25-CG	Charcoal gray

Replacement Handsets

LYNN ELECTRONICS



8000 SERIES REPLACEMENT HANDSET

K-Type replacement handset for all phones in the 8000 Series.

Anixter No. Vendor No. Description 185547 B-1000 Black

8000 SERIES AMPLIFIED HEARING HANDSET

Amplified hearing handset for the 8100 Series of the PARTNER 18- or 34-button display. Thumbwheel adjustment provides 0 to 20 dB (nominal) gain over standard handset. This handset is hearing aid-compatible.

Anixter No. Vendor No. Description 143572 010K-B Black 157203 010K-MC Misty cream

7000 SERIES REPLACEMENT HANDSET

R-type replacement handset for all phones in the 7000 Series.

 Anixter No.
 Vendor No.
 Description

 125897
 3152-009
 Black

 125896
 3152-009
 Misty cream

Continued on next page >>



Telephone Accessories

(continued) Replacement Handsets

7000 SERIES AMPLIFIED HEARING HEADSET

R-type amplified handset for the 7000 Series voice terminal. Thumbwheel adjustment provides 0 to 20 dB (nominal) gain over standard handset.

Anixter No. Vendor No. Description 105963 010M-B02D Black 105964 010M-MC Misty cream

W3 Series Replacement Handsets

WALKER EQUIPMENT



G-STYLE (500) STANDARD HANDSETS

 Anixter No.
 Vendor No.
 Description

 104315
 W3-500M-00
 Black

 107236
 W3-500M-09
 Ivory

 220398
 W3-500M-44
 Ash

K-STYLE STANDARD HANDSETS

 Anixter No.
 Vendor No.
 Description

 104649
 W3-K-M
 Black

 107240
 W3-K-M-09
 Ivory

 267463
 W3-K-M-44
 Ash

W6 Series Amplified Replacement Handsets

WALKER EQUIPMENT



K-STYLE ELECTRET TRANSMITTER

 Anixter No.
 Vendor No.
 Description

 087750
 W6-K-M-00
 Black

 074935
 W6-K-M-44
 Ash

G-STYLE (500) CARBON TRANSMITTER

Anixter No. Vendor No. Description 099574 W6-500M-44 Ash

G-STYLE (500) ELECTRET TRANSMITTER

 Anixter No.
 Vendor No.
 Description

 094412
 W6-500M-00
 Black

 084178
 W6-500M-09
 Ivory

G-STYLE (500) CARBON TRANSMITTER, NOISE-CANCELING

 Anixter No.
 Vendor No.
 Description

 107042
 W6-500M-NC-1-00
 Black

 122885
 W6-500M-NC-1-44
 Ash

Push-to-talk Handsets

WALKER EQUIPMENT



500-Type push-to-talk carbon transmitter.

Anixter No. Vendor No. Color 211846 PTT-500TCM-00 Black

Noise Censor

WAI KFR FQUIPMENT



Noise censor converts standard G-Style handset into a noise-canceling handset.

Anixter No.	Vendor No.	Descriptio
120454	NC-1-00	Black
128072	NC-1-09	lvory
120456	NC-1-13	Beige
127498	NC-1-44	Ash



Telephone Accessories

In-line Handset Amplifier

WALKER EQUIPMENT



Small, separate units that plug into the side of the telephone, powered by an AC/DC converter. The original telephone handset plugs into the amplifier. Amplifier unit has a volume-control dial to adjust sound level up or down. Amplifies call by 20 dB. Compatible with most standard and electronic telephones.

Anixter No.	Vendor No.	Descriptio
081278	W10-09	lvory
082668	W10-00	Black
087362	W10-44	Ash

Mini-size Shoulder Rest

SOFTALK



The Mini-Softalk was designed to fit on phone handsets with flat backs, such as the popular Merlin and many of the cordless phone designs. It is compact, but still offers the convenience of a comfortable phone rest.

Anixter No.	Vendor No.	Description
083280	301	Black
083282	305	lvory
083284	315	Ash
129876	335	Misty cream

Standard-size Shoulder Rest

SOFTALK

Anixter No.	Vendor No.	Description
083266	100	Beige
083267	101	Black
083271	105	lvory

TWISSTOP

PROFORMA PRINTGRAPHICS



Eliminates twisted and tangled handset cords. TWISSTOP installs quickly and easily into the standard modular jack on virtually any telephone handset.

Anixter No.	Vendor No.	Description
121861	10414	Almond
097959	40414	Clear

ComSwitch Line-sharing Devices

COMMAND COMMUNICATIONS

Reduce communications expenses by using one of the ComSwitch series of line-sharing devices, the perfect telephone line manager for small offices/home offices. Just plug it in anywhere on a regular telephone line and all incoming calls are automatically routed to the correct piece of equipment.

Anixter No.	Vendor No.	Description
188554	CS5500	Three devices, one line

Stinger 90 Model 196 Line-powered Ringer

DEES COMMUNICATIONS



The Stinger 90 Model 196, line-powered telephone ringer provides 110 dBA output and is driven from the ringing voltage on the CO line. Rugged weatherproof housing is suitable for indoor or outdoor use. The model 196 is equipped with a three-position switch for volume control and comes with a modular cord plus screw terminals. Can be wall-mounted.

Anixter No.	Vendor No.	Description
099058	196	Line-powered ringer

Telephone Accessories

DSI-375 Meridian Custom Ringer

DEES COMMUNICATIONS

Enhances the ringing performance of NTI's Meridian Business Sets by allowing for distinctive ringing, second-call alert-tone cadence, a common audible (loud bells) and much more.

Anixter No. Vendor No. Description
134431 DSI-375 Custom ringer

Message-waiting Lamp

VIKING ELECTRONICS



The Model LM-1A message-waiting lamp provides a visual indication of ringing and off-hook condition. Can be used for message-waiting and voicemail systems that provide 90 V DC to 120 V DC.

Anixter No. Vendor No. Description
284277 LM-1A Message waiting lamp

Two-way Ringdown Circuit

VIKING ELECTRONICS



The DLE-200B allows two-way communication between most standard telecom products such as modems, fax machines, key systems, PABXs and standard single-line telephones. Provides salespeople with an easy-to-use method of conducting on-site demonstrations. The DLE-200B eliminates the need to locate phone lines and disrupt the customer's phone service.

FEATURES

- Compatible modems and fax machine speeds up to 28.8 kbps
- 32 V DC talk battery
- Standard ring cadence (two seconds ON, four seconds OFF) and three custom/ distinctive ringing selections
- Provides 150 mS CPC breaks after hang-up on either port (which can be disabled)
- Switch-selectable audio attenuation

- Provides two seconds of precise dial tone after off hook (which can be disabled)
- Provides ring-back signal to calling device
- One- or two-way ringdown capability
- Selectable five or continuous number of rings
- Used for demonstrating telecom equipment trade shows, meetings, colleges, etc.
- Used for demonstrating the distinctive ring detection feature of Viking's FAXJ-1000
- Ringdown point-to-point communications

Anixter No. Vendor No. Description

166768 DLE-200B Two-way ringdown circuit

Amplified Remote Access Device

VIKING ELECTRONICS



The RAD-AMP extends the usefulness of your phone system to remote employees, as well as providing call forwarding to remote employees or locations. As a line extender, the RAD-AMP provides authorized users remote access to PABX, Centrex or electronic key system features. As a call diverter, the RAD-AMP provides call forwarding from one location to another. After detecting an inbound call, the RAD-AMP accesses a second phone line, dials a preprogrammed touch-tone number, and then bridges the two lines. As a telecommuting extender, the RAD-AMP gives remote workers access to most PABX/KSU features from their home or cell phone. The home-based employee hears a special tone when answering and has the option of taking the work-related call. Remote call center personnel can "Log-in" and "Log-out" or change their forwarding number as their location changes. Using touch-tones, remote workers can use phone system features to transfer the call to another extension or voice mail, start a conference call, and generate a page or any other feature available to an analog PABX/KSU extension.

FEATURES

- · Improved audio amplifier
- · Programmable six-digit security code
- Programmable ring delay
- Remote night switch
- Disconnects on CPC, busy, return dial tone, maximum call time or by dialing #7
- Nonvolatile memory (no batteries required)
- Auxiliary dry contacts
- Programmable 15-second-to-49.5-minute call timer
- Compatible with analog stations on PABX and KSU systems
- Simple programmable toll restriction

Anixter No. Vendor No. Description

224936 RAD-AMP Amplified remote access device



Telephone Accessories

Hot-line Touch-tone Dialer

VIKING ELECTRONICS



The K-1900-5 will automatically dial a preprogrammed number, of up to 32 digits, whenever an associated telephone is taken off hook. Using nonvolatile E2 memory, the K-1900-5 is phone line-powered and will operate on any loop-start central office line or analog PABX/KSU extension.

The K-1900-5 is easily programmed remotely or locally using a standard touch-tone phone.

FEATURES

- Touch-tone programmable
- Telephone line-powered
- Nonvolatile E2 memory (no batteries required)
- Ring detection (will not dial on inbound calls)
- User-programmable security code
- Programmable pauses in one- and four-second increments
- Programmable to interrupt user touch-tone dialing to help control fraudulent calls from hand-held dialers, etc.
- Programmable dialing speed (normal or fast)
- Can be configured to operate from a contact closure

Anixter No. Vendor No.

Description

193548 K-1900-5

Hot-line touch-tone dialer

Paging Amplifier Loud Ringer

VIKING ELECTRONICS



The PA-2A provides loud ringing and paging to electronic key systems, 1A2 key systems and PABXs as well as non-KSU phones and multiline phones. Paging is accomplished by connecting the PA-2A to a paging port or unused telephone line input (trunk port) of nearly any phone system. The PA-2A will also generate adjustable loud ringing from up to six analog lines or from a dry contact closure. Either a loud electronic warble, or one of three other soft-chime sounds, may be selected. An external "night transfer" switch can be added to turn loud ringing on or off in night bell applications.

FEATURES

- Two watts of paging power
- All lines are optically coupled for compatibility with fax switches and analog PABX/KSU stations
- Can provide background music from an external source (trunk mode only)
- Paging from an unused trunk port or paging port
- Choose one of four ringing sounds: electronic warble (traditional loud ringer), double gong (two identical "gong" tones), quadruple chime (four descending chime tones), door chime (ding-dong)
- Provides loud ringing or night bell, from one to six lines for warehouses, vards, etc.
- Output for controlling a 12 V relay from one to six ringing lines
- Page alert tone (trunk mode only)
- 600 ohm output for sourcing high-powered amplifiers

Anixter No. Vendor No.

Description

122272 PA-2A

Ringer and paging amp

Service Observation Unit

VIKING ELECTRONICS



The SO-24A allows supervisors to silently monitor employee phones without disrupting the activity at their workstation. The information gathered may be used for quality purposes, to train, motivate, even assist customer service and telemarketing representatives. A supervisor may enter the conversation by dialing an asterisk. A cassette recorder output permits automatic or manual recording of conversations. The SO-24A features improved audio and can now be easily expanded to 240 stations by installing additional SO-24A units. The SO-24A can be programmed with a two, three, or four digit dial-up code to match extension numbers.

FFATIIRFS

- 24-station capacity can be expanded to 240 stations at any time
- Compatible with analog PABX/KSU stations
- Configurable for digital phones (requires the SO-24 AK and a dedicated pair of wires)
- Monitor stations from an unused phone system line input or to a dedicated single-line phone
- Add remote observing with a RAD-AMP Remote Access Device
- Built-in talk assist
- Dial-up code can be programmed to match the phone system's station or extension numbers
- Cassette recorder output with automatic or touch-tone control
- Automatic gain control equalizes in- and outbound conversation levels
- Call-progress tones for observing supervisor

Anixter No. Vendor No.

Description

274197 S0-24A

Service observation unit



Telephone Accessories

Remote Touch-tone Controller

VIKING ELECTRONICS



The RC-2A Remote Controller provides remote relay operation from any standard touch-tone telephone. The controller is designed to be installed either locally or remotely. For local installations the RC-2A can be installed in series on any analog communications path, such as analog C.O. lines, analog PABX/KSU stations or Viking's W-Series Doorboxes and will passively monitor for touch-tone commands. For off-premise applications, the RC-2A will answer analog C.O. lines or PABX/KSU stations after a selectable ring delay. A field programmable access code can also be programmed to prevent unauthorized usage. The RC-2A will then allow remote relay operation.

FEATURES

- · Programmable access code
- Normally open or normally closed relay
- Selectable relay closure times
- Selectable ring delay (1, 2, 6 or 15)
- Easy installation with modular jacks and screw terminals

Anixter No. Vendor No.

Description

122270

RC-2A

Remote touch-tone controller

Push to Call Speakerphone

VIKING ELECTRONICS





The E-10A and E-20B can be connected directly to a C.O. line or analog PABX/KSU station when used in conjunction with a hot-line dialer or programmed ring down circuit. When the "Call" button is pressed, the E-10A or E-20B will come off-hook and will remain off-hook until a CPC is detected or the pre-selected timeout has elapsed, the unit will then automatically disconnect. For outdoor or harsh environments, the E-10A and E-20B are available with Enhanced Weather Protection (EWP).

FFATURES

- Phone line-powered
- Weather resistant
- Optional Enhanced Weather Protection (EWP)
- Adjustable microphone and speaker volume
- Intelligent call progress detection for automatic hang-up on CPC, silence, busy signal or time out
- Selectable auto-answer feature allows remote monitoring
- VOX (mic/speaker) switching speed selection

Anixter No.	Vendor No.	Description
122128	E-10A	Flush mount, aluminum, black
254829	E-20B	Surface mount, plastic, light gray
320928	E-10A-EWP	Flush mount, aluminum, black with Enhanced Weather Protection
320929	E-20B-EWP	Surface mount, plastic, light gray with Enhanced Weather Protection



Telephone Accessories

VE-Series Backboxes

VIKING ELECTRONICS



The VE-3x5, VE-5x5, VE-6x7 and VE-5x10 add vandal and weather resistance, as well as versatility to many Viking products. The VE-Series backboxes are available in black powder painted steel or stainless steel. The weather-resistant boxes are designed to be surface-mounted to a wall, post, single-gang box or a VE-GNP gooseneck pedestal. Note: The VE-3x5 is not compatible with the VE-GNP pedestals and is not available in stainless steel.

The VE-3x5 is designed to be used with the E-40 or E-50 Series entry phones. The VE-5x5 is designed to be used with the E-10, E-30, E-35, E-60, E-65, E-70 and E-75 series hands-free phones, the E-1600-20A and E-1600-30A emergency phones, as well as the W-1000, W-3000, and W-3005 hands-free doorboxes.

The VE-6x7 is designed to be used with the K-1700-3 and K-1705-3 hands-free phone and the VE-5x10 is designed to be used with the K-1500-7, K-1900-7 and the K-1900-8 vandal-resistant phones. The VE-Series backboxes are also compatible with EWP versions of these products. The VE-GNP gooseneck pedestals are designed to be used with the VE-5x5, VE-6x7 and VE-5x10 backboxes and are ideal for drive-up communications. The VE-PNL's are VE-Series backboxes with a blank aluminum panel. The user can customize the clear-coated aluminum panel to mount an HID-1 card reader, keypad or switch. The kits come complete with box, gasket, panel and screws. Model numbers that end with "SS" are stainless steel versions.

- The VE-Series surface-mount boxes are designed to surface mount the following products:
- VE-3x5 E-40 series and E-50 series
- VE-5x5 E-10A, E-30, E-35, E-60, E-65, E-70, E-75, E-1600-20A, E-1600-30A, W-1000, W-3000 and W-3005
- VE-5x10 K-1500-7, K-1900-7 and K-1900-8
- VE-6x7 K-1700-3 and K-1705-3

Anixter No.	Vendor No.	Description
260191	VE-5X5	Surface-mount box for E-10A, E-30, E-35,
		E-60, E-65, E-70, E-75, E-1600-20A,
		E-1600-30A, W-1000, W-3000 and W-3005
320931	VE-5X10	Surface-mount box for K-1500-7,
		K-1900-7 and K-1900-8
260190	VE-6X7	Surface-mount box for the
		K-700-3 and K-1705-3
320933	VE-GNP	Gooseneck pedestal, black
320934	VE-GNP-2	Dual gooseneck pedestal
320935	VE-5X5-PNL	The VE-5x5-PNL is a VE-5x5 with a blank
		clear-coated aluminum panel
339088	VE-6X7-PNL	The VE-6x7-PNL is a VE-6x7 with a blank
		clear-coated aluminum panel

Anixter No.	Vendor No.	Description
339089	VE-5X10-PNL	The VE-5x10-PNL is a VE-5x10 with a blank clear coated aluminum panel
366785	VE-3X5	Stainless steel surface-mount box for E-40 series and E-50
366786	VE-5X5-SS	Stainless steel surface-mount box for E-10A, E-30, E-35, E-60, E-65, E-70, E-75, E-1600-20A, E-1600-30A, W-1000 W-3000 and W-3005
366787	VE-6X7-SS	Stainless steel surface-mount box for the K-700-3 and K-1705-3
366788	VE-5X10-SS	Stainless steel surface-mount box for K-1500-7, K-1900-7 and K-1900-8
366792	VE-GNP-IG	Gooseneck pedestal, in-ground/ wet cement-mount
366793	VE-GNP-SS	Gooseneck pedestal, stainless steel



At any given time, Anixter carries over \$6.1 billion in product inventory in our global distribution network. Chances are, we have the product you need in stock today. Just give us a call at 1.800.ANIXTER and let us know what you need! We can ship it today!



Anixter was built on the principle that "you can't sell from an empty wagon." We believe maintaining a broad and deep inventory is key to our ability to serve you better. On occasion, Anixter has held up to \$5 million in dedicated inventory for a strategic customer. We dedicated 35 percent of our 192,000 square-foot warehouse in Memphis, TN, for a project for one of the nation's largest retailers.

We also inventoried \$5 million of Anixter-owned and non-Anixter-owned inventory for a large financial institution in our 100,000 square-foot warehouse in Anaheim, CA.

Holding that level of inventory in our warehouses is nothing to us at Anixter! In our Electrical and

Electronic Wire & Cable division alone, we will stock and sell approximately 1.5 billion feet of electrical and electronic cable this year. That's about 285,000 miles of cable! When it comes to stocked product, you've come to the right place at Anixter.

Anixter can for you too.

