



# STABILITY FITOCLIMA 600 & 1200 STABILITY

STABILITY STORAGE  
AND PHOTOSTABILITY TESTING CHAMBERS



ICH, GMP, WHO, FDA COMPLIANT





**ARALAB** is a company specialized in designing, developing, manufacturing and servicing of high quality climatic chambers and controlled environment rooms.

Since 1985 we have been perfecting ways to create and control temperature, humidity, light, air flow and many other environmental conditions.

Only the highest quality components are used to manufacture our chambers so customers can have the best equipment for their research and testing purposes.

**Control the environment, your own climate.**



**FitoClima Stability and Photostability Testing chambers provide the environmental control and flexibility to meet the evolving needs of customers throughout the years.**

**COMMON APPLICATIONS INCLUDE:**

- PHARMACEUTICALS
- COSMETICS
- FOOD AND BEVERAGES
- VETERINARY
- STORAGE AND CONSERVATION
- QUALITY CONTROL AND RESEARCH



Certified ISO:9001 for its Quality Management System















**KEY FEATURES**













- Ready to use. No assembly needed
- Minimal footprint, for efficient use of laboratory space
- Future proof design. The interior can be reconfigured at any time for the most efficient use of the available storage space and content dimensions
- Content protection, with configurable high / low temperature and humidity alarms and automatic email notifications
- Remote diagnostics, allowing a fast and accurate technical support
- FDA 21 CFR part 11 compliant software
- Compliant and recognized by ICH, FDA, GMP and other leading industry standards

## TECHNICAL SPECIFICATIONS

### ● ● ● ● TECHNICAL DATA FOR FITOCLIMA 600 & 1200 STABILITY CHAMBERS

TEMPERATURE RANGE <sup>[1]</sup>		-5°C to 60°C
TEMPERATURE PRECISION		± 0,5°C
TEMPERATURE UNIFORMITY		± 1,0°C
HUMIDITY RANGE <sup>[1]</sup>		35 to 90% rH
HUMIDITY PRECISION		± 1% RH
HUMIDITY UNIFORMITY		± 2% RH
SHELVES (STANDARD CONFIGURATION) <sup>[2]</sup>		FitoClima 600: 4 stainless steel wire shelves FitoClima 1.200: 8 stainless steel wire shelves
STANDARD WIRE SHELF SIZE		630m x 510m
STORAGE <sup>[2]</sup>		0.33 m <sup>2</sup> and 18 Kg weight load (per shelf)
STORAGE (STANDARD CONFIGURATION) <sup>[2]</sup>		FitoClima 600: 1,33 m <sup>2</sup> FitoClima 1.200: 2,67 m <sup>2</sup>
AIRFLOW		0.2 m/s uniform across the shelves
INTERNAL VOLUMES		600 or 1.200 liters


### ● ● ● ● FITOCLIMA MODELS REFERENCE - STANDARD CONTROLLED ENVIRONMENT VARIABLES

FITOCLIMA 600/1200 P		Temperature only
FITOCLIMA 600/1200 PH	 	Temperature and Humidity
FITOCLIMA 600 PLH	   	Temperature, Humidity, UV and Visible lights
FITOCLIMA 600 PLH-R	    	Temperature, Humidity, UV and Visible lights. Radiometer and light sensors are integrated with the chamber for an automatic control of the irradiation exposure of test specimens

[1] Temperature and Humidity uniformity performances in Stability Testing chambers. The Photostability testing model temperature range with lights on is 5°C to 45°C and will present greater variations in temperature and humidity uniformity due to heat dissipation from lamps



[2] Additional shelves can be fitted (600 model - up to 10 shelves; 1200 model - up to 20 shelves). Reinforced perforated shelves with 40Kg weight load also available  
Performances measured in factory with room temperature between 20°C and 25°C.


### ● ● ● ● TEMPERATURE & HUMIDITY WORKING RANGE







## DIMENSIONS AND DRAWINGS

### ● ● ● ● FITOCLIMA 600

EXTERNAL DIMENSIONS (HxWxD) (mm)		1.980 x 745 x 950
INTERNAL DIMENSIONS (HxWxD) (mm)		1.330 x 600 x 680






- Standard refrigeration system is air cooled
- Services hub installation needs:
  -  ½" demineralized water supply  
Conductivity: <math><40\mu\text{S}/\text{cm}</math>  
Pressure: 1-5 Bar
  -  50mm water drain at floor level

-  Electrical cabinet installation needs:  
Supply power: 230VAC, 50Hz, 16A / Single Phase + Neutral + Ground  
Electrical protection: Circuit breaker 16A + N with 300mA differential
  -  RJ45 communication port

## DIMENSIONS AND DRAWINGS

### ● ● ● ● FITOCLIMA 1.200

EXTERNAL DIMENSIONS (HxWxD) (mm)		1.980 x 1.450 x 810
INTERNAL DIMENSIONS (HxWxD) (mm)		1.330 x 1.320 x 680



- Standard refrigeration system is air cooled
- Services hub installation needs:
    - ½" demineralized water supply
    - Conductivity: <math><40\mu\text{S}/\text{cm}</math>
    - Pressure: 1-5 Bar
    - 50mm water drain at floor level

- Electrical cabinet installation needs:
    - Supply power: 230VAC, 50Hz, 16A / Single Phase + Neutral + Ground
    - Electrical protection: Circuit breaker 16A + N with 300mA differential
    - RJ45 communication port

## EQUIPMENT DESCRIPTION



### CONSTRUCTION

- New generation multi-color 7 inch touch-screen ClimaPlus© controller
- Open door alarm with configurable time-out function
- Free slots for connecting and integrating external devices with the ClimaPlus controller
- Highly resistant stainless-steel interior
- Photostability chamber with shelves in reflective white coating for better light uniformity and distribution
- Polyurethane insulation
- Exterior zinc plated steel and gray epoxy paint
- Pivoting door(s) with spring lock, magnetic gasket and safety lock(s)
- 4 or 5 casters with built in brakes for effortless mobility and control
- 80mm diameter side port
- Accessible technical compartment for faster maintenance procedures




### CLIMATIC CONTROL

- Air-cooled, CFC free, mechanical refrigeration by hermetic compressor
- Dual heating technology with hot gas by-pass and stainless steel electric heaters
- Humidification by ultrasonic generator with automatic water level control and self-cleaning function
- Also available with steam generator
- Dehumidification by condensation on the cooling system evaporator
- PT100 RTD temperature sensor and capacitive humidity sensor



### AIR FLOW

- Dynamic airflow with EC (variable) blower
- Air renovation through adjustable lateral port-holes
- Uniform air velocity of 0.2 meters per second across shelves
- Airflow speed adjustable on the ClimaPlus© controller





### CONTENT PROTECTION AND AUTOMATIC DIAGNOSTICS

- Independent thermostats for maximum and minimum temperature limits
- Automatic cut-off function, in case of excessive heating or cooling
- Configurable maximum and minimum temperature and humidity limits
- Visual and audible alarms for temperature and humidity limits
- New synoptic diagram function: a self-diagnostics tool that checks all active components of the system allowing for faster procedures and minimizing any possible downtimes


## CLIMAPLUS CONTROLLER

- Programmable Logic Controller exclusively developed by Aralab for FitoClima chambers
- Easy to use touch-screen interface
- 190mm x 150mm multicolor display
- Controls every environmental variable available for any specific FitoClima model (Temperature, Humidity, Lights, Airflow, CO<sub>2</sub>, and connected external devices)
- Friendly program editor for creating 32 programs of 24 segments each, allowing the design of complex and comprehensive climatic simulation programs
- Password protection of the controller functions
- Content and research protection feature, with configurable High and Low Temperature and Humidity alarms and automatic notifications
- Managing, monitoring and recording of all alarms
- Non-volatile memory, allowing the automatic restart of previously defined set-points or on-going programs due to power failure, without losing data
- Real-time monitoring of all the functions and active components of the equipment, allowing for a fast and accurate diagnostic in case of malfunction
- Possibility to control and program events by external commands and with external devices
- Graphical view of programs and climatic variables
- Ethernet and Wi-Fi for connecting computers to the controller
- ClimaPlus controller functions also available at the PC/Laptop with the FitoLog software pack




## FITOLOG SOFTWARE

The FitoLog software pack (FDA 21 CFR part 11 compliant) is a set of applications designed to facilitate the programming, monitoring, managing and recording of programs and data from the FitoClima chambers. It consists of 3 applications: **FitoLog**, **FitoLogView** and **FitoProgram**.




### FITOLOG

Displays and records in real time all data and details related to the set-points, running variables and equipment behaviour. It also retrieves information about the active components of the chamber, running processes, errors, alarms and allows the configuration of periodic or alarm triggered remote notifications (by email or SMS, depending on existing connections and accessories).



### FITOLOGVIEW

It is a working tool to process the data recorded by the FitoLog program. One can view, print and export the log contents to other file types, and analyse the data in other data management software (Excel, Star Office, Access or others).



### FITOPROGRAM

This application simplifies the creation of programs and its integration on the chamber ClimaPlus controller. Up to 32 programs, each with 24 segments, can be designed and linked to create detailed environmental profiles and simulations.

## CONTENT SECURED WITH ALARMS, NOTIFICATIONS, FAST DIAGNOSTICS AND PROMPT TROUBLESHOOTING

With FitoLog it is possible to gather data from each of the chambers systems, which makes it a very useful tool to diagnose any necessary maintenance. This tool works as the "black box" of the equipment, giving Aralab technicians the necessary data to remotely carry out a fast and efficient diagnostic. All that is needed is a FitoLog file.



## COMMON ACCESSORIES

### PLEASE CONSULT ARALAB FOR OTHER ITEMS

FitoLog® software pack for PC/Laptops, enabling data monitoring, logging and managing operations directly on a computer – FDA 21 CFR part 11 compliant

IQ, OQ, PQ procedures and documentation

ISO 17025 Temperature and Humidity calibrations

Additional stainless steel wire shelves

Additional lateral entry port

Reinforced stainless steel shelves for heavier test specimens

20 liter water tank with electric pump and security valve

Conductivity meter, for water quality control

5 stage Reverse Osmosis with pre-decalcification system

Wireless connections

Double glazed glass doors



ISQ

IFQC

Continuação do Relatório

RELATÓRIO DE BREVÊS

1. OBJETIVO: Verificar a conformidade dos resultados obtidos com os requisitos especificados no plano de testes.

2. ABRANGÊNCIA: Verificar a conformidade dos resultados obtidos com os requisitos especificados no plano de testes.

3. METODOLOGIA: Verificar a conformidade dos resultados obtidos com os requisitos especificados no plano de testes.

Característica	Medida	Limite Inferior	Limite Superior	Resultado	Observações
Temperatura	22,0	20,0	24,0	22,0	OK (20-24)
Umidade	65,0	60,0	70,0	65,0	OK (60-70)
Temperatura	22,0	20,0	24,0	22,0	OK (20-24)
Umidade	65,0	60,0	70,0	65,0	OK (60-70)
Temperatura	22,0	20,0	24,0	22,0	OK (20-24)
Umidade	65,0	60,0	70,0	65,0	OK (60-70)

4. RESULTADOS: Os resultados obtidos estão em conformidade com os requisitos especificados no plano de testes.

5. CONCLUSÃO: O sistema de controle de ambiente está operando corretamente e os resultados obtidos estão em conformidade com os requisitos especificados no plano de testes.

6. OBSERVAÇÕES: Não há observações.

7. DATA: 10/10/2023

8. LOCAL: Laboratório de Testes de Estabilidade

9. TÉCNICO: [Assinatura]

10. ENGENHEIRO: [Assinatura]

Features and specifications are subject to change. Aralab continuously studies ways to further develop its products to achieve better performances and overall product quality. As a result, characteristics and specifications provided in this document may be subject to changes.

Let's meet!  
aralab@aralab.pt  
www.aralab.pt  
T: +351 219 154 960



**Control the environment**  
Your own climate