

BASIC 2 Selection of luminaires and accessories

Rettungszeichenleuchten

Safety luminaires

Rettungszeichenleuchten		Rettungszeichenleuchten				Safety luminaires	
BASIC 2 E-LED RZ1 9071 xx 010x 9071 09 0110 (115mA)	BASIC 2 E-LED Ice RZ1¹ 9071 0x 0300 9071 09 0310 (115mA)	BASIC 2 E-LED RZ2 9071 xx 020 9071 09 0210 (115mA)	BASIC 2 E-LED Ice RZ2¹ 9071 0x 0400 9071 09 0410 (115mA)	BASIC 2 E-SIGN RZ 9071 xx 070 9071 09 0710 (115mA)	BASIC 2 E-SIGN RZ plus 9071 xx 080x 9071 09 0810 (115mA)	BASIC 2 E-LED SL 9071 xx 010 9071 09 0110 (115mA)	BASIC 2 E-LED SL Ice¹ 9071 0x 0300 9071 09 0310 (115mA)
Wall mounting parallel	Wall mounting parallel	Ceiling mounting/wall mounting 90°	Ceiling mounting/wall mounting 90°	Ceiling mounting/wall mounting parallel/wall mounting 90°	Ceiling mounting/wall mounting parallel	Ceiling mounting/wall mounting parallel	Ceiling mounting/wall mounting parallel
9071 00 0001 E-LED RZ1 RD rain roof	9071 00 0001 E-LED RZ1 RD rain roof	9071 00 0002 E-LED RZ2 RD rain roof	9071 00 0002 E-LED RZ2 RD rain roof	9071 00 0005 E-SIGN pictogram PX ³	9071 00 0005 E-SIGN pictogram PX ³	9071 00 0001 E-LED RZ1 RD rain roof	9071 00 0001 E-LED RZ1 RD rain roof
9071 00 0007 E-LED RZ1 inlay pictogram PX ³	9071 00 0007 E-LED RZ1 inlay pictogram PX ³	9071 00 0006 E-LED RZ2 inlay pictogram PX ³	9071 00 0006 E-LED RZ2 inlay pictogram PX ³	9071 00 0018 E-SIGN pictogram ISO 7010	9071 00 0018 E-SIGN pictogram ISO 7010	9071 00 0003 E-LED panel PL/PR/PU/BL EK 24m	9071 00 0003 E-LED panel PL/PR/PU/BL EK 24m
9071 00 0020 E-LED RZ1 inlay pictogram ISO 7010	9071 00 0020 E-LED RZ1 inlay pictogram ISO 7010	9071 00 0019 E-LED RZ2 inlay pictogram ISO 7010	9071 00 0019 E-LED RZ2 inlay pictogram ISO 7010	9071 00 0010 E-SIGN PE 0,5m suspension set	9071 00 0010 E-SIGN PE 0,5m suspension set	9071 00 0004 E-LED panel PX EK 24m	9071 00 0004 E-LED panel PX EK 24m
9071 00 0013 E-LED IP65 set ¹		9071 00 0010 E-LED PE 0,5m suspension set	9071 00 0012 E-LED BE mounting kit ²	9071 00 0011 E-SIGN PE 1,0m suspension set	9071 00 0011 E-SIGN PE 1,0m suspension set	9071 00 0023 E-LED Scheibe ISO 7010 EK 24m	9071 00 0023 E-LED Scheibe ISO 7010 EK 24m
		9071 00 0011 E-LED PE 1,0m suspension set		9071 00 0012 E-SIGN BE mounting kit ²	9071 00 0012 E-SIGN BE mounting kit ²	9071 00 0010 E-LED PE 0,5m suspension set	9071 00 0012 E-LED BE mounting kit ²
		9071 00 0012 E-LED BE mounting kit ²				9071 00 0011 E-LED PE 1,0m suspension set	
		9071 00 0013 E-LED IP65 set ¹				9071 00 0012 E-LED BE mounting kit ²	
						9071 00 0013 E-LED IP65 Set ¹	
9071 00 0008 E-LED DE recessed ceiling mounting box		9071 00 0008 E-LED DE recessed ceiling mounting box		9071 00 0014 E-SIGN DE recessed mounting box	9071 00 0014 E-SIGN DE recessed mounting box	9071 00 0008 E-LED DE recessed ceiling mounting box	
9071 00 0009 E-LED DE E-Line mounting adapter		9071 00 0009 E-LED DE E-Line mounting adapter		9071 00 0015 E-SIGN concrete mounting kit	9071 00 0015 E-SIGN concrete mounting kit	9071 00 0009 E-LED DE E-Line mounting adapter	

THE ARTICLE NUMBERS

Explained using the example BASIC2 RZ1/SL.

- 9071 xx 010x — Nominal operating time
 - 0 = scCMR 1-8 h / or for centrally supplied luminaire
 - 1 = scAT 1 h
 - 2 = scAT 2 h
 - 3 = scAT 3 h
 - 4 = scAT 8 h
- 9071 0x 0300 — Type of monitoring
 - 3 = ILS
 - 5 = Imax350
 - 9 = PLC24

¹ The use of accessories changes the protection class. The IP65 mounting set is included in the scope of delivery of the Ice variants.
² Chains or ropes are not included in the set. ³ Pictogram set parametrizable. A standard pictogram set is included in the scope of delivery of the luminaire.

NOTE: All dimensions in the dimensional drawings are given in mm. The illustrations are partly shown proportionally reduced or enlarged

RAL FARBEN Note: Various components are available in custom colors and in all RAL colors on request.

Protection against weather influences