


Product Lineup

See the Possibilities.

Matrox Graphics offers the most extensive line of reliable multi-display solutions on the market today.





Matrox Multi-Display Graphics Cards

A pioneer in multi-monitor graphics technology, Matrox offers the most extensive line of multi-display graphics solutions — dual, quad and beyond — on the market today. We work hard to deliver the optimal combination of fanless design, low power consumption, best-of-breed 2D image quality, high MTBF and long product life cycles. Our solutions offer flexible multi-display configurations — from stretched to independent, in pivot and clone mode for widescreen and custom monitors — to give you more workspace to see and do more.

Product	Part Number	Max. # of Displays				Card Type	Graphics Memory	Form Factor Card/Bracket	On-Board Connectors	Maximum Resolutions (Per Display)			List Price USD	Optional Adapter/Cable Upgrade(s) ² (sold separately)	
		DisplayPort	DVI	Analog	Total					DisplayPort	DVI	Analog		Cable Description	Cable Part Number
C-Series – Quad and six-output board offering the best combination of performance, power consumption, and display density.															
C420 LP PCIe x16	C420-E2GBLAF	4	4	—	4	PCIe x16	2GB GDDR5	LP / ATX & LP	4 x miniDP	2560x1600 ¹⁴	2560x1600 (dual-link) ¹⁵ 1920x1200 (single-link) ¹⁵	—	\$570	Mini DisplayPort to DisplayPort adapter	CAB-MDP-DPF
C680 PCIe x16	C680-E2GBF	6	6	—	6	PCIe x16	2GB GDDR5	ATX / ATX	6 x miniDP	4096x2160 ¹⁴	2560x1600 (dual-link) ¹⁵ 1920x1200 (single-link) ¹⁵	—	\$695	Mini DisplayPort to DisplayPort adapter Board-to-board framelock cable	CAB-MDP-DPF CAB-FL-F
M-Series - Low power consumption. Fanless cooling¹⁰. Dual and Quad multi-monitor support. Exceptional performance and image quality.															
M9120 PCIe x16	M9120-E512F	—	2	2	2	PCIe x16	512MB DDR2	ATX / ATX	DVI-I x 2	—	1920x1200	2048x1536	\$259	—	—
M9120 Plus LP PCIe x1	M9120-E512LAU1F	—	2	4 ⁴	4 ⁸	PCIe x1	512MB DDR2	LP / ATX & LP	LFH-60	—	1920x1200	2048x1536 (x2) or 1920x1200 (x3, x4) ³	\$329	LFH-60 to 4xHD15 Analog	CAB-L60-4XAF
M9120 Plus LP PCIe x16	M9120-E512LPUF	—	2	4 ⁴	4 ⁸	PCIe x16	512MB DDR2	LP / LP & ATX	LFH-60	—	1920x1200	2048x1536 (x2) or 1920x1200 (x3, x4) ³	\$329	LFH-60 to 4xHD15 Analog	CAB-L60-4XAF
M9125 PCIe x16	M9125-E512F	—	2	2	2	PCIe x16	512MB DDR2	ATX / ATX	DVI-I x 2	—	1920x1200 and 2560x1600	2048x1536	\$399	—	—
M9128 LP PCIe x16	M9128-E1024LAF	2	2 ⁸	—	2	PCIe x16	1GB DDR2	LP / ATX & LP	DP x2	2560x1600	1920x1200	—	\$259	DP to DVI-D (DVI Single-Link)	CAB-DP-DVIF
M9138 LP PCIe x16	M9138-E1024LAF	3	3 ⁸	—	3	PCIe x16	1GB DDR2	LP / ATX & LP	3 x miniDP	2560x1600	1920x1200	—	\$395	DP to DVI-D (DVI Single-Link)	CAB-DP-DVIF
M9140 LP PCIe x16	M9140-E512LAF	—	4	4	4	PCIe x16	512MB DDR2	LP / ATX & LP	KX20	—	1920x1200	1920x1200	\$599	—	—
M9148 LP PCIe x16	M9148-E1024LAF	4	4	—	4	PCIe x16	1GB DDR2	LP / ATX & LP	4 x miniDP	2560x1600	1920x1200	—	\$629	—	—
M9188 PCIe x16	M9188-E2048F	8	8	—	8	PCIe x16	2 GB DDR2	ATX / ATX	8 x miniDP	2560x1600	1920x1200	—	\$1995	—	—
P-Series - Ultra-low power consumption. Fanless cooling. Dual and quad multi-monitor support. Easy to deploy.															
P690 LP PCIe x1	P69-MDDE128LA1F	—	2	2	2	PCIe x1	128MB	LP / ATX & LP	LFH-60	—	1920x1200	2048x1536	\$249	LFH-60 to 2xDVI-D (6ft)	CAB-L60-2XD6F
P690 LP PCIe x16	P69-MDDE128LPF	—	2	2	2	PCIe x16	128MB	LP / LP & ATX	LFH-60	—	1920x1200	2048x1536	\$249	LFH-60 to 2xDVI-D (6ft)	CAB-L60-2XD6F
P690 PCI	P69-MDDP128F	—	2	2	2	PCI	128MB	ATX / ATX	DVI-I x 2	—	1920x1200	2048x1536	\$199	—	—
P690 PCIe x16	P69-MDDE128F	—	2	2	2	PCIe x16	128MB	ATX / ATX	DVI-I x 2	—	1920x1200	2048x1536	\$199	—	—
P690 Plus LP PCI	P69-MDDP256LAUF	—	2	4 ⁴	4	PCI	256MB	LP / ATX & LP	LFH-60	—	1920x1200	2048x1536 (x2), 1920x1200 (x3, x4) ¹⁻³	\$289	LFH-60 to 4xHD15 Analog & LFH-60 to 2xDVI-D (6ft)	CAB-L60-4XAF & CAB-L60-2XD6F
P690 Plus LP PCIe x16	P69-MDDE256LAUF	—	2	4 ⁴	4	PCIe x16	256MB	LP / ATX & LP	LFH-60	—	1920x1200	2048x1536 (x2), 1920x1200 (x3, x4) ¹⁻³	\$289	LFH-60 to 4xHD15 Analog & LFH-60 to 2xDVI-D (6ft)	CAB-L60-4XAF & CAB-L60-2XD6F
G-Series - Cost-effective and highly flexible DualHead graphics cards.															
G550 LP PCI	G55MDDAP32DSF	—	2 ⁸	2	2	PCI, 32-bit, 66 MHz	32MB	LP / ATX & LP	LFH-60	—	1280x1024 ^{1,5}	2048x1536 (main), 1600x1200 (secondary)	\$149	HD15 to 1xSDTV (TV-OUT) & LFH-60 to 2xDVI-I (1ft) & LFH-60 to 2xDVI-D (6ft)	CAB-HD15-TVF & CAB-L60-2XD6F & CAB-L60-2XD6F
G550 LP PCIe	G55-MDDE32LPDF	—	2	2	2	PCIe x1	32MB	LP / LP & ATX	LFH-60	—	1280x1024 ¹	2048x1536 (main), 1600x1200 (secondary)	\$169	HD15 to 1xSDTV (TV-OUT) & LFH-60 to 2xDVI-D (6ft)	CAB-HD15-TVF & CAB-L60-2XD6F
G550 PCIe	G55-MDDE32F	—	2	2	2	PCIe x1	32MB	ATX / ATX	DVI-I x 2	—	1280x1024 ¹	2048x1536 (main), 1600x1200 (secondary)	\$139	HD15 to 1xSDTV (TV-OUT)	CAB-HD15-TVF



Graphics expansion Modules

Add external multi-monitor support to laptops, desktops and workstations. Customers benefit from multi-display computing — without the need to open PC chassis.

Product	Part Number	Max. # of Displays				How it Connects		Maximum Resolutions (Per Display) ⁶			Hardware Included	Dimensions (WxDxH)	List Price USD	Optional Adapter/Cable Upgrade(s) ² (sold separately)	
		DisplayPort	Digital	Analog	Total	To System	To Monitors	DisplayPort	DVI	Analog				Cable Description	Cable Part Number
DualHead2Go Digital ME	D2G-DP2D-MIF	—	2	—	2	Mini DisplayPort or Thunderbolt ¹³	DVI	—	2x 1920x1200	—	Mini-DP-to-DP input cable, USB cable	3.8"x 2.5"x1.1"	\$179	—	—
DualHead2Go Digital SE	D2G-DP2D-IF	—	2	—	2	DisplayPort or Mini DisplayPort	DVI	—	2x 1920x1200	—	DP-to-DP input cable, USB cable	3.8"x 2.5"x1.1"	\$179	—	—
DualHead2Go Analog Edition	D2G-A2A-IF	—	—	2	2	VGA	VGA	—	—	2x 1280x1024	2-ft VGA-to-VGA (analog) monitor cable, USB cable	3.8"x 3.6"x0.94"	\$169	—	—
DualHead2Go Digital Edition	D2G-A2D-IF	—	2	2 ⁸	2	VGA	VGA or DVI	—	2x 1920x1200	2x 1680x1050	2-ft VGA-to-VGA (analog) monitor cable, USB cable	3.9" x 5.5" x 1.3"	\$229	DVI to VGA adaptor	ADP-DVI-AF
TripleHead2Go Digital SE	T2G-DP3D-IF	—	3	—	3	DisplayPort or Mini DisplayPort or Thunderbolt ¹³	DVI	—	3x 1920x1080 ^{9,11} 3x 1680x1050 ⁹ 2x 1920x1200	—	DP-to-DP input cable, Mini-DP-to-DP input cable, USB cable	5.25"x2.5"x1.1"	\$279	—	—
TripleHead2Go Digital Edition	T2G-D3D-IF	—	3	3 ⁸	3	VGA or Dual-link DVI	VGA or DVI	—	3x 1920x1080 ^{7,11} 3x 1680x1050 ⁹ 2x 1920x1200	3x 1360x768 2x 1680x1050	2-ft VGA-to-VGA monitor cable, 2-ft DVI-to-DVI monitor cable, USB cable	4.4"x5.5"x1.1"	\$329	DVI to VGA adaptor	ADP-DVI-AF
TripleHead2Go DP Edition	T2G-DP-MIF	3	3 ⁸	3 ¹²	3	DisplayPort or Mini DisplayPort or Thunderbolt ¹³	VGA, DVI or DisplayPort	3x 1920x1080 ⁹ 2x 1920x1200	3x 1920x1080 ^{9,11} 3x 1680x1050 ⁹ 2x 1920x1200	3x 1360x768 2x 1920x1080	DP-to-DP input cable, Mini-DP-to-DP input cable, USB cable	3.85"x3.5"x1.1"	\$329	DisplayPort to DVI	CAB-DP-DVIF

¹ The resolution & refresh rate of each display must be the same. ² Cable pricing details available at www.matrox.com/graphics ³ 1920x1200 supported with quad analog upgrade cable ⁴ LFH-60 to 4xHD15 cable upgrade required ⁵ LFH-60 to dual DVI-I cable upgrade required ⁶ Maximum resolution supported is GXM model, system, operating system and display dependent. ⁷ These modes are available when TripleHead2Go Digital Edition is connected to the system's dual-link DVI output, and are not available under any Mac OS X operating system. ⁸ Using optional adapter cable (sold separately). ⁹ Widescreen resolutions higher than 3x1360x768 are not available under any Mac OS X operating system. ¹⁰ M9188 does have a fan for cooling. ¹¹ Resolution supported at 50Hz which may be incompatible with some displays. ¹² Using 3rd party active adapter cable (sold separately). ¹³ Thunderbolt system connectivity is supported only under Mac. ¹⁴ Passive adapters may be required (sold separately). ¹⁵ Third-party active adapters required (sold separately).

Visit www.matrox.com/graphics for all software and hardware upgrade options and complete product line details.

KVM Extenders

Matrox Extio separates standard peripherals — keyboard, video and mouse — from the computer by up to 1 km (3280 ft)¹ with fiber-optic cabling to deliver a user experience with less noise, less heat and more workspace.

Product ²	Part Number	Max. # of Displays	Graphics Memory	Connectors	Maximum Resolutions (Per Display)			Maximum Distance	Interface card required
					DisplayPort	Digital	Analog		
Extio F2208	XTO2-F2208F	2	1GB	2 DisplayPort connectors, 5 USB 2.0 ports, dual-LC fiber-optic connector, audio connectors, power input	2560x1600	1920x1200 ³	1920x1200 ³	400 m (1312 ft) in Multimode 1 km (3280 ft) in Single-mode	PCIe x1 (Part # XTO2A-FESLPAF)
Extio F2408	XTO2-F2408F	4	1GB	4 DisplayPort connectors, 5 USB 2.0 ports, dual-LC fiber-optic connector, audio connectors, power input	2560x1600	1920x1200 ³	1920x1200 ³	400 (1312 ft) in Multimode 1 km (3280 ft) in Single-mode	PCIe x1 (Part # XTO2A-FESLPAF)
Extio F2408E Expander	XTO2EX-F2408F	4	1GB	4 DisplayPort connectors, dual-LC fiber-optic connector, power input	2560x1600	1920x1200 ³	1920x1200 ³	5 m (must use cable provided)	—

¹ Matrox Extio F2208 and F2408 ship with multi-mode fiber optic cable transceivers. Single-mode transceiver kit available separately.

² Fiber optic cables for products are required and sold separately. ³ Two DisplayPort to DVI connector adapters included with Extio F2208. Four DisplayPort to DVI connector adapters included with Extio F2408. DisplayPort to Analog (VGA) adapters available from 3rd party vendors.

Matrox Avio consists of a transmitter and receiver pair, which captures dual digital video, keyboard, mouse, analog stereo audio and USB 2.0 from the host system and extends them uncompressed up to 4 km (2.5 miles) over a single duplex LC-LC fiber optic cable.

Product	Part Number	Video Input Connector	Video Output Connector ¹	Maximum Resolution	USB HID ports	USB 2.0 ports	Keyboard & Mouse		Analog Stereo Audio	Maximum Distance ²
							USB	PS/2		
Avio F120 Transmitter	AV-F120TXF	1x DVI-I SL/DL 1x DVI-I SL	1x DVI-I SL/DL 1x DVI-I SL	2x 1920x1200 1x 2560x1600 1x 4096x2160	2	2	Yes	Yes	Yes	400 m (1312 ft) in Multimode 10 km (6.2 mi) in Single-mode
Avio F120 Receiver	AV-F120RXF	—	1x DVI-I SL/DL 1x DVI-I SL	2x 1920x1200 1x 2560x1600 1x 4096x2160	4	—	Yes	Yes	Yes	400 m (1312 ft) in Multimode 10 km (6.2 mi) in Single-mode
Avio F125 Transmitter	AV-F125TXF	1x DVI-I SL/DL 1x DVI-I SL	1x DVI-I SL/DL 1x DVI-I SL	2x 1920x1200 1x 2560x1600 1x 4096x2160	2	2	Yes	Yes	Yes	400 m (1312 ft) in Multimode 10 km (6.2 mi) in Single-mode
Avio F125 Receiver	AV-F125RXF	—	1x DVI-I SL/DL 1x DVI-I SL	2x 1920x1200 1x 2560x1600 1x 4096x2160	2	4	Yes	Yes	Yes	400 m (1312 ft) in Multimode 10 km (6.2 mi) in Single-mode

¹ In Dual-link DVI mode, only a single display is supported. ² Matrox Avio SFP+ Single-Mode upgrade kit required (Part# AV-SFP10G-2SMF)

AV over IP

Matrox MaeveX features an encoder/decoder pair that delivers Full HD 1080p60 video and audio over standard LAN connectivity at user-defined low bit rates for minimal network bandwidth consumption and at a fraction of the cost of other solutions. The MaeveX Encoder also provides open standard encoding, allowing for both MaeveX Decoder and software based playback. Recording up to 1080p60 to NAS or a network-shared drive is also enabled. All MaeveX hardware comes packaged with Matrox PowerStream software, allowing for easy remote management of MaeveX devices and enabling of a wide variety of user-defined stream-management features. Matrox also offers an even more cost-effective option with the MaeveX Encoder/Decoder Bundle (P/N: MVX-ED5150F) at an MSRP of USD \$1299.

Product	Part Number	Video Input Connector	Video Output Connector	Network Connector	Maximum Resolution (Digital)	Audio Stereo	Video Encoding/Decoding	Recording	Bit Rates	Streaming Protocols	Networking Interface	List Price USD
MaeveX 5150 Encoder	MVX-E5150F	1 x HDMI 1 x DVI ¹	1 x HDMI 1 x DVI ¹	1 x RJ45	1920x1080p60 1920x1200	HDMI & Analog	H.264/MPEG-4 Part 10 (AVC)	Yes	100Kbps to 25Mbps	UDP, RTP/RTSP/RTCP	100/1000 Base-T Ethernet	\$999
MaeveX 5150 Decoder	MVX-D5150F	—	1 x HDMI 1 x DVI ²	2 x RJ45	1920x1080p60 1920x1200	HDMI & Analog	H.264/MPEG-4 Part 10 (AVC)	No	100Kbps to 25Mbps	UDP, RTP/RTSP/RTCP	100/1000 Base-T Ethernet	\$549

¹ Via an included adapter. ² Via a separately sold adapter.

Display Wall Controller Boards

Build small or large collaborative video walls for control rooms, corporate boardrooms, and digital signage applications using multi-functional add-in boards that facilitate capture and display of both analog and digital video sources at full HD Truecolor image quality.

Product	Part Number	Board Type	Interface	Memory	Transfer rate	Output Resolutions ¹		Input Resolutions ¹ (Per Display)				
						SL-DVI	RGB (VGA)	SL-DVI ²	RGB (VGA) ²	Component (VPbPr)	S-Video Composite	SDI
Mura MPX-4/0	MURA-MPX40HF	4 outputs 0 inputs	PCI Express x16 (Gen2)	2GB ³	64 Gbit/sec	2048x1152 @ 60Hz	2048x1536 @ 60Hz	—	—	—	—	—
Mura MPX-4/2	MURA-MPX42HF	4 outputs 2 inputs	PCI Express x16 (Gen2)	2GB ³	64 Gbit/sec	2048x1152 @ 60Hz	2048x1536 @ 60Hz	1920x1200 @ 60Hz 2560x1600 @ 30Hz	1920x1200 @ 60Hz 2048x1536 @ 47Hz	1080i	NTSC/PAL SECAM	—
Mura MPX-4/4	MURA-MPX44HF	4 outputs 4 inputs	PCI Express x16 (Gen2)	2GB ³	64 Gbit/sec	2048x1152 @ 60Hz	2048x1536 @ 60Hz	1920x1200 @ 60Hz 2560x1600 @ 30Hz	1920x1200 @ 60Hz 2048x1536 @ 47Hz	1080i	NTSC/PAL SECAM	—
Mura MPX-SDI	MURA-MPXSDIF	2 outputs 2 inputs	PCI Express x16 (Gen1)	1GB ³	32 Gbit/sec	2048x1152 @ 60Hz	2048x1536 @ 60Hz	—	—	—	—	1920x1080 @ 60Hz
Mura MPX-V8	MURA-MPXV8F	0 outputs 8 inputs	PCI Express x4 (Gen1)	128MB ⁴	8 Gbit/sec	—	—	—	—	—	NTSC/PAL SECAM	—
Mura MPX-V16	MURA-MPXV16F	0 outputs 16 inputs	PCI Express x4 (Gen1)	256MB ⁴	8 Gbit/sec	—	—	—	—	—	NTSC/PAL SECAM	—

¹ Maximum resolutions listed. Support for standard and custom resolutions available. For specific requirements contact Matrox.

² RGB (VGA) adapter included with Mura MPX 4/0, Mura MPX 4/2, and Mura MPX 4/4. Matrox adapters sold separately for component, s-video, and composite. Contact Matrox for details.

³ Shared memory for inputs and outputs. ⁴ Input memory.

Learn More or Purchase

North America Corporate Headquarters: 1 800-361-1408 or 514-822-6000
International: 514-822-6366

Email: graphics@matrox.com

© 2014 Matrox Graphics, Inc. All rights reserved. Matrox reserves the right to change specifications without notice. Matrox and Matrox product names are registered trademarks in Canada or other countries and/or trademarks of Matrox Electronic Systems, Ltd and/or Matrox Graphics Inc. All other company and product names are registered trademarks and/or trademarks of their respective owners. \$GE-5429-B September 2014

matrox[®]
Graphics for Professionals