



6Gb/s SATA Enterprise 2.5" SSDs

CloudSpeed™ Product Family of SATA SSDs

Cost-effective storage for a variety of read-intensive and mixed use application workloads.

CloudSpeed Eco™ and CloudSpeed Ascend™/Read-Intensive Application Workloads

- Web Servers
- Web 2.0 Content Repository
- Photo Sharing
- Media Streaming
- Video on Demand (VOD)
- Cloud Computing
Virtual Tape Libraries (VTL)
- Web-based Applications
- File Servers

CloudSpeed Ultra™/Mixed-Use Application Workloads

- On-Line Transaction Processing (OLTP)
Databases
- Financial Transactions
- E-Commerce
- SQL Logging
- Collaboration
- E-Mail/Messaging

The next generation of CloudSpeed™ SATA SSDs are designed with a range of endurance and optimized for read-intensive and mixed-use application workloads in enterprise and cloud computing environments. Leveraging SanDisk's proprietary Guardian Technology™ Platform, tier-one OEM-enterprise firmware, proven power fail technology and the latest generation of 19nm cMLC (Eco model only) and eMLC NAND flash, CloudSpeed SSDs offer all the features expected from an enterprise-class drive at the right value.

Available in capacities of 100GB-960GB*, the CloudSpeed SSD product family features a 6Gb/s SATA interface and provides data transfer rates up to 475/450 MB/s** sequential read/write and performance up to 75K/30K IOPS random read/write. CloudSpeed SSDs offer high data integrity by employing a combination of powerful error correction and detection, full data path protection, thermal monitoring, and data fail recovery. These enterprise features enable CloudSpeed SSDs to deliver up to 5x higher endurance than competing client MLC SSDs.

Guardian Technology™ Platform

The product family of CloudSpeed SATA SSDs is powered by SanDisk's proprietary Guardian Technology Platform, a suite of enterprise features that include FlashGuard™, DataGuard™ and EverGuard™ technologies.

FlashGuard Technology combines Aggregated Flash Management, which treats all flash elements as a single system, and Advanced Signal Processing, which dynamically adjusts flash parameters throughout the life of the SSD, to reliably extract significantly more life from cost-effective MLC flash, making it suitable for read-intensive and mixed-use application workloads.

DataGuard Technology features full data path protection, safeguarding user data from corruption along all data paths in the SSD.

EverGuard Technology protects against loss of user data in the event of unexpected power interruptions using a 3rd generation backup power circuit design and high-reliability discrete capacitors.

CloudSpeed™ Product Family of 2.5" SATA SSDs

	CloudSpeed Eco™	CloudSpeed Ascend™	CloudSpeed Ultra™
Performance			
Interface	6Gb/s SATA		
Sequential Read/Write (MB/s)**	Up to 475/450 MB/s ¹	Up to 470/450 MB/s ¹	Up to 450/400 MB/s ¹
Random Read/Write (IOPS)	Up to 80K/14K ²	Up to 70K/14K ²	Up to 75K/30K ²
Access Time	< 2.0 ms		
Capacity	cMLC	eMLC	eMLC
19nm MLC User Capacities*	240GB, 480GB, 960GB	120GB, 240GB, 480GB, 960GB	100GB, 200GB, 400GB, 800GB
Reliability			
Data Reliability (BER)	1 unrecoverable error in 10 ¹⁷ bits read ³		
MTBF***	2 Million Hours	2.5 Million Hours	
Data Fail Recovery	Recover up to 1 NAND flash erase block of data		
Power Fail Recovery	High-reliability backup-power circuitry		
Temperature Monitoring	Performance throttling upon warning/critical temperature		
Warranty	The lesser of 3 years or maximum endurance used****		The lesser of 5 years or maximum endurance used*****
Endurance			
19nm MLC User Capacities*	1 DWPD ⁵ /****	1 DWPD ⁵ /*****	3 DWPD ⁵ /*****
Power			
Vcc	5V ± 5%		
Active (Typ)	5.2W		
Idle	2.2W		
Environmental			
Shock (operating)	1000g @ 1.0 msec, 1 shock along each axis, X, Y, Z, in each direction		
Vibration (operating)	2.17 g rms 7-800 Hz		
Operating Temperature	0° C to 70° C (internal)		
Storage Temperature	-40° C to 95° C		
Humidity	5% to 95%, non-condensing, relative humidity ⁴		
Altitude	-200 feet to 10,000 feet		
Mechanical			
Length	100.2 mm		
Width	69.85 mm		
Height	7 mm		

(1) Based on a 128KB transfer rate, using Oakgate SVF exerciser
 (2) Based on 4KB transfer rate using Oakgate SVG exerciser
 (3) The JEDEC 64.8 specification requires 1 in 10¹⁷ for enterprise-class SSDs
 (4) Based on MIL-STD 810-F, Method 507.4
 (5) Endurance @ JeDEC 219 Workload

CloudSpeed Eco - Ordering Information

Capacity & Part Number

(240GB) - SDFNDAR-240G-1Hxx

(480GB) - SDFNDAR-480G-1Hxx

(960GB) - SDFNCAR-960G-1Hxx

xx - Pack Out Option for CloudSpeed Eco:

Generic/Sample: A2 10 Pack: 02 Bulk Pack: 03

CloudSpeed Ascend - Ordering Information

(120GB) - SDFFOEAR-120G-1Hxx

(240GB) - SDFFODAR-240G-1Hxx

(480GB) - SDFFODAR-480G-1Hxx

(960GB) - SDFFOCAR-960G-1Hxx

CloudSpeed Ultra - Ordering Information

(100GB) - SDFFOEAM-100G-1Hxx

(200GB) - SDFFODAM-200G-1Hxx

(400GB) - SDFFODAM-400G-1Hxx

(800GB) - SDFFOCAM-800G-1Hxx

xx - Pack Out Option for CloudSpeed Ascend and CloudSpeed Ultra:

Generic/Sample: A1 10 Pack: 02 Bulk Pack: 03

Specifications subject to change without notice.
 *1 GB = 1,000,000,000 bytes. Actual user capacity less.
 **Up to stated speed. Based on internal testing; performance may vary depending upon drive capacity, host device, OS and application. 1 megabyte (MB) = 1 million bytes.
 ***MTBF - Mean Time Between Failures based on parts stress analysis.

****Warranty/DWPD - The lesser of 3 years from the date of manufacture of the product or the date on which the product's relevant endurance thresholds set forth in the product specifications are reached.
 *****Warranty/DWPD - The lesser of 5 years from the date of manufacture of the product or the date on which the product's relevant endurance thresholds set forth in the product specifications are reached.

© 2016 Western Digital Corporation. All rights reserved. SanDisk, the SanDisk logo, CloudSpeed, CloudSpeed Eco, CloudSpeed Ascend, CloudSpeed Ultra, Guardian Technology, FlashGuard, DataGuard and EverGuard are trademarks of Western Digital Corporation or its affiliates, registered in the U.S. and other countries. Other brand names mentioned herein are for identification purposes only and may be the trademarks of their holder(s). CloudSpeed Family SSD Datasheet CSR-10.13.14 r102816

Contact information

ESS.channelsales@sandisk.com
 ESS.OEMsales@sandisk.com
 businesspartners@sandisk.com

SanDisk Americas

951 SanDisk Drive
 Milpitas, CA 95035-7933, USA
 T: 1-866-744-2165

SanDisk Europe, Middle East, Africa

Unit 100, Airside Business Park,
 Swords, County Dublin, Ireland
 T: 1-866-744-2165

SanDisk Asia Pacific

Suite C,D,E, 23/F, No. 918 Middle
 Huahai Rd., Jiu Shi Renaissance Building,
 Shanghai, 20031, P.R. China
 T: 1-866-744-2165

For more information, please visit:

www.sandisk.com/enterprise

SanDisk®
 a Western Digital brand

At SanDisk, we're expanding the possibilities of data storage. For more than 25 years, SanDisk's ideas have helped transform the industry, delivering next generation storage solutions for consumers and businesses around the globe.

951 SanDisk Drive | Milpitas | CA 95035 | USA