





4-Port PS/2 Rack Mount KVM Switch Kit with Audio TK-403KR (B1.2R)

TRENDnet's 4-Port PS/2 Rack Mount KVM Switch Kit with Audio allows you to manage up to four computers/servers with just one keyboard (with PS/2 cable), monitor, mouse(with PS/2 cable), and pair of speakers. This kit comes with four sets of 1.8 meter (6 foot) cables needed to connect computers.

Switch between PCs with a simple press of a button. With its rack mount kit and slim 1U height, it is perfect for mounting on a 19" server rack. The TK-403KR also features, Auto-Scan, Audible Feedback, and Hot-Key support.

PRODUCT OVERVIEW

- · 4-port KVM switch with VGA and PS/2 connection to computers
- · Device monitoring with Auto-Scan and audible feedback
- High quality 2048 x 1536 resolution for a crisp display
- · All required cabling included
- · Rack mount kit

FEATURES

- · Controls up to four computers/servers with one set of console device
- VGA monitor port
- · PS/2 keyboard and mouse ports
- · 3.5 mm audio and microphone ports
- · Four sets of 1.8 m (6 foot) detachable KVM cables with VGA, PS/2, and audio connectors
- PS/2 keyboard / mouse emulation
- Supports up to 2048 x 1536 resolution
- · Mouse reset hotkey supports for non-PnP operating system
- · Auto-scan mode for monitoring computers and beeping sound for switching confirmation
- · Standard 19" (1U) rack mount kit
- Sturdy metal housing
- · Plug & Play and Hot-Pluggable
- · 2-year limited warranty

TK-403KR rev: 11.20.2012



SPECIFICATIONS

HARDWARE		
Connections	Up to 4 computers/servers	
Cable	4 sets of 1.8 m (6 ft.) PS/2 audio combination KVM cables	
Cable Interface (all male)	 To KVM 1 x PS/2 Keyboard 6-pin mini-Din 1 x PS/2 Mouse 6-pin mini-Din 1 x VGA HDB 15-pin To Computer 1 x PS/2 Keyboard 6-pin mini-Din 1 x PS/2 Mouse 6-pin mini-Din 1 x PS/2 Mouse 6-pin mini-Din 1 x VGA HDB 15-pin 1 x 3.5 mm speaker jack 1 x 3.5 mm microphone jack 	
PC Ports (all female)	 4 x PS/2 Keyboard 6-pin mini-Din 4 x PS/2 Mouse 6-pin mini-Din 4 x VGA HDB 15-pin 	
Console Ports (all female)	sole Ports (all female) • 1 x PS/2 Keyboard 6-pin mini-Din • 1 x PS/2 Mouse 6-pin mini-Din • 1 x VGA HDB 15-pin • 1 x 3.5 mm speaker jack • 1 x 3.5 mm microphone jack	
Computer Selection	Front panel push buttons or keyboard hotkey commands	
Auto Scan Intervals	5~100 seconds (default 5 seconds)	
Keyboard / Mouse Emulation	• PS/2	
Power	 Bus-Powered Input: 100~240 V AC Output: 9 V DC, 500 mA optional external power adapter 	
Dimensions	• 255 x 120 x 45 mm (10 x 4.7 x 1.8 in.)	
Weight	• 0.93 kg (2.04 lbs.)	
Temperature	 Operating: 0°C ~ 40°C (32°F ~104°F) Storage: -20°C ~ 60°C (-4°F ~ 140°F) 	
Humidity	Max 90% (non-condensing)	
Certifications	• CE, FCC	



NETWORKING SOLUTIONS

4-Port PS/2 Rack Mount KVM Switch Kit w/ Audio TK-403KR



PACKAGE CONTENTS

TK-	403KR
Qui	ick Installation Guide
4 x PS/2 audio combination KVM cable (1.8 m / 6 ft.)	
Rad	ck Mount Kit

RELATED PRODUCTS

TK-208K	2-Port PS/2 KVM Switch Kit w/ Audio
TK-408K	4-Port PS/2 KVM Switch Kit with Audio
TK-423K	4-Port USB / PS/2 KVM Switch Kit w/ Audio

CONTACT INFORMATION

TRENDNET

20675 Manhattan Place,Torrance, CA 90501 USA Tel: 1-310-961-5500 Fax: 1-310-961-5511 Web: www.trendnet.com Email: sales@trendnet.com **1-888-326-6061**

