

Terminal blocks for explosive atmosphere






- When connecting conductors of more than 16 mm², do not use the PR3 rail as it cannot carry the nominal currents.






- In order to preserve the rated voltages, a separator end section must be used, at each change of block spacing, and at each extremity of a jumper bar. When using a shield connector, please consult us.




- The terminal blocks can be used with a maximum voltage of 10% above the voltage classification according to EN 50019.


- These terminal blocks meet Standard EN 50019.



<p>MA 2,5/5.SNB Spacing 5 mm .200"</p>  <p>Grey body MA 2,5/5.SNB 0115 504.15</p>	<p>M 4/6.SNB Spacing 6 mm .238"</p>  <p>Grey body M 4/6.SNB 0115 686.13 Orange body M 4/6.SNB 0105 053.22 Beige V0 body M 4/6.SNB V0 0195 686.14</p>	<p>M 6/8.SNB Spacing 8 mm .315"</p>  <p>Grey body M 6/8.SNB 0115 688.25 Orange body M 6/8.SNB 0105 055.24 Beige V0 body M 6/8.SNB V0 0195 688.26</p>	<p>M 4/6.SN... Spacing 6 mm .238"</p>  <p>Grey body M 4/6.SN 0115 214.11 Orange body M 4/6.SN2 0105 022.13 Beige V0 body M 4/6.SN3 0115 404.11</p>	<p>M 4/6.SNBT.4A Spacing 6 mm .238"</p>  <p>Grey body M 4/6.SNBT.4A 0115 480.11 Beige V0 body M 4/6.SNBT.4A V0 0195 480.12</p>
------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

<p>M 4/6.D2.2S2... Spacing 6 mm .238"</p>  <p>Grey body M 4/6.D2.2S2 0199 444.25 With 4 test socket-screws M 4/6.D2.2S2.T 0199 448.01 M 4/6.D2.2S2.T23 0199 447.20</p>	<p>M 4/6.D2.S1R... Spacing 6 mm .238"</p>  <p>Grey body M 4/6.D2.S1R 0199 452.25 With 4 test socket-screws M 4/6.D2.S1R.T 0199 456.21 M 4/6.D2.S1R.T23 0199 455.20</p>	<p>M 4/8.SN Spacing 8 mm .315"</p>  <p>Grey body M 4/8.SN 0115 659.07 Beige V0 body M 4/8.SN V0 0195 659.00</p>	<p>MTC 6 Spacing 6 mm .238"</p>  <p>Grey body MTC 6 0115 206.22</p>	<p>71LTVV Spacing 7 mm .276"</p>  <p>Grey body 71LTVV 0112 262.26 Beige V0 body 71LTVV V0 0192 262.27</p>
---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

<p>M 6/8.RS Spacing 8 mm .315"</p>  <p>Grey body M 6/8.RS 0115 685.12 Beige V0 body M 6/8.RS V0 0195 685.13</p>	<p>M 10/10.RS Spacing 10 mm .394"</p>  <p>Grey body M 10/10.RS 0115 320.27 Beige V0 body M 10/10.RS V0 0195 320.20</p>	<p>M 6/8.STP.RS Spacing 8 mm .315"</p>  <p>Grey body M 6/8.STP.RS 0115 678.02 Beige V0 body M 6/8.STP.RS V0 0195 678.03</p>		
-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--	--



All spring connection terminal blocks are  certified

