

AMBIT ENGINEERING, INC. CIVIL ENGINEERS AND LAND SURVEYORS

200 Griffin Road, Unit 3, Portsmouth, NH 03801
Phone (603) 430-9282 Fax 436-2315

20 October 2022

Peter Stith, Technical Advisory Committee Chair
City of Portsmouth
1 Junkins Avenue
Portsmouth, NH 03801

**RE: Request for Site Plan Approval at 161 Deer Street to be known as 88 Maplewood Avenue,
Mixed Use Site Development**

Dear Mr. Stith and TAC Members:

On behalf of Tom Balon and EightKPH, LLC we are pleased to submit the attached plan set for **Site Plan Review** for the above-mentioned project and request that we be placed on the agenda for your **November 1, 2022** Technical Advisory Committee Meeting. The project consists of the replacement of the existing one story commercial building at 161 Deer Street with a new 4 story with a Penthouse building with the associated and required site improvements. The new building is intended to be known as 88 Maplewood Avenue. The re-development will include parking below street level.

The site redevelopment consists of replacing the existing structure with a new structure. The site is known as DSA Lot 5; part of the Consolidation and Subdivision Approved by the Planning Board in 2016. The property was a part of the overall planning for development on the 5 lots and had a proposed building designed; however that building did not go through and complete the permit process entirely. This application revises the proposed building and as such is in HDC review. The property is located in the CD – 5, Downtown Overlay, North End Incentive, and Historic Districts. The design package has been revised to address concerns expressed at our first TAC Hearing on September 6, 2022.

The following plans are included in our submission:

- Cover Sheet – This shows the Development Team, Legend, Site Location, and Site Zoning.
- Subdivision Plan – This plan show the plan which created the current property boundaries.
- Existing Conditions Plan C1 – This plan shows the existing site conditions in detail.
- Demolition Plan C2 – This plan shows demolition of the existing building and associated site features.
- Site Plan C3 – This plan shows the site development in detail with the associated Zoning Development Standards and Floor Area calculations. Also shown are impervious surface calculations and the areas dedicated to Community Space. The plan proposes to dedicate 20% (Minimum) Community Space to gain building height.
- Architectural Renderings Floor Plans, and Building Elevations.

- Landscape Plans – Site landscape features and specifications.
- Parking Level Plan C4 – This plan shows the lower level parking layout.
- Utility Plan C5 – This plan shows proposed site utilities.
- Grading Plan C6 – This plan shows proposed site grading.
- Detail Sheets D1 to D5 – These plans show site details.

Additional Information Provided:

Preliminary Code Review
ADA Parking Analysis
Complete Drainage Analysis
Vehicle Turning Movements

We look forward to the Technical Advisory Committee review of this submission and look forward to an in-person presentation.

Sincerely,

John Chagnon

John R. Chagnon, PE
CC: Tom Balon, Carla Goodknight, Terrance Parker



PRELIMINARY CODE STUDY

APPLICABLE CODES

- Basic code and fire rating information per 2015 IBC and 2015 NFPA 101 (with New Hampshire modifications).
- Per New Hampshire law, the more restrictive of NFPA 101 and IBC Means of Egress is to be used.
- Accessibility regulations compliance with IBC Chapter 11 and ANSI NH RSA 155-A:5.

GENERAL PROJECT DESCRIPTION

This project consists of the construction of a new mixed-use building in Portsmouth, New Hampshire.

The building will be four stories in height with a fifth story penthouse and a basement below. The basement will be used for parking and mechanical space, the first floor will be commercial space, and the second, third, fourth, and fifth floors will be residential dwelling units.

The building will be protected throughout by an NFPA-13 automatic sprinkler system.

BUILDING DATA

Zoning District:	CD5 - Character District 5
Overlay Districts:	Downtown Overlay District, North End Incentive Overlay District, Historic District
Occupancies:	R2 Residential S2 Storage (parking garage) M Mercantile (assumed worst case at first floor commercial)
Building height:	62 feet
Number of stories above grade:	Five (note 1)
Number of Residential units:	19 (six per floor at 2nd, 3rd, and 4th plus 1 at penthouse)
Footprint area:	17,800 SF
Construction Type:	Type II-B (noncombustible, unprotected) (note 4)
Sprinkler system:	NFPA-13 automatic sprinkler system
Standby power (note 5):	Required by IBC for elevator as means of egress (5 stories) Required by City of Portsmouth for garage ventilation



HEIGHT AND AREA LIMITATIONS

Construction type:	Type II-B	IBC section 602
Height limitation:	R2: 75 feet (S sprinkler) S2: 75 feet (S sprinkler) M: 75 feet (S sprinkler)	IBC table 504.3
Story limitation	R2: 5 stories (S sprinkler) S2: 4 stories (S sprinkler) M: 3 stories (S sprinkler)	IBC table 504.4
Area limitation:	R2: 48,000 SF (SM sprinkler) S2: 78,000 SF (SM sprinkler) M: 37,500 SF (SM sprinkler)	IBC table 506.2
Street frontage increase:	Not required for compliance	IBC table 506.3

FIRE RATINGS

IBC Type II-B Construction

Note: Some structural members in otherwise unrated assemblies may require fire protection when supporting fire rated assemblies above. Requirements are subject to local building officials.

<u>Basic building elements</u>	<u>Fire rating</u>	<u>Code reference</u>
Structural frame:	0 hour	IBC table 601
Exterior bearing walls:	0 hour	IBC table 601
Interior bearing walls (not acting as fire separation):	0 hour	IBC table 601
Interior non-bearing walls (not acting as fire separation):	0 hour	IBC table 601
Floor construction:	0 hour	IBC table 601
Roof construction:	0 hour	IBC table 601
<u>Interior fire separations</u>	<u>Fire rating</u>	<u>Code reference</u>
Separation between S2 and M:	2 hours (first floor assembly)	NFPA 88A
Separation between M and R2:	1 hour (second floor assembly)	IBC section 508.4
Stair (vertical enclosure) walls:	2 hour fire barrier (note 2)	IBC table 1023.2
Exit access corridor walls:	1/2 hour fire partition (note 3)	IBC table 1020.1
Elevator hoistway:	2 hour fire barrier	IBC section 713.4
Elevator machine room enclosure:	2 hour fire barrier	IBC section 3005.4
Dwelling unit separations (walls):	1/2 hour fire partition	IBC section 708.3 ex.2
Dwelling unit separations (floor/ceiling):	1/2 hour	IBC section 711.2.4.3 ex

(continued next page)



Interior fire separations	Fire rating	Code reference
Dwelling unit/corridor separations:	1/2 hour	IBC section 708.3 ex.1
Mechanical shafts:	2 hour fire barrier	IBC section 713.4
Electric room enclosure (>112-1/2 kVA):	1 hour fire barrier (if applicable)	NEC 450.21(B)
Trash collection rooms:	1 hour fire barrier	NFPA 101 30.3.2.1.1
Storage rooms outside of dwellings:	0 hours with sprinkler system	NFPA 101 30.3.2.1.1
Common mechanical rooms:	1 hour fire barrier	NFPA 101 8.7.1
<u>Opening protectives</u>		
Exit access (stair enclosure) doors:	1-1/2 hour (90 minute)	IBC table 716.4
Elevator hoistway doors:	1-1/2 hour (90 minute)	IBC table 716.4
Elevator machine room doors:	1-1/2 hour (90 minute)	IBC table 716.4
Dwelling unit entry & corridor doors:	1/3 hour (20 minute)	IBC table 716.4
Electric room doors:	3/4 hour (45 minute)	IBC table 716.4
Trash room doors:	3/4 hour (45 minute)	IBC table 716.4
Common mechanical room doors:	3/4 hour (45 minute)	IBC table 716.4

ACCESSIBILITY

- Sixty percent of public building entrances must be accessible. IBC section 1105.1
- The main accessible entrance must be at or near the main ambulatory entrance.
- All public areas of the building must be accessible including the corridor side of dwelling unit entrances. An accessible route must be provided throughout the building except within multi-level dwelling units and within mechanical areas.
- No Type A accessible dwelling units are required because the site contains less than 20 dwelling units. IBC section 1107.6.2.2.1
- All dwelling units must conform to Fair Housing Act requirements due to new construction with more than four dwelling units and elevator access to all floors. All dwelling units must be at least Type B accessible per IBC. IBC section 1107.6.2.2.2
- At least one parking space shall be accessible in the lower level garage (2% of total 29 spaces = 0.58 spaces required). IBC section 1106.2
- At least one van accessible parking space is required at the lower level garage, since a van space is required for every six accessible parking spaces. The minimum vertical clearance at the van space is 7'-0" (note 6). IBC section 1106.5 ex.
- Each public bathroom shall be accessible. Where multiple single-user bathrooms are clustered at a single location, at least 50 percent but not less than one room at each cluster shall be accessible. IBC section 1109.2



NOTES

- 1) Basement is not a story above grade per IBC definition (floor above is less than 6' above grade plane).
- 2) Walls denoted as fire barriers must be continuous from the top of slab below to the underside of roof deck above.
- 3) Walls denoted as fire partitions must be continuous from the top of slab or deck below to the fire rated membrane above.
- 4) Combustible materials are permitted in construction Type II-B under specific conditions as listed in IBC Section 603.1. Item 1 of this section permits fire-retardant-treated wood to be used in nonbearing partitions where the required fire rating is 2 hours or less. This means that the exterior wall system of the building must be constructed using either GWB sheathing (such as Densglass) or FRT plywood sheathing. A separate building wrap product (such as Blueskin) or a fluid applied barrier system may then be installed over this sheathing for a complete exterior assembly. Because it is not fabricated using FRT wood, combined sheathing products such as ZIP sheathing cannot be used in Type II-B construction.
- 5) Owner has proposed using a battery system for standby power (such as Tesla Powerwall). This will require AHJ approval as a standby power source.
- 6) IBC Section 1106.5 allows an exception for van accessible parking spaces in private garages serving R2 residential occupancies, allowing the vertical clearance to be reduced to 7'-0" minimum, where the 2010 ADA Standards require 8'-2" clear height at van accessible spaces with no exceptions listed. Since this project is not subject to the requirements of the ADA Standards, and the lower level garage is a private garage serving the R2 residential occupancy, the clear height at the van space may be 7'-0" minimum.

END OF DOCUMENT

**TABLE 1106.1
ACCESSIBLE PARKING SPACES**

TOTAL PARKING SPACES PROVIDED IN PARKING FACILITIES	REQUIRED MINIMUM NUMBER OF ACCESSIBLE SPACES
1 to 25	1
26 to 50	2
51 to 75	3
76 to 100	4
101 to 150	5
151 to 200	6
201 to 300	7
301 to 400	8
401 to 500	9
501 to 1,000	2% of total
1,001 and over	20, plus one for each 100, or fraction thereof, over 1,000

❖ The required number of accessible parking spaces is based on the accessible parking requirements of the 2010 ADA Standard. It does not reflect the demographic statistics on wheelchair usage that were used to scope other requirements in Chapter 11, because the majority of disabled parking permit and license plate holders in most states are ambulatory, mobility-impaired persons. The required ratios are intended to be responsive to the anticipated demand for all facilities, such that accessible parking spaces will be reasonably available on demand. Section 1111.1 states that signage is not required on the one required accessible parking space when the total number of parking spaces provided is four or less. This could be burdensome for the building tenant in that the accessible parking space, which is restricted for use only by authorized vehicles, could constitute anywhere from 25 to 100 percent of the available parking. This may unduly restrict the availability of parking for all other vehicles and patrons of the facility. While not reserved by signage, the space must still be sized in accordance with a van-accessible space.

1106.2 Groups I-1, R-1, R-2, R-3 and R-4. Accessible parking spaces shall be provided in Group I-1, R-1, R-2, R-3 and R-4 occupancies in accordance with Items 1 through 4 as applicable.

- In Group R-2, R-3 and R-4 occupancies that are required to have *Accessible, Type A or Type B dwelling units or sleeping units*, at least 2 percent, but not less than one, of each type of parking space provided shall be accessible.
- In Group I-1 and R-1 occupancies, accessible parking shall be provided in accordance with Table 1106.1.
- Where at least one parking space is provided for each dwelling unit or sleeping unit, at least one accessible parking space shall be provided for each Accessible and Type A unit.

4. Where parking is provided within or beneath a building, accessible parking spaces shall be provided within or beneath the building.

❖ This section provides a separate criterion for the required number of accessible parking spaces for occupancies in Groups I-1, R-1, R-2, R-3 and R-4 that include Accessible, Type A or Type B units.

The 2-percent requirement in Item 1 for R-2, R-3 and R-4 is based on HUD's FHAG. Section 1107.7 identifies buildings where Type A and Type B units may not be required. For example, a townhouse development may not have any Type A or Type B dwelling units required, therefore, no accessible parking spaces are required. Designers should keep in mind that asking for accessible parking spaces is a common accommodation asked for by residents in both townhouse and apartment developments. While not required, it would be good design practice to exceed code and at least have space on the parking lot to add accessible parking when requested.

Per Item 2, assisted living facilities (Group I-1) and hotels and motels (Group R-1) should use Table 1106.1 to determine the number of accessible parking spaces required.

Due to the higher anticipated need, per Item 3, when a residential parking lot provides one or more spaces for each dwelling or sleeping unit, there should be accessible parking spaces for each Accessible or Type A unit in the facility, in addition to the 2 percent required by Items 1 or 2. For example, a 100-unit hotel has 100 parking spaces for the guests. Four Accessible guestrooms are required. Table 1106.1 would require four accessible spaces. Item 3 would require an additional four accessible spaces. Therefore the hotel will have to provide eight accessible parking spaces, two sized for a van.


Per Item 4, where parking is provided within or beneath a building, accessible parking spaces also are to be provided within or beneath the building. If a combination of surface and covered parking is provided, accessible parking may be provided in both locations. This is intended to establish consistency in the type and location of parking spaces available to all people. If parking is provided in individual private parking garages, 2 percent of the parking garages would have to contain accessible parking spaces (see the exception to Section 1106.5).

In a development, typically parking for dwelling units is considered on a site basis rather than a building-by-building basis. Accessible parking should be dispersed throughout the development so as to provide the best access possible. It is not the intent to require accessible parking spaces at the entrance to every building, or within every strip of parking garages. For example, it would not be logical to ask for a surface space and a garage space for each building in developments with multiple four-unit buildings. See Section 1106.5 for a discussion of the distribution of van-accessible spaces.

DRAINAGE ANALYSIS


SITE DEVELOPMENT

88 MAPLEWOOD AVENUE
PORTSMOUTH, NH



PREPARED FOR
EIGHTKPH, LLC.

23 AUGUST 2022
AMENDED: 20 OCTOBER 2022



 **AMBIT ENGINEERING, INC.**
Civil Engineers & Land Surveyors

200 Griffin Road, Unit 3
Portsmouth, NH 03801
Phone: 603.430.9282; Fax: 603.436.2315
E-mail: jrc@ambitengineering.com
(Ambit Job Number 2271.04)

TABLE OF CONTENTS***REPORT***

Executive Summary	1
Introduction / Project Description	2
Methodology	2
Site Specific Information	3
Pre-Development Drainage	4
Post-Development Drainage	5
Offsite Infrastructure Capacity	6
Erosion and Sediment Control Practices	6
Conclusion	7
References	8

ATTACHMENTS

Existing Subcatchment Plan	
Proposed Subcatchment Plan	

APPENDIX

Vicinity (Tax) Map	A
Tables, Charts, Etc.	B
HydroCAD Drainage Analysis Calculations	C
Soil Survey Information	D
FEMA FIRM Map	E
Inspection & Long Term Maintenance Plan	F

EXECUTIVE SUMMARY

This drainage analysis examines the pre-development (existing) and post-development (proposed) stormwater drainage patterns for the proposed building at 88 Maplewood Avenue in Portsmouth, NH. The site is shown on the City of Portsmouth Assessor's Tax Map 125 as Lot 17-3. The project proposes to replace the current building and associated parking lot. The total size of the lot together is 22,667 square-feet (0.520 acres). The size of the total drainage area is 41,807 square-feet (0.960 acres).

The site plans will provide for the future construction of a new building, with associated landscaping, utilities, and underground parking. The new building will be serviced by public water and sewer. The development has the potential to increase stormwater runoff to adjacent properties, and therefore must be designed in a manner to prevent that occurrence. This will be done primarily by capturing stormwater runoff and routing it through appropriate stormwater facilities, designed to ensure that there will be no increase in peak runoff from the site as a result of this project.

The hydrologic modeling utilized for this analysis uses the "Extreme Precipitation" values for rainfall from The Northeast Regional Climate Center (Cornell University), with a 15% increase to comply with local ordinance.

INTRODUCTION / PROJECT DESCRIPTION

This drainage report is designed to assist the owner, planning board, contractor, regulatory reviewer, and others in understanding the impact of the proposed development project on local surface water runoff and quality. The project site is shown on the City of Portsmouth, NH Assessor's Tax Map 125 as Lot 17-3. Bounding the site to north is a railroad and then a cemetery. Bounding the site to east is Maplewood Avenue. Bounding the site to south is Deer Street. Bounding the site to the west is an existing Banking facility with drive-up window. A vicinity map is included in the Appendix to this report. The existing building and associated parking lot will be demolished.

This report includes information about the existing site and the proposed construction necessary to analyze stormwater runoff and to design any required mitigation. The report includes maps of pre-development and post-development watersheds, subcatchment areas and calculations of runoff. The report will provide a narrative of the stormwater runoff and describe numerically and graphically the surface water runoff patterns for this site.

Proposed stormwater management and treatment structures and methods will also be described, as well as erosion and sediment control practices. To fully understand the proposed site development the reader should also review a complete site plan set in addition to this report.

METHODOLOGY

"Extreme Precipitation" values from The Northeast Regional Climate Center (Cornell University) have been used for modeling purposes. These values have been used in this analysis, with a 15% addition to comply with local ordinances.

This report uses the US Soil Conservation Service (SCS) Method for estimating stormwater runoff. The SCS method is published in The National Engineering Handbook (NEH), Section 4 "Hydrology" and includes the Technical Release No. 20, (TR-20) "Computer Program for Project Formulation Hydrology", and Technical Release No. 55 (TR-55) "Urban Hydrology for Small Watersheds" methods. This report uses the HydroCAD version 10.20 program, written by HydroCAD Software Solutions LLC, Chocorua, N.H., to apply these methods for

the calculation of runoff and for pond modeling. Rainfall data and runoff curve numbers are taken from “The Stormwater Management and Erosion Control Handbook for Urban and Developing Areas in New Hampshire.”

Time of Concentration (Tc) is calculated by entering measured flow path data such as flow path type, length, slope and surface characteristics into the HydroCAD program. For the purposes of this report, a minimum time of concentration of 5 minutes is used.

The storm events used for the calculations in this report are the 2-year, 10-year, 25-year, and 50-year (24-hour) storms. Watershed basin boundaries have been delineated using topographic maps prepared by Ambit Engineering and field observations to confirm.

In addition, the City of Portsmouth produced the “Deer Street Outfall Drainage Evaluation,” published October 17, 2018. This report was used to evaluate the future impacts of the proposed drainage network.

SITE SPECIFIC INFORMATION

Based on the United States Department of Agriculture (USDA) Natural Resources Conservation Service (NRCS), Soil Survey of Rockingham County, New Hampshire the site is made up of two soil types:

Soil Symbol	Soil Name and Slopes
699	Urban land
799	Urban land – Canton Complex (3-15% slopes)

Canton complex is well drained with a stated depth to water table and restrictive feature of more than 80 inches. However, due to the primary urban fill component of the soil, as well as the proximity to North Mill Pond, the Hydrologic Soil Group will be assumed to be D.

The physical characteristics of the site consist of flat (0-15%) grades that generally slope from the northeast to the southwest. Elevations on the site range from 12 to 15 feet above sea level. The existing site is developed and includes an existing building located in the center of the lot, with an asphalt parking lot to the north. Vegetation around the developed portion of the lot consists of established grasses and some landscape areas.

According to the Federal Emergency Management Agency (FEMA) Flood Insurance Rate Map (FIRM) number 33015C0259F (effective date January 29, 2021), the project site is located in Zone X and is determined to be outside of the 0.2% annual chance floodplain. A copy of the FIRM map is included in the Appendix.

PRE-DEVELOPMENT DRAINAGE

In the pre-development condition, the site has been analyzed as two watershed basins (E1 and E2) based on localized topography and discharge location. Subcatchment E1 contains the southwesterly part of the lot, as well as part of the western adjacent lot and drains to a catch basin in the southwest. Subcatchment E2 contains a much smaller northeasterly part of the lot and drains to a catch basin to the north. Subcatchments E1 and E2 drain to discharge points DP1 and DP2, respectively. DP1 is located at a catch basin across the street from 'Statey Bar and Grill,' while DP2 is a catch basin near the north corner of the property. The "Deer Street Outfall Drainage Evaluation" raises concerns about the existing pipe to which both discharge points are currently connected. From the report: "Based on the evaluations described above, and in detail in the following report, we have concluded additional drainage capacity is needed now and in the future at the Deer Street Outfall." The report estimates that the pipe nearest the site (from DMH 4980) will flow at capacity during the 10-year storm event, and several of the surrounding pipes in the drainage network will be surcharged. The possibility was raised that part of this flow be diverted through an additional outlet pipe through Maplewood Avenue. However, stormwater design that diverts drainage toward the Maplewood Avenue drainage network is not feasible at this time.

Table 1: Pre-Development Watershed Basin Summary

Watershed Basin ID	Basin Area (SF)	Tc (MIN)	CN	10-Year Runoff (CFS)	50-Year Runoff (CFS)	To Design Point
E1	38,820	5.0	95	7.03	10.80	DP1
E2	2,987	5.0	87	0.48	0.78	DP2

POST-DEVELOPMENT DRAINAGE

The proposed development has been designed to match the pre-development drainage patterns to the greatest extent feasible. In the post-development condition, the site has been analyzed as three subcatchment basins, (P1, P1a and P2). Subcatchments P1 and P1a are related to the area of subcatchment E1. Subcatchment P1a contains the roof of the proposed building, and drains through a roof filter and R-Tank storage system before discharging to an outfall pipe downstream from DP1. Subcatchment P2 is related to the area of subcatchment E2. Subcatchments P1 and P2 drain to Discharge Points DP1 and DP2, respectively. Note that Subcatchment P2 drains toward Maplewood Avenue.

Table 2: Post-Development Watershed Basin Summary

Watershed Basin ID	Basin Area (SF)	Tc (MIN)	CN	10-Year Runoff (CFS)	50-Year Runoff (CFS)	Design Point
P1	19,402	5.0	95	3.51	5.40	DP1
P1a	16,944	5.0	98	3.13	4.76	DP1
P2	5,462	5.0	95	0.99	1.52	DP2

The overall impervious coverage of the subcatchment areas analyzed in this report **increases** from 0.759 acres (79.12%) in the pre-development condition to 0.866 acres (90.19%) in the post-development condition. The project proposes the construction of a R-Tank storage system on site, reducing the peak flow discharge from the site, as well as a downspout filter, providing treatment.

Table 3 shows a summary of the comparison between pre-developed flows and post-developed flows for each design point. The comparison shows the reduced flows as a result of the R-Tank. Note the inclusion of Discharge Point 3 (DP3), representative of the net flows from DP1 and DP2, located at the outfall pipe headed toward North Mill Pond.

Table 3: Pre-Development to Post-Development Comparison

Design Point	Q2 (CFS)		Q10 (CFS)		Q50 (CFS)		Description
	Pre	Post	Pre	Post	Pre	Post	
DP1	4.51	3.97	7.03	6.49	10.80	10.04	Staley Basin
DP2	0.28	0.63	0.48	0.99	0.78	1.52	North Corner
DP3	4.79	4.60	7.51	7.48	11.59	11.56	Combined Flow

Discharge Point 2 experiences a significant increase in peak discharge, however, the city infrastructure to be utilized by both discharge points are connected by the same drainage network, as shown by DP3. The net effect of both discharge points on the drainage network shows peak flows at or below existing levels. Discharge Point 2, if connected to a new drainage network, would lower the peak flow to Discharge Point 3.

The City of Portsmouth classifies any project that disturbs more than 15,000 square feet of area where over 40% of the existing area is already impervious as a redevelopment project. The City requires that such projects treat at least 30% of their existing impervious area and 100% of any additional impervious area using filtration or infiltration practices. This expectation is exceeded with the treatment of the proposed 16,944 sf rooftop.

$(100\%)(4,626 \text{ sf pervious}) + (30\%)(18,041 \text{ sf impervious}) = 10,038 \text{ sf required treatment}$

OFFSITE INFRASTRUCTURE CAPACITY

Retention and routing of the stormwater to the City infrastructure is done on-site through the use of the R-Tank storage system, and has been designed as not to increase the peak flow rate to the local drainage system, therefore no impact to city infrastructure is anticipated.

EROSION AND SEDIMENT CONTROL PRACTICES

The erosion potential for this site as it exists is moderate due to the presence of existing impervious surfaces. During construction, the major potential for erosion is wind and

stormwater runoff. The contractor will be required to inspect and maintain all necessary erosion control measures, as well as installing any additional measures as required. All erosion control practices shall conform to “The Stormwater Management and Erosion Control Handbook for Urban and Developing Areas in New Hampshire.” Some examples of erosion and sediment control measures to be utilized for this project during construction may include:

- Silt Soxx (or approved alternative) located at the toe of disturbed slopes
- Filter baskets in catch basins
- Stabilized construction entrance at access point to the site
- Temporary mulching and seeding for disturbed areas
- Spraying water over disturbed areas to minimize wind erosion

After construction, permanent stabilization will be accomplished by permanent seeding, landscaping, and surfacing the access drives and parking areas with asphalt paving and other areas with impervious walkways.

CONCLUSION



The proposed development has been designed to match the pre-development drainage patterns to the greatest extent feasible. With the design of the R-Tank system, the post-development runoff rates are reduced to below the pre-development runoff rates. The proposed downspout filter will provide treatment to part of the runoff. Erosion and sediment control practices will be implemented for both the temporary condition during construction and for final stabilization after construction. Therefore, there are no negative impacts to downstream receptors or adjacent properties anticipated as a result of this project. Additionally, the diversion of some flow from Deer Street will be advantageous in the event the City pursues an additional outlet pipe to North Mill Pond through Maplewood Avenue.

REFERENCES

1. Comprehensive Environmental Inc. and New Hampshire Department of Environmental Services. *New Hampshire Stormwater Manual (Volumes 1, 2 and 3)*, December 2008 (Revision 1.0).
2. Minnick, E.L. and H.T. Marshall. *Stormwater Management and Erosion and Sediment Control Handbook for Urban and Developing Areas in New Hampshire*, prepared by Rockingham County Conservation District, prepared for New Hampshire Department of Environmental Services, in cooperation with USDA Soil Conservation Service, August 1992.
3. HydroCAD Software Solution, LLC. *HydroCAD Stormwater Modeling System Version 10.20* copyright 2013.
4. CMA Engineers. *Deer Street Outfall Drainage Evaluation*, October 2018.



SITE DEVELOPMENT
88 MAPLEWOOD AVENUE
PORTSMOUTH, N.H.

JOB NUMBER: 2271
SCALE: 1" = 50'
SUBMITTED: 10-20-2022



SITE DEVELOPMENT
88 MAPLEWOOD AVENUE
PORTSMOUTH, N.H.


JOB NUMBER: 2271
SCALE: 1" = 50'
SUBMITTED: 10-20-2022



APPENDIX A
VICINITY (TAX) MAP


SITE DEVELOPMENT
88 MAPLEWOOD AVENUE
PORTSMOUTH, N.H.

JOB NUMBER: 2271
SCALE: 1" = 60'
SUBMITTED: 08-04-2022




APPENDIX B
TABLES, CHARTS, ETC.



APPENDIX C
HYDROCAD DRAINAGE
ANALYSIS CALCULATIONS



DP1




DP2



Subcat



Reach



Pond



Link

Routing Diagram for Existing Conditions David T
Prepared by Ambit Engineering, Printed 2022-10-20
HydroCAD® 10.20-2f s/n 00801 © 2022 HydroCAD Software Solutions LLC

Existing Conditions David T

Prepared by Ambit Engineering

HydroCAD® 10.20-2f s/n 00801 © 2022 HydroCAD Software Solutions LLC

Printed 2022-10-20

Page 2

Project Notes

Defined 5 rainfall events from output (37) IDF

Existing Conditions David T

Prepared by Ambit Engineering

HydroCAD® 10.20-2f s/n 00801 © 2022 HydroCAD Software Solutions LLC

Printed 2022-10-20

Page 3

Rainfall Events Listing (selected events)

Event#	Event Name	Storm Type	Curve	Mode	Duration (hours)	B/B	Depth (inches)	AMC
1	2-yr	Type II 24-hr		Default	24.00	1	3.68	2
2	10-yr	Type II 24-hr		Default	24.00	1	5.59	2
3	25-yr	Type II 24-hr		Default	24.00	1	7.08	2
4	50-yr	Type II 24-hr		Default	24.00	1	8.48	2

Existing Conditions David T

Prepared by Ambit Engineering

HydroCAD® 10.20-2f s/n 00801 © 2022 HydroCAD Software Solutions LLC

Printed 2022-10-20

Page 4

Area Listing (all nodes)

Area (acres)	CN	Description (subcatchment-numbers)
0.146	80	>75% Grass cover, Good, HSG D (E1, E2)
0.285	98	Paved parking, HSG D (E1, E2)
0.167	98	Roofs, HSG D (E1)
0.361	95	Urban commercial, 85% imp, HSG D (E1)
0.960	94	TOTAL AREA

Existing Conditions David T

Prepared by Ambit Engineering

HydroCAD® 10.20-2f s/n 00801 © 2022 HydroCAD Software Solutions LLC

Printed 2022-10-20

Page 5

Soil Listing (all nodes)

Area (acres)	Soil Group	Subcatchment Numbers
0.000	HSG A	
0.000	HSG B	
0.000	HSG C	
0.960	HSG D	E1, E2
0.000	Other	
0.960		TOTAL AREA

Existing Conditions David T

Prepared by Ambit Engineering

HydroCAD® 10.20-2f s/n 00801 © 2022 HydroCAD Software Solutions LLC

Printed 2022-10-20

Page 6

Ground Covers (all nodes)

HSG-A (acres)	HSG-B (acres)	HSG-C (acres)	HSG-D (acres)	Other (acres)	Total (acres)	Ground Cover	Subcatchment Numbers
0.000	0.000	0.000	0.146	0.000	0.146	>75% Grass cover, Good	E1, E2
0.000	0.000	0.000	0.285	0.000	0.285	Paved parking	E1, E2
0.000	0.000	0.000	0.167	0.000	0.167	Roofs	E1
0.000	0.000	0.000	0.361	0.000	0.361	Urban commercial, 85% imp	E1
0.000	0.000	0.000	0.960	0.000	0.960	TOTAL AREA	

Existing Conditions David T

Prepared by Ambit Engineering

HydroCAD® 10.20-2f s/n 00801 © 2022 HydroCAD Software Solutions LLC

Type II 24-hr 2-yr Rainfall=3.68"

Printed 2022-10-20

Page 7

Time span=5.00-20.00 hrs, dt=0.05 hrs, 301 points
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN
Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

Subcatchment E1: DP1

Runoff Area=38,820 sf 82.21% Impervious Runoff Depth>2.92"
Tc=5.0 min CN=95 Runoff=4.51 cfs 0.217 af

Subcatchment E2: DP2

Runoff Area=2,987 sf 38.97% Impervious Runoff Depth>2.18"
Tc=5.0 min CN=87 Runoff=0.28 cfs 0.012 af

Link DP3:

above 1,000.00 cfs Inflow=4.79 cfs 0.229 af
Primary=0.00 cfs 0.000 af Secondary=4.79 cfs 0.229 af

Total Runoff Area = 0.960 ac Runoff Volume = 0.229 af Average Runoff Depth = 2.86"
20.88% Pervious = 0.200 ac 79.12% Impervious = 0.759 ac

Existing Conditions David T

Prepared by Ambit Engineering

HydroCAD® 10.20-2f s/n 00801 © 2022 HydroCAD Software Solutions LLC

Type II 24-hr 2-yr Rainfall=3.68"

Printed 2022-10-20

Page 8

Summary for Subcatchment E1: DP1[49] Hint: $T_c < 2dt$ may require smaller dt

Runoff = 4.51 cfs @ 11.95 hrs, Volume= 0.217 af, Depth> 2.92"
 Routed to Link DP3 :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type II 24-hr 2-yr Rainfall=3.68"

Area (sf)	CN	Description
11,260	98	Paved parking, HSG D
7,281	98	Roofs, HSG D
4,544	80	>75% Grass cover, Good, HSG D
15,735	95	Urban commercial, 85% imp, HSG D
38,820	95	Weighted Average
6,904		17.79% Pervious Area
31,916		82.21% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Summary for Subcatchment E2: DP2[49] Hint: $T_c < 2dt$ may require smaller dt

Runoff = 0.28 cfs @ 11.95 hrs, Volume= 0.012 af, Depth> 2.18"
 Routed to Link DP3 :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type II 24-hr 2-yr Rainfall=3.68"

Area (sf)	CN	Description
1,164	98	Paved parking, HSG D
1,823	80	>75% Grass cover, Good, HSG D
2,987	87	Weighted Average
1,823		61.03% Pervious Area
1,164		38.97% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Summary for Link DP3:

Inflow Area = 0.960 ac, 79.12% Impervious, Inflow Depth > 2.86" for 2-yr event
 Inflow = 4.79 cfs @ 11.95 hrs, Volume= 0.229 af
 Primary = 0.00 cfs @ 5.00 hrs, Volume= 0.000 af, Atten= 100%, Lag= 0.0 min
 Secondary = 4.79 cfs @ 11.95 hrs, Volume= 0.229 af

Existing Conditions David T

Prepared by Ambit Engineering

HydroCAD® 10.20-2f s/n 00801 © 2022 HydroCAD Software Solutions LLC

Type II 24-hr 2-yr Rainfall=3.68"

Printed 2022-10-20

Page 9

Primary outflow = Inflow above 1,000.00 cfs, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

Existing Conditions David T

Prepared by Ambit Engineering

HydroCAD® 10.20-2f s/n 00801 © 2022 HydroCAD Software Solutions LLC

Type II 24-hr 10-yr Rainfall=5.59"

Printed 2022-10-20

Page 10

Time span=5.00-20.00 hrs, dt=0.05 hrs, 301 points
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN
Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

Subcatchment E1: DP1

Runoff Area=38,820 sf 82.21% Impervious Runoff Depth>4.66"
Tc=5.0 min CN=95 Runoff=7.03 cfs 0.346 af

Subcatchment E2: DP2

Runoff Area=2,987 sf 38.97% Impervious Runoff Depth>3.87"
Tc=5.0 min CN=87 Runoff=0.48 cfs 0.022 af

Link DP3:

above 1,000.00 cfs Inflow=7.51 cfs 0.368 af
Primary=0.00 cfs 0.000 af Secondary=7.51 cfs 0.368 af

Total Runoff Area = 0.960 ac Runoff Volume = 0.368 af Average Runoff Depth = 4.60"
20.88% Pervious = 0.200 ac 79.12% Impervious = 0.759 ac

Existing Conditions David T

Prepared by Ambit Engineering

HydroCAD® 10.20-2f s/n 00801 © 2022 HydroCAD Software Solutions LLC

Type II 24-hr 10-yr Rainfall=5.59"

Printed 2022-10-20

Page 11

Summary for Subcatchment E1: DP1

[49] Hint: Tc<2dt may require smaller dt

Runoff = 7.03 cfs @ 11.95 hrs, Volume= 0.346 af, Depth> 4.66"
 Routed to Link DP3 :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type II 24-hr 10-yr Rainfall=5.59"

Area (sf)	CN	Description
11,260	98	Paved parking, HSG D
7,281	98	Roofs, HSG D
4,544	80	>75% Grass cover, Good, HSG D
15,735	95	Urban commercial, 85% imp, HSG D
38,820	95	Weighted Average
6,904		17.79% Pervious Area
31,916		82.21% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Summary for Subcatchment E2: DP2

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.48 cfs @ 11.95 hrs, Volume= 0.022 af, Depth> 3.87"
 Routed to Link DP3 :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type II 24-hr 10-yr Rainfall=5.59"

Area (sf)	CN	Description
1,164	98	Paved parking, HSG D
1,823	80	>75% Grass cover, Good, HSG D
2,987	87	Weighted Average
1,823		61.03% Pervious Area
1,164		38.97% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Summary for Link DP3:

Inflow Area = 0.960 ac, 79.12% Impervious, Inflow Depth > 4.60" for 10-yr event
 Inflow = 7.51 cfs @ 11.95 hrs, Volume= 0.368 af
 Primary = 0.00 cfs @ 5.00 hrs, Volume= 0.000 af, Atten= 100%, Lag= 0.0 min
 Secondary = 7.51 cfs @ 11.95 hrs, Volume= 0.368 af

Existing Conditions David T

Prepared by Ambit Engineering

HydroCAD® 10.20-2f s/n 00801 © 2022 HydroCAD Software Solutions LLC

Type II 24-hr 10-yr Rainfall=5.59"

Printed 2022-10-20

Page 12

Primary outflow = Inflow above 1,000.00 cfs, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

Existing Conditions David T

Prepared by Ambit Engineering

HydroCAD® 10.20-2f s/n 00801 © 2022 HydroCAD Software Solutions LLC

Type II 24-hr 25-yr Rainfall=7.08"

Printed 2022-10-20

Page 13

Time span=5.00-20.00 hrs, dt=0.05 hrs, 301 points
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN
Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

Subcatchment E1: DP1

Runoff Area=38,820 sf 82.21% Impervious Runoff Depth>6.02"
Tc=5.0 min CN=95 Runoff=8.98 cfs 0.447 af

Subcatchment E2: DP2

Runoff Area=2,987 sf 38.97% Impervious Runoff Depth>5.21"
Tc=5.0 min CN=87 Runoff=0.64 cfs 0.030 af

Link DP3:

above 1,000.00 cfs Inflow=9.62 cfs 0.477 af
Primary=0.00 cfs 0.000 af Secondary=9.62 cfs 0.477 af

Total Runoff Area = 0.960 ac Runoff Volume = 0.477 af Average Runoff Depth = 5.96"
20.88% Pervious = 0.200 ac 79.12% Impervious = 0.759 ac

Existing Conditions David T

Prepared by Ambit Engineering

HydroCAD® 10.20-2f s/n 00801 © 2022 HydroCAD Software Solutions LLC

Type II 24-hr 25-yr Rainfall=7.08"

Printed 2022-10-20

Page 14

Summary for Subcatchment E1: DP1

[49] Hint: Tc<2dt may require smaller dt

Runoff = 8.98 cfs @ 11.95 hrs, Volume= 0.447 af, Depth> 6.02"
 Routed to Link DP3 :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type II 24-hr 25-yr Rainfall=7.08"

Area (sf)	CN	Description
11,260	98	Paved parking, HSG D
7,281	98	Roofs, HSG D
4,544	80	>75% Grass cover, Good, HSG D
15,735	95	Urban commercial, 85% imp, HSG D
38,820	95	Weighted Average
6,904		17.79% Pervious Area
31,916		82.21% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Summary for Subcatchment E2: DP2

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.64 cfs @ 11.95 hrs, Volume= 0.030 af, Depth> 5.21"
 Routed to Link DP3 :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type II 24-hr 25-yr Rainfall=7.08"

Area (sf)	CN	Description
1,164	98	Paved parking, HSG D
1,823	80	>75% Grass cover, Good, HSG D
2,987	87	Weighted Average
1,823		61.03% Pervious Area
1,164		38.97% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Summary for Link DP3:

Inflow Area = 0.960 ac, 79.12% Impervious, Inflow Depth > 5.96" for 25-yr event
 Inflow = 9.62 cfs @ 11.95 hrs, Volume= 0.477 af
 Primary = 0.00 cfs @ 5.00 hrs, Volume= 0.000 af, Atten= 100%, Lag= 0.0 min
 Secondary = 9.62 cfs @ 11.95 hrs, Volume= 0.477 af

Existing Conditions David T

Prepared by Ambit Engineering

HydroCAD® 10.20-2f s/n 00801 © 2022 HydroCAD Software Solutions LLC

Type II 24-hr 25-yr Rainfall=7.08"

Printed 2022-10-20

Page 15

Primary outflow = Inflow above 1,000.00 cfs, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

Existing Conditions David T

Prepared by Ambit Engineering

HydroCAD® 10.20-2f s/n 00801 © 2022 HydroCAD Software Solutions LLC

Type II 24-hr 50-yr Rainfall=8.48"

Printed 2022-10-20

Page 16

Time span=5.00-20.00 hrs, dt=0.05 hrs, 301 points
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN
Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

Subcatchment E1: DP1

Runoff Area=38,820 sf 82.21% Impervious Runoff Depth>7.29"
Tc=5.0 min CN=95 Runoff=10.80 cfs 0.541 af

Subcatchment E2: DP2

Runoff Area=2,987 sf 38.97% Impervious Runoff Depth>6.49"
Tc=5.0 min CN=87 Runoff=0.78 cfs 0.037 af

Link DP3:

above 1,000.00 cfs Inflow=11.59 cfs 0.578 af
Primary=0.00 cfs 0.000 af Secondary=11.59 cfs 0.578 af

Total Runoff Area = 0.960 ac Runoff Volume = 0.578 af Average Runoff Depth = 7.23"
20.88% Pervious = 0.200 ac 79.12% Impervious = 0.759 ac

Existing Conditions David T

Prepared by Ambit Engineering

HydroCAD® 10.20-2f s/n 00801 © 2022 HydroCAD Software Solutions LLC

Type II 24-hr 50-yr Rainfall=8.48"

Printed 2022-10-20

Page 17

Summary for Subcatchment E1: DP1[49] Hint: $T_c < 2dt$ may require smaller dt

Runoff = 10.80 cfs @ 11.95 hrs, Volume= 0.541 af, Depth> 7.29"
 Routed to Link DP3 :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type II 24-hr 50-yr Rainfall=8.48"

Area (sf)	CN	Description
11,260	98	Paved parking, HSG D
7,281	98	Roofs, HSG D
4,544	80	>75% Grass cover, Good, HSG D
15,735	95	Urban commercial, 85% imp, HSG D
38,820	95	Weighted Average
6,904		17.79% Pervious Area
31,916		82.21% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Summary for Subcatchment E2: DP2[49] Hint: $T_c < 2dt$ may require smaller dt

Runoff = 0.78 cfs @ 11.95 hrs, Volume= 0.037 af, Depth> 6.49"
 Routed to Link DP3 :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type II 24-hr 50-yr Rainfall=8.48"

Area (sf)	CN	Description
1,164	98	Paved parking, HSG D
1,823	80	>75% Grass cover, Good, HSG D
2,987	87	Weighted Average
1,823		61.03% Pervious Area
1,164		38.97% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Summary for Link DP3:

Inflow Area = 0.960 ac, 79.12% Impervious, Inflow Depth > 7.23" for 50-yr event
 Inflow = 11.59 cfs @ 11.95 hrs, Volume= 0.578 af
 Primary = 0.00 cfs @ 5.00 hrs, Volume= 0.000 af, Atten= 100%, Lag= 0.0 min
 Secondary = 11.59 cfs @ 11.95 hrs, Volume= 0.578 af

Existing Conditions David T

Prepared by Ambit Engineering




HydroCAD® 10.20-2f s/n 00801 © 2022 HydroCAD Software Solutions LLC

Type II 24-hr 50-yr Rainfall=8.48"

Printed 2022-10-20

Page 18

Primary outflow = Inflow above 1,000.00 cfs, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs



Routing Diagram for 2022-10-19 Proposed Conditions David T
 Prepared by Ambit Engineering, Printed 2022-10-19
 HydroCAD® 10.20-2f s/n 00801 © 2022 HydroCAD Software Solutions LLC

Project Notes

Defined 5 rainfall events from output (37) IDF

2022-10-19 Proposed Conditions David T

Prepared by Ambit Engineering

HydroCAD® 10.20-2f s/n 00801 © 2022 HydroCAD Software Solutions LLC

Printed 2022-10-19

Page 3

Rainfall Events Listing (selected events)

Event#	Event Name	Storm Type	Curve	Mode	Duration (hours)	B/B	Depth (inches)	AMC
1	2-yr	Type II 24-hr		Default	24.00	1	3.68	2
2	10-yr	Type II 24-hr		Default	24.00	1	5.59	2
3	25-yr	Type II 24-hr		Default	24.00	1	7.08	2
4	50-yr	Type II 24-hr		Default	24.00	1	8.48	2

2022-10-19 Proposed Conditions David T

Prepared by Ambit Engineering

HydroCAD® 10.20-2f s/n 00801 © 2022 HydroCAD Software Solutions LLC

Printed 2022-10-19

Page 4

Area Listing (all nodes)

Area (acres)	CN	Description (subcatchment-numbers)
0.040	80	>75% Grass cover, Good, HSG D (P1, P2)
0.170	98	Paved parking, HSG D (P1, P2)
0.389	98	Roofs, HSG D (P1a)
0.361	95	Urban commercial, 85% imp, HSG D (P1)
0.960	96	TOTAL AREA

2022-10-19 Proposed Conditions David T

Prepared by Ambit Engineering

HydroCAD® 10.20-2f s/n 00801 © 2022 HydroCAD Software Solutions LLC

Printed 2022-10-19

Page 5

Soil Listing (all nodes)

Area (acres)	Soil Group	Subcatchment Numbers
0.000	HSG A	
0.000	HSG B	
0.000	HSG C	
0.960	HSG D	P1, P1a, P2
0.000	Other	
0.960		TOTAL AREA

2022-10-19 Proposed Conditions David T

Prepared by Ambit Engineering

HydroCAD® 10.20-2f s/n 00801 © 2022 HydroCAD Software Solutions LLC

Printed 2022-10-19

Page 6

Ground Covers (all nodes)

HSG-A (acres)	HSG-B (acres)	HSG-C (acres)	HSG-D (acres)	Other (acres)	Total (acres)	Ground Cover	Subcatchment Numbers
0.000	0.000	0.000	0.040	0.000	0.040	>75% Grass cover, Good	P1, P2
0.000	0.000	0.000	0.170	0.000	0.170	Paved parking	P1, P2
0.000	0.000	0.000	0.389	0.000	0.389	Roofs	P1a
0.000	0.000	0.000	0.361	0.000	0.361	Urban commercial, 85% imp	P1
0.000	0.000	0.000	0.960	0.000	0.960	TOTAL AREA	

2022-10-19 Proposed Conditions David T

Prepared by Ambit Engineering

HydroCAD® 10.20-2f s/n 00801 © 2022 HydroCAD Software Solutions LLC

Printed 2022-10-19

Page 7

Pipe Listing (all nodes)

Line#	Node Number	In-Invert (feet)	Out-Invert (feet)	Length (feet)	Slope (ft/ft)	n	Width (inches)	Diam/Height (inches)	Inside-Fill (inches)
1	1P	7.18	6.93	44.0	0.0057	0.013	0.0	12.0	0.0
2	2P	12.70	11.00	10.0	0.1700	0.013	0.0	12.0	0.0

2022-10-19 Proposed Conditions David T

Type II 24-hr 2-yr Rainfall=3.68"

Prepared by Ambit Engineering

Printed 2022-10-19

HydroCAD® 10.20-2f s/n 00801 © 2022 HydroCAD Software Solutions LLC

Page 8

Time span=5.00-20.00 hrs, dt=0.05 hrs, 301 points
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN
Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

Subcatchment P1: Runoff Area=19,402 sf 83.60% Impervious Runoff Depth>2.92"
Tc=5.0 min CN=95 Runoff=2.25 cfs 0.108 af

Subcatchment P1a: Roof Runoff Area=16,944 sf 100.00% Impervious Runoff Depth>3.18"
Tc=5.0 min CN=98 Runoff=2.05 cfs 0.103 af

Subcatchment P2: DP2 Runoff Area=5,462 sf 83.16% Impervious Runoff Depth>2.92"
Tc=5.0 min CN=95 Runoff=0.63 cfs 0.030 af

Pond 1P: Peak Elev=10.59' Storage=0.010 af Inflow=2.05 cfs 0.103 af
Outflow=1.84 cfs 0.103 af

Pond 2P: (new Pond) Peak Elev=13.22' Inflow=2.05 cfs 0.103 af
12.0" Round Culvert x 2.00 n=0.013 L=10.0' S=0.1700 '/' Outflow=2.05 cfs 0.103 af

Link DP1: above 1,000.00 cfs Inflow=3.97 cfs 0.211 af
Primary=0.00 cfs 0.000 af Secondary=3.97 cfs 0.211 af

Link DP3: above 1,000.00 cfs Inflow=4.60 cfs 0.242 af
Primary=0.00 cfs 0.000 af Secondary=4.60 cfs 0.242 af

Total Runoff Area = 0.960 ac Runoff Volume = 0.242 af Average Runoff Depth = 3.02"
9.81% Pervious = 0.094 ac 90.19% Impervious = 0.866 ac

2022-10-19 Proposed Conditions David T

Type II 24-hr 2-yr Rainfall=3.68"

Prepared by Ambit Engineering

Printed 2022-10-19

HydroCAD® 10.20-2f s/n 00801 © 2022 HydroCAD Software Solutions LLC

Page 9

Summary for Subcatchment P1:

[49] Hint: Tc<2dt may require smaller dt

Runoff = 2.25 cfs @ 11.95 hrs, Volume= 0.108 af, Depth> 2.92"
 Routed to Link DP1 :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type II 24-hr 2-yr Rainfall=3.68"

Area (sf)	CN	Description
821	80	>75% Grass cover, Good, HSG D
2,846	98	Paved parking, HSG D
15,735	95	Urban commercial, 85% imp, HSG D
19,402	95	Weighted Average
3,181		16.40% Pervious Area
16,221		83.60% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Summary for Subcatchment P1a: Roof

[49] Hint: Tc<2dt may require smaller dt

Runoff = 2.05 cfs @ 11.95 hrs, Volume= 0.103 af, Depth> 3.18"
 Routed to Pond 2P : (new Pond)

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type II 24-hr 2-yr Rainfall=3.68"

Area (sf)	CN	Description
9,126	98	Roofs, HSG D
7,818	98	Roofs, HSG D
16,944	98	Weighted Average
16,944		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Summary for Subcatchment P2: DP2

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.63 cfs @ 11.95 hrs, Volume= 0.030 af, Depth> 2.92"
 Routed to Link DP3 :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type II 24-hr 2-yr Rainfall=3.68"

2022-10-19 Proposed Conditions David T

Type II 24-hr 2-yr Rainfall=3.68"

Prepared by Ambit Engineering

Printed 2022-10-19

HydroCAD® 10.20-2f s/n 00801 © 2022 HydroCAD Software Solutions LLC

Page 10

Area (sf)	CN	Description
920	80	>75% Grass cover, Good, HSG D
4,542	98	Paved parking, HSG D
5,462	95	Weighted Average
920		16.84% Pervious Area
4,542		83.16% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Summary for Pond 1P:

[82] Warning: Early inflow requires earlier time span

[44] Hint: Outlet device #3 is below defined storage

Inflow Area = 0.389 ac, 100.00% Impervious, Inflow Depth > 3.18" for 2-yr event
 Inflow = 2.05 cfs @ 11.95 hrs, Volume= 0.103 af
 Outflow = 1.84 cfs @ 11.99 hrs, Volume= 0.103 af, Atten= 10%, Lag= 2.4 min
 Primary = 1.84 cfs @ 11.99 hrs, Volume= 0.103 af
 Routed to Link DP1 :

Routing by Stor-Ind method, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Peak Elev= 10.59' @ 11.99 hrs Surf.Area= 0.006 ac Storage= 0.010 af

Plug-Flow detention time= 2.9 min calculated for 0.103 af (100% of inflow)
 Center-of-Mass det. time= 2.6 min (733.9 - 731.3)

Volume	Invert	Avail.Storage	Storage Description
#1A	7.86'	0.006 af	9.25'W x 27.46'L x 4.07'H Field A 0.024 af Overall - 0.008 af Embedded = 0.016 af x 40.0% Voids
#2A	8.11'	0.008 af	ACF R-Tank LD 2 x 40 Inside #1 Inside= 15.7"W x 33.9"H => 3.52 sf x 2.35'L = 8.3 cf Outside= 15.7"W x 33.9"H => 3.70 sf x 2.35'L = 8.7 cf 40 Chambers in 4 Rows
		0.014 af	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	7.18'	12.0" Round Culvert L= 44.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 7.18' / 6.93' S= 0.0057 '/ Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.79 sf
#2	Device 1	9.46'	Custom Weir/Orifice, Cv= 2.62 (C= 3.28) Head (feet) 1.70 3.50 3.50 4.00 Width (feet) 0.20 0.20 4.00 4.00
#3	Device 1	7.76'	5.0" Vert. Orifice/Grate C= 0.600 Limited to weir flow at low heads

Primary OutFlow Max=1.80 cfs @ 11.99 hrs HW=10.55' (Free Discharge)

- ↑ 1=Culvert (Passes 1.80 cfs of 6.01 cfs potential flow)
- ↑ 2=Custom Weir/Orifice (Weir Controls 0.74 cfs @ 3.41 fps)
- ↑ 3=Orifice/Grate (Orifice Controls 1.05 cfs @ 7.73 fps)

Summary for Pond 2P: (new Pond)

[82] Warning: Early inflow requires earlier time span

[57] Hint: Peaked at 13.22' (Flood elevation advised)

Inflow Area = 0.389 ac, 100.00% Impervious, Inflow Depth > 3.18" for 2-yr event
 Inflow = 2.05 cfs @ 11.95 hrs, Volume= 0.103 af
 Outflow = 2.05 cfs @ 11.95 hrs, Volume= 0.103 af, Atten= 0%, Lag= 0.0 min
 Primary = 2.05 cfs @ 11.95 hrs, Volume= 0.103 af
 Routed to Pond 1P :

Routing by Stor-Ind method, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Peak Elev= 13.22' @ 11.95 hrs

Device	Routing	Invert	Outlet Devices
#1	Primary	12.70'	12.0" Round Culvert X 2.00 L= 10.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 12.70' / 11.00' S= 0.1700 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.79 sf

Primary OutFlow Max=2.05 cfs @ 11.95 hrs HW=13.22' (Free Discharge)

- ↑ 1=Culvert (Inlet Controls 2.05 cfs @ 2.46 fps)

Summary for Link DP1:

Inflow Area = 0.834 ac, 91.25% Impervious, Inflow Depth > 3.04" for 2-yr event
 Inflow = 3.97 cfs @ 11.97 hrs, Volume= 0.211 af
 Primary = 0.00 cfs @ 5.00 hrs, Volume= 0.000 af, Atten= 100%, Lag= 0.0 min
 Routed to Link DP3 :
 Secondary = 3.97 cfs @ 11.97 hrs, Volume= 0.211 af
 Routed to Link DP3 :

Primary outflow = Inflow above 1,000.00 cfs, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

Summary for Link DP3:

Inflow Area = 0.960 ac, 90.19% Impervious, Inflow Depth > 3.02" for 2-yr event
 Inflow = 4.60 cfs @ 11.96 hrs, Volume= 0.242 af
 Primary = 0.00 cfs @ 5.00 hrs, Volume= 0.000 af, Atten= 100%, Lag= 0.0 min
 Secondary = 4.60 cfs @ 11.96 hrs, Volume= 0.242 af

Primary outflow = Inflow above 1,000.00 cfs, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

2022-10-19 Proposed Conditions David T

Type II 24-hr 10-yr Rainfall=5.59"

Prepared by Ambit Engineering

Printed 2022-10-19

HydroCAD® 10.20-2f s/n 00801 © 2022 HydroCAD Software Solutions LLC

Page 12

Time span=5.00-20.00 hrs, dt=0.05 hrs, 301 points
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN
Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

Subcatchment P1: Runoff Area=19,402 sf 83.60% Impervious Runoff Depth>4.66"
Tc=5.0 min CN=95 Runoff=3.51 cfs 0.173 af

Subcatchment P1a: Roof Runoff Area=16,944 sf 100.00% Impervious Runoff Depth>4.90"
Tc=5.0 min CN=98 Runoff=3.13 cfs 0.159 af

Subcatchment P2: DP2 Runoff Area=5,462 sf 83.16% Impervious Runoff Depth>4.66"
Tc=5.0 min CN=95 Runoff=0.99 cfs 0.049 af

Pond 1P: Peak Elev=11.36' Storage=0.013 af Inflow=3.13 cfs 0.159 af
Outflow=3.01 cfs 0.159 af

Pond 2P: (new Pond) Peak Elev=13.37' Inflow=3.13 cfs 0.159 af
12.0" Round Culvert x 2.00 n=0.013 L=10.0' S=0.1700 '/' Outflow=3.13 cfs 0.159 af

Link DP1: above 1,000.00 cfs Inflow=6.49 cfs 0.332 af
Primary=0.00 cfs 0.000 af Secondary=6.49 cfs 0.332 af

Link DP3: above 1,000.00 cfs Inflow=7.48 cfs 0.380 af
Primary=0.00 cfs 0.000 af Secondary=7.48 cfs 0.380 af

Total Runoff Area = 0.960 ac Runoff Volume = 0.381 af Average Runoff Depth = 4.76"
9.81% Pervious = 0.094 ac 90.19% Impervious = 0.866 ac

2022-10-19 Proposed Conditions David T

Type II 24-hr 10-yr Rainfall=5.59"

Prepared by Ambit Engineering

Printed 2022-10-19

HydroCAD® 10.20-2f s/n 00801 © 2022 HydroCAD Software Solutions LLC

Page 13

Summary for Subcatchment P1:

[49] Hint: Tc<2dt may require smaller dt

Runoff = 3.51 cfs @ 11.95 hrs, Volume= 0.173 af, Depth> 4.66"
 Routed to Link DP1 :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type II 24-hr 10-yr Rainfall=5.59"

Area (sf)	CN	Description
821	80	>75% Grass cover, Good, HSG D
2,846	98	Paved parking, HSG D
15,735	95	Urban commercial, 85% imp, HSG D
19,402	95	Weighted Average
3,181		16.40% Pervious Area
16,221		83.60% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Summary for Subcatchment P1a: Roof

[49] Hint: Tc<2dt may require smaller dt

Runoff = 3.13 cfs @ 11.95 hrs, Volume= 0.159 af, Depth> 4.90"
 Routed to Pond 2P : (new Pond)

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type II 24-hr 10-yr Rainfall=5.59"

Area (sf)	CN	Description
9,126	98	Roofs, HSG D
7,818	98	Roofs, HSG D
16,944	98	Weighted Average
16,944		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Summary for Subcatchment P2: DP2

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.99 cfs @ 11.95 hrs, Volume= 0.049 af, Depth> 4.66"
 Routed to Link DP3 :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type II 24-hr 10-yr Rainfall=5.59"

2022-10-19 Proposed Conditions David T

Type II 24-hr 10-yr Rainfall=5.59"

Prepared by Ambit Engineering

Printed 2022-10-19

HydroCAD® 10.20-2f s/n 00801 © 2022 HydroCAD Software Solutions LLC

Page 14

Area (sf)	CN	Description
920	80	>75% Grass cover, Good, HSG D
4,542	98	Paved parking, HSG D
5,462	95	Weighted Average
920		16.84% Pervious Area
4,542		83.16% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Summary for Pond 1P:

[82] Warning: Early inflow requires earlier time span

[44] Hint: Outlet device #3 is below defined storage

[79] Warning: Submerged Pond 2P Primary device # 1 OUTLET by 0.30'

Inflow Area = 0.389 ac, 100.00% Impervious, Inflow Depth > 4.90" for 10-yr event
 Inflow = 3.13 cfs @ 11.95 hrs, Volume= 0.159 af
 Outflow = 3.01 cfs @ 11.97 hrs, Volume= 0.159 af, Atten= 4%, Lag= 1.1 min
 Primary = 3.01 cfs @ 11.97 hrs, Volume= 0.159 af
 Routed to Link DP1 :

Routing by Stor-Ind method, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Peak Elev= 11.36' @ 11.97 hrs Surf.Area= 0.006 ac Storage= 0.013 af

Plug-Flow detention time= 2.8 min calculated for 0.159 af (100% of inflow)
 Center-of-Mass det. time= 2.5 min (731.3 - 728.8)

Volume	Invert	Avail.Storage	Storage Description
#1A	7.86'	0.006 af	9.25'W x 27.46'L x 4.07'H Field A 0.024 af Overall - 0.008 af Embedded = 0.016 af x 40.0% Voids
#2A	8.11'	0.008 af	ACF R-Tank LD 2 x 40 Inside #1 Inside= 15.7"W x 33.9"H => 3.52 sf x 2.35'L = 8.3 cf Outside= 15.7"W x 33.9"H => 3.70 sf x 2.35'L = 8.7 cf 40 Chambers in 4 Rows
		0.014 af	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	7.18'	12.0" Round Culvert L= 44.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 7.18' / 6.93' S= 0.0057 '/ Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.79 sf
#2	Device 1	9.46'	Custom Weir/Orifice, Cv= 2.62 (C= 3.28) Head (feet) 1.70 3.50 3.50 4.00 Width (feet) 0.20 0.20 4.00 4.00
#3	Device 1	7.76'	5.0" Vert. Orifice/Grate C= 0.600 Limited to weir flow at low heads

Primary OutFlow Max=2.89 cfs @ 11.97 hrs HW=11.29' (Free Discharge)

- ↑ 1=Culvert (Passes 2.89 cfs of 6.81 cfs potential flow)
- ↑ 2=Custom Weir/Orifice (Weir Controls 1.69 cfs @ 3.49 fps)
- ↑ 3=Orifice/Grate (Orifice Controls 1.20 cfs @ 8.78 fps)

Summary for Pond 2P: (new Pond)

[82] Warning: Early inflow requires earlier time span

[57] Hint: Peaked at 13.37' (Flood elevation advised)

Inflow Area = 0.389 ac, 100.00% Impervious, Inflow Depth > 4.90" for 10-yr event
 Inflow = 3.13 cfs @ 11.95 hrs, Volume= 0.159 af
 Outflow = 3.13 cfs @ 11.95 hrs, Volume= 0.159 af, Atten= 0%, Lag= 0.0 min
 Primary = 3.13 cfs @ 11.95 hrs, Volume= 0.159 af
 Routed to Pond 1P :

Routing by Stor-Ind method, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Peak Elev= 13.37' @ 11.95 hrs

Device	Routing	Invert	Outlet Devices
#1	Primary	12.70'	12.0" Round Culvert X 2.00 L= 10.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 12.70' / 11.00' S= 0.1700 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.79 sf

Primary OutFlow Max=3.13 cfs @ 11.95 hrs HW=13.37' (Free Discharge)

- ↑ 1=Culvert (Inlet Controls 3.13 cfs @ 2.79 fps)

Summary for Link DP1:

Inflow Area = 0.834 ac, 91.25% Impervious, Inflow Depth > 4.77" for 10-yr event
 Inflow = 6.49 cfs @ 11.96 hrs, Volume= 0.332 af
 Primary = 0.00 cfs @ 5.00 hrs, Volume= 0.000 af, Atten= 100%, Lag= 0.0 min
 Routed to Link DP3 :
 Secondary = 6.49 cfs @ 11.96 hrs, Volume= 0.332 af
 Routed to Link DP3 :

Primary outflow = Inflow above 1,000.00 cfs, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

Summary for Link DP3:

Inflow Area = 0.960 ac, 90.19% Impervious, Inflow Depth > 4.76" for 10-yr event
 Inflow = 7.48 cfs @ 11.96 hrs, Volume= 0.380 af
 Primary = 0.00 cfs @ 5.00 hrs, Volume= 0.000 af, Atten= 100%, Lag= 0.0 min
 Secondary = 7.48 cfs @ 11.96 hrs, Volume= 0.380 af

Primary outflow = Inflow above 1,000.00 cfs, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

2022-10-19 Proposed Conditions David T

Type II 24-hr 25-yr Rainfall=7.08"

Prepared by Ambit Engineering

Printed 2022-10-19

HydroCAD® 10.20-2f s/n 00801 © 2022 HydroCAD Software Solutions LLC

Page 16

Time span=5.00-20.00 hrs, dt=0.05 hrs, 301 points
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN
Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

Subcatchment P1: Runoff Area=19,402 sf 83.60% Impervious Runoff Depth>6.02"
Tc=5.0 min CN=95 Runoff=4.49 cfs 0.223 af

Subcatchment P1a: Roof Runoff Area=16,944 sf 100.00% Impervious Runoff Depth>6.24"
Tc=5.0 min CN=98 Runoff=3.97 cfs 0.202 af

Subcatchment P2: DP2 Runoff Area=5,462 sf 83.16% Impervious Runoff Depth>6.02"
Tc=5.0 min CN=95 Runoff=1.26 cfs 0.063 af

Pond 1P: Peak Elev=11.46' Storage=0.013 af Inflow=3.97 cfs 0.202 af
Outflow=4.18 cfs 0.202 af

Pond 2P: (new Pond) Peak Elev=13.48' Inflow=3.97 cfs 0.202 af
12.0" Round Culvert x 2.00 n=0.013 L=10.0' S=0.1700 '/' Outflow=3.97 cfs 0.202 af

Link DP1: above 1,000.00 cfs Inflow=8.66 cfs 0.425 af
Primary=0.00 cfs 0.000 af Secondary=8.66 cfs 0.425 af

Link DP3: above 1,000.00 cfs Inflow=9.93 cfs 0.488 af
Primary=0.00 cfs 0.000 af Secondary=9.93 cfs 0.488 af

Total Runoff Area = 0.960 ac Runoff Volume = 0.488 af Average Runoff Depth = 6.11"
9.81% Pervious = 0.094 ac 90.19% Impervious = 0.866 ac

2022-10-19 Proposed Conditions David T

Type II 24-hr 25-yr Rainfall=7.08"

Prepared by Ambit Engineering

Printed 2022-10-19

HydroCAD® 10.20-2f s/n 00801 © 2022 HydroCAD Software Solutions LLC

Page 17

Summary for Subcatchment P1:

[49] Hint: Tc<2dt may require smaller dt

Runoff = 4.49 cfs @ 11.95 hrs, Volume= 0.223 af, Depth> 6.02"
 Routed to Link DP1 :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type II 24-hr 25-yr Rainfall=7.08"

Area (sf)	CN	Description
821	80	>75% Grass cover, Good, HSG D
2,846	98	Paved parking, HSG D
15,735	95	Urban commercial, 85% imp, HSG D
19,402	95	Weighted Average
3,181		16.40% Pervious Area
16,221		83.60% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Summary for Subcatchment P1a: Roof

[49] Hint: Tc<2dt may require smaller dt

Runoff = 3.97 cfs @ 11.95 hrs, Volume= 0.202 af, Depth> 6.24"
 Routed to Pond 2P : (new Pond)

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type II 24-hr 25-yr Rainfall=7.08"

Area (sf)	CN	Description
9,126	98	Roofs, HSG D
7,818	98	Roofs, HSG D
16,944	98	Weighted Average
16,944		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Summary for Subcatchment P2: DP2

[49] Hint: Tc<2dt may require smaller dt

Runoff = 1.26 cfs @ 11.95 hrs, Volume= 0.063 af, Depth> 6.02"
 Routed to Link DP3 :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Type II 24-hr 25-yr Rainfall=7.08"

2022-10-19 Proposed Conditions David T

Type II 24-hr 25-yr Rainfall=7.08"

Prepared by Ambit Engineering

Printed 2022-10-19

HydroCAD® 10.20-2f s/n 00801 © 2022 HydroCAD Software Solutions LLC

Page 18

Area (sf)	CN	Description
920	80	>75% Grass cover, Good, HSG D
4,542	98	Paved parking, HSG D
5,462	95	Weighted Average
920		16.84% Pervious Area
4,542		83.16% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Summary for Pond 1P:

- [82] Warning: Early inflow requires earlier time span
- [44] Hint: Outlet device #3 is below defined storage
- [88] Warning: Qout>Qin may require smaller dt or Finer Routing
- [79] Warning: Submerged Pond 2P Primary device # 1 OUTLET by 0.46'

Inflow Area = 0.389 ac, 100.00% Impervious, Inflow Depth > 6.24" for 25-yr event
 Inflow = 3.97 cfs @ 11.95 hrs, Volume= 0.202 af
 Outflow = 4.18 cfs @ 11.95 hrs, Volume= 0.202 af, Atten= 0%, Lag= 0.2 min
 Primary = 4.18 cfs @ 11.95 hrs, Volume= 0.202 af
 Routed to Link DP1 :

Routing by Stor-Ind method, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Peak Elev= 11.46' @ 11.95 hrs Surf.Area= 0.006 ac Storage= 0.013 af

Plug-Flow detention time= 2.7 min calculated for 0.201 af (100% of inflow)
 Center-of-Mass det. time= 2.4 min (730.3 - 727.9)

Volume	Invert	Avail.Storage	Storage Description
#1A	7.86'	0.006 af	9.25'W x 27.46'L x 4.07'H Field A 0.024 af Overall - 0.008 af Embedded = 0.016 af x 40.0% Voids
#2A	8.11'	0.008 af	ACF R-Tank LD 2 x 40 Inside #1 Inside= 15.7"W x 33.9"H => 3.52 sf x 2.35'L = 8.3 cf Outside= 15.7"W x 33.9"H => 3.70 sf x 2.35'L = 8.7 cf 40 Chambers in 4 Rows
		0.014 af	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	7.18'	12.0" Round Culvert L= 44.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 7.18' / 6.93' S= 0.0057 '/ Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.79 sf
#2	Device 1	9.46'	Custom Weir/Orifice, Cv= 2.62 (C= 3.28) Head (feet) 1.70 3.50 3.50 4.00 Width (feet) 0.20 0.20 4.00 4.00
#3	Device 1	7.76'	5.0" Vert. Orifice/Grate C= 0.600 Limited to weir flow at low heads

Primary OutFlow Max=4.10 cfs @ 11.95 hrs HW=11.45' (Free Discharge)

- ↑ 1=Culvert (Passes 4.10 cfs of 6.97 cfs potential flow)
- ↑ 2=Custom Weir/Orifice (Weir Controls 2.87 cfs @ 2.56 fps)
- ↑ 3=Orifice/Grate (Orifice Controls 1.23 cfs @ 8.98 fps)

Summary for Pond 2P: (new Pond)

[82] Warning: Early inflow requires earlier time span

[57] Hint: Peaked at 13.48' (Flood elevation advised)

Inflow Area = 0.389 ac, 100.00% Impervious, Inflow Depth > 6.24" for 25-yr event
 Inflow = 3.97 cfs @ 11.95 hrs, Volume= 0.202 af
 Outflow = 3.97 cfs @ 11.95 hrs, Volume= 0.202 af, Atten= 0%, Lag= 0.0 min
 Primary = 3.97 cfs @ 11.95 hrs, Volume= 0.202 af
 Routed to Pond 1P :

Routing by Stor-Ind method, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Peak Elev= 13.48' @ 11.95 hrs

Device	Routing	Invert	Outlet Devices
#1	Primary	12.70'	12.0" Round Culvert X 2.00 L= 10.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 12.70' / 11.00' S= 0.1700 '/ Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.79 sf

Primary OutFlow Max=3.97 cfs @ 11.95 hrs HW=13.48' (Free Discharge)

- ↑ 1=Culvert (Inlet Controls 3.97 cfs @ 3.01 fps)

Summary for Link DP1:

Inflow Area = 0.834 ac, 91.25% Impervious, Inflow Depth > 6.12" for 25-yr event
 Inflow = 8.66 cfs @ 11.95 hrs, Volume= 0.425 af
 Primary = 0.00 cfs @ 5.00 hrs, Volume= 0.000 af, Atten= 100%, Lag= 0.0 min
 Routed to Link DP3 :
 Secondary = 8.66 cfs @ 11.95 hrs, Volume= 0.425 af
 Routed to Link DP3 :

Primary outflow = Inflow above 1,000.00 cfs, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

Summary for Link DP3:

Inflow Area = 0.960 ac, 90.19% Impervious, Inflow Depth > 6.10" for 25-yr event
 Inflow = 9.93 cfs @ 11.95 hrs, Volume= 0.488 af
 Primary = 0.00 cfs @ 5.00 hrs, Volume= 0.000 af, Atten= 100%, Lag= 0.0 min
 Secondary = 9.93 cfs @ 11.95 hrs, Volume= 0.488 af

Primary outflow = Inflow above 1,000.00 cfs, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

2022-10-19 Proposed Conditions David T

Type II 24-hr 50-yr Rainfall=8.48"

Prepared by Ambit Engineering

Printed 2022-10-19

HydroCAD® 10.20-2f s/n 00801 © 2022 HydroCAD Software Solutions LLC

Page 20

Time span=5.00-20.00 hrs, dt=0.05 hrs, 301 points
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN
Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

Subcatchment P1: Runoff Area=19,402 sf 83.60% Impervious Runoff Depth>7.29"
Tc=5.0 min CN=95 Runoff=5.40 cfs 0.270 af

Subcatchment P1a: Roof Runoff Area=16,944 sf 100.00% Impervious Runoff Depth>7.49"
Tc=5.0 min CN=98 Runoff=4.76 cfs 0.243 af

Subcatchment P2: DP2 Runoff Area=5,462 sf 83.16% Impervious Runoff Depth>7.29"
Tc=5.0 min CN=95 Runoff=1.52 cfs 0.076 af

Pond 1P: Peak Elev=11.50' Storage=0.013 af Inflow=4.76 cfs 0.243 af
Outflow=4.64 cfs 0.243 af

Pond 2P: (new Pond) Peak Elev=13.59' Inflow=4.76 cfs 0.243 af
12.0" Round Culvert x 2.00 n=0.013 L=10.0' S=0.1700 '/' Outflow=4.76 cfs 0.243 af

Link DP1: above 1,000.00 cfs Inflow=10.04 cfs 0.513 af
Primary=0.00 cfs 0.000 af Secondary=10.04 cfs 0.513 af

Link DP3: above 1,000.00 cfs Inflow=11.56 cfs 0.589 af
Primary=0.00 cfs 0.000 af Secondary=11.56 cfs 0.589 af

Total Runoff Area = 0.960 ac Runoff Volume = 0.589 af Average Runoff Depth = 7.37"
9.81% Pervious = 0.094 ac 90.19% Impervious = 0.866 ac

2022-10-19 Proposed Conditions David T

Type II 24-hr 50-yr Rainfall=8.48"

Prepared by Ambit Engineering

Printed 2022-10-19

HydroCAD® 10.20-2f s/n 00801 © 2022 HydroCAD Software Solutions LLC

Page 21

Summary for Subcatchment P1:

[49] Hint: Tc<2dt may require smaller dt

Runoff = 5.40 cfs @ 11.95 hrs, Volume= 0.270 af, Depth> 7.29"
Routed to Link DP1 :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
Type II 24-hr 50-yr Rainfall=8.48"

Area (sf)	CN	Description
821	80	>75% Grass cover, Good, HSG D
2,846	98	Paved parking, HSG D
15,735	95	Urban commercial, 85% imp, HSG D
19,402	95	Weighted Average
3,181		16.40% Pervious Area
16,221		83.60% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Summary for Subcatchment P1a: Roof

[49] Hint: Tc<2dt may require smaller dt

Runoff = 4.76 cfs @ 11.95 hrs, Volume= 0.243 af, Depth> 7.49"
Routed to Pond 2P : (new Pond)

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
Type II 24-hr 50-yr Rainfall=8.48"

Area (sf)	CN	Description
9,126	98	Roofs, HSG D
7,818	98	Roofs, HSG D
16,944	98	Weighted Average
16,944		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Summary for Subcatchment P2: DP2

[49] Hint: Tc<2dt may require smaller dt

Runoff = 1.52 cfs @ 11.95 hrs, Volume= 0.076 af, Depth> 7.29"
Routed to Link DP3 :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
Type II 24-hr 50-yr Rainfall=8.48"

2022-10-19 Proposed Conditions David T

Type II 24-hr 50-yr Rainfall=8.48"

Prepared by Ambit Engineering

Printed 2022-10-19

HydroCAD® 10.20-2f s/n 00801 © 2022 HydroCAD Software Solutions LLC

Page 22

Area (sf)	CN	Description
920	80	>75% Grass cover, Good, HSG D
4,542	98	Paved parking, HSG D
5,462	95	Weighted Average
920		16.84% Pervious Area
4,542		83.16% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Summary for Pond 1P:

[82] Warning: Early inflow requires earlier time span

[44] Hint: Outlet device #3 is below defined storage

[79] Warning: Submerged Pond 2P Primary device # 1 OUTLET by 0.50'

Inflow Area = 0.389 ac, 100.00% Impervious, Inflow Depth > 7.49" for 50-yr event
 Inflow = 4.76 cfs @ 11.95 hrs, Volume= 0.243 af
 Outflow = 4.64 cfs @ 11.95 hrs, Volume= 0.243 af, Atten= 3%, Lag= 0.2 min
 Primary = 4.64 cfs @ 11.95 hrs, Volume= 0.243 af
 Routed to Link DP1 :

Routing by Stor-Ind method, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Peak Elev= 11.50' @ 11.95 hrs Surf.Area= 0.006 ac Storage= 0.013 af

Plug-Flow detention time= 2.7 min calculated for 0.243 af (100% of inflow)
 Center-of-Mass det. time= 2.3 min (729.7 - 727.4)

Volume	Invert	Avail.Storage	Storage Description
#1A	7.86'	0.006 af	9.25'W x 27.46'L x 4.07'H Field A 0.024 af Overall - 0.008 af Embedded = 0.016 af x 40.0% Voids
#2A	8.11'	0.008 af	ACF R-Tank LD 2 x 40 Inside #1 Inside= 15.7"W x 33.9"H => 3.52 sf x 2.35'L = 8.3 cf Outside= 15.7"W x 33.9"H => 3.70 sf x 2.35'L = 8.7 cf 40 Chambers in 4 Rows
		0.014 af	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	7.18'	12.0" Round Culvert L= 44.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 7.18' / 6.93' S= 0.0057 '/ Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.79 sf
#2	Device 1	9.46'	Custom Weir/Orifice, Cv= 2.62 (C= 3.28) Head (feet) 1.70 3.50 3.50 4.00 Width (feet) 0.20 0.20 4.00 4.00
#3	Device 1	7.76'	5.0" Vert. Orifice/Grate C= 0.600 Limited to weir flow at low heads

Primary OutFlow Max=4.61 cfs @ 11.95 hrs HW=11.50' (Free Discharge)

- ↑ 1=Culvert (Passes 4.61 cfs of 7.02 cfs potential flow)
- ↑ 2=Custom Weir/Orifice (Weir Controls 3.38 cfs @ 2.55 fps)
- ↑ 3=Orifice/Grate (Orifice Controls 1.23 cfs @ 9.05 fps)

Summary for Pond 2P: (new Pond)

[82] Warning: Early inflow requires earlier time span

[57] Hint: Peaked at 13.59' (Flood elevation advised)

Inflow Area = 0.389 ac, 100.00% Impervious, Inflow Depth > 7.49" for 50-yr event
 Inflow = 4.76 cfs @ 11.95 hrs, Volume= 0.243 af
 Outflow = 4.76 cfs @ 11.95 hrs, Volume= 0.243 af, Atten= 0%, Lag= 0.0 min
 Primary = 4.76 cfs @ 11.95 hrs, Volume= 0.243 af
 Routed to Pond 1P :

Routing by Stor-Ind method, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs
 Peak Elev= 13.59' @ 11.95 hrs

Device	Routing	Invert	Outlet Devices
#1	Primary	12.70'	12.0" Round Culvert X 2.00 L= 10.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 12.70' / 11.00' S= 0.1700 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.79 sf

Primary OutFlow Max=4.76 cfs @ 11.95 hrs HW=13.59' (Free Discharge)

- ↑ 1=Culvert (Inlet Controls 4.76 cfs @ 3.22 fps)

Summary for Link DP1:

Inflow Area = 0.834 ac, 91.25% Impervious, Inflow Depth > 7.38" for 50-yr event
 Inflow = 10.04 cfs @ 11.95 hrs, Volume= 0.513 af
 Primary = 0.00 cfs @ 5.00 hrs, Volume= 0.000 af, Atten= 100%, Lag= 0.0 min
 Routed to Link DP3 :
 Secondary = 10.04 cfs @ 11.95 hrs, Volume= 0.513 af
 Routed to Link DP3 :

Primary outflow = Inflow above 1,000.00 cfs, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

Summary for Link DP3:

Inflow Area = 0.960 ac, 90.19% Impervious, Inflow Depth > 7.37" for 50-yr event
 Inflow = 11.56 cfs @ 11.95 hrs, Volume= 0.589 af
 Primary = 0.00 cfs @ 5.00 hrs, Volume= 0.000 af, Atten= 100%, Lag= 0.0 min
 Secondary = 11.56 cfs @ 11.95 hrs, Volume= 0.589 af

Primary outflow = Inflow above 1,000.00 cfs, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

APPENDIX D
SOIL SURVEY INFORMATION



United States
Department of
Agriculture

NRCS

Natural
Resources
Conservation
Service

A product of the National
Cooperative Soil Survey,
a joint effort of the United
States Department of
Agriculture and other
Federal agencies, State
agencies including the
Agricultural Experiment
Stations, and local
participants


Custom Soil Resource Report for Rockingham County, New Hampshire



Custom Soil Resource Report Soil Map



Soil Map may not be valid at this scale.



MAP LEGEND

Area of Interest (AOI)

 Area of Interest (AOI)

Soils

 Soil Map Unit Polygons

 Soil Map Unit Lines

 Soil Map Unit Points

Special Point Features

-  Blowout
-  Borrow Pit
-  Clay Spot
-  Closed Depression
-  Gravel Pit
-  Gravelly Spot
-  Landfill
-  Lava Flow
-  Marsh or swamp
-  Mine or Quarry
-  Miscellaneous Water
-  Perennial Water
-  Rock Outcrop
-  Saline Spot
-  Sandy Spot
-  Severely Eroded Spot
-  Sinkhole
-  Slide or Slip
-  Sodic Spot

-  Spoil Area
-  Stony Spot
-  Very Stony Spot
-  Wet Spot
-  Other
-  Special Line Features


Water Features

 Streams and Canals

Transportation

-  Rails
-  Interstate Highways
-  US Routes
-  Major Roads
-  Local Roads

Background

 Aerial Photography

MAP INFORMATION

The soil surveys that comprise your AOI were mapped at 1:24,000.

Warning: Soil Map may not be valid at this scale.

Enlargement of maps beyond the scale of mapping can cause misunderstanding of the detail of mapping and accuracy of soil line placement. The maps do not show the small areas of contrasting soils that could have been shown at a more detailed scale.

Please rely on the bar scale on each map sheet for map measurements.

Source of Map: Natural Resources Conservation Service
 Web Soil Survey URL:
 Coordinate System: Web Mercator (EPSG:3857)

Maps from the Web Soil Survey are based on the Web Mercator projection, which preserves direction and shape but distorts distance and area. A projection that preserves area, such as the Albers equal-area conic projection, should be used if more accurate calculations of distance or area are required.

This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.

Soil Survey Area: Rockingham County, New Hampshire
 Survey Area Data: Version 24, Aug 31, 2021

Soil map units are labeled (as space allows) for map scales 1:50,000 or larger.

Date(s) aerial images were photographed: Sep 19, 2021—Nov 1, 2021

The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.

Map Unit Legend

Map Unit Symbol	Map Unit Name	Acres in AOI	Percent of AOI
699	Urban land	0.5	91.5%
799	Urban land-Canton complex, 3 to 15 percent slopes	0.0	8.5%
Totals for Area of Interest		0.5	100.0%

Map Unit Descriptions

The map units delineated on the detailed soil maps in a soil survey represent the soils or miscellaneous areas in the survey area. The map unit descriptions, along with the maps, can be used to determine the composition and properties of a unit.

A map unit delineation on a soil map represents an area dominated by one or more major kinds of soil or miscellaneous areas. A map unit is identified and named according to the taxonomic classification of the dominant soils. Within a taxonomic class there are precisely defined limits for the properties of the soils. On the landscape, however, the soils are natural phenomena, and they have the characteristic variability of all natural phenomena. Thus, the range of some observed properties may extend beyond the limits defined for a taxonomic class. Areas of soils of a single taxonomic class rarely, if ever, can be mapped without including areas of other taxonomic classes. Consequently, every map unit is made up of the soils or miscellaneous areas for which it is named and some minor components that belong to taxonomic classes other than those of the major soils.

Most minor soils have properties similar to those of the dominant soil or soils in the map unit, and thus they do not affect use and management. These are called noncontrasting, or similar, components. They may or may not be mentioned in a particular map unit description. Other minor components, however, have properties and behavioral characteristics divergent enough to affect use or to require different management. These are called contrasting, or dissimilar, components. They generally are in small areas and could not be mapped separately because of the scale used. Some small areas of strongly contrasting soils or miscellaneous areas are identified by a special symbol on the maps. If included in the database for a given area, the contrasting minor components are identified in the map unit descriptions along with some characteristics of each. A few areas of minor components may not have been observed, and consequently they are not mentioned in the descriptions, especially where the pattern was so complex that it was impractical to make enough observations to identify all the soils and miscellaneous areas on the landscape.

The presence of minor components in a map unit in no way diminishes the usefulness or accuracy of the data. The objective of mapping is not to delineate pure taxonomic classes but rather to separate the landscape into landforms or landform segments that have similar use and management requirements. The delineation of such segments on the map provides sufficient information for the development of resource plans. If intensive use of small areas is planned, however,

Custom Soil Resource Report

onsite investigation is needed to define and locate the soils and miscellaneous areas.

An identifying symbol precedes the map unit name in the map unit descriptions. Each description includes general facts about the unit and gives important soil properties and qualities.

Soils that have profiles that are almost alike make up a *soil series*. Except for differences in texture of the surface layer, all the soils of a series have major horizons that are similar in composition, thickness, and arrangement.

Soils of one series can differ in texture of the surface layer, slope, stoniness, salinity, degree of erosion, and other characteristics that affect their use. On the basis of such differences, a soil series is divided into *soil phases*. Most of the areas shown on the detailed soil maps are phases of soil series. The name of a soil phase commonly indicates a feature that affects use or management. For example, Alpha silt loam, 0 to 2 percent slopes, is a phase of the Alpha series.

Some map units are made up of two or more major soils or miscellaneous areas. These map units are complexes, associations, or undifferentiated groups.

A *complex* consists of two or more soils or miscellaneous areas in such an intricate pattern or in such small areas that they cannot be shown separately on the maps. The pattern and proportion of the soils or miscellaneous areas are somewhat similar in all areas. Alpha-Beta complex, 0 to 6 percent slopes, is an example.

An *association* is made up of two or more geographically associated soils or miscellaneous areas that are shown as one unit on the maps. Because of present or anticipated uses of the map units in the survey area, it was not considered practical or necessary to map the soils or miscellaneous areas separately. The pattern and relative proportion of the soils or miscellaneous areas are somewhat similar. Alpha-Beta association, 0 to 2 percent slopes, is an example.

An *undifferentiated group* is made up of two or more soils or miscellaneous areas that could be mapped individually but are mapped as one unit because similar interpretations can be made for use and management. The pattern and proportion of the soils or miscellaneous areas in a mapped area are not uniform. An area can be made up of only one of the major soils or miscellaneous areas, or it can be made up of all of them. Alpha and Beta soils, 0 to 2 percent slopes, is an example.

Some surveys include *miscellaneous areas*. Such areas have little or no soil material and support little or no vegetation. Rock outcrop is an example.

Rockingham County, New Hampshire

699—Urban land

Map Unit Composition

Urban land: 85 percent

Minor components: 15 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Minor Components

Not named

Percent of map unit: 15 percent

Hydric soil rating: No

799—Urban land-Canton complex, 3 to 15 percent slopes

Map Unit Setting

National map unit symbol: 9cq0

Elevation: 0 to 1,000 feet

Mean annual precipitation: 42 to 46 inches

Mean annual air temperature: 45 to 48 degrees F

Frost-free period: 120 to 160 days

Farmland classification: Not prime farmland

Map Unit Composition

Urban land: 55 percent

Canton and similar soils: 20 percent

Minor components: 25 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Canton

Setting

Parent material: Till

Typical profile

H1 - 0 to 5 inches: gravelly fine sandy loam

H2 - 5 to 21 inches: gravelly fine sandy loam

H3 - 21 to 60 inches: loamy sand

Properties and qualities

Slope: 3 to 8 percent

Depth to restrictive feature: More than 80 inches

Drainage class: Well drained

Runoff class: Low

Capacity of the most limiting layer to transmit water (Ksat): High (2.00 to 6.00 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None

Frequency of ponding: None

Available water supply, 0 to 60 inches: Low (about 5.3 inches)

Custom Soil Resource Report

Interpretive groups

Land capability classification (irrigated): None specified
Land capability classification (nonirrigated): 2e
Hydrologic Soil Group: A
Ecological site: F144AY034CT - Well Drained Till Uplands
Hydric soil rating: No

Minor Components

Udorthents

Percent of map unit: 5 percent
Hydric soil rating: No

Squamscott and scitico

Percent of map unit: 4 percent
Landform: Marine terraces
Hydric soil rating: Yes

Walpole

Percent of map unit: 4 percent
Landform: Depressions
Hydric soil rating: Yes

Chatfield

Percent of map unit: 4 percent
Hydric soil rating: No

Scituate and newfields

Percent of map unit: 4 percent
Hydric soil rating: No

Boxford and eldridge


Percent of map unit: 4 percent
Hydric soil rating: No

APPENDIX E
FEMA FIRM MAP

National Flood Hazard Layer FIRMMette



70°46'3"W 43°4'55"N



70°45'26"W 43°4'29"N

Basemap: USGS National Map: Orthoimagery: Data refreshed October, 2020

Legend

SEE FIS REPORT FOR DETAILED LEGEND AND INDEX MAP FOR FIRM PANEL LAYOUT

SPECIAL FLOOD HAZARD AREAS	
	Without Base Flood Elevation (BFE) <i>Zone A, V, A99</i>
	With BFE or Depth <i>Zone AE, AO, AH, VE, AR</i>
	Regulatory Floodway

	0.2% Annual Chance Flood Hazard, Areas of 1% annual chance flood with average depth less than one foot or with drainage areas of less than one square mile <i>Zone X</i>
	Future Conditions 1% Annual Chance Flood Hazard <i>Zone X</i>
	Area with Reduced Flood Risk due to Levee. See Notes. <i>Zone X</i>
	Area with Flood Risk due to Levee <i>Zone D</i>

OTHER AREAS OF FLOOD HAZARD

	NO SCREEN Area of Minimal Flood Hazard <i>Zone X</i>
	Effective LOMRs
	Area of Undetermined Flood Hazard <i>Zone D</i>

OTHER AREAS

	Channel, Culvert, or Storm Sewer
	Levee, Dike, or Floodwall

	20.2 Cross Sections with 1% Annual Chance Water Surface Elevation
	17.5 Cross Sections with 1% Annual Chance Water Surface Elevation

	Coastal Transect
	Base Flood Elevation Line (BFE)

	Limit of Study
	Jurisdiction Boundary

	Coastal Transect Baseline
	Profile Baseline
	Hydrographic Feature

OTHER FEATURES

	Digital Data Available
	No Digital Data Available
	Unmapped

MAP PANELS

The pin displayed on the map is an approximate point selected by the user and does not represent an authoritative property location.



This map complies with FEMA's standards for the use of digital flood maps if it is not void as described below. The basemap shown complies with FEMA's basemap accuracy standards

The flood hazard information is derived directly from the authoritative NFHL web services provided by FEMA. This map was exported on 5/19/2022 at 11:08 AM and does not reflect changes or amendments subsequent to this date and time. The NFHL and effective information may change or become superseded by new data over time.

This map image is void if the one or more of the following map elements do not appear: basemap imagery, flood zone labels, legend, scale bar, map creation date, community identifiers, FIRM panel number, and FIRM effective date. Map images for unmapped and unmodernized areas cannot be used for regulatory purposes.

APPENDIX F
INSPECTION & LONG TERM
MAINTENANCE PLAN



AMBIT ENGINEERING, INC.
Civil Engineers & Land Surveyors

***INSPECTION & LONG-TERM MAINTENANCE PLAN
FOR
SITE DEVELOPMENT***

**88 MAPLEWOOD AVE.
PORTSMOUTH, NH**

Introduction

The intent of this plan is to provide EightKPH, LLC (herein referred to as “owner”) with a list of procedures that document the inspection and maintenance requirements of the stormwater management system for this development. Specifically, the Bio Clean downspout filter, R-Tank storage units and associated structures on the project site (collectively referred to as the “Stormwater Management System”). The contact information for the owner shall be kept current, and if there is a change of ownership of the property this plan must be transferred to the new owner.

The following inspection and maintenance program is necessary to keep the stormwater management system functioning properly and will help in maintaining a high quality of stormwater runoff to minimize potential environmental impacts. By following the enclosed procedures, the owner will be able to maintain the functional design of the stormwater management system and maximize its ability to remove sediment and other contaminants from site generated stormwater runoff.

Annual Report

The owner shall prepare an annual Inspection & Maintenance Report. The report shall include a summary of the system’s maintenance and repair by transmission of the Inspection & Maintenance Log and other information as required. A copy of the report shall be delivered annually to the City of Portsmouth Code Enforcement Officer, if required.

Inspection & Maintenance Checklist/Log

The following pages contain the Stormwater Management System Inspection & Maintenance Requirements and a blank copy of the Stormwater Management System Inspection & Maintenance Log. These forms are provided to the owner as a guideline for performing the inspection and maintenance of the Stormwater Management System. This is a guideline and should be periodically reviewed for conformance with current practice and standards.

Stormwater Management System Components

The Stormwater Management System is designed to mitigate both the quantity and quality of site-generated stormwater runoff. As a result, the design includes the following elements:

Non-Structural BMPs

Non-Structural best management practices (BMP's) include temporary and permanent measures that typically require less labor and capital inputs and are intended to provide protection against erosion of soils. Examples of non-structural BMP's on this project include but are not limited to:

- Temporary and Permanent mulching
- Temporary and Permanent grass cover
- Trees
- Shrubs and ground covers
- Miscellaneous landscape plantings
- Dust control
- Tree protection
- Topsoiling
- Sediment barriers
- Stabilized construction entrance

Structural BMPs

Structural BMPs are more labor and capital-intensive structures or installations that require more specialized personnel to install. Examples on this project include but are not limited to:

- ACF R-Tank stormwater storage system
- Bio Clean Downspout Filter
- Outlet Control Structures and Storm Drains

Inspection and Maintenance Requirements

The following summarizes the inspection and maintenance requirements for the various BMPs that may be found on this project.

1. **Grassed areas (until established):** After each rain event of 0.5" or more during a 24-hour period, inspect grassed areas for signs of disturbance, such as erosion. If damaged areas are discovered, immediately repair the damage. Repairs may include adding new topsoil, lime, seed, fertilizer and mulch.
2. **Plantings:** Planting and landscaping (trees, shrubs) shall be monitored bi-monthly during the first year to insure viability and vigorous growth. Replace dead or dying vegetation with new stock and make adjustments to the conditions that caused the dead or dying vegetation. During dryer times of the year, provide weekly watering or irrigation during the establishment period of the first year.

Make the necessary adjustments to ensure long-term health of the vegetated covers, i.e. provide more permanent mulch or compost or other means of protection.

3. **Bio Clean Downspout Filter:** Refer to the manufacturer's Operation and Maintenance manual for guidance, included herewith.
4. **ACF R-Tank stormwater storage system:** Reference the attached operations and maintenance manual for proper maintenance of the system.
5. **Outlet Control Structures and Storm Drains:** Monitor accumulation of debris in outlet control structures monthly or after significant rain events. Remove sediments when they accumulate within the outlet pipe. During construction, maintain inlet protection until all roadways and parking areas have been stabilized. Prior to the end of construction, inspect the drains and basins for accumulations and remove and clean by jet-vacuuming.

Pollution Prevention

The following pollution prevention activities shall be undertaken to minimize potential impacts on stormwater runoff quality. The Contractor is responsible for all activities during construction. The Owner is responsible thereafter.

Spill Procedures

Any discharge of waste oil or other pollutant shall be reported immediately to the New Hampshire Department of Environmental Services (NHDES). The Contractor/Owner will be responsible for any incident of groundwater contamination resulting from the improper discharge of pollutants to the stormwater system, and may be required by NHDES to remediate incidents that may impact groundwater quality. If the property ownership is transferred, the new owner will be informed of the legal responsibilities associated with operation of the stormwater system, as indicated above.

Sanitary Facilities

Sanitary facilities shall be provided during all phases of construction.

Material Storage

No on site trash facility is provided until homes are constructed. The contractors are required to remove trash from the site. Hazardous material storage is prohibited.

Material Disposal

All waste material, trash, sediment, and debris shall be removed from the site and disposed of in accordance with applicable local, state, and federal guidelines and regulations. Removed sediments shall be if necessary dewatered prior to disposal.

Snow & Ice Management for Standard Asphalt and Walkways

Snow storage will be located such that no direct untreated discharges are possible to receiving waters from the storage site. Salt storage areas shall be covered and located such that no direct discharges are possible to receiving waters from the storage site. Salt and sand shall be used as minimally as possible.

Invasive Species

Monitor the Stormwater Management System for signs of invasive species growth. If caught early, their eradication is much easier. The most likely places where invasions start is in wetter, disturbed soils or detention ponds. Species such as phragmites and purple loose-strife are common invaders in these wetter areas. If they are found, the owner shall refer to the fact-sheet created by the University of New Hampshire Cooperative Extension (or other source) or contact a wetlands scientist with experience in invasive species control to implement a plan of action for eradication. Measures that do not require the application of chemical herbicides should be the first line of defense.



Figure 1: Lythrum salicaria, Purple Loosestrife. Photo by Liz West.

Figure 2: Phragmites australis. Photo by Le Loup Gris

CLOSED DRAINAGE STRUCTURE LONG-TERM MAINTENANCE SHEET

INSPECTION REQUIREMENTS		
ACTION TAKEN	FREQUENCY	MAINTENANCE REQUIREMENTS
<ul style="list-style-type: none"> -Outlet Control Structures -Drain Manholes -Catch Basins 	Every other Month	<ul style="list-style-type: none"> <i>Check for erosion or short-circuiting</i> <i>Check for sediment accumulation</i> <i>Check for floatable contaminants</i>
<ul style="list-style-type: none"> -Drainage Pipes 	1 time per 2 years	<ul style="list-style-type: none"> <i>Check for sediment accumulation/clogging, or soiled runoff.</i> <i>Check for erosion at outlets.</i>


MAINTENANCE LOG	
PROJECT NAME	
INSPECTOR NAME	INSPECTOR CONTACT INFO
DATE OF INSPECTION	REASON FOR INSPECTION <input type="checkbox"/> LARGE STORM EVENT <input type="checkbox"/> PERIODIC CHECK-IN
IS CORRECTIVE ACTION NEEDED? <input type="checkbox"/> YES <input type="checkbox"/> NO	DESCRIBE ANY PROBLEMS, NEEDED MAINTENANCE
DATE OF MAINTENANCE	PERFORMED BY
NOTES	

SERVICE MANUAL

(Cleaning Procedures)

Bio Clean DOWNSPOUT FILTER

Screen Type With Hydrocarbon Boom



TOOLS AND EQUIPMENT NEEDED:

1. Medium size flat scred driver
2. BioSorb hydrocarbon boom. 25-1/2" X 2" dia.
(Call Bio Clean to order)
3. Trash container or bag
4. Wooden dowel approx. 3' x 1/2' dia.



DETAIL OF PARTS



P.O. BOX 869, Oceanside, Ca. 92049
(760) 433-7640 Fax (760) 433-3176
www.biocleanenvironmental.net






REMOVING FILTER




(STEP 4. AT BOTTOM LEFT OF PAGE)

CLEANING FILTER







REPLACING FILTER INSERT



REPLACING FILTER



STEP 11.
POSITION DOWNSPOUT FILTER
BETWEEN PIPES.



STEP 14.
SLIP LISTED ADAPTER/REDUCER
DOWNWARD ON TO
DOWNSPOUT FILTER.

STEP 15.
SECURE BY TIGHTENING
BOTH CLAMPS
WITH SCREWDRIVER.


ENSURE CLAMPS
ARE PROPERLY TIGHTENED.
SERVICE COMPLETE.

STEP 12.
SLIP LISTED ADAPTER/REDUCER
UP ON TO DOWNSPOUT FILTER
UNTIL BASE OF DOWNSPOUT FILTER
RESTS IN BOTTOM OF ADAPTER/REDUCER.

STEP 13.
SECURE BY TIGHTENING
BOTH CLAMPS.

APPROPRIATE INSTALLATION

FILTER CENTERED BETWEEN PIPES WITH EVEN GAPS ON TOP AND BOTTOM



A Forterra Company

P.O. BOX 869, Oceanside, Ca. 92049
(760) 433-7640 Fax (760) 433-3176
www.biocleanenvironmental.net

STABILIZED CONSTRUCTION ENTRANCE CONSTRUCTION MAINTENANCE SHEET

INSPECTION REQUIREMENTS		
ACTION TAKEN	FREQUENCY	MAINTENANCE REQUIREMENTS
ENTRANCE SURFACE <i>-Check for sediment accumulation/clogging of stone</i> <i>-Check Vegetative filter strips</i>	After heavy rains, as necessary	<i>-Top dress pad with new stone.</i> <i>-Replace stone completely if completely clogged.</i> <i>-Maintain vigorous stand of vegetation.</i>
WASHING FACILITIES (if applicable) <i>-Monitor Sediment Accumulation</i>	As often as necessary	<i>-Remove Sediments from traps.</i>

MAINTENANCE LOG	
PROJECT NAME	
INSPECTOR NAME	INSPECTOR CONTACT INFO
DATE OF INSPECTION	REASON FOR INSPECTION <input type="checkbox"/> LARGE STORM EVENT <input type="checkbox"/> PERIODIC CHECK-IN
IS CORRECTIVE ACTION NEEDED? <input type="checkbox"/> YES <input type="checkbox"/> NO	DESCRIBE ANY PROBLEMS, NEEDED MAINTENANCE
DATE OF MAINTENANCE	PERFORMED BY
NOTES	



R-TANK OPERATION, INSPECTION & MAINTENANCE

Operation

Your ACF R-Tank System has been designed to function in conjunction with the engineered drainage system on your site, the existing municipal infrastructure, and/or the existing soils and geography of the receiving watershed. Unless your site included certain unique and rare features, the operation of your R-Tank System will be driven by naturally occurring systems and will function autonomously. However, upholding a proper schedule of Inspection & Maintenance is critical to ensuring continued functionality and optimum performance of the system.

Inspection

Both the R-Tank and all stormwater pre-treatment features incorporated into your site must be inspected regularly. Inspection frequency for your system must be determined based on the contributing drainage area, but should never exceed one year between inspections (six months during the first year of operation).

Inspections may be required more frequently for pre-treatment systems. You should refer to the manufacturer requirements for the proper inspection schedule.

With the right equipment your inspection and measurements can be accomplished from the surface without physically entering any confined spaces. If your inspection does require confined space entry, you **MUST** follow all local/regional requirements as well as OSHA standards.

R-Tank Systems may incorporate Inspection Ports, Maintenance Ports, and/or adjoining manholes. Each of these features are easily accessed by removing the lid at the surface. With the cover removed, a visual inspection can be performed to identify sediment deposits within the structure. Using a flashlight, ALL access points should be examined to complete a thorough inspection.

Inspection Ports

Usually located centrally in the R-Tank System, these perforated columns are designed to give the user a base-line sediment depth across the system floor.

Maintenance Ports

Usually located near the inlet and outlet connections, you'll likely find deeper deposits of heavier sediments when compared to the Inspection Ports.

Manholes

Most systems will include at least two manholes - one at the inlet and another at the outlet. There may be more than one location where stormwater enters the system, which would result in additional manholes to inspect.

Bear in mind that these manholes often include a sump below the invert of the pipe connecting to the R-Tank. These sumps are designed to capture sediment before it reaches the R-Tank, and they should be kept clean to ensure they function properly. However, existence of sediment in the sump does **NOT** necessarily mean sediment has accumulated in the R-Tank.

After inspecting the bottom of the structure, use a mirror on a pole (or some other device) to check for sediment or debris in the pipe connecting to the R-Tank.

R-TANK OPERATION INSPECTION & MAINTENANCE

If sediment or debris is observed in any of these structures, you should determine the depth of the material. This is typically accomplished with a stadia rod, but you should determine the best way to obtain the measurement.

All observations and measurements should be recorded on an Inspection Log kept on file. We've included a form you can use at the end of this guideline.

Maintenance

The R-Tank System should be back-flushed once sediment accumulation has reached 6" or 15% of the total system height. Use the chart below as a guideline to determine the point at which maintenance is required on your system.

R-Tank Unit	Height	Max Sediment Dept
Mini	9.5"	1.5"
Single	17"	3"
Double	34"	5"
Triple	50"	6"
Quad	67"	6"
Pent	84"	6"

Before any maintenance is performed on your system, be sure to plug the outlet pipe to prevent contamination of the adjacent systems.

To back-flush the R-Tank, water is pumped into the system through the Maintenance Ports as rapidly as possible. Water should be pumped into ALL Maintenance Ports. The turbulent action of the water moving through the R-Tank will suspend sediments which may then be pumped out.

If your system includes an Outlet Structure, this will be the ideal location to pump contaminated water out of the system. However, removal of back-flush water may be accomplished through the Maintenance Ports, as well.

For systems with large footprints that would require extensive volumes of water to properly flush the system, you should consider performing your maintenance within 24 hours of a rain event. Stormwater entering the system will aid in the suspension of sediments and reduce the volume of water required to properly flush the system.

Once removed, sediment-laden water may be captured for disposal or pumped through a Dirtbag™ (if permitted by the locality).



2831 Cardwell Road
Richmond, Virginia, 23234
800.448.3636
FAX 804.743.7779
acfenvironmental.com

Step-By-Step Inspection & Maintenance Routine

1) Inspection

- a. Inspection Port
 - i. Remove Cap
 - ii. Use flashlight to detect sediment deposits
 - iii. If present, measure sediment depth with stadia rod
 - iv. Record results on Maintenance Log
 - v. Replace Cap
- b. Maintenance Port/s
 - i. Remove Cap
 - ii. Use flashlight to detect sediment deposits
 - iii. If present, measure sediment depth with stadia rod
 - iv. Record results on Maintenance Log
 - v. Replace Cap
 - vi. Repeat for ALL Maintenance Ports
- c. Adjacent Manholes
 - i. Remove Cover
 - ii. Use flashlight to detect sediment deposits
 - iii. If present, measure sediment depth with stadia rod, accounting for depth of sump (if present)
 - iv. Inspect pipes connecting to R-Tank
 - v. Record results on Maintenance Log
 - vi. Replace Cover
 - vii. Repeat for ALL Manholes that connect to the R-Tank

2) Maintenance

- a. Plug system outlet to prevent discharge of back-flush water
- b. Determine best location to pump out back-flush water
- c. Remove Cap from Maintenance Port
- d. Pump water as rapidly as possible (without over-topping port) into system until at least 1" of water covers system bottom
- e. Replace Cap
- f. Repeat at ALL Maintenance Ports
- g. Pump out back-flush water to complete back-flushing
- h. Vacuum all adjacent structures and any other structures or stormwater pre-treatment systems that require attention
- i. Sediment-laden water may be captured for disposal or pumped through a Dirtbag™.
- j. Replace any remaining Caps or Covers
- k. Record the back-flushing event in your Maintenance Log with any relevant specifics



R-Tank Maintenance Log

Site Name: _____

Location: _____

System Owner: _____

Company Responsible
for Maintenance: _____

Contact: _____


Phone Number: _____

Date	Location	Depth to Bottom	Depth to Sediment	Sediment Depth	Observations/Notes	Initials

For more information about our products, contact Inside Sales at 800.448.3636 or email at info@acfenv.com

Methods for Disposing Non-Native Invasive Plants

Prepared by the Invasives Species Outreach Group, volunteers interested in helping people control invasive plants. Assistance provided by the Piscataquog Land Conservancy and the NH Invasives Species Committee. Edited by Karen Bennett, Extension Forestry Professor and Specialist.



Tatarian honeysuckle

Lonicera tatarica

USDA-NRCS PLANTS Database / Britton, N.L., and A. Brown. 1913. *An illustrated flora of the northern United States, Canada and the British Possessions*. Vol. 3: 282.

Non-native invasive plants crowd out natives in natural and managed landscapes. They cost taxpayers billions of dollars each year from lost agricultural and forest crops, decreased biodiversity, impacts to natural resources and the environment, and the cost to control and eradicate them.

Invasive plants grow well even in less than desirable conditions such as sandy soils along roadsides, shaded wooded areas, and in wetlands. In ideal conditions, they grow and spread even faster. There are many ways to remove these non-native invasives, but once removed, care is needed to dispose the removed plant material so the plants don't grow where disposed.

Knowing how a particular plant reproduces indicates its method of spread and helps determine

the appropriate disposal method. Most are spread by seed and are dispersed by wind, water, animals, or people. Some reproduce by vegetative means from pieces of stems or roots forming new plants. Others spread through both seed and vegetative means.

Because movement and disposal of viable plant parts is restricted (see NH Regulations), viable invasive parts can't be brought to most transfer stations in the state. Check with your transfer station to see if there is an approved, designated area for invasives disposal. This fact sheet gives recommendations for rendering plant parts non-viable.

Control of invasives is beyond the scope of this fact sheet. For information about control visit www.nhinvasives.org or contact your UNH Cooperative Extension office.

New Hampshire Regulations

Prohibited invasive species shall only be disposed of in a manner that renders them nonliving and nonviable. (Agr. 3802.04)

No person shall collect, transport, import, export, move, buy, sell, distribute, propagate or transplant any living and viable portion of any plant species, which includes all of their cultivars and varieties, listed in Table 3800.1 of the New Hampshire prohibited invasive species list. (Agr 3802.01)

How and When to Dispose of Invasives?

To prevent seed from spreading remove invasive plants before seeds are set (produced). Some plants continue to grow, flower and set seed even after pulling or cutting. Seeds can remain viable in the ground for many years. If the plant has flowers or seeds, place the flowers and seeds in a heavy plastic bag “head first” at the weeding site and transport to the disposal site. The following are general descriptions of disposal methods. See the chart for recommendations by species.

Burning: Large woody branches and trunks can be used as firewood or burned in piles. For outside burning, a written fire permit from the local forest fire warden is required unless the ground is covered in snow. Brush larger than 5 inches in diameter can't be burned. Invasive plants with easily airborne seeds like black swallow-wort with mature seed pods (indicated by their brown color) shouldn't be burned as the seeds may disperse by the hot air created by the fire.

Bagging (solarization): Use this technique with softer-tissue plants. Use heavy black or clear plastic bags (contractor grade), making sure that no parts of the plants poke through. Allow the bags to sit in the sun for several weeks and on dark pavement for the best effect.

Tarping and Drying: Pile material on a sheet of plastic and cover with a tarp, fastening the tarp to the ground and monitoring it for escapes. Let the material dry for several weeks, or until it is clearly nonviable.

Chipping: Use this method for woody plants that don't reproduce vegetatively.

Burying: This is risky, but can be done with watchful diligence. Lay thick plastic in a deep pit before placing the cut up plant material in the hole. Place the material away from the edge of the plastic before covering it with more heavy plastic. Eliminate as much air as possible and toss in soil to weight down the material in the pit. Note that the top of the buried material should be at least three feet underground. Japanese knotweed should be at least 5 feet underground!

Drowning: Fill a large barrel with water and place soft-tissue plants in the water. Check after a few weeks and look for rotted plant material (roots, stems, leaves, flowers). Well-rotted plant material may be composted. A word of caution- seeds may still be viable after using this method. Do this before seeds are set. This method isn't used often. Be prepared for an awful stink!

Composting: Invasive plants can take root in compost. Don't compost any invasives unless you know there is no viable (living) plant material left. Use one of the above techniques (bagging, tarping, drying, chipping, or drowning) to render the plants nonviable before composting. Closely examine the plant before composting and avoid composting seeds.






Japanese knotweed
Polygonum cuspidatum
USDA-NRCS PLANTS Database /
Britton, N.L., and A. Brown. 1913. *An illustrated flora of the northern United States, Canada and the British Possessions*. Vol. 1: 676.

Be diligent looking for seedlings for years in areas where removal and disposal took place.

Suggested Disposal Methods for Non-Native Invasive Plants

This table provides information concerning the disposal of removed invasive plant material. If the infestation is treated with herbicide and left in place, these guidelines don't apply. Don't bring invasives to a local transfer station, unless there is a designated area for their disposal, or they have been rendered non-viable. This listing includes wetland and upland plants from the New Hampshire Prohibited Invasive Species List. The disposal of aquatic plants isn't addressed.

Woody Plants	Method of Reproducing	Methods of Disposal
Norway maple <i>(Acer platanoides)</i> European barberry <i>(Berberis vulgaris)</i> Japanese barberry <i>(Berberis thunbergii)</i> autumn olive <i>(Elaeagnus umbellata)</i> burning bush <i>(Euonymus alatus)</i> Morrow's honeysuckle <i>(Lonicera morrowii)</i> Tatarian honeysuckle <i>(Lonicera tatarica)</i> showy bush honeysuckle <i>(Lonicera x bella)</i> common buckthorn <i>(Rhamnus cathartica)</i> glossy buckthorn <i>(Frangula alnus)</i>	Fruit and Seeds 	<p>Prior to fruit/seed ripening</p> <p>Seedlings and small plants</p> <ul style="list-style-type: none"> ▪ Pull or cut and leave on site with roots exposed. No special care needed. <p>Larger plants</p> <ul style="list-style-type: none"> ▪ Use as firewood. ▪ Make a brush pile. ▪ Chip. ▪ Burn. <hr/> <p>After fruit/seed is ripe</p> <p>Don't remove from site.</p> <ul style="list-style-type: none"> ▪ Burn. ▪ Make a covered brush pile. ▪ Chip once all fruit has dropped from branches. ▪ Leave resulting chips on site and monitor.
oriental bittersweet <i>(Celastrus orbiculatus)</i> multiflora rose <i>(Rosa multiflora)</i>	Fruits, Seeds, Plant Fragments 	<p>Prior to fruit/seed ripening</p> <p>Seedlings and small plants</p> <ul style="list-style-type: none"> ▪ Pull or cut and leave on site with roots exposed. No special care needed. <p>Larger plants</p> <ul style="list-style-type: none"> ▪ Make a brush pile. ▪ Burn. <hr/> <p>After fruit/seed is ripe</p> <p>Don't remove from site.</p> <ul style="list-style-type: none"> ▪ Burn. ▪ Make a covered brush pile. ▪ Chip – only after material has fully dried (1 year) and all fruit has dropped from branches. Leave resulting chips on site and monitor.

Non-Woody Plants	Method of Reproducing	Methods of Disposal
<p>garlic mustard (<i>Alliaria petiolata</i>)</p> <p>spotted knapweed (<i>Centaurea maculosa</i>)</p> <ul style="list-style-type: none"> ▪ Sap of related knapweed can cause skin irritation and tumors. Wear gloves when handling. <p>black swallow-wort (<i>Cynanchum nigrum</i>)</p> <ul style="list-style-type: none"> ▪ May cause skin rash. Wear gloves and long sleeves when handling. <p>pale swallow-wort (<i>Cynanchum rossicum</i>)</p> <p>giant hogweed (<i>Heracleum mantegazzianum</i>)</p> <ul style="list-style-type: none"> ▪ Can cause major skin rash. Wear gloves and long sleeves when handling. <p>dame's rocket (<i>Hesperis matronalis</i>)</p> <p>perennial pepperweed (<i>Lepidium latifolium</i>)</p> <p>purple loosestrife (<i>Lythrum salicaria</i>)</p> <p>Japanese stilt grass (<i>Microstegium vimineum</i>)</p> <p>mile-a-minute weed (<i>Polygonum perfoliatum</i>)</p>	<p>Fruits and Seeds</p> 	<p>Prior to flowering</p> <p>Depends on scale of infestation</p> <p>Small infestation</p> <ul style="list-style-type: none"> ▪ Pull or cut plant and leave on site with roots exposed. <p>Large infestation</p> <ul style="list-style-type: none"> ▪ Pull or cut plant and pile. (You can pile onto or cover with plastic sheeting). ▪ Monitor. Remove any re-sprouting material. <hr/> <p>During and following flowering</p> <p>Do nothing until the following year or remove flowering heads and bag and let rot.</p> <p>Small infestation</p> <ul style="list-style-type: none"> ▪ Pull or cut plant and leave on site with roots exposed. <p>Large infestation</p> <ul style="list-style-type: none"> ▪ Pull or cut plant and pile remaining material. (You can pile onto plastic or cover with plastic sheeting). ▪ Monitor. Remove any re-sprouting material.
<p>common reed (<i>Phragmites australis</i>)</p> <p>Japanese knotweed (<i>Polygonum cuspidatum</i>)</p> <p>Bohemian knotweed (<i>Polygonum x bohemicum</i>)</p>	<p>Fruits, Seeds, Plant Fragments</p> <p>Primary means of spread in these species is by plant parts. Although all care should be given to preventing the dispersal of seed during control activities, the presence of seed doesn't materially influence disposal activities.</p>	<p>Small infestation</p> <ul style="list-style-type: none"> ▪ Bag all plant material and let rot. ▪ Never pile and use resulting material as compost. ▪ Burn. <p>Large infestation</p> <ul style="list-style-type: none"> ▪ Remove material to unsuitable habitat (dry, hot and sunny or dry and shaded location) and scatter or pile. ▪ Monitor and remove any sprouting material. ▪ Pile, let dry, and burn.




January 2010

UNH Cooperative Extension programs and policies are consistent with pertinent Federal and State laws and regulations, and prohibits discrimination in its programs, activities and employment on the basis of race, color, national origin, gender, religion, age, disability, political beliefs, sex, sexual orientation, or veteran's, marital or family status. College of Life Sciences and Agriculture, County Governments, NH Dept. of Resources and Economic Development, Division of Forests and Lands, NH Fish and Game ,and U.S. Dept. of Agriculture cooperating.

J:\JOBS\2\UN2200s\UN2270s\UN2271\2022 Site Plan\Plans & Specs\Site\2271.04 TURNING TEMPLATE 2022.dwg, 10/20/2022 1:58:45 PM, SHARP MX-3071 (0300380X00)

VEHICLE TURNING TEMPLATE

OWNER: EIGHTKPH, LLC
PROPERTY LOCATION: 88 MAPLEWOOD AVENUE
CITY OF PORTSMOUTH
COUNTY OF ROCKINGHAM
STATE OF NEW HAMPSHIRE



SCALE: 1"=20' 10/20/2022



AMBIT ENGINEERING, INC.
Civil Engineers & Land Surveyors

200 Griffin Road - Unit 3
Portsmouth, N.H. 03801-7114
Tel (603) 430-9282
Fax (603) 436-2315

OWNER/APPLICANT:

EIGHTKPH, LLC
233 VAUGHAN STREET, UNIT 301
PORTSMOUTH, N.H. 03801
Tel. (617) 901-7993

CIVIL ENGINEER & LAND SURVEYOR:

AMBIT ENGINEERING, INC.
200 GRIFFIN ROAD, UNIT 3
PORTSMOUTH, N.H. 03801
Tel. (603) 430-9282
Fax (603) 436-2315

ARCHITECT:

CJ ARCHITECTS
233 VAUGHAN STREET, SUITE 101
PORTSMOUTH, N.H. 03801
TEL. (603) 431-2808

LANDSCAPE ARCHITECT:
TERRA FIRMA LANDSCAPE ARCHITECTURE

163A COURT STREET
PORTSMOUTH, NH 03801
TEL. (603) 430-8388

TRAFFIC ENGINEER:
GORRILL PALMER

707 SABLE OAKS DRIVE, SUITE 30
SOUTH PORTLAND, ME 04106
TEL. (207) 772-2515

SITE DEVELOPMENT EIGHTKPH, LLC


88 MAPLEWOOD AVENUE (FORMERLY 161 DEER STREET) PORTSMOUTH, NEW HAMPSHIRE

PERMIT PLANS



PERMIT LIST:
NHDES SEWER DISCHARGE PERMIT:
PORTSMOUTH HDC:
PORTSMOUTH SITE PLAN:

LEGEND:

EXISTING	PROPOSED	
---	---	PROPERTY LINE
---	---	SETBACK
S	S	SEWER PIPE
SL	SL	SEWER LATERAL
G	G	GAS LINE
D	D	STORM DRAIN
W	W	WATER LINE
WS	WS	WATER SERVICE
UGE	UGE	UNDERGROUND ELECTRIC
OHW	OHW	OVERHEAD ELECTRIC/WIRES
---	---	FOUNDATION DRAIN
---	---	EDGE OF PAVEMENT (EP)
100	100	CONTOUR
97x3	98x0	SPOT ELEVATION
○	○	UTILITY POLE
⊙	⊙	WALL MOUNTED EXTERIOR LIGHTS
⊙	⊙	TRANSFORMER ON CONCRETE PAD
⊙	⊙	ELECTRIC HANDHOLD
⊙	⊙	SHUT OFFS (WATER/GAS)
⊙	⊙	GATE VALVE
⊙	⊙	HYDRANT
⊙	⊙	CATCH BASIN
⊙	⊙	SEWER MANHOLE
⊙	⊙	DRAIN MANHOLE
⊙	⊙	TELEPHONE MANHOLE
⊙	⊙	PARKING SPACE COUNT
⊙	⊙	PARKING METER
LSA	LSA	LANDSCAPED AREA
TBD	TBD	TO BE DETERMINED
CI	CI	CAST IRON PIPE
COP	COP	COPPER PIPE
DI	DI	DUCTILE IRON PIPE
PVC	PVC	POLYVINYL CHLORIDE PIPE
RCP	RCP	REINFORCED CONCRETE PIPE
AC	AC	ASBESTOS CEMENT PIPE
VC	VC	VITRIFIED CLAY PIPE
EP	EP	EDGE OF PAVEMENT
EL	EL	ELEVATION
FF	FF	FINISHED FLOOR
INV	INV	INVERT
S =	S =	SLOPE FT/FT
TBM	TBM	TEMPORARY BENCH MARK
TYP	TYP	TYPICAL



LOCUS MAP
SCALE: 1" = 1,000'



INDEX OF SHEETS

DWG. NO.	DESCRIPTION
-	SUBDIVISION PLAN
C1	EXISTING CONDITIONS PLAN
C2	DEMOLITION PLAN
C3	SITE PLAN
-	ARCHITECTURAL PLANS
-	LANDSCAPE PLANS
C4	PARKING LEVEL PLAN
C5	UTILITY PLAN
C6	GRADING PLAN
D1-D5	DETAILS

UTILITY CONTACTS

ELECTRIC:
EVERSOURCE
1700 LAFAYETTE ROAD
PORTSMOUTH, N.H. 03801
Tel. (603) 436-7708, Ext. 555.5678
ATTN: MICHAEL BUSBY, P.E. (MANAGER)

NATURAL GAS:
UNITIL
325 WEST ROAD
PORTSMOUTH, N.H. 03801
Tel. (603) 294-5144
ATTN: DAVE BEAULIEU

CABLE:
COMCAST
155 COMMERCE WAY
PORTSMOUTH, N.H. 03801
Tel. (603) 679-5695 (X1037)
ATTN: MIKE COLLINS

SEWER & WATER:
PORTSMOUTH DEPARTMENT OF PUBLIC WORKS
680 PEVERLY HILL ROAD
PORTSMOUTH, N.H. 03801
Tel. (603) 427-1530
ATTN: JIM TOW

COMMUNICATIONS:
CONSOLIDATED COMMUNICATIONS
JOE CONSIDINE
1575 GREENLAND ROAD
GREENLAND, N.H. 03840
Tel. (603) 427-5525

PORTSMOUTH APPROVAL CONDITIONS NOTE:
ALL CONDITIONS ON THIS PLAN SET SHALL REMAIN IN EFFECT IN PERPETUITY PURSUANT TO THE REQUIREMENTS OF THE CITY OF PORTSMOUTH SITE PLAN REVIEW REGULATIONS.

APPROVED BY THE PORTSMOUTH PLANNING BOARD


CHAIRMAN _____ DATE _____

**SITE PERMIT PLANS
SITE DEVELOPMENT
EIGHTKPH, LLC
88 MAPLEWOOD AVENUE
FORMERLY 161 DEER STREET
PORTSMOUTH, N.H.**

AMBIT ENGINEERING, INC.
Civil Engineers & Land Surveyors
200 Griffin Road - Unit 3
Portsmouth, N.H. 03801-7114
Tel (603) 430-9282
Fax (603) 436-2315

PLAN SET SUBMITTAL DATE: 20 OCTOBER 2022

C/H
L-CHIP
ROA338849



LOCATION MAP SCALE: 1" = 300'

LEGEND:

- N/F NOW OR FORMERLY
- RP RECORD OF PROBATE
- RCRD ROCKINGHAM COUNTY REGISTRY OF DEEDS
- MAP 11/LOT 21
- IR FND IRON ROD FOUND
- IP FND IRON PIPE FOUND
- IR SET IRON ROD SET
- DH FND DRILL HOLE FOUND
- DH SET DRILL HOLE SET
- NHND NHDOT BOUND FOUND
- BND w/DH BOUND WITH DRILL HOLE
- ST BND w/DH STONE BOUND WITH DRILL HOLE
- RR SPK RAILROAD SPIKE

138-62-1 ASSESSOR'S MAP 138 LOT 62-1

ASSESSOR'S MAP/LOT NUMBER ASSIGNMENT

LOT 1	138-62-1
LOT 2	125-17-1
LOT 3	125-17
LOT 4	125-17-2
LOT 5	125-17-3
LOT 6	138-62

ABUTTERS LIST

- | | | |
|--|--|---|
| <p>125 1
N/F HANOVER APARTMENTS, LLC
c/o CATHARTES PRIVATE INVESTMENTS
11 BEACON STREET, SUITE 1120
BOSTON, MA 02108
5387/2814</p> | <p>125 16
N/F JOHN W. GRAY REVOCABLE TRUST
BRADFORD A. GRAY REVOCABLE TRUST
7 PATRIOTS WAY
RYE, N.H. 03870
3895/643</p> | <p>138 61
N/F PETER HAPPNY
66 ROCK STREET
PORTSMOUTH, N.H. 03801
2302/1079
D-31107</p> |
| <p>125 2
N/F THIRTY MAPLEWOOD, LLC
117 BOW STREET
PORTSMOUTH, N.H. 03801
5099/2424</p> | <p>125 21
N/F NORTH END MASTER DEVELOPMENT L.P.
501 DANFORTH STREET
PORTLAND, ME 04102
5569/2553</p> | <p>138 62
N/F DEER STREET ASSOCIATES
P.O. BOX 100
YORK HARBOR, ME. 03911
5518/2744</p> |
| <p>125 3
N/F EMERSON HOVEY
POST 168 VWV
23R DEER STREET
PORTSMOUTH, N.H. 03801</p> | <p>125 28
N/F GOWEN G. EDWARD, JR.
REVOCABLE LIVING TRUST
COWEN G. EDWARD, JR., TRUSTEE
355 GREAT BAY ROAD
GREENLAND, N.H. 03840
4327/2531</p> | <p>138 63
N/F KEARSARGE MILL CONDOMINIUM ASSOCIATION
191 HILL STREET
PORTSMOUTH, N.H. 03801
2596/1585
D-14855</p> |
| <p>125 11
N/F 136 HILL STREET CONDOMINIUM ASSOCIATION
136 HILL STREET
PORTSMOUTH, N.H. 03801
4823/873
C-34853</p> | <p>138 60
N/F CITY OF PORTSMOUTH
P.O. BOX 628
PORTSMOUTH, N.H. 03802</p> | <p>138 64
N/F HANOVER PLACE CONDOMINIUM ASSOCIATION
349 HANOVER STREET
PORTSMOUTH, N.H. 03801
4807/18
D-33379</p> |
| <p>125 14
N/F HILL HANOVER GROUP, LLC
c/o JPK PROPERTIES, LLC
1 NEW HAMPSHIRE AVENUE, #125
PORTSMOUTH, N.H. 03801
4356/10</p> | | |

CURVE TABLE



CURVE	RADIUS	ARC LENGTH	CHORD LENGTH	CHORD BEARING	DELTA ANGLE
C1	486.00'	104.20'	104.00'	S35°55'41"E	12°17'05"
C2	37.00'	48.72'	45.28'	S07°58'11"W	75°26'43"
C3	155.00'	56.30'	55.99'	N53°24'20"E	20°48'43"
C4	86.00'	71.12'	69.11'	S04°30'52"E	47°22'49"
C5	86.00'	45.63'	45.10'	S13°00'13"E	30°24'08"
C6	86.00'	25.48'	25.39'	S10°41'12"W	16°58'41"

LENGTH TABLE

LINE	BEARING	DISTANCE
L1	N31°17'20"E	39.07'
L2	N31°26'32"E	17.92'
L3	N43°07'25"E	47.08'
L4	S46°46'25"E	7.69'
L5	S40°13'28"E	24.63'
L6	S47°00'33"W	38.74'
L7	N42°48'33"W	54.65'
L8	N43°03'00"W	46.10'
L9	S46°48'04"W	10.00'
L10	N46°09'30"W	48.26'
L11	N43°06'02"E	61.50'
L12	N30°51'54"E	56.64'
L13	N43°06'02"E	22.52'
L14	S46°53'58"E	38.87'
L15	N43°06'02"E	49.82'
L16	N63°48'43"E	28.42'
L17	N45°20'34"E	64.73'
L18	N28°12'12"E	10.82'
L19	N28°12'12"E	10.70'
L20	N55°38'43"W	57.54'
L21	N45°47'00"E	31.08'
L22	S87°48'09"E	20.15'
L23	N45°47'00"E	34.67'
L24	S40°13'28"E	20.31'
L25	S40°13'28"E	4.32'
L26	N39°12'52"E	42.20'
L27	S43°06'02"W	48.48'

PLAN REFERENCES:

- PLAN OF LAND FOR NETTY AND GERALD TAUBE, AUGUST 2004 BY MILLETTE, SPRAGUE & COLWELL, RCRD D-32051.
- CONDOMINIUM SITE PLAN FOR HANOVER PLACE CONDOMINIUM, 349 HANOVER STREET, PORTSMOUTH NH. BY MILLETTE, SPRAGUE AND COLWELL, INC. DATED 12/20/05. RCRD D-33379.
- KEARSARGE MILL CONDOMINIUMS, HANOVER STREET, PORTSMOUTH, NH. BY KIMBALL CHASE DATED 2/18/17. RCRD D-34716.
- BOUNDARY LINE AGREEMENT PLAN, KEARSARGE MILL CONDOMINIUMS, PORTSMOUTH, NH. BY JONES & BEACH ENGINEERS, INC. DATED 4/10/97. RCRD D-25421.
- KEARSARGE MILLS CONDOMINIUM PLANS FOR MAYFAIR REALTY TRUST, CAMBRIDGE PORT TRUST, PORTSMOUTH, NH. BY KIMBALL CHASE. RCRD D-14855.
- EASEMENT PLAN, TAX MAP 164 - LOT 4, BOSTON & MAINE CORPORATION TO THE CITY OF PORTSMOUTH OFF BREWSTER STREET, PORTSMOUTH, NH. BY AMBIT ENGINEERING, INC. DATED 4/19/03. RCRD D-37720.
- SUBDIVISION OF LAND OF PORTSMOUTH MFG. AND POWER CO., PORTSMOUTH, NH BY JOHN W. DURGIN DATED NOV. 1925. RCRD #0368.
- LAND IN PORTSMOUTH, NH PORTS. MFG. & POWER CO. TO HAROLD S. WOODS. BY JOHN W. DURGIN DATED NOV. 1926. RCRD #00389.
- TAX MAP 125 LOT 14 & MAP 138 LOT 62, PROPERTY OF HILL HANOVER GROUP, LLC, HILL, HANOVER & AUTUMN STREETS, PORTSMOUTH, NH. BY MSC, INC. DATED 10/10/2008. NOT RECORDED.
- PLAN OF LAND IN PORTSMOUTH, NH, PORTSMOUTH MFG. & POWER CO. TO FRANK E. BROOKS BY JOHN W. DURGIN DATED FEB. 1918. RCRD #078.
- CONDOMINIUM SITE PLAN, 136 HILL STREET CONDOMINIUM, PORTSMOUTH, NH, TAX MAP 125 LOT 11. BY ANDOVER CONSULTANTS, INC. DATED JULY 12, 2007. RCRD C-34853.
- LAND IN PORTSMOUTH, NH, BOSTON & MAINE RAILROAD TO ROGER E. MOULTON AND CHESTER GOODWIN, DATED MARCH 1950. RCRD 01684.
- PROPOSED PROPERTY TRANSFER, TAX MAP 125 - LOT 17, BOSTON & MAINE TO DEER STREET LIMITED PARTNERSHIP, 165 DEER STREET, PORTSMOUTH, NH BY AMBIT ENGINEERING, INC. DATED 6/13/13. RCRD D-37797.
- PLAN OF LAND FOR DEER STREET ASSOCIATES, DEER & BRIDGE STREETS AND MAPLEWOOD AVENUE, PORTSMOUTH AVENUE BY AMBIT SURVEY DATED SEPTEMBER 1993. RCRD D-22543.
- PROPOSED ROADWAY ALIGNMENT AND LAND TRANSFER PLAN, CITY OF PORTSMOUTH TO DEER STREET ASSOCIATES (TO BE RECORDED).



NOTES:

- PARCELS ARE SHOWN ON THE CITY OF PORTSMOUTH ASSESSOR'S MAPS AS MAP 125, LOT 17 & MAP 138, LOT 62.
- OWNERS OF RECORD:
MAP 125, LOT 17
DEER STREET ASSOCIATES
P.O. BOX 100
YORK HARBOR, ME 03911
3395/2669, 5534/2077, 5453/138
MAP 138, LOT 62
DEER STREET ASSOCIATES
P.O. BOX 100
YORK HARBOR, ME 03911
5518/2744
- PARCELS ARE NOT IN A FLOOD HAZARD ZONE AS SHOWN ON FIRM PANEL 33015C0259E. MAY 17, 2005.
- EXISTING LOT AREA:
LOT 17 109,987 S.F. 2.5250 ACRES
LOT 62 42,604 S.F. 0.9781 AC
PROPOSED LOT AREAS:
LOT 1 54,017 S.F. 1.2401 AC
LOT 2 8,519 S.F. 0.1956 AC
LOT 3 26,503 S.F. 0.6084 AC
LOT 4 18,347 S.F. 0.4212 AC
LOT 5 22,667 S.F. 0.5204 AC
LOT 6 22,538 S.F. 0.5174 AC
- ZONING DISTRICTS:
CENTRAL BUSINESS B (CBB), HISTORIC OVERLAY DISTRICT (PARTIAL), & OFFICE RESEARCH (OR)
- THE PURPOSE OF THIS PLAN IS TO SHOW THE CONSOLIDATION OF TAX MAP 125 LOT 17 AND TAX MAP 138 LOT 62 AND THE SUBDIVISION OF THAT LOT INTO 6 LOTS.
- LOT 2 TO BE A NON-BUILDABLE LOT UNTIL SUCH TIME AS FRONTAGE IS CREATED OR LOT 2 IS MERGED WITH AN ADJACENT PARCEL.
- THE EXISTING SITE IMPROVEMENTS SHALL BE ALLOWED TO REMAIN. AT SUCH TIME AS THE LOTS ARE NOT UNDER COMMON OWNERSHIP, EASEMENTS SHALL BE CREATED TO ALLOW THE BUILDINGS ACROSS BOUNDARY LINES TO REMAIN OR THE BUILDINGS SHALL BE REMOVED. ANY EASEMENTS CREATED SHALL BE REVIEWED AND APPROVED BY THE CITY OF PORTSMOUTH.
- FOR SITE EASEMENT RESTRICTIONS AND LOCATIONS SEE "PROPERTY EASEMENTS" PLAN DATED 12/15/14 BY AMBIT ENGINEERING.


NO.	DESCRIPTION	DATE
4	TAX MAP/LOT NUMBERS	5/18/16
3	ISSUED FOR RECORDING; MONUMENTS	3/24/16
2	REVISED LOTS 1, 2, AND 3	8/6/15
1	ISSUED FOR APPROVAL	7/31/15
0	ISSUED FOR COMMENT	7/28/15

CONSOLIDATION & SUBDIVISION
PLAN
TAX MAP 125, LOT 17
&
TAX MAP 138, LOT 62
DEER STREET ASSOCIATES
BRIDGE, DEER, & HILL STREETS
CITY OF PORTSMOUTH
COUNTY OF ROCKINGHAM
STATE OF NEW HAMPSHIRE


DIMENSIONAL REQUIREMENTS:
ZONE CBB
MIN. LOT AREA: 2,000 S.F.
FRONTAGE: NO REQUIRED DISTANCE
SETBACKS:
FRONT: 0 FEET
SIDE: 0 FEET
REAR: 0 FEET
MAXIMUM STRUCTURE HEIGHT: 45' OR 3.5 STORIES, WHICHEVER IS LESS
MAXIMUM BUILDING COVERAGE: 95%
MINIMUM OPEN SPACE: 0%
ZONE OR
DUE TO THE PROXIMITY TO NORTH MILL POND, ZONE REQUIREMENTS ARE A MIX OF OFFICE RESEARCH & INDUSTRIAL ZONES. REFER TO ZONING ORDINANCE FOR DIMENSIONS.

APPROVED BY THE PORTSMOUTH PLANNING BOARD

CHAIRMAN 9/7/16
DATE



D-39699



LOCATION MAP

SCALE: 1" = 300'

SEWER STRUCTURE TABLE


STRUCTURE	RIM ELEV.	INV. ELEV. IN	INV. ELEV. OUT	PIPE SIZE & TYPE
1499	15.80	-1.80	-1.80	48" BRICK BOX
1501	13.58	-0.30	-0.32	24" (NNE)
2305	10.90	-1.17	-1.17	48" VC

PLAN REFERENCES:

- 1) CONSOLIDATION & SUBDIVISION PLAN TAX MAP 125, LOT 17 & TAX MAP 138, LOT 62 DEER STREET ASSOCIATES, BRIDGE, DEER, AND HILL STREETS. PREPARED BY AMBIT ENGINEERING, INC. DATED JULY 2015. SCALE: 1"=50'. RCRD D-39699.
- 2) PLAN OF RESTRICTIVE COVENANT TAX MAP 164, LOT 4 BOSTON AND MAINE CORPORATION TO DEER STREET ASSOCIATES. PREPARED BY AMBIT ENGINEERING, INC. DATED DECEMBER 2016. SCALE: 1"=50'.
- 3) EASEMENT PLAN TAX MAP 125- LOT 17, FOR FOUNDRY PLACE, LLC. PREPARED BY AMBIT ENGINEERING, INC. DATED NOVEMBER 2018. LATEST REVISION #3 DATED 4/16/20. SCALE: 1" = 20'.

TBM 4
CHISELED SQUARE
IN NE CORNER OF
TRANSFORMER PAD
EL.=14.77



TBM 5
CHISELED SQUARE
IN NE QUADRANT
OF MAST BASE
EL.=15.20



LEGEND (SEE COVER SHEET)

DRAIN STRUCTURE TABLE

STRUCTURE	RIM ELEV.	INV. ELEV. IN	INV. ELEV. OUT	PIPE SIZE & TYPE
CB 3522	10.12	7.52±	-	12" RCP (NE)
CB 3523	9.52	6.32	-	12" (NW)
DMH 3540	10.81	NA	-	18" RCP (NE) 36" (SW)
DMH 3541	10.26	1.56	-	48" RCP (NW)
		7.52±	2.10	12" RCP (SW) 12" RCP (SE) 36" (S)
		1.96	-	36" (NE)
DMH 8159	15.96	12.36	11.81	12" RCP (NNE)
		8.78	5.06	18" CPP (ESE)
		5.06	-	12" RCP (NW)
		4.96	-	18" RCP (SW)
DMH 8160	13.50	9.5	8.6	12" PVC (NNE)
		8.6	5.5	12" RCP (NNW)
		5.5	-	12" RCP (W)
		5.55	-	12" RCP (SE)
DMH 8161	13.20	9.75	5.72	12" RCP (WSW)
		5.68	-	12" RCP (NW)
		5.68	-	12" RCP (ENE)
CB 8167	13.45	-	-	-
		8.95	-	12" RCP (SSE)
CB 8168	13.19	-	-	-
		9.83±	-	12" RCP (ENE)
CB 12480	15.46	-	-	-
		11.11	-	18" CPP (WNW)



AMBIT ENGINEERING, INC.
Civil Engineers & Land Surveyors
200 Griffin Road - Unit 3
Portsmouth, N.H. 03801-7114
Tel (603) 430-9282
Fax (603) 436-2315

- NOTES:**
- 1) PARCEL IS SHOWN ON THE CITY OF PORTSMOUTH ASSESSORS MAP 125 AS LOT 17-3.
 - 2) OWNER OF RECORD:
EIGHTKPH, LLC
233 VAUGHAN STREET
UNIT 301
PORTSMOUTH, NH 03801
6348/2213
 - 3) PARCEL IS LOCATED IN CHARACTER DISTRICT 5 ZONE; DOWNTOWN OVERLAY, NORTH END INCENTIVE OVERLAY & HISTORIC DISTRICTS.
 - 4) DIMENSIONAL REQUIREMENTS (ALSO SEE ORDINANCE):
CHARACTER DISTRICT 5:
MIN. LOT AREA: NO REQUIREMENT
FRONTAGE: NO REQUIREMENT
SETBACKS:
FRONT (MAX.): 5 FEET (PRIMARY)
FRONT (MAX.): 5 FEET (SECONDARY)
SIDE: NO REQUIREMENT
REAR: GREATER OF 5 FEET FROM REAR LOT LINE OR 10 FEET FROM CENTER OF ALLEY

MAXIMUM STRUCTURE HEIGHT: SEE CITY PLAN
MAXIMUM STRUCTURE COVERAGE: 90%
MAXIMUM BUILDING FOOTPRINT: 20,000 S.F.
MINIMUM OPEN SPACE: 5%
MINIMUM FRONT LOT LINE BUILDOUT: 80%
 - 5) LOT AREA: 22,667 S.F.
0.5204 ACRES
 - 6) PARCEL IS NOT IN A SPECIAL FLOOD HAZARD AREA AS SHOWN ON FIRM PANEL 33015C0259F, EFFECTIVE JANUARY 29, 2021
 - 7) THE PURPOSE OF THIS PLAN IS TO SHOW THE EXISTING CONDITIONS ON TAX MAP 125, LOT 17-3 IN PORTSMOUTH, NH.
 - 8) VERTICAL DATUM IS NAVD83. BASIS OF VERTICAL DATUM IS REDUNDANT RTN GNSS OBS.
 - 9) PARCEL MAY BE SUBJECT TO TEMPORARY CONSTRUCTION EASEMENTS AS SHOWN ON RCRD D-42091 SHEET 2.
 - 10) PARCEL IS SUBJECT TO AGREEMENT REGARDING RELOCATION OF UNDERGROUND FACILITIES 5751/1504.

**SITE DEVELOPMENT
EIGHTKPH, LLC
88 MAPLEWOOD AVENUE
PORTSMOUTH, N.H.**

NO.	DESCRIPTION	DATE
1	SEWER CONNECTION	10/20/22
0	ISSUED FOR COMMENT	8/23/22

REVISIONS

N/F
PORTWALK HI, LLC
C/O CATHARTES PRIVATE INVESTMENTS
6 LIBERTY SQUARE PMB 90767
BOSTON, MA 02109
5387/2820




SCALE: 1" = 20' AUGUST 2022

**EXISTING CONDITIONS
PLAN**

C1

DEMOLITION NOTES


- A) THE LOCATIONS OF UNDERGROUND UTILITIES ARE APPROXIMATE AND THE LOCATIONS ARE NOT GUARANTEED BY THE OWNER OR THE DESIGNER. IT IS THE CONTRACTORS' RESPONSIBILITY TO LOCATE UTILITIES AND ANTICIPATE CONFLICTS. CONTRACTOR SHALL REPAIR EXISTING UTILITIES DAMAGED BY THEIR WORK AND RELOCATE EXISTING UTILITIES THAT ARE REQUIRED TO BE RELOCATED PRIOR TO COMMENCING ANY WORK IN THE IMPACTED AREA OF THE PROJECT.
- B) ALL MATERIALS SCHEDULED TO BE REMOVED SHALL BECOME THE PROPERTY OF THE CONTRACTORS UNLESS OTHERWISE SPECIFIED. THE CONTRACTOR SHALL DISPOSE OF ALL MATERIALS OFF-SITE IN ACCORDANCE WITH ALL FEDERAL, STATE, AND LOCAL REGULATIONS, ORDINANCES AND CODES. THE CONTRACTOR SHALL COORDINATE REMOVAL, RELOCATION, DISPOSAL, OR SALVAGE OF UTILITIES WITH THE OWNER AND APPROPRIATE UTILITY COMPANY.
- C) ANY EXISTING WORK OR PROPERTY DAMAGED OR DISRUPTED BY CONSTRUCTION/ DEMOLITION ACTIVITIES SHALL BE REPLACED OR REPAIRED TO THE ORIGINAL EXISTING CONDITIONS BY THE CONTRACTOR AT NO ADDITIONAL COST TO THE OWNER.
- D) THE CONTRACTOR SHALL VERIFY LOCATION OF ALL EXISTING UTILITIES AND CALL DIG SAFE AT LEAST 72 HOURS PRIOR TO THE COMMENCEMENT OF ANY DEMOLITION/CONSTRUCTION ACTIVITIES.
- E) SAWCUT AND REMOVE PAVEMENT ONE FOOT OFF PROPOSED EDGE OF PAVEMENT TRENCH IN AREAS WHERE PAVEMENT IS TO BE REMOVED.
- F) IT IS THE CONTRACTOR'S RESPONSIBILITY TO FAMILIARIZE THEMSELVES WITH THE CONDITIONS OF ALL THE PERMIT APPROVALS.
- G) THE CONTRACTOR SHALL OBTAIN AND PAY FOR ADDITIONAL CONSTRUCTION PERMITS, NOTICES AND FEES NECESSARY TO COMPLETE THE WORK AND ARRANGE FOR AND PAY FOR ANY INSPECTIONS AND APPROVALS FROM THE AUTHORITIES HAVING JURISDICTION. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ANY ADDITIONAL AND OFF-SITE DISPOSAL OF MATERIALS REQUIRED TO COMPLETE THE WORK.
- H) THE CONTRACTOR SHALL REMOVE AND DISPOSE OF ALL EXISTING STRUCTURES, CONCRETE, UTILITIES, VEGETATION, PAVEMENT, AND CONTAMINATED SOIL WITHIN THE WORK LIMITS SHOWN UNLESS SPECIFICALLY IDENTIFIED TO REMAIN. ANY EXISTING DOMESTIC / IRRIGATION SERVICE WELLS IN THE PROJECT AREA IDENTIFIED DURING THE CONSTRUCTION AND NOT CALLED OUT ON THE PLANS SHALL BE BROUGHT TO THE ATTENTION OF THE OWNER AND ENGINEER FOR PROPER CAPPING / RE-USE.
- I) ALL WORK WITHIN THE CITY OF PORTSMOUTH RIGHT OF WAY SHALL BE COORDINATED WITH THE CITY OF PORTSMOUTH DEPARTMENT OF PUBLIC WORKS (DPW).
- J) REMOVE TREES AND BRUSH AS REQUIRED FOR COMPLETION OF WORK. CONTRACTOR SHALL GRUB AND REMOVE ALL SLUMPS WITHIN LIMITS OF WORK AND DISPOSE OF OFF-SITE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL LAWS AND REGULATIONS.
- K) CONTRACTOR SHALL PROTECT ALL PROPERTY MONUMENTATION THROUGHOUT DEMOLITION AND CONSTRUCTION OPERATIONS. SHOULD ANY MONUMENTATION BE DISTURBED, THE CONTRACTOR SHALL EMPLOY A NH LICENSED LAND SURVEYOR TO REPLACE THEM.
- L) PROVIDE INLET PROTECTION BARRIERS AT ALL CATCH BASINS WITHIN CONSTRUCTION LIMITS AND MAINTAIN FOR THE DURATION OF THE PROJECT. INLET PROTECTION BARRIERS SHALL BE HIGH FLOW SILT SACK BY ACF ENVIRONMENTAL OR APPROVED EQUAL. INSPECT BARRIERS WEEKLY AND AFTER EACH RAIN OF 0.25 INCHES OR GREATER. CONTRACTOR SHALL COMPLETE A MAINTENANCE INSPECTION REPORT AFTER EACH INSPECTION. SEDIMENT DEPOSITS SHALL BE REMOVED AFTER EACH STORM EVENT OR MORE OFTEN IF WARRANTED OR FABRIC BECOMES CLOGGED. EROSION CONTROL MEASURES SHALL BE INSTALLED PRIOR TO THE START OF ANY CLEARING OR DEMOLITION ACTIVITIES.
- M) THE CONTRACTOR SHALL PAY ALL COSTS NECESSARY FOR TEMPORARY PARTITIONING, BARRICADING, FENCING, SECURITY AND SAFELY DEVICES REQUIRED FOR THE MAINTENANCE OF A CLEAN AND SAFE CONSTRUCTION SITE.
- N) ANY CONTAMINATED MATERIAL REMOVED DURING THE COURSE OF THE WORK WILL REQUIRE HANDLING IN ACCORDANCE WITH NHDES REGULATIONS. CONTRACTOR SHALL HAVE A HEALTH AND SAFETY PLAN IN PLACE, AND COMPLY WITH ALL APPLICABLE PERMITS, APPROVALS, AUTHORIZATIONS, AND REGULATIONS



- NOTES:**
- 1) THE CONTRACTOR SHALL NOTIFY DIG SAFE AT 1-888-DIG-SAFE (1-888-344-7233) AT LEAST 72 HOURS PRIOR TO COMMENCING ANY EXCAVATION ON PUBLIC OR PRIVATE PROPERTY WITHIN 100 FEET OF UNDERGROUND UTILITIES. THE EXCAVATOR IS RESPONSIBLE TO MAINTAIN MARKS. DIG SAFE TICKETS EXPIRE IN THIRTY DAYS.
 - 2) UNDERGROUND UTILITY LOCATIONS ARE BASED UPON BEST AVAILABLE EVIDENCE AND ARE NOT FIELD VERIFIED. LOCATING AND PROTECTING ANY ABOVEGROUND OR UNDERGROUND UTILITIES IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR AND/OR THE OWNER. UTILITY CONFLICTS SHOULD BE REPORTED AT ONCE TO THE DESIGN ENGINEER.
 - 3) CONTRACTOR SHALL INSTALL AND MAINTAIN EROSION CONTROL MEASURES IN ACCORDANCE WITH THE "NEW HAMPSHIRE STORMWATER MANUAL, VOLUME 3, EROSION AND SEDIMENT CONTROLS DURING CONSTRUCTION. (NHDES DECEMBER 2008).
 - 4) CITY STREET LIGHTING CIRCUIT TO BE REVIEWED PRIOR TO CONSTRUCTION AND REPLACEMENT POWER SOURCE IDENTIFIED.


**SITE DEVELOPMENT
 EIGHTKPH, LLC
 88 MAPLEWOOD AVENUE
 PORTSMOUTH, N.H.**

1	SEWER CONNECTION	10/22/20
0	ISSUED FOR COMMENT	8/23/22
NO.	DESCRIPTION	DATE
REVISIONS		



SCALE: 1" = 20' AUGUST 2022

**DEMOLITION
 PLAN C2**



LOCATION MAP

SCALE: 1" = 300'

PLAN REFERENCES:

- 1) CONSOLIDATION & SUBDIVISION PLAN TAX MAP 125, LOT 17 & TAX MAP 138, LOT 62 DEER STREET ASSOCIATES, BRIDGE, DEER, AND HILL STREETS. PREPARED BY AMBIT ENGINEERING, INC. DATED JULY 2015. SCALE: 1"=50'. RCRD D-39699.
- 2) PLAN OF RESTRICTIVE COVENANT TAX MAP 164, LOT 4 BOSTON AND MAINE CORPORATION TO DEER STREET ASSOCIATES. PREPARED BY AMBIT ENGINEERING, INC. DATED DECEMBER 2016. SCALE: 1"=50'.
- 3) EASEMENT PLAN TAX MAP 125- LOT 17, FOR FOUNDRY PLACE, LLC. PREPARED BY AMBIT ENGINEERING, INC. DATED NOVEMBER 2018. LATEST REVISION #3 DATED 4/16/20. SCALE: 1" = 20'.

COMMUNITY SPACE:

- TOTAL LOT AREA: 22,667 S.F.
- PROPOSED COMMUNITY SPACE: 4,714 S.F. (20.8%)
 - 12' WIDE PEDESTRIAN SIDEWALK: 1,563 S.F.
 - POCKET PARK: 3,151 S.F.

GFA

Basement	17,189 SF
First Floor	17,189 SF
Second Floor	17,189 SF
Third Floor	17,189 SF
Fourth Floor	17,189 SF
Penthouse	7,344 SF

BUILDING DATA:

PROPOSED BUILDING: 17,093 S.F. FOOTPRINT


HEIGHT DATA:

LOT	REQUIRED HEIGHT & STORIES	PROPOSED HEIGHT & STORIES
17-3	4 STORIES AND PENTHOUSE	*62'

*SEE COMMUNITY SPACE

IMPERVIOUS SURFACE AREAS (TO PROPERTY LINE)

STRUCTURE	EXISTING IMPERVIOUS (S.F.)	PROPOSED IMPERVIOUS (S.F.)
MAIN STRUCTURE	7281	17093
SIDEWALKS	0	3,332
PAVEMENT	9465	0
CONCRETE	98	216
RETAINING WALL	0	193
CURBING	123	56
STEPS	0	6
TOTAL	16,967	20,896
LOT SIZE	22,667	22,667
% LOT COVERAGE	74.9%	92.2%



AMBIT ENGINEERING, INC.
Civil Engineers & Land Surveyors
200 Griffin Road - Unit 3
Portsmouth, N.H. 03801-7114
Tel (603) 430-9282
Fax (603) 436-2315

- NOTES:**
- 1) PARCEL IS SHOWN ON THE CITY OF PORTSMOUTH ASSESSORS MAP 125 AS LOT 17-3.
 - 2) OWNER OF RECORD: EIGHTKPH, LLC, 233 VAUGHAN STREET, UNIT 301, PORTSMOUTH, NH 03801, 6348/2213
 - 3) PARCEL IS LOCATED IN CHARACTER DISTRICT 5 ZONE; DOWNTOWN OVERLAY, NORTH END INCENTIVE OVERLAY & HISTORIC DISTRICTS.
 - 4) DIMENSIONAL REQUIREMENTS: SEE ZONING TABLE.
 - 5) LOT AREA: 22,667 S.F. 0.5204 ACRES
 - 6) PARCEL IS NOT IN A SPECIAL FLOOD HAZARD AREA AS SHOWN ON FIRM PANEL 33015C0259F, EFFECTIVE JANUARY 29, 2021
 - 7) THE PURPOSE OF THIS PLAN IS TO SHOW THE PROPOSED DEVELOPMENT ON TAX MAP 125, LOT 17-3 IN PORTSMOUTH, NH. PROPOSED USE: FIRST FLOOR COMMERCIAL AND 19 RESIDENTIAL UNITS ON UPPER FLOORS.
 - 8) VERTICAL DATUM IS NAVD88. BASIS OF VERTICAL DATUM IS REDUNDANT RTN GNSS OBS.
 - 9) PARCEL IS BENEFITTED BY A RESTRICTIVE COVENANT (NO BUILD EASEMENT) ON THE ADJACENT BOSTON AND MAINE PROPERTY.
 - 10) REQUIRED PARKING: 125-17-2 COMMERCIAL BANKING: 4,500 S.F. 4,500 S.F. X 1/400 S.F. = 12 SPACES REQUIRED 12 SPACES PROVIDED 125-17-3 FIRST FLOOR: EXEMPT 19 DWELLING UNITS: 1.3/UNIT X 19 UNITS = 25 VISITOR: 19/5 X 1 = 4 29 SPACES REQUIRED 29 SPACES PROVIDED
 - 11) ALL WORK IN THE CITY R.O.W. SHALL MEET CITY STANDARDS. CITY WILL NEED TO REVIEW AND APPROVE FINAL DETAILS AND CUT SHEETS. CONSTRUCTION INSPECTION WILL BE REQUIRED.

ZONING DEVELOPMENT STANDARD

CD5: CHARACTER DISTRICT 5

BUILDING PLACEMENT (PRINCIPAL):

	REQUIRED	EXISTING	PROPOSED
MAX. PRINCIPLE FRONT YARD:	5 FEET	15'	5.0'
MAX. SECONDARY FRONT YARD:	5 FEET	24'	5.7'
MIN. SIDE YARD:	NR	29'	4.0'
MIN. REAR YARD:	5 FEET	42'	15.2'
FRONT LOT LINE BUILDOUT:	80% MIN	75%	83%
ABUT RAILROAD:	15'	42'	15.2'

BUILDING TYPES:

PERMITTED BUILDING TYPES: LIVE/WORK BUILDING*, SMALL COMMERCIAL BUILDING, LARGE COMMERCIAL BUILDING, MIXED-USE BUILDING*, FLEX SPACE BUILDING, COMMUNITY BUILDING PROPOSED: MIXED-USE BUILDING
*RESIDENTIAL USES ARE NOT PERMITTED ON THE GROUND FLOOR IN THE DOWNTOWN OVERLAY DISTRICT.

PERMITTED FACADE TYPES: STOOP, STEP, SHOPFRONT, OFFICEFRONT, RECESSED ENTRY, GALLERY, ARCADE

BUILDING FORM:


	REQUIRED	EXISTING	PROPOSED
MAX STRUCTURE HEIGHT:	62* FEET	<35'	62'
MAX. FINISHED FLOOR SURFACE OF GROUND FLOOR ABOVE SIDEWALK GRADE:	36 INCHES	4"	18"
MIN. GROUND STORY HEIGHT:	12 FEET	-	17'
MIN. SECOND STORY HEIGHT:	10 FEET	-	11.5'
FACADE GLAZING (WINDOW/PERIMETER):	70% SHOP 20-50% OTHER	-	COMPLIES

ROOF TYPE ALLOWED: FLAT, GABLE, HIP

LOT OCCUPATION:

	REQUIRED	EXISTING	PROPOSED
MAX BUILDING BLOCK:	225 FEET	120'	180'
MAX FACADE MOD. LENGTH:	100 FEET	120'	60'
MIN. ENTRANCE SPACING:	50 FEET	40'+/-	50'
MAX BUILDING COVERAGE:	90%	32%	75.4%
MAX BUILDING FOOTPRINT:	20,000 SF	7,281 S.F.	17,093 S.F.
MIN. LOT AREA:	NR	22,667 S.F.	22,667 S.F.
MIN. LOT AREA/DWELLING (LOT AREA/# OF UNITS):	NR	-	-
MIN. OPEN SPACE :	5%	68%	24.6%

*WITH COMMUNITY SPACE AND PENTHOUSE



THIS SITE SHALL BE RECORDED IN THE ROCKINGHAM COUNTY REGISTRY OF DEEDS.

ALL IMPROVEMENTS SHOWN ON THIS SITE PLAN SHALL BE CONSTRUCTED AND MAINTAINED IN ACCORDANCE WITH THE PLAN BY THE PROPERTY OWNER AND ALL FUTURE PROPERTY OWNERS. NO CHANGES SHALL BE MADE ON THIS SITE PLAN WITHOUT THE EXPRESS APPROVAL OF THE PORTSMOUTH PLANNING DIRECTOR.

APPROVED BY THE PORTSMOUTH PLANNING BOARD

CHAIRMAN _____ DATE _____

SITE DEVELOPMENT EIGHTKPH, LLC 88 MAPLEWOOD AVENUE PORTSMOUTH, N.H.

NO.	DESCRIPTION	DATE
2	DRIVEWAY LOCATION, BUILDING FOOTPRINT	10/20/22
1	LOADING AREA, NOTE 11	9/6/22
0	ISSUED FOR COMMENT	8/23/22

REVISIONS

SCALE: 1" = 20' AUGUST 2022

SITE PLAN **C3**



REVISIONS:

EIGHT KPH, LLC
88 MAPLEWOOD AVENUE
PORTSMOUTH, NEW HAMPSHIRE




ARCHITECTS
233 VAUGHAN STREET
SUITE 101
PORTSMOUTH, NH 03801
(603) 431-2808
www.cjarchitects.net


DATE:	09/06/2022
DRAWN BY:	SRT
APPROVED BY:	CJG
SCALE:	
JOB NUMBER:	2201

A1


NOT FOR CONSTRUCTION




1 LOWER LEVEL PLAN
1" = 20'




4 PENTHOUSE LEVEL PLAN
1" = 20'



3 SECOND, THIRD, AND FOURTH LEVEL PLAN
1" = 20'



2 FIRST LEVEL PLAN
1" = 20'



5 ROOF PLAN
1" = 20'

NOT FOR CONSTRUCTION

REVISIONS:

EIGHT KPH, LLC
88 MAPLEWOOD AVENUE
PORTSMOUTH, NEW HAMPSHIRE



ARCHITECTS
233 VAUGHAN STREET
SUITE 101
PORTSMOUTH, NH 03801
(603) 431-2808
www.cjarchitects.net

PLANS
DATE: 10/20/2022
DRAWN BY: SRT
APPROVED BY: CJG
SCALE: 1" = 20'
JOB NUMBER: 2201

A2



1 DEER STREET ELEVATION
1" = 10'



2 MAPLEWOOD AVENUE ELEVATION
1" = 10'



3 RAILROAD ELEVATION
1" = 10'



4 SIDE ELEVATION
1" = 10'

REVISIONS:

EIGHT KPH, LLC
88 MAPLEWOOD AVENUE
PORTSMOUTH, NEW HAMPSHIRE



ARCHITECTS
233 VAUGHAN STREET
SUITE 101
PORTSMOUTH, NH 03801
(603) 431-2808
www.cjarchitects.net



ELEVATIONS

DATE: 10/20/2022
DRAWN BY: SRT
APPROVED BY: CJG
SCALE:
JOB NUMBER: 2201

A3

NOT FOR CONSTRUCTION

BOSTON & MAINE RAILROAD



METAL SCREEN FENCE W/ HISTORICAL THEME
 TRANSFORMERS ON CONCRETE PADS (TYP.)
 3/4" CRUSHED STONE

PROPOSED RETAINING WALL
 PROPOSED ALUMINUM FENCE ON TOP OF WALL
 OUTLET CONTROL BASIN

4' BENCH (TYP.)
 6' BENCH (TYP.)
 10' BENCH (TYP.)

BOLLARD LIGHT (TYP.)
 GRANITE PAVING (TYP.)
 12" W. CRUSHED STONE (TYP.)
 5' BRICK SIDEWALK

3' W. ARCHITECTURAL AWNING (CONTINUOUS)

NATIVE GROUNDCOVER ON R-TANK SYSTEM
 4' W. BRICK SIDEWALK
 (4) BIKE RACKS ON CONCRETE PAD

4' WIDE x 50'+/- LENGTH
 CONTINUOUS TREE GRATE

COLUMNAR TREE
 W/ TREE GUARD

PLANTED URNS TO RECEIVE DRIP
 WATER FROM BALCONIES (TYP.)

PROPOSED 4 STORY
 WITH A PENTHOUSE
 BUILDING 17,093 S.F.

125/17-3

PROPOSED DOOR (TYP.)

PROPOSED BRICK
 SIDEWALK (TYP.)

PROPOSED DOOR (TYP.)
 PROPOSED STEP

COLUMNAR TREE
 W/ TREE GUARD

BACKLESS BENCH


STREET LAMPS (TYP.)

DEER STREET

8" SPACE BETWEEN GRATE AND CURB
 CONTINUOUS GRATE W/ 3 TREES (TYP.)

MAPLEWOOD AVE.



"DOWNTOWN"
 "STRAWBERRY BANKE"
 FOUNDRY GARAGE




terra firma
 landscape architecture
 163.a Court Street - Portsmouth, NH 03801
 office: 603.430.8368 | terrace@terrafirmalandscape.com

Project Title		8 KPH		LANDSCAPE PLAN	
Design Firm	terra firma landscape architecture 163.a Court Street Portsmouth, NH	Project ID	8 KPH	Project Name	88MAPLEWOOD
Scale	1"=10'-0"	Revision	Revision	Project No.	00/00/00
Sheet No.	L-1	Project ID	8 KPH	Project Name	88MAPLEWOOD
THIS SHEET IS SCALED FOR 22x34 PAPER, DO NOT ENLARGE OR REDUCE.		Revision	8 KPH	Project No.	00/00/00
		Checked By	TP	Date	10/20/2022
		Reviewed By	TP	Issue Notes	TAC SUBMISSION ENTRY + DETAIL UPDATES
		Submitted By	TP	No.	A
		Project Manager	TP	Date	10/28/2022

BOSTON & MAINE RAILROAD



terra firma
landscape architecture
163.a court street - portsmouth, nh 03801
office: 603.430.9368 | terrace@terrafirmalandscape.com



SEED: CLOVER, TREFOIL, ANDROPOGON


PROPOSED 4 STORY
WITH A PENTHOUSE
BUILDING 17,093 S.F.

125/17-3


ID	Qty	Botanical Name	Common Name	Scheduled Size
AOS	25	Aster oblongifolius 'October Skies'	Aromatic Aster	2 QT
ARB	3	Acer rubrum 'Bowhall'	Bowhall Maple	3 1/2" Cal.
CFF	11	Carpinus betulus 'Frans Fontaine'	Frans Fontaine Hornbeam	2 1/2" Cal.
CP	31	Comptonia peregrina	Sweet Fern	2 QT
ERA	89	Eragrostis spectabilis	Purple Lovegrass	2 QT
HYP	30	Hypericum 'Hidcote'	St. Johnswort	5 Gal.
PVS	50	Panicum virgatum 'Shenandoah'	Shenandoah Switch Grass	2 Gal.
QGP	4	Quercus p. 'Green Pillar'	Green Pillar Oak	2-2 1/2"
SSB	269	Schizachyrium scoparium 'The Blues'	The Blues Little Bluestem	2 QT

THIS SHEET IS SCALED FOR 22x34 PAPER, DO NOT ENLARGE OR REDUCE.


Design Firm	terra firma landscape architecture 163.a Court Street Portsmouth, NH	Project File	8 KPH	Scale	1"=10'-0"	Sheet No.	L-2 of 1
Designed By	TP	Checked By	TP	Project ID	8 KPH	Date	10/20/2022
Drawn By	TC	Reviewed By	TP	Drawing Code	88MAPLEWOOD	No.	A
Reviewed By	TP	Submitted By	TP	CAD File Name	88MAPLEWOOD	Issue Notes	TAC SUBMISSION
Project Manager	TP	Plot Date	00/00/00				ENTRY + DETAIL UPDATES




1
L-3
TREE PLANTING - 2"+ CAL.
SCALE: NTS




2
L-3
PYRAMIDAL EVERGREEN TREE PLANTING
SCALE: NTS



3
L-3
SHRUB/GROUND COVER PLANTING DETAIL
SCALE: NTS



4
L-3
B&B SHRUB PLANTING
SCALE: NTS



5
L-3
GROUND COVER SPACING DETAIL
SCALE: NTS

LANDSCAPE NOTES:

1. THE CONTRACTOR SHALL LOCATE AND VERIFY THE EXISTENCE OF ALL UTILITIES PRIOR TO STARTING WORK.
2. THE CONTRACTOR SHALL SUPPLY ALL PLANT MATERIALS IN QUANTITIES SUFFICIENT TO COMPLETE THE PLANTINGS SHOWN ON THE DRAWINGS.
3. ALL MATERIAL SHALL CONFORM TO THE GUIDELINES ESTABLISHED BY THE CURRENT AMERICAN STANDARD FOR NURSERY STOCK PUBLISHED BY THE AMERICAN ASSOCIATION OF NURSERYMEN.
4. ALL PLANT SUBSTITUTIONS MUST BE APPROVED BY THE LANDSCAPE ARCHITECT.
5. ALL PLANT MATERIALS SHALL BE EXACTLY AS SPECIFIED BY THE LANDSCAPE ARCHITECT. IF PLANT SPECIES CULTIVARS ARE FOUND TO VARY FROM THAT SPECIFIED AT ANY TIME DURING THE GUARANTEE PERIOD, THE LANDSCAPE ARCHITECT RESERVES THE RIGHT TO HAVE THE CONTRACTOR REPLACE THAT PLANT MATERIAL. THE LANDSCAPE ARCHITECT RESERVES THE RIGHT TO REJECT ANY PLANT DELIVERED TO THE SITE FOR AESTHETIC REASONS BEFORE PLANTING. THE LANDSCAPE CONTRACTOR IS RESPONSIBLE FOR THE QUALITY FOR ALL THE PLANTS.
6. PLANTS SHALL BE SUBJECT TO INSPECTION AND APPROVAL AT THE PLACE OF GROWTH, UPON DELIVERY OR AT THE JOB SITE WHILE WORK IS ON-GOING TO CONFORMITY TO SPECIFIED QUALITY, SIZE AND VARIETY.
7. PLANTS FURNISHED IN CONTAINERS SHALL HAVE THE ROOTS WELL ESTABLISHED IN THE SOIL MASS AND SHALL HAVE AT LEAST ONE (1) GROWING SEASON. ROOT-BOUND PLANTS OR INADEQUATELY SIZED CONTAINERS TO SUPPORT THE PLANT MAY BE DEEMED UNACCEPTABLE.
8. NO PLANT SHALL BE PUT IN THE GROUND BEFORE GRADING HAS BEEN FINISHED AND APPROVED BY THE LANDSCAPE ARCHITECT.
9. ALL PLANTS SHALL BE INSTALLED AND DETAILED PER PROJECT SPECIFICATIONS.
10. ALL PLANTS SHALL BE WATERED THOROUGHLY TWICE DURING THE FIRST 24-HOUR PERIOD AFTER PLANTING. ALL PLANTS SHALL BE WATERED WEEKLY, OR MORE OFTEN IF NECESSARY, DURING THE FIRST TWO GROWING SEASONS.
11. ALL PLANTS SHALL BE GUARANTEED BY THE CONTRACTOR FOR NOT LESS THAN ONE FULL YEAR FROM THE TIME OF PROVISIONAL ACCEPTANCE. DURING THIS TIME, THE OWNER SHALL MAINTAIN ALL PLANT MATERIALS IN THE ABOVE MANNER. IT IS THE CONTRACTOR'S RESPONSIBILITY TO INSPECT THE PLANTS TO ENSURE PROPER CARE. IF THE CONTRACTOR IS DISSATISFIED WITH THE CARE GIVEN, HE SHALL IMMEDIATELY, AND IN SUFFICIENT TIME TO PERMIT THE CONDITION TO BE RECTIFIED, NOTIFY THE LANDSCAPE ARCHITECT IN WRITING OR OTHERWISE FORFEIT HIS CLAIM. LANDSCAPE CONTRACTOR SHALL PRUNE PLANTINGS OF DEAD LIMBS OR TWIGS DURING THE FIRST YEAR OF GROWTH.
12. FINAL ACCEPTANCE BY THE LANDSCAPE ARCHITECT WILL BE MADE UPON THE CONTRACTOR'S REQUEST AFTER ALL CORRECTIVE WORK HAS BEEN COMPLETED.
13. LANDSCAPE CONTRACTOR SHOULD REPLACE DEAD PLANTINGS IMMEDIATELY UPON OWNER DIRECTION WITHIN THE WARRANTY PERIOD AND AGAIN AT THE END OF THE GUARANTEE PERIOD, THE CONTRACTOR SHALL HAVE REPLACED ANY PLANT MATERIAL THAT IS MISSING, NOT TRUE TO SIZE AS SPECIFIED, THAT HAVE DIED, THAT HAVE LOST THEIR NATURAL SHAPE DUE TO DEAD BRANCHES, EXCESSIVE PRUNING OR INADEQUATE OR IMPROPER CARE, OR THAT ARE, IN THE OPINION OF THE LANDSCAPE ARCHITECT, IN UNHEALTHY OR UNSIGHTLY CONDITION.
14. ALL LANDSCAPE AREAS TO BE GRASS COMMON TO REGION EXCEPT FOR INTERIOR LANDSCAPED ISLANDS OR WHERE OTHER PLANT MATERIAL IS CALLED FOR.
15. ALL TREES AND SHRUBS TO BE PLANTED IN MULCH BEDS WITH DEFINED AND CUT EDGES TO SEPARATE TURF GRASS AREAS.
16. FOR ANY LANDSCAPE AREA SO DESIGNATED TO REMAIN, WHETHER ON OR OFF-SITE, REMOVE WEEDS, ROCKS, CONSTRUCTION ITEMS, ETC., THEN APPLY GRASS SEED OR PINE BARK MULCH AS DEPICTED ON PLANS.
17. LANDSCAPE CONTRACTOR SHALL FEED AND PRUNE EX. TREES, ON OR JUST OFF SITE, THAT HAVE EXPERIENCED ROOT BASE INTRUSION OR DAMAGE DURING CONSTRUCTION IMMEDIATELY AND FOR THE DURATION OF THE WARRANTY PERIOD AT THE DIRECTION OF THE LANDSCAPE ARCHITECT.
18. EXISTING TREES TO REMAIN SHALL BE PROTECTED WITH TEMPORARY SNOW FENCING AT THE EDGE OF THE EX. TREE CANOPY THE CONTRACTOR SHALL NOT STORE VEHICLES OR MATERIALS WITHIN THE LANDSCAPED AREAS. ANY DAMAGE TO EXISTING TREES, SHRUBS OR LAWN SHALL BE REPAIRED BY THE CONTRACTOR AT NO ADDITIONAL COST TO THE OWNER.
19. ALL MULCH AREAS SHALL RECEIVE A 2" LAYER OF SHREDDED PINE BARK MULCH.
20. ALL WORK SHALL BE DONE IN STRICT ACCORDANCE WITH PROJECT SPECIFICATIONS.

terra firma
landscape architecture
163.a court street - portsmouth, nh 03801
office: 603.430.6588 | terrace@terrafirmalandscape.com






Date	Revision	Project ID	Drawing Code	CAD File Name	Plot Date
8/23/2022	Revision	8 KPH	8 KPH	88MAPLEWOOD	00/00/00
Designed By	Drawn By	Checked By	Reviewed By	Submitted By	Project Manager
TP	TC	TP	TP	TP	TP
terra firma landscape architecture 163.a Court Street Portsmouth, NH			Consultant		
Project File	8 KPH		PLANTING DETAILS		
Scale	SEE DETAILS				
Sheet No.	L-3				
Sheet Title	of 1				

TAC SUBMISSION
ENTRY + DETAIL UPDATES
Issue Notes



IRON AGE DESIGNS
 (877) 418-3568 or (206) 276-0925
 2104 SW 152nd St. Suite #4
 Burien, WA 98166
 info@ironagegrates.com

OR EQUAL



MINNIONE 4' SQ. TREE GRATES ARRAYED WITH 2' x 4' EXTENSION PANELS. OR EQUAL.

MID-SUPPORTS TO BE SUPPLIED BY MANUFACTURER TO BE USED AS NEEDED.

CAST IRON WITH A BAKED-ON-OIL FINISH.

TREES PLANTED IN TREE GRATE SYSTEM TO BE PLANTED IN "CU-STRUCTURAL SOIL" TO 36" DEPTH, "CU-STRUCTURAL SOIL" OR EQUAL TO BE UNDER EXTENSION PANELS TO 36" DEEP. BACKFILL TREE PIT WITH TOPSOIL.

1
L-4

CONTINUOUS TREE GRATE (4' WIDE x 50' LONG)
SCALE: NTS

THIS SHEET IS SCALED FOR 22x34 PAPER, DO NOT ENLARGE OR REDUCE.

terra firma
 landscape architecture
 163.a court street - portsmouth, nh 03801
 phone: 603.450.8388 | terrafirma@terrafirmalandscape.com

8/23/2022
 Revision
 8 KPH
 Drawing Code
 88MAPLEWOOD
 CAD File Name
 00/00/00

TP
TC
TP
TP
TP


terra firma landscape architecture
 163.a Court Street
 Portsmouth, NH

8 KPH

LANDSCAPE DETAILS

SEE DETAILS

L-4
of
1



VECTOR™ SEATING SYSTEM

STANDALONE BENCH NOMINAL DIMENSIONS (CONTINUED)

MODEL	OVERALL LENGTH	OVERALL DEPTH	OVERALL HEIGHT*	SEAT HEIGHT	OVERALL WEIGHT**	
					WITHOUT SIDE PANELS	TWO STAINLESS STEEL SIDE PANELS
SBVTR-96C-2E-0B	95.9" (2436 mm)	16.9" (429 mm)	17.5" (445 mm)	17.5" (445 mm)	111 lbs (50 kg)	169 lbs (77 kg)
SBVTR-96C-2E-4B	95.9" (2436 mm)	16.9" (429 mm)	29.5" (749 mm)	17.5" (445 mm)	171 lbs (78 kg)	229 lbs (104 kg)
SBVTR-96A-2E-0B	95.9" (2436 mm)	16.9" (429 mm)	17.5" (445 mm)	17.5" (445 mm)	124 lbs (56 kg)	182 lbs (83 kg)
SBVTR-96A-2E-4B	95.9" (2436 mm)	16.9" (429 mm)	29.5" (749 mm)	17.5" (445 mm)	184 lbs (83 kg)	242 lbs (110 kg)

ADD-ON BENCH NOMINAL DIMENSIONS


MODEL	OVERALL LENGTH	OVERALL DEPTH	OVERALL HEIGHT*	SEAT HEIGHT	OVERALL WEIGHT**	
					WITHOUT SIDE PANELS	TWO STAINLESS STEEL SIDE PANELS
SBVTR-24C-1E1M-0B	25.7" (653 mm)	16.9" (429 mm)	17.5" (445 mm)	17.5" (445 mm)	53 lbs (24 kg)	73 lbs (33 kg)
SBVTR-24C-1M-0B	23.4" (594 mm)	16.9" (429 mm)	17.5" (445 mm)	17.5" (445 mm)	36 lbs (16 kg)	56 lbs (25 kg)
SBVTR-24C-1E-0B	23.4" (594 mm)	16.9" (429 mm)	17.5" (445 mm)	17.5" (445 mm)	36 lbs (16 kg)	56 lbs (25 kg)
SBVTR-24A-1E1M-0B	25.7" (653 mm)	16.9" (429 mm)	17.5" (445 mm)	17.5" (445 mm)	56 lbs (25 kg)	76 lbs (34 kg)
SBVTR-24A-1M-0B	23.4" (594 mm)	16.9" (429 mm)	17.5" (445 mm)	17.5" (445 mm)	39 lbs (18 kg)	59 lbs (27 kg)
SBVTR-24A-1E-0B	23.4" (594 mm)	16.9" (429 mm)	17.5" (445 mm)	17.5" (445 mm)	39 lbs (18 kg)	59 lbs (27 kg)

*Add 12" (305 mm) for optional seat back.
 *Add 2.5" (64 mm) for optional end or intermediate seat divider.
 **Add 15 lbs (7 kg) for each additional optional seat back.
 **Add 2 lbs (1 kg) for each additional optional end or intermediate seat divider.

T 800.451.0410 | www.forms-surfaces.com

1
L-5

ENTRY BENCH
SCALE: NTS



VECTOR™ SEATING SYSTEM


The Vector Seating System is a modern, modular design that goes in whatever direction your seating needs take. This highly customizable line invites you to mix interchangeable bench and planter modules, choose materials and finishes to suit your design scheme, and personalize your layouts with optional seat backs and seat dividers, LED accent lighting below bench seats, and/or side panels in stainless steel. Coordinating Vector Table Ensembles expand the line's reach.

MATERIAL & CONSTRUCTION DETAILS

CONFIGURATIONS	SIDE PANEL OPTIONS	PLANTER MODULE
<ul style="list-style-type: none"> There are seven basic components to the Vector Seating System: four linear benches (2-, 4-, 6-, and 8-foot lengths), a 2' planter module, and two 120° angle benches. The components can be specified to connect to each other in a linear fashion and/or branch off of the sides. In addition to linear benches, standard configurations include Tri-Hub and Oblique. See page 7 for details. All seating components are available with or without seat backs. Seat backs are not available at some connection points. Wall-top configurations are also available. Please contact us to discuss your project's specific requirements. 	<ul style="list-style-type: none"> All seating components are available with or without side panels on one or both sides. Stainless steel side panels are available in three stainless steel finishes or can be powdercoated. Side panels can be specified with Rainfall perforation or no pattern. See page 2 for details. 	<ul style="list-style-type: none"> Planter frame is aluminum with a powdercoat finish. Planter capacity is 14 gallons. Planter liner is molded polyethylene. Drainage holes are optional. Stainless steel side panels are available in the same finishes and pattern as bench components. See page 2 for details.
FRAME AND SEAT OPTIONS	OPTIONAL SEAT DIVIDERS	LED ACCENT LIGHTING
<ul style="list-style-type: none"> Frame is aluminum with a powdercoat finish. Seats are available in two material options. FSC® 100% Cumaru hardwood seat slats (8 slats per bench) have a natural oiled finish that enhances the wood's rich color (FSC License Code: FSC-C004453). Extruded aluminum seat slats (4 slats per bench) feature a lightly grooved surface for enhanced appearance and a non-slip feel. Aluminum slats are powdercoated. See the Forms+Surfaces Powdercoat Chart for details. Optional aluminum seat backs are powdercoated to match the bench frame. 	<ul style="list-style-type: none"> Cast aluminum end and intermediate seat dividers are available for all of the seating components. Seat dividers are powdercoated to match the frame. Due to the inherent nature of metal castings, glass powdercoats are not offered for cast components. 	<ul style="list-style-type: none"> Optional LED accent lighting is available for all seating components. Accent lighting attaches to the underside of the seating components. Accent lighting is offered in 3000K warm white and 4000K cool white LEDs.
INSTALLATION & MAINTENANCE	MAINTENANCE	
<ul style="list-style-type: none"> The Vector Seating System can be freestanding or surface mounted. Configurations with seat backs must be surface mounted. Stainless steel anchors and mounting bolts are sold separately. Wall-top mounting is customized per project. Can be shipped flat packed. 	<ul style="list-style-type: none"> Metal surfaces can be cleaned as needed using a soft cloth or brush with warm water and a mild detergent. Avoid abrasive cleaners. Cumaru hardwood slats can be maintained by re-oiling as needed with Penotri™ hardwood finish or similar products. 	

SBVTR 96A-2E-0B | Vector Seating System, 8 foot, aluminum slats, standalone, no seat backs

FORMS + SURFACES BACKLESS ALUMINUM SLAT 8' STAND-ALONE VECTOR BENCH OR EQUAL DARK GREY METALLIC TEXTURE POWDER COAT ON FRAME AND SEAT. ADD-ON OF 2 SEAT DIVIDERS.




IRON AGE DESIGNS
 (877) 418-3568 or (206) 276-0925
 2104 SW 152nd St. Suite #4
 Burien, WA 98166
 info@ironagegrates.com
 OR EQUAL



2
L-5

TREE GUARD
SCALE: NTS



3
L-5

URNS AT ENTRY
SCALE: NTS

Kornegay Design, A Landscape Forms Company
 Dune Planter, 44" Diam, 32" Height.
 IN GRAPHITE (IRON OXIDE).

Kornegay Design, A Landscape Forms Company
 212 South 18th Street
 Phoenix, Arizona 85034
 p: 800.430.6209
 f: 269.381.3455
 https://kornegaydesign.com/

terra firma
landscape architecture
 163.a court street - portsmouth, nh 03801
 office 603.436.8388 | terrafirmalandarch.com

8/23/2022
 Revision
 8 KPH
 Drawing Code
 88MAPLEWOOD
 00/00/00

TP
 TC
 TP
 TP
 TP

terra firma landscape architecture
 163.a Court Street
 Portsmouth, NH

8 KPH

LANDSCAPE DETAILS


SEE DETAILS

L-5
 of
 1

TAC SUBMISSION
 ENTRY + DETAIL UPDATES
 10/20/2022
 8/28/2022

Date
 No.
 Issue Notes


THIS SHEET IS SCALED FOR 22x34 PAPER, DO NOT ENLARGE OR REDUCE.



WALPOLE THREE-RAIL ECHELON PLUS STYLE ALUMINUM FENCE OR EQUAL

Walpole Outdoors OR EQUAL
100 River Ridge Drive, Suite 302
Norwood, MA 02062
(866) 253-3108
<https://walpoleoutdoors.com/>

1
L-6
FENCE WITH MOUNTED LIGHTS
SCALE: 1/2"=1'-0"



2
L-6
RAILROAD TIE BOLLARD
SCALE: NTS

CAST LANDSCAPE Old world craftsmanship... tomorrow's technology

CAST Savannah Deck Light (CDL2CB)
Product Information

CAST Solid Bronze Savannah Deck Light - Rugged and Stylish



Description:
This compact and stylish solid bronze deck light is a durable and reliable fixture for wall and post mounting.

- Features:**
- ▶ Solid bronze hood and base
 - ▶ Glare-free illumination
 - ▶ Pre-wired with 25' tin-coated No-Ox® marine grade wire
 - ▶ High-temp socket
 - ▶ Spider Splice® ready

Uses:
Suitable for downlighting when mounted on retaining walls, structure surfaces, posts and pilings.

Construction:
Solid bronze hood and base; 25' tin-coated #18-2 No-Ox® marine-grade wire.

Dimensions:
3.2" wide x 3" tall x 1.5" deep

Specifications:
Lamp: Includes 2.5W, 9-15 volt operating range, T5 LED Lamp (SL921T5200L).
Halogen Option: 12 volt, 10W, T3 wedge-based - 18W max. (CWB1210X).

Listing:
U.L. 1838 Listed Low Voltage Luminaire for wet locations





www.cast-lighting.com 800.914.CAST
© Copyright 2020, CAST Lighting LLC. All rights reserved. Revised December 2019

3
L-6
DECK LIGHTS FOR FENCE
SCALE: NTS



Project Title	8 KPH	Project No.	B	Issue	TAC SUBMISSION
Scale	SEE DETAILS	Date	A	Entry	ENTRY + DETAIL UPDATES
Sheet No.	L-6	No.	A	Issue Notes	
Design Firm	terra firma landscape architecture 163.a Court Street Portsmouth, NH	Project Manager	88MAPLEWOOD	Date	00/00/00
Project Title	LANDSCAPE DETAILS	Project ID	8 KPH	Revision	
Scale	SEE DETAILS	Checked By	TP	Revision	
Sheet No.	L-6	Designed By	TP	Revision	
		Drawn By	TC	Revision	
		Reviewed By	TP	Revision	
		Submitted By	TP	Revision	
		Project Manager	TP	Revision	
		Date	8/23/2022	Revision	



This drawing reveals the copyrighted intellectual property of Columbia Cascade Company. Not for use by others without our express written authorization. Authorization for use is hereby granted to architects, landscape architects and similar design professionals solely for the purpose of specifying TimberForm products.

COLUMBIA CASCADE COMPANY
Makers of TimberForm®, PipeLine®, SuperForm®, TimberForm™-2, SuperPipe®, CycLoops® and CycleLocker® Products.
1300 S.W. Sixth Avenue, Suite 310 Portland, Oregon 97201-3464 U.S.A. Telephone 503/223-1157 Facsimile 503/223-4530 WWW.TIMBERFORM.COM

File: **TIMBERFORM CYCLOOPS MODEL NO. 2174-01 VERTICAL CYCLOOPS**

Scale: 1"=1'-0" Drawn by: AT 07-04-10 Cr'd by: CWS

Drawing No. **W-2174-01** Sheet **1 of 1**

No. 2174 Wall CycLoops Bicycle Rack

Bicycle Rack shall be TimberForm® Wall CycLoops™ model No. 2174, to accommodate one bicycle, in color or finish selected by the owner's representative and in the quantity shown on the bill of materials or the project drawings. Manufacturer, Columbia Cascade Company, 1300 SW Sixth Avenue, Suite 310, Portland OR 97201-3464 U.S.A.

1. Materials

Bicycle Rack shall be single loop of 1 inch i.d. schedule 40 mild steel seamless pipe with a minimum wall thickness of .133 inch. *Easily vandalized thin wall tubing is not allowed.* Loop shall include a pre-drilled flange permanently welded to ends which will accommodate two half inch diameter wall anchor bolts (contractor supplied).

2. Construction

Bicycle Rack shall be a single unit. Bicycle Rack shall be deburred and ground smooth after fabrication.

3. Finishes

Steel and cast iron parts shall be coated with CASPAX-7, a tough, opaque, UV resistant exterior grade polyester powder coating applied to a minimum thickness of 6 mils. *Liquid, epoxy or lead-containing powder coatings are not acceptable.*

Preparation of the mild steel substrate shall incorporate the phosphate system. Substrate preparation shall consist first of mechanical cleaning to remove heavy mill scale, rust, varnish, grease, etc., with surfaces uniformly abraded to promote quality of finish coating. Chemical cleaning in accordance with TT-C-490C, Methods I and III shall remove impurities from the surfaces.

After the two-step cleaning process, the metal substrate shall receive a corrosion-inhibiting iron phosphate pre-coating in accordance with TT-C-490C, Type II, prior to the application of the powder color coat. The color coating shall be applied by the electrostatic method and then oven-cured at 400 degrees Fahrenheit to chemically bond the coating to the substrate and to render the coated metal resistant to abrasion, impact, chipping, weathering, and rusting.

-Or- Mild steel (-G) bicycle rack shall be hot-dipped galvanized per ASTM 123 after complete fabrication.

-Or- Stainless steel (-S) bicycle rack shall have No. 4 polish finish.

Visit www.timberform.com to view and download drawings (PDF or DWG), product specifications and placement guidelines.

SUPER CYCLOOPS

Two lengths are offered to accommodate eight (2175-8) or ten (2175-10) bicycles.

Super CycLoops bike racks employ hefty 4-1/2" (115mm) diameter ASTM schedule 40 steel pipe with integral smaller steel dividers permanently welded in place. Standard Super CycLoops mounting is by embedment, pedestal (surface) mounting with matching base covers is optional.

CURVY CYCLOOPS

Curvy CycLoops can be configured in almost any shape to fit jobsite architecture—circle, oval, arc, angle, square, polygon or serpentine. U.S. Design Patent D372,889.

WALL CYCLOOPS

The 2174 Wall CycLoops is a single loop (one bike) 1-5/16" (13.3mm) diameter ASTM schedule 40 curved steel pipe permanently welded to a 16" (405mm) long mounting plate.

BOLLARD CYCLOOPS

Bollard CycLoops are domed 4-1/2" (115mm) diameter steel posts that are 3' (915mm) tall. Integral steel loops are at bike height. Select from one, two or three loop models.

The 2174-01 is for vertically hanging a single bike on a wall.


TimberForm® WALL CYCLOOPS 2174-01 VERTICAL HANGING BIKE RACK OR EQUAL

1

GARAGE VERTICAL BIKE RACK DETAIL

SCALE: NTS

L-7



FORMS + SURFACES TRIO BIKE RACK OR EQUAL

BIKE RACK DETAIL

SCALE: NTS

2

L-7

TRIO™ BIKE RACK

PRODUCT DATA

The Trio Bike Rack is the perfect complement to our Trio product line. Providing an excellent opportunity for design continuity, the Trio Bike Rack draws on the same triangular shape and exaggerated void seen in both our Trio Bench and Trio Lighting. Contemporary in design, its simple yet sculptural form allows it to be integrated into a myriad of settings.

MATERIAL & FINISHES

MATERIAL	FINISHES	GUIDELINES & SECURITY	INSTALLATION	MAINTENANCE
Body is made of corrosion-resistant cast aluminum with powdercoat finish.	See the Forms+Surfaces Powdercoat Chart for details. CustomRAL colors are available for an upcharge. Due to the inherent nature of metal castings, gloss powdercoats are not offered for cast components.	Meets Association of Pedestrian and Bicycle Professionals (APBP) guidelines. A locking point detail and mounting configurations that meet APBP guidelines can be found on pages 1 and 2 of this document.	Trio Bike Racks must be surface mounted with embedded anchors. Stainless steel anchors and larger-resistant stainless steel screws are included.	Metal surfaces can be cleaned as needed using a soft cloth or brush with warm water and a mild detergent. Avoid abrasive cleaners.

NOMINAL DIMENSIONS

OVERALL LENGTH	OVERALL DEPTH	OVERALL HEIGHT	WEIGHT
12" (305 mm)	2.75" (70 mm)	33.5" (851 mm)	25 lbs (11.3 kg)

LOCKING POINT AND CONFIGURATION EXAMPLES

The Trio Bike Rack was designed to allow for a multitude of locking point and configuration options to meet your individual needs. Please note that for optimal performance, Forms+Surfaces recommends a 36" center-to-center placement. See diagrams below and the separate installation instructions document for more details.

A standard U-lock can be locked at this location to meet APBP guidelines for security and functionality.

LOCKING POINT EXAMPLE

T 800.451.0410 | www.forms-surfaces.com

FORMS+SURFACES

page 1 of 2 | Rev. 11-17-17

TRIO™ BIKE RACK

PRODUCT DATA

LOCKING POINT AND CONFIGURATION EXAMPLES (Continued)

ENVIRONMENTAL CONSIDERATIONS

- Please refer to the Trio Bike Rack Environmental Data Sheet for detailed environmental impact information.
- Trio aluminum casting has up to 95% recycled content and is fully recyclable.
- Standard powdercoat finishes are no-VOC; non-standard powdercoat finishes are no- or low-VOC, depending on color.
- Low maintenance.

MODEL NUMBER AND DESCRIPTION

MODEL	DESCRIPTION
TRIO	Trio Bike Rack

PRODUCT OPTIONS

The following options are available for an upcharge:

- Premium Texture Colors from Forms+Surfaces Powdercoat Chart.
- CustomRAL powdercoat color.

LEAD TIME: 4 weeks. Shorter lead times may be available upon request. Please contact us to discuss your specific timing requirements.

PRICING: Please contact us at 800.451.0410 or sales@forms-surfaces.com. All Forms+Surfaces, we design, manufacture and sell our products directly to you. Our sales team is available to assist you with questions about our products, requests for quotes, and orders. Territory Managers are located worldwide to assist with the front-end specification and quoting process, and our in-house Project Sales Coordinators follow your project through from the time you place an order to shipment.

TO ORDER SPECIFY: Quantity, model and powdercoat color for body casting. Quote/Order Forms are available on our website to lead you through the specification process in a simple checkbox format.

T 800.451.0410 | www.forms-surfaces.com

FORMS+SURFACES

page 2 of 2 | Rev. 11-17-17

terra firma
landscape architecture

163.a Court Street - Portsmouth, NH 03801
office: 603.430.9388 | terrence@terrafirmalandscape.com

Date	Revision	Project ID	Drawing Code	CAD File Name	Plot Date
8/23/2022	Revision		8 KPH	88MAPLEWOOD	00/00/00

Designed By: TP
Drawn By: TC
Checked By: TP
Reviewed By: TP
Submitted By: TP
Project Manager: TP

terra firma landscape architecture
163.a Court Street
Portsmouth, NH

8 KPH


LANDSCAPE DETAILS

Scale: SEE DETAILS

Sheet No. **L-7**
of
1

THIS SHEET IS SCALED FOR 22X34 PAPER, DO NOT ENLARGE OR REDUCE.

ITEM	QTY	DESCRIPTION	MODELNUMBER	APPROVED BY:
1	1	OGDEN, STRAIGHT, WLRLR-48 IN	OGM1900-SS4-WLR	
2	2	OGDEN, SQUARE LEG	OGM1900-MS1	DATE:
3	2	OGDEN, CENTER ARM, STYLE 1	OGM1900-CA1	




MAGLIN MAGLIN SITE FURNITURE WWW.MAGLIN.COM TEL: 800-716-5506 FAX: 877-260-9393	THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MAGLIN SITE FURNITURE. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MAGLIN SITE FURNITURE IS PROHIBITED.	TITLE: OGDEN, STRAIGHT, IPE, SQUARE LEG MODEL NO: OGM1900-190667	DATE: 10/20/2022 SHEET: 1 OF 3

MAGLIN BACKLESS, 4' STRAIGHT OGDEN BENCH OR EQUAL.

1
L-8

POCKET PARK 4' BENCH
SCALE: NTS

ITEM	QTY	DESCRIPTION	MODELNUMBER	APPROVED BY:
1	1	OGDEN, STRAIGHT, WLRLR-72 IN	OGM1900-SS6-WLR	
2	2	OGDEN, SQUARE LEG	OGM1900-MS1	DATE:
3	2	OGDEN, CENTER ARM, STYLE 1	OGM1900-CA1	




MAGLIN MAGLIN SITE FURNITURE WWW.MAGLIN.COM TEL: 800-716-5506 FAX: 877-260-9393	THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MAGLIN SITE FURNITURE. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MAGLIN SITE FURNITURE IS PROHIBITED.	TITLE: OGDEN, STRAIGHT, IPE, SQUARE LEG MODEL NO: OGM1900-190668	DATE: 10/20/2022 SHEET: 1 OF 3

MAGLIN BACKLESS, 6' STRAIGHT OGDEN BENCH OR EQUAL.

2
L-8

POCKET PARK 6' BENCH
SCALE: NTS

ITEM	QTY	DESCRIPTION	MODELNUMBER	APPROVED BY:
1	2	BACKED OGDEN, STRAIGHT, WLRLR-60 IN	OGM1900-B1-SS3-WLRLR	
2	3	OGDEN, SQUARE LEG	OGM1900-MS1	DATE:
3	3	BACKED OGDEN, CENTER ARM, STYLE 1	OGM1900-BCA1	



MAGLIN MAGLIN SITE FURNITURE WWW.MAGLIN.COM TEL: 800-716-5506 FAX: 877-260-9393	THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MAGLIN SITE FURNITURE. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MAGLIN SITE FURNITURE IS PROHIBITED.	TITLE: BACKED OGDEN, STRAIGHT, IPE, SQUARE LEG MODEL NO: OGM1900-190665	DATE: 10/20/2022 SHEET: 1 OF 3

MAGLIN BACKED, 10' STRAIGHT OGDEN BENCH OR EQUAL.


3
L-8

POCKET PARK 10' BENCH
SCALE: NTS

THIS SHEET IS SCALED FOR 22x34 PAPER, DO NOT ENLARGE OR REDUCE.



Design Firm terra firma landscape architecture 163.a Court Street Portsmouth, NH	Project Title 8 KPH	Scale SEE DETAILS	Sheet Title LANDSCAPE DETAILS	Sheet No. L-8 of 1
Designed By TP	Drawn By TC	Checked By TP	Reviewed By TP	Submitted By TP
TAC SUBMISSION ENTRY + DETAIL UPDATES				No. A B Date 8/28/2022



AMBIT ENGINEERING, INC.
Civil Engineers & Land Surveyors
200 Griffin Road - Unit 3
Portsmouth, N.H. 03801-7114
Tel (603) 430-9282
Fax (603) 436-2315

NOTES:

- 1) PARCEL IS SHOWN ON THE CITY OF PORTSMOUTH ASSESSOR'S MAP 125 AS LOT 17-3.
- 2) OWNER OF RECORD:
EIGHTKPH, LLC
233 VAUGHAN STREET
UNIT 301
PORTSMOUTH, NH 03801
6348/2213
- 3) THE PURPOSE OF THIS PLAN IS TO SHOW THE PARKING FOR THE PROPOSED SITE DEVELOPMENT ON ASSESSOR'S MAP 125 LOT 17-3 IN THE CITY OF PORTSMOUTH.
- 4) REQUIRED PARKING:
FIRST FLOOR: EXEMPT
19 DWELLING UNITS: 1.3/UNIT X 19 UNITS = 25
VISITOR: 19/5 X 1 = 4
TOTAL REQUIRED: 29
TOTAL PROVIDED: 29

**SITE DEVELOPMENT
EIGHTKPH, LLC
88 MAPLEWOOD AVENUE
PORTSMOUTH, N.H.**




1	BUILDING FOOTPRINT	10/20/22
0	ISSUED FOR COMMENT	8/23/22

REVISIONS

NO.	DESCRIPTION	DATE

SCALE: 1" = 10' AUGUST 2022

PARKING LEVEL PLAN **C4**



Residential Units Area

Unit 201	2,407 SF
Unit 202	2,761 SF
Unit 203	2,536 SF
Unit 204	2,537 SF
Unit 205	2,593 SF
Unit 206	2,881 SF
Unit 301	2,407 SF
Unit 302	2,761 SF
Unit 303	2,536 SF
Unit 304	2,537 SF
Unit 305	2,593 SF
Unit 306	2,881 SF
Unit 401	2,407 SF
Unit 402	2,761 SF
Unit 403	2,536 SF
Unit 404	2,537 SF
Unit 405	2,593 SF
Unit 406	2,881 SF
Penthouse Unit	7,344 SF




R7-8a
12" x 18"
SIGN ON POST

EACH SPACE SHALL HAVE THIS SIGN DISPLAYED PER ADA CODE

SIGNAGE

LEGEND SYMBOL



HANDICAP ACCESSIBLE SYMBOL




K-4438
12" x 18"
SIGN ON POST

SIGNAGE

PROVIDE SIGN (PER ADA CODE) AT EACH HANDICAP ACCESSIBLE SPACE

HANDICAP ACCESS AISLE NO PARKING SIGN



NOTES:

- 1) SYMBOL TO BE PAINTED IN ALL HANDICAPPED SPACES.
- 2) SYMBOL, PAINT AND SIGNAGE TO CONFORM TO AMERICANS WITH DISABILITIES ACT (ADA).
- 3) ALL VAN ACCESSIBLE SPACES SHALL HAVE "VAN ACCESSIBLE" PLATE INSTALLED ON SIGN POST BELOW HANDICAP SIGN.

APPROVED BY THE PORTSMOUTH PLANNING BOARD




CHAIRMAN _____ DATE _____

1 C4 HANDICAP PARKING DETAIL NTS

UTILITY NOTES:

- 1) SEE EXISTING CONDITIONS PLAN FOR BENCHMARK INFORMATION.
- 2) COORDINATE ALL UTILITY WORK WITH APPROPRIATE UTILITY.
- 3) SEE GRADING AND DRAINAGE PLAN FOR PROPOSED GRADING AND EROSION CONTROL MEASURES.
- 4) ALL WATER MAIN INSTALLATIONS SHALL BE CLASS 52, POLYWRAPPED, CEMENT LINED DUCTILE IRON PIPE.
- 5) ALL WATERMAIN INSTALLATIONS SHALL BE PRESSURE TESTED AND CHLORINATED AFTER CONSTRUCTION AND BEFORE ACTIVATING THE SYSTEM. CONTRACTOR SHALL COORDINATE WITH THE CITY OF PORTSMOUTH.
- 6) ALL SEWER PIPE SHALL BE PVC SDR 35 UNLESS OTHERWISE STATED.
- 7) ALL WORK WITHIN CITY R.O.W. SHALL BE COORDINATED WITH CITY OF PORTSMOUTH.
- 8) CONTRACTOR SHALL MAINTAIN UTILITY SERVICES TO ADJUTING PROPERTIES THROUGHOUT CONSTRUCTION.
- 9) ANY CONNECTION TO EXISTING WATERMAIN SHALL BE CONSTRUCTED BY THE CITY OF PORTSMOUTH.
- 10) EXISTING UTILITIES TO BE REMOVED SHALL BE CAPPED AT THE MAIN AND MEET THE DEPARTMENT OF PUBLIC WORKS STANDARDS FOR CAPPING OF WATER AND SEWER SERVICES.
- 11) ALL ELECTRICAL MATERIAL WORKMANSHIP SHALL CONFORM TO THE NATIONAL ELECTRIC CODE, LATEST EDITION, AND ALL APPLICABLE STATE AND LOCAL CODES.
- 12) THE EXACT LOCATION OF NEW UTILITY SERVICES AND CONNECTIONS SHALL BE COORDINATED WITH BUILDING DRAWINGS AND UTILITY COMPANIES.
- 13) ADJUST ALL MANHOLES, CATCH BASINS, CURB BOXES, ETC. WITHIN LIMITS OF WORK TO FINISH GRADE.
- 14) ALL UNDERGROUND CONDUITS SHALL HAVE NYLON PULL ROPES TO FACILITATE PULLING CABLES.
- 15) THE CONTRACTOR SHALL OBTAIN, PAY FOR, AND COMPLY WITH ALL REQUIRED PERMITS, ARRANGE FOR ALL INSPECTIONS, AND SUBMIT COPIES OF ACCEPTANCE CERTIFICATED TO THE OWNER PRIOR TO THE COMPLETION OF PROJECT.
- 16) THE CONTRACTOR SHALL PROVIDE AND INSTALL ALL MANHOLES, BOXES, FITTINGS, CONNECTORS, COVER PLATES AND OTHER MISCELLANEOUS ITEMS NOT NECESSARILY DETAILED IN THESE DRAWING TO RENDER INSTALLATION OF UTILITIES COMPLETE AND OPERATIONAL.
- 17) CONTRACTOR SHALL PROVIDE EXCAVATION, BEDDING, BACKFILL AND COMPACTION FOR NATURAL GAS SERVICES.
- 18) A 10-FOOT MINIMUM EDGE TO EDGE HORIZONTAL SEPARATION SHALL BE PROVIDED BETWEEN ALL WATER AND SANITARY SEWER LINES. AN 18-INCH MINIMUM OUTSIDE TO OUTSIDE VERTICAL SEPARATION SHALL BE PROVIDED AT ALL WATER/SANITARY SEWER CROSSINGS WATER ABOVE SEWER.
- 19) SAWCUT AND REMOVE PAVEMENT AND CONSTRUCT PAVEMENT TRENCH PATCH FOR ALL PROPOSED UTILITIES LOCATED IN EXISTING PAVEMENT AREAS TO REMAIN.
- 20) GATE VALVES, FITTINGS, ETC. SHALL MEET THE REQUIREMENTS OF THE CITY OF PORTSMOUTH.
- 21) COORDINATE TESTING OF SEWER CONSTRUCTION WITH THE CITY OF PORTSMOUTH.
- 22) ALL SEWER PIPES WITH LESS THAN 6" COVER SHALL BE INSULATED.
- 23) CONTRACTOR SHALL COORDINATE ALL ELECTRIC WORK INCLUDING BUT NOT LIMITED TO: CONDUIT CONSTRUCTION, MANHOLE CONSTRUCTION, UTILITY POLE CONSTRUCTION, OVERHEAD WIRE RELOCATION, AND TRANSFORMER CONSTRUCTION WITH POWER COMPANY.
- 24) CONTRACTOR SHALL PHASE UTILITY CONSTRUCTION, PARTICULARLY WATER MAIN AND GAS MAIN CONSTRUCTION AS TO MAINTAIN CONTINUOUS SERVICE TO ADJUTING PROPERTIES. CONTRACTOR SHALL COORDINATE TEMPORARY SERVICES TO ADJUTERS WITH UTILITY COMPANY AND AFFECTED ADJUTER.

SEWER STRUCTURE SCHEDULE						
STRUCTURE	PROP/EX	RIM	PIPE SIZE/TYPE	INVERT IN	INVERT OUT	DIRECTION
SMH 1499	EX	15.80	48" BRICK BOX	-1.80	-1.80	
SMH 1501	EX	13.58	24"	-0.30	-0.32	
SMH 2305	EX	10.90	48" VC	-1.17		
6" COMM.	PROP		6"	-0.35 @ PIPE	12.0 @ BLDG.	
6" RES.	PROP		6"	-0.64 @ PIPE	12.0 @ BLDG.	



AMBIT ENGINEERING, INC.
Civil Engineers & Land Surveyors
200 Griffin Road - Unit 3
Portsmouth, N.H. 03801-7114
Tel (603) 430-9282
Fax (603) 436-2315


- NOTES:**
- 1) THE CONTRACTOR SHALL NOTIFY DIG SAFE AT 1-888-DIG-SAFE (1-888-344-7233) AT LEAST 72 HOURS PRIOR TO COMMENCING ANY EXCAVATION ON PUBLIC OR PRIVATE PROPERTY.
 - 2) UNDERGROUND UTILITY LOCATIONS ARE BASED UPON BEST AVAILABLE EVIDENCE AND ARE NOT FIELD VERIFIED. LOCATING AND PROTECTING ANY ABOVEGROUND OR UNDERGROUND UTILITIES IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR AND/OR THE OWNER. UTILITY CONFLICTS SHOULD BE REPORTED AT ONCE TO THE DESIGN ENGINEER.
 - 3) CONTRACTOR SHALL INSTALL AND MAINTAIN EROSION CONTROL MEASURES IN ACCORDANCE WITH THE "NEW HAMPSHIRE STORMWATER MANUAL, VOLUME 3, EROSION AND SEDIMENT CONTROLS DURING CONSTRUCTION." (NHDES DECEMBER 2008).
 - 4) INSTALL CATCH BASIN INLET PROTECTION ON ALL EXISTING AND PROPOSED CATCH BASINS UNTIL CONSTRUCTION IS COMPLETED AND THE SITE IS STABILIZED.
 - 5) ALL WATER MAIN AND SANITARY SEWER WORK SHALL MEET THE STANDARDS OF THE NEW HAMPSHIRE STATE PLUMBING CODE AND CITY OF PORTSMOUTH DEPARTMENT OF PUBLIC WORKS.
 - 6) UTILITY AS-BUILTS SHALL BE SUBMITTED TO THE CITY OF PORTSMOUTH DEPARTMENT OF PUBLIC WORKS UPON COMPLETION OF THE PROJECT.
 - 7) EVERSOURCE WORK ORDER #TBD.
 - 8) PROPOSED SEWER FLOW:
15,263 S.F. COMMERCIAL
15,263 X (2.5 GPD/100 S.F.)=382 GALLONS PER DAY.
(POSSIBLE RESTAURANT) (4,000 GPD)
19 UNITS X 210 GPD=3,990 GPD
TOTAL FLOW: 4,372 GPD TO 7,990 GPD
 - 9) CUT AND CAP THE EXISTING BUILDING SEWER CONNECTIONS AT THE SEWER MAINS.
 - 10) THIS PROJECT WILL PROVIDE PRIMARY & SECONDARY CONDUIT TO THE PROPOSED PULL BOX. PRIMARY LOOP CONNECTION WILL BE BY OTHERS. EASEMENT ON LOT 17-2 TO BE PROVIDED.

APPROVED BY THE PORTSMOUTH PLANNING BOARD

CHAIRMAN _____ DATE _____


**SITE DEVELOPMENT
EIGHTKPH, LLC
88 MAPLEWOOD AVENUE
PORTSMOUTH, N.H.**

NO.	DESCRIPTION	DATE
2	EVERSOURCE EASEMENT LAYOUT	10/20/22
1	COMMUNITY SPACE ELECTRICAL CIRCUITS, NOTE 9	9/6/22
0	ISSUED FOR COMMENT	8/23/22



SCALE: 1" = 20' AUGUST 2022

UTILITY PLAN **C5**



AMBIT ENGINEERING, INC.
Civil Engineers & Land Surveyors
200 Griffin Road - Unit 3
Portsmouth, N.H. 03801-7114
Tel (603) 430-9282
Fax (603) 436-2315


DRAINAGE STRUCTURE SCHEDULE						
STRUCTURE	PROP/EX	RIM	PIPE SIZE/TYPER	INVERT IN	INVERT OUT	DIRECTION
CB 8168	EX	13.19	12" RCP	9.93	9.83	NE
DMH 3540	EX	10.81	48" RCP		1.56	NW
OCS 1	PROP	16.45	12"	10.9	7.92	
CB 1	PROP	11.50	12" HDPE	7.79	7.69	
CB 2	PROP	13.56	12" HDPE	10.22	10.12	

PIPE SCHEDULE			
PIPE #	PIPE SIZE	LENGTH	SLOPE
P1	12"	13'	0.05
P2	12"	47'	0.004
P3	12"	5'	0.02
P4	12"	31'	0.004
P5	12"	8'	0.004
P6	TWIN 12"	17'	0.17

*ALL PIPE TO BE HDPE

NOTES:


- 1) THE CONTRACTOR SHALL NOTIFY DIG SAFE AT 1-888-DIG-SAFE (1-888-344-7233) AT LEAST 72 HOURS PRIOR TO COMMENCING ANY EXCAVATION ON PUBLIC OR PRIVATE PROPERTY WITHIN 100 FEET OF UNDERGROUND UTILITIES. THE EXCAVATOR IS RESPONSIBLE TO MAINTAIN MARKS. DIG SAFE TICKETS EXPIRE IN THIRTY DAYS.
- 2) UNDERGROUND UTILITY LOCATIONS ARE BASED UPON BEST AVAILABLE EVIDENCE AND ARE NOT FIELD VERIFIED. LOCATING AND PROTECTING ANY ABOVEGROUND OR UNDERGROUND UTILITIES IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR AND/OR THE OWNER. UTILITY CONFLICTS SHOULD BE REPORTED AT ONCE TO THE DESIGN ENGINEER.
- 3) CONTRACTOR SHALL INSTALL AND MAINTAIN EROSION CONTROL MEASURES IN ACCORDANCE WITH THE "NEW HAMPSHIRE STORMWATER MANUAL, VOLUME 3, EROSION AND SEDIMENT CONTROLS DURING CONSTRUCTION. (NHDES DECEMBER 2008).



**SITE DEVELOPMENT
EIGHTKPH, LLC
88 MAPLEWOOD AVENUE
PORTSMOUTH, N.H.**

NO.	DESCRIPTION	DATE
2	BUILDING FOOTPRINT	10/20/22
1	DRAIN PIPE SIZE	9/6/22
0	ISSUED FOR COMMENT	8/23/22

REVISIONS



SCALE: 1" = 10' AUGUST 2022

GRADING & DRAINAGE PLAN **C6**

EROSION CONTROL NOTES

CONSTRUCTION SEQUENCE

DO NOT BEGIN CONSTRUCTION UNTIL ALL LOCAL, STATE AND FEDERAL PERMITS HAVE BEEN APPLIED FOR AND RECEIVED.

IF REQUIRED THE CONTRACTOR SHALL OBTAIN AN NPDES PHASE II STORMWATER PERMIT AND SUBMIT A NOTICE OF INTENT (N.O.I) BEFORE BEGINNING CONSTRUCTION AND SHALL HAVE ON SITE A STORMWATER POLLUTION PREVENTION PLAN (S.W.P.P.P.) AVAILABLE FOR INSPECTION BY THE PERMITTING AUTHORITY DURING THE CONSTRUCTION. THE CONTRACTOR SHALL BE RESPONSIBLE FOR CARRYING OUT THE S.W.P.P.P. AND INSPECTING AND MAINTAINING ALL BMP'S CALLED FOR BY THE PLAN. THE CONTRACTOR SHALL SUBMIT A NOTICE OF TERMINATION (N.O.T.) FORM TO THE REGIONAL EPA OFFICE WITHIN 30 DAYS OF FINAL STABILIZATION OF THE ENTIRE SITE OR TURNING OVER CONTROL OF THE SITE TO ANOTHER OPERATOR.

INSTALL PERIMETER CONTROLS, I.E., SILT/SOXX AND CATCH BASIN PROTECTION AROUND THE LIMITS OF DISTURBANCE AND OFF SITE AREAS AS NEEDED BEFORE ANY EARTH MOVING OPERATIONS. THE USE OF HAYBALES IS NOT ALLOWED.

PLACE FODS OR OTHER SITE ENTRANCE AS NEEDED.

CUT AND GRUB ALL TREES, SHRUBS, SAPLINGS, BRUSH, VINES AND REMOVE OTHER DEBRIS AND RUBBISH AS REQUIRED. DEMOLISH BUILDINGS AND FENCES AS NEEDED.

ROUGH GRADE SITE: CONSTRUCT RETAINING WALL.

CONSTRUCT BUILDING FOUNDATION.

LAYOUT AND INSTALL ALL BURIED UTILITIES AND SERVICES UP TO 10' OF THE PROPOSED BUILDING FOUNDATIONS. CAP AND MARK TERMINATIONS OR LOG SWING TIES.

COMPLETE BUILDING.

CONNECT UTILITIES.

PLACE BINDER LAYER OF PAVEMENT FOR SIDEWALKS.

PLANT LANDSCAPING IN AREAS OUT OF WAY OF BUILDING CONSTRUCTION. PREPARE AND STABILIZE FINAL SITE GRADING BY ADDING TOPSOIL, SEED, MULCH AND FERTILIZER.

AFTER BUILDINGS ARE COMPLETED, FINISH ALL REMAINING LANDSCAPED WORK.

CONSTRUCT SIDEWALKS.

REMOVE TRAPPED SEDIMENTS FROM COLLECTION DEVICES AS APPROPRIATE, AND THEN REMOVE TEMPORARY EROSION CONTROL MEASURES UPON COMPLETION OF FINAL STABILIZATION OF THE SITE.

GENERAL CONSTRUCTION NOTES

THE EROSION CONTROL PROCEDURES SHALL CONFORM TO SECTION 645 OF THE "STANDARD SPECIFICATION FOR ROAD AND BRIDGE CONSTRUCTION" OF THE NHDOT, AND "STORM WATER MANAGEMENT AND EROSION AND SEDIMENT CONTROL HANDBOOK FOR URBAN AND DEVELOPING AREAS IN NEW HAMPSHIRE". THE PROJECT IS TO BE MANAGED IN A MANNER THAT MEETS THE REQUIREMENTS AND INTENT OF RSA 430:53 AND CHAPTER AGR 3800 RELATIVE TO INVASIVE SPECIES.

DURING CONSTRUCTION AND THEREAFTER, EROSION CONTROL MEASURES ARE TO BE IMPLEMENTED AS NOTED. THE SMALLEST PRACTICAL AREA OF LAND SHOULD BE EXPOSED AT ANY ONE TIME DURING DEVELOPMENT. NO DISTURBED AREA SHALL BE LEFT UNSTABILIZED FOR MORE THAN 45 DAYS.

ANY DISTURBED AREAS WHICH ARE TO BE LEFT TEMPORARILY, AND WHICH WILL BE REGRADED LATER DURING CONSTRUCTION SHALL BE MACHINE HAY MULCHED AND SEEDED WITH RYE GRASS TO PREVENT EROSION.

DUST CONTROL: IF TEMPORARY STABILIZATION PRACTICES, SUCH AS TEMPORARY VEGETATION AND MULCHING, DO NOT ADEQUATELY REDUCE DUST GENERATION, APPLICATION OF WATER OR CALCIUM CHLORIDE SHALL BE APPLIED IN ACCORDANCE WITH BEST MANAGEMENT PRACTICES.

SILT FENCES AND SILT/SOXX SHALL BE PERIODICALLY INSPECTED DURING THE LIFE OF THE PROJECT AND AFTER EACH STORM. ALL DAMAGED SILT FENCES AND SILT/SOXX SHALL BE REPAIRED. SEDIMENT DEPOSITS SHALL PERIODICALLY BE REMOVED AND DISPOSED IN A SECURED LOCATION.

AVOID THE USE OF FUTURE OPEN SPACES (LOAM AND SEED AREAS) WHEREVER POSSIBLE DURING CONSTRUCTION. CONSTRUCTION TRAFFIC SHALL USE THE ROADBEDS OF FUTURE ACCESS DRIVES AND PARKING AREAS.

ADDITIONAL TOPSOIL REQUIRED FOR THE ESTABLISHMENT OF VEGETATION SHALL BE STOCKPILED IN AMOUNTS NECESSARY TO COMPLETE FINISHED GRADING OF ALL EXPOSED AREAS—CONSTRUCT SILT FENCE OR SILT/SOXX AROUND TOPSOIL STOCKPILE.

AREAS TO BE FILLED SHALL BE CLEARED, GRUBBED AND STRIPPED OF TOPSOIL TO REMOVE TREES, VEGETATION, ROOTS OR OTHER OBJECTIONABLE MATERIAL. STUMPS SHALL BE DISPOSED OF IN AN APPROVED FACILITY.

ALL FILLS SHALL BE PLACED AND COMPACTED TO REDUCE EROSION, SLIPPAGE, SETTLEMENT, SUBSIDENCE OR OTHER RELATED PROBLEMS.

ALL NON-STRUCTURAL, SITE-FILL SHALL BE PLACED AND COMPACTED TO 90% MODIFIED PROCTOR DENSITY IN LAYERS NOT EXCEEDING 18 INCHES IN THICKNESS UNLESS OTHERWISE NOTED.

FROZEN MATERIAL OR SOFT, MUCKY OR HIGHLY COMPRESSIBLE MATERIAL, TRASH, WOODY DEBRIS, LEAVES, BRUSH OR ANY DELETERIOUS MATTER SHALL NOT BE INCORPORATED INTO FILLS.

FILL MATERIAL SHALL NOT BE PLACED ON FROZEN FOUNDATION SUBGRADE.

DURING CONSTRUCTION AND UNTIL ALL DEVELOPED AREAS ARE FULLY STABILIZED, ALL EROSION CONTROL MEASURES SHALL BE INSPECTED WEEKLY AND AFTER EACH ONE HALF INCH OF RAINFALL.

THE CONTRACTOR SHALL MODIFY OR ADD EROSION CONTROL MEASURES AS NECESSARY TO ACCOMMODATE PROJECT CONSTRUCTION.

ALL ROADWAYS AND PARKING AREAS SHALL BE STABILIZED WITHIN 72 HOURS OF ACHIEVING FINISHED GRADE. ALL CUT AND FILL SLOPES SHALL BE SEEDED/LOAMED WITHIN 72 HOURS OF ACHIEVING FINISHED GRADE.

AN AREA SHALL BE CONSIDERED STABLE IF ONE OF THE FOLLOWING HAS OCCURRED:
 - BASE COURSE GRAVELS HAVE BEEN INSTALLED ON AREAS TO BE PAVED
 - A MINIMUM OF 85% VEGETATED GROWTH HAS BEEN ESTABLISHED
 - A MINIMUM OF 3 INCHES OF NON-EROSIVE MATERIAL SUCH AS STONE OR RIPRAP HAS BEEN INSTALLED
 - EROSION CONTROL BLANKETS HAVE BEEN INSTALLED

VEGETATIVE PRACTICE

FOR PERMANENT MEASURES AND PLANTINGS:

LIMESTONE SHALL BE THOROUGHLY INCORPORATED INTO THE LOAM LAYER AT A RATE OF 2 TONS PER ACRE.

FERTILIZER SHALL BE SPREAD ON THE TOP LAYER OF LOAM AND WORKED INTO THE SURFACE. FERTILIZER APPLICATION RATE SHALL BE 500 POUNDS PER ACRE OF 10-20-20 FERTILIZER.

SEED SHALL BE SOWN AT THE RATES SHOWN IN THE TABLE BELOW. IMMEDIATELY BEFORE SEEDING, THE SOIL SHALL BE LIGHTLY RAKED, ONE HALF THE SEED SHALL BE SOWN IN ONE DIRECTION AND THE OTHER HALF AT RIGHT ANGLES TO THE ORIGINAL DIRECTION. IT SHALL BE LIGHTLY RAKED INTO THE SOIL TO A DEPTH NOT OVER 1/4 INCH AND ROLLED WITH A HAND ROLLER WEIGHING NOT OVER 100 POUNDS PER LINEAR FOOT OF WIDTH. HAY MULCH SHALL BE APPLIED IMMEDIATELY AFTER SEEDING AT A RATE OF 1.5 TO 2 TONS PER ACRE, AND SHALL BE HELD IN PLACE USING APPROPRIATE TECHNIQUES FROM THE EROSION AND SEDIMENT CONTROL HANDBOOK.

THE SURFACE SHALL BE WATERED AND KEPT MOIST WITH A FINE SPRAY AS REQUIRED, WITHOUT WASHING AWAY THE SOIL, UNTIL THE GRASS IS WELL ESTABLISHED. ANY AREAS WHICH ARE NOT SATISFACTORILY COVERED SHALL BE RESEEDD, AND ALL NOXIOUS WEEDS REMOVED.

A GRASS SEED MIXTURE CONTAINING THE FOLLOWING SEED REQUIREMENTS SHALL BE:

GENERAL COVER	PROPORTION	SEEDING RATE
CREeping RED FESCUE	50%	100 LBS/ACRE
KENTUCKY BLUEGRASS	50%	

SLOPE SEED (USED ON ALL SLOPES GREATER THAN OR EQUAL TO 3:1)		
CREeping RED FESCUE	42%	
TALL FESCUE	42%	48 LBS/ACRE
BIRDSFOOT TREFOIL	16%	

IN NO CASE SHALL THE WEED CONTENT EXCEED ONE PERCENT BY WEIGHT. ALL SEED SHALL COMPLY WITH APPLICABLE STATE AND FEDERAL SEED LAWS.

FOR TEMPORARY PROTECTION OF DISTURBED AREAS:
 MULCHING AND SEEDING SHALL BE APPLIED AT THE FOLLOWING RATES:
 PERENNIAL RYE: 0.7 LBS/1,000 S.F.
 MULCH: 1.5 TONS/ACRE

MAINTENANCE AND PROTECTION

THE CONTRACTOR SHALL MAINTAIN ALL LOAM & SEED AREAS UNTIL FINAL ACCEPTANCE AT THE COMPLETION OF THE CONTRACT. MAINTENANCE SHALL INCLUDE WATERING, WEEDING, REMOVAL OF STONES AND OTHER FOREIGN OBJECTS OVER 1/2 INCHES IN DIAMETER WHICH MAY APPEAR AND THE FIRST TWO (2) CUTTINGS OF GRASS NO CLOSER THAN TEN (10) DAYS APART. THE FIRST CUTTING SHALL BE ACCOMPLISHED WHEN THE GRASS IS FROM 2 1/2 TO 3 INCHES HIGH. ALL BARE AND DEAD SPOITS WHICH BECOME APPARENT SHALL BE PROPERLY PREPARED, LIMED AND FERTILIZED, AND RESEEDD BY THE CONTRACTOR AT HIS EXPENSE AS MANY TIMES AS NECESSARY TO SECURE GOOD GROWTH. THE ENTIRE AREA SHALL BE MAINTAINED, WATERED AND CUT UNTIL ACCEPTANCE OF THE LAWN BY THE OWNER'S REPRESENTATIVE.

THE CONTRACTOR SHALL TAKE WHATEVER MEASURES ARE NECESSARY TO PROTECT THE GRASS WHILE IT IS DEVELOPING.

TO BE ACCEPTABLE, SEEDED AREAS SHALL CONSIST OF A UNIFORM STAND OF AT LEAST 90 PERCENT ESTABLISHED PERMANENT GRASS SPECIES, WITH UNIFORM COUNT OF AT LEAST 100 PLANTS PER SQUARE FOOT.

SEEDED AREAS WILL BE FERTILIZED AND RESEEDD AS NECESSARY TO INSURE VEGETATIVE ESTABLISHMENT.

THE SWALES WILL BE CHECKED WEEKLY AND REPAIRED WHEN NECESSARY UNTIL ADEQUATE VEGETATION IS ESTABLISHED.

THE SILT FENCE OR SILT/SOXX BARRIER SHALL BE CHECKED AFTER EACH RAINFALL AND AT LEAST DAILY DURING PROLONGED RAINFALL.


SILT FENCING AND SILT/SOXX SHALL BE REMOVED ONCE VEGETATION IS ESTABLISHED, AND DISTURBED AREAS RESULTING FROM SILT FENCE AND SILT/SOXX REMOVAL SHALL BE PERMANENTLY SEEDED.

WINTER NOTES

ALL PROPOSED VEGETATED AREAS WHICH DO NOT EXHIBIT A MINIMUM OF 85% VEGETATIVE GROWTH BY OCTOBER 15TH, OR WHICH ARE DISTURBED AFTER OCTOBER 15TH, SHALL BE STABILIZED BY SEEDING AND INSTALLING EROSION CONTROL BLANKETS ON SLOPES GREATER THAN 3:1, AND SEEDING AND PLACING 3 TO 4 TONS OF MULCH PER ACRE, SECURED WITH ANCHORED NETTING, ELSEWHERE. THE INSTALLATION OF EROSION CONTROL BLANKETS OR MULCH AND NETTING SHALL NOT OCCUR OVER ACCUMULATED SNOW OR ON FROZEN GROUND AND SHALL BE COMPLETED IN ADVANCE OF THAW OR SPRING MELT EVENTS.

ALL DITCHES OR SWALES WHICH DO NOT EXHIBIT A MINIMUM OF 85% VEGETATIVE GROWTH BY OCTOBER 15TH, OR WHICH ARE DISTURBED AFTER OCTOBER 15TH, SHALL BE STABILIZED TEMPORARILY WITH STONE OR EROSION CONTROL BLANKETS APPROPRIATE FOR THE DESIGN FLOW CONDITIONS.

AFTER NOVEMBER 15TH, INCOMPLETE ROAD OR PARKING SURFACES, WHERE WORK HAS STOPPED FOR THE WINTER SEASON, SHALL BE PROTECTED WITH A MINIMUM OF 3 INCHES OF CRUSHED GRAVEL PER NHDOT ITEM 304.3.



- NOTES:**
- ALL MATERIAL TO MEET FILITREXX® SPECIFICATIONS.
 - FILITREXX® SYSTEM SHALL BE INSTALLED BY A CERTIFIED FILITREXX® INSTALLER.
 - THE CONTRACTOR SHALL MAINTAIN THE COMPOST FILTRATION SYSTEM IN A FUNCTIONAL CONDITION AT ALL TIMES. IT WILL BE ROUTINELY INSPECTED AND REPAIRED WHEN REQUIRED.
 - SILT/SOXX DEPICTED IS FOR MINIMUM SLOPES, GREATER SLOPES MAY REQUIRE ADDITIONAL PLACEMENTS.
 - THE COMPOST FILTER MATERIAL WILL BE DISPersed ON SITE WHEN NO LONGER REQUIRED, AS DETERMINED BY THE ENGINEER.

A

C6

(AS NEEDED)

NTS

**FILITREXX®
SILT/SOXX™ FILTRATION SYSTEM**


FODS TRACKOUT CONTROL SYSTEM

INSTALLATION:

THE PURPOSE AND DESIGN OF THE FODS TRACKOUT CONTROL SYSTEM IS TO EFFECTIVELY REMOVE MOST SEDIMENT FROM VEHICLE TIRES AS THEY EXIT A DISTURBED LAND AREA ONTO A PAVED STREET. THIS MANUAL IS A PLATFORM FROM WHICH TO INSTALL A FODS TRACKOUT CONTROL SYSTEM. (NOTE: THIS IS NOT A ONE SIZE FITS ALL GUIDE.) THE INSTALLATION MAY NEED TO BE MODIFIED TO MEET THE EXISTING CONDITIONS, EXPECTATIONS, OR DEMANDS OF A PARTICULAR SITE. THIS IS A GUIDELINE. ULTIMATELY THE FODS TRACKOUT CONTROL SYSTEM SHOULD BE INSTALLED SAFELY WITH PROPER ANCHORING AND SIGNS PLACED AT THE ENTRANCE AND EXIT TO CAUTION USERS AND OTHERS.

KEY NOTES:

- FODS TRACKOUT CONTROL SYSTEM MAT.
- FODS SAFETY SIGN.
- ANCHOR POINT.
- SILT OR ORANGE CONSTRUCTION FENCE.



Stormwater Management System Components

The Stormwater Management System is designed to mitigate both the quantity and quality of site-generated stormwater runoff. As a result, the design includes the following elements:

Non-Structural BMPs

Non-Structural best management practices (BMP's) include temporary and permanent measures that typically require less labor and capital inputs and are intended to provide protection against erosion of soils. Examples of non-structural BMP's on this project include but are not limited to:

- Temporary and Permanent mulching and grass cover
- Trees, Shrubs and ground covers and landscape plantings
- Dust control
- Sediment barriers; Catch basin bags
- Stabilized construction entrance

Structural BMPs

Structural BMPs are more labor and capital-intensive structures or installations that require more specialized personnel to install. Examples on this project include but are not limited to:

- ACF R-Tank stormwater storage system
- Bio Clean Downspout Filter
- Outlet Control Structures and Storm Drains

Inspection and Maintenance Requirements

The following summarizes the inspection and maintenance requirements for the various BMPs that may be found on this project.


Grassed areas (until established): After each rain event of 0.5" or more during a 24-hour period, inspect grassed areas for signs of disturbance, such as erosion. If damaged areas are discovered, immediately repair the damage. Repairs may include adding new topsoil, lime, seed, fertilizer and mulch.

Plantings: Planting and landscaping (trees, shrubs) shall be monitored bi-monthly during the first year to insure viability and vigorous growth. Replace dead or dying vegetation with new stock and make adjustments to the conditions that caused the dead or dying vegetation. During dryer times of the year, provide weekly watering or irrigation during the establishment period of the first year. Make the necessary adjustments to ensure long-term health of the vegetated covers, i.e. provide more permanent mulch or compost or other means of protection.

Bio Clean Downspout Filter: Refer to the manufacturer's Operation and Maintenance manual for guidance, included herewith.

ACF R-Tank stormwater storage system: Reference the attached operations and maintenance manual for proper maintenance of the system.

Outlet Control Structures and Storm Drains: Monitor accumulation of debris in outlet control structures monthly or after significant rain events. Remove sediments when they accumulate within the outlet pipe. During construction, maintain inlet protection until all roadways and parking areas have been stabilized. Prior to the end of construction, inspect the drains and basins for accumulations and remove and clean by jet-vacuuming.



AMBIT ENGINEERING, INC.
 Civil Engineers & Land Surveyors
 200 Griffin Road - Unit 3
 Portsmouth, N.H. 03801-7114
 Tel (603) 430-9282
 Fax (603) 436-2315


NOTES:

- THE CONTRACTOR SHALL NOTIFY DIG SAFE AT 1-888-DIG-SAFE (1-888-344-7233) AT LEAST 72 HOURS PRIOR TO COMMENCING ANY EXCAVATION ON PUBLIC OR PRIVATE PROPERTY.
- UNDERGROUND UTILITY LOCATIONS ARE BASED UPON BEST AVAILABLE EVIDENCE AND ARE NOT FIELD VERIFIED. LOCATING AND PROTECTING ANY ABOVEGROUND OR UNDERGROUND UTILITIES IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR AND/OR THE OWNER. UTILITY CONFLICTS SHOULD BE REPORTED AT ONCE TO THE DESIGN ENGINEER.
- CONTRACTOR SHALL INSTALL AND MAINTAIN EROSION CONTROL MEASURES IN ACCORDANCE WITH THE "NEW HAMPSHIRE STORMWATER MANUAL, VOLUME 3, EROSION AND SEDIMENT CONTROLS DURING CONSTRUCTION. (NHDES DECEMBER 2008).
- DEER STREET SHALL BE SWEEPED DAILY DURING THE ENTIRE CONSTRUCTION DURATION.
- PROJECT CMPP WILL BE REQUIRED. CONSTRUCTION TEAM TO COORDINATE WITH CITY OF PORTSMOUTH.

SITE DEVELOPMENT
EIGHTKPH, LLC
88 MAPLEWOOD AVENUE
PORTSMOUTH, N.H.

NO.	ISSUED FOR COMMENT	8/23/22
	DESCRIPTION	DATE


REVISIONS




SCALE: AS SHOWN AUGUST 2022

EROSION PROTECTION NOTES AND DETAILS


D1



- NOTES:**
- 1) ALL CONDUIT TO BE U.L. LISTED, SCH. 80 UNDER ALL TRAVEL WAYS, & SCHED. 40 FOR THE REMAINDER.
 - 2) NORMAL CONDUIT SIZES FOR PSNH ARE 3 INCH FOR SINGLE PHASE PRIMARY AND SECONDARY VOLTAGE CABLES, 4 INCH FOR THREE PHASE SECONDARY, AND 5 INCH FOR THREE PHASE PRIMARY.
 - 3) ALL WORK TO CONFORM TO THE NATIONAL ELECTRICAL CODE (LATEST REVISION)
 - 4) INSTALL A 200# PULL ROPE FOR EACH CONDUIT
 - 5) VERIFY ALL CONDUIT SPECIFICATIONS WITH UTILITY COMPANY'S PRIOR TO ANY CONSTRUCTION.




E BURIED ELEC/COMM CABLE
C5 (MAY NOT BE IN SAME TRENCH SEE PLANS) NTS



F TYPICAL PAVEMENT CROSS-SECTION
C3 ON SITE PROPERTY ONLY NTS

CONSTRUCTION NOTE:
EXISTING GRANITE CURB DISTURBED BY CONSTRUCTION SHALL BE REUSED AND ANY MISSING CURB SHALL BE REPLACED WITH NEW CURB MATCHING EXISTING CURB SIZE. NO CURB LESS THAN 3' IN LENGTH WILL BE ALLOWED.



BRICK PAVEMENT NOTES


SCOPE OF WORK:

- 1) THE WORK SHALL CONSIST OF CONSTRUCTING/RECONSTRUCTING THE SUB-BASE AND CONSTRUCTING A NEW BRICK SIDEWALK AS DIRECTED IN THE FIELD BY THE ENGINEER.
- 2) REVEAL SHALL BE 5" (COORDINATE WITH PORTSMOUTH DPW).

METHODS OF CONSTRUCTION:


- A) ALL LABOR AND MATERIALS SHALL CONFORM TO THE STATE OF NEW HAMPSHIRE STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION, SECTION 608, AND CITY OF PORTSMOUTH SPECIFICATIONS FOR NEW BRICK SIDEWALK, SECTION 6.
- B) ALL BRICKS SHALL CONFORM TO THE REQUIREMENTS OF ASTM STANDARD SPECIFICATIONS FOR BUILDING BRICKS: CLASS SX, TYPE 1, APPLICATION PX. THE BRICKS SHALL BE NO. 1, WIRE CUT TYPE FOR PAVING, WITH A COMPRESSIVE STRENGTH OF NOT LESS THAN 6,000 POUNDS PER SQUARE INCH. THE BRICKS SHALL NOT BE CORED OR HAVE FROGS AND SHALL BE OF A STANDARD SIZE (2.25" X 4 X 8").
- C) EXCAVATION FOR SIDEWALKS SHALL BE AT A DEPTH OF 10 INCHES BELOW FINISH GRADE. IN AREAS NOT BUTTING CURBING OR BUILDINGS, THE EXCAVATION SHALL BE 6 INCHES WIDER THAN THE FINISHED SIDEWALK WIDTH. AT ALL DRIVE CROSSINGS, THE DEPTH OF EXCAVATION SHALL BE INCREASED ACCORDINGLY. THE CONTRACTOR SHALL PROVIDE NEAT AND SQUARE CUTTING OF EXISTING ASPHALT ROAD SURFACE AS NEEDED. ALL UNSUITABLE MATERIAL SHALL BE REMOVED AND DISPOSED OF OFF-SITE AT THE CONTRACTOR'S OWN EXPENSE.
- D) THE BASE MATERIAL SHALL CONSIST OF A MIXTURE OF STONES OR ROCK FRAGMENTS AND PARTICLES WITH 100% PASSING THE 3 INCH SIEVE, 95% TO 100% PASSING THE 2 INCH SIEVE, 55% TO 85% PASSING THE 1 INCH SIEVE, AND 27% TO 52% PASSING THE NO. 4 SIEVE. AT LEAST 50% OF THE MATERIALS RETAINED ON THE 1 INCH SIEVE SHALL HAVE A FRACTURED FACE. THE BASE MATERIAL SHALL BE THOROUGHLY COMPACTED TO THE DEPTH SPECIFIED OR DIRECTED. IN THE WAY OF ALL DRIVE CROSSINGS THE BASE WILL BE INCREASED TO A COMPACTED DEPTH OF 12 INCHES. GRAVEL REQUIREMENTS FOR RECONSTRUCTION WILL BE AS DIRECTED, BASED ON SITE CONDITIONS. THE WORK INCLUDES BACKING UP ANY AND ALL CURB BEING INSTALLED BY OTHERS ON BOTH SIDES.
- E) THE CLAY BRICK PAVERS SHALL BE LAID IN A 1 INCH BED OF A SAND MIXTURE COMPRISED OF: 3 PARTS SAND MIXED WITH 1 PART PORTLAND CEMENT.
- F) THE CONTRACTOR SHALL LAY THE BRICKS SO THAT APPROXIMATELY 5.2 BRICKS SHALL COVER ONE SQUARE FOOT.
- G) THE SIDEWALK SHALL PITCH TOWARDS THE STREET AS SHOWN ON THE GRADING PLAN.
- H) IN AREAS WHERE THE FRONT OF THE BRICK SIDEWALK IS NOT ADJACENT TO GRANITE CURBING, THE CONTRACTOR SHALL INSTALL EDGING TO HOLD THE BRICKS IN PLACE. SUCH EDGING SHALL BE INSTALLED PER THE MANUFACTURER'S RECOMMENDATIONS.
- I) THE CONTRACTOR SHALL SUBMIT A SAMPLE OF THE BRICKS FOR APPROVAL BY THE CITY BEFORE BRICKS ARE INSTALLED.
- J) 2" BITUMINOUS PAVING LAYER MAY BE SUBSTITUTED WITH 2" COMPACTED GRAVEL ON SITE AREAS THAT ARE PRIVATE PROPERTY AND NOT IN PUBLIC EASEMENT AREAS INCLUDING COMMUNITY SPACE.

G BRICK SIDEWALK w/ VERTICAL GRANITE CURB
C3 (STONE DUST BEDDING OVER BITUMINOUS PAVING) NTS





NOTES:
1. CURB RAMPS MUST HAVE A DETECTABLE WARNING FEATURE EXTENDING THE FULL WIDTH OF THE RAMP. A HEIGHT OF NOMINAL 0.2", THE DETECTABLE SURFACE MUST CONSIST OF RAISED TRUNCATED SPACING OF NOMINAL 2.35". THE TEXTURE OF THE DETECTABLE WARNING FEATURE MUST CONTRAST VISUALLY WITH THE SURROUNDING SURFACES (LIGHT-ON-DARK OR DARK-ON-LIGHT).
2. DETECTABLE WARNING SURFACE SHALL BE IRON PANEL TO FILL THE SPACE SHOWN ON THE SITE PLAN.

H DETECTABLE WARNING SURFACE
C3 24" WIDE NTS



I GRANITE CURBING DETAILS
C3 WHERE AND IF SPECIFIED NTS



- NOTES:**
1. See sheet "Requirements for Padmounted Transformer Slab Details".
 2. All reinforcing to be #6 bars.
 3. 1" PVC conduit sleeve for ground grid leads.
 4. The ground grid shall be supplied and installed by the customer and is to be buried at least 12" below grade. Eight feet of extra wire for each ground grid leg shall be left exposed in the cable compartment to allow for the connection to the transformer. The two 8" ground rods may be either galvanized steel or copperweld and they shall be connected to the grid with NEC approved connectors.

J TRANSFORMER PAD
C5 EVERSOURCE NTS

AMBIT ENGINEERING, INC.
Civil Engineers & Land Surveyors
200 Griffin Road - Unit 3
Portsmouth, N.H. 03801-7114
Tel (603) 430-9282
Fax (603) 436-2315

- NOTES:**
- 1) THE CONTRACTOR SHALL NOTIFY DIG SAFE AT 1-888-DIG-SAFE (1-888-344-7233) AT LEAST 72 HOURS PRIOR TO COMMENCING ANY EXCAVATION ON PUBLIC OR PRIVATE PROPERTY.
 - 2) UNDERGROUND UTILITY LOCATIONS ARE BASED UPON BEST AVAILABLE EVIDENCE AND ARE NOT FIELD VERIFIED. LOCATING AND PROTECTING ANY ABOVEGROUND OR UNDERGROUND UTILITIES IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR AND/OR THE OWNER. UTILITY CONFLICTS SHOULD BE REPORTED AT ONCE TO THE DESIGN ENGINEER.
 - 3) CONTRACTOR SHALL INSTALL AND MAINTAIN EROSION CONTROL MEASURES IN ACCORDANCE WITH THE "NEW HAMPSHIRE STORMWATER MANUAL, VOLUME 3, EROSION AND SEDIMENT CONTROLS DURING CONSTRUCTION. (NHDES DECEMBER 2008).


SITE DEVELOPMENT
EIGHTKPH, LLC
88 MAPLEWOOD AVENUE
PORTSMOUTH, N.H.

NO.	DESCRIPTION	DATE
1	DETAIL G	9/6/22
0	ISSUED FOR COMMENT	8/23/22

STATE OF NEW HAMPSHIRE
JOHN CHAGNON
No. 7851
LICENSED PROFESSIONAL ENGINEER

SCALE: AS SHOWN AUGUST 2022


DETAILS **D2**




AMBIT ENGINEERING, INC.
Civil Engineers & Land Surveyors
200 Griffin Road - Unit 3
Portsmouth, N.H. 03801-7114
Tel (603) 430-9282
Fax (603) 436-2315

NOTES:

- 1) THE CONTRACTOR SHALL NOTIFY DIG SAFE AT 1-888-DIG-SAFE (1-888-344-7233) AT LEAST 72 HOURS PRIOR TO COMMENCING ANY EXCAVATION ON PUBLIC OR PRIVATE PROPERTY.
- 2) UNDERGROUND UTILITY LOCATIONS ARE BASED UPON BEST AVAILABLE EVIDENCE AND ARE NOT FIELD VERIFIED. LOCATING AND PROTECTING ANY ABOVEGROUND OR UNDERGROUND UTILITIES IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR AND/OR THE OWNER. UTILITY CONFLICTS SHOULD BE REPORTED AT ONCE TO THE DESIGN ENGINEER.
- 3) CONTRACTOR SHALL INSTALL AND MAINTAIN EROSION CONTROL MEASURES IN ACCORDANCE WITH THE "NEW HAMPSHIRE STORMWATER MANUAL, VOLUME 3, EROSION AND SEDIMENT CONTROLS DURING CONSTRUCTION." (NHDES DECEMBER 2008).




K SMALL BLOCK RETAINING WALL
C3 GENEST - BRUSSELS - UNILOCK WALL
COORDINATE COLOR WITH OWNER NTS




L CATCH BASIN INLET BASKET
C6 NTS

- 1) INLET BASKETS SHALL BE INSTALLED IMMEDIATELY AFTER CATCH BASIN CONSTRUCTION IS COMPLETE AND SHALL REMAIN IN PLACE AND BE MAINTAINED UNTIL PAVEMENT BINDER COURSE IS COMPLETE.
- 2) FILTER FABRIC SHALL BE PUSHED DOWN AND FORMED TO THE SHAPE OF THE BASKET. THE SHEET OF FABRIC SHALL BE LARGE ENOUGH TO BE SUPPORTED BY THE BASKET FRAME WHEN HOLDING SEDIMENT AND, SHALL EXTEND AT LEAST 6" PAST THE FRAME. THE INLET GRATE SHALL BE PLACED OVER THE BASKET/FRAME AND WILL SERVE AS THE FABRIC ANCHOR.
- 3) THE FILTER FABRIC SHALL BE A GEOTEXTILE FABRIC; POLYESTER, POLYPROPYLENE, STABILIZED NYLON, POLYETHYLENE, OR POLYVINYLIDENE CHLORIDE MEETING THE FOLLOWING SPECIFICATIONS:
-RAB STRENGTH: 45 LB. MIN. IN ANY PRINCIPAL DIRECTION (ASTM D1682)
-MULLEN BURST STRENGTH: MIN. 60 psi (ASTM D774)
- 4) THE FABRIC SHALL HAVE AN OPENING NO GREATER THAN A NUMBER 20 U.S. STANDARD SIEVE AND A MINIMUM PERMEABILITY OF 120 gpm/s.f. (MULTIPLY THE PERMITTIVITY IN SEC.-1 FROM ASTM 54491-85 CONSTANT HEAD TEST USING THE CONVERSION FACTOR OF 74.)
- 5) THE INLET BASKET SHALL BE INSPECTED WITHIN 24 HOURS AFTER EACH RAINFALL OR DAILY DURING EXTENDED PERIODS OF PRECIPITATION. REPAIRS SHALL BE MADE IMMEDIATELY, AS NECESSARY, TO PREVENT PARTICLES FROM REACHING THE DRAINAGE SYSTEM AND/OR CAUSING SURFACE FLOODING.
- 6) SEDIMENT DEPOSITS SHALL BE REMOVED AFTER EACH STORM EVENT OR MORE OFTEN IF THE FABRIC BECOMES CLOGGED.




- TRENCH NOTES:**
- A) TRENCH BACKFILL:
- IN PAVED AREAS, SUITABLE MATERIAL FOR TRENCH BACKFILL SHALL BE THE NATURAL MATERIAL EXCAVATED DURING CONSTRUCTION, BUT SHALL EXCLUDE DEBRIS, PIECES OF PAVEMENT, ORGANIC MATTER, TOP SOIL, ALL WET OR SOFT MUCK, PEAT OR CLAY, ALL EXCAVATED LEDGE MATERIAL, AND ALL ROCKS OVER SIX INCHES IN LARGEST DIMENSION, OR ANY MATERIALS DEEMED TO BE UNACCEPTABLE BY THE ENGINEER.
 - IN CROSS-COUNTRY CONSTRUCTION, SUITABLE MATERIAL SHALL BE AS DESCRIBED ABOVE, EXCEPT THAT THE ENGINEER MAY PERMIT THE USE OF TOP SOIL, LOAM, MUCK OR PEAT, IF HE IS SATISFIED THAT THE COMPLETED CONSTRUCTION WILL BE ENTIRELY STABLE.
 - B) "W" = MAXIMUM ALLOWABLE TRENCH WIDTH TO A PLANE 12 INCHES ABOVE THE PIPE. FOR PIPES 15 INCHES NOMINAL DIAMETER OR LESS, W SHALL BE NO MORE THAN 36 INCHES. FOR PIPES GREATER THAN 15 INCHES NOMINAL DIAMETER, W SHALL BE 24 INCHES PLUS PIPE O.D..
 - C) TRENCH SHEETING:
THE CONTRACTOR IS SOLELY RESPONSIBLE FOR SAFE EXCAVATION PRACTICES.
 - D) MINIMUM PIPE COVER FOR UTILITY MAINS (UNLESS GOVERNED BY OTHER CODES):
5" MINIMUM FOR SEWER (IN PAVEMENT)
4" MINIMUM FOR SEWER (CROSS COUNTRY)
3" MINIMUM FOR STORMWATER DRAINS
5" MINIMUM FOR WATER MAINS
 - E) ALL PAVEMENT CUTS SHALL BE REPAIRED BY THE INFRARED HEAT METHOD.


M TYPICAL PIPE TRENCH
C5 NTS




N CATCH BASIN OUTLET HOOD
C6 THE "SNOUT" NTS



O TYPICAL SIDEWALK TIP DOWNS
C3 NTS




- GENERAL NOTES:**
- CONCRETE SPECIFICATIONS:**
- 1) 4000 PSI @ 28 DAYS.
 - 2) 4%-6% ENTRAINED AIR.
 - 3) TANK PENETRATIONS ARE INTEGRALLY CAST.
 - 4) ALL JOINTS SEALED WITH BUTYL RESIN.
 - 5) EXTERIOR TO BE COATED.
- GREASE TRAP INFORMATION:**
- 1) TANKS SHOULD BE PUMPED AS NEEDED.
 - 2) ACCESS COVERS SHOULD HAVE RISERS TO BRING COVER ACCESS TO GRADE.
 - 3) TANKS CAN BE VACUUM TESTED AT AN ADDITIONAL COST.



P SHEA CONCRETE
C5 1000 GALLON 2 COMP. GREASE TRAP
14,825 Lbs ITEM # M1000H H20 LOAD RATED NTS



SITE DEVELOPMENT
EIGHTKPH, LLC
88 MAPLEWOOD AVENUE
PORTSMOUTH, N.H.

NO.	DESCRIPTION	DATE
2	DETAIL K	10/20/22
1	DETAIL O & P	9/6/22
0	ISSUED FOR COMMENT	8/23/22




SCALE: AS SHOWN AUGUST 2022

DETAILS **D3**



CATCH BASIN DETAIL

NTS



R-TANK SYSTEM	
1. BASE STONE STORAGE NOT INCLUDED IN VOLUMES.	
2. COVER STONE STORAGE NOT INCLUDED IN VOLUMES.	
R-TANK MODULE TYPE	DOUBLE
TRAFFIC LOAD	PEDESTRIAN
# OF DOUBLE R-TANKS	40
TOTAL SYSTEM STORAGE	604.7 CF
R-TANK STORAGE VOLUME	330.1 CF
STONE STORAGE VOLUME (40% VOID RATIO)	274.6 CF
TOP OF COVER STONE ELEV. (12")	11.93
ACF BX-12 GEOGRID ELEV.	11.93
TOP OF R-TANK ELEV.	10.93
TANK INVERT IN	10.16
INVERT OF STONE BASE (3") OUT	7.86
MIN. STONE PERIMETER WIDTH 2.0 FT	2.0 FT
SYSTEM IS 27.46 FT LONG BY 9.25 FT WIDE, INCLUDING APRON	

GENERAL NOTES:

- MINIMUM PIPE SIZE FOR HOME SERVICES SHALL BE SIX INCHES.
- PIPE AND JOINT MATERIALS:
 - PIPE AND FITTINGS SHALL CONFORM TO THE FOLLOWING ASTM STANDARDS:

ASTM STANDARDS	GENERIC PIPE MATERIAL	SIZES APPROVED
D3034	*PVC (SOLID WALL)	8" THROUGH 15" (SDR 35)
F679	PVC (SOLID WALL)	18" THROUGH 27" (T-1 & T-2)
F789	PVC (SOLID WALL)	4" THROUGH 18" (T-1 TO T-3)
F794	PVC (RIBBED WALL)	8" THROUGH 36"
AWWA C900	PVC (SOLID WALL)	8" THROUGH 18"

 *PVC: POLYVINYL CHLORIDE
 - JOINT SEALS FOR PVC PIPE SHALL BE OIL RESISTANT COMPRESSION RINGS OF ELASTOMERIC MATERIAL CONFORMING TO ASTM D-3212 AND SHALL BE PUSH-ON BELL AND SPIGOT TYPE.
 - DUCTILE IRON PIPE, FITTINGS AND JOINTS.
 - DUCTILE IRON PIPE AND FITTINGS FOR SEWERS SHALL CONFORM TO THE FOLLOWING STANDARDS OF THE UNITED STATES OF AMERICA STANDARDS INSTITUTE:

A21.50	THICKNESS DESIGN OF DUCTILE IRON PIPE AND WITH ASTM A-536 DUCTILE IRON CASTINGS.
A21.51	DUCTILE IRON PIPE, CENTRIFUGALLY CAST IN METAL MOULDS OR SAND LINED MOULDS FOR SEWER APPLICATIONS.
 - JOINTS SHALL BE OF THE MECHANICAL OR PUSH ON TYPE. JOINTS AND GASKETS SHALL CONFORM TO:

A21.11	RUBBER GASKET JOINTS FOR CAST IRON PRESSURE PIPE & FITTINGS.
--------	--
- DAMAGED PIPE SHALL BE REJECTED AND REMOVED FROM THE JOB SITE.
- JOINTS SHALL BE DEPENDENT UPON A NEOPRENE OR ELASTOMERIC GASKET FOR WATER TIGHTNESS. ALL JOINTS SHALL BE PROPERLY MATCHED WITH THE PIPE MATERIALS USED. WHERE DIFFERING MATERIALS ARE TO BE CONNECTED, AS AT THE STREET SEWER WYE OR AT THE FOUNDATION WALL, APPROPRIATE MANUFACTURED ADAPTERS SHALL BE USED.
- TEES AND WYES: WHERE A TEE OR WYE IS NOT AVAILABLE IN THE EXISTING STREET SEWER, AN APPROPRIATE CONNECTION SHALL BE MADE DEPENDING ON THE PIPE ENCOUNTERED, FOR PVC PIPE, USE PVC SADDLES OR INSERT-A-TEE, OR CUT IN A SANITARY TEE. FOR CLAY PIPE, USE INSERT-A-TEE OR CUT IN A SANITARY TEE. ALL WORK TO BE APPROVED BY GOVERNING BODY.
- HOUSE SEWER INSTALLATION: THE PIPE SHALL BE HANDLED, PLACED AND JOINTED IN ACCORDANCE WITH INSTALLATION GUIDES OF THE APPROPRIATE MANUFACTURER. IT SHALL BE CAREFULLY BEDDED ON A 4 INCH LAYER OF CRUSHED STONE AND/OR GRAVEL AS SPECIFIED IN NOTE 10. BEDDING AND REFILL FOR DEPTH OF 12 INCHES ABOVE THE TOP OF THE PIPE SHALL BE CAREFULLY AND THOROUGHLY TAMPED BY HAND OR WITH APPROPRIATE MECHANICAL DEVICES. THE PIPE SHALL BE LAID AT A CONTINUOUS AND CONSTANT GRADE FROM THE STREET SEWER CONNECTION TO THE FOUNDATION AT A GRADE OF NOT LESS THAN 1/4 INCH PER FOOT. PIPE JOINTS MUST BE MADE UNDER DRY CONDITIONS. IF WATER IS PRESENT, ALL NECESSARY STEPS SHALL BE TAKEN TO DEWATER THE TRENCH.
- TESTING: WHEN REQUIRED BY THE GOVERNING AUTHORITY, TESTING SHALL CONFORM TO ENV-WQ 704.07.
- ILLEGAL CONNECTIONS: NOTHING BUT SANITARY WASTE FLOW FROM DWELLING TOILETS, SINKS, LAUNDRY ETC. SHALL BE PERMITTED. ROOF LEADERS, FOOTING DRAINS, SUMP PUMPS OR OTHER SIMILAR CONNECTIONS CARRYING RAIN WATER, DRAINAGE OR GROUND WATER SHALL NOT BE PERMITTED.
- WATER SERVICE SHALL NOT BE LAID IN SAME TRENCH AS SEWER SERVICE, UNLESS IT IS ON A SHELF 12" HIGHER, AND 18" APART.



GENERAL NOTES- CONT'D:

- BEDDING: SCREENED GRAVEL AND/OR CRUSHED STONE, FREE FROM CLAY, LOAM, ORGANIC MATTER AND MEETING ASTM C33 STONE SIZE NO. 67.

100% PASSING	1 INCH SCREEN
90%-100% PASSING	3/4 INCH SCREEN
20%- 55% PASSING	3/8 INCH SCREEN
0%- 10% PASSING	#4 SIEVE
0%- 5% PASSING	#8 SIEVE


 WHERE ORDERED BY THE ENGINEER TO STABILIZE THE TRENCH BASE, GRADED SCREENED GRAVEL OR CRUSHED STONE 1/2 INCH TO 1-1/2 INCH SHALL BE USED.
- LOCATION: THE LOCATION OF THE TEE OR WYE SHALL BE RECORDED AND FILED IN THE MUNICIPAL RECORDS. IN ADDITION, A FERROUS METAL ROD OR PIPE SHALL BE PLACED OVER THE TEE OR WYE AS DESCRIBED IN THE TYPICAL "CHIMNEY" DETAIL, TO AID IN LOCATING THE BURIED PIPE WITH A DIP NEEDLE OR PIPE FINDER.
- CAST-IN-PLACE CONCRETE: SHALL CONFORM TO THE REQUIREMENTS FOR CLASS A (3000 PSI) CONCRETE OF THE NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION STANDARD SPECIFICATIONS AS FOLLOWS:

CEMENT:	6.0 BAGS PER CUBIC YARD
WATER:	5.75 GALLONS PER BAG OF CEMENT
MAXIMUM AGGREGATE SIZE:	3/4 INCH
- CHIMNEYS: IF VERTICAL DROP INTO SEWER IS GREATER THAN 4 FEET, A CHIMNEY SHALL BE CONSTRUCTED FOR THE HOUSE CONNECTION OR MAIN. CHIMNEY INSTALLATION AS RECOMMENDED BY THE PIPE MANUFACTURER MAY BE USED IF APPROVED BY THE ENGINEER.
- BACKFILL UP TO SUBBASE GRAVEL SHALL BE WITH EXCAVATED SOIL FROM TRENCHING OPERATIONS. COMPACT IN 8" LIFTS WITH VIBRATORY PLATE COMPACTORS TO 90% OF MODIFIED PROCTOR DENSITY. IF FINE-GRAINED, COMPACT WITH POGO STICKS OR SHEEPSFOOT ROLLERS. PLACE NO LARGE ROCKS WITHIN 24" OF PIPE. TRENCHES THAT ARE NOT ADEQUATELY COMPACTED SHALL BE RE-EXCAVATED AND BACKFILLED UNDER THE SUPERVISION OF THE DESIGN ENGINEER OR GOVERNING BODY. UNSUITABLE BACKFILL MATERIAL INCLUDES CHUNKS OF PAVEMENT, TOPSOIL, ROCKS OVER 6" IN SIZE, MUCK, PEAT OR PIECES OF PAVEMENT.
- THE CONTRACTOR IS SOLELY RESPONSIBLE FOR JOB-SITE SAFETY AND COMPLIANCE WITH GOVERNING REGULATIONS.
- ORDERED EXCAVATION OF UNSUITABLE MATERIAL BELOW GRADE. REFILL WITH BEDDING MATERIAL. FOR TRENCH WIDTHS SEE TRENCH DETAIL.
- SAND BLANKET: CLEAN SAND, FREE FROM ORGANIC MATTER, SO GRADED THAT 90% - 100% PASSES A 1/2 INCH SIEVE AND NOT MORE THAN 15% WILL PASS A #200 SIEVE. BLANKET MAY BE OMITTED FOR DUCTILE IRON AND REINFORCED CONCRETE PIPE PROVIDED THAT NO STONE LARGER THAN 2 INCHES IS IN CONTACT WITH THE PIPE.
- BASE COURSE GRAVEL, IF ORDERED BY THE ENGINEER, SHALL MEET THE REQUIREMENTS OF DIVISION 500 OF THE LATEST EDITION OF THE STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION OF THE STATE OF NEW HAMPSHIRE, DEPARTMENT OF TRANSPORTATION.
- FOR CROSS COUNTRY CONSTRUCTION, BACKFILL OR FILL SHALL BE MOUND TO A HEIGHT OF 6 INCHES ABOVE THE ORIGINAL GROUND SURFACE.
- IF FULL ENCASEMENT IS UTILIZED, DEPTH OF CONCRETE BELOW PIPE SHALL BE 1/4 I.D. (4" MIN.) BLOCK SUPPORT SHALL BE SOLID CONCRETE BLOCKS.
- CONTRACTOR SHALL INSTALL AND MAINTAIN EROSION CONTROL MEASURES IN ACCORDANCE WITH THE "NEW HAMPSHIRE STORMWATER MANUAL, VOLUME 3, EROSION AND SEDIMENT CONTROLS DURING CONSTRUCTION. (NHDES DECEMBER 2008).
- THE CONTRACTOR SHALL NOTIFY DIG SAFE AT 1-888-DIG-SAFE (1-888-344-7233) AT LEAST 72 HOURS PRIOR TO COMMENCING ANY EXCAVATION.
- THE PURPOSE OF THESE NOTES IS TO DETAIL STANDARDS FOR SEWER CONSTRUCTION.
- ALL WORK SHALL BE IN COMPLIANCE WITH NHDES CODE OF ADMINISTRATIVE RULES PART ENV-WQ 704 DESIGN OF SEWERS.



BIKE RACK
OPTIONAL VERSION

NTS




SEWER SERVICE CONNECTION DETAIL

NTS

NOTE: COORDINATE DESIGN OF SEWER CONNECTION WITH CITY OF PORTSMOUTH DPW. PROVIDE SHOP DRAWINGS FOR REVIEW.

SITE DEVELOPMENT
EIGHTKPH, LLC
88 MAPLEWOOD AVENUE
PORTSMOUTH, N.H.

NO.	DESCRIPTION	DATE
2	DETAIL R & S	10/20/22
1	PIPE SIZES; DETAIL T	9/6/22
0	ISSUED FOR COMMENT	8/23/22
REVISIONS		




SCALE: AS SHOWN AUGUST 2022

DETAILS

D4

SERVICE MANUAL (Cleaning Procedures)

Bio Clean DOWNSPOUT FILTER Screen Type With Hydrocarbon Boom



TOOLS AND EQUIPMENT NEEDED:

1. Medium size flat screed driver
2. BioSorb hydrocarbon boom. 25-1/2" X 2" dia. (Call Bio Clean to order)
3. Trash container or bag
4. Wooden dowel approx. 3' x 1/2" dia.


DETAIL OF PARTS




P.O. BOX 869, Oceanside, Ca. 92049
(760) 433-7640 Fax (760) 433-3176
www.biocleanenvironmental.net

PAGE 1 OF 5

REMOVING FILTER




CLEANING FILTER



PAGE 2 OF 5

REPLACING FILTER INSERT



PAGE 3 OF 5


R-TANK SYSTEM

STEP-BY-STEP INSPECTION & MAINTENANCE ROUTINE

- 1) INSPECTION
 - A. INSPECTION PORT
 1. REMOVE CAP
 2. USE FLASHLIGHT TO DETECT SEDIMENT DEPOSITS
 3. IF PRESENT, MEASURE SEDIMENT DEPTH WITH STADIA ROD
 4. RECORD RESULTS ON MAINTENANCE LOG
 5. REPLACE CAP
 - B. MAINTENANCE PORT/S
 1. REMOVE CAP
 2. USE FLASHLIGHT TO DETECT SEDIMENT DEPOSITS
 3. IF PRESENT, MEASURE SEDIMENT DEPTH WITH STADIA ROD
 4. RECORD RESULTS ON MAINTENANCE LOG
 5. REPLACE CAP
 6. REPEAT FOR ALL MAINTENANCE PORTS
 - C. ADJACENT MANHOLES
 1. REMOVE COVER
 2. USE FLASHLIGHT TO DETECT SEDIMENT DEPOSITS
 3. IF PRESENT, MEASURE SEDIMENT DEPTH WITH STADIA ROD, ACCOUNTING FOR DEPTH OF SUMP (IF PRESENT)
 4. INSPECT PIPES CONNECTING TO R-TANK
 5. RECORD RESULTS ON MAINTENANCE LOG
 6. REPLACE COVER
 7. REPEAT FOR ALL MANHOLES THAT CONNECT TO THE R-TANK
- 2) MAINTENANCE
 - A. PLUG SYSTEM OUTLET TO PREVENT DISCHARGE OF BACK-FLUSH WATER
 - B. DETERMINE BEST LOCATION TO PUMP OUT BACK-FLUSH WATER
 - C. REMOVE CAP FROM MAINTENANCE PORT
 - D. PUMP WATER AS RAPIDLY AS POSSIBLE (WITHOUT OVER-TOPPING PORT) INTO SYSTEM UNTIL AT LEAST 1" OF WATER COVERS SYSTEM BOTTOM.
 - E. REPLACE CAP
 - F. REPEAT AT ALL MAINTENANCE PORTS
 - G. PUMP OUT BACK-FLUSH WATER TO COMPLETE BACK-FLUSHING
 - H. VACUUM ALL ADJACENT STRUCTURES AND ANY OTHER STRUCTURES OR STORMWATER PRE-TREATMENT SYSTEMS THAT REQUIRE ATTENTION.
 - I. SEDIMENT-LADEN WATER MAY BE CAPTURED FOR DISPOSAL OR PUMPED THROUGH A DIRTBAG™.
 - J. REPLACE ANY REMAINING CAPS OR COVERS
 - K. RECORD THE BACK-FLUSHING EVENT IN YOUR MAINTENANCE LOG WITH ANY RELEVANT SPECIFICS

APPROPRIATE INSTALLATION


FILTER CENTERED BETWEEN PIPES WITH EVEN GAPS ON TOP AND BOTTOM



P.O. BOX 869, Oceanside, Ca. 92049
(760) 433-7640 Fax (760) 433-3176
www.biocleanenvironmental.net

PAGE 5 OF 5

REPLACING FILTER



PAGE 4 OF 5



AMBIT ENGINEERING, INC.
Civil Engineers & Land Surveyors
200 Griffin Road - Unit 3
Portsmouth, N.H. 03801-7114
Tel (603) 430-9282
Fax (603) 436-2315

NOTES:


- 1) THE CONTRACTOR SHALL NOTIFY DIG SAFE AT 1-888-DIG-SAFE (1-888-344-7233) AT LEAST 72 HOURS PRIOR TO COMMENCING ANY EXCAVATION ON PUBLIC OR PRIVATE PROPERTY WITHIN 100 FEET OF UNDERGROUND UTILITIES. THE EXCAVATOR IS RESPONSIBLE TO MAINTAIN MARKS. DIG SAFE TICKETS EXPIRE IN THIRTY DAYS.
- 2) UNDERGROUND UTILITY LOCATIONS ARE BASED UPON BEST AVAILABLE EVIDENCE AND ARE NOT FIELD VERIFIED. LOCATING AND PROTECTING ANY ABOVEGROUND OR UNDERGROUND UTILITIES IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR AND/OR THE OWNER. UTILITY CONFLICTS SHOULD BE REPORTED AT ONCE TO THE DESIGN ENGINEER.
- 3) CONTRACTOR SHALL INSTALL AND MAINTAIN EROSION CONTROL MEASURES IN ACCORDANCE WITH THE "NEW HAMPSHIRE STORMWATER MANUAL, VOLUME 3, EROSION AND SEDIMENT CONTROLS DURING CONSTRUCTION. (NHDES DECEMBER 2008).
- 4) INSPECTION AND MAINTENANCE REQUIREMENTS
THE FOLLOWING SUMMARIZES THE INSPECTION AND MAINTENANCE REQUIREMENTS FOR THE VARIOUS BMPs THAT MAY BE FOUND ON THIS PROJECT.
GRASSED AREAS (UNTIL ESTABLISHED): AFTER EACH RAIN EVENT OF 0.5" OR MORE DURING A 24-HOUR PERIOD, INSPECT GRASSED AREAS FOR SIGNS OF DISTURBANCE, SUCH AS EROSION. IF DAMAGED AREAS ARE DISCOVERED, IMMEDIATELY REPAIR THE DAMAGE. REPAIRS MAY INCLUDE ADDING NEW TOPSOIL, LIME, SEED, FERTILIZER AND MULCH.
PLANTINGS: PLANTING AND LANDSCAPING (TREES, SHRUBS) SHALL BE MONITORED BI-MONTHLY DURING THE FIRST YEAR TO INSURE VIABILITY AND VIGOROUS GROWTH. REPLACE DEAD OR DYING VEGETATION WITH NEW STOCK AND MAKE ADJUSTMENTS TO THE CONDITIONS THAT CAUSED THE DEAD OR DYING VEGETATION. DURING DRIER TIMES OF THE YEAR, PROVIDE WEEKLY WATERING OR IRRIGATION DURING THE ESTABLISHMENT PERIOD OF THE FIRST YEAR. MAKE THE NECESSARY ADJUSTMENTS TO ENSURE LONG-TERM HEALTH OF THE VEGETATED COVERS, I.E. PROVIDE MORE PERMANENT MULCH OR COMPOST OR OTHER MEANS OF PROTECTION.

BIO CLEAN DOWNSPOUT FILTER: REFER TO THE MANUFACTURER'S OPERATION AND MAINTENANCE MANUAL FOR GUIDANCE, INCLUDED HEREWITH.
ACF R-TANK STORMWATER STORAGE SYSTEM: REFERENCE THE ATTACHED OPERATIONS AND MAINTENANCE MANUAL FOR PROPER MAINTENANCE OF THE SYSTEM.

OUTLET CONTROL STRUCTURES AND STORM DRAINS: MONITOR ACCUMULATION OF DEBRIS IN OUTLET CONTROL STRUCTURES MONTHLY OR AFTER SIGNIFICANT RAIN EVENTS. REMOVE SEDIMENTS WHEN THEY ACCUMULATE WITHIN THE OUTLET PIPE. DURING CONSTRUCTION, MAINTAIN INLET PROTECTION UNTIL ALL ROADWAYS AND PARKING AREAS HAVE BEEN STABILIZED. PRIOR TO THE END OF CONSTRUCTION, INSPECT THE DRAINS AND BASINS FOR ACCUMULATIONS AND REMOVE AND CLEAN BY JET-VACUUMING.

**SITE DEVELOPMENT
EIGHTKPH, LLC
88 MAPLEWOOD AVENUE
PORTSMOUTH, N.H.**

NO.	DESCRIPTION	DATE
0	ISSUED FOR COMMENT	10/20/22
REVISIONS		



SCALE: AS SHOWN AUGUST 2022

DETAILS

D5