



Disk Station DS209+II

High-Performance 2-bay SATA NAS Server for Small-and-Medium Business Users

Key Features

- High Speed 48+ MB/Sec RAID 1 Write 52+ MB/Sec RAID 1 Read
- Windows + Mac + Linux
- Power Saving (14.4W~30W)

Shipped with Disk Station Manager 2.1 that provides:

- AJAX-Based Management Interface
- Windows ADS Support
- Encrypted Network Backup
- Encrypted FTP with Hack Prevention
- Business Mail Server
- Corporate Surveillance
- Schedule Power On/Off

And more...

Synology Disk Station DS209+II offers PC server equivalent performance for efficient data sharing and backup. Its high performance coupled with sophisticated Synology Disk Station Manager 2.1 provides an ideal solution for cross platform sharing, secure server backup, Windows ADS integration, business mail server, and corporate surveillance.

Management & Backup

Synology Disk Station DS209+II supports large-capacity RAID 0 and reliable RAID 1 volume types, Users can also use one hard drive to create a Non-RAID volume and change it to RAID 1 at a later time or expand a RAID 1 volume with larger hard drives.

When User Home is enabled, Synology Disk Station DS209+II automatically creates a home folder for every user account to provide each user with a private space to store data. This eliminates the need for the administrator to repeatedly create shared folders and user accounts.

Synology Network Backup allows users to back up files from one to another Synology Disk Station or any rsynccompatible server, The Local Backup allows backups to external hard drives via USB or eSATA, both providing flexible scheduling options.

Secure File Sharing

Synology File Station 2 simplifies file management with a web browser by introducing Windows-style user's interface and advanced features including drag-n-drop, sub-folder privilege settings, multiple files upload and download, and remote unzip features.

HTTPS provides a secure way for Internet access. When it's enabled, connections to the web-based Web Station, Photo Station 3, File Station 2, Surveillance Station 2, and Audio Station are all secured with SSL/TLS.

FTP service over SSL/TLS encryption ensures file sharing at a high security level. Unicode, write-only and sophisticated bandwidth management are also supported.

Office Applications

Synology Mail Station add-on provides a one step installation and enables Synology Disk Station DS209+II to be a mail server that supports Outlook-like Web mail, SMTP, POP3, and IMAP.

Synology Surveillance Station 2 enables Synology Disk Station DS209+II to be an economical network video recording (NVR) solution. Over 130 popular IP cameras of varying brand names are supported.

Eco Friendly

Synology Disk Station is designed and developed perpetually with the concept of energy saving. Compared with its average PC counterparts, Synology Disk Station DS209+II consumes a relatively low amount of power and hibernates when not in use. This not only helps to save energy but also extends the lifespan of the hard disk.

Additionally, all Synology products are produced with RoHS compliant parts and packed with recyclable packing materials. Synology recognizes its responsibility as a global citizen and is continually working to reduce the environmental impact of the products we create.

CONNECTIONS & BUTTONS



LAN

Technical Specifications

- CPU: 1.06GHz, 64bit@DDR533, with floating point

- CPU: 1.06GHz, 64biteDDR533, with floating poir RAM Size: 512 MB Internal HDD¹⁰: 2X 3.5" SATA(II) or 2X 2.5" SATA/ SSD using Synology. 2.5" Disk Holder Type B External HDD Interface: 3X USB 2.0 ports, 1X eSATA port

- Size: 16 Imm X 218mm X 88mm
 Weight: 0.38kg
 LAN: 1X Gigabit
 Fan: 1X (70mmX70mm)
 Noise Level⁽²⁾: 24 dB(A)
 Power Recovery
 AC Input Power Voltage: 100V to 240V
- Power Frequency: 50Hz to 60Hz, Single Phase

- Power Frequency: 50Hz to 60Hz, Single Phase Max HDD Support (Internal HDD): 4TB™

 Max Supported IP Camera #79: 10

 Operating Temperature: 5°C to 35°C (40°F to 95°F)

 Storage Temperature: -10°C to 70°C (15°F to 155°F)

 Relative Humidity: 5% to 95°SRH

Maximum Operating Altitude: 10,000 feet

Power Consumption⁽³⁾
- 30W (Access); 14.4W (Hibernation)

Certification
FCC Class B, CE Class B, BSMI Class B

Networking Protocols

- AFP (3.1)
- Telnet/SSH

Windows ADS Domain Integration

- ADS Support

 Domain users login via Samba/AFP/FTP

 Synology Data Replicator 3 for Domain Users

- Security
 FTP over SSL/TLS (explicit)
- FTP Auto-Block
- Encrypted Network Backup
 Encrypted rsync
 HTTPS Connection

File System

- FAT (External Disk Only) NTFS (External Disk Read Only)

- File Sharing

 Max User Accounts: 2,048

 Max Groups: 256

 Max Shared Folder: 256

- Max Concurrent Connections (SAMBA, FTP. AFP): 256

Utilities

- Synology Assistant
 Synology Data Replicator 3
 Synology Download Redirector
 Add Printer Wizard

- Surveillance Station 2
- Photo Station 3
- File Station 2 Audio Station
- Web Station
- PHP/MySQL Download Station 2 iTunes Server

Packages - Mail Station

- SqueezeCenter Webalizer

- PnP Multimedia Service Support Sony PS3, Microsoft Xbox360 Audio Format: AAC, FLAC, M4A, MP3, Ogg Vorbis,
- WAV, WMA, WMA VBR, WMA PRO, WMA Lossless
- WAY, WMA, WMA YEK, WMA FRO, WMA LOSSIESS VIdeo Format: ASF, AVI, DAT, DIVX, MP4, MPEG1, MPEG2, MPEG4, VOB, WMV, XvID Image Format: BMP, JPG (jpe, jpeg), GIF, ICO, PNG, PSD, TIF (tiff), UFO Playlist Format: WPL, M3U

- Subtitle: srt, psb, smi, ass, ssa, sub, idx, ifo

- iTunes Server Support
 Audio Format: MP3, M4A, M4P, WAV⁽⁴⁾, AIF⁽⁴⁾
 Playlist Format: M3U, WPL

- Audio Station Support
- USB Mode: (Audio) AAC, FLAC, M4A, MP3, Ogg Vorbis, WMA, WMA VBR (Playlist) M3U, WPL (Internet Radio) SHOUTcast, Radioio
- Streaming Mode: (Audio) MP3 (Playlist) M3U, WPL

- Photo Station 3 Support
 Video Format: ASF, AVI, MPEG1, MPEG4, WMV, XviD, DivX, FLV, DAT(s), MP4(s), MPEG2(s), RM(s),

- RMVB(5), VOB(5) Image Format: BMP, JPG (jpe, jpeg), GIF

- Management
 AJAX-based Management UI
 BitTorrent Port Range Setup
 BitTorrent DHT Support
- CIFS Recycle Bin
- Download Station Bandwidth control
- Download Station Bandwidth contro Download Station Port Range Setup Editable HTTP Error Page Email Alert Message Email Notification for New User Package Management

- External HDD Hibernation Scheduled Power On/Off

- Scheduled Power On/Off Firmware Upgrade FTP passive port range Hide-able Shared Folder Internal HDD Hibernation Removable Default Shared Folder
- Ez-Internet PPPoE
- UPS Management (Over USB 2.0) User Quota Web-based Download Station

- RAID Management
 Volume Type: Basic, JBOD, RAID 0, RAID 1
- RAID change: Basic to RAID 1

• Expand with Larger Hard Drives: RAID 1

Backup Solutions

- Network Backup
- Local Backup Desktop Backup (using Synology Data Replicator)
- 3rd-Party Backup Support

Supported Clients

- Windows 2000 onward Mac OS X 10.3 onward

- Printer Support⁽⁶⁾
 Max Printer #: 2
 Supported Protocols: LPR, CIFS, AppleTalk

English, Danish, Dutch, Norwegian, Swedish, German, French, Italian, Polish, Russian, Spanish, Korean, Traditional Chinese, Simplified Chinese, Hungarian, Turkish, Portuguese Brazil,

Portuguese European

Environment RoHS Compliant

- Package Content
 DS209+II Main Unit
 Installation CD
- Welcome Note Assembling Kit

- ASSEMBLING KIT
 AC Power Adapter
 AC Power Cord
 2M RJ-45 LAN Cable
 2X SATA Hard Drive Power Cable
 2X SATA Hard Drive Data Cable

(1) Hard drive not included.
(2) FAN only, Measured at 2300–6200RPM, varied among models. More details about dR(A) value, check http://www.quietnoise.com/facts.htm (3) Measured with 2 Seagate 750GB 573750640NS hard drive. The figures could vary on different environments.
(4) The music can be streamed, but the metadata (ex: title, album) may not be indexed on the Tlunes. (5) User can click and download the file, but not play it in Photo Station 3 as compressed Flash video. (6) For Mac users, DS209+II supports PostScript USB printers only.

printers only. (7) 1 free license to install 1 IP camera. Additional licenses can be purchased to expand the license quota.
(8) The actual capacity will differ according to volume

SYNOLOGY INC.

Founded in 2000, Synology is a young and energetic company dedicated to developing high-performance, reliable, versatile, and environmentally-friendly Network Attached Storage (NAS) products. Our goal is to deliver user-friendly solutions and solid ustomer service to satisfy the needs of businesses, home offices, individual users and families.

Copyright © 2009, Synology Inc. All rights reserved. Synology, the Synology logo are trademarks or registered trademarks of Synology Inc. Other product and company names mentioned herein may be trademarks of their respective companies. Synology may make changes to specification and product descriptions at anytime, without notice. Printed in Taiwan, DS209+II-2009-ENU-REV001

http://www.synology.com

3F-3, No. 106, Chang An W. Rd., Taipei, Taiwa Tel: 886 2 2552 1814 Fax: 886 2 2552 1824

