



H87M-P32 (MS-7846v1.1) m-ATX Motherboard

Support Intel® Haswell processors for LGA 1150 socket





Motherboard Specification

Processor Support

■ Support Intel® Haswell processors for LGA 1150 socket

Base Clock

■ 100 MHz/125

Chipset

■ Intel® H87 chipset

Memory Support

- Support 2 DDR3 DIMMs1066/ 1333/ 1600 MHz up to 32GB max
- Supports Dual-Channel mode

LAN

■ Supports LAN 10/100/1000 Fast Ethernet by Realtek® RTL8111E

Audio

- Chip integrated by Realtek® ALC887
- Flexible 8-channel audio with jack sensing
- Compliant with Azalia 1.0 Spec

SATA

■ 4 SATA 6Gb/s (SATA1~SATA4) ports by Intel® H87

USB 3.0

■ 4 USB 3.0 ports by Intel® H87 (rear x 2, front x 2)

Connectors

- Back panel
 - 1 PS/2 mouse port
 - 1 PS/2 keyboard port
 - 2 USB 2.0 ports
 - 2 USB 3.0 ports
 - 1 VGA port
 - 1 serial port
 - 1 parallel port
 - 1 LAN port
- 3 flexible audio ports
- On-Board
 - 2 USB 2.0 connectors
 - 1 USB 3.0 connector
 - 1 Chassis Intrusion connector
 - 1 Front Panel Audio connector
 - 1 TPM Module connector1 Serial connector
- Slots
- 1 PCIE x16 slot
- 1 PCIE x1 slot
- 2 PCI slots

Form Factor

■ m-ATX (243 x 228 mm)

Feature on Focus

- All Solid Cap design
- Click BIOS İV
- Super Charger
- M-Flash
- SATA 6Gb/s
- USB 3.0

Mounting

■ 6 mounting holes

These specification is subject to change without prior notice.