

2610+
High performance at low cost



HIGHLIGHTS AT A GLANCE:

- Print speed up to 683 cps
- Up to 20.000 pages/month
- 24 wires print head for excellent print quality
- Straight paper path for easy paper handling
- Metal tear bar
- Ethernet with IPv6 support, parallel and USB interface as standard
- SB Host interface for easy firmware-update
- • User-friendly, backlit illuminated LC display

2610+

The new Tally Dascom 2610+ is the **further developed variant** of the successful Tally Dascom 2600.

Thanks to the two-part upper cover, the printed pages can now be removed even more easily from the end of the book. A **metal tear bar** ensures that even thicker paper or multiple sets are separated cleanly. The **durable ribbon for 15 million characters** can easily be replaced. The new ribbon mask ensures that the ribbon is inserted correctly. In addition to the standard interfaces **USB, Parallel and Ethernet** (with IPv6 support), the Tally Dascom 2600+ now also has a **USB host interface**, so that new firmware can easily be installed with the help of a USB stick.

The new print head is not only **up to 20% faster**, but also allows for a **noise reduction of up to 2 decibels** thanks to its design.

TECHNICAL DATA

Print speed	683 cps (Fastest Draft); 600 cps (HS-Draft), 513 cps (Draft), 114 cps (LQ) bei 10 cpi
Resolution	Up to 360 x 360 dpi
Throughput (ECMA 132)	457 pages per hour
Character density	10, 12, 15, 17.1, 20 cpi
Line density	2, 3, 4, 6, 8, 12 lpi
Print head lifetime	500 Mio. impact per wire
RAM	256 kB
Interface Standard	Parallel (Bi-directional), USB 2.0 and Ethernet (10/100BaseT, IPv6) USB Host
Interface Optional	Serial RS-232
Administration	Tally WebPanel via Ethernet; Config-Tool via USB/Parallel
Emulations Standard	IBM ProPrinter XL24, Epson ESC P/2, MTPL + Barcode + LCP Epson FX 9-Nadel Emulation
Fonts	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 14 Barcodes and large character printing
Consumables	Ribbon: 15 Mio. characters
Paper handling Standard	One tractor usable as push (front or rear) or pull (top) version, continuous paper with straight paper path and park position, cut sheet front insertion, tear or front off
Paper handling Optional	Additional push tractor (rear)
Copies	Push tractor front: 1 original + 5 copies; Pull tractor top: 1 original + 5 copies; Cut sheet: 1 original + 5 copies
Paper types	Cut sheets, continuous forms, multi-part forms
Paper weight	60-120 g/m ²
Paper format	Width: 76 to 420 mm; Length: 76 to 599 mm
Weight	10,6 kg
Dimensions	600 x 265 x 200 mm (W x D x H)
Noise	<53 dB(A)
Voltage	100 - 240 V autosensing
Power consumption	60 Watt printing; <3 W Sleep Mode
Temperature	+10° to +40° C; 10% to 85% rel. humidity
Print volume	20.000 pages per month
MTBF	20.000 hours
Driver	Windows 7/8/10 and Server 2008/2012 (32/64 Bit); SAP

Configuration:

- **2610+** Standard model

DASCOM GB Ltd
Hart House, Priestley Road
Basingstoke | Hampshire RG24 9PU | ENGLAND
Tel.: +44 1256 355 130 | Fax: +44 1256 481 400
info.gb@dascom-com | www.dascom.co.uk

DASCOM Europe GmbH
Heuweg 3 | 89079 Ulm | GERMANY
Tel.: +49 731 2075-0 | Fax: +49 731 2075-100
info@dascom.com | www.dascomeurope.de

DASCOM (Holdings) LTD.
R. 1811-1816A | Nan Fung Centre
264-298 Castle Peak Road | Tuen Wan, N. T. | Hong Kong
Tel.: +852 2498 1507 | Fax: +852 2413 6047