

Overview



- | | |
|---|---|
| <ul style="list-style-type: none"> 8. 3 External 5.25" Bays 9. 3 Internal 3.5" Bays 10. 8 DIMM Slots for DDR3 ECC Memory 11. 600W, 90% Efficient Power Supply 12. Rear I/O: Rear Power Button & LED, PS/2 Ports, 1 1394a, 4 USB 2.0, 2 USB 3.0, 1 RJ-45 to Integrated GbE, 1 Audio Line In, 1 Audio Line Out, 1 Microphone | <ul style="list-style-type: none"> 13. Intel Xeon Processors E5-1600 family (4C/6C) or E5-2600 family (8C) 14. 2 PCIe x16 Gen3 Slots 15. 1 PCIe x8 Gen3, 1 PCIe x8(x4) Gen2, 1 PCIe x4(x1) Gen2, 1 PCI Slot 16. 6 Internal USB 2.0 Ports 17. 10 SATA Ports |
|---|---|

Form Factor	Convertible Minitower
Operating Systems	Preinstalled: <ul style="list-style-type: none"> • Windows 7 Ultimate 64-Bit • Windows 7 Professional 32-Bit

Overview

- Windows 7 Professional 64-Bit
- Windows 8 Pro 64-bit
- Windows 8 (China) 64-bit
- Windows 8 Pro Downgrade to Windows 7 32-bit
- Windows 8 Pro Downgrade to Windows 7 64-bit
- SUSE Linux Enterprise Desktop 11 (90 day license)
- HP Installer Kit for Linux (includes drivers for 64-bit OS versions of RHEL 5 & 6 and SUSE Linux Enterprise Desktop 11)
- Red Hat Enterprise Linux Desktop (Preinstall NOT available; 1 year paper license only)

Supported:

- Genuine Windows® 7 Enterprise 32/64
- Windows® XP Professional 32/64 (on select configurations)*

Notes: *See the "Windows XP Support Matrix for Z Workstations" at: http://www.hp.com/support/workstation_manuals

Notes: For detailed OS/hardware support information for Linux, see: http://www.hp.com/support/linux_hardware_matrix

Available Processors

Name	Cores	Clock Speed (GHz)	Cache (MB)	Memory Speed (MHz)	QPI Speed (GT/s)	Hyper-Threading	Featuring Intel® vPro™ Technology	Intel® Turbo Boost Technology ¹	TDP (W)
Intel® Xeon® E5-2687W processor	8	3.1	20	1600	8.0	Y	Y	3, 7	150
Intel Xeon E5-2665 processor	8	2.4	20	1600	8.0	Y	Y	4, 7	115
Intel Xeon E5-1660 processor	6	3.3	15	1600	-	Y	Y	3, 6	130
Intel Xeon E5-1650 processor	6	3.2	12	1600	-	Y	Y	3, 6	130
Intel Xeon E5-1620 processor	4	3.6	10	1600	-	Y	Y	2, 3	130
Intel Xeon E5-1607 processor	4	3.0	10	1066	-	N	Y	N/A	130
Intel Xeon E5-1603 processor	4	2.8	10	1066	-	N	Y	N/A	130

¹The specifications shown in this column represent the following: (all core maximum turbo steps, one core maximum turbo steps). Turbo boost stepping occurs in 100MHz increments. Processors that do not have turbo functionality are denoted as N/A.

NOTE: Although the Intel Xeon E5-2600 processor family supports dual processors, the HP Z420 Workstation does not support dual processor configurations.

Available Processor Disclaimers

Intel's numbering is not a measurement of higher performance. Processor numbers differentiate features within each processor family, not across different processor families. See: http://www.intel.com/products/processor_number/ for details.
64-bit computing on Intel® 64 architecture requires a computer system with a processor, chipset, BIOS, operating system, device drivers and applications enabled for Intel 64 architecture. Processor will not operate (including 32-bit operation) without an Intel 64 architecture-enabled BIOS. Performance will vary depending on your hardware and software configurations. See: <http://www.intel.com/info/em64t> for more

Overview

	<p>information. Quad-Core, Six-Core, and Eight-Core technologies are designed to improve performance of multithreaded software products and hardware-aware multitasking operating systems and may require appropriate operating system software for full benefits. Check with software provider to determine suitability. Not all customers or software applications will necessarily benefit from use of these technologies.</p>
Color	Jack Black
Convertibility	Yes. 5.25" drives rotate for Minitower or Desktop orientation.
Expansion Slots (see system board section for more details)	<p>Slot 1 (top): PCI Express Gen2 x4(1)* Full-height, Full-length</p> <p>Slot 2: PCI Express Gen3 x 16 Full-height, Full-length (with extender)</p> <p>Slot 3: PCI Express Gen2 x 8(4)* with open-ended connector** Full-height, Full-length (with extender)</p> <p>Slot 4: PCI Express Gen3 x8 with open-ended connector** Full-height, Full-length (with extender)</p> <p>Slot 5: PCI Express Gen3 x16 Full-height, Full-length (with extender)</p> <p>Slot 6: PCI 32bit/33MHz Full-height, Full-length (with extender)</p> <p>* x<number> = number of lanes or size of the physical/mechanical connector. (number) = number of lanes supported electrically. Typically communicated as x# mechanical, x(#)electrical.</p> <p>** open-ended connector allows a greater bandwidth (e.g. x16) card to be installed physically into a lower bandwidth connector/slot.</p>
Expansion Bays (see storage section for more details)	<p>3 internal 3.5" bays (with acoustic dampening rail assemblies pre-installed) 3 external 5.25" bays (4th HDD occupies one external bay)</p> <p>Top and Middle 5.25" bay device depth limit: 206mm (8.11 inches)</p> <p>Bottom 5.25" bay device depth limit: 173mm (6.81 inches)</p>
Front I/O	2 USB 3.0, 1 USB 2.0, 1 IEEE 1394a standard, 1 Headphone, 1 Microphone
Internal I/O	6 USB 2.0 ports available by three separate 2x5 headers. Each 2x5 header supports either one HP Internal USB Port Kit (EM165AA) or one 22-in-1 Media Card Reader.
Rear I/O	2 USB 3.0, 4 USB 2.0, 1 IEEE 1394a port, 2 PS/2, RJ-45 (NIC), 1 Audio Line-In, 1 Audio Line-Out, 1 Microphone. Serial supported with optional connector on PCI bracket cabled to system board connector

Overview

Interfaces Supported	22-in-1 Media Card Reader (optional) 10-channel SATA interface (2 @ 6.0 Gb/s, 8 @ 3.0 Gb/s). 6 channels are eSATA configurable (2 @ 6Gb/s, 4 @ 3Gb/s) for use with eSATA CTO/AMO Kit. USB 2.0, USB 3.0, IEEE 1394a interface	
Chassis Dimensions (HxWxD)	Standard minitower orientation: 44.76 x 17.78 x 44.52 cm (17.6 x 7.0 x 17.5 in) Converted desktop orientation: 17.9 x 44.76 x 44.52 cm (7.0 x 17.6 x 17.5 in)	
Weight	Exact weights depend upon configuration. Minimum: 12.5kg (27.5 lbs) Standard: 13.2kg (29.2 lbs) Maximum: 17.7kg (39 lbs)	
Temperature	Operating:	5° to 35°C (40° to 95°F)
	Non-operating	-40° to 60°C (-40° to 140°F)
Humidity	Operating:	8% to 85% relative humidity, non-condensing
	Non-operating	8% to 90% relative humidity, non-condensing
Maximum Altitude (non-pressurized)	Operating:	3,048m (10,000ft)
	Non-operating	9,144m (30,000ft)
Power Supply	600 watts wide-ranging, active Power Factor Correction, 90% Efficient The Z420 600W power supply efficiency report can be found at this link: http://www.plugloadsolutions.com/psu_reports/HEWLETT_PACKARD_623193-001_ECOS_2619_1_600W_Report.pdf	
Workstation ISV Certifications	See the latest list of certifications at http://www.hp.com/united-states/campaigns/workstations/partnerships.html	

Supported Components

Processors

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
Intel Xeon E5-2600 Series - CTO				
Intel® Xeon® Processor E5-2687W 8C 3.10GHz	Y	N		See note 1
Intel® Xeon® Processor E5-2665 8C 2.40GHz	Y	N		
Intel Xeon E5-1600 Series				
Intel® Xeon® Processor E5-1660 6C 3.30GHz	Y	N		
Intel® Xeon® Processor E5-1650 6C 3.20GHz	Y	N		
Intel® Xeon® Processor E5-1650 6C 3.20GHz	Y	N		
Intel® Xeon® Processor E5-1620 4C 3.60GHz	Y	N		
Intel® Xeon® Processor E5-1607 4C 3.00GHz	Y	N		
Intel® Xeon® Processor E5-1603 4C 2.80GHz	Y	N		

NOTE 1: HP Liquid Cooling option available for all the above processors. HP Liquid Cooling option is required on the E5-2687W processor model.

NOTE 2: Intel's numbering is not a measurement of higher performance.

Monitors / Displays

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
HP DreamColor LP2480zx Professional Display				
HP ZR30w 30-inch S-IPS LCD Monitor				
HP ZR2740w 27-inch LED Backlit IPS Monitor				
HP ZR2440w 24-inch LED Backlit IPS Monitor				
HP ZR2240w 21.5-inch LED Backlit IPS Monitor				
HP ZR2040w 20-inch LED Backlit IPS Monitor				
Supported by all operating systems available from HP				
Screen size measured diagonally				

Hard Drives

Sub-Section Description/Notes

Up to (4) 3.5-inch 15K rpm SAS drives: 300, 450, 600 GB; 2.4 TB max

Up to (4) 2.5-inch 10K rpm SAS drives: 300, 600 GB; 2.4 TB max

NOTE: SAS controller add-in card required

NOTE: 4th SFF HDDs will be automatically installed into the top optical bay in a Handle/HDD carrier

Removable Boot Drive option

Supported Components

SAS Hard Drives

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
HP SAS (Serial Attached SCSI) Hard Drives for HP Workstations				
600GB SAS 15K rpm 6Gb/s 3.5" HDD	Y	Y	VM647AA	
450GB SAS 15K rpm 6Gb/s 3.5" HDD	Y	Y	LU968AA	
300GB SAS 15K rpm 6Gb/s 3.5" HDD	Y	Y	LU967AA	
HP 600GB SAS 10K SFF HDD	Y	Y	A2Z21AA	
HP 300GB SAS 10K SFF HDD	Y	Y	A2Z20AA	

Sub-Section Description/Notes

Up to (4) 3.5-inch 7200 rpm SATA drives: 250, 500 GB, 1.0, 2.0, 3.0 TB; 12.0 TB max

Up to (4) 2.5-inch 10K rpm SATA drives: 250, 500 GB, 1.0 TB; 4.0 TB max

Up to (1) 2.5-inch SATA Self-Encrypting Drive (SED): 500 GB

NOTE: 3.0 TB drive not available as HDD1 due to GPT restrictions

Removable Boot Drive option

SATA Hard Drives

SATA (Serial ATA) Hard Drives for HP Workstations

250GB SATA 7200 rpm 6Gb/s 3.5" HDD	Y	Y	LQ034AA	
500GB SATA 7200 rpm 6Gb/s 3.5" HDD	Y	Y	LQ036AA	
1TB SATA 7200 rpm 6Gb/s 3.5" HDD	Y	Y	LQ037AA	
2.0TB SATA 7200 rpm 6Gb/s 3.5" HDD	Y	Y	QB576AA	
3.0TB SATA 7200 rpm 6Gb/s 3.5" HDD	Y	Y	QF298AA	
250GB SATA 10K rpm SFF HDD	Y	Y	B8X18AA	
500GB SATA 10K rpm SFF HDD	Y	Y	B8X19AA	
1TB SATA 10K rpm SFF HDD	Y	Y	B8X20AA	
500GB SATA 7.2K SED SFF HDD	Y	N		

Sub-Section Description/Notes

Up to (4) 2.5-inch SATA Solid State Drives: (Micron 6Gb/s) 128, 256 GB: 1TB max; (Intel 3Gb/s) 160, 300 GB: 1.2 TB max

Up to (1) 2.5-inch SATA Self-Encrypting Solid State Drive (SED SSD): (Micron 6Gb/s) 256 GB

NOTE: 4th SSDs will be automatically installed into the top optical bay in a Handle/HDD carrier

SATA Solid State Drives

HP Solid State Drives (SSDs) for Workstations

HP 256GB SATA 6Gb/s SSD	Y	Y	A3D26AA	
HP 128GB SATA 6Gb/s SSD	Y	Y	A3D25AA	
HP 300GB SATA 3Gb/s SSD	Y	Y	LZ069AA	
HP 160GB SATA 3Gb/s SSD	Y	Y	LZ704AA	
HP 256GB SATA 6Gb/s SED SSD	Y	N		

Supported Components

For hard drives, 1 GB = 1 billion bytes; TB = 1 trillion bytes. Actual formatted capacity is less.

Hard Drive Controllers

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
Integrated SATA 6.0 Gb/s Controller				
Integrated SATA 6.0 Gb/s Controller	Y	N		Two ports
Integrated SATA 3.0 Gb/s Controller				
Integrated SATA 3.0 Gb/s Controller	Y	N		Eight ports
Factory integrated RAID on motherboard for SATA drives				
RAID 0 Configuration - Striped Array	Y	N		Note 1
RAID 0 Data Configuration -- Boot/OS Drive + 2 Drive Striped Array	Y	N		Note 1
RAID 1 Configuration - Mirrored Array	Y	N		Note 1
RAID 10 Configuration - Striped/Mirrored Array	Y	N		Note 1
LSI 9212 4-Port SAS 6Gb/s RAID Card				
LSI 9212 4-Port SAS 6Gb/s RAID Card	Y	Y	XP310AA	Note 2
LSI MegaRAID® 9260-8i SAS 6Gb/s ROC RAID Card and iBBU08 Battery Backup Unit				
LSI MegaRAID® 9260-8i SAS 6Gb/s ROC RAID Card	N	Y	WE465AA	Note 2
Optional: LSI iBBU08 Battery Backup Unit for LSI 9260-8i	N	Y	LA783AA	

SATA hardware RAID is supported on Linux systems that have support for the Intel RSTe technology. The Linux kernel, with built-in software RAID, provides excellent functionality and performance. It is a good alternative to hardware-based RAID. Please visit http://www.hp.com/support/linux_hardware_matrix for RAID capabilities with Linux.

All drives must be identical in type and capacity.
RAID arrays greater than 2 TB are fully supported.

NOTE 1: Requires hard drives with identical speed, capacity, and interface. Specific user-configured hardware SAS RAID configurations are supported on this Linux system. For details, please visit http://www.hp.com/support/linux_hardware_matrix

NOTE 2: Specific user-configured hardware SAS RAID configurations are supported on this Linux system. IS: Striping of 2 or more HDDs into a single logical volume

IM: Mirroring of 2 HDDs into a single logical volume

IME: Mirroring of 3 or more HDDs into a single logical volume.

For details, please visit http://www.hp.com/support/linux_hardware_matrix

Supported Components

Graphics

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes	Supported # of cards	Mixed?
Professional 2D						
NVIDIA NVS300 512MB Graphics	Y	Y	XP612AA	Note 1	3	NO
NVIDIA NVS 310 512MB Graphics	Y	Y	A7U59AA	Note 1	3	YES
NVIDIA NVS 510 2GB Graphics	Y	Y	C2J98AA	Note 4	2	YES
Entry 3D						
NVIDIA Quadro 410 512MB Graphics	Y	Y	A7U60AA		2	NO
NVIDIA Quadro K600 1GB Graphics	Y	Y	C2J92AA		2	NO
NVIDIA Quadro 600 1GB Graphics	Y	Y	WS093AA		2	NO
AMD FirePro V3900 1GB Graphics	Y	Y	A6R69AA		2	NO
Mid-range 3D						
NVIDIA Quadro K2000 2GB Graphics	Y	Y	C2J93AA		2	NO
NVIDIA Quadro 2000 1GB Graphics	Y	Y	WS094AA		2	NO
High End 3D						
AMD FirePro W7000 4GB Graphics	Y	Y	C2K00AA	Note 3	1	NO
AMD FirePro V7900 2GB Graphics	Y	Y	LS993AA	Note 3	1	NO
NVIDIA Quadro K4000 3GB Graphics	Y	Y	C2J94AA		1	NO
NVIDIA Quadro 4000 2GB Graphics	Y	Y	WS095AA		1	NO
NVIDIA Quadro K5000 4GB Graphics	Y	Y	C2J95AA	Note 3	1	NO
NVIDIA Quadro 6000 6GB Graphics	N	Y	WS097AA	Note 3	1	NO

Note 1: When configuring with a 3rd NVS 300 or NVS 310, the configuration requires the Z4 Fan and Front Card Guide Kit, which is available both CTO (QE150AV) and AMO (A2Z46AA).

Note 2: If 1st graphics card is NVS 510 then 2nd graphics card must be NVS 510 or NVS 310.

Note 3: Configuration requires the Z4 Fan and Front Card Guide Kit, which is available both CTO (QE150AV) and AMO (A2Z46AA).

High Performance GPU Computing

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
NVIDIA Tesla C2075 Compute Processor	Y	Y	QB035AA	Notes 1, 2

NOTE 1: Tesla C2075 does not have an operational graphics output.

All Tesla configurations require the addition of either NVIDIA Quadro 600 1st graphics or NVIDIA Quadro 2000 1st graphics.

NOTE 2: All Tesla configurations require the Z4 Fan and Front Card Guide Kit, which is available both CTO (QE150AV) and AMO (A2Z46AA).

Supported Components

Memory	CTO	Option Kit Part Number	Support Notes
	DDR3-1600 ECC Unbuffered DIMMs - CTO		
	8GB DDR3-1600 ECC Unbuffered RAM		
	4GB DDR3-1600 ECC Unbuffered RAM		
	2GB DDR3-1600 ECC Unbuffered RAM		
	Sub-Section Description/Notes		
	For details on the supported memory configurations on the HP Z420 Workstation, please refer to the System Technical Specifications - System Board section of this document.		
	Each processor supports up to 4 channels of DDR3 memory. To realize full performance at least 1 DIMM must be inserted into each channel.		
	The CPUs determine the speed at which the memory is clocked. If a 1066MHz capable CPU is used in the system, the maximum speed the memory will run at is 1066MHz regardless of the specified speed of the memory.		
	AMO		
	DDR3-1600 ECC Unbuffered DIMMs - AMO		
	HP 8GB (1x8GB) DDR3-1600 ECC RAM	A2Z50AA	
	HP 4GB (1x4GB) DDR3-1600 ECC RAM	A2Z48AA	
	HP 2GB (1x2GB) DDR3-1600 ECC RAM	A2Z47AA	
	NOTE: Only unbuffered DDR3 DIMMs are supported.		

Multimedia and Audio Devices

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
Integrated Intel/Realtek HD ALC262 Audio	Y	N		
HP Thin USB Powered Speakers	Y	Y	KK912AA	
Creative Recon3D PCIe Audio Card	Y	Y	B0U68AA	

Supported Components

Optical and Removable Storage

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
HP 16X DVD-ROM SATA Drive (non Lightscribe)	Y	Y	AR629AA	Note 1
HP 16X DVD+/-RW SuperMulti SATA Drive (non-Lightscribe)	Y	Y	QS208AA	
HP Blu-ray Writer	Y	Y	AR482AA	Note 2
HP 22-in-1 Media Card Reader Kit (Workstations)	Y	Y	NK361AA	
HP CMT Handle in Top Optical Bay	Y	Y	A9A48AA	Note 3

Actual speeds may vary. Does not permit copying of commercially available DVD movies or other copyright protected materials. Intended for creation and storage of your original material and other lawful uses. Double Layer discs can store more data than single layer discs. However, double-layer discs burned with this drive may not be compatible with many existing single-layer DVD drives and players.

As Blu-ray is a new format containing new technologies, certain disc, digital connection, compatibility and/or performance issues may arise, and do not constitute defects in the product. Flawless playback on all systems is not guaranteed. In order for some Blu-ray titles to play, they may require a DVI or HDMI digital connection and your display may require HDCP support. HD-DVD movies cannot be played on this workstation.

NOTE 1: Not supported as a 2nd drive option.

NOTE 2: Cannot be ordered in combination with another Blu-ray Writer.

NOTE 3: The HP CMT Handle in Top Optical Bay kit, which contains two SFF internal drive bays, is installed automatically when customers order a 4th SFF hard drive.

Controller Cards

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
HP IEEE 1394b FireWire PCIe Card	Y	Y	NK653AA	

Supported Components

Networking and Communications

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
Integrated Intel 82579LM PCIe GbE Controller	Y	N		
Intel Gigabit CT Desktop NIC	Y	Y	FH969AA	Note 1
Broadcom NetXtreme Gigabit Ethernet Plus NIC (PCIe)	Y	Y	FS215AA	Notes 1 & 2
HP 361T PCIe Dual Port Gigabit NIC	N	Y	C3N37AA	Note 1
HP Wireless NIC 802.11b/g/n PCIe Card	N	Y	FH971AA	
HP X520 10GbE Dual Port Adapter	Y	Y	C3N52AA	
HP 10GbE SFP+ SR Transceiver	Y	Y	C3N53AA	

NOTE 1: Gigabit Ethernet indicates compliance with IEEE standard 802.3ab for Gigabit Ethernet and does not connote actual operating speed of 1 Gb/sec. For high speed transmission, connection to a Gigabit Ethernet server and network infrastructure is required.

NOTE 2: This is a PCI Express card based on the Broadcom 5761 chip. This card does not support DASH 1.1 manageability on this platform.

Racking and Physical Security

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
HP Solenoid Hood Lock & Hood Sensor	Y	Y	DE618A	
HP Business PC Security Lock Kit	N	Y	PV606AA	
HP xw4/Z2/Z4 Depth Adjustable Fixed Rail Rack Kit	N	Y	WH340AA	

Input Devices

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
HP PS/2 Standard Keyboard	Y	Y	DT527A	
HP USB Standard Keyboard	Y	Y	DT528A	
HP PS/2 Optical Scroll Mouse	Y	Y	EY703AA	
HP USB 2-Button Optical Scroll Mouse	Y	Y	DC172B	
HP USB Laser Mouse	Y	Y	GW405AA	
HP USB Optical 3-Button Mouse	Y	Y	DY651A	
HP USB Smart Card Keyboard	N	Y	ED707AA	
HP 2.4GHz Wireless Keyboard & Mouse	N	Y	NB896AA	
HP USB Optical 3-Button 2.9M OEM Mouse	N	Y	ET424AA	
HP SpaceExplorer 3D USB Controller	N	Y	RY429AA	
HP SpacePilot 3D USB Intelligent Controller	N	Y	WH343AA	
HP PS/2 Keyboard	Y	Y	QY774AA	
HP PS/2 Mouse	Y	Y	QY775AA	
HP USB Keyboard	Y	Y	QY776AA	
HP USB Optical Mouse	Y	Y	QY777AA	

Supported Components

HP USB 1000dpi Laser Mouse	Y	Y	QY778AA
----------------------------	---	---	---------

Product numbers QY774AA-QY778AA represent the new 2012 products with the updated product design. The previous models will be phased out over time

Other Hardware

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
HP Z420 Front Memory Duct	Y	Y	C4J29AA	Note 1
HP Z420 Handle in Top Optical Bay	Y	Y	A9A48AA	
HP Z4 Fan and Front Card Guide Kit	Y	Y	A2Z46AA	
HP Serial Port Adapter	Y	Y	PA716A	
HP eSATA PCI Cable Kit	Y	Y	GM110AA	
HP Internal USB Port Kit	N	Y	EM165AA	Note 2
HP Optical Bay HDD Mounting Bracket	N	Y	NQ099AA	
HP Power Cord Kit	N	Y	DM293A	
Configure minitower in desktop orientation	Y	N		
HP Workstation Mouse Pad	Y	N		Japan only
HP Energy Star Enabled Configuration	Y	N		

Note 1: The HP Z420 Front Memory Duct is available to add to any configuration for improved system cooling, but is required for 4 x 8GB and 8 x 8GB memory configurations and for configurations including the HP Liquid Cooling Solution thermal kit.

Note 2: The HP Internal USB Port kit has a single USB 2.0 type A connector.

Software

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
HP Performance Advisor	Y	Y		Note 1
HP Remote Graphics Software (RGS) V5	Y	N		Note 2
HP ProtectTools Security	Y	N		Note 3
Buy Office	Y	N		Note 4
HP Power Assistant	Y	N		
PDF Complete - Corporate Edition	Y	N		
Cyberlink PowerDVD / Power2Go	Y	N		Media playback/authoring software

NOTE 1: Available as a free download here: www.hp.com/go/performanceadvisor

NOTE 2: Supports both 32 and 64 bit versions of Windows 7 Professional and Enterprise, Windows XP Professional and Enterprise, and RHEL V6

NOTE 3: Must select as a Configure to Order option. Delivered as a "Drop in the Box" CD

NOTE 4: Must select as a Configure to Order option

Supported Components

Operating Systems

Support Notes

Windows 8 Pro 64-bit

Windows 8 (China) 64-bit

Windows 8 Pro Downgrade to Windows 7 32-bit

Windows 8 Pro Downgrade to Windows 7 64-bit

Genuine Windows® 7 Ultimate 64-bit

Note 1

Genuine Windows® 7 Professional 32-bit

Note 1

Genuine Windows® 7 Professional 64-bit

Note 1

SUSE Linux Enterprise Desktop 11

HP Linux Installer Kit

Red Hat Enterprise Linux (RHEL) Workstation - Paper License (1yr)

Note 2

NOTE 1: See <http://www.microsoft.com/windows/windows-7/> for support details.

NOTE 2: This second OS must be ordered with the HP Linux Installer Kit as the first OS.

System Technical Specifications

System Board	
System Board Form Factor	ATX 243.84 x 304.8 mm (9.6 x 12 inches)
Processor Socket	Single LGA2011
CPU Bus Speed	QPI: Up to 8.0GT/sec
Chipset	Intel® C602 Chipset
Super I/O Controller	Nuvoton NPCD379H (SIO-12)
Memory Expansion Slots	8 DDR3 memory slots
Memory Type Supported	DDR3, UDIMM (Unbuffered), ECC
Memory Modes	Channel Interleaved
Memory Speed Supported	1066MHz, 1333MHz, and 1600MHz DDR3
Memory Protection	ECC available on data, parity on address and command
Memory	
Memory Configuration Table	Please refer to the table below for details on how supported memory configurations are installed in your system.

Capacity (GB)	Type	Front Slots				Rear Slots			
		DIMM 1	DIMM 2	DIMM 3	DIMM 4	DIMM 5	DIMM 6	DIMM 7	DIMM 8
2	UDIMM	2GB							
4	UDIMM	2GB							2GB
6	UDIMM	2GB		2GB					2GB
8	UDIMM	2GB		2GB			2GB		2GB
12	UDIMM	4GB		4GB					4GB
16	UDIMM	2GB	2GB	2GB	2GB	2GB	2GB	2GB	2GB
16	UDIMM	4GB		4GB			4GB		4GB
32	UDIMM	4GB	4GB	4GB	4GB	4GB	4GB	4GB	4GB
32	UDIMM	8GB		8GB			8GB		8GB
64	UDIMM	8GB	8GB	8GB	8GB	8GB	8GB	8GB	8GB
Slot Load Order		1	5	3	7	8	4	6	2

For a detailed diagram, please refer to the label located on the inside of the system side panel.

Maximum Memory	Supports up to 64GB
Memory Configuration (Supported)	Only ECC DIMMs are supported.
Note on Maximum Memory	*Maximum memory capacities assume 64-bit operating systems such as Genuine Windows® 7 Ultimate 64-bit or Genuine Windows® 7 Professional 64-bit. Genuine Windows® 7 Professional 32-bit supports up to 4GB. Linux 32-bit supports up to 8GB.
PCI Express Connectors	2 x16 PCIe Gen3 1 x8 PCIe Gen3 1 x8 PCIe (x4) Gen2 1 x4 PCIe (x1) Gen2

System Technical Specifications

PCI Connectors (5.0V)	1 PCI	
Supported Drive Interfaces	SATA	Integrated 10-channel SATA interface (2@6Gb/s, 8@3Gb/s). Supports RAID 0, 1, 5, 10 and NCQ. Factory integrated RAID is Microsoft Windows only.
	Integrated RAID	NOTE: Requires identical hard drives (speeds, capacity, interface)
Integrated Graphics	No	
Network Controller	Integrated Intel 82579 Gbit LAN Supports the following management functionalities: Intel AMT7.0, TXT, DASH 1.1, WOL, and PXE 2.1	
External SATA (eSATA)	6 ports are eSATA configurable with optional eSATA After-Market Option cable kit.	
IDE connector	No	
Floppy connector	No	
Serial	1 internal header	
2nd Serial	No	
Parallel	No	
AUX IN (audio)	No	
IEEE 1394 Connector(s)	Front	1 IEEE 1394a standard
	Rear	1 IEEE 1394a standard; 2 IEEE 1394b (requires optional PCIe card)
	Internal	No
USB Connector(s)	Front	2 USB 3.0 1 USB 2.0
	Rear	2 USB 3.0 4 USB 2.0
	Internal	6 USB 2.0 ports available by three separate 2x5 headers: each header supports either a HP Internal USB Port Kit or USB Media Card Reader, one on each header. Each Internal Port Kit has two USB 2.0 connectors.
HD Integrated Audio	Realtek ALC262	
Flash ROM	Yes	
CPU Fan Header	Yes	
Chassis Fan Header	1 Rear System Chassis Fan Header	
Front PCI Fan Header	Yes	
Front Control Panel/Speaker Header	Yes	
CMOS Battery Holder - Lithium	Yes	
Integrated Trusted Platform Module	Integrated TPM 1.2	
Power Supply Headers	Yes	
Power Switch, Power LED & Hard Drive LED Header	Yes	
Clear Password Jumper	Yes	
Serial Port	1 internal header	

System Technical Specifications

Parallel Port	No
Keyboard/Mouse	USB or PS/2

Power Supply

Power Supply	600W 90% Efficient, Custom PSU (Wide Ranging, Active PFC)	
Operating Voltage Range	90–269 VAC	
Rated Voltage Range	100–240 V	118 V
Rated Line Frequency	50–60 Hz	400 Hz
Operating Line Frequency Range	47–66 Hz	393–407 Hz
Rated Input Current	100–240 V @ 8.0 A	118 V @ 8.0 A
Heat Dissipation	Typical: 1365btu/hr (344 kg-cal/hr) Maximum: 2354btu/hr (593 kg-cal/hr)	
Power Supply Fan	92x25 mm variable speed	
ENERGY STAR Qualified (Configuration dependent)	Yes	
80 PLUS® Compliant	90% Efficient The Z420 600W power supply efficiency report can be found at this link: http://www.pluginloadsolutions.com/psu_reports/HEWLETT_PACKARD_623193-001_ECOS_2619_1_600W_Report.pdf	
FEMP Standby Power Compliant @115V (Wake-on LAN disabled) (<2W in S5 - Power Off)	Yes	
EuP Compliant @ 230V (<1 W in S5 - Power Off)	Yes	
CECP Compliant @ 220V (<4W in S3 - Suspend to RAM)	Yes; Configuration dependent	
Power Consumption in sleep mode (as defined by ENERGY STAR) - Suspend to RAM (S3) (Instantly Available PC) measured at 115V.	<10W	
Built-in Self Test LED	Yes	
Surge Tolerant Full Ranging Power Supply (withstands power surges up to 2000V)	Yes	

Hood Lock Header	Yes
Hood Sensor Header	Yes
Memory Fan	1 Memory Fan Header

System Technical Specifications

System Configurations							
Example Configuration #1 (ENERGY STAR QUALIFIED)	Processor Info	1x Intel Xeon E5-1603 (Quad-Core)					
	Memory Info	1x 2GB DDR3 1600 (UDIMM)					
	Graphics Info	1x NVIDIA NVS 300					
	Disks/Optical/Floppy	1x 250GB SATA 7200/1x 16X DVD-ROM SATA					
	PSU	600W 90% Custom PSU					
	Other	-					
Energy Consumption		115 VAC		230 VAC		100 VAC	
		LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
	Windows Idle (S0)	50.0 W		48.9 W		49.5 W	
	Windows Busy Typ (S0)	118 W		115 W		118 W	
	Windows Busy Max (S0)	130 W		127 W		129 W	
	Sleep (S3)	3.56 W	3.42 W	3.782 W	3.66 W	3.53 W	3.41 W
	Off (S5)	1.34 W	1.20 W	1.58 W	1.45 W	1.31 W	1.18 W
	Zero Power Mode (ErP)	0.20 W		0.43 W		0.17 W	
Heat Dissipation**		115 VAC		230 VAC		100 VAC	
		LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
	Windows Idle (S0)	171 btu/hr		167 btu/hr		169 btu/hr	
	Windows Busy Typ (S0)	403 btu/hr		392 btu/hr		403 btu/hr	
	Windows Busy Max (S0)	444 btu/hr		433 btu/hr		440 btu/hr	
	Sleep (S3)	12.2 btu/hr	11.7 btu/hr	12.9 btu/hr	12.5 btu/hr	12.0 btu/hr	11.6 btu/hr
	Off (S5)	4.57 btu/hr	4.09 btu/hr	5.39 btu/hr	4.95 btu/hr	4.47 btu/hr	4.03 btu/hr
	Zero Power Mode (ErP)	0.68 btu/hr		1.47 btu/hr		0.58 btu/hr	

Example Configuration #2 (ENERGY STAR QUALIFIED)	Processor Info	1x Intel Xeon E5-1650 (Six-Core)					
	Memory Info	2x 4GB DDR3 1600 (UDIMM)					
	Graphics Info	1x NVIDIA Quadro 2000					
	Disks/Optical/Floppy	2x 500GB SATA 7200/1x 16X DVD+-RW SuperMulti SATA					
	Power Supply	600W 90% Custom PSU					
	Other	-					
Energy Consumption		115 VAC		230 VAC		100 VAC	
		LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
	Windows Idle (S0)	73.9 W		72.9 W		73.8 W	
	Windows Busy Typ (S0)	272 W		270 W		277 W	
	Windows Busy Max (S0)	298 W		294 W		300 W	
	Sleep (S3)	4.31 W	4.18 W	4.53 W	4.41 W	4.27 W	4.17 W
	Off (S5)	1.35 W	1.20 W	1.59 W	1.44 W	1.32 W	1.17 W
	Zero Power Mode (ErP)	0.21 W		0.43 W		0.17 W	
Heat Dissipation**		115 VAC		230 VAC		100 VAC	
		LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
	Windows Idle (S0)	252 btu/hr		249 btu/hr		252 btu/hr	
	Windows Busy Typ (S0)	928 btu/hr		921 btu/hr		945 btu/hr	
	Windows Busy Max (S0)	1017 btu/hr		1003 btu/hr		1024 btu/hr	
	Sleep (S3)	14.7 btu/hr	14.3 btu/hr	15.5 btu/hr	15.1 btu/hr	14.6 btu/hr	14.2 btu/hr
	Off (S5)	4.61 btu/hr	4.09 btu/hr	5.43 btu/hr	4.91 btu/hr	4.50 btu/hr	3.99 btu/hr
	Zero Power Mode (ErP)	0.72 btu/hr		1.47 btu/hr		0.58 btu/hr	

System Technical Specifications

Example Configuration #3	Processor Info Memory Info Graphics Info Disks/Optical/Floppy Power Supply Other	1x Intel Xeon E5-2665 (Eight-Core) 8x 4GB DDR3 1600 (UDIMM) 1x NVIDIA Quadro 5000 4x 600GB SAS 15K/1x 16X DVD+-RW SuperMulti SATA 600W 90% Custom PSU LSI 9212 SAS Card					
Energy Consumption		115 VAC		230 VAC		100 VAC	
		LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
	Windows Idle (S0)	152 W		151 W		154 W	
	Windows Busy Typ (S0)	347 W		346 W		354 W	
	Windows Busy Max (S0)	421 W		430 W		432 W	
	Sleep (S3)	6.77 W	6.68 W	6.96 W	6.82 W	6.79 W	6.63 W
	Off (S5)	1.33 W	1.20 W	1.55 W	1.42 W	1.30 W	1.18 W
	Zero Power Mode (ErP)	0.19 W		0.41 W		0.16 W	
Heat Dissipation**		115 VAC		230 VAC		100 VAC	
		LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
	Windows Idle (S0)	519 btu/hr		515 btu/hr		525 btu/hr	
	Windows Busy Typ (S0)	1184 btu/hr		1181 btu/hr		1208 btu/hr	
	Windows Busy Max (S0)	1437 btu/hr		1467 btu/hr		1474 btu/hr	
	Sleep (S3)	23.1 btu/hr	23.8 btu/hr	23.8 btu/hr	23.3 btu/hr	23.2 btu/hr	22.6 btu/hr
	Off (S5)	4.54 btu/hr	4.09 btu/hr	5.29 btu/hr	4.85 btu/hr	4.44 btu/hr	4.03 btu/hr
	Zero Power Mode (ErP)	0.65 btu/hr		1.40 btu/hr		0.55 btu/hr	

Declared Noise Emissions (Entry-level and High-end configurations)		
System Configuration (Entry level)	Processor Info	Intel Xeon E5-2665 2.40 GHz
	Memory Info	4 - DDR3 2 GB 1600 MHz UDIMM
	Graphics Info	NVIDIA Q400
	Disks/Optical/Floppy	Single 500 GB 7200 RPM SATA DVD-RW

Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)		Sound Power (LWAd, bels)	Deskside Sound Pressure (LpAm, decibels)
	Idle	3.5	18
	SATA Hard drive Operating (random reads)	3.6	19
	DVD-ROM Operating (sequential reads)	5.2	37

System Technical Specifications

System Configuration (High-end)	Processor Info	Intel Xeon E5-1660 3.30 GHz
	Memory Info	8 - 4 GB DDR3 1600 MHz UDIMM
	Graphics Info	NVIDIA Q4000
	Disks/Optical/Floppy	2 - 600 GB 15K RPM SAS 3.5" DVD-RW

Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)		Sound Power (LWAd, bels)	Deskside Sound Pressure (LpAm, decibels)
	Idle	4.9	32
	SATA Hard drive Operating (random reads)	5.0	34
	DVD-ROM Operating (sequential reads)	5.3	41

Environmental Requirements	Temperature	Operating: 5° to 35° C (40° to 95° F) Non-operating: -40° to 60° C (-40° to 140° F)
	Humidity	Operating: 8% to 85% RH, non-condensing Non-operating: 8% to 90% RH, non-condensing
	Maximum Altitude	Operating: 3,000 m (10,000 feet) Non-operating: 9,100 m (30,000 feet)
	Dynamic (new)	Shock Operating: ½-sine: 40g, 2-3ms Non-operating: ½-sine: 160 cm/s, 2-3ms (~100g) square: 422 cm/s, 20g NOTE: Values represent individual shock events and do not indicate repetitive shock events. Vibration Operating random: 0.5g (rms), 5-300 Hz Non-operating random: 2.0g (rms), 10-500 Hz NOTE: Values do not indicate continuous vibration.
	Cooling	Above 1524 m (5,000 ft) altitude, maximum operating temperature is de-rated by 1° C (1.8° F) per 305 m (1,000 ft) elevation increase

Physical Security and Serviceability	
Access Panel	Tool-less Includes system board and memory information.
Optical Drive	Tool-less
Hard Drives	Tool-less
Expansion Cards	Tool-less
Processor Socket	Tool-less
Green User Touch Points	Yes, on primary serviceable components.

System Technical Specifications

Color-coordinated Cables and Connectors	Yes
Memory	Tool-less
System Board	Screw-In
Dual Color Power and HD LED on Front of Computer	Yes
Configuration Record SW	Yes
Over-Temp Warning on Screen	Yes, at POST screen on reboot
Restore CD/DVD Set	Restores the computer to its original factory shipping image; can be obtained via HP Support.
Dual Function Front Power Switch	Yes, causes a fail-safe power off when held for 4 seconds
Padlock Support	Yes (optional): Locks side cover and secures chassis from theft 5.56 mm (0.2188 in) diameter padlock loop at rear of system
Cable Lock Support	Yes, Kensington Cable Lock (optional): Locks side cover and secures chassis from theft 3 mm x 7 mm slot at rear of system
Universal Chassis Clamp Lock Support	Yes (optional): Locks side cover and locks cables to chassis. Secures chassis from theft and allows multiple units to be chained together when used with optional cable Threaded feature at rear of system
Solenoid Lock and Hood Sensor	Yes (optional) The Solenoid Hood Lock eliminates the need for a physical key by making the chassis lockable through software and a password. You can also lock and unlock the chassis remotely over the network. The Sensor Kit detects when the access panel has been removed
Rear Port Control Cover	Yes (optional);locks rear IO cables to prevent cable theft
Serial, Parallel, USB, Audio, Network, Enable/Disable Port Control	Yes, enables or disables serial, USB, audio, and network ports
Removable Media Write/Boot Control	Yes, prevents ability to boot from removable media on supported devices (and can disable writes to media)
Power-On Password	Yes, prevents an unauthorized person from booting up the workstation
Setup Password	Yes, prevents an unauthorized person from changing the workstation configuration
3.3V Aux Power LED on System PCA	Yes
NIC LEDs (integrated) (Green & Amber)	Yes
CPUs and Heatsinks	A T-15 Torx or flat blade screwdriver is needed to remove the CPU heatsink before the CPU can be removed. CPU removal is tool-less
Power Supply Diagnostic LED	Yes
Front Power Button	Yes, ACPI multi-function
Rear Power Button	Yes
Front Power LED	Yes, blue (normal), red (fault)

System Technical Specifications

Front Hard Drive Activity LED	Yes, green
Front ODD Activity LED	Yes
Internal Speaker	Yes
System/Emergency ROM Flash Recovery	Recovers corrupted system BIOS.
Cooling Solutions	Air cooled forced convection, liquid cooling (optional)
Power Supply Fans	92 mm x 92 mm x 25 mm 4-wire (non-serviceable)
CPU Heatsink Fan	92 x 25 mm 5-wire PWM
Chassis Fan	92 mm x 92mm x 25 mm 4-wire PWM
Memory Heatsink Fan	Yes, rear memory
HP Advanced System Diagnostics Offline Edition	<p>HP Vision Diagnostics Offline Edition</p> <p>The diagnostics utility enables you to perform testing and to view critical computer hardware and software configuration information from various sources. This utility enables you to:</p> <ul style="list-style-type: none"> • Run diagnostics • View the hardware configuration of the system <p>Key features and benefits</p> <p>HP Vision Diagnostics simplifies the process of effectively identifying, diagnosing, and isolating the hardware issues. In addition to robust management tools, service tools can be invaluable in quickly resolving system problems. To streamline the service process and resolve problems quickly, it is necessary to have the right information available at the time that a service call is placed. The primary information requirement, which is also the one that provides the greatest Vision into potential system issues, is the configuration of the system. Vision Diagnostics helps provide higher system availability. Typical uses of the Vision Diagnostics are:</p> <ul style="list-style-type: none"> • Testing and diagnosing apparent hardware failures • Documenting system configurations for upgrade planning, standardization, inventory tracking, disaster recovery, and maintenance • Sending configuration information to another location for more in-depth analysis
Access Panel Key Lock	No
ACPI-Ready Hardware	<p>Advanced Configuration and Power Management Interface (ACPI).</p> <ul style="list-style-type: none"> • Allows the system to wake from a low power mode. • Controls system power consumption, making it possible to place individual cards and peripherals in a low-power or powered-off state without affecting other elements of the system
Trusted Platform Module Chip with optional ProtectTools Software	Yes, Infineon SLB9635TT1.2
Integrated Chassis Handles	<p>No</p> <p>Optional Handle in Top Optical Bay kit</p>
Power Supply	Requires T15 Torx or flat blade screwdriver
PCI Card Retention	Yes, rear (all), middle (optional), front (full-length cards with extender, used in with the front card guide and fan holder)

System Technical Specifications

Flash ROM	Yes
Diagnostic Power Switch LED on board	Yes
Clear Password Jumper	Yes
Clear CMOS Button	Yes
CMOS Battery Holder	Yes
DIMM Connectors	Yes
HP ProtectTools Security Manager	Yes - Not supported on Linux

BIOS	
BIOS 32-bit Services	Standard BIOS 32-bit Service Directory Proposal v0.4
PCI 3.0 Support	Full BIOS support for PCI Express through industry standard interfaces.
ATAPI	ATAPI Removable Media Device BIOS Specification Version 1.0.
BBS	BIOS Boot Specification v1.01.
WMI Support	WMI is Microsoft's implementation of Web-Based Enterprise Management (WBEM) for Windows. WMI is fully compliant with the Distributed Management Task Force (DMTF) Common Information Model (CIM) and WBEM specifications
BIOS Boot Spec 1.01+	Provides more control over how and from what devices the workstation will boot.
BIOS Power On	Users can define a specific date and time for the system to power on.
ROM Based Computer Setup Utility (F10)	Review and customize system configuration settings controlled by the BIOS.
System/Emergency ROM Flash Recovery with Video	Recovers system BIOS in corrupted Flash ROM
Replicated Setup	Saves BIOS settings to diskette or USB flash device in human readable file. Repset.exe utility can then replicate these settings on machines being deployed without entering Computer Configuration Utility (F10 Setup).
SMBIOS	System Management BIOS 2.7, for system management information.
Boot Control	Disables the ability to boot from removable media on supported devices.
Memory Change Alert	Alerts management console if memory is removed or changed.
Thermal Alert	Monitors the temperature state within the chassis. Three modes: <ul style="list-style-type: none"> ● NORMAL - normal temperature ranges. ● ALERTED - excessive temperatures are detected. Raises a flag so action can be taken to avoid shutdown or provide for a smoother system shutdown. ● SHUTDOWN - excessive temperatures are encountered. Automatically shuts down the computer without warning before hardware component damage occurs.
Remote ROM Flash	Provides secure, fail-safe ROM image management from a central network console.
ACPI (Advanced Configuration and Power Management Interface)	Allows the system to enter and resume from low power modes (sleep states). Enables an operating system to control system power consumption based on the dynamic workload. Makes it possible to place individual cards and peripherals in a low-power or powered-off state without affecting other elements of the system. Supports ACPI 2.0 for full compatibility with 64-bit operating systems.

System Technical Specifications

Ownership Tag	A user-defined string stored in non-volatile memory that is displayed in the BIOS splash screen.
Remote Wakeup/ Remote Shutdown	System administrators can power on, restart, and power off a client computer from a remote location.
Instantly Available PC (Suspend to RAM - ACPI sleep state S3)	Allows for very low power consumption with quick resume time.
Remote System Installation via F12 (PXE 2.1) (Remote Boot from Server)	Allows a new or existing system to boot over the network and download software, including the operating system.
ROM revision levels	Reports the system BIOS revision level in Computer Configuration Utility (F10 Setup). Version is available through an industry standard interface (SMBIOS) so that management SW applications can use and report this information.
System board revision level	Allows management SW to read revision level of the system board. Revision level is digitally encoded into the HW and cannot be modified.
Start-up Diagnostics (Power-on Self-Test)	Assesses system health at boot time with selectable levels of testing
Auto Setup when new hardware installed	System automatically detects addition of new hardware.
Keyboard-less Operation	The system can be booted without a keyboard.
Localized ROM Setup	Common BIOS image supports System Configuration Utility (F10 Setup) menus in 12 languages with local keyboard mappings.
Asset Tag	The user or MIS to set a unique tag string in non-volatile memory.
Per-slot Control	Allows I/O slot parameters (option ROM enable/disable, bus latency) to be configured individually.
Adaptive Cooling	Control parameters are set according to detected hardware configuration for optimal acoustics.
Pre-boot Diagnostics	(Pre-video) critical errors are reported via beeps and blinks on the power LED
Industry Standard Specification Support	
UEFI Specification Revision	2.1
Industry Standard	Revision Supported by the BIOS
ACPI	Advanced Configuration and Power Management Interface, Version 2.0c
ATA (IDE)	AT Attachment 6 with Packet Interface (ATA/ATAPI-6), Revision 3b
CD Boot	"El Torito" Bootable CD-ROM Format Specification Version 1.0
EDD	<ul style="list-style-type: none"> Enhanced Disk Drive Specification Version 1.1 BIOS Enhanced Disk Drive Specification Version 3.0
EHCI	Enhanced Host Controller Interface for Universal Serial Bus, Revision 1.0
PCI	PCI Local Bus Specification, Revision 2.3 PCI Power Management Specification, Revision 1.1 PCI Firmware Specification, Revision 3.0, Draft .7
PCI Express	PCI Express Base Specification, Revision 2.0 PCI Express Base Specification, Revision 3.0
PMM	POST Memory Manager Specification, Version 1.01

System Technical Specifications

SATA	<ul style="list-style-type: none"> Serial ATA Specification, Revision 1.0a Serial ATA 3 Gb/s: Serial ATA Specification, Revision 2.5 Serial ATA 6 Gb/s: Serial ATA Specification, Revision 3.0
SPD	PC SDRAM Serial Presence Detect (SPD) Specification, Revision 1.2B
TPM	Trusted Computing Group TPM Specification Version 1.2
UHCI	Universal Host Controller Interface Design Guide, Revision 1.1
USB	Universal Serial Bus Revision 1.1 Specification Universal Serial Bus Revision 2.0 Specification Universal Serial Bus Revision 3.0 Specification
SMBIOS	System Management BIOS Reference Specification, Version 2.7

Social and Environmental Responsibility

Eco-Label Certifications & Declarations	<p>This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:</p> <ul style="list-style-type: none"> ENERGY STAR® (energy-saving features available on selected configurations-Windows only) US Federal Energy Management Program (FEMP) China Energy Conservation Program IT ECO declaration
Batteries	<p>The battery in this product complies with EU Directive 2006/66/EC Battery size: CR2032 (coin cell) Battery type: Lithium Metal</p> <p>The battery in this product does not contain:</p> <ul style="list-style-type: none"> Mercury greater than 5ppm by weight Cadmium greater than 10ppm by weight Lead greater than 40ppm by weight
Restricted Material Usage	<p>This product meets the material restrictions specified in HP's General Specification for the Environment. http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/gse.pdf</p> <p>Hewlett-Packard is committed to compliance with all applicable environmental laws and regulations, including the European Union Restriction of Hazardous Substances (RoHS) Directive. HP's goal is to exceed compliance obligations by meeting the requirements of the RoHS Directive on a worldwide basis.</p>
BFR/PVC-Free Statement	<p>This product is brominated flame retardant, chlorinated flame retardant and polyvinyl chloride free (BFR/CFR/PVC free) meeting the industry definition of 'BFR/CFR/PVC-free' per the iNEMI Position Statement on "Low Halogen" Electronics. Plastic parts incorporated into the chassis generally contain < 1000 ppm (0.1%) of bromine or chlorine. Printed circuit board and substrate laminates generally contain < 1500 ppm (0.15%) of total bromine and chlorine. Service parts after purchase may not be BFR/CFR/PVC-free.</p> <p>External accessories, including power supplies, power cords, and peripherals as well as the following customer-configurable internal components: 3 ½" SAS HDDs, Intel SAS Upgrade Module, LSI 9260-8i SAS 6Gb/s ROC RAID Card, Creative Recon3D PCIe Audio Card, Liquid Cooling Solution and Broadcom 5761 Gigabit PCIe NIC are not BFR/CFR/PVC-free.</p>

System Technical Specifications

End-of-Life Management and Recycling	Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: http://www.hp.com/recycle or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner. This product is greater than 90% recyclable by weight when properly disposed of at end of life.
Hewlett-Packard Corporate Environmental Information	For more information about HP's commitment to the environment: Global Citizenship Report http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html
Additional Information	This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive - 2002/96/EC. <ul style="list-style-type: none"> ● Plastic parts weighing over 25 grams used in the product are marked per ISO 11469 and ISO1043. ● This product is >90% recycle-able when properly disposed of at end of life. <p>EPEAT Gold - ENERGY STAR qualified configurations of this product are in compliance with the IEEE 1680 (EPEAT) standard at the Gold level where HP registers workstation products. See http://ww2.epeat.net/CompanyDetail.aspx?CompanyID=24 for registration status in your country.</p>
Packaging	HP Workstation product packaging meets the HP General Specification for the Environment at http://www.hp.com/hpinfo/globalcitizenship/society/gen_specifications.html <ul style="list-style-type: none"> ● Does not contain restricted substances listed in HP Standard 011-1 General Specification for the Environment ● Does not contain ozone-depleting substances (ODS) ● Does not contain heavy metals (lead, mercury, cadmium or hexavalent chromium) in excess of 100 ppm sum total for all heavy metals listed ● Maximizes the use of post-consumer recycled content materials in packaging materials ● All packaging material is recyclable ● All packaging material is designed for ease of disassembly ● Reduced size and weight of packages to improve transportation fuel efficiency ● Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards formatting
Packaging Materials	
Internal	Cushions and plastic bags made of low density polyethylene (LDPE).
External	Outer carton, accessories carton, and insert made of corrugated paper board.

Manageability	
Industry Standard Specifications	This product meets the following industry standard specifications for manageability functionality: <ul style="list-style-type: none"> ● DASH 1.1 required functionalities via Intel LAN on motherboard
Intel Active Management Technology (AMT)	Intel Active Management Technology (AMT) 7.0 An advanced set of remote management features and functionality providing IT administrators the latest and most effective tools to remotely discover, heal, and protect networked client systems regardless of the system's health or power state. AMT 7.0 includes the following advanced management functions: <ul style="list-style-type: none"> ● Power Management (on, off, reset) ● Hardware Inventory (includes BIOS and firmware revisions) ● Hardware Alerting ● Agent Presence ● System Defense Filters ● SOL/IDER

System Technical Specifications

	<ul style="list-style-type: none"> ● Cisco NAC/SDN Support ● ME Wake-on-LAN ● DASH 1.1 compliance ● IPv6 Support ● Fast Call for Help - a client inside or outside the firewall may initiate a call for help via BIOS screen, periodic connections, or alert triggered connection ● Remote Scheduled Maintenance - pre-schedule when the system connects to the IT or service provider console for maintenance. ● Remote Alerts - automatically alert IT or service provider if issues arise ● Access Monitor - Provides oversight into Intel® AMT actions to support security requirements ● PC Alarm Clock ● Microsoft NAP Support ● Host Base set-up and configuration ● Management Engine (ME) firmware roll back
Intel® vPro™ Technology	<p>The HP Z420 Workstation supports Intel vPro technology when configured as outlined below:</p> <ul style="list-style-type: none"> ● Intel Xeon processor E5-1600 product family or E5-2600 product family featuring Intel vPro Technology ● Intel C602 chipset ● Intel 82579LM GbE LAN
Remote Manageability Software Solutions	<p>The HP Z420 Workstation is supported on the following remote manageability software consoles:</p> <ul style="list-style-type: none"> ● LANDesk Management Suite (HP recommended solution) ● Microsoft System Center Configuration Manager ● HP Client Automation Enterprise <p>For questions or support for manageability needs, please visit http://www.hp.com/go/easydeploy</p>
System Software Manager	<p>For questions or support for SSM, please visit: http://www.hp.com/go/ssm</p>
Service, Support, and Warranty	<p>On-site Warranty and Service (Note 1): Three-years, limited warranty and service offering delivers on-site, next business-day (Note 2) service for parts and labor and includes free telephone support (Note 3) 8am - 5pm. Global coverage (Note 2) ensures that any product purchased in one country and transferred to another, non-restricted country will remain fully covered under the original warranty and service offering.</p> <p>NOTE 1: Terms and conditions may vary by country. Certain restrictions and exclusions apply.</p> <p>NOTE 2: On-site service may be provided pursuant to a service contract between HP and an authorized HP third-party provider, and is not available in certain countries. Global service response times are based on commercially reasonable best effort and may vary by country.</p> <p>NOTE 3: Technical telephone support applies only to HP-configured, HP and HP-qualified, third-party hardware and software. Toll-free calling and 24x7 support service may not be available in some countries. HP Care Pack Services extend service contracts beyond the standard warranties. Service starts from date of hardware purchase. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at http://www.hp.com/go/lookuptool. Additional HP Care Pack Services information by product is available at http://www.hp.com/hps/carepack. Service levels and response times for HP Care Packs may vary depending on your geographic location.</p>
Product Change Notification	<ul style="list-style-type: none"> ● Program to proactively communicate Product Change Notifications (PCNs) and Customer Advisories by email to customers, based on a user-defined profile. ● PCNs provide advance notification of hardware and software changes to be implemented in the factory providing time to plan for transition. ● Customer Advisories provide concise, effective problem resolution, greatly reducing the need to call technical support.

Stable & Consistent Offerings

As part of its commitment to hardware, software, and solution innovation, HP is proud to introduce this breakthrough platform configuration stability to HP Workstation customers. HP Stable & Consistent Offerings are built on the foundation of a carefully chosen set of hardware and software designed and tested to work with all HP Z Workstation platforms through their end of life. These components and their corresponding HP Workstation platform compatibility are outlined in this section.

HP Stable & Consistent Offerings are available worldwide to all HP Workstation customers—no special programs, no additional cost, no kidding. Simply select your hardware and software components when you customize your HP Workstation and be assured that you'll be able to buy that same configuration throughout the lifecycle of the product.

Processors	Product #	Offering
	A2H76AV	Intel® Xeon® Processor E5-1620 4C 3.60GHz

Hard Drives	Product #	Offering
	QE198AV	HP 500 GB SATA 7200 1st HDD
	QE199AV	HP 500 GB SATA 7200 2nd HDD
	QE200AV	HP 500 GB SATA 7200 3rd HDD
	QE201AV	HP 500 GB SATA 7200 4th HDD
	QE190AV	HP 1 TB SATA 7200 1st HDD
	QE191AV	HP 1 TB SATA 7200 2nd HDD
	QE192AV	HP 1 TB SATA 7200 3rd HDD
	QE193AV	HP 1 TB SATA 7200 4th HDD

Graphics	Product #	Offering
	A7U44AV	NVIDIA NVS 310 512MB Graphics
	A7U45AV	NVIDIA NVS 310 512MB Graphics (2nd)

Memory	Product #	Offering
	QE252AV	2GB (1x2GB) DDR3-1600 ECC Unbuffered RAM
	QE254AV	4GB (2x2GB) DDR3-1600 ECC Unbuffered RAM
	B0Q75AV	6GB (3x2GB) DDR3-1600 ECC Unbuffered RAM
	QE256AV	8GB (4x2GB) DDR3-1600 ECC Unbuffered RAM
	QE258AV	16GB (8x2GB) DDR3-1600 ECC Unbuffered RAM
	QE257AV	16GB (4x4GB) DDR3-1600 ECC Unbuffered RAM
	QE260AV	32GB (8x4GB) DDR3-1600 ECC Unbuffered RAM

Optical and Removable Storage	Product #	Offering
	QE236AV	HP 16X DVD+-RW SuperMulti SATA 1st Drive
	QE237AV	HP 16X DVD+-RW SuperMulti SATA 2nd Drive

Stable & Consistent Offerings

Operating Systems**Product #****Offering**

QD971AV

Genuine Windows® 7 Professional 64-bit

Technical Specifications - Processors

Processors

Intel® Xeon® Processor E5-2665 8C 2.40GHz
Intel® Xeon® Processor E5-2687W 8C 3.10GHz

Intel® Xeon® Processor E5-1660 6C 3.30GHz
Intel® Xeon® Processor E5-1650 6C 3.20GHz
Intel® Xeon® Processor E5-1620 4C 3.60GHz
Intel® Xeon® Processor E5-1607 4C 3.00GHz
Intel® Xeon® Processor E5-1603 4C 2.80GHz

Processor Note

For detailed processor specifications, please refer to the Overview section at the beginning of this document.

Technical Specifications - Hard Drives

HP SAS (Serial Attached SCSI) Hard Drives for HP Workstations	600GB SAS 15K rpm 6Gb/s 3.5" HDD	Capacity	600GB
		Height	1 in; 2.54 cm
		Width	Media Diameter 3.5 in; 8.9 cm
			Physical Size 4 in; 10.17 cm
		Interface	SAS
		Synchronous Transfer Rate (Maximum)	6.0 Gb/s
		Buffer	16 MB
		Seek Time (typical reads, includes controller overhead, including settling)	Single Track 0.2 ms
			Average 3.4 ms
		Rotational Speed	Full Stroke 6.6 ms
		Logical Blocks	15,000 rpm
		Operating Temperature	1,172,123,568 - 512 byte blocks
			50° to 95° F (10° to 35° C)

	450GB SAS 15K rpm 6Gb/s 3.5" HDD	Capacity	450GB
		Height	1 in; 2.54 cm
		Width	Media Diameter 3.5 in; 8.9 cm
			Physical Size 4 in; 10.17 cm
		Interface	SAS
		Synchronous Transfer Rate (Maximum)	6Gb/s
		Buffer	16MB
		Seek Time (typical reads, includes controller overhead, including settling)	Single Track 0.2 ms
			Average 3.4 ms
		Rotational Speed	Full Stroke 6.6 ms
		Operating Temperature	15,000 rpm
			50° to 95° F (10° to 35° C)

	300GB SAS 15K rpm 6Gb/s 3.5" HDD	Capacity	300GB
		Height	1 in; 2.54 cm
		Width	Media Diameter 3.5 in; 8.9 cm
			Physical Size 4 in; 10.17 cm
		Interface	SAS
		Synchronous Transfer Rate (Maximum)	6Gb/s
		Buffer	16MB

Technical Specifications - Hard Drives

	Seek Time (typical reads, includes controller overhead, including settling)	Single Track	0.2 ms
		Average	3.4 ms
		Full Stroke	6.6 ms
	Rotational Speed		15,000 rpm
	Operating Temperature		50° to 95° F (10° to 35° C)
HP 300GB SAS 10K SFF HDD	Capacity		300GB
	Height		0.6 in; 1.53 cm
	Width	Media Diameter	2.5 in; 6.36 cm
		Physical Size	2.75 in; 6.99 cm
	Interface		SAS 6Gb/s
	Synchronous Transfer Rate (Maximum)		Up to 600MB/s
	Buffer		64MB
	Cache		multi-segmentable cache buffer
	Seek Time (typical reads, includes controller overhead, including settling)	Single Track	0.4 ms (max)
		Average	3.6 ms
		Full Stroke	7.3 ms
	Rotational Speed		10,000 rpm
	Logical Blocks		585,937,500
	Operating Temperature		41° to 131° F (5° to 55° C)
HP 600GB SAS 10K SFF HDD	Capacity		600GB
	Height		0.6 in; 1.53 cm
	Width	Media Diameter	2.5 in; 6.36 cm
		Physical Size	2.75 in; 6.99 cm
	Interface		SAS 6Gb/s
	Synchronous Transfer Rate (Maximum)		Up to 600MB/s
	Buffer		64MB
	Cache		multi-segmentable cache buffer
	Seek Time (typical reads, includes controller overhead, including settling)	Single Track	0.4 ms (max)
		Average	3.6 ms
		Full Stroke	7.3 ms
	Rotational Speed		10,000 rpm
	Logical Blocks		1,172,123,568
	Operating Temperature		41° to 131° F (5° to 55° C)

Technical Specifications - Hard Drives

SATA (Serial ATA) Hard Drives for HP Workstations

**3.0TB SATA 7200 rpm
6Gb/s 3.5" HDD**

Capacity	3.0TB
Height	1 in; 2.54 cm
Width	
	Media Diameter 3.5 in; 8.9 cm
	Physical Size 4.0 in; 10.17 cm
Interface	Serial ATA (6.0Gb/s), NCQ enabled
Synchronous Transfer Rate (Maximum)	Up to 6.0 Gb/s
Buffer	64MB
Seek Time (typical reads, includes controller overhead, including settling)	Single Track 0.6 ms
	Average 11 ms
	Full Stroke Not Specified
Rotational Speed	7,200 rpm
Operating Temperature	41° to 140° F (5° to 60° C)

**2.0TB SATA 7200 rpm
6Gb/s 3.5" HDD**

Capacity	2.0TB
Height	1 in; 2.54 cm
Width	
	Media Diameter 3.5 in; 8.9 cm
	Physical Size 4 in; 10.17 cm
Interface	Serial ATA (6.0 Gb/s), NCQ Enabled
Synchronous Transfer Rate (Maximum)	Up to 600 MB/s
Buffer	64MB
Seek Time (typical reads, includes controller overhead, including settling)	Single Track 1.0 ms
	Average 11 ms
	Full Stroke 18 ms
Rotational Speed	7,200 rpm
Logical Blocks	3,907,029,168
Operating Temperature	41° to 131° F (5° to 55° C)

**1TB SATA 7200 rpm 6Gb/s
3.5" HDD**

Capacity	1 Terabyte (1000 GB)
Height	1 in; 2.54 cm
Width	
	Media Diameter 3.5 in; 8.9 cm
	Physical Size 4.0 in; 10.17 cm
Interface	Serial ATA (6.0Gb/s), NCQ enabled
Synchronous Transfer Rate (Maximum)	Up to 600 MB/s
Buffer	32MB

Technical Specifications - Hard Drives

	Seek Time (typical reads, includes controller overhead, including settling)	Single Track	2 ms
		Average	11 ms
		Full Stroke	21 ms
	Rotational Speed		7,200 rpm
	Logical Blocks		1,953,525,168
	Operating Temperature		41° to 131° F (5° to 55° C)
500GB SATA 7200 rpm 6Gb/s 3.5" HDD	Capacity		500GB
	Height		1 in; 2.5 cm
	Width	Media Diameter	3.5 in; 8.9 cm
		Physical Size	4 in; 10.17 cm
	Interface		Serial ATA (6.0Gb/s), NCQ enabled
	Synchronous Transfer Rate (Maximum)		Up to 600MB/s
	Buffer		16 MB
	Seek Time (typical reads, includes controller overhead, including settling)	Single Track	2 ms
		Average	11 ms
		Full Stroke	21 ms
	Rotational Speed		7,200 rpm
	Logical Blocks		976,773,168
	Operating Temperature		41° to 131° F (5° to 55° C)
250GB SATA 7200 rpm 6Gb/s 3.5" HDD	Capacity		250 GB
	Height		1 in; 2.54 cm
	Width	Media Diameter	3.5 in; 8.9 cm
		Physical Size	4.0 in; 10.17 cm
	Interface		Serial ATA (6.0Gb/s), NCQ enabled
	Synchronous Transfer Rate (Maximum)		Up to 600MB/s
	Buffer		8 MB
	Seek Time (typical reads, includes controller overhead, including settling)	Single Track	2 ms
		Average	11 ms
		Full Stroke	21 ms
	Rotational Speed		7,200 rpm
	Logical Blocks		488,397,168
	Operating Temperature		41° to 131° F (5° to 55° C)
250GB SATA 10K rpm SFF	Capacity		250GB

Technical Specifications - Hard Drives

HDD

Height	0.6 in; 1.53 cm
Width	Media Diameter 2.5 in; 6.36 cm
	Physical Size 2.75 in; 6.99 cm
Interface	Serial ATA (6Gb/s)
Synchronous Transfer Rate (Maximum)	Up to 600MB/s
Buffer	64MB
Cache	Adaptive
Seek Time (typical reads, includes controller overhead, including settling)	Single Track 1.2ms (typical)
	Average 3.6ms
	Full Stroke 9.0ms (typical)
Rotational Speed	10K rpm
Operating Temperature	41° to 131° F (5° to 55° C)

500GB SATA 10K rpm SFF HDD

Capacity	500GB
Height	0.6 in; 1.53 cm
Width	Media Diameter 2.5 in; 6.36 cm
	Physical Size 2.75 in; 6.99 cm
Interface	Serial ATA (6Gb/s)
Synchronous Transfer Rate (Maximum)	Up to 600MB/s
Buffer	64MB
Cache	Adaptive
Seek Time (typical reads, includes controller overhead, including settling)	Single Track 1.2ms (typical)
	Average 3.6ms
	Full Stroke 9.0ms (typical)
Rotational Speed	10K rpm
Operating Temperature	41° to 131° F (5° to 55° C)

1TB SATA 10K rpm SFF HDD

Capacity	1TB
Height	0.6 in; 1.53 cm
Width	Media Diameter 2.5 in; 6.36 cm
	Physical Size 2.75 in; 6.99 cm
Interface	Serial ATA (6Gb/s)
Synchronous Transfer Rate (Maximum)	Up to 600 MB/s
Buffer	64MB
Cache	Adaptive

Technical Specifications - Hard Drives

Seek Time (typical reads, includes controller overhead, including settling)	Single Track	1.2ms (typical)
	Average	3.6ms
	Full Stroke	9.0ms (typical)
Rotational Speed	10K rpm	
Operating Temperature	41° to 131° F (5° to 55° C)	

500GB SATA 7.2K SED SFF HDD	Capacity	500GB	
	Height	0.275 in; 0.7 cm	
	Width		Media Diameter 2.5 in; 6.36 cm
			Physical Size 2.75 in; 6.99 cm
	Interface	Serial ATA (6Gb/s)	
	Synchronous Transfer Rate (Maximum)	Up to 600MB/s	
	Buffer	32MB	
	Seek Time (typical reads, includes controller overhead, including settling)	Single Track	1ms
		Average	4.2ms
		Full Stroke	25ms (typical)
	Rotational Speed	7,200 rpm	
Operating Temperature	32° to 140° F (0° to 60° C)		

HP Solid State Drives (SSDs) for Workstations

HP 128GB SATA 6Gb/s SSD	Capacity	128GB	
	Height	0.28 in; 0.7 cm	
	Width		Physical Size 2.5 in; 6.36 cm
	Interface	SATA 6Gb/s	
	Synchronous Transfer Rate (Maximum)	Up to 500MB/s (Sequential Read)	
	Operating Temperature	32° to 158° F (0° to 70° C)	

HP 256GB SATA 6Gb/s SSD	Capacity	256GB	
	Height	0.28 in; 0.7 cm	
	Interface	SATA 6Gb/s	
	Synchronous Transfer Rate (Maximum)	Up to 500MB/s (Sequential Read)	
	Operating Temperature	32° to 158° F (0° to 70° C)	

Technical Specifications - Hard Drives

HP 256GB SATA 6Gb/s SED SSD	Capacity	256GB	
	Height	0.28 in; 0.7 cm	
	Width	Physical Size	2.5 in; 6.36 cm
	Interface	6Gb/s SATA	
	Synchronous Transfer Rate (Maximum)	Up to 500MB/s (Sequential Read)	
	Operating Temperature	32° to 158° F (0° to 70° C)	
	HP 160GB SATA 3Gb/s SSD	Capacity	160GB
Width	Physical Size	2.5 in; 6.36 cm	
Interface	SATA 3Gb/s		
Synchronous Transfer Rate (Maximum)	Up to 270MB/s (Sequential Read)		
Operating Temperature	32° to 158° F (0° to 70° C)		
HP 300GB SATA 3Gb/s SSD	Capacity	300GB	
	Width	Physical Size	2.5 in; 6.36 cm
	Interface	SATA 3Gb/s	
	Synchronous Transfer Rate (Maximum)	Up to 270MB/s (Sequential Read)	
	Operating Temperature	32° to 158° F (0° to 70° C)	

Technical Specifications - Hard Drive Controllers

LSI 9212 4-Port SAS 6Gb/s RAID Card	PCI Bus	8-lane, 5GT/s PCI Express 2.0
	PCI Modes	Bus Master DMA
	RAID Levels	RAID 0, 1, 1E and 10
	PCI Data Burst Transfer Rate	Half Duplex, x4 PCIe 2000 MB/s Full Duplex, x8 PCIe 4000 MB/s
	SAS Bandwidth	Half Duplex Single lane - 600 MB/s Wide Port (2 lanes) - 1200 MB/s Wide Port (4 lanes) - 2400 MB/s
		Full Duplex Single SAS Lane - 1200 MB/s Wide Port (2 lanes) - 2400 MB/s Wide Port (4 lanes) - 4800 MB/s
	PCI Card Type	3.3V Add-in card
	PCI Voltage	12 V ± 10%
	PCI Power	13.5 Watts
	Bracket	Full height and Low-profile
	Certification Level	PCI-Express 2.0
	IO Bus	1x4 6Gb/s SAS ports
	SAS Processor	LSISAS2008
Internal Connectors	Four x1 SATA	
External Connectors	None	
Maximum Number of SCSI Devices	256	
LED Indicators	Internal Activity/Fault per x4 port - Heartbeat	

LSI MegaRAID® 9260-8i SAS 6Gb/s ROC RAID Card and iBBU08 Battery Backup Unit	PCI Bus	PCI-Express (Gen2) V2.0 x8 lanes
	PCI Modes	Bus Master DMA
	RAID Levels	RAID 0, 1, 5, and 6 RAID spans 10, 50 and 60
	PCI Data Burst Transfer Rate	Up to 4GB/s
	PCI Card Type	Low profile, single PCIe slot design with full height bracket.
		The optional iBBU08 Battery Backup unit mounts on the controller card and the assembly remains within a single PCIe slot width.
	PCI Voltage	+3.3V Add-in Card
	PCI Power	12.5 Watts
	Certification Level	PCI-Express 2.0
	IO Bus	Eight 3 Gb/s and 6Gb/s compatible SAS/SATA ports
	Internal Connectors	Two SAS SFF8087 x4
	External Connectors	None

Technical Specifications - Hard Drive Controllers

Maximum Number of SCSI 32.

Devices

NOTE: HP Workstations do not support this many internal drives.

LED Indicators

Connector LEDs indicate whether the internal connector is active for ports 0-3 and 4-7

Technical Specifications - Graphics

NVIDIA NVS 300 512MB Graphics	Form Factor	2.7 inches (H) x 5.7 inches (L), Half-Height
	Graphics Controller	NVIDIA NVS 300 Graphics Board
	Bus Type	PCI Express x16, Generation 2.0
	Memory	512 MB GDDR3 SDRAM unified graphics memory
	Connectors	DMS-59 Includes DMS-59 to Dual DVI-I adapter DMS-59 to Dual DisplayPort adapter and DMS-59 to Dual VGA adapter available as an option DMS-59 to Dual DisplayPort adapter required for HP ZR30w Display
	Maximum Resolution	DVI: two digital displays up to 1920 x 1200 DisplayPort: two digital displays up to 2560 x 1600 VGA: two analog displays up to 1920 x 1080
	Image Quality Features	
	Display Output	This card support up to two displays: <ul style="list-style-type: none">• Drives DVI enabled digital displays at resolutions up to 1920 x 1200 at 60 Hz with reduced blanking• Drives DisplayPort enabled digital displays at resolutions up to 2560 x 1600 at 60 Hz with reduced blanking (through optional DMS-59 to DisplayPort adapter)• Drives VGA enabled analog displays at resolutions up to 1920 x 1080 (through optional DMS-59 to VGA adapter)
	Supported Graphics APIs	OpenGL 3.3 DirectX 10.1
	Available Graphics Drivers	Genuine Windows 7 Professional (64-bit and 32-bit) Genuine Windows Vista Business (64-bit and 32-bit) Microsoft Windows XP Professional (64-bit and 32-bit) Red Hat Enterprise Linux(RHEL) 5 Desktop/Workstation Red Hat Enterprise Linux(RHEL) 6 Desktop/Workstation SUSE Linux Enterprise Desktop 11 (64-bit and 32-bit) HP qualified drivers may be preloaded or available from the HP support Web site: http://welcome.hp.com/country/us/en/support.html Novell SUSE Linux Enterprise drivers may also be obtained from: ftp://download.nvidia.com/novell or http://www.nvidia.com
	Power Consumption	<18 Watts

NVIDIA NVS 310 512MB Graphics	Form Factor	Low Profile: 2.713 inches in height x 6.150 inches in length
	Graphics Controller	NVIDIA NVS 310
	Bus Type	PCI Express x16, 2.0 compliant
	Memory	Size: 512MB DDR3 Clock: 875Mhz Memory Bandwidth: 14GB/s

Technical Specifications - Graphics

Connectors	2 x DisplayPort 1.2
Maximum Resolution	Up to 2560 x 1600 (digital display) per display.
Image Quality Features	See Display Output section. The following video formats are supported: <ul style="list-style-type: none">- MPEG2- MPEG4 Part 2 Advanced Simple Profile- H.264 SVC codec support- Support for 3D Blu Ray- VC1- DivX version 3.11 and later- MVC A full range of video resolutions are supported including 1080p, 1080i, 720p, 480p and 480i. The NVS 310 GPU provides hardware acceleration for the computationally intensive parts of video processing, as well as provides improved video playback speeds via faster decode and transcode.
Display Output	Up to 2 displays in the following configurations: DisplayPort output: <ul style="list-style-type: none">● Drives two DisplayPort enabled digital display at resolutions up to 2560 x 1600 at 60 Hz with reduced blanking, when connected natively using the 2 DisplayPort connectors on the NVS 310 graphics card● Supports 2 monitors up to resolution of 1920 x 1200 at 60 Hz with reduced blanking using DisplayPort 1.2 multi stream topology technology. DVI-D output: <ul style="list-style-type: none">● Drives two digital display at resolutions up to 1920 x 1200 at 60 Hz with reduced blanking using DisplayPort to DVI-D single-link cable adaptors● Drives two digital display at resolutions up to 2560x 1600 at 60 Hz with reduced blanking using DisplayPort to DVI-D dual-link cable adaptors HDMI output: <ul style="list-style-type: none">● NVS 310 is capable of driving two high definition (HD) panels up to resolutions of 1920 x 1080P at 60 Hz using DisplayPort to HDMI cable adaptors VGA display output: <ul style="list-style-type: none">● Drives two analog display at resolutions up to 1920 x 1200 at 60 Hz using DisplayPort to VGA cable adaptors
Shading Architecture	Shader Model 5.0
Supported Graphics APIs	DX11, OpenGL 4.1
Available Graphics Drivers	Genuine Windows 7 Professional (64-bit and 32-bit) Microsoft Windows XP Professional (64-bit and 32-bit) Red Hat Enterprise Linux(RHEL)

Technical Specifications - Graphics

SUSE Linux Enterprise Desktop 11 (64-bit and 32-bit)

HP qualified drivers may be preloaded or the latest HP qualified drivers are available from the HP support Web site:

<http://welcome.hp.com/country/us/en/support.html>

SUSE Linux Enterprise drivers may also be obtained from:

<ftp://download.nvidia.com/novell> or <http://www.nvidia.com>

Power Consumption

19.5 Watts

Note

The thermal solution used on this card is an active fan heatsink.

NVIDIA NVS 510 2GB Graphics

Form Factor

Low Profile, 2.713 inches × 6.3 inches, single slot

Graphics Controller

NVS 510 GPU
Core Clock: 797 Mhz
Memory Clock: 891 Mhz
CUDA Cores: 192

Bus Type

PCI Express x16, Generation 2.0

Memory

2GB DDR3

Connectors

Four mini-DisplayPort.
Four mini-DisplayPort to DisplayPort adapters included.
(DisplayPort to DVI-D, DisplayPort to VGA, DisplayPort to HDMI, and DisplayPort to Dual-Link DVI adapters available as separate accessories)

Maximum Resolution

Mini-DisplayPort connectors support ultra-high-resolution panels (up to 3840 x 2160 @ 60Hz)

NOTE: This card supports up to four displays. For Windows XP, only 2 active displays are supported.

Image Quality Features

10-bit internal display processing, including hardware support for 10-bit scan-out

Display Output

DisplayPort with Multi-Stream Technology (MST) and High Bit Rate 2 (HBR2) support.

Digital Display Support

1. DisplayPort Output

- Drives four DisplayPort enabled digital display at resolutions up to 3840 × 2160 at 60 Hz with reduced blanking, when connected natively using the 4 DisplayPort connectors on the NVS 510 graphics card.

- DisplayPort Multi-Stream Topology (MST) Technology: Supports various combinations of display resolutions and number of displays when using DisplayPort multi stream topology technology - up to a maximum of 4 monitors at a resolution of 1920 × 1200 at 60 Hz with reduced blanking.

2. DVI-D Output

- Drives four digital displays at resolutions up to 1920 × 1200 at 60 Hz with reduced blanking using DisplayPort to DVI-D single-link cable adaptors.

- Drives four digital displays at resolutions up to 2560 × 1600 at 60 Hz with reduced blanking using DisplayPort to DVI-D dual-link cable adaptors.

Technical Specifications - Graphics

3. HDMI Output

- The NVS 510 graphics board is capable of driving four high definition (HD) panels up to resolutions of 1920 × 1080P at 60 Hz using DisplayPort to HDMI cable adaptors.

Analog Display Support

1. VGA display output

- Drives four analog displays at resolutions up to 1920 × 1200 at 60 Hz using DisplayPort to VGA cable adaptors.

Supported Graphics APIs

Full Microsoft DirectX 11, Shader Model 5.0 support
Full OpenGL 4.3 support

Available Graphics Drivers

Genuine Windows 7 Professional (64-bit and 32-bit)
Microsoft Windows XP Professional (64-bit and 32-bit)
Red Hat Enterprise Linux(RHEL) 6 Desktop/Workstation
SUSE Linux Enterprise Desktop 11 (64-bit and 32-bit)

HP qualified drivers may be preloaded or available from the HP support Web site:

<http://welcome.hp.com/country/us/en/support.html>

Power Consumption

33.4 Watts

Note

Heatsink cooler design is active.

NVIDIA Quadro 410 512MB Graphics

Form Factor

Low Profile:
2.713 inches × 5.7 inches, single slot

Graphics Controller

NVIDIA Quadro 410

Bus Type

PCI Express x16, 3.0 compliant

Memory

Size: 512MB DDR3
Clock: 900MHz
Memory Bandwidth: 14GB/s

Connectors

One dual-link DVI-I connector
One DisplayPort connector

Maximum Resolution

Up to 2560 × 1600 (digital display) per display.

RAMDAC

400 MHz integrated RAMDAC

Display Output

Maximum resolution over DisplayPort: 2560 × 1600 × 32 bpp at 60 Hz (reduced blanking)

Maximum resolution over DVI port: 2560 × 1600 × 32 bpp at 60 Hz (reduced blanking)

Maximum resolution over VGA (through DVI to VGA cable): 2048 × 1536 × 32 bpp at 85 Hz

Shading Architecture

Shader Model 5.0

Supported Graphics APIs

DX11, OpenGL 4.2

Available Graphics Drivers

Genuine Windows 7 Professional (64-bit and 32-bit)
Microsoft Windows XP Professional (64-bit and 32-bit)
Red Hat Enterprise Linux(RHEL)

Technical Specifications - Graphics

SUSE Linux Enterprise Desktop 11 (64-bit and 32-bit)

HP qualified drivers may be preloaded or the latest HP qualified drivers are available from the HP support Web site:

<http://welcome.hp.com/country/us/en/support.html>

SUSE Linux Enterprise drivers may also be obtained from:

<ftp://download.nvidia.com/novell> or <http://www.nvidia.com>

NVIDIA Quadro K600 1GB Graphics	Form Factor	2.731" H x 6.3" L Single Slot, Low Profile Full Height Profile bracket installed Low Profile bracket included
	Graphics Controller	NVIDIA Quadro K600 Graphics Card Kepler GK107 GPU 192 CUDA cores Max Power: 41 Watts
	Bus Type	PCI Express 2.0 x16
	Memory	1 GB GDDR3, 891 Mhz 128-bit memory I/O path 29 GB/s memory bandwidth
	Connectors	1 DL-DVI(I) output, 1 DisplayPort output CTO: No video cable adapter included AMO: One DP-to-DVI adapter included with card
	Maximum Resolution	Additional DVI-to-VGA, DisplayPort-to-VGA or DisplayPort-to-DVI adapters are available as accessories DisplayPort: - up to 3840 x 2160 x 30 bpp @ 60Hz - supports High Bit Rate 2 (HBR2) and Multi-Stream Transport (MST)
	Image Quality Features	DL-DVI(I) output: - up to 2560 x 1600 x 32 bpp @ 60Hz 10-bit internal display processing pipeline 10-bit scan-out support
	Display Output	VGA: - requires use of DVI-to-VGA and/or DP-to-VGA video cable adapters - 400 Mhz integrated RAMDAC - Max resolution: 2048 x 1536 x 32 bpp @ 85 Hz DL-DVI(I): - Max resolution: 2560 x 1600 x 32 bpp @ 60 Hz SL-DVI(I): - Max resolution: 1920 x 1200 x 32 bpp @ 60 Hz DisplayPort: - Supports HBR2 and MST - Max resolution: 3840 x 2160 x 30 bpp @ 60 Hz (only one monitor can be

Technical Specifications - Graphics

	connected to the Quadro K600 DisplayPort connector at this resolution) - Max number of daisy-chained monitors: 2
Shading Architecture	Full Microsoft DirectX 11 Shader Model 5.0
Supported Graphics APIs	OpenGL 4.3 DirectX 11 API support includes: CUDA C, CUDA C++, DirectCompute 5.0, OpenCL, Java, Python, and Fortran
Available Graphics Drivers	Windows 8 Pro 64-bit Windows 8 (China) 64-bit Genuine Windows 7 Professional (64-bit and 32-bit) Red Hat Enterprise Linux (RHEL) 5 Desktop/Workstation (64-bit) Red Hat Enterprise Linux(RHEL) 6 Desktop/Workstation SUSE Linux Enterprise Desktop 11 (64-bit) HP qualified drivers may be preloaded or available from the HP support Web site: http://welcome.hp.com/country/us/en/support.html SUSE Linux Enterprise drivers may also be obtained from: ftp://download.nvidia.com/novell or http://www.nvidia.com
Notes	<ol style="list-style-type: none">1. Quadro K600 offered as CTO does not include a video cable adapter. Video cable adapters must be ordered separately.2. Quadro K600 offered as AMO includes one DP-to-DVI video cable adapter. Additional cables must be ordered separately.3. Quadro K600 is Windows 8 Compliant.4. A total maximum of 2 active monitors are supported across all display output types.

NVIDIA Quadro 600 1GB Graphics

Form Factor	2.731" H x 6.6" L Single Slot Small Form Factor
Graphics Controller	NVIDIA Quadro 600 Graphics Card
Bus Type	PCI Express 2.0 x16
Memory	1 GB GDDR3 128-bit
Connectors	1 DVI-I output, 1 DisplayPort output One DP to DVI adapter included with card DVI to VGA, DisplayPort to VGA and DisplayPort to DVI adapters available as accessories
Maximum Resolution	DisplayPort (up to 2560 x 1600 @ 60Hz and 1920x1200 @ 120Hz) Dual-link DVI-I output (up to 2560 x 1600 @ 60Hz and 1920x1200 @ 120Hz)
Shading Architecture	Shader Model 5.0

Technical Specifications - Graphics

Supported Graphics APIs	OpenGL 4.0 DirectX 11 CUDA API support includes: CUDA C, CUDA C++, DirectCompute 5.0, OpenCL, Java, Python, and Fortran
Available Graphics Drivers	Genuine Windows 7 Professional (64-bit and 32-bit) Genuine Windows Vista Business (64-bit and 32-bit) Microsoft Windows XP Professional (64-bit and 32-bit) Red Hat Enterprise Linux (RHEL) 5 Desktop/Workstation (64-bit and 32-bit) Red Hat Enterprise Linux(RHEL) 6 Desktop/Workstation SUSE Linux Enterprise Desktop 11 (64-bit and 32-bit)
	HP qualified drivers may be preloaded or available from the HP support Web site: http://welcome.hp.com/country/us/en/support.html
	SUSE Linux Enterprise drivers may also be obtained from: ftp://download.nvidia.com/novell or http://www.nvidia.com
Power Consumption	40 Watts

AMD FirePro V3900 1GB Graphics

Form Factor	Full height, half length (full-height bracket included)
Graphics Controller	AMD FirePro™ V3900 professional graphics
Bus Type	PCI Express® x16, Generation 2.1
Memory	1GB DDR3 memory
Connectors	1 DL DVI, 1 DP output One DP to DVI adapter included
Maximum Resolution	2560x1600 per display (5120x1600 max. horizontal resolution)
Display Output	1 DisplayPort® 1.2 1 Dual-link DVI
Supported Graphics APIs	OpenCL™ 1.1, DirectX® 11 and OpenGL 4.2
Available Graphics Drivers	Genuine Windows® 7 Professional (64-bit and 32-bit) Genuine Windows Vista® Business (64-bit and 32-bit) Microsoft® Windows XP® Professional (64-bit and 32-bit) Red Hat Enterprise Linux(RHEL) SUSE Linux Enterprise Desktop 11 (64-bit and 32-bit)
	HP qualified drivers may be preloaded or available from the HP support Web site: http://welcome.hp.com/country/us/en/support.html
Power Consumption	<50W
Note	AMD Eyefinity technology can support multiple displays using a single enabled AMD FirePro™ professional graphics card; the number of supported displays varies by card model. Microsoft® Windows® 7, Windows Vista®, or Linux® is required in order to support more than 2 displays. Depending on the card model, native DisplayPort™ connectors and/or certified DisplayPort™ active or passive adapters to convert your monitor's native input to your card's DisplayPort™ or Mini-DisplayPort™ connector(s) may be required. See www.amd.com/firepro for details.

Technical Specifications - Graphics

NVIDIA Quadro K2000 2GB Form Factor Graphics

	4.38" H x 7.97" L Single Slot, Full Height
Graphics Controller	NVIDIA Quadro K2000 Graphics Card Kepler GK107 GPU 384 CUDA cores Max Power: 51.1 Watts
Bus Type	PCI Express 2.0 x16
Memory	2 GB GDDR5, 2000 Mhz 128-bit memory I/O path 64 GB/s memory bandwidth
Connectors	1 DL-DVI(I) output, 2 DisplayPort outputs CTO: No video cable adapter included AMO: One DP-to-DVI adapter included with card
Maximum Resolution	Additional DVI-to-VGA, DisplayPort-to-VGA or DisplayPort-to-DVI adapters are available as accessories DisplayPort: - up to 3840 x 2160 x 30 bpp @ 60Hz - supports High Bit Rate 2 (HBR2) and Multi-Stream Transport (MST)
Image Quality Features	DL-DVI(I) output: - up to 2560 x 1600 x 32 bpp @ 60Hz <ul style="list-style-type: none">• 10-bit internal display processing pipeline• 10-bit scan-out support
Display Output	VGA: - requires use of DVI-to-VGA and/or DP-to-VGA video cable adapters - 400 Mhz integrated RAMDAC - Max resolution: 2048 x 1536 x 32 bpp @ 85 Hz DL-DVI(I): - Max resolution: 2560 x 1600 x 32 bpp @ 60 Hz SL-DVI(I): - Max resolution: 1920 x 1200 x 32 bpp @ 60 Hz DisplayPort: - Supports HBR2 and MST - Max resolution: 3840 x 2160 x 30 bpp @ 60 Hz (only one monitor can be connected to a Quadro K2000 DisplayPort connector at this resolution) - Max number of DisplayPort daisy-chained monitors or hub connected monitors from a single Quadro K2000 DisplayPort connector: 4 with maximum resolution of 1920 x 1200
Shading Architecture	Maximum number of monitors across all available Quadro K2000 outputs is 4. Full Microsoft DirectX 11 Shader Model 5
Supported Graphics APIs	OpenGL 4.3 DirectX 11 API support includes: CUDA C, CUDA C++, DirectCompute 5.0, OpenCL, Java, Python, and Fortran

Technical Specifications - Graphics

Available Graphics Drivers

Windows 8 Pro 64-bit
Windows 8 (China) 64-bit
Genuine Windows 7 Professional (64-bit and 32-bit)

Red Hat Enterprise Linux (RHEL) 5 Desktop/Workstation (64-bit)
Red Hat Enterprise Linux(RHEL) 6 Desktop/Workstation
SUSE Linux Enterprise Desktop 11 (64-bit)

HP qualified drivers may be preloaded or available from the HP support Web site:

<http://welcome.hp.com/country/us/en/support.html>

SUSE Linux Enterprise drivers may also be obtained from:

<ftp://download.nvidia.com/novell> or <http://www.nvidia.com>

Notes

1. Quadro K2000 offered as CTO does not include a video cable adapter. Video cable adapters must be ordered separately.
2. Quadro K2000 offered as AMO includes one DP-to-DVI video cable adapter. Additional cables must be ordered separately.

NVIDIA Quadro 2000 1GB Graphics

Form Factor

4.376" H x 7" L
Single Slot

Graphics Controller

NVIDIA Quadro 2000 Graphics Card

Bus Type

PCI Express 2.0 x16

Memory

1 GB GDDR5
128-bit

Connectors

1 DVI-I output, 2 DisplayPort outputs
One DP to DVI adapter included with card

DVI to VGA, DisplayPort to VGA and DisplayPort to DVI adapters available as accessories

Maximum Resolution

Dual DisplayPort (up to 2560 x 1600 @ 60Hz and 1920x1200 @ 120Hz)
Dual-link DVI-I output (up to 2560 x 1600 @ 60Hz and 1920x1200 @ 120Hz)

Image Quality Features

- Up to 16K x16K texture and render processing
- Transparent multisampling and super sampling
- 16x angle independent anisotropic filtering
- 128-bit floating point performance
- 32-bit per-component floating point texture filtering and blending
- Support for any combination of two connected displays
- DisplayPort 1.1a, HDMI 1.3a, and HDCP support
- NVIDIA® 3D Vision™ technology, 3D DLP, Interleaved, and other 3D stereo format support
- Full OpenGL quad buffered stereo support
- Underscan/overscan compensation and hardware scaling
- NVIDIA® nView® multi-display technology

Shading Architecture

Shader Model 5.0

Technical Specifications - Graphics

Supported Graphics APIs	OpenGL 4.0 DirectX 11 CUDA API support includes: CUDA C, CUDA C++, DirectCompute 5.0, OpenCL, Java, Python, and Fortran
Available Graphics Drivers	Genuine Windows 7 Professional (64-bit and 32-bit) Genuine Windows Vista Business (64-bit and 32-bit) Microsoft Windows XP Professional (64-bit and 32-bit) Red Hat Enterprise Linux (RHEL) 5 Desktop/Workstation (64-bit and 32-bit) Red Hat Enterprise Linux(RHEL) 6 Desktop/Workstation SUSE Linux Enterprise Desktop 11 (64-bit and 32-bit) HP qualified drivers may be preloaded or available from the HP support Web site: http://welcome.hp.com/country/us/en/support.html SUSE Linux Enterprise drivers may also be obtained from: ftp://download.nvidia.com/novell or http://www.nvidia.com
Power Consumption	62 Watts

AMD FirePro V7900 2GB Graphics

Form Factor	Full height, full length, single slot
Graphics Controller	AMD FirePro™ V7900 Professional Graphics
Bus Type	PCI Express™ x16, Generation 2.1
Memory	2GB GDDR5
Connectors	4 x DisplayPort 1.2 Two DP to DVI adapters included with card
Maximum Resolution	2560 x1600
Display Output	Up to 4 simultaneous displays (using AMD Eyefinity with Windows 7 or Linux)
Shading Architecture	Shader Model 5.0
Supported Graphics APIs	DirectX 11 and OpenGL 4.1
Available Graphics Drivers	Genuine Windows 7 Professional (64-bit and 32-bit) Genuine Windows Vista Business (64-bit and 32-bit) Microsoft Windows XP Professional (64-bit and 32-bit) Red Hat Enterprise Linux(RHEL) SUSE Linux Enterprise Desktop 11 (64-bit and 32-bit) HP qualified drivers may be preloaded or available from the HP support Web site: http://welcome.hp.com/country/us/en/support.html
Power Consumption	< 150W
Note	AMD Eyefinity technology can support multiple displays using a single enabled AMD FirePro™ professional graphics card; the number of supported displays varies by card model. Microsoft® Windows® 7, Windows Vista®, or Linux® is required in order to support more than 2 displays. Depending on the card model, native DisplayPort™ connectors and/or certified DisplayPort™ active or passive adapters to convert your monitor's native input to your card's DisplayPort™ or Mini-DisplayPort™ connector(s) may be required. See www.amd.com/firepro for details.

Technical Specifications - Graphics

NVIDIA Quadro K4000 3GB Form Factor Graphics	4.376" H x 9.5" L Single Slot, Full Height
Graphics Controller	NVIDIA Quadro K4000 Graphics Card Kepler GK106 GPU 768 CUDA cores Max Power: 80 Watts
Bus Type	PCI Express 2.0 x16
Memory	3 GB GDDR5, 2800 Mhz 192-bit memory I/O path 134 GB/s memory bandwidth
Connectors	1 DL-DVI(I) output, 2 DisplayPort outputs CTO: No video cable adapter included AMO: One DP-to-DVI adapter included with card
Maximum Resolution	Additional DVI-to-VGA, DisplayPort-to-VGA or DisplayPort-to-DVI adapters are available as accessories DisplayPort: - up to 3840 x 2160 x 30 bpp @ 60Hz - supports High Bit Rate 2 (HBR2) and Multi-Stream Transport (MST)
Image Quality Features	DL-DVI(I) output: - up to 2560 x 1600 x 32 bpp @ 60Hz <ul style="list-style-type: none">• 10-bit internal display processing pipeline• 10-bit scan-out support
Display Output	VGA: - requires use of DVI-to-VGA and/or DP-to-VGA video cable adapters - 400 Mhz integrated RAMDAC - Max resolution: 2048 x 1536 x 32 bpp @ 85 Hz DL-DVI(I): - Max resolution: 2560 x 1600 x 32 bpp @ 60 Hz SL-DVI(I): - Max resolution: 1920 x 1200 x 32 bpp @ 60 Hz DisplayPort: - Supports HBR2 and MST - Max resolution: 3840 x 2160 x 30 bpp @ 60 Hz (only one monitor can be connected to a Quadro K4000 DisplayPort connector at this resolution) - Max number of DisplayPort daisy-chained monitors or hub connected monitors from a single Quadro K4000 DisplayPort connector: 4 with maximum resolution of 1920 x 1200 HDMI: - Requires use of DP-to-HDMI cable - Max Resolution: 1920 x 1080 x 32 bpp @ 60Hz Maximum number of monitors across all available Quadro K4000 outputs is 4.

Technical Specifications - Graphics

Shading Architecture	Full Microsoft DirectX 11 Shader Model 5.0
Supported Graphics APIs	OpenGL 4.3 DirectX 11 API support includes: CUDA C, CUDA C++, DirectCompute 5.0, OpenCL, Java, Python, and Fortran
Available Graphics Drivers	Windows 8 Pro 64-bit Windows 8 (China) 64-bit Genuine Windows 7 Professional (64-bit and 32-bit) Red Hat Enterprise Linux (RHEL) 5 Desktop/Workstation (64-bit) Red Hat Enterprise Linux(RHEL) 6 Desktop/Workstation SUSE Linux Enterprise Desktop 11 (64-bit) HP qualified drivers may be preloaded or available from the HP support Web site: http://welcome.hp.com/country/us/en/support.html SUSE Linux Enterprise drivers may also be obtained from: ftp://download.nvidia.com/novell or http://www.nvidia.com
Notes	<ol style="list-style-type: none">1. Quadro K4000 offered as CTO does not include a video cable adapter. Video cable adapters must be ordered separately.2. Quadro K4000 offered as AMO includes one DP-to-DVI video cable adapter. Additional cables must be ordered separately.3. Quadro K4000 is Windows 8 Compliant.4. A total maximum of 4 active monitors are supported across all display output types. To get 4 monitors, at least one monitor must be daisy chained on a DisplayPort output.5. A DisplayPort hub device may be used to connect multiple DisplayPort monitors to a single Quadro K4000 DisplayPort output.

NVIDIA Quadro 4000 2GB Graphics	Form Factor	4.376" H x 9.50" L Single Slot
	Graphics Controller	NVIDIA Quadro 4000 Graphics Card
	Bus Type	PCI Express 2.0 x16
	Memory	2 GB GDDR5 256-bit
	Connectors	1 DVI-I output, 2 DisplayPort outputs; One DP to DVI adapter included with card DVI to VGA, DisplayPort to VGA and DisplayPort to DVI (single- link or dual-link) adapters available as accessories (Optional stereo bracket available from 3rd party)
	Maximum Resolution	Dual DisplayPort (up to 2560 x 1600 @ 60Hz and 1920x1200 @ 120Hz) Dual-link DVI-I output (up to 2560 x 1600 @ 60Hz and 1920x1200 @ 120Hz)
	RAMDAC	400 MHz integrated RAMDAC
	Image Quality Features	<ul style="list-style-type: none">● Up to 16K x16K texture and render processing● Transparent multisampling and super sampling● 16x angle independent anisotropic filtering

Technical Specifications - Graphics

- 128-bit floating point performance
- 32-bit per-component floating point texture filtering and blending
- Support for any combination of two connected displays
- DisplayPort 1.1a, HDMI 1.3a, and HDCP support
- NVIDIA 3D Vision™ technology, 3D DLP, Interleaved, and other 3D stereo format support
- Full OpenGL quad buffered stereo support
- Underscan/overscan compensation and hardware scaling
- NVIDIA nView® multi-display technology

Shading Architecture Shader Model 5.0

Supported Graphics APIs OpenGL 4.0
DirectX 11
CUDA API support includes:
CUDA C, CUDA C++, DirectCompute 5.0, OpenCL, Java, Python, and Fortran

Available Graphics Drivers Genuine Windows 7 Professional (64-bit and 32-bit)
Genuine Windows Vista Business (64-bit and 32-bit)
Microsoft Windows XP Professional (64-bit and 32-bit)
Red Hat Enterprise Linux (RHEL) 5 Desktop/Workstation (64-bit and 32-bit)
Red Hat Enterprise Linux (RHEL) 6 Desktop/Workstation
SUSE Linux Enterprise Desktop 11 (64-bit and 32-bit)

HP qualified drivers may be preloaded or available from the HP support Web site: <http://welcome.hp.com/country/us/en/support.html>

Novell SUSE Linux Enterprise drivers may also be obtained from: <ftp://download.nvidia.com/novell> or <http://www.nvidia.com>

Power Consumption 142 Watts

NVIDIA Quadro K5000 4GB Graphics Form Factor

4.376" H x 10.5" L
Dual Slot

Graphics Controller NVIDIA Quadro K5000 Graphics Card based on the GK104 GPU

Bus Type PCI Express 2.0 x16

Memory 4GB GDDR5
173GB/s memory bandwidth

Connectors DVI-I (1), DVI-D (1), DP (2), Optional 3D Stereo bracket with 3-pin mini-DIN connector.
No adapter included with card.

DVI to VGA, DisplayPort to VGA, DisplayPort to DVI, and DisplayPort to Dual-Link DVI adapters available as accessories

Image Quality Features

- DisplayPort with Multi-Stream Technology (MST) and High Bit Rate 2 (HBR2), HDMI 1.4, and HDCP support
- NVIDIA 3D Vision™ technology

Display Output 400 MHz integrated RAMDAC

- Maximum resolution over VGA (through DVI to VGA cable): 2048 × 1536 × 32 bpp at 85 Hz

Technical Specifications - Graphics

Dual-link internal TMDS (DVI 1.0)

- Maximum resolution over digital port (single GPU and SLI mode): 2560 × 1600 × 32 bpp at 60 Hz (reduced blanking)

Single-link internal TMDS (DVI 1.0)

- Maximum resolution over digital port (single GPU and SLI mode): 1920 × 1200 × 32 bpp at 60 Hz (reduced blanking)

DisplayPort with MST and HBR2.

- Maximum resolution: 3840 × 2160 × 36 bpp at 60Hz

HDMI

- Maximum resolution: 1920 × 1080 × 32 bpp at 60Hz

Supported Graphics APIs

OpenGL 4.2
DirectX 11 Shader model 5.0 Support
API support for NVIDIA's CUDA™ C, CUDA C++, DirectCompute 5.0, OpenCL, Java, Python, Fortran

Available Graphics Drivers

Genuine Windows 7 Professional (64-bit and 32-bit)
Genuine Windows Vista Business (64-bit and 32-bit)
Microsoft Windows XP Professional (64-bit and 32-bit)
Red Hat Enterprise Linux (RHEL) 5 Desktop/Workstation (64-bit and 32-bit)
Red Hat Enterprise Linux (RHEL) 6 Desktop/Workstation
SUSE Linux Enterprise Desktop 11 (64-bit and 32-bit)

HP qualified drivers may be preloaded or available from the HP support Web site:

<http://welcome.hp.com/country/us/en/support.html>

Power Consumption

122 Watts

Note

No display output adapter included.

Technical Specifications - Graphics

AMD FirePro W7000 4GB Graphics	Form Factor	Full height, full length, single slot
	Graphics Controller	AMD FirePro™ W7000 Professional Graphics Max Power: <150 Watts
	Bus Type	PCI Express™ x16, Generation 3.0
	Memory	4GB GDDR5, 153.6 GB/s bandwidth, ECC support
	Connectors	4 x DisplayPort with HBR2 and MST support. No video adapters included.
	Maximum Resolution	DisplayPort: 4096x2160 @24bpp 60Hz Dual Link DVI: 2560x1600 (requires DP to DL-DVI adapter) Single Link DVI: 1920x1200 (requires DP to DVI adapter) VGA: 1920x1200 (requires DP to VGA adapter)
	Image Quality Features	Advanced support for 8-bit, 10-bit, and 16-bit per RGB color component
	Display Output	Max number of monitors supported using DisplayPort: 6 Monitor chaining from a single DisplayPort options(subject to a max of 6 total monitors across all outputs, requires use of DisplayPort Monitors supporting MST or the use of DisplayPort hubs) <ul style="list-style-type: none">● 1 4096x2169 display● 2 2560x1600 displays● 4 1920x1200 displays
	Shading Architecture	Shader Model 5.0
	Supported Graphics APIs	OpenGL® 4.2 with OpenGL Shading Language OpenCL 1.1 Microsoft® DirectX® 11.1
	Available Graphics Drivers	Windows 7 Professional (64-bit and 32-bit) Windows 8 (64bit and 32-bit) Red Hat Enterprise Linux(RHEL) SUSE Linux Enterprise Desktop 11 (64-bit and 32-bit) HP qualified drivers may be preloaded or available from the HP support Web site: http://welcome.hp.com/country/us/en/support.html
	Note	AMD Eyefinity technology can support multiple displays using a single enabled AMD FirePro™ professional graphics card; the number of supported displays varies by card model. Microsoft® Windows® 7, Windows Vista®, or Linux® is required in order to support more than 2 displays. Depending on the card model, native DisplayPort™ connectors and/or certified DisplayPort™ active or passive adapters to convert your monitor's native input to your card's DisplayPort™ or Mini-DisplayPort™ connector(s) may be required. See www.amd.com/firepro for details.

Technical Specifications - Graphics

NVIDIA Quadro 6000 6GB Graphics	Form Factor	4.376" H x 9.75" L Dual Slot
	Graphics Controller	NVIDIA Quadro 6000 Graphics Card
	Bus Type	PCI Express 2.0 x16
	Memory	6 GB GDDR5 384-bit ECC Memory
	Connectors	1 DVI-I output, 2 DisplayPort outputs, 1 Stereo(3-pin mini DIN); One DP to DVI adapter included with card
		DVI to VGA, DisplayPort to VGA and DisplayPort to dual link DVI adapters available as accessories
	Maximum Resolution	Dual DisplayPort (up to 2560 x 1600 @ 60Hz and 1920x1200 @ 120Hz) Dual-link DVI-I output (up to 2560 x 1600 @ 60Hz and 1920x1200 @ 120Hz)
	Image Quality Features	<ul style="list-style-type: none"> ● 30-bit color ● Up to 16K x16K texture and render processing ● Transparent multisampling and super sampling ● 16x angle independent anisotropic filtering ● 128-bit floating point performance ● 32-bit per-component floating point texture filtering and blending ● 64x full scene antialiasing (FSAA) / 128x FSAA in SLI Mode ● Support for any combination of two connected displays ● DisplayPort 1.1a, HDMI 1.3a, and HDCP support ● NVIDIA 3D Vision™ technology, 3D DLP, Interleaved, and other 3D stereo format support ● Full OpenGL quad buffered stereo support ● Underscan/overscan compensation and hardware scaling ● NVIDIA nView® multi-display technology
	Shading Architecture	Shader Model 5.0
	Supported Graphics APIs	OpenGL 4.0 DirectX 11 CUDA API support includes: CUDA C, CUDA C++, DirectCompute 5.0, OpenCL, Java, Python, and Fortran
	Available Graphics Drivers	Genuine Windows 7 Professional (64-bit and 32-bit) Genuine Windows Vista Business (64-bit and 32-bit) Microsoft Windows XP Professional (64-bit and 32-bit) Red Hat Enterprise Linux (RHEL) 5 Desktop/Workstation (64-bit and 32-bit) Red Hat Enterprise Linux (RHEL) 6 Desktop/Workstation SUSE Linux Enterprise Desktop 11 (64-bit and 32-bit)
		HP qualified drivers may be preloaded or available from the HP support Web site: http://welcome.hp.com/country/us/en/support.html
		Novell SUSE Linux Enterprise drivers may also be obtained from: ftp://download.nvidia.com/novell or http://www.nvidia.com
	Power Consumption	<250 Watts

Technical Specifications - High Performance GPU Computing

NVIDIA Tesla C2075 Compute Processor

Form Factor	4.376 inches by 9.75 inches Dual Slot
System Interface	PCI Express Gen2 ×16
Video Outputs	One Dual Link DVI-I (Entry graphics level of performance)
Memory	6GB GDDR5
Peak Memory Bandwidth	+170 GB/s
Supported APIs	CUDA API support includes: CUDA C, CUDA C++, DirectCompute 5.0, OpenCL, Java, Python, and Fortran
Supported Operating Systems	Genuine Windows 7 Professional (64-bit) Genuine Windows Vista Business (64-bit) Microsoft Windows XP Professional (64-bit) Red Hat Enterprise Linux (RHEL) 5, 6 Desktop/Workstation (64-bit) SUSE Linux Enterprise Desktop 11 (64-bit) HP qualified drivers may be preloaded or available from the HP support Web site: http://welcome.hp.com/country/us/en/support.html Novell SUSE Linux Enterprise drivers may also be obtained from: ftp://download.nvidia.com/novell or http://www.nvidia.com
Processor Cores	448 CUDA cores
Power Consumption	~215 Watts

NOTE 1: A 1110W PSU is required for Tesla C2075 on the Z800

NOTE 2: A 600W PSU is required for Tesla C2075 on the Z400

NOTE 3: A 1125W PSU is required for Tesla C2075 on the Z820

Technical Specifications - Multimedia and Audio Devices

**HP Thin USB Powered
Speakers**

Frequency Response (-
3dB, 24-bit/96kHz input) F0 to 20kHz

Dimensions Speakers: 14.52 x 9.50 x 2.45 cm (5.72 x 3.74 x 0.96 in) per speaker

Technical Specifications - Optical and Removable Storage

HP DVD-ROM Drive	Description	5.25-inch, half-height, tray-load	
	Mounting Orientation	Either horizontal or vertical	
	Interface Type	SATA/ATAPI	
	Dimensions (WxHxD)	15.0 x 4.4 x 20.3 cm (5.9 x 1.7 x 8.0 in)	
	Disc Capacity	DVD-ROM Single layer: Up to 4.7 GB Double layer: Up to 8.5 GB	
	Access Times	DVD-ROM Single Layer	< 140 ms (typical)
		CD-ROM Mode 1	< 125 ms (typical)
		Full Stroke DVD	< 250 ms (seek)
		Full Stroke CD	< 210 ms (seek)
	Power	Source	SATA DC power receptacle
		DC Power Requirements	5 VDC ± 5%-100 mV ripple p-p 12 VDC ± 5%-200 mV ripple p-p
		DC Current	5 VDC - <1000 mA typical, < 1600 mA maximum 12 VDC - < 600 mA typical, < 1400 mA maximum
	Operating Environmental (all conditions non-condensing)	Temperature	41° to 122° F (5° to 50° C)
		Relative Humidity	10% to 90%
Maximum Wet Bulb Temperature		86° F (30° C)	
Operating Systems Supported		Windows 7 Professional 32-bit and 64-bit, Windows Vista Business 64*, Windows Vista Business 32*, Windows Vista Home Basic 32*, Windows 2000, Windows XP Professional or Windows XP Home 32*. Red Hat Enterprise Linux(RHEL) WS4**, 5, 6 Desktop/Workstation, Removed reference to "Novell" because of acquisition and changed product reference to "SUSE Linux Enterprise Desktop 10 & 11", No driver is required for this device. Native support is provided by the operating system.	

HP DVD+/-RW Drive	Description	5.25-inch, half-height, tray-load
	Mounting Orientation	Either horizontal or vertical
	Interface Type	SATA/ATAPI
	Dimensions (WxHxD)	15.0 x 4.4 x 17.5 cm (5.9 x 1.7 x 8.0 in)
	Disc Formats	DVD-RAM
		DVD+R
DVD+RW		
DVD+R DL		
DVD-R DL		
	DVD-R	
	DVD-RW	

Technical Specifications - Optical and Removable Storage

		CD-R	
		CD-RW	
Disc Capacity	DVD-ROM		8.5 GB DL or 4.7 GB standard
	Full Stroke DVD		< 240 ms (seek)
	Full Stroke CD		< 200 ms (seek)
Maximum Data Transfer Rates	CD ROM Read		CD-ROM, CD-R Up to 40X CD-RW Up to 32X
	DVD ROM Read	DVD-RAM	Up to 12X
		DVD+RW	Up to 8X
		DVD-RW	Up to 8X
		DVD+R DL	Up to 12X
		DVD-R DL	Up to 12X
		DVD-ROM	Up to 16X
		DVD-ROM DL	Up to 12X
		DVD+R	Up to 16X
		DVD-R	Up to 16X
Power	Source		SATA DC power receptacle
	DC Power Requirements		5 VDC ± 5%-100 mV ripple p-p 12 VDC ± 5%-200 mV ripple p-p
	DC Current		5 VDC -<1000 mA typical, <1600 mA maximum 12 VDC -<1200 mA typical, <2000 mA maximum
Operating Environmental (all conditions non-condensing)	Temperature		41° to 122° F (5° to 50° C)
	Relative Humidity		10% to 90%
	Maximum Wet Bulb Temperature		86° F (30° C)
	Operating Systems Supported		Windows 8 32-bit and 64-bit, Windows 7 Professional 32-bit and 64-bit, Windows Vista Business 64*, Windows Vista Business 32*, Windows Vista Home Basic 32*, Windows 2000, Windows XP Professional or Windows XP Home 32*. Red Hat Enterprise Linux(RHEL) WS4**, 5, 6 Desktop/Workstation SUSE Linux Enterprise Desktop 10 & 11
	Kit Contents		No driver is required for this device. Native support is provided by the operating system. HP SATA SuperMulti DVD Writer Drive, Roxio Easy Media Creator software, Intervideo WinDVD Software, installation guide, and DVD+R media.

HP Blu-Ray Writer	Description	5.25-inch, half-height, tray-load
	Mounting Orientation	Either horizontal or vertical
	Interface Type	SATA

Technical Specifications - Optical and Removable Storage

Dimensions (WxHxD)	15.0 x 4.4 x 20.3 cm (5.9 x 1.7 x 8.0 in)		
Disc Formats	BD-ROM BD-R BD-RE DVD-RAM DVD+R DVD+RW DVD+R DL DVD-R DL DVD-R DVD-RW CD-R CD-RW		
Disc Capacity	DVD-ROM	8.5 GB DL or 4.7 GB standard	
	Blu-ray	50 GB DL or 25 GB standard	
	Full Stroke DVD	< 250 ms (seek)	
	Full Stroke CD	< 210 ms (seek)	
	Blu-ray	Blu-ray	
	Startup Time (Time to drive ready from tray loading)	BD-ROM (SL/DL)	25S / 28S
		BD-R (SL/DL)	25S / 28S
		BD-RE (SL/DL)	25S / 28S
		DVD-ROM (SL/DL)	18S / 18S
		DVD-R (SL/DL)	25S / 25S
		DVD-RW	25S
		DVD+R (SL/DL)	25S / 25S
		DVD+RW	25S
		DVD-RAM	45S
		CD-ROM	45S
Maximum Data Transfer Rates	CD ROM Read	CD-ROM	Up to 40X
		CD-R	Up to 40X
		CD-RW	Up to 40X
	DVD ROM Read	DVD-RAM	Up to 5X
		DVD+RW	Up to 10X
		DVD-RW	Up to 10X
		DVD+R DL	Up to 8X
		DVD-R DL	Up to 8X
		DVD-ROM	Up to 16X
		DVD-ROM DL	Up to 8X
		DVD+R	Up to 12X
		DVD-R	Up to 12X
	Blu-Ray	BD-ROM	Up to 6X
		BD-ROM DL	Up to 4.8X
		BD-R	Up to 6X

Technical Specifications - Optical and Removable Storage

		BD-R DL	Up to 4.8X
		BD-R	Up to 6X
		BD-RE SL/DL	Up to 4.8X
Power	Source	SATA DC power receptacle	
	DC Power Requirements	5 VDC \pm 5%-100 mV ripple p-p 12 VDC \pm 10%-100 mV ripple p-p	
	DC Current	5 VDC -900 mA typical, 1200 mA maximum 12 VDC -1000 mA typical, 1600 mA maximum	
Operating Environmental (all conditions non-condensing)	Temperature	41° to 122° F (5° to 50° C)	
	Relative Humidity	15% to 80%	
	Maximum Wet Bulb Temperature	86° F (30° C)	
	Operating Systems Supported	Windows 7 Professional 32-bit and 64-bit, Windows Vista Business 64*, Windows Vista Business 32*, Windows Vista Home Basic 32*, Windows 2000, Windows XP Professional or Windows XP Home 32*. Red Hat Enterprise Linux(RHEL) WS4**, 5, 6 Desktop/Workstation, SUSE Linux Enterprise Desktop 10 & 11	
		* No driver is required for this device. Native support is provided by the operating system.	
		** RHEL WS4 not supported on Z200/Z200SFF	
	Kit Contents	HP Blue Laser RW Drive, Roxio Easy Media Creator software, Intervideo WinDVD Software, installation guide.	
Disclaimer	As Blu-Ray is a new format containing new technologies, certain disc, digital connection, compatibility and/or performance issues may arise, and do not constitute defects in the product. Flawless playback on all systems is not guaranteed. In order for some Blu-Ray titles to play, they may require a DVI or HDMI digital connection and your display may require HDCP support. HD-DVD movies cannot be played on this workstation.		

Technical Specifications - Optical and Removable Storage

HP 22-in-1 Media Card Reader	Description	The Media Card Reader device uses the same physical form factor and mounting as a Floppy Disk Drive. The device connects to a 2x5 two-channel USB header on the motherboard of the system. There is no USB controller card provided. Please see the Disc Formats section below for a list of flash memory card formats that are supported.
	Mounting Orientation	The Media Card Reader can be mounted in a dedicated Floppy Drive bay (if the chassis provides one) or in an appropriate Optical Bay adapter. It will operate in any orientation.
	Interface Type	USB 2.0 (one channel dedicated to the separate USB port; one channel dedicated to the flash memory card slots)
	Dimensions (WxHxD)	124.5 x 101.6 x 25.4 mm (4.9 x 4.0 x 1.0 in)
	Disc Formats	<ul style="list-style-type: none">xD-PictureMicro SDMicro SDHCSDSDHCSDXCMini SDMini SDHCMultiMediaCard (MMC)Reduced Size MultiMediaCard (RS MMC)MultiMedia Card 4.2 (MMC Plus, including MMC Plus HC)Reduced Size MultiMedia Card 4.2 (MMC Mobile, including MMC Mobile HC)CompactFlash Card Type ICompactFlash Card Type IIMicroDriveMemory Stick (MS)MagicGate Memory Stick (MG)MagicGate Memory Stick DuoMemory Stick SelectMemory Stick Duo (MS Duo)Memory Stick PRO (MS PRO)Memory Stick PRO Duo (MS PRO Duo)Memory Stick PRO-HG Duo <p>Two additional formats are usable with adapters (not supplied):</p> <ul style="list-style-type: none">MMC MicroMemory Stick Micro (M2)

Technical Specifications - Controller Cards

HP IEEE 1394b FireWire PCIe Card	Data Transfer Rate	Supports up to 800 Mbps
	Devices Supported	IEEE-1394 compliant devices
	Bus Type	PCIe card full height PCIe slots
	Ports	Two IEEE-1394b bilingual 9-Pin Connector (Rear)
	Internal Connectors	One 10-Pin header Custom Connector
	System Requirements	Windows 7 Professional 32-bit and 64-bit, Microsoft® Windows® XP Professional, Windows XP Home, Windows Vista, SLED 11 and RHEL 6. Intel Pentium® G series or higher processor, 128-MB RAM, 1-GB Hard Drive, CD-ROM drive, built in sound system, Available PCIe slot.
	Temperature – Operating	50° to 131° F (10° to 55° C)
	Temperature – Storage	-22° to 140° F (-30° to 60° C)
	Relative Humidity – Operating	20% to 80%
	Compliances	FCC Part 15B, cULus 60950, CE Mark EN55022B(1995)/EN55024-1998 STD, Taiwan BSMI CNS13438, Korea MIC
Operating Systems Supported	Windows 7 Professional 32-bit and 64-bit, Windows Vista® Business 32-bit and 64-bit, Windows® XP Professional, XP Professional 64-bit. Not supported on Linux.	

Technical Specifications - Networking and Communications

Integrated Intel 82579LM PCIe GbE Controller	Connector	RJ-45
	Controller	Intel 82579LM GbE platform LAN connect networking controller
	Memory	24 KB FIFO packet buffer memory
	Data Rates Supported	10/100/1000 Mbps
	Compliance	802.1P, 802.1Q, 802.2, 802.3, 802.3ab, 802.3az, 802.3u
	Bus Architecture	PCI Express and SMBus
	Data Transfer Mode	PCIe-based interface for active state operation (S0 state) and SMBus for host and management traffic (Sx low power state)
	Power Requirement	Requires 3.3V and 1.05V or just 3.3V with integrated regulators
	Boot ROM Support	Yes
	Network Transfer Mode	Full-duplex; Half-duplex (not supported for the 1000BASE-T transceiver)
	Network Transfer Rate	10BASE-T (half-duplex) 10 Mbps 10BASE-T (full-duplex) 20 Mbps 100BASE-TX (half-duplex) 100 Mbps 100BASE-TX (full-duplex) 200 Mbps 1000BASE-T (full-duplex) 2000 Mbps
	Management Capabilities	WOL, auto MDI crossover, PXE, Multi-port teaming, RSS, Advanced cable diagnostic. AMT 7.0 support

Intel Gigabit CT Desktop NIC	Connector	RJ-45
	Controller	Intel WG82574L Gigabit Ethernet Controller
	Memory	Integrated Dual 48K configurable transmit receive FIFO Buffers
	Data Rates Supported	10/100/1000 Mbps
	Compliance	IEEE 802.1P, 802.1Q, 802.2, 802.3, 802.3AB and 802.3u compliant, 802.3x flow control
	Bus Architecture	PCI-E 1.0a
	Data Path Width	X1, 250 MB/s, Bi-directional interface
	Data Transfer Mode	Bus-master DMA
	Hardware Certifications	FCC, B, CE, TUV- cTUVus Mark Canada and United States, TUV- GS Mark for European Union
	Power Requirement	Aux 3.3V, 3.0 Watts in 1000base-T and 2.0 Watts in 100Base-T
	Boot ROM Support	Yes
	Network Transfer Rate	10BASE-T (half-duplex) 10 Mbps 10BASE-T (full-duplex) 20 Mbps 100BASE-TX (half-duplex) 100 Mbps 100BASE-TX (full-duplex) 200 Mbps 1000BASE-T (full-duplex) 2000 Mbps
	Operating Temperature	32° to 131°F (0° to 55° C)
	Operating Humidity	85% at 131° F (55° C)
Dimensions	12.1 x 5.7 x 2.0 cm (4.75 x 2.25 x 0.8 in)	

Technical Specifications - Networking and Communications

Operating System Driver Support	Windows 7 Professional 32-bit and 64-bit, Windows Vista Business 64, Windows Vista Business 32, Windows XP Professional, Windows XP x64. Red Hat Enterprise Linux 4 (RHEL4.8 or newer)*, Red Hat Enterprise Linux 5 (RHEL5.3 or newer), Red Hat Enterprise Linux 6, SUSE Linux Enterprise Desktop (SLED) 11
	RHEL 4 and 5, SLED 10, are not supported on the Z220 CMT/SFF
Management Capabilities	WOL , PXE, DMI, WFM 2.0
Kit Contents	Intel Gigabit CT Desktop NIC, low profile bracket, CD containing Intel PROset II NIC drivers, quick install guide, product warranty statement

Broadcom (5761) NetXtreme Gigabit Ethernet Plus NIC

Connector	RJ-45
Controller	Broadcom 5761 PCI-Express LAN Controller
Memory	8 MB NVRAM serial Flash
Data Rates Supported	10/100/1000 Mbps
Compliance	IEEE 802.1P, 802.1Q, 802.2, 802.3, 802.3AB, 802.3u, and 802.3x
Bus Architecture	PCI-Express
Data Path Width	Single Channel PCI-Express
Data Transfer Mode	Bus Master DMA
Hardware Certifications	FCC class B, Canada and US NRTL Mark, C-Tick for Australia, BSMI for Taiwan, VCCI for Japan, MIC for Korea, GOST for Russia, UL listed (E212044), European Union Notice (CE 0682)
Power Requirement	1.8W @ 3.3V
Boot ROM Support	Yes
Network Transfer Mode	Full-duplex Half-duplex (not available for the 1000BASE-T transceiver)
Network Transfer Rate	10BASE-T (half-duplex) 10 Mbps 10BASE-T (full-duplex) 20 Mbps 100BASE-TX (half-duplex) 100 Mbps 100BASE-TX (full-duplex) 200 Mbps 1000BASE-T (full-duplex) 2000 Mbps
Operating Temperature	32° to 131°F (0° to 55° C)
Operating Humidity	131° F (55° C) with 5% to 95% non-condensing humidity
Dimensions	7 cm x 10.5 cm (2.75 in x 4.13 in), low profile compatible
Operating System Driver Support	Windows 7 Professional 32-bit and 64-bit, Windows Vista 32-bit SP1, Windows Vista x64 SP1, Windows XP 32 bit professional, Windows XP x64 Red Hat Enterprise Linux (RHEL) 5, 6; Novell SLED 10 & 11
Management Capabilities	ACPI, WOL and DMI 2.0, PXE 2.0, WfM 2.0, Broadcom mgmt utility, ASF2.0, DASH 1.0 and DASH 1.1 profiles
Kit Contents	Broadcom NetXtreme Gigabit Ethernet Plus NIC, Broadcom NetXtreme Gigabit Ethernet Plus NIC USB Cable Assembly, CD, drivers, quick install guide, product warranty statement

Technical Specifications - Networking and Communications

HP 361T PCIe Dual Port Gigabit NIC	Connector	Two RJ-45
	Controller	Intel® Ethernet I350 Controller
	Data Rates Supported	10/100/1000 Mbps, Half- and full-duplex
	Compliance	802.3, 802.3u, 802.3x, 802.3ab, 802.3ad, 802.1p, 802.1Q, 802.3az, IEEE 1588 PCIe v2.0 standard RoHS (6 of 6) FCC (U.S. only) Class B DOC (Canada) Class B CE EN 55024, EN55022 Class B VCCI Class II UL 1950 CSA 950 EN 60950 CE ACPI 1.1a Microsoft WHQL (Windows Hardware Quality Labs)
	Bus Architecture	PCI-E 1.0a
	Data Path Width	Four lane (x4) PCI Express compatible with x4, x8, and x16 PCI Express slots
	Power Requirement	4.1W idle without EEE link partner 3.2W idle with EEE link partner 4.2W maximum
	Network Transfer Rate	10BASE-T (half-duplex) 10 Mb/s 10BASE-T (full-duplex) 20 Mb/s 100BASE-TX (half-duplex) 100 Mb/s 100BASE-TX (full-duplex) 200 Mb/s 1000BASE-T (full-duplex) 2000 Mb/s
	Operating Temperature	32° to 131°F (0° to 55° C)
	Operating Humidity	10% to 95% non-condensing
	Dimensions (H x W x D)	5.3 x 2.5 in (13.50 cm x 6.4 cm) (without brackets)
	Operating System Driver Support	Windows 7 Professional 32-bit and 64-bit. Red Hat Enterprise Linux(RHEL) WS4, 5, 6 Desktop/Workstation Novell SLED 10 & SLED 11
	Management Capabilities	WOL , PXE 2.1
	Kit Contents	HP 361T PCIe Dual Port Gigabit NIC PCA with a standard height bracket attached to it (the low profile bracket is included in the clamshell that the PCA ships in) Product Warranty statement and the Quick Install Card (QIC).

HP X520 10GbE Dual Port Adapter	Hardware Certifications	FCC B, UL, CE, VCCI, BSMI, CTICK, KCC
--	--------------------------------	---------------------------------------

Technical Specifications - Networking and Communications

HP 10GbE SFP+ SR Transceiver	Operating Temperature	0°C to 45°C (32°F to 113°F)
	Operating Humidity	0% to 85%, noncondensing
	Dimensions (H x W x D)	0.47(h) x 0.54(w) x 2.19(d) inches (1.19 x 1.38 x 5.57 cm)

© 2013 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Intel, Xeon, and QuickPath are trademarks of Intel Corporation in the U.S. and other countries. Microsoft and Windows are U.S. registered trademarks of Microsoft Corporation.