

Enclosure and rack systems



schneider-electric.com/en/product-category/7500-it-racks-and-accessories

WESCO[®]

Life Is On

Schneider
Electric

Schneider Electric NetShelter™ enclosures, open frame racks, and related products provide a complete solution to meet the challenges facing server and networking applications in every environment.

- Best-in-class NetShelter enclosures offer the most standard features to facilitate installation and speed of deployment, integrating seamlessly with the full line of Schneider Electric InfraStruxure™ components.
- Rack power distribution units (PDUs), jointly designed with NetShelter enclosures, enable pinpoint control and monitoring of rack-level power.
- Rack accessories provide superior cable management capabilities for high-density networking and blade applications.

Schneider Electric enclosure and rack systems

Today's high-density server and networking applications demand a rack infrastructure that can mount a mix of different equipment and support high-capacity cable management in an efficient, flexible design.

Racks and enclosures: the building blocks of every IT environment

Trends like virtualization, consolidation, convergence, and blade server adoption are forcing different types of equipment to share the same space. Today's high-density devices generate tremendous amounts of heat. Rapidly changing business conditions require the IT environment to adapt and adjust faster than ever, and the imperative of uninterrupted uptime now has the corollary demand of efficiency.

Whether it's a network closet, server room, or data center of any size, IT operations rely on racks and enclosures for support, organization, and management of the rack-mount equipment. Servers, storage, switches, routers, PDUs, console port servers, KVM switches — today's racks and enclosures are expected to support a greater number and variety of applications and devices.



Table of contents

NetShelter SX applications and selection.....	Page 4
NetShelter SX enclosure features.....	Page 6
NetShelter SX networking enclosure.....	Page 7
NetShelter SX cable management.....	Page 8
Shelves and mounting hardware.....	Page 12
Rack components.....	Page 13
Open frame racks.....	Page 14
NetShelter CX enclosure.....	Page 16
Specialty enclosures.....	Page 17
Rack cooling and airflow management.....	Page 18
Rack power distribution.....	Page 19
LCD monitors and KVM switches.....	Page 20
NetBotz security and environmental monitoring.....	Page 21
NetShelter enclosure and rack accessory compatibility chart.....	Page 22
Online resources.....	Page 28



[Click here to access the latest electronic version of this brochure.](#)

NetShelter SX applications and selection

The world's most versatile rack enclosure for demanding IT environments

Ready for high-density environments right out of the box, NetShelter SX rack enclosures offer the most standard features on the market today. Influenced by 10 years of customer feedback, Schneider Electric has specifically engineered the next-generation NetShelter SX enclosure to handle today's power-hungry, high-density server and networking applications.

The NetShelter SX is the base building block of the InfraStruxure system. NetShelter SX has many inherent features that facilitate a faster installation and reduce handling after installation, lowering your installation and operating costs. In addition, the homogenous appearance of the NetShelter SX and its sister components in an InfraStruxure solution provides a clean, consistent look that every first-rate data center requires.

Rack enclosure systems for converged IT: high-efficiency, high-density, integrated solutions

With IT hardware trending toward Converged Infrastructure (CI) and single-source IT providers, a simplified prebuilt and pretested solution is more standardized, better defined, and quickly becoming preferred over the numerous combinations of IT hardware and software solutions of the past. Customers are looking for solutions that deliver fully populated IT racks — whether to the customer site or a co-location facility.

Schneider Electric rack systems have been pre-engineered as an optimized system for efficiently housing multiple IT equipment types in high-density situations. Special packaging options for NetShelter SX enable integrators to “rack and stack” the solution for a truly end-to-end converged system delivered prebuilt, pretested, racked, and shipped to the end customer. The packaging provides peace of mind of safe delivery of costly IT investment and the partner provides a choice of simplified, plug-and-play, integrated solutions.

Rack enclosure systems for server applications: high efficiency, high density

Servers are the lifeblood of any organization's IT operations. But keeping today's high-density servers up and running — keeping that lifeblood pumping — has become more challenging than ever. Current trends, such as virtualization, consolidation, and adoption of blade servers, mean more devices, more power, and more heat packed into each enclosure. And that means more cable clutter blocking proper airflow, more hot air recirculation concerns, and more cold air leakage, leading to more inefficiency.

Schneider Electric server enclosure systems have been pre-engineered as an optimized system to provide proper front-to-back airflow to prevent hot air recirculation and promote efficient cable management that permits quick and easy installation of new options as servers change.

Take the NetShelter SX 3D tour.

Features

Best-in-class design

Offers most standard features to facilitate installation and speed of deployment.

Guarantees compatibility with all EIA standard 19 in. rack-mount equipment — or your money back.

Integrates seamlessly with the full line of InfraStruxure components.

Greatest flexibility

Available in 24U, 42U, 45U, and 48U heights, 24 in. and 30 in. widths, and 32.5 in., 42 in., and 47.5 in. depths.

Easily adjustable vertical mounting rails for equipment varying in depth.

Rapid installation of vertical rack PDUs in the rear vertical zero-U accessory channel of NetShelter enclosures.

Superior cable management capabilities

Accommodate high-density networking and blade applications.

Easy installation to enable faster and easier moves, adds, and changes.

Promote proper airflow to improve cooling efficiency.



Applications for height

24U enclosures — Remote offices and small spaces.

42U enclosures — Standard height used globally, designed to fit through standard doorways.

45U enclosures — Enclosures with additional U-spaces for environments that standardize on a 45U, 7 ft. enclosure height.

48U enclosures — More U-spaces for more equipment in the same footprint.

Applications for width

24 in. wide enclosures are the standard for most server applications. For higher densities, a deeper enclosure may be required.

30 in. wide enclosures offer more space for high-capacity cable management and power distribution. Typically, wider enclosures are used for networking applications but the extra side space is often requested in blade server applications.




Applications for depth

32.5 in. is the preferred depth for AV equipment.

42 in. is the standard depth and meets most low- to medium-density applications.

48 in. deep enclosures are becoming the new standard because of increasing server depth crowding cable and power space.



NetShelter SKU	Height	Width	Depth	Application
AR3100 ①③④⑤	42U	24 in.	42 in.	Low/medium-density servers
AR3105 ③④⑤	45U	24 in.	42 in.	Low/medium-density servers
AR3107 ①③④	48U	24 in.	42 in.	Low/medium-density servers
AR3150 ①③④	42U	30 in.	42 in.	Networking and blade applications
AR3155 ③④	45U	30 in.	42 in.	Networking and blade applications
AR3157 ①③	48U	30 in.	42 in.	Networking and blade applications
AR3300 ①③④	42U	24 in.	47.5 in.	Medium/high-density servers
AR3305 ③④	45U	24 in.	47.5 in.	Medium/high-density servers
AR3307 ①③④	48U	24 in.	47.5 in.	Medium/high-density servers
AR3350 ①③④	42U	30 in.	47.5 in.	HD networking and blade applications
AR3355 ③④	45U	30 in.	47.5 in.	HD networking and blade applications
AR3357 ①③	48U	30 in.	47.5 in.	Networking and blade applications
AR3140 ①	42U	30 in.	42 in.	High-density networking
AR3340 ①	42U	30 in.	47.5 in.	Very-high-density networking
AR3347 ①	48U	30 in.	47.5 in.	Very-high-density networking
AR3200	42U	24 in.	42 in.	2 x 20U compartments for colocation
AR3104	24U	24 in.	42 in.	Remote server applications
AR3810	42U	24 in.	32.5 in.	Audiovisual applications
AR3812	42U	24 in.	32.5 in.	Audiovisual applications
AR3814	24U	24 in.	32.5 in.	Audiovisual applications

- ① The following can be preconfigured without standard doors and side panels. Reference part numbers AR3___X609 for no sides, AR3___X610 for no doors, and AR3___X617 for no sides/no doors. More configurations are available; contact your local Schneider Electric sales representative for more information.
- ② TAA Compliant enclosure available.
- ③ White enclosure available.
- ④ Shock packaging available for shipping enclosures with up to 2,000 lbs. of equipment installed.

NetShelter SX enclosure features

More standard features for faster installation

1 Cable access roof

- Eight cable entry slots
- Toolless mounting of overhead cable trough system
- Snap-in mounting to allow easy roof removal and installation with cables in place



2 Integrated baying brackets

- Preinstalled on frame, front and back
- Spacing options at 24 in.
- Bays with other Schneider Electric power and cooling products

3 Preinstalled leveling feet and castors

- Easily adjustable leveling from top-down
- Castors standard on all enclosures

4 Toolless, zero-U accessory channel

- Toollessly mount rack PDUs
- Toollessly mount vertical cable organizers



5 Easily adjustable vertical mounting rails

- Simple screw and cam engagement
- Captive screws — no loose hardware
- Easy visual alignment for quick adjustment
- Adjust in 0.25 in. increments through enclosure
- Hole cutouts for 0U installation (AR8469) of Data Distribution Cable (DDC) accessories

6 Half-height side panels

- Easy and safe handling
- Quick release latch
- Lockable — same key as doors
- Enclosure width remains the same with or without sides attached



Other standard features include:

- Integrated electrical bonding of sides, doors, roof, and rails to frame
- Ventilated front and rear doors
- Split-rear ventilated rear doors for better clearance in hot aisle
- Numbered U positions front and back
- Open bottom for unobstructed under-floor access
- 3,000 lb. static load, 2,250 lb. dynamic (rolling) load
- UL Listed
- Electronic Industries Association (EIA)/ECA-310-E compliant
- Meets IBC® seismic requirements with proper bolt-down hardware

NetShelter SX networking enclosure

Optimized NetShelter SX design for enhanced networking application support and a superior solution for side airflow Cisco Nexus®, Catalyst®, and MDS networking switches

1 Cable access roof

- Extra-large cable access slots for high-density cabling and brush strips for air containment
- Two spring-loaded pins allow for easy roof removal and installation with cables in place



2 Networking-style mounting rails

- Easily align rails that adjust in 0.25 in. increments
- Left vertical mounting rail contains additional cable channel
- Rail position preset to accommodate Cisco switches and cable management



3 Preinstalled vertical cable managers

- Front vertical mounting rails feature preinstalled, single-sided vertical cable managers
- Smooth plastic fingers provide proper bend radius for cables



4 Vertical mounting rails for side-to-side airflow

- Front-right vertical mounting rail open for improved side airflow



AR3340 with AR7725 duct kits for Cisco Nexus 7009

- AR3140 — 42U x 30 in. W x 42 in. D
- AR3340 — 42U x 30 in. W x 47.5 in. D
- AR3347 — 48U x 30 in. W x 47.5 in. D

Side airflow cooling

Support cooling for small and large networking switches mounted within an enclosure.

- Side airflow solution (AR7742/AR7747) for Cisco Nexus 7018
- Side airflow duct kit (AR7715) mounts inside 30 in. wide enclosures for Cisco 6500 and 9500 series switches
- Side airflow duct kit (AR7725) mounts inside 30 in. wide enclosures for Cisco Nexus 7009

All solutions

- Direct cool air at the front of the enclosure directly and predictably to the intake at the side of side airflow switches
- Consist of two duct assemblies that act as diverters, utilizing the existing fan power of the switch
- Contain a system of baffles located throughout the enclosure to mitigate exhaust air from recirculating back into the air intake



AR3340 networking enclosure and AR7742 side airflow solution for Nexus 7018



AR3140 networking enclosure and AR7715 internal side airflow duct kit for Catalyst and MDS

NetShelter SX cable management

Server and networking applications

As the number of IT components within each rack enclosure continues to increase, so do the number of power and data cables. Schneider Electric offers a large selection of vertical and horizontal cable managers to address today's cable routing demands. From toolless-install ring-style managers for server applications, to high-density finger-type managers for supporting patching and switches, Schneider Electric is a leader in innovative, application-driven solutions. Our unique overhead cable management system turns the top of the enclosure into a cable tray, eliminating the need to use space under a raised floor and permitting better organization in nonraised floor environments.

Schneider Electric has a strong history supporting the server applications in data centers around the world. The innovative, toolless, snap-in accessories have become the benchmark for server cable management.



Check out "Cable Management for Enclosure and Rack Systems" for a comprehensive list of cable management options.



High-capacity cable managers can be used to support fiber and copper cable bundles.

1 AR7580A — High-capacity vertical cable manager for NetShelter SX 30 in. wide enclosures (AR3x5x), supports 190 to 250 CAT 6A/CAT 6 data cables per section and 190 CAT 6A (0.25 in. to 0.30 in. dia.) per channel section. Each kit covers one corner of the enclosure.

2 AR7581A — Hinged covers for AR7580A vertical cable managers.

3 Fiber slack spools for mounting to the vertical mounting rails of NetShelter SX 30 in. wide enclosures (AR3x5x).

Additional high-capacity vertical cable managers and covers available for specific enclosure heights, 42, 45, and 48U. Visit the website for a complete listing.



NetShelter SX cable management

Toolless accessories

Vertical cable management

Schneider Electric specializes in toolless-install accessories by the use of the zero-U channels located in the rear of every NetShelter SX enclosure.

1 Vertical 0U accessory channels

- Allows toolless mounting of vertical rack PDUs
- Toollessly mount vertical cable organizers
- Additional vertical 0U accessory channels:
 - AR7502: Vertical 0U accessory channel, 42U, qty. 2
 - AR7552: Vertical 0U accessory channel, 45U, qty. 2
 - AR7572: Vertical 0U accessory channel, 48U, qty. 2
 - AR7511: Narrow vertical 0U accessory channel, 42U
 - AR7505: Vertical cable organizer, center rear mount

2 AR8442 — Vertical cable organizer, eight cable rings, zero U

- Supports 35 to 55 CAT 6/CAT 6A data cables
- Mounts toollessly on the vertical 0U accessory channel

3 AR8443A — Vertical fiber organizer

- Installs toollessly
- Takes up one bay of channel
- Fiber spool only kit available (AR8444)

4 AR8457 — Data distribution 0U SX panel

- Installs toollessly
- Takes up one bay of channel
- Toollessly mount up to four DDC cable heads, 24 ports for rack-to-rack connections

5 AR7710 — Cable containment brackets with rack PDU mounting

- Low-profile vertical cable management
- Support 60 to 90 CAT 6/CAT 6A data cables
- Mount toollessly on the vertical 0U accessory channel

6 AR7711 — Zero-U accessory bracket


- Mounts rack PDUs in rear-facing orientation
- Supports third-party accessories in numerous mounting configurations
- Mounts 1U or 2U patch panels or other networking accessories

7 AR8621 — Hook-and-loop cable managers, qty. 10

- Mount toollessly on the vertical 0U accessory channel
- Secure and bundle cables with hook-and-loop ties

8 AR7721, 22, 23 — Low-profile vertical cable managers, zero U

- Supports up to 38 CAT 6A or 251 fiber cables
- Mounts toollessly on the vertical 0U accessory channel



NetShelter SX cable management

Horizontal cable managers

Finger-type horizontal cable managers

Cable managers for patching and crossover applications featuring smooth radius plastic fingers that protect the cable from kinking and binding. Hinged, snap-on covers provide a clean look and retain large cable bundles. These cable managers include hardware for double-sided configurations with two units.

- **AR8602A** — 1U horizontal cable manager with 4 in. fingers and snap-on cover
- **AR8600A** — 2U horizontal cable manager with 4 in. fingers and snap-on cover
- **AR8612** — 1U horizontal cable manager with 6 in. fingers and snap-on cover
- **AR8606** — 2U horizontal cable manager with 6 in. fingers and snap-on cover
- **AR8603A** — 2U horizontal cable manager with 6 in. fingers, snap-on cover, rear cable pass-through holes, and slots for AR8008BLK/AR8016ABLK horizontal cable channel
- **AR8605** — 3U horizontal cable manager with 6 in. fingers, snap-on cover, rear cable pass-through holes, and cable channel slots



Ring-type horizontal cable managers

Economical cable managers for patching applications featuring various configurations to meet specific needs.

- **AR8425A** — 1U horizontal cable manager with four rings
- **AR8426A** — 2U horizontal cable manager with four rings
- **AR8428** — 2U horizontal cable manager with four rings and pass-through holes
- **AR8427A** — 2U horizontal cable manager with multiple rings and small cable retainers
- **AR8113A** — Cable management rings (qty. 5 large, 5 small)
- **AR7707** — Cable management rings, 8 in. deep for 30 in. wide enclosures (AR3x5x), qty. 8

Horizontal cable management accessories

- **AR8429** — 1U cable pass-through manager with brush strip
- **AR8129** — Cable management arm for use with sliding shelves
- **AR8008BLK** — Horizontal cable side channel (18 in. to 30 in. adjustment) for routing cable front-to-back between the standard wide rack mounting rails or AR8603 and AR8428 horizontal cable managers
- **AR8016ABLK** — Horizontal cable side channel (10 in. to 18 in. adjustment) for routing cable front-to-back between the standard wide rack mounting rails or AR8603 and AR8428 horizontal cable managers
- **AR7706** — Mounting rail brush strips for 30 in. wide enclosures (AR3x5x), qty. 6



NetShelter SX cable management

Overhead cable troughs and partitions

- NetShelter enclosures feature the ability to integrate a system of troughs and partitions for routing power and data cable across the top of the enclosures
- Troughs and partitions reduce the need for expensive suspended cable tray systems
- Troughs and partitions install toollessly with snap-in tabs and have standard attachment points for cable ladder systems
- Enclosure troughs are shown here; for information on power and cooling troughs and partitions, see the [Schneider Electric website](#)

1 Power cable trough

- Supports power distribution cables
- Provides separation from data cables
- Data cables pass through underneath to front partitioned area
- **AR8561**— Cable trough, 24 in. enclosures
- **AR8571**— Cable trough, 30 in. enclosures

2 Pass-through data cable partition

- Partitions the top of the enclosure into cable routing areas
- Pass-through hole provides cable access into multiple cable areas
- **AR8163ABLK** — Pass-through data partition, 24 in. enclosures
- **AR8173BLK** — Pass-through data partition, 30 in. enclosures

3 Solid data cable partition

- Partitions the top of the enclosure into cable routing areas
- Solid face provides clean appearance at the front of the enclosure
- **AR8162ABLK** — Solid data partition, 24 in. enclosures
- **AR8172BLK** — Solid data partition, 30 in. enclosures



Check out [Application Note #133: "Cable Trough, Ladder, and Partition Configuration Guide."](#)

4 Cable ladders and accessories

Cable ladders and attachment kits for routing power and data cabling overhead from rack to rack.



Cable Ladders and Attachment Kits	SKU	Ladder Accessories	SKU
Cable Ladder 6 in. (AR8164AKIT 6 in. ladder with attach kit)	AR8164ABLK	Ladder Corner Clamp	AR8461
Cable Ladder 12 in. (AR8165AKIT 12 in. ladder with attach kit)	AR8165ABLK	Ladder Angle Clamp	AR8462
Alternate Mounting — Ladder to Power Troughs	AR8576	Ladder Stacking	AR8463
Alternate Mounting — Ladder to Data Partitions	AR8177BLK	Ladder Wall Termination	AR8465
Ladder to NetShelter SX Roof	AR8168BLK	Ladder Clamp Kit	AR8169
Ladder Elevation Bracket	AR8186		
Ladder to Two-post Rack	AR8460		




Shelves and mounting hardware

Mounting accessories to aid in the installation of IT equipment and secure racks into position

Shelving

Fixed and sliding shelves to enable the mounting of tower units, monitors, and other equipment into the rack environment.

- AR8105BLK — Fixed shelf 50 lb.
- AR8122BLK — Fixed shelf 250 lb.
- AR8123BLK — Sliding shelf 100 lb.
- AR8128BLK — Sliding shelf 200 lb.
- AR8422 — Double-side fixed shelf for two-post rack
- AR8126ABLK — 17 in. sliding keyboard shelf
- AR8127BLK — 19 in. sliding rotating keyboard shelf
- AR8006A — Misc. equipment support rails for 24 in. wide enclosure



Bolt-down and stabilization

Stabilization plates and hardware to prevent tip-over in stand-alone rack applications and meet specific anchoring requirements.

- AR7700 — NetShelter SX stabilization plate to prevent tipping when sliding out equipment
- AR7701 — NetShelter SX bolt-down kit — meets IBC seismic requirements for moderate seismic zones
- AR7701-S — NetShelter SX bolt-down kit — meets IBC seismic requirements for high seismic zones



Miscellaneous mounting brackets

Variety of mounting brackets for mounting IT equipment.


- AR7711— Zero-U multipurpose accessory mounting bracket for side mounting of 1U/2U products and rack PDUs
- AR8150BLK — 23 in. to 19 in. mounting adapter brackets for use with AR7510 23 in. EIA mounting rails



Hardware kits

Available for additional hardware needs or to accommodate equipment mounted in varying mounting options.


- AR8100 — M6 cage nuts and screws, qty. 32
- AR8400 — #12-24 screws, qty. 100
- AR8005 — #10-32 cage nuts, qty. 36



Rack components


Replacement doors, side panels, roofs

Standard doors, side panels, and roofs are available for all enclosure sizes. [Check the enclosure product page options tab for a list of these rack components.](#)



Specialty roofs, side panels, and accessories

- AR7252 — Networking roof for high-density cabling 30 in. wide x 42 in. deep
- AR7716 — Networking roof for high-density cabling 30 in. wide x 42 in. deep
- AR7215 — NetShelter AV enclosure top mount conduit access adapter
- AR7209 — Open roof support bridge for overhead troughs and partitions
- AR7305A — NetShelter SX pass-through side panel 42U x 42 in. deep
- AR7313 — NetShelter SX pass-through side panel 42U x 47.5 in. deep
- AR7315 — NetShelter SX pass-through side panel 45U x 42 in. deep
- AR7316 — NetShelter SX pass-through side panel 45U x 47.5 in. deep
- AR7375 — NetShelter SX pass-through side panel 48U x 42 in. deep
- AR7314 — NetShelter SX pass-through side panel 48U x 47.5 in. deep
- AR7714 — Replacement snap-in brush strips for SX roofs
- ACF501 — Roof fan for 24 in. wide x 42 in. deep enclosures, 120 Vac
- ACF502 — Roof fan for 24 in. wide x 42 in. deep enclosures, 208 – 230 Vac
- ACF503 — Roof fan for 30 in. wide x 42 in. deep enclosures, 120 Vac
- ACF504 — Roof fan for 30 in. wide x 42 in. deep enclosures, 208 – 230 Vac
- ACF505 — Roof fan for NetShelter AV 24 in. wide x 32.5 in. deep, 115 Vac
- AR8132A — Combination lock handle for NetShelter SX enclosures, qty. 2




Rails

Mounting rails

Vertical EIA rail mounting kits for different widths and depths.


- AR7510 — 23 in. EIA mounting rails for 42U x 30 in. wide enclosures



Recessed rail kits

Intermediate mounting rails for supporting shallow depth equipment.

- AR7503 — 42U x 24 in. wide
- AR7504 — 48U x 24 in. wide
- AR7508 — 42U x 30 in. wide
- AR7578 — 48U x 30 in. wide



Open frame racks

NetShelter two- and four-post open frame racks

The NetShelter two- and four-post open frame racks offer a quality solution for the economical installation of rack-mountable equipment, where security at the individual rack level is not required. Open frame racks provide unobstructed airflow and fast, easy access to installed equipment, and can be paired with high-density vertical cable managers for maximum cable volume. The two-post rack offers cost-conscious customers a simple solution for supporting networking equipment and patching applications. The four-post rack offers more strength and features for supporting servers and networking equipment. Recent improvements to the four-post racks increase cable management options and flexibility.



Performance vertical cable managers AR8625 and AR8765 shown

Performance vertical cable managers

- Preassembled, ready for installation
- Fits two- and four-post open frame racks
- Slam-to-latch full length door opens to left or right
- Cable management backplate or midspan bracket for toollessly mounting cable management accessories and rack PDUs
- AR8615 — 6 in. wide, 84 in. height, single-sided
- AR8625 — 6 in. wide, 84 in. height, double-sided
- AR8635 — 10 in. wide, 84 in. height, single-sided
- AR8645 — 10 in. wide, 84 in. height, double-sided
- AR8665 — 12 in. wide, 84 in. height, single-sided
- AR8675 — 12 in. wide, 84 in. height, double-sided

AR201 — two-post rack

- Self-squaring design
- 45U mounting spaces (84 in. tall)
- Black finish
- 6061-T6 structural grade aluminum
- Weight capacity (static load) 750 lb.



AR203A/AR204A — four-post rack

- Threaded #12-24 holes (AR204A)
- Square holes for cage nuts and server mounts (AR203A)
- New design for easier assembly
- Steel construction
- 44U mounting spaces (84 in. tall)
- Black finish
- Multiple toolless mounting points for hook-and-loop fasteners (AR8621) or toolless cable management rings (AR7540)
- Multiposition rack PDU mounting bracket (AR8652)
- Reversible stabilization plates
- Grounding inserts
- Weight capacity (static load) 2,000 lb.



VDIM33174 — 4U overhead patch frame

- 19 in. frame
- Weight capacity up to 33 lb.
- Attaches to cable ladder and wire basket trays for network patching overhead row



Vertical cable managers

- Unassembled option for site assembly
- Fits two- and four-post open frame racks
- Cable management backplate for toollessly mounting cable management accessories
- AR8715 — 6 in. wide, 84 in. height, single-sided
- AR8725 — 6 in. wide, 84 in. height, double-sided
- AR8728 — 6 in. wide, 96 in. height, single-sided
- AR8765 — 12 in. wide, 84 in. height, single-sided
- AR8768 — 12 in. wide, 96 in. height, single-sided
- AR8775 — 12 in. wide, 84 in. height, double-sided

Open frame racks

Performance vertical cable manager: Accessories and applications

1 AR8444 — Cable slack spools

- Toollessly mounts on back panel
- Provides smooth radius support for cable slack



2 AR8621 — Toolless hook-and-loop cable managers

- 18 in. straps for large data cable bundles
- Various mounting positions on back panel of vertical cable managers



3 AR8680 — Cable divider/organizer

- For creating multiple cable pathways within vertical cable managers
- Includes tie-off features for securing cabling using toolless hook-and-loop cable managers (AR8621)




4 Vertical rack PDUs and patching

- Cable management backplate (single-sided) or midspan brackets (double-sided) allow:
 - Toollessly mount, front or rear, multiple vertical rack PDUs
 - 19 in. patch panels can be installed vertically (double-sided only)

Four-post rack accessories

AR8652 — Rack PDU mounting bracket

- Mounts on sides as a spacer when using vertical cable managers between two racks
- Mounts on face of vertical rails, perpendicular, for single rack applications
- Designed to toollessly mount Schneider Electric rack PDUs



AR8450A — Trough and partition adapter

- Provides mounting locations for overhead trough and partition cable management system



AR8652 mounted on right rear corner of four-post rack with rack PDU



NetShelter CX enclosure

Soundproofed “server room in a box,” which allows for IT deployment wherever and whenever it is needed


Conveniently deploy servers and networking equipment in a quiet, ventilated, secure, and office-ready cabinet. The NetShelter CX is a cost-effective alternative for when there is no space, budget, or time for a traditional server room or wiring closet.



NetShelter CX features

Cable management

Full-height vertical cable trays, front, middle, and rear of all units.




Composite wood structure

Composite structure with acoustic foam lining keeps hardware quiet and secure.

Integrated fan module

Each unit is outfitted with a fan module providing up to 3.6 kW thermal capacity.




Zero-U rack PDU

Each unit includes a Basic Rack PDU (AP9567) preinstalled, providing 13 available outlets with AR4018A, 12 with AR4024A, and 11 with AR4038A.

Cable egress

Cable egress provides discrete and quiet exit of up to 400 CAT 5/6 cables.



Castors

Each unit sits on four castors, two swivel and two fixed, for ease of deployment and mobility.

Standard features

Floor space requirements: Enclosures are designed to be placed directly against a wall. Clearance of 8 inches on both sides of the cabinet is essential for normal operation.

Cooling system: One ultra-low-noise exhaust fan module, 1.2 kW maximum recommended total thermal load (or 4,100 BTU/hr.). One module with AR4018A, two with AR4024A, and three with AR4038A.

Noise reduction: 18.5 dB broadband noise reduction, measured 39 in. in front of the enclosure (HP® and Dell™ servers were used as noise source in noise reduction measurements).

Mobility:

- Four heavy-duty castor-type wheels
- Front wheels have 360° rotation for maneuverability — rear wheels have fixed front-to-back motion for stability

Rear and side access:

- Detachable rear side panels, left and right, for equipment installation and maintenance access
- Detachable rear fan modules give completely open rear rack access

Cable management: 3 in. width, full-height vertical 0U accessory channels located on each side at the front, middle, and rear of the rack.

Grounding: All equipment installed within a NetShelter CX should have conventional grounding via power cables but, unlike conventional metal-case cabinets, the NetShelter CX has no requirement for additional grounding in the form of ground strapping or pipe earthing, etc. The enclosure shell is constructed entirely from nonconductive materials, and the rack is completely isolated from outside contact.

Door locking: Key-operated lock.

NetShelter CX Mini enclosure

The CX “Mini” is a purpose-built tower server enclosure aimed at small, non-IT spaces such as home office, school, AV, small office, and remote office environments.



NetShelter CX accessories — Mini

- **AR4000MV12U** — 12U vertical mounting rail kit for NetShelter CX Mini. Converts basic enclosure to a 12U rack enclosure.
- **AR4000MV-FR** — Fixed rail kit for NetShelter CX Mini provides two horizontal mounting ledges for equipment placement. Must be used with AR4000MV12U vertical mounting rail kit.
- **AR4601** — Bolt-down kit — two L-shaped brackets secure the enclosure to the floor.

NetShelter CX Mini features

- **Ventilation system** — The ultra-low-noise exhaust fan module has a 800 W maximum recommended total thermal load.
- **Cable management** — Two cable ports allow passage into and out of the enclosure for power and networking cables.
- **Mobility** — Four office-style castors.
- **Access** — A detachable and lockable rear panel ensures security and quick access to the equipment inside.
- **Integrated power strip** — Includes three IEC outlets and two sets of three regional-specific equipment cords. The power strip is removable to allow installation through the rear, without power-off equipment.

NetShelter CX accessories — 18, 24, 38U

- **AR4601** — Bolt-down kit — two L-shaped brackets secure the enclosure to the floor.
- **AR4602** — Allows use of NetShelter SX handles including combination lock handles (AR8132A) and NetBotz Rack Access PX-HID (AP9361).
- **AR4701** — Dust filter pack for 18 and 24U. Increases the Ingress Protection Rating (IP) from IP44 to IP54 and reduces the risk of dust-related equipment issues.
- **AR4702** — Dust filter pack for 38U. Includes filters for bottom and top of enclosure air intake holes.
- **AR4703** — Fan booster increases the CX thermal capacity by up to 40%.



AR4601



AR4702



AR4703



AR4602

Specialty enclosures

NetShelter WX wall-mount enclosure

Support remote patching and networking applications in a convenient wall-mount rack with an easy-install rear-hinged section and reversible doors.

- **AR100** — 13U x 23 in. wide x 25 in. deep, wall-mount enclosure with vented sides and glass front door
- **AR100HD** — 13U x 23 in. wide x 25 in. deep, wall-mount enclosure with vented sides and full vented front door
- **AR8206ABLK** — Roof fan tray 120 V
- **AR8207BLK** — Roof fan tray 208/230 V
- **AR8359** — Castor kit for NetShelter WX
- **AR8355** — Ventilation plates for NetShelter WX



AR100



AR109

- **AR106** — 6U x 24 in. wide x 16 in. deep enclosure with perforated door
- **AR109** — 9U x 24 in. wide x 16 in. deep enclosure with perforated door
- **AR112** — 12U x 24 in. wide x 20 in. deep enclosure with perforated door
- **AR8213** — Roof fan tray 120V” as an accessory for the AR106, AR109, AR112 only.

NetShelter seismic enclosure

Enclosure designed for essential facilities and carrier applications in seismic environments. Meets NEBS test standard GR-63-CORE Zone 4 at 1,000 lb. equipment load.

- **AR2144BLK** — 42U x 24 in. wide x 42 in. deep, NEBS enclosure, with sides.
- **AR2145BLK** — 42U x 24 in. wide x 42 in. deep, NEBS enclosure, without sides.




AR2145BLK

Rack cooling and airflow management

Air sealing

Covers open rack space to prevent air recirculation and reduce bypass airflow to improve cooling efficiency.

- **AR8136BLK** — 1U toolless snap-in blanking panel, 10 pk
- **AR8136BLK200** — 1U toolless snap-in blanking panel, 200 pk
- **AR8108BLK** — 1U standard metal blanking panel, 2 pk
- **AR8101BLK** — 1U, 2U, 4U, 8U, blanking panel kit
- **AR7708** — NetShelter SX Air Recirculation Prevention Kit for closing gaps and pass-through holes between side panels and equipment mounting rails
- **AR7731** — NetShelter SX external air sealing kit seals external openings at roof and floor, 10 pk



AR7731

AR8101BLK

AR8136BLK

KoldLok® raised floor grommets

Seal a variety of cutouts in a raised floor environment to reduce cold air leakage and improve cooling efficiency under the raised floor.

- **AR7720** — Integral raised floor grommet (enclosed) for new installation, 10 pk
- **AR7730** — Surface-mount raised floor grommet (split) for existing cables, 10 pk
- **AR7740** — Extended raised floor grommet to cover length of floor tile, 10 pk



AR7720

AR7740

Rack fan panel

2U rack-mounted fan panel and accessories.

- **ACF600** — 2U rack fan panel
- **ACF601** — Rack fan panel temperature controller
- **ACAC40000** — 2U vent panel with temperature display
- **ACAC40001** — 2U vent panel




ACF600

Side airflow cooling

Support cooling for small and large networking switches mounted within networking enclosures.

- **AR7742 (42U)/AR7747 (48U)** — Side airflow solution for Cisco Nexus 7018 attaches to sides of 47.5 in. deep enclosures
- **AR7715** — Side airflow duct kit mounts inside 30 in. wide enclosures for Cisco 6509, 6513, 9509, 9513, and 9500 series switches
- **AR7725** — Side airflow duct kit mounts inside 30 in. wide enclosures for Cisco Nexus 7009 series switches
- Consists of two duct assemblies that act as diverters, utilizing the existing fan power of the switch
- Systems of baffles are located throughout the enclosure to mitigate exhaust air from recirculating back into the air intake



AR7715



AR7725



AR7715

Ducting only

Vertical Exhaust Duct (VED) for NetShelter SX is an easy-to-install, low-cost cooling option that can increase the efficiency of the attached cooling system.

- **AR7751** — VED for 24 in. enclosures, short range
 - **AR7752** — VED for 24 in. enclosures, tall range
 - **AR7753** — VED for 30 in. enclosures, short range
 - **AR7754** — VED for 30 in. enclosures, tall range
 - **AR7755** — Overhead cable extension for VED 24 in.
 - **AR7756** — Overhead cable extension for VED 30 in.
- VEDs also available in white.

Roof fan trays available for 42 in. deep enclosures, see "Rack components" on page 13.



AR7751 and AR7755 installed on AR3300 with cable management

Rack power distribution

Global power densities are increasing and becoming more unpredictable. Whether deploying rack power distribution in a wiring closet, server room, or data center, Schneider Electric offers a consistent way to meet a variety of power density applications up to 22 kW per strip.

Schneider Electric Rack PDUs have sufficient power and receptacle outputs to meet high kW loads in a minimal amount of space. Their ease of installation accelerates speed of deployment and reduces installation costs. With advanced rack power distribution, Schneider Electric offers real-time remote load monitoring of connected equipment and individual outlet power control for remote power recycling.

The Metered and Switched Rack PDU offers advanced features to meet today's data center demands

Monitors input and all breakers on the strip (local and remote) and offers user-customizable warning and overload settings, plus automated alarm notifications. Enables enhanced capacity management and network management.

- Web interface
- Telnet, SNMP
- Security
- Schneider Electric StruxureWare™ for Data Centers

Manage power at the rack level with pinpoint control

- **Basic Rack PDU** — Entry-level power distribution for rack-mount equipment
- **Metered Rack PDU** — Advanced power distribution provides real-time remote monitoring of connected loads
- **Switched Rack PDU** — Premium power distribution allows remote control of individual outlets and monitoring of aggregate current consumption
- **Metered-by-Outlet** — Provides real-time remote monitoring of each individual outlet
- **Rack Automatic Transfer Switch** — Provides redundant power to single-corded equipment




Rack PDU local display

Load indicator LEDs Serial connection: local configuration and out-of-band management

User interactive display for local access


Environmental monitoring port for external temperature/humidity probe



AP7000 Series

Local two-digit LED current monitoring display

Network management: access, configure, and receive warnings from remote locations via Web, SNMP, and Telnet



AP8000 Series

CAN In/Out ports for future functionality

Local USB port for flashing firmware updates and downloading data/event logs (not to be used as serial port)



For a comprehensive list of Rack PDUs, download the latest pocket guide.

LCD monitors and KVM switches

Optimize rack space.
Maximize system visibility.

Rack LCD Consoles include a keyboard, mouse, 17 in./19 in. LCD console, and optional integrated 8/16 port analog KVM switch (17 in. model only), all in a compact 1U design. This compact design allows a KVM switch to be mounted in the rear of the Rack LCD Console or eliminate the need for a separate KVM switch altogether by choosing a Rack LCD Console with integrated 8/16 port analog KVM switch. The console is easily installed and minimizes support and maintenance costs, ensuring lower cost of ownership. The ultra-thin LCD screen, touch pad technology, and easy-to-install single user rack-mount kit combine to form a high-quality, streamlined solution built for server management. The Rack LCD Consoles can be used in a variety of IT environments, from computer rooms to large data centers.

- Ultra-thin 17 in. or 19 in. LCD monitor
- Integrated keyboard with number pad
- USB port for external media
- Space-saving 1U design
- Touch pad mouse
- Easy to install

Access your servers across the room or across the world.

Schneider Electric Rack KVM switches empower IT administrators through both local and remote POST- and BIOS-level access and control of connected servers. Schneider Electric Analog, CAT-5 Analog, and IP KVM switches help reduce total cost of ownership — minimizing space, hardware, electricity, and cabling by leveraging just one keyboard, monitor, and mouse for multiple servers. Improve return on investment and flexibility through enterprise-level scalability with centralized management. IT infrastructure management in data centers, computer rooms, and remote branch offices is now possible with greater control and peace of mind with Rack KVM switches.



AP5201

KVM Switches with Coaxial-Type Connection	SKU
8-Port Analog KVM	AP5201
16-Port Analog KVM	AP5202



AP5808

LCD Console	SKU
17 in. Rack LCD Console	AP5717
19 in. Rack LCD Console	AP5719

LCD Console with Integrated KVM Switch	SKU
17 in. Rack LCD Console with Integrated 8-Port KVM Switch	AP5808
17 in. Rack LCD Console with Integrated 16-Port KVM Switch	AP5816
KVM USB Cable, 6 ft.	AP5821
KVM USB Cable, 12 ft.	AP5822
KVM USB Cable, 25 ft.	AP5823



AP5816

KVM Switches with CAT-5 Type Connection	SKU
32-Port Digital Enterprise IP KVM with Virtual Media, Two Remote Users	KVM2132P
16-Port Digital Enterprise IP KVM with Virtual Media, Two Remote Users	KVM2116P
16-Port Digital IP KVM with Virtual Media, One Remote User	KVM1116P
16-Port Analog Enterprise KVM with Virtual Media, Two Local Users	KVM0216A
16-Port Analog KVM, One Local User	KVM0116A
8-Port Analog KVM, One Local User	KVM0108A
KVM USB Server Module	KVM-USB
KVM PS/2 Server Module	KVM-PS2
KVM USB Server Module with Virtual Media	KVM-USBVM
KVM PS/2 Server Module with Virtual Media	KVM-PS2VM
KVM USB Server Module with Virtual Media and CAC Support	KVM-USBVMCAC
KVM Serial Server Module	KVM-SERIAL
KVM to Rack PDU Power Management Cable	AP5641
KVM 1U Bracket for Rear Mount Behind Rack LCD Console	KVM-LCDMOUNT
KVM Access Software License Upgrade to Enterprise (1,024 Nodes)	SEKVM1024N

Cables	2 ft.	3 ft.	6 ft.	12 ft.	25 ft.
KVM USB Cable			AP5253	AP5257	AP5261
KVM PS/2 Cable		AP5264	AP5250	AP5254	AP5258
KVM Daisy-chain Cable	AP5262		AP5263		

NetBotz security and environmental monitoring

Security and environmental monitoring for network closets to data centers

NetBotz

Surveillance:

- Leverage NetBotz™, Pelco™ IP, and CCTV camera technology to monitor IT assets remotely

Management capabilities:

- Alarming allows alerts, multiple notification methods, scheduling, graph and video attachments, and escalation
- StruxureWare Central available for centralized monitoring of multiple appliances

Environmental monitoring:

- Wide range of sensor support to monitor the health of your IT assets
- Temperature, humidity, leak, door, smoke, vibration, dew point, airflow, dry contact, 4 – 20 mA, and 0 – 5 V

Access control:

- Control and manage access privileges for NetShelter SX enclosures over the network



NBWL0455

NBPD0155

NBPD0160



NBRK0201




NBRK0451

High-level security option for NetShelter SX

NetBotz rack access PX — HID system AP9361

- Configure individual HID proximity cards for access or schedule access to equipment for maintenance purposes
- Control and manage rack access privileges from a Web browser
- Perform audit trails on rack access
- Receive alarm notification when the rack is in a compromised security state



AP9361



AP9361

NetBotz rack access pod 170 — NBPD0171

- Rack access pod connects via A-Link and mounts in the rack basement, minimizing space usage
- Rack access solution scales easily and can be used with any NetShelter SX brand enclosures



NBPD0171



NetShelter enclosure and rack accessory compatibility chart

SKU	Description	AR3100 NetShelter SX 1070 Deep 42U x 600 (W)	AR3105 NetShelter SX 1070 Deep 45U x 600 (W)	AR3107 NetShelter SX 1070 Deep 48U x 600 (W)	AR3150 NetShelter SX 1070 Deep 45U x 750 (W)	AR3155 NetShelter SX 1070 Deep 45U x 750 (W)	AR3157 NetShelter SX 1070 Deep 48U x 750 (W)	AR3300 NetShelter SX 1200 Deep 42U x 600 (W)	AR3305 NetShelter SX 1200 Deep 45U x 600 (W)	AR3307 NetShelter SX 1200 Deep 48U x 600 (W)	AR3350 NetShelter SX 1200 Deep 42U x 750 (W)	AR3355 NetShelter SX 1200 Deep 45U x 750 (W)	AR3357 NetShelter SX 1200 Deep 48U x 750 (W)	AR3140 Networking 1070 Deep 42U x 750 (W)	AR3340 Networking 1200 Deep 42U x 750 (W)	AR3347 Networking 1200 Deep 48U x 750 (W)	AR3104 NetShelter SX 1070 Deep 24U x 600 (W)	AR3200 Co-location SX 1070 Deep 42U x 600 (W)	AR3810 NetShelter SX AV 825 Deep 42U x 600 (W)	AR3814 NetShelter SX AV 825 Deep 24U x 600 (W)
Vertical Cable Management																				
AR7502	NetShelter SX 42U Vertical PDU Mount and Cable Organizer	•			•			•			•			•	•				•	
AR7505	Rear Center Mount Cable Tree for NetShelter SX	•		•	•		•	•		•	•		•	•	•	•			•	
AR7511	Narrow Vertical Cable Organizer, NetShelter SX, 42U	•			•			•			•			•	•				•	
AR7552	Vertical Cable Organizer, NetShelter SX, 45U		•					•					•							
AR7572	NetShelter SX 48U Vertical PDU Mount and Cable Organizer			•						•				•						
AR7580A	Vertical Cable Manager for NetShelter SX 750 mm Wide 42U (Qty 2)				•						•									
AR7581A	Hinged Covers for NetShelter SX 750 mm Wide 42U Vertical Cable Manager (Qty 2)				•						•									
AR7585	Vertical Cable Manager for NetShelter SX 750 mm Wide 45U (Qty 2)							•					•							
AR7586	Hinged Covers for NetShelter SX 750 mm Wide 45U Vertical Cable Manager (Qty 2)							•					•							
AR7588	Vertical Cable Manager for NetShelter SX 750 mm Wide 48U (Qty 2)							•						•						
AR7589	Hinged Covers for NetShelter SX 750 mm Wide 48U Vertical Cable Manager (Qty 2)							•						•						
AR7706	NetShelter SX 750 mm Mounting Rail Brush Strips				•	•	•				•	•	•							
AR7721	Vertical Cable Manager for NetShelter SX 600 mm Wide, 42U	•						•												
AR7722	Vertical Cable Manager for NetShelter SX 600 mm Wide, 45U		•						•											
AR7723	Vertical Cable Manager for NetShelter SX 600 mm Wide, 48U			•					•	•										
AR8442	Vertical Cable Organizer for NetShelter OU Channel	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
AR8443A	Vertical Fiber Organizer	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
AR8444	Fiber Spools	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
AR8008BLK	Side Channel Cable Trough				•	•	•				•	•	•							
AR8016ABLK	NetShelter SX Side Channel Cable Trough				•	•	•				•	•	•							
Rack Cooling SKUs																				
AR7708	NetShelter SX Air Recirculation Prevention Kit	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
ACF001	RM Air Distribution Unit 120 V	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
ACF002	RM Air Distribution Unit 208/230 V	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
ACF003	RM Air Distribution Unit 100 V	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
ACF501	NetShelter SX Roof Fan Tray 115 VAC	•	•	•													•	•		
ACF502	NetShelter SX Roof Fan Tray 208 – 230 VAC	•	•	•													•	•		
ACF503	NetShelter SX Roof Fan Tray 115 VAC 750 mm				•	•	•							•						
ACF504	NetShelter SX Roof Fan Tray 208 – 230 VAC 750 mm				•	•	•							•						
AR7715	NetShelter SX Internal Side Air Flow Duct Kit				•	•	•				•	•	•	•	•	•				
AR7725	NetShelter SX Internal Side Airflow Duct Kit for Nexus 7009				•	•	•				•	•	•	•	•	•				
AR7742	NetShelter SX 42U Nexus 7018 Duct Kit														•					
AR7747	NetShelter SX 48U Nexus 7018 Duct Kit															•				

October 2015

©2015 Schneider Electric. All Rights Reserved.
Schneider Electric, NetShelter, InfraStruxure, NetBotz, Pelco, StruxureWare, Energy University, and Life Is On Schneider Electric are trademarks owned by Schneider Electric Industries SAS or its affiliated companies. All other trademarks are the property of their respective owners.
998-4936_GMA-US_B

