

Transcend®

SSD230S Solid State Drive

SSD230S Solid State Drive

2.5" Solid State Drive SATA III 6Gb/s SSD230S

Transcend's SATA III 6Gb/s SSD230S uses the latest 3D NAND technology that features vertical, stacked expansion of storage cells. By using high-quality flash memory and enhanced firmware algorithms, the SSD230S delivers greater performance and reliability.



3D expansion to break through limits

Unlike planar NAND memory, 3D NAND flash features memory cells stacked vertically in multiple layers. 3D NAND overcomes density limitations of 2D planar NAND, and delivers a higher level of performance and endurance.



Performance boost for everyday computing

Taking full advantage of the SATA III 6Gb/s interface and built-in SLC caching technology, Transcend's SSD230S achieves exceptional transfer speeds of up to 560MB/s read and 520MB/s write.



Guaranteed endurance and reliability

Transcend's SSD230S offers great Terabytes Written (TBW) values (up to 1,120 TB) indicating the total amount of data you can write into the drive over its lifetime. It also features RAID engine and LDPC coding, Garbage Collection, Wear-leveling, and DevSleep.





2.5" Solid State Drive SATA III 6Gb/s SSD230S

Features

- Up to 560 MB/s read; 520 MB/s write
- 3D NAND flash memory and DDR3 DRAM cache
- Engineered with a RAID engine and LDPC (Low-Density Parity Check) coding to ensure data integrity; built-in SLC caching technology for exceptional transfer speeds
- Supports DevSleep ultra low power state, S.M.A.R.T., TRIM, and NCQ commands
- Download the SSD Scope software from Transcend's official website



SSD Scope Software

Transcend SSD Scope is advanced, user-friendly software that makes it easy to ensure your Transcend SSD remains healthy, and continues to run fast and error-free by determining the condition and optimizing the performance of your drive.

Specification

Appearance			
Dimensions	100 mm x 69.85 mm x 6.8 mm (3.94" x 2.75" x 0.28") 53 g (1.87 oz)		
Weight			
Storage			
Flash Type	Type 3D NAND flash		
Capacity	128GB / 256GB / 512GB / 1TB / 2TB		

Operating Environment

1 0	
Operating Temperature	0°C (32°F) ~ 70°C (158°F)
Operating Voltage	5V±5%

Performance

renormance		
Sequential Read/Write (CrystalDiskMark)	Read: 560 MB/s Write: 520 MB/s	
4K Random Read/Write (IOmeter)	Read: 85,000 IOPS Write: 89,000 IOPS	
Mean Time Between Failures (MTBF)	2,000,000 hour(s)	
Terabytes Written (TBW)	1,120 TB	
Drive Writes Per Day (DWPD)	0.3 (5 yrs)	
Note	Speed may vary due to host hardware, software, usage, and storage capacity.	
Warranty		
Certificate	CE/FCC/BSMI/KC/RCM	
Warranty	Five-year Limited Warranty	

Ordering Information

TS128GSSD230S
TS256GSSD230S
TS512GSSD230S
TS1TSSD230S
TS2TSSD230S

Product specifications are subject to change without notice. Pictures shown may differ from actual products. When used as a storage capacity unit, one terabyte (TB) = one trillion bytes. Total accessible capacity varies depending on operating environment.



2.5″ SSD Comparison	SSD2200 CATA UL CCL /c	Transcend*	Transcend*	Transcend'			
	SATA III 6Gb/s SSD220Q	SATA III 6Gb/s SSD230S	SATA III 6Gb/s SSD220S	SATA III 6Gb/s SSD370S			
Appearance							
Dimensions		100 mm x 69.85 mm x 6.8 mm (3.94" x 2.75" x 0.28")					
Weight	45 g (1.59 oz)	53 g (1.87 oz)	45 g (1.59 oz)	57 g (2.01 oz)			
Storage							
Flash Type	QLC NAND flash	3D NAND flash	3D NAND flash	MLC NAND flash			
Capacity	500GB ~ 2TB	128GB ~ 2TB	120GB ~ 960GB	32GB ~ 1TB			
Operating Environment							
Operating Temperature		0°C (32°F) ~ 70°C (158°F)				
Performance							
Sequential Read/Write	550 MB/s	560 MB/s	550 MB/s	530 MB/s			
(CrystalDiskMark)	500 MB/s	520 MB/s	500 MB/s	460 MB/s			
4K Random Read/Write (IOmeter)	81,000 IOPS 80,000 IOPS	85,000 IOPS 89,000 IOPS	65,000 IOPS 75,000 IOPS	75,000 IOPS 75,000 IOPS			
Mean Time Between Failures (MTBF)	2,000,000 hour(s)	2,000,000 hour(s)	2,000,000 hour(s)	2,000,000 hour(s)			
Terabytes Written (TBW)	400 TB	1,120 TB	320 TB	2,940 TB			
Drive Writes Per Day (DWPD)	0.19 (3 yrs)	0.3 (5 yrs)	0.3 (3 yrs)	2.5 (3 yrs)			
Warranty							
Warranty	Three-year Limited Warranty	Five-year Limited Warranty	Three-year Limited Warranty	Three-year Limited Warranty			
Technology							
TRIM & NCQ Command	\checkmark	\checkmark	\checkmark	\checkmark			
S.M.A.R.T.	\checkmark	\checkmark	\checkmark	\checkmark			
DDR3 DRAM Cache	-	\checkmark	-	\checkmark			
Advanced Garbage Collection	\checkmark	\checkmark	\checkmark	\checkmark			
DevSleep Mode	\checkmark	\checkmark	\checkmark	\checkmark			
RAID Engine	\checkmark	\checkmark	\checkmark	-			
LDPC Coding	\checkmark	\checkmark	\checkmark	-			

*Speed may vary due to host hardware, software, usage, and storage capacity.