



## VP-3

1:3 VGA Distribution Amplifier

---



The Kramer **VP-3** is a newly updated, high-performance 1:3 distribution amplifier designed to accept a single VGA, SVGA, XGA, etc., source and distribute it to three identical outputs using female 15pin HD connectors. Bandwidth 350MHz ensures that the **VP-3** remains transparent even at high-resolution VGA modes. The input and outputs are DC coupled, and provide buffering and isolation which conforms to the highest standards. The **VP-3** is housed in a rugged, desktop sized enclosure but can be rack mounted using the RK-MEDN kit which holds one unit in one vertical space of a standard 19" rack. Combined with Kramer's other VGA switchers and DA's, many VGA routing requirements can be solved.

TECHNICAL SPECIFICATIONS

---

INPUT:	1 VGA/XGA on a 15-pin HD connector.
OUTPUTS:	3 VGA/XGA on 15-pin HD connectors.
MAX. OUTPUT LEVEL:	2.2 Vpp/75Ω (R, G, B).
VIDEO BANDWIDTH (-3DB):	350MHz.
DIFF. GAIN:	0.17%.
DIFF. PHASE:	0.06Deg.
K-FACTOR:	0.05%.
S/N RATIO:	74dB.
COUPLING:	DC.
POWER CONSUMPTION:	230V AC, 50/60 Hz (115V AC, USA) 4.3 VA.
INCLUDED ACCESSORIES:	Power cord.
OPTIONS:	Model RK-MEDN rack mount kit holds one unit in two vertical spaces.