



## BILDVERARBEITUNGS-TECHNOLOGIE

Die Gryphon™ 4500 Serie ist die Premiumreihe im Datalogic Segment der Universal-Scanner. Das neue ergonomische Design garantiert höchste Anwenderfreundlichkeit. Ein innovativer Mexapixel Sensor mit weißer Beleuchtung sorgt außerdem für eine starke Leseleistung.

## TECHNOLOGIE FÜR DEN POS

Der Gryphon I GD4500 kann sowohl als Handheld- als auch als Präsentationsscanner verwendet werden. Dabei unterstützt ihn die Motionix™ Technologie, die anhand der Bewegungen des Anwenders automatisch den passenden Scanmodus einstellt. Diese Technologie funktioniert sowohl mit, als auch ohne Verwendung eines Standhalters. Sowohl die Zieleinrichtung, als auch der Sensor können individuell programmiert werden.

Die weiße Beleuchtung ist für das menschliche Auge angenehmer und steigert außerdem die Leseleistung bei farbigen Etiketten. Die klar sichtbare 4-Punkt-Zieleinrichtung definiert eine präzise Lesezone und reduziert Fehllesungen, da das zentrale Zielkreuz die Erfassung von mehreren Barcodes untereinander vereinfacht.

## EINFACHE VERWENDUNG UND INBETRIEBNAHME

Der Gryphon I GD4500 ist ein omnidirektionaler Imager, der 1D-, 2D-, Post-, Stapel- und Composite Codes wie z.B. PDF417 schnell und zuverlässig auch von mobilen Geräten erfasst. Um kleinere, kondensierende Codes zu erfassen gibt es spezielle High Density (HD) Modelle. Für die Erfassung von digitalen Wasserzeichen wurde eine Version mit roter Beleuchtung entwickelt.

Die verbesserte Optik bietet außerdem eine bessere Bewegungstoleranz und schnelle Erfassung, wenn Codes mit hoher Geschwindigkeit vorbei geführt werden.



### EIGENSCHAFTEN

- 1 MP Optik für höchste Leseleistung und Tiefenschärfe
- Datalogic Technologie mit klar sichtbarer, weißer Beleuchtung und 4-Punkt Zieleinrichtung mit zentralem Zielkreuz
- Patentierte „Green Spot“ Technologie und 3GL™ (3 grüne LED's) für eindeutige Lesebestätigung
- Motionix™ Bewegungserfassungs-Technologie für nahtlosen Wechsel des Lesemodus
- Omnidirektionale Erfassung
- Verbesserte Optik für höhere Bewegungstoleranz
- Bild- und Dokumentenerfassung
- Erfasst 1D-, 2D- und Post-Codes plus Stapel- und Composite Codes
- Spezielle Modelle für die Erfassung von digitalen Wasserzeichen und DPM-Codes
- Mehrfach-Schnittstelle: nur USB oder RS-232 / USB / Keyboard Wedge
- EASEOFCARE Serviceangebote schützen Ihre Investition und sorgen gleichzeitig für maximale Produktivität und RO

### BRANCHE-APPLIKATIONEN

- Retail - Point of Sale
- Einfache Produktionsumgebung
- Gesundheitswesen: Laboratorien, Apotheken, Patientenpflege
- Zugangskontrollen, Transportwesen und Unterhaltungsindustrie
- Dienstleistungen: Postämter, Banken, öffentliche Ämter, Versorgungsunternehmen

## SPEZIFIKATION

### DEKODIERLEISTUNG

1D- / LINEAR CODES	Erfasst alle Standard 1D-Codes inklusive GS1 DataBar™ Linearcodes.
2D CODES	Aztec Code; China Han Xin Code; Data Matrix; MaxiCode; Micro QR Code; QR Code
POST CODES	Australische Post; Britische Post; Chinesische Post; IMB; Japanische Post; KIX Post; Planet Code; Postnet; Royal Mail Code (RM4SCC)
STAPEL CODES	EAN/JAN Composite; GS1 DataBar Composite; GS1 DataBar Stapelcode erweitert; GS1 DataBar Stapel GS1 DataBar Stapel Omnidirektional; MacroPDF; MicroPDF417; PDF417; UPC A/E Composite
DIGITALE WASSERZEICHEN	Digimarc Barcodes

### ELEKTRONIK

STROM	Betrieb: < 300 mA @ 5V; < 200 mA @ 12V Standby/Ruhezustand: < 90 mA @ 5V; < 50 mA @ 12V
EINGANGSSPANNUNG	GD4520: 5 VDC GD4590: 4,5 - 14,0 VDC

### UMGEBUNG

UMGEBUNGSLICHT FALLSCHUTZ	0 - 100,000 lux hält wiederholtem Fall aus 1,8 m h auf Beton stand 16 kV
ESD SCHUTZ (LUFT-ENTLADUNG) LUFTFEUCHTIGKEIT (NICHT KONDENSIEREND) STAUB-/WASSERFEST TEMPERATUR	0 - 95% IP52 Betrieb: 0 bis 50 °C Lager/Transport: -40 bis 70 °C

### SCHNITTSTELLEN

SCHNITTSTELLEN	GD4520: nur USB GD4590: RS-232 / USB / Keyboard Wedge Multi-Schnittstelle
----------------	--

### PHYSISCHE EIGENSCHAFTEN

GEHÄUSEFARBEN	Schwarz; weiß
ABMESSUNGEN	16,6 x 6,8 x 10,9 cm
GEWICHT	161 g

### LESELEISTUNG

BILDERFASSUNG	Graphik Formate: BMP, JPEG, TIFF; Greyscale: 256, 16, 2
BILDSSENSOR LICHT QUELLE	1 Megapixel: 1280 x 800 pixel Rpter Ziel-Laser 650 nm Beleuchtung: warmes weiß; Hyper rote LED für Digimarc 35 IPS
BEWEGUNGSTOLERANZ PRINT CONTRAST RATIO (MINIMUM) LESEWINKEL LESEANZEIGEN	15% Pitch: +/- 65°; Roll (Tilt): 360°; Skew (Yaw): +/- 65° Beeper (Ton einstellbar); Lesebestätigung über Three Green Lights (3GL) & 'Green Spot' auf dem Code, Duale „Good Read“ LEDs
AUFLÖSUNG (MAXIMUM)	High Density (HD): 1D Linear: 0.077 mm / 3 mils; PDF417: 0.077 mm / 3 mils; Data Matrix: 0.102 mm / 4 mils; Standard Range (SR): 1D Linear: 0.102 mm / 4 mils; PDF417: 0.127 mm / 5 mils; Data Matrix: 0.195 mm / 7.5 mils

### LESEREICHWEITE

TYPISCHE TIEFENSCHÄRFE	Minimale Distanz richtet sich nach Symbollänge und Scanwinkel. Druckauflösung abhängig von Kontrast und Umgebungslicht.
<b>GD4500 Standard Reichweite (SR)</b> Code 39: 5 mils: 7,0 bis 38,0 cm Code 39: 10 mils: 2,2 bis 58,0 cm Data Matrix: 10 mils: 5,5 bis 27,0 cm Data Matrix: 15 mils: 2,8 bis 41,0 cm EAN-13: 13 mils: 1,0 bis 71,0 cm PDF417: 10 mils: 2,5 bis 41,0 cm QR Code: 10 mils: 5,5 bis 24,0 cm	<b>GD4500 High Density (HD)</b> Code 39: 3 mils: 5,0 bis 15,0 cm Code 39: 5 mils: 0,5 bis 25,0 cm Data Matrix: 5 mils: 5,5 bis 9,0 cm Data Matrix: 10 mils: 2,0 bis 27,0 cm EAN-13: 7,5 mils: 2,0 bis 23,5 cm EAN-13: 13 mils: 1,0 bis 40,0 cm PDF417: 4 mils: 3,0 bis 12,0 cm PDF417: 10 mils: 0,5 bis 31,0 cm QR Code: 10 mils: 2,0 bis 25,0 cm

### SICHERHEIT & ZERTIFIZIERUNGEN

AMTLICHE GENEHMIGUNGEN	Das Produkt besitzt für den bestimmungsgemäßen Gebrauch alle notwendigen Zulassungen bezüglich Sicherheit. Die Schnellbetriebnahme enthält eine Liste aller Zertifizierungen.
UMWELTBESTIMMUNGEN LASERKLASSE	Entspricht China RoHS; und EU RoHS Achtung: Laserstrahl – nicht in den Strahl blicken! IEC 60825 Klasse 2

### UTILITIES

DATALOGIC ALADDIN™	Datalogic Aladdin Konfigurationsprogramm ist kostenlos zum Download verfügbar
OPOS / JAVAPOS	JavaPOS und OPOS Utilities sind kostenlos zum Download verfügbar
REMOTE HOST DOWNLOAD	Geringere Servicekosten und einfachere Inbetriebnahme

### GEWÄHRLEISTUNG

GEWÄHRLEISTUNG	5-Jahre
----------------	---------

## ZUBEHÖR

### Halter/Standhalter

- 11-0360 Universalhalter, schwarz
- 11-0362 Universalhalter, grau
- HLD-G041-BK Tisch-/Wandhalter, G041, schwarz
- HLD-G041-WH Tisch-/Wandhalter, G041, weiß
- STD-G041-BK Basis-Stand, G041, schwarz
- STD-G041-WH Basis-Stand, G041, weiß



# GRYPHON™ 4500-HC 2D SERIES



WIRELESS CHARGING

WIRELESS, QUICK, CAREFREE

## THE PURPOSE OF BAR CODE READERS IN THE HEALTHCARE INDUSTRY

The key mission of scanners in the healthcare industry is to improve the quality of patient care while reducing medication errors. Additionally, healthcare environments have requirements that scanners need to be regularly cleaned and disinfected. The Datalogic Gryphon™ HC product series is specifically developed for healthcare applications with Disinfectant-Ready enclosures treated with anti-microbial additives and are designed to withstand daily cleaning with harsh disinfectant solutions.

The Gryphon 4500-HC 2D readers can decode virtually any 1D and 2D bar code symbology and can read codes from LCD monitors, cell phones, smartphones and other mobile devices. High Density (HD) models are also available for reading smaller, condensed codes.

Ideally suited for stationary applications in administration, laboratory and hospital environments, the GD4500-HC 2D desktop model offers an affordable corded solution, while the GM4500-HC 2D or GBT4500-HC 2D cordless models (STAR or Bluetooth®) provide extended mobility for cordless operations.

Datalogic distinctive reading technology with highly visible white-illumination is easier on the human eyes and reads colored labels better. The highly visible 4-Dot aimer provides a clear indication of the reading area, making targeting codes quick and easy. Datalogic's patented 'Green Spot' technology provides additional visual good-read confirmation which is ideal for quiet environments like bedside patient care.

One of the most important technical innovations that the Gryphon 4500 wireless readers achieve is the wireless charging system for the battery, which enhances the reliability of the entire solution, while lowering the total cost of ownership (no need for contact cleaning or maintenance procedures).

## ALL PRODUCTS

- Disinfectant-Ready enclosures treated with anti-microbial additives (ISO22196 and JISZ 2801 compliant models available)
- Motionix™ motion-sensing technology for seamless reading mode transitions
- Omnidirectional reading of 1D, 2D, postal codes, stacked and composite bar codes and dot codes
- Extremely snappy reading performance
- Extended reading distances and improved capability of reading small, condensed, curved, poorly printed, and reflective bar codes
- Advanced motion tolerance optics
- Highly visible 4-Dot aimer with center cross for targeted scanning
- Image capture and document scanning capabilities
- Datalogic's patented 'Green Spot' technology and exclusive 3GL™ (3 Green Lights) for superior good-read feedback
- USB Certified Kits Available
- ISO22196 Compliant Models Available

## WIRELESS MODELS

- Choice of Bluetooth wireless technology version 4.0 with BLE or Datalogic's STAR Cordless System (radio frequencies available in 433 MHz or 910 MHz)
- Datalogic's distinctive Wireless Battery Charging System
- Adjustable position cradle with Scan-While-Charging capability
- Batch Mode capability
- Point-to-point / Point-to-multi-point transmission
- Long lasting user-replaceable Lithium-Ion battery
- Vibration feedback



MEDITECH



## GRYPHON™ 4500-HC 2D SERIES

# TECHNICAL SPECIFICATIONS

### DECODING CAPABILITY

<b>1D / linear codes</b>	Autodiscriminates all standard 1D codes including GS1 DataBar™ linear codes.
<b>2D codes</b>	Aztec Code; China Han Xin Code; Data Matrix; MaxiCode; Micro QR Code; QR Code; Dot code
<b>Postal codes</b>	Australian Post; British Post; China Post; IMB; Japanese Post; KIX Post; Planet Code; Postnet; Royal Mail Code (RM4SCC)
<b>Stacked codes</b>	EAN/JAN Composites; GS1 DataBar Composites; GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional; MacroPDF; MicroPDF417; PDF417; UPC A/E Composites

### ELECTRICAL

<b>Current</b>	Operating: <300 mA @ 5V; < 200 mA @ 12V Standby/Idle: < 90 mA @ 5V; <50 mA @ 12V
<b>Input voltage</b>	GD4520: 5 VDC GD4590: 4.5 - 14.0 VDC

### ENVIRONMENTAL

<b>Ambient light</b>	0 - 100,000 lux
<b>Drop resistance</b>	Withstands repeated drops from 1.8 m / 6.0 ft onto a concrete surface.
<b>ESD Protection (Air Discharge)</b>	16 kV
<b>Humidity (Non-Condensing)</b>	0 - 95%
<b>Particulate and Water Sealing</b>	IP52
<b>Temperature</b>	Operating: 0 to 50 °C / 32 to 122 °F Storage/Transport: -40 to 70 °C / -40 to 158 °F

### INTERFACES

<b>Interfaces</b>	GD4520: USB only GD4590: RS-232 / USB / Keyboard Wedge Multi-Interface
-------------------	---

### PHYSICAL CHARACTERISTICS

<b>Colors Available</b>	Light Green/Light Grey (Rubber/Plastic)
<b>Dimensions</b>	16.6 x 6.8 x 10.9 cm / 6.5 x 2.7 x 4.3 in
<b>Weight</b>	161.0 g / 5.7 oz

## DATALOGIC DISINFECTANT-READY ENCLOSURES FOR HEALTHCARE

Datalogic offers bar code readers designed specifically for the healthcare industry with Disinfectant-Ready enclosures treated with anti-microbial additives that can help fight against the spreading of germs. This is particularly important if the scanner is traveling room-to-room on a medication cart with a nurse. The Disinfectant-Ready enclosures can withstand daily cleaning with harsh chemical cleaning solutions commonly used in a healthcare environment.



REFER TO THE DEVICE INSTRUCTION MANUAL FOR PROPER CLEANING METHODS WHEN USING THESE CHEMICALS. DISINFECTANTS SHOULD NOT BE SPRAYED OR Poured ONTO THE SCANNER UNIT. THE SCANNERS MUST ALWAYS BE WIPED DRY AFTER DISINFECTING.

### READING PERFORMANCE

<b>Image Capture</b>	Graphic Formats: BMP, JPEG, TIFF; Greyscale: 256, 16, 2
<b>Image Sensor</b>	1 Megapixel: 1280 x 800 pixels
<b>Light source</b>	Aiming: Red Laser 650 nm Illumination: Warm White; Hyper Red LED for Digimarc
<b>Motion tolerance</b>	35 IPS
<b>Print contrast ratio (minimum)</b>	15%
<b>Reading angle</b>	Pitch: +/- 65°; Roll (Tilt): 360°; Skew (Yaw): +/- 65°
<b>Reading indicators</b>	Beeper (Adjustable Tone); Datalogic Three Green Lights (3GL) Good Read Feedback; Datalogic 'Green Spot' on the Code, Dual Good Read LEDs
<b>Resolution (maximum)</b>	High Density (HD): 1D Linear: 0.077 mm / 3 mils; PDF417: 0.077 mm / 3 mils; Data Matrix: 0.102 mm / 4 mils Standard Range (SR): 1D Linear: 0.102 mm / 4 mils; PDF417: 0.127 mm / 5 mils; Data Matrix: 0.195 mm / 7.5 mils

### READING RANGES

<b>Typical depth of field</b>	Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent.
-------------------------------	--

#### GD4500 Standard Range (SR)

Code 39: 5 mils: 7.0 to 38.0 cm / 2.7 to 14.9 in  
Code 39: 10 mils: 2.2 to 58.0 cm / 0.8 to 22.8 in  
Data Matrix: 10 mils: 5.5 to 27.0 cm / 2.2 to 10.6 in

Data Matrix: 15 mils: 2.8 to 41.0 cm / 1.1 to 16.1 in  
EAN-13: 13 mils: 1.0 to 71.0 cm / 0.4 to 27.9 in  
PDF417: 10 mils: 2.5 to 41.0 cm / 1.0 to 16.1 in  
QR Code: 10 mils: 5.5 to 24.0 cm / 2.2 to 9.5 in

#### GD4500 High Density (HD)

Code 39: 3 mils: 5.0 to 15.0 cm / 2.0 to 5.9 in  
Code 39: 5 mils: 0.5 to 25.0 cm / 0.2 to 9.8 in  
Data Matrix: 5 mils: 5.5 to 9.0 cm / 2.2 to 3.5 in

Data Matrix: 10 mils: 2.0 to 27.0 cm / 0.8 to 10.6 in  
EAN-13: 7.5 mils: 2.0 to 23.5 cm / 0.8 to 9.3 in  
EAN-13: 13 mils: 1.0 to 40.0 cm / 0.4 to 15.7 in  
PDF417: 4 mils: 3.0 to 12.0 cm / 1.2 to 4.7 in  
PDF417: 10 mils: 0.5 to 31.0 cm / 0.2 to 12.2 in  
QR Code: 10 mils: 2.0 to 25.0 cm / 0.8 to 9.8 in

### SAFETY & REGULATORY

<b>Agency Approvals</b>	The product meets necessary safety and regulatory approvals for its intended use. The Quick Reference Guide for this product can be referred to for a complete list of certifications.
<b>Environmental Compliance</b>	Complies to China RoHS; Complies to EU RoHS
<b>Laser Classification</b>	Caution Laser Radiation - Do not stare into beam; IEC 60825 Class 2

### UTILITIES

<b>Datalogic Aladdin™</b>	Datalogic Aladdin configuration program is available for download at no charge.
<b>OPOS JavaPOS</b>	JavaPOS and OPOS Utilities are available for download at no charge.
<b>Remote Host Download</b>	Lowers service costs and improves operations

### WARRANTY

<b>Warranty</b>	5-Year Factory Warranty
-----------------	-------------------------

### PRODUCT CHEMICAL CONTENT

Sani-Cloth® HB, Sani-Cloth® Plus, Super Sani-Cloth®	Quaternary Ammonium Chloride solution
Hepacide Quat II	Virucidal disinfectant cleaner
Alcohol Wipes	70% Isopropyl Alcohol
CaviWipes™	Isopropanol 10-20%; Ethylene Glycol Monobutyl Ether 1-5%
Virex® 256	n-Alkyl Dimethyl Benzyl Ammonium Chloride; Didecyl Dimethyl Ammonium Chloride
409® Glass and Surface Cleaner	n-Alkyl Dimethyl Benzyl Ammonium Chloride; n-Propoxypropanol
Windex® Blue	Isopropyl Alcohol
Clorox® Bleach	Sodium Hypochlorite; Sodium Hydroxide
100% Gentle dish soap and water	

## GRYPHON™ 4500-HC 2D SERIES

# TECHNICAL SPECIFICATIONS

### CORDLESS COMMUNICATIONS

<b>Datalogic STAR Cordless System™</b>	Effective Radiated Power: 433.92 MHz: < 6.3 mW; 910 MHz: < 50 mW Multi-Point Configuration: Max. Readers per Radio Receiver: 16; Point-to-Point Configuration; Radio Frequency: 433.92 MHz; 910 MHz; Two Way Communications Radio Range (Open Air): 50.0 m / 164.0 ft; Range distances are measured using the base station.
--	---

### DECODING CAPABILITY

<b>1D / linear codes</b>	Autodiscriminates all standard 1D codes including GS1 DataBar™ linear codes.
<b>2D codes</b>	Aztec Code; China Han Xin Code; Data Matrix; MaxiCode; Micro QR Code; QR Code; Dot code
<b>Postal codes</b>	Australian Post; British Post; China Post; IMB; Japanese Post; KIX Post; Planet Code; Postnet; Royal Mail Code (RM4SCC)
<b>Stacked codes</b>	GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional; MacroPDF; MicroPDF417; PDF417; UPC A/E Composites

### ELECTRICAL

<b>Battery</b>	Battery Type: Lithium-Ion: 3250 mAh Charge Time: External Power: 4 Hours @ 12 VDC; Reads per Charge: 80,000
<b>Cradle Indicator LEDs</b>	Battery Charging (flashing orange); Charge Completed (steady green)
<b>Current</b>	Charging (Typical): < 6 W; Scanner only: 330 mA @ 3.7 V (Operative) Cradle Only: 80 mA @ 5 V (Operative)
<b>Input voltage</b>	4.5 - 14 VDC +/- 5%

### ENVIRONMENTAL

<b>Ambient light</b>	0 - 100,000 lux
<b>Drop resistance</b>	Withstands repeated drops from 1.8 m / 6.0 ft onto a concrete surface.
<b>ESD Protection (Air Discharge)</b>	16 kV
<b>Humidity (Non-Condensing)</b>	0 - 95%
<b>Particulate and Water Sealing</b>	IP52
<b>Temperature</b>	Operating: 0 to 50 °C / 32 to 122 °F Storage/Transport: -40 to 70 °C / -40 to 158 °F

### INTERFACES

<b>Interfaces</b>	RS-232 / USB / Keyboard Wedge Multi-Interface
-------------------	---

### PHYSICAL CHARACTERISTICS

<b>Colors Available</b>	Light Green/Light Grey (Rubber/Plastic)
<b>Dimensions</b>	16.6 x 6.8 x 10.9 cm / 6.5 x 2.7 x 4.3 in
<b>Weight</b>	235 g / 8.29 oz
<b>Enclosure</b>	Disinfectant-Ready Enclosure Treated with Anti-Microbial Additives (ISO22196 and JISZ 2801 compliant models available)

### READING PERFORMANCE

<b>Image Capture</b>	Graphic Formats: BMP, JPEG, TIFF; Greyscale: 256, 16, 2
<b>Image Sensor</b>	1 Megapixel: 1280 x 800 pixels
<b>Light source</b>	Aiming: Red Laser 650 nm Illumination: Warm White;
<b>Motion tolerance</b>	35 IPS
<b>Print contrast ratio (minimum)</b>	15%
<b>Reading angle</b>	Pitch: +/- 65°; Roll (Tilt): 360°; Skew (Yaw): +/- 65°
<b>Reading indicators</b>	Beeper (adjustable tone); Vibration feedback option available for quiet places; Datalogic Three Green Lights (3GL) Good Read Feedback: Datalogic 'Green Spot' on the Code, Dual Good Read LEDs
<b>Resolution (maximum)</b>	High Density (HD): 1D Linear: 0.077 mm / 3 mils; PDF417: 0.077 mm / 3 mils; Data Matrix: 0.102 mm / 4 mils Standard Range (SR): 1D Linear: 0.102 mm / 4 mils; PDF417: 0.127 mm / 5 mils; Data Matrix: 0.195 mm / 7.5 mils

### READING RANGES

<b>Typical depth of field</b>	Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent.
	<b>GD4500 Standard Range (SR)</b>
	Code 39: 5 mils: 7.0 to 38.0 cm / 2.7 to 14.9 in Code 39: 10 mils: 2.2 to 58.0 cm / 0.8 to 22.8 in Data Matrix: 10 mils: 5.5 to 27.0 cm / 2.2 to 10.6 in Data Matrix: 15 mils: 2.8 to 41.0 cm / 1.1 to 16.1 in EAN-13: 13 mils: 1.0 to 71.0 cm / 0.4 to 27.9 in PDF417: 10 mils: 2.5 to 41.0 cm / 1.0 to 16.1 in QR Code: 10 mils: 5.5 to 24.0 cm / 2.2 to 9.5 in

### SAFETY & REGULATORY

<b>Agency Approvals</b>	The product meets necessary safety and regulatory approvals for its intended use. The Quick Reference Guide for this product can be referred to for a complete list of certifications.
<b>Environmental Compliance</b>	Complies to China RoHS; Complies to EU RoHS
<b>Laser Classification</b>	Caution Laser Radiation - Do not stare into beam; IEC 60825 Class 2

### UTILITIES

<b>Datalogic Aladdin™</b>	Datalogic Aladdin configuration program is available for download at no charge.
<b>OPOS JavaPOS</b>	JavaPOS and OPOS Utilities are available for download at no charge.
<b>Remote Host Download</b>	Lowers service costs and improves operations

### WARRANTY

<b>Warranty</b>	3-Year Factory Warranty
-----------------	-------------------------



# GRYPHON™ 4500-HC 2D SERIES

## TECHNICAL SPECIFICATIONS

### CORDLESS COMMUNICATIONS

<b>Bluetooth Wireless Technology</b>	Piconet: Max. Readers per Radio Receiver: 7 Profiles: SPP (Serial Port Profile) Protocol: Bluetooth 4.0 with BLE Certified Class 1, Class 2 and Class 3; Radio Frequency: 2.4 GHz Radio Range (Open Air): 100.0 m / 328.0 ft; Range distances are measured using the base station. Range with connection to other Bluetooth peripherals may show different results. Security: Data Encryption; Scanner Authentication
--------------------------------------	--

### DECODING CAPABILITY

<b>1D / linear codes</b>	Autodiscriminates all standard 1D codes including GS1 DataBar™ linear codes.
<b>2D codes</b>	Aztec Code; China Han Xin Code; Data Matrix; MaxiCode; Micro QR Code; QR Code; Dot code
<b>Postal codes</b>	Australian Post; British Post; China Post; IMB; Japanese Post; KIX Post; Planet Code; Postnet; Royal Mail Code (RM4SCC)
<b>Stacked codes</b>	EAN/JAN Composites; GS1 DataBar Composites; GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional; MacroPDF; MicroPDF417; PDF417; UPC A/E Composites

### ELECTRICAL

<b>Battery</b>	Battery Type: Lithium-Ion: 3250 mAh Charge Time: External Power: 4 Hours @ 12 VDC; Reads per Charge: 80,000
<b>Cradle Indicator LEDs</b>	Battery Charging (flashing orange); Charge Completed (steady green)
<b>Current</b>	Charging (Typical): < 6 W; Gun Only: 330 mA @ 3.7 V (Operative) Cradle Only: 80 mA @ 5 V (Operative)
<b>Input voltage</b>	4.5 - 14 VDC +/- 5%

### ENVIRONMENTAL

<b>Ambient light</b>	0 - 100,000 lux
<b>Drop resistance</b>	Withstands repeated drops from 1.8 m / 6.0 ft onto a concrete surface.
<b>ESD Protection (Air Discharge)</b>	16 kV
<b>Humidity (Non-Condensing)</b>	0 - 95%
<b>Particulate and Water Sealing</b>	IP52
<b>Temperature</b>	Operating: 0 to 50 °C / 32 to 122 °F Storage/Transport: -40 to 70 °C / -40 to 158 °F

### INTERFACES

<b>Interfaces</b>	RS-232 / USB / Keyboard Wedge Multi-Interface
-------------------	---

### PHYSICAL CHARACTERISTICS

<b>Colors Available</b>	Light Green/Light Grey (Rubber/Plastic)
<b>Dimensions</b>	16.6 x 6.8 x 10.9 cm / 6.5 x 2.7 x 4.3 in
<b>Weight</b>	235 g / 8.29 oz
<b>Enclosure</b>	Disinfectant-Ready Enclosure Treated with Anti-Microbial Additives (ISO22196 and JISZ 2801 compliant models available)

### READING PERFORMANCE

<b>Image Capture</b>	Graphic Formats: BMP, JPEG, TIFF; Greyscale: 256, 16, 2
<b>Image Sensor</b>	1 Megapixel: 1280 x 800 pixels
<b>Light source</b>	Aiming: Red Laser 650 nm Illumination: Warm White;
<b>Motion tolerance</b>	35 IPS
<b>Print contrast ratio (minimum)</b>	15%
<b>Reading angle</b>	Pitch: +/- 65°; Roll (Tilt): 360°; Skew (Yaw): +/- 65°
<b>Reading indicators</b>	Beeper (adjustable tone); Vibration feedback option available for quiet places; Datalogic Three Green Lights (3GL) Good Read Feedback: Datalogic 'Green Spot' on the Code, Dual Good Read LEDs
<b>Resolution (maximum)</b>	High Density (HD): 1D Linear: 0.077 mm / 3 mils; PDF417: 0.077 mm / 3 mils; Data Matrix: 0.102 mm / 4 mils Standard Range (SR): 1D Linear: 0.102 mm / 4 mils; PDF417: 0.127 mm / 5 mils; Data Matrix: 0.195 mm / 7.5 mils

### READING RANGES

<b>Typical depth of field</b>	Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent.
-------------------------------	--

<i>GD4500 Standard Range (SR)</i>	<i>GD4500 High Density (HD)</i>
Code 39: 5 mils: 7.0 to 38.0 cm / 2.7 to 14.9 in	Code 39: 3 mils: 5.0 to 15.0 cm / 2.0 to 5.9 in
Code 39: 10 mils: 2.2 to 58.0 cm / 0.8 to 22.8 in	Code 39: 5 mils: 0.5 to 25.0 cm / 0.2 to 9.8 in
Data Matrix: 10 mils: 5.5 to 27.0 cm / 2.2 to 10.6 in	Data Matrix: 5 mils: 5.5 to 9.0 cm / 2.2 to 3.5 in
Data Matrix: 15 mils: 2.8 to 41.0 cm / 1.1 to 16.1 in	Data Matrix: 10 mils: 2.0 to 27.0 cm / 0.8 to 10.6 in
EAN-13: 13 mils: 1.0 to 71.0 cm / 0.4 to 27.9 in	EAN-13: 7.5 mils: 2.0 to 23.5 cm / 0.8 to 9.3 in
PDF417: 10 mils: 2.5 to 41.0 cm / 1.0 to 16.1 in	EAN-13: 13 mils: 1.0 to 40.0 cm / 0.4 to 15.7 in
QR Code: 10 mils: 5.5 to 24.0 cm / 2.2 to 9.5 in	PDF417: 4 mils: 3.0 to 12.0 cm / 1.2 to 4.7 in
	PDF417: 10 mils: 0.5 to 31.0 cm / 0.2 to 12.2 in
	QR Code: 10 mils: 2.0 to 25.0 cm / 0.8 to 9.8 in

### SAFETY & REGULATORY

<b>Agency Approvals</b>	The product meets necessary safety and regulatory approvals for its intended use. The Quick Reference Guide for this product can be referred to for a complete list of certifications.
<b>Environmental Compliance</b>	Complies to China RoHS; Complies to EU RoHS
<b>Laser Classification</b>	Caution Laser Radiation - Do not stare into beam; IEC 60825 Class 2

### UTILITIES

<b>Datalogic Aladdin™</b>	Datalogic Aladdin configuration program is available for download at no charge.
<b>OPOS JavaPOS</b>	JavaPOS and OPOS Utilities are available for download at no charge.
<b>Remote Host Download</b>	Lowers service costs and improves operations

### WARRANTY

<b>Warranty</b>	3-Year Factory Warranty
-----------------	-------------------------

## ACCESSORIES

### Mount / Stands



• 11-0362:  
Holder, Multi-  
Purpose, Grey



• HLD-G041-WH  
Desk/Wall Holder,  
G041, White



• STD-G041-WH  
Basic Stand, G041,  
White

### Cordless Products

- Battery/Battery Charger
- MC-GM45 Battery Charger, 4-Slot
  - RBP-GM45 Removable Battery Pack



- Base Stations/Chargers
- WLC4090-HC-BT Base station; Wireless Charger; Multi-Interface; HC; Bluetooth
  - WLC4090-HC-433 Base station; Wireless Charger; Multi-Interface; HC; 433 MHz
  - WLC4090-HC-910 Base station; Wireless Charger; Multi-Interface; HC; 910 MHz

