




- 200-927BK** RG6 CCS Black – Reel in Box
- 200-927WH** RG6 CCS White – Reel in Box
- 200-929BK** RG6 CCS UL/CM Black – Spool
- 200-929WH** RG6 CCS UL/CM White – Spool
- 200-931BK** RG6 CCS UL/CM Black – Reel in Box
- 200-931IV** RG6 CCS UL/CM Ivory – Reel in Box
- 200-931WH** RG6 CCS UL/CM White – Reel in Box
- 200-942BK** RG6 Copper UL/CM Black – Reel in Box
- 200-942WH** RG6 Copper UL/CM White – Reel in Box



- 200-935BK** RG6 Copper UL/CM w/Ground Black – Spool
- 200-935WH** RG6 Copper UL/CM w/Ground White – Spool
- 200-945BK** RG6 CCS w/Ground Black – Spool
- 200-945WH** RG6 CCS w/Ground White – Spool
- 200-946BK** RG6 CCS UL/CM w/Ground Black – Reel in Box
- 200-946WH** RG6 CCS UL/CM w/Ground White – Reel in Box



- 200-936BK** RG6-Quad Copper UL/CM Black – Spool
- 200-936WH** RG6-Quad Copper UL/CM White – Spool
- 200-937BK** RG6-Quad CCS UL/CM Black – Spool
- 200-937WH** RG6-Quad CCS UL/CM White – Spool



- 200-938BK** RG6 Copper UL/CM Dual Black – Spool
- 200-938WH** RG6 Copper UL/CM Dual White – Spool
- 200-948BK** RG6 CCS UL/CM Dual Black – Reel in Box
- 200-948WH** RG6 CCS UL/CM Dual White – Reel in Box



- 200-939BK** RG6 Copper UL/CM Dual w/Ground Black – Spool
- 200-939WH** RG6 Copper UL/CM Dual w/Ground White – Spool
- 200-940BK** RG6 CCS UL/CM Dual w/Ground Black – Reel in Box
- 200-940WH** RG6 CCS UL/CM Dual w/Ground White – Reel in Box
- 200-949BK** RG6 CCS Dual w/Ground Black – Reel in Box
- 200-949WH** RG6 CCS Dual w/Ground White – Reel in Box

## Series-6 Coaxial Drop Cable

RG6/U Coaxial Cable  
 Suitable for Digital HDTV Applications, CATV and Satellite Installations  
 Fully Sweep Tested to 3GHz  
 18 AWG Solid Copper or Copper-Clad Steel Center Conductor  
 Gas Injected Polyethylene Dielectric  
 Aluminum Foil Shield Bonded to Dielectric Insulator  
 Aluminum Braid Shield, 60% or 60%-40% Coverage  
 17 AWG Copper-Clad Steel Ground Wire  
 Flame Retardant Lead-Free PVC Jacket, Foot-Marked Inhibitor additive protects cable from UV damage  
 Dielectric 0.180" (4.57mm) nom. OD  
 PVC Jacket 0.275" (7.00mm) nom. OD  
 Nominal Impedance 75 ±3 Ohms  
 Nominal Attenuation 6.54dB @ 1GHz, 10.0dB @ 2250MHz  
 Structural Return Loss 20dB max @ 5-1000MHz, 15dB max @ 1001-2250MHz

### CCS Conductor, UL/CM

- 200-929BK** 1000' RG6 Black – Spool
- 200-929WH** 1000' RG6 White – Spool
- 200-931BK** 1000' RG6 Black – Reel in Box
- 200-931IV** 1000' RG6 Ivory – Reel in Box
- 200-931WH** 1000' RG6 White – Reel in Box
- 200-937BK** 1000' RG6-Quad Black – Spool
- 200-937WH** 1000' RG6-Quad White – Spool
- 200-940BK** 500' RG6 Dual w/Ground Black – Reel in Box
- 200-940WH** 500' RG6 Dual w/Ground White – Reel in Box
- 200-946BK** 1000' RG6 w/Ground Black – Reel in Box
- 200-946WH** 1000' RG6 w/Ground White – Reel in Box
- 200-948BK** 500' RG6 Dual Black – Reel in Box
- 200-948WH** 500' RG6 Dual White – Reel in Box

### CCS Conductor, Non-UL

- 200-927BK** 1000' RG6 Black – Reel in Box
- 200-927WH** 1000' RG6 White – Reel in Box
- 200-945BK** 500' RG6 w/Ground Black – Spool
- 200-945WH** 500' RG6 w/Ground White – Spool
- 200-949BK** 500' RG6 Dual w/Ground Black – Reel in Box
- 200-949WH** 500' RG6 Dual w/Ground White – Reel in Box

### Copper Conductor, UL/CM

- 200-935BK** 1000' RG6 w/Ground Black – Spool
- 200-935WH** 1000' RG6 w/Ground White – Spool
- 200-936BK** 1000' RG6-Quad Black – Spool
- 200-936WH** 1000' RG6-Quad White – Spool
- 200-938BK** 1000' RG6 Dual Black – Spool
- 200-938WH** 1000' RG6 Dual White – Spool
- 200-939BK** 500' RG6 Dual w/Ground Black – Spool
- 200-939WH** 500' RG6 Dual w/Ground White – Spool
- 200-942BK** 1000' RG6 Black – Reel in Box
- 200-942WH** 1000' RG6 White – Reel in Box

*See Steren Catalog pg. A12  
for more products in this category*