

PRODUCT DATASHEETP CLAS A 75 11.5 W/2700K E27

PARATHOM MOTION SENSOR CLASSIC A | Special LED lamps with motion sensor, classic bulb shape



AREAS OF APPLICATION

- For indoor use only

PRODUCT BENEFITS

- Short payback period thanks to low energy consumption and maintenance costs
- Energy-saving lighting solution thanks to automatic switch off at daylight
- Very long lifetime of up to 25,000 h
- Automatic light switch off 15 seconds after the last motion detection
- Illumination threshold for automatic switching: 10 lx
- Low energy consumption
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time

PRODUCT FEATURES

- LED alternative to conventional lamps
- High color consistency: \leq 6 SDCM
- Mercury-free lamps



TECHNICAL DATA

Electrical data

| Rated wattage | 11.50 W |
|---------------------|----------|
| Nominal wattage | 11.50 W |
| Nominal voltage | 220240 V |
| Operating frequency | 5060 Hz |

Photometrical data

| Rated color temperature | 2700 K |
|---|------------|
| Lumen main.fact.at end of nom.life time | 0.70 |
| Light color (designation) | Warm White |
| Color temperature | 2700 K |
| Luminous flux | 1060 lm |
| Color rendering index Ra | ≥80 |
| Nominal luminous flux | 1060 lm |

Dimensions & weight



Lifespan

| Nominal lamp life time | 25000 h |
|----------------------------|---------|
| Rated lamp life time | 25000 h |
| Number of switching cycles | 100000 |

Additional product data

| Base (standard designation) | E27 |
|-----------------------------|-----|
| Mercury-free | Yes |

| Product remark | All technical parameters apply to the entire lampDue to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not | |
|----------------|---|--|
| | necessarily match the actual technical parameters of each individual product, which can vary from the typical value | |

Capabilities

| Dimmable | No |
|----------|----|
|----------|----|

Certificates & standards

| Energy efficiency class | A+ |
|-------------------------|----|

Country-specific categorizations

| ILCOS | DRAA/F-11,5/827-220-240-E27-60 | |
|-----------------|--------------------------------|--|
| Order reference | LEDPCLA75MS 11, | |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075815698 | Folding carton box 1 | 62 mm x 62 mm x 126 mm | 97.00 g | 0.48 dm³ |
| 4058075815704 | Shipping carton box 10 | 327 mm x 136 mm x 141 mm | 1068.00 g | 6.27 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.