



FAST AND RELIABLE



INCREASE WORK FFFICIENCY WITH

FASTER SCANNING

High-Speed, High-Volume Scanning

A high-speed engine, made possible by advances in hardware image processing technology, provides maximum efficiency when processing large volumes of documents.

140_{ppm} 280_{ipm} 120_{ppm} 240_{ipm}

ADF 750 sheets (LTR/A4)


RELIABLE PAPER FEED

ToughFeed

TOUGHFEED

Document Protection

Multiple sensors check the paper feed conditions to automatically optimize the scanning of various documents while preventing them from being damaged.




- Acoustic jam microphone sensor Scanning is stopped when an abnormal noise is detected during the paper feed.
- Feed pressure sensor Detects the amount of pressure being applied by the feed roller and automatically adjusts the height of the feed tray.
- Stapled document detection sensor Used to detect various types of stapled documents to immediately stop the scanner when staples are detected.

NEW MECHANICAL DESKEW


The KV-S8147 is capable of correcting up to 10 degrees of physical document skew during the feeding process.

Document skewing is corrected using an independent feed motor and roller system.





Skewed documents entering the feeder.



Skewing is then reduced mechanically before scanning

DOUBLE FEED RETRY (KV-S8147 ONLY)

If a double feed is detected, the double feed retry function will return the documents to the feed tray automatically, then rescan the documents again.



Double feeding is detected.

Documents are returned to the trav.

The double-fed documents are re-fed, separated, and scanned.


ADJUSTABLE FEED/EXIT TRAY

The document feed tray automatically lifts documents to the optimal position for reliable feeding.

Feed Tray

The feed tray quickly rises and maintains optimal pressure against the feed rollers.





Exit Tray

The exit tray remains at the optimal height from the scanners exit rollers to prevent fluctuations.





Double Feed Skip (DFS)

Double Feed Skip (DFS) provides users the ability to ignore and skip a double feed detection and continue scanning without restarting the scan process. This feature is designed for applications where special document types are fed, such as envelopes or documents with labels on them.



HIGH DURABILITY, LOW MAINTENANCE

NEW TOUGH, RELIABLE, LONG-LIFE ROLLER

The KV-S8127 and KV-S8147 have a rated feed roller replacement life of 600,000 scanned pages. Panasonic offers two feed roller kit options depending on actual scanning volume.

Roller Exchange Kit

Model No.	KV-SS100	KV-SS101
Contents	Single Replacement Roller Kit Feed roller unit (2 pieces) Double feed prevention roller unit (1 piece) Separation roller unit (1 piece)	*Trained technician or operator recommended. • Feed roller (12 pieces) • Double feed prevention roller (6 pieces) • Separation roller (6 pieces) • Double feed prevention roller torque limiter (3 pieces)
Roller Replacement	600,000 sheets	3,600,000 sheets*

^{*} KV-SS101 is a set with parts for six replacements. 1 replacement = 600,000 sheets

HIGHLY DURABLE GLASS COATING

The use of a highly durable glass coating reduces vertical streaking of images due to the effects of paper dust, and decreases the required frequency of maintenance.

EASY MAINTENANCE

Maintenance of the paper transport path is easy because the ADF door opens widely. In addition, the built-in cleaning mode rotates the conveyor and exit rollers to easily clean the entire surface of each without manually rotating the rollers.





FULL-COLOR LCD

An easy to see, full color LCD display provides users with simple access to the scanner's built-in settings and maintenance counters.







Job screen

Menu screen



COMPARE THE PERFORMANCE of PANASONIC SCANNERS

ENGINEERED FOR THE REAL WORLD

ATIONS	Image Sensor Type	3 Line Color Contact Image Sensor Automatic Black and White Background Reference	
E E	Light Source	RGB LED	
TECHNICAL SPECIFICATIONS	Optical Resolution	100 – 600 dpi (1 dpi step) 1,200 dpi (Interpolated) Optical: 300 dpi / 600 dpi (Automatic switch)	
TECHNIC	Output Resolution	Color: 24-bit Grayscale: 8-bit Monochrome: 1-bit	
	Output Color Depth	Color: 24-bit Grayscale: 8-bit Monochrome: 1-bit	
	Image Processing Function	Automatic Brightness Adjustment, Automatic Image Emphasis, Dynamic Threshold, White Level From Paper, Automatic Separation, Noise Reduction, Auto Preview, Auto Rescan, Multi color Dropout, Dither, Error Diffusion Detection	
NCE	Scanning Speed ¹	Simplex: Up to 120 ppm (KV-S8127) Up to 140 ppm (KV-S8147)	
PERFORMANCE		Duplex: Up to 240 ipm (KV-S8127) Up to 280 ipm (KV-S8147)	
œ			
	ADF Capacity	Up to 750 Sheets: 21 lbs. (80 g/m2)*	
PE	ADF Capacity Document Size	Up to 750 Sheets: 21 lbs. [80 g/m2]* ADF Manual Feeding: 1.9 in. x 4.33 in. to 12.09 in. x unlimited [KV-S8127] 1.9 in. x 2.75 in. to 12.09 in. x unlimited [KV-S8147]	
PE		ADF Manual Feeding: 1.9 in. x 4.33 in. to 12.09 in. x unlimited (KV-S8127)	
9d		ADF Manual Feeding: 1.9 in. x 4.33 in. to 12.09 in. x unlimited (KV-S8127) 1.9 in. x 2.75 in. to 12.09 in. x unlimited (KV-S8147) ADF Automatic Feeding:	

*LDG/A3: Up to 500 sheets

The scanning speed differs depending on the host computer, the operating system, the application, the measuring method, the quantity of data in the image, and the paper type. The scanning speed depends on a measuring meth

- ENERGY STAR and the ENERGY STAR mark are registered U.S. marks.

- ISIS is a registered trademark or trademark of EMC Corporation in the United States and other countries.

- Windows, Windows Vista, Windows Server and Internet Explorer are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

- Mozilla and Firefox are registered trademarks of the Mozilla Foundation.

- Google and Google Chrome are trademarks or registered trademarks of Google, Inc.

- All other brand or product names are the property of their respective holders.

This product is designed to reduce hazardous chemical substances in accordance with the RoHS directive.

AC 100-120 V, 50/60 Hz, 2.7 A Power Requirements² PHYSICAL SPECIFICATIONS AC 100-240 V. 50/60 Hz. 2.7-1.5 A Maximum (Scanning): 140W or less **Power Consumption** Minimum (Ready): 35W or less Sleep: 2.0 W or less Power Off: 0.5 W or less Dimensions (WxDxH) 21.5 in.×18.7 in. ×17.1 in. (545 x 474 x 435 mm) Weight 98 lbs. [44.4 kg] **Inbox Contents** Quick Installation Guide, Power cord, USB 3.0 Cable, Panasonic Software CD-ROM, Double Feed Prevention Roller, Shading Paper and Attachment Guide **Bundled Software** Panasonic Image Capture Plus, Panasonic User Utility, Universal TWAIN Driver, ISIS Driver, WIA Driver Options Roller Exchange Kit: KV-SS100 (600K Roller Kit) and KV-SS101 (3.6M Roller Kit), Roller Cleaning Paper: KV-SS03. Pre and Post Imprinters: KV-SS014. Ink. cartridge: KV-SS021, Kofax® VRS Elite 5 (KV-S8127-V and KV-S8147-V), Network Scanning Option: KV-SSM100, Flatbed Scanner Option: KV-SS080, Site Central Management Software Windows® XP SP3 (32bit/64bit), **OS Support** Windows Vista® SP2 (32bit/64bit), Windows® 7 (32bit/64bit), Windows® 8 (32bit/64bit), Windows® 8.1 (32bit/64bit), Windows® 10 (32bit/64bit), Windows Server® 2003 SP2 (32bit/64bit), Windows Server® 2003 R2 SP2 (32bit/64bit), Windows Server® 2008 SP2 (32bit/64bit), Windows Server® 2008 R2 SP1 [64bit]. Windows Server® 2012 (64bit) Feed Detection Features Control Sheet Detection, Long Paper. Intelligent Double Feed Detection, Stapled Document Detection, Acoustic Jam Detection Other Functions Barcode Detection, Length Control, Patch Code Detection (Ttype 2, 3, T), Double Feed Skip, Double Feed Retry (KV-S8147 only), Mechanical Deskew (KV-S8147 only), 100 Programmable Work-flows , Long Paper Mode 6 Months On-Site Warranty Next Business Day Onsite & Pro-Tech Service Options Service Available





Streamline your scanning process

The KV-S8127 and KV-S8147 high-volume production scanners, mark the latest additions to Panasonic's line of document scanners. Designed for banks, government, service bureaus and any high volume scanning environment. The KV-S8100 series delivers top of the line features and functionality to help increase efficiency and decrease production scanning costs.

Both models support a large capacity of 750 sheets via the built-in ADF*, advanced hardware image processing, and Panasonic's Toughfeed intelligent feed control for scanning a wide range of documents from thin paper to cardboard. The highly durable, long life rollers can scan up to 600,000 documents between replacements.

To find out more about Panasonic Scanning Solutions visit us.panasonic.com/scanners or call 877-207-0035 to speak to a Panasonic Sales Rep