



P5271i

Display Technology > DLP™, Digital Light Display
Native Resolution > XGA 1024x768
Compressed Resolution > Maximum UXGA (1600 x 1200), 1080p (1920 x 1080)
Typical colors > 1.07 Billion Colors
Brightness (ANSI lumens) > 3,100 ANSI Lumens (Standard) - 2,480 ANSI Lumens (ECO)
Dimension (WxDxH) > 341 x 261 x 120 mm (13.4" x 10.3" x 4.7")
Weight > 9.2 lbs (4.2 Kg)
Contrast Ratio > 3700:1
Noise Level > 26 dBA (ECO mode) - 29 dBA (Standard mode)
Computer Compatibility IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards 1080p (1,920x1,080), WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Video Compatibility > NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
Aspect Ratio > 4:3 Native, 16:9 compatible
Picture in Picture Support > N/A
Projection Mode > Front, Rear, Front-Ceiling, Rear-Ceiling
Projection Lens > F = 2.41 ~ 3.2, f = 18.39mm ~ 29.42mm 1:1.6 Manual Zoom and Manual Focus
Projection Screen > 28" (71cm) ~ 300" (762cm)
Digital Zoom > 2X
Throw Ratio > 61"@2m (1.62 ~ 2.64:1)
Projection Distance >

4.9' (1.5m) ~ 32.4' (9.9m)
Horizontal Scan > 30k ~ 100k Hz
Vertical Scan > 50-85Hz, 50 ~ 120 Hz (Available from Dec 2009)
Lamp Type > Osram 230 W user replaceable P-VIP lamp
Lamp Life > 4'000 Hours (ECO) - 2'500 Hours (Standard)
Keystone Correction > +/-40 Degrees (Vertical), Manual
Audio > One Internal Speaker with 2 watts Output
Power Supply > AC input 100~240V auto-switching power supply
Power Consumption > 295 Watts (Operation), <1 Watts (Standby, wireless off)
Uniformity > 90%
I/O Connectors Input Interface: Analog RGB/Component Video (D-sub) x 2 Composite Video (RCA) x 1 S-Video (Mini DIN) x1 > DVI (HDCP) x 1 HDMI (Video, HDCP) x 1 PC Audio (Stereo mini jack) x 2 USB (Type B) x 1 RS232 (Mini DIN) x 1 Output Interface: > Analog RGB (D-sub) x 1 Network Audio (Stereo mini jack) x 1 Control Interface: > USB (Type B) x 1 RS232 (Mini DIN) x 1 Wired remote control port (Mini jack) x 1
Bundled Accessories AC power cord VGA cable Composite video cable DVI cable Remote control > Battery x 2 for remote control Carrying case User's guide (CD-ROM) Quick start guide Security card
Warranty > All of Acer projectors support a two year carry-in warranty, five years warranty for the DMD chip and one year warranty for the lamp.